

CSE370 : Database Systems

Assignment 01 | Spring 2026

ID : 23241004 | Name : Afnan Mohammad Hafiz

No 1 Query (as Plain Text)	create table runners(student_id int, student_name varchar(30), email varchar(40), distance_covered int, time_taken_mins int);
No 1 SS (of Query & Output in Shell)	<pre>database changed MariaDB [Marathon_23241004]> create table runners(-> student_id int, -> student_name varchar(30), -> email varchar(40), -> distance_covered int, -> time_taken_mins int ->); Query OK, 0 rows affected (0.016 sec) MariaDB [Marathon_23241004]></pre>
No 2 Query (as Plain Text)	insert into runners values (101, 'Mikasa Ackerman', 'mikasa.a@g.bracu.ac.bd', 5, 35), (102, 'Edward Elric', 'e.elric@iub.ac.bd', 10, 59), (103, 'Riza Hawkeye', 'riza.h@ewu.ac.bd', 5, 38),

	<pre>(104, 'Bruce Wayne', 'b.wayne@g.bracu.ac.bd', 10, 63), (105, 'Peter Parker', 'p.parker@iub.ac.bd', 5, 33), (106, 'Alphonse Elric', 'a.elric@iub.ac.bd', 10, 55), (107, 'Son Goku', 'son.goku@g.bracu.ac.bd', 5, 46), (108, 'Gon Freecss', 'gon.f@g.bracu.ac.bd', 10, 68), (109, 'Tanjiro Kamado', 'tanjiro.k@g.bracu.ac.bd', 5, 29), (110, 'Roy Mustang', 'roy.m@ewu.ac.bd', 10, 83);</pre>
No 2 SS (of Query & Output in Shell)	<pre>MariaDB [Marathon_23241004]> insert into runners values -> (101, 'Mikasa Ackerman', 'mikasa.a@g.bracu.ac.bd', 5, 35), -> (102, 'Edward Elric', 'e.elric@iub.ac.bd', 10, 59), -> (103, 'Riza Hawkeye', 'riza.h@ewu.ac.bd', 5, 38), -> (104, 'Bruce Wayne', 'b.wayne@g.bracu.ac.bd', 10, 63), -> (105, 'Peter Parker', 'p.parker@iub.ac.bd', 5, 33), -> (106, 'Alphonse Elric', 'a.elric@iub.ac.bd', 10, 55), -> (107, 'Son Goku', 'son.goku@g.bracu.ac.bd', 5, 46), -> (108, 'Gon Freecss', 'gon.f@g.bracu.ac.bd', 10, 68), -> (109, 'Tanjiro Kamado', 'tanjiro.k@g.bracu.ac.bd', 5, 29), -> (110, 'Roy Mustang', 'roy.m@ewu.ac.bd', 10, 83); Query OK, 10 rows affected (0.068 sec) Records: 10 Duplicates: 0 Warnings: 0</pre>
No 3 Query (as Plain Text)	<pre>select * from runners where distance_covered>6;</pre>

No 3 SS (of Query & Output in Shell)	<pre> MariaDB [Marathon_23241004]> select * from runners -> where distance_covered>6; +-----+-----+-----+-----+-----+ student_id student_name email distance_covered time_taken_mins +-----+-----+-----+-----+-----+ 102 Edward Elric e.elric@iub.ac.bd 10 59 104 Bruce Wayne b.wayne@g.bracu.ac.bd 10 63 106 Alphonse Elric a.elric@iub.ac.bd 10 55 108 Gon Freecss gon.f@g.bracu.ac.bd 10 68 110 Roy Mustang roy.m@ewu.ac.bd 10 83 +-----+-----+-----+-----+-----+ 5 rows in set (0.001 sec) </pre>
No 4 Query (as Plain Text)	<pre> select upper(student_name) from runners order by time_taken_mins DESC; </pre>

No 4 SS (of Query & Output in Shell)	<pre> MariaDB [Marathon_23241004]> select upper(student_name) -> from runners -> order by time_taken_mins DESC; +-----+ upper(student_name) +-----+ ROY MUSTANG GON FREECSS BRUCE WAYNE EDWARD ELRIC ALPHONSE ELRIC SON GOKU RIZA HAWKEYE MIKASA ACKERMAN PETER PARKER TANJIRO KAMADO +-----+ 10 rows in set (0.000 sec) </pre>
No 5 Query (as Plain Text)	<pre> alter table runners change distance_covered total_distance decimal(3,1); </pre>

No 5 SS (of Query & Output in Shell)	<pre> MariaDB [Marathon_23241004]> alter table runners -> change distance_covered total_distance decimal(3,1); Query OK, 10 rows affected (0.060 sec) Records: 10 Duplicates: 0 Warnings: 0 MariaDB [Marathon_23241004]> </pre>
No 6 Query (as Plain Text)	<pre> alter table runners add kmh decimal(3,1); </pre>
No 6 SS (of Query & Output in Shell)	<pre> MariaDB [Marathon_23241004]> alter table runners -> add kmh decimal(3,1); Query OK, 0 rows affected (0.009 sec) Records: 0 Duplicates: 0 Warnings: 0 MariaDB [Marathon_23241004]> </pre>
No 7 Query (as Plain Text)	<pre> update runners set kmh= (total_distance * 60) / time_taken_mins; </pre>
No 7 SS (of Query & Output in Shell)	<pre> MariaDB [Marathon_23241004]> update runners -> set kmh= (total_distance * 60) / time_taken_mins; Query OK, 10 rows affected, 10 warnings (0.004 sec) Rows matched: 10 Changed: 10 Warnings: 10 MariaDB [Marathon_23241004]> </pre>

No 8 Query (as Plain Text)	select (total_distance / 10) * (time_taken_mins / 60) * 100 as points, student_id, student_name, kmh from runners;
No 8 SS (of Query & Output in Shell)	<pre> MariaDB [Marathon_23241004]> select (total_distance / 10) * (time_taken_mins / 60) * 100 -> as points, student_id, student_name, kmh -> from runners; +-----+-----+-----+-----+ points student_id student_name kmh +-----+-----+-----+-----+ 29.166666650 101 Mikasa Ackerman 8.6 98.333333300 102 Edward Elric 10.2 31.666666650 103 Riza Hawkeye 7.9 105.000000000 104 Bruce Wayne 9.5 27.500000000 105 Peter Parker 9.1 91.666666600 106 Alphonse Elric 10.9 38.333333300 107 Son Goku 6.5 113.333333300 108 Gon Freecss 8.8 24.166666650 109 Tanjiro Kamado 10.3 138.333333300 110 Roy Mustang 7.2 +-----+-----+-----+-----+ 10 rows in set (0.000 sec) </pre>
No 9 Query (as Plain Text)	select student_name from runners where total_distance=10 and time_taken_mins between 40 and 60;

No 9 SS (of Query & Output in Shell)	<pre> MariaDB [Marathon_23241004]> select student_name from runners -> where total_distance=10 and time_taken_mins between 40 and 60; +-----+ student_name +-----+ Edward Elric Alphonse Elric +-----+ 2 rows in set (0.000 sec) </pre>
No 10 Query (as Plain Text)	<pre> select student_name from runners where email like '%@g.bracu.ac.bd'; </pre>
No 10 SS (of Query & Output in Shell)	<pre> MariaDB [Marathon_23241004]> select student_name from runners -> where email like '%@g.bracu.ac.bd'; +-----+ student_name +-----+ Mikasa Ackerman Bruce Wayne Son Goku Gon Freecss Tanjiro Kamado +-----+ 5 rows in set (0.001 sec) </pre>

