

LinuxLab#02#P1

▼ Create a user account with the following attribute

a. username: islam

b. Fullname: Islam Askar

c. Password: islam

```
[root@cloud afnan]# useradd islam
[root@cloud afnan]# passwd islam
Changing password for user islam.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
Sorry, passwords do not match.
passwd: Authentication token manipulation error
[root@cloud afnan]# passwd islam
Changing password for user islam.
New password:
Retype new password:
passwd: all authentication tokens updated successfully.
[root@cloud afnan]#
```

▼ Fullname:

```
ot@cloud afnan]# useradd -c "Islam Askar" islam
```

▼ Create a user account with the following attribute

a. Username: baduserb. Full name: Bad Userc. Password: baduser

```
ng
[root@cloud afnan]# useradd -c "Bad User" baduser
```

LinuxLab#02#P1 1

```
[root@cloud afnan]# passwd baduser

Changing password for user baduser.

New password:

Retype new password:

passwd: all authentication tokens updated successfully.

[root@cloud afnan]#
```

▼ Create a supplementary (Secondary) group called pgroup with group ID of 30000

```
[sudo] password for afnan:
[root@cloud afnan]# groupadd pgroup -g 30000
```

▼ Create a supplementary group called badgroup

```
[root@cloud afnan]# groupadd badgroup
[root@cloud afnan]# tail -4 /etc/group
islam:x:1001:
baduser:x:1002:
pgroup:x:30000:
badgroup:x:30001:
```

▼ Add islam user to the badgroup group as a supplementary group

```
[root@cloud afnan]# id islam
uid=1001(islam) gid=1001(islam) groups=1001(islam)
[root@cloud afnan]# gpasswd -a islam badgroup
Adding user islam to group badgroup
[root@cloud afnan]# id isla,
id: 'isla,': no such user
[root@cloud afnan]# id islam
uid=1001(islam) gid=1001(islam) groups=1001(islam).30001(badgroup)
```

▼ Modify the password of islam's account to password

```
[root@cloud afnan]# passwd islam
Changing password for user islam.
New password:
Retype new password:
passwd: all authentication tokens updated successfully.
[root@cloud afnan]#
```

▼ Modify islam's account so the password expires after 30 days

LinuxLab#02#P1 2

```
[root@cloud afnan]# usermod -e 30 islam
[root@cloud afnan]# id islam
uid=1001(islam) gid=1001(islam) groups=1001(islam),30001(badgroup)
[root@cloud afnan]# |
```

▼ Lock baduser account so he can't log in

```
[root@cloud afnan]# usermod -L baduser
[root@cloud afnan]#
```

▼ Delete baduser account

```
[root@cloud afnan]# userdel baduser
[root@cloud afnan]# id baduser
id: 'baduser': no such user
[root@cloud afnan]#
```

▼ Delete the supplementary group called badgroup.

```
[root@cloud afnan]# groupdel badgroup
[root@cloud afnan]#
```

LinuxLab#02#P1 3