



South Africa liquid fuels market story

Inland supply, corridor capture and tank
turnover

Durban-Lesedi corridor into Gauteng

8 October 2026

Investment conditions, nine-world priorities and targeted data
requests; commercial thresholds remain open

Photo source: Royal Vopak | Terminal Durban | vopak.com

Strictly Confidential



Slow demand growth and greater import reliance set the baseline; road-to-rail shifts, EV adoption, power recovery and refinery changes could reshape the outlook

Baseline / reference	What the evidence establishes	What changes the outlook
 Fuel demand and power	2013–2023 CAGR: petrol –2.08%; diesel +0.82%. Eskom OCGT fuel use fell 40% in FY2025.	Growth, rail, EVs and efficiency alter transport demand; fleet recovery and new generation alter diesel dispatch.
 Domestic supply and imports	2020–2025 imports rose by 5.43bn litres of diesel and 2.73bn of petrol. The sourcing mix has shifted.	SAPREF and PetroSA restart paths, Secunda gas/MRG and Natref output can change domestic supply.
 Corridor position and tank turnover	Durban and Lesedi provide coastal and inland assets serving Gauteng. Working capacity and turns are open.	Route costs, access and customer capture determine flow; achievable turnover determines handling headroom.
 Medium / Medium reference world	M/M anchors the nine-world matrix. Historical evidence is assembled; numerical calibration remains open.	Vary demand and supply around M/M, then test capture, turnover and returns to identify investment triggers.

Executive summary — baseline and changes. Comparable historical periods differ: Department sales 2013–2023; SARS imports 2020–2025; Eskom FY2025 vs FY2024 (own diesel + kerosene). M/M is a reference framework, not a calibrated forecast.

Prioritise capture and turnover through existing assets; expand where profitable demand exceeds achievable capacity

Working recommendation	Investment logic	Condition for commitment
 Capture inland supply	Win accessible customer flows from imported and domestic sources.	Prove delivered competitiveness and sufficient customer volume.
 Use existing assets first	Increase turnover where tanks and receipt/dispatch allow.	Confirm working capacity and the actual operating constraint.
 Stage corridor and capacity spend	Compare access improvements, rail loading, debottlenecking and new tanks.	Fund the least-cost viable option that removes the proven constraint.
 Keep strategic options open	Test all nine worlds and emerging gateways; screen EV adjacencies separately.	Apply p4 to fuel-capacity expansion; assess operational and EV options on their own economics.

Working recommendation, not an approved investment. Four numeric decision tests follow on p4; nine-world investment priorities on p5. Customer, operating and commercial inputs remain open.

Expand fuel-logistics capacity only when four investment tests pass

Decision test	Numeric condition	What we know now	Investment consequence
 Customer volume	Secured incremental m ³ /year ≥ break-even m ³ /year.	Volume threshold: pending customer commitments, rates and project costs.	Size and phase the option to the volume that can actually be won.
 Route economics	Delivered-cost headroom ≥ RO/m ³ after the required margin.	Headroom: pending matched quotes for the same product and destination.	Include emerging Maputo and Walvis Bay routes and domestic alternatives.
 Capacity constraint	Captured m ³ /year – achievable m ³ /year > 0.	Actual shortfall: unknown. Each 1bn L/year equals 0.23 Durban / 0.60 Lesedi gross monthly turns.	Improve access or dispatch first where they bind; add tanks only if storage binds.
 Incremental return	NPV > RO at the agreed hurdle rate.	NPV and hurdle: pending finance inputs. Test ramp-up and downside volumes.	Select a viable option and stage commitment against contracts and delivery.

Decision rules for fuel-capacity expansion, not measured results. Gross turns indicate scale, not achievable working capacity; Durban includes mixed products. Full NPV requires project cash flows. Cost-saving improvements need their own incremental-return test; EV investment is assessed separately. SCR synthesis: p34.

Nine worlds identify investment priorities; capacity expansion must pass the four tests

Fuel demand / domestic supply	HIGH supply	MEDIUM supply	LOW supply
LOW demand	L / H DEFEND UTILISATION Prioritise low-capex efficiency. Screen rail access / EV adjacencies.	L / M PHASE COMMITMENTS Debottleneck proven constraints. Screen EV adjacencies separately.	L / L REPLACE LOST SUPPLY Test import corridor / rail access. Add tanks only after the four tests.
MEDIUM demand	M / H CAPTURE DOMESTIC FLOWS Test inland / rail connections. Defer unsupported import expansion.	M / M BASELINE CHOICE Use tanks better; price rail access. Stage capacity behind contracts.	M / L SECURE IMPORT ACCESS Test corridor / rail debottlenecks. Expand only at binding limits.
HIGH demand	H / H EXPAND DISTRIBUTION Test inland links and rail access. Tank growth follows captured flow.	H / M UNLOCK THROUGHPUT Debottleneck corridor / dispatch. Add tanks if shortfall persists.	H / L TEST STAGED EXPANSION Secure import / corridor capacity. Test rail access and extra tanks.


Each world: captured volume → route economics → required turns / bottleneck → investment option → return.

Qualitative priorities, not calculated recommendations. Rail options need volume, access and returns; rail freight recovery also changes fuel demand. EV adjacencies require a separate customer case and are not implied by low demand. Lever definitions remain in the appendix; original import-direction matrix retained in v22 and slide notes.

Petrol demand has declined while diesel has grown slowly, limiting the case for demand-led expansion outlook

Demand trend

Change over 2013–2023



01 | Petrol 2013–2023

11.15 to 9.04 bn litres
-2.12 bn L / -19.0%
CAGR -2.1% per year

02 | Diesel 2013–2023

11.89 to 12.91 bn litres
+1.02 bn L / +8.6%
CAGR +0.8% per year

FIASA 2024 observations are excluded from this comparison: source definitions are not reconciled.

The demand history supports a selective investment case: growth must translate into captured corridor throughput and sufficient tank turns.

Department sales 2013–2023. CAGR from comparable endpoints: petrol -2.08%, diesel +0.82%. FIASA 2024 is excluded from the trend calculation; its observations remain in the evidence data.

Power shortages and road freight have supported diesel consumption, but that support can change with increased support for rail reform and improved Eskom


Demand support	2024 vs 2025	2024	2025	Implication for demand
 Power generation	Own OCGT fuel • million litres • financial years			
	OCGT fuel	1,129.5	679.1	-39.9%
	EAF: 54.56% → 60.60% Cost*: R23.87bn → R13.32bn			
 Road freight	Reported payload • million tonnes • calendar years			
	Road	979.8	976.5	-0.3%
	Rail	160.7	168.3	+4.7%
 Sector activity	Real GVA • Rbn, 2015 prices • calendar years			
	Agriculture	114.8	134.8	+17.4%
	Mining	205.1	205.5	+0.2%
	Manufacturing	523.2	517.0	-1.2%

Eskom Integrated Report 2025 pp100,141: own-fleet diesel + kerosene; *cost includes storage/demurrage. Stats SA P7162 Dec 2025 p7: both years from the revised vintage. Stats SA P0441 Q2 2026 annual real GVA: agriculture includes forestry/fishing. FY and calendar-year periods shown separately. Bars start at zero; scales are common within each panel, not across different units. Light blue = 2024; navy = 2025.

The shut down of domestic refining capacity has lowered domestic production and has increased imports shifting how inland demand is supplied

Import trend

Change since 2020



01 | Diesel import

6.81 to 12.25 bn litres
Increase: 5.43 bn litres
CAGR: 12.4% (2020–2025)

02 | Petrol import

1.72 to 4.45 bn litres
Increase: 2.73 bn litres
CAGR: 21.0% (2020–2025)


More inland handling opportunity;
capture and turnover determine benefit.

Additional imported litres create handling demand. Vopak benefits where it captures inland flows and can increase turnover or profitably remove a constraint.

SARS litre-reported petrol/diesel codes, complete calendar years. 2020–2025 changes are historical comparisons, not plant-level causal attribution. Export histories retained in the source report; unit/blend exclusions remain.

Emerging Maputo and Walvis Bay routes must be tested alongside Durban and domestic supply

Competing supply corridors



Same product, same destination

01 | Compare delivered cost

Product, handling, transport, border, losses and inventory finance.

02 | Establish price headroom

Bearable charge less actual logistics cost. Capacity and reliability constrain capture.

03 | Include domestic sources

Secunda and Natref also serve inland demand; routes and access need validation.

Next action

Match route costs and access to the same product and Gauteng destination.

Maputo and Walvis Bay are emerging alternatives to include by destination. Compare delivered cost, capacity and reliable access before estimating how much inland demand Vopak can capture.

© OpenStreetMap contributors (ODbL; osm.org/copyright) / Geofabrik; Natural Earth; geoBoundaries. Shared LAEA projection. Paths test road connectivity, not tanker access. Secunda uses a city reference; Natref a mapped site. Terminal access, turn restrictions and operating rail/pipeline services remain unvalidated. Emerging alternatives are in scope; relative competitiveness is not yet quantified.


Increasing asset utilisation through higher turnover could let Durban and Lesedi serve more demand through existing tanks and corridor growth opportunities

Gross handling sensitivity

Durban



Lesedi



bn litres/year; 1 / 2 / 3 monthly turns are an existing authored sensitivity, not measured site limits.

Investment test

01 | Calculate required turns

Captured annual throughput divided by eligible working capacity, then by 12.

02 | Test achievable handling

Check receipt / dispatch, pipeline access, seasonal peaks and stock policy.

03 | Identify the binding constraint

Use existing assets first; debottleneck or add tanks where the constraint is profitable.

Next action

Confirm working tankage and achieved turns before sizing any additional storage.


Required working-capacity turns must be compared with achievable turns at each terminal. Gross handling equivalents do not establish spare capacity or actual market share.

Registered REG-TERMINAL-HANDLING-TURNS: 1/2/3 turns per month, authored operational sensitivity, not the demand-supply worlds or measured limits. Gross Durban mixed-product tankage; no assumed eligible fraction. Do not sum inter-terminal transfers as unique demand.

Accelerated rail recovery, EV adoption and ICE technology efficiency could reduce transport fuel demand in the medium to long term

Rail recovery


million tonnes



D2: capacity, reliability, transferable freight
Tonnes require haul distance and traction
before conversion to net diesel savings.

EV uptake


vehicles sold / year



D3: affordability, charging, fleet replacement
Sales history is not fleet penetration.
L/M/H adoption calibration remains open.

Fleet efficiency

L/100 km; draft engine




D4: new-cohort efficiency and mileage
Dashed paths are existing model diagnostics.
OEM history and Medium calibration are open.

The time series establish the starting points. Rail, adoption and efficiency levers must be calibrated into the same three demand paths before the matrix is quantified.

Stats SA freight payload; staged naamsa BEV/PHEV annual sales 2019–2025; existing engine petrol-ICE efficiency diagnostics. Dashed efficiency paths are assumptions, not historical OEM evidence. Medium and causal fuel impacts remain uncalibrated.

Power generation recovery could lower diesel use further, while outages and replacement delays could sustain domestic demand




Eskom recovery has lowered diesel dispatch. Wind, solar and gas timing must be tested against demand, fleet retirements and dependable output before forecasting residual diesel.

Eskom FY ending March. Fuel/EAF: 2025 report; GWh: staged 2024–2026 reports. Own Eskom and IPP generation separated. Private backup and load-shedding histories are missing; no assumed annual generation gap is assigned entirely to diesel.

SAPREF could expand the supply footprint, while Natref unavailability would reduce it

Reported history

Illustrative 2036 capacity cases



These capacity cases anchor the supply-axis discussion. Translate them into product output, then test imports, corridor capture and required tank turns in each of the nine worlds.

FIASA 2025 p49; registered review_capacity_scenarios.yaml and review_supply_worlds.yaml. Illustrative 2036 sensitivities, not calibrated production forecasts. Other plants held at 2025 reported values; Secunda gas/MRG and PetroSA restart effects remain unquantified. Low is not a Natref closure prediction.

Emerging gateways could redirect inland growth; delivered cost and reliable access determine capture

Competing route	What changes the choice	Investment implication
Durban–Lesedi	Pipeline, rail and road costs; reliable receipt and inland dispatch.	Test access and handling improvements that protect competitive customer supply.
Maputo / Matola	Delivered cost, border time and capacity into each inland destination.	Include as an emerging alternative; test customer exposure and corridor responses.
Walvis Bay	Distance, transit, border costs and feasible destination coverage.	Consider emerging inland opportunities; compare reach customer by customer.
Domestic sources	Secunda / Natref availability, product output and distribution access.	Test inland handling and connections as well as import infrastructure.

Compare common product, destination, price date and tax basis. Emerging gateways must be considered; no relative cost ranking is asserted without quotes and verified access. Landlocked SADC opportunities require separate market/access evidence.

Choose the investment that removes the proven constraint—and earns a return

Investment option	When it becomes relevant	Decision / commitment trigger
 Existing assets / debottlenecking	Customer growth can be served through better tank turns, scheduling or receipt/dispatch.	Use available working capacity; invest in the specific bottleneck where incremental value is positive.
 Corridor / rail access	Competitive customer flows are constrained by transport capacity, cost or reliability.	Secure service and volume commitments. Compare access contracts, loading assets and partnership investment.
 Additional tank capacity	Profitable captured flows exceed achievable handling and storage remains the binding constraint.	Size and stage tanks against contracted demand; pass the four tests and downside cases.
 EV-related adjacencies	Identified charging / fleet-energy customers offer a viable opportunity as transport electrifies.	Screen partnerships or dedicated assets separately: demand, power access, strategic fit and return must be proven.

Investment menu, not approved projects. Network rail recovery is an external fuel-demand driver; Vopak rail loading/access is a distinct investment option. EV uptake reduces some fuel demand; it does not itself prove an EV investment case. Project costs, contracts and returns remain open.

Resolve customer volume, working capacity and project economics first to determine the investment

Data request	Required detail	Decision it unlocks
FIRST Volume DR02 / DR05	Monthly unique deliveries, customer destination, contract term and contestable volumes; separate terminal transfers.	Establish the m ³ /year Vopak can secure and the revenue it supports.
FIRST Capacity DR03	Eligible working m ³ , actual turns, committed capacity, stock policy and receipt/dispatch limits.	Calculate the throughput shortfall and identify whether tanks, access or dispatch bind.
FIRST Economics DR04 / DR06	Matched delivered costs, access, rates, incremental costs and capex; hurdle, ramp-up and working capital.	Calculate route headroom, break-even volume and incremental return by option.
THEN Stress tests DR01 / DR07 / DR08	Reconciled product balance; annual demand, power and plant-output paths.	Test how far demand or supply must change before the preferred investment changes.
SEPARATE EV case DR09	Customer energy demand, charging utilisation, power connection, delivery partner, capex and contribution.	Decide whether an EV adjacency merits development on its own economics.

Request prepared, not sent. Sequence is proposed, not a quantified sensitivity ranking. Nigel to coordinate Vopak data; Manish to reconcile public evidence. Latest 36 complete months where available. Detailed requests and decision triggers logged; owners and commercial inputs remain to be confirmed.

Appendix

Supporting evidence and calibration

Durban-Lesedi corridor into Gauteng

8 October 2026

Detailed evidence, assumptions and remaining calibration requirements

Photo source: Royal Vopak | Terminal Durban | vopak.com




The supporting evidence calibrates demand, supply and the terminal investment tests

Evidence group	Detail retained	Connection to the story
Demand	Activity, freight, EVs, efficiency and power	D1–D5 create the three demand paths.
Supply	Plant output, gas availability and restart timing	S1–S4 create the three domestic-supply paths.
Capture and operations	Routes, customer share, working tankage and turnover	T1–T5 translate each world into terminal flows and constraints.
Returns	Rates, costs, capex and funding; separate EV adjacency economics.	F1 translates each investment option into cash flow and returns.

The main story runs from the opening thesis to the investment tests. The added lever register and power/supply calibration pages record what remains to be populated.

Fuel demand has diverged from GDP, so sector activity and fuel intensity need separate treatment

index: 2013 = 100; matched 2013-2023 window




Economic weakness means limited growth in real activity and investment. Structural change means a different mix of output, travel and fuel use; this chart alone cannot attribute causality.

Staged GDP and department fuel sales, indices 2013=100. Sector attribution remains open; COVID distorts short-period comparisons.

Fixed investment has weakened while FDI fluctuates, limiting a simple growth-led fuel argument

percent of GDP / calendar year



Fixed investment helps frame productive capacity. FDI can include large transactions; neither series is a direct investor-confidence measure or an additional fuel-demand multiplier.

World Bank WDI, FDI net inflows and gross fixed capital formation as % of GDP, 2010–2025. Confidence series remains an evidence gap.


Mining, agriculture and aviation expose fuel demand to different activity drivers

Evidence	Interpretation	Implication for Vopak
Mining	Output, commodity mix and haul distance influence diesel use and freight.	Separate mine activity from the fuel impact of changing freight mode.
Agriculture	Crop cycles, weather, irrigation and logistics can shift seasonal diesel use.	Establish sector activity and fuel exposure before assigning a headwind.
Aviation	Traffic, distance, load factors and aircraft efficiency drive jet-fuel demand.	Keep jet fuel separate from petrol/diesel shares and verify terminal eligibility.
Manufacturing	Real output and industrial composition help explain the economic backdrop.	Test changes using sector data; a national fuel chart does not prove deindustrialisation.

Analytical framework following user comments. Sector-specific exhibits and causal attribution remain to be completed.

Higher fuel prices strengthen EV running-cost incentives, but ownership economics determine uptake

nominal ZAR/litre; full-year monthly averages



Shipping disruption, crude prices and FX can move fuel costs temporarily. EV adoption depends on sustained total ownership cost, purchase affordability, charging access and fleet replacement.

Department fuel-price history, nominal R/litre. No quantified geopolitical premium or calibrated EV adoption response is asserted.


New-vehicle efficiency gains affect fuel demand gradually as older vehicles leave the fleet

Evidence	Interpretation	Implication for Vopak
Fleet growth	More vehicles or distance travelled can raise demand.	Measure activity before attributing lower fuel volumes to efficiency.
Efficiency	New-cohort consumption gains enter the fleet over successive replacement cycles.	Obtain OEM and real-world evidence by segment; do not apply new-vehicle gains to every vehicle.
EV substitution	EVs remove some combustion-engine vehicle activity from the fuel calculation.	Count each vehicle transition once, then calculate efficiency on the remaining combustion fleet.

Mechanism supported by existing cohort architecture. OEM historical and future efficiency evidence is still missing; no new forecast shown.

Eskom's own OCGT fuel use fell 40% in FY2025 as availability improved

million litres / FY ending 31 March




Reported fuel fell from 1,129.5 to 679.1 million litres as EAF improved from 54.56% to 60.60%. This removes part of the recent diesel-demand support.

Eskom integrated report 2025: FY March, own-fleet diesel + kerosene. EAF association is not a dispatch model; private backup use excluded.

Road carries most reported freight tonnage, making transferable haul distance a key diesel lever

million tonnes / complete calendar year



Payload establishes the historical direction. Diesel displacement requires corridor tonne-kilometres, road fuel intensity, rail traction and last-mile activity.

Stats SA monthly freight payload, complete calendar years. National tonnes are not corridor tonne-kilometres or transferable freight.


Rail funding and reliable service determine how much road freight can return to rail

Evidence	Interpretation	Implication for Vopak
Network ambition	The supplied brief reports a 250 Mt target dependent on a funding plan.	Do not treat every additional rail tonne as road displacement. Commodity, corridor and origin matter.
Funding constraint	Brief: R46.34bn approved over five years, including R1.71bn expansion.	Maintenance and sustaining spend dominate. A published plan is insufficient evidence of delivered capacity.
Container corridor	Brief: R2.11bn in 2026/27–2028/29; private funding expected thereafter.	Prioritise Durban–Gauteng road/rail competition and reconcile the corridor to Network Statement v4.
Two fuel effects	Rail can displace truck diesel while improved infrastructure also changes fuel-distribution economics.	Keep freight-demand effects separate from the route delivering fuel to Gauteng.

User-supplied AIA Transnet Funding Brief, Sep 2026, pp1–2; cites FY2026 AFS and Network Statement v4 Annexure 17. Primary figures not independently reconciled.

Gauteng demand establishes market scale, while Lesedi capture and turnover determine throughput

billion litres / complete calendar year



2022 petrol + diesel sales total 6.81bn litres. Lesedi's 140,000m³ equals 2.06% of that annual market per effective gross-capacity turn. Actual turns and Gauteng allocation remain unknown.

Department provincial sales, latest complete staged year 2022; Vopak Lesedi current capacity. Cross-vintage scale test only, not current observed market share.

Every market world passes through explicit demand, supply, capture and operating levers

Lever IDs	Inputs to calibrate	Output / remaining evidence
D1–D5 demand	D1 sector growth; D2 rail; D3 EV adoption; D4 efficiency; D5 power.	Historical volumes and time series feed L/M/H demand. OEM, corridor tonne-km and backup evidence remain open.
S1–S4 supply	S1 SAPREF; S2 Secunda gas/MRG; S3 Natref; S4 PetroSA.	Dates, utilisation, availability and yields produce L/M/H domestic output. Medium and plant marginal effects require calibration.
T1–T2 capture	T1 delivered route economics/access; T2 customer/product/destination capture.	Allocate domestic and imported fuel to unique terminal deliveries. Tariffs, rights and commercial allocation remain open.
T3–T5 operations	T3 eligible working tankage; T4 turnover; T5 receipt/dispatch, peaks and stock policy.	Compare required with achievable turns, occupancy and headroom. Existing 1/2/3-turn sensitivity is illustrative only.
F1 finance	Storage/handling terms, costs, capex, tax, working capital and hurdle rate.	Translate constrained throughput into cash flow, NPV, IRR and investment triggers. Commercial inputs remain open.

Medium is the reference market world; operational sensitivities are separate. Owner: Nigel / analyst and commercial teams. Resolve each missing input before numeric adoption or investment reliance.

Generation timing must close the power balance before residual diesel can be forecast

Time series	Assumption / lever	Evidence status and next use
Recovery history	EAF, unserved energy / load-shedding hours, OCGT GWh and litres.	EAF, Eskom fuel and Eskom/IPP GWh staged. Comparable load-shedding and private backup series still needed.
Generation supply by year	Existing fleet and retirement profile; wind, solar and gas commissioning; availability and utilisation.	Obtain dated Eskom / approved planning schedules. Report annual GWh alongside dependable capacity and dispatch constraints.
Residual dispatch	Electricity demand, hourly/seasonal shape, storage, imports, reserve needs and fuel constraints.	An annual GWh shortfall alone cannot determine diesel use. Calibrate feasible peaking dispatch, then apply consumption rates.
L/M/H demand contribution	Sustained recovery, reference and setback assumptions across the same planning horizon.	Output generation and diesel time series with solid actuals / dashed assumptions. No uncalibrated future values are drawn.

Requested generation-balance exhibit remains quantitatively incomplete. Owner: Nigel / power analyst; trigger: before D5 adoption. Do not convert installed renewable MW directly into dependable diesel displacement.

SAPREF and Natref define capacity sensitivities; plant output must complete the supply paths

Plant lever	Required time-series inputs	Scenario treatment
S1 SAPREF	High illustration adds 400 kbpd: assumed 2029 FID plus 48 months gives 2033 availability. Low/Medium add none.	Separate the import phase from refinery commissioning; establish ramp-up, availability and product yields.
S3 Natref	108 kbpd retained in Medium/High; excluded in the Low stress case at 2036. No closure date assumed.	This is a hypothetical availability test. Confirm operating outlook; do not infer closure from an outage.
S2 Secunda	150 kbpd reported crude-equivalent footprint held in all three capacity illustrations.	Gas decline and MRG diversion can reduce liquid output without changing nameplate. Quantify the gas balance and liquids penalty.
S4 PetroSA	No restart addition included in these three capacity illustrations.	Test funded restart scope, feedstock, timing and yields separately; zero reported contribution is not proof of dismantled capacity.

Illustrative footprint cases: 250 / 358 / 758 kbpd; not a complete low/base/high production range. Owner: Manish; Nigel review. Resolve dates, operating factors, yields and gas effects before nine-world output adoption or investment use.

Public capacity ratios establish scale but cannot substitute for realised terminal throughput

Catchment	Initial inference	What the result can support
Durban	45.1% of the combined published gross capacity of Vopak and Bidvest in Durban.	A two-operator footprint proxy with mixed products and an incomplete market denominator. It does not establish Durban throughput share.
Gauteng / Lesedi	2022 petrol + diesel sales: 6.81bn litres. Lesedi's gross capacity equals 2.06% of that market per effective annual turn.	A cross-vintage scale test. Current sales, eligible working capacity, actual turns and Gauteng allocation are needed for a throughput estimate.
Investment implication	Convert eligible tankage and realised turns into unique customer deliveries, then compare with existing capacity.	A large market can coexist with spare terminal capacity. Market scale alone does not establish a need for additional tanks.

Operator capacities: Vopak Durban 360,246m³, Bidvest Durban 439,306m³, Lesedi 140,000m³. Department Gauteng sales 2022; appendix p27. Transfers between terminals must not be double-counted.

A matched demand snapshot is available, but the domestic supply balance still needs reconciliation

Evidence / bn litres	Petrol	Diesel
2022 national sales	9.18	12.72
2022 Gauteng sales	3.53	3.28
2022 imports / exports	5.46 / 0.85	11.95 / 0.89
2021 balance diagnostic	0.51 statistical difference needed to reconcile reported supply and final consumption.	2.10 statistical difference needed to reconcile reported supply and final consumption.
Decision consequence	Sales less net imports is a residual, not measured domestic output. Confirm product and stock boundaries.	Provincial sales establish demand scale, not source allocation or flows captured by Vopak.

Department sales: four quarters; SARS trade: 12 months and litre units only, blends/other units excluded. 2021 energy-balance consumption differs from sales; statistical differences are not stock changes. Source hashes and exact values: [investment_bridge_2026_10_08/evidence.json](#).

The six-step bridge is implemented for screening; calibration now depends on the requested inputs

Work package	Implemented now	Input needed to complete the decision
1 Baseline	Matched 2022 sales/trade; 2021 balance diagnostic.	Reconcile production, stocks and source definitions.
2 Route competition	Delivered cost and bearable-charge calculation; route readiness register.	Matched quotes, service capacity and access.
3 Vopak capture	Capture calculation constrained by accessible market and route capacity.	Customer allocation and unique terminal deliveries.
4 Existing assets	Required-turn and operating-bottleneck calculation; gross-turn screen.	Working capacity, achievable turns and peak limits.
5 Investment options	Pre-tax break-even volume calculation.	Commercial inputs and full incremental cash flows.
6 Nine worlds	Nine-cell output register and demand/supply balance calculation.	Annual L/M/H paths; rerun routes, capture and returns.

Screening functions tested with synthetic cases; commercial outputs remain unpopulated. Not integrated into the forecast engine or independently reviewed. Owners, request IDs and expiry triggers: workstreams/WSO_governance/workplan/sa_investment_bridge_2026_10_08.csv.

Demand, supply and corridor access translate into captured throughput and required tank turns

Argument	Situation	Complication	Resolution / decision
 Transport demand	Subdued aggregate growth masks different product trends. Road freight supports diesel use.	Sector growth, rail recovery, EVs and efficiency change fuel demand.	D1–D4 define activity, rail, EV and efficiency paths. Translate them into capturable product demand.
 Power demand	Power shortages supported diesel use; Eskom consumption has recently fallen.	Recovery may persist or reverse through outages and replacement delays.	D5 adds fleet recovery, replacement timing and diesel dispatch to the same demand paths.
 Domestic supply	Reduced local production has increased reliance on imports.	SAPREF, Natref and Secunda can change domestic fuel output materially.	S1–S4 define plant output and sourcing mix. Imports are one consequence of the domestic balance.
 Corridor competition	Durban connects imported fuel to inland customers.	Alternative gateways, delivered costs, reliability and access alter flows.	T1–T2 compare delivered economics and capture for domestic and imported fuel serving common destinations.
 Vopak investment	Durban and Lesedi provide connected assets whose throughput can rise through higher turnover.	Working tankage, receipt/dispatch, peaks and stock requirements constrain achievable turnover.	T3–T5 compare working capacity, required/achievable turns and dispatch limits. F1 tests incremental returns.

Lever IDs are mapped in the appendix. All nine market worlds use explicit routing, capture and operational assumptions. Tank occupancy, turnover and throughput utilisation are separate measures. Competitiveness varies by destination; neither alternative gateway is yet established as competitive into Gauteng.