Certified Adaptive Examination of Peripheral Blood Smears: When Information-Gain Stopping Fails, and What Can Be Guaranteed Instead

Qudrat Ullah

***Abstract*—Automated examination of blood smears increasingly decides which fields to inspect and when to stop. We ask what it can guarantee about what it did not examine. We use pre-registered simulations from 28,280 expert-labelled cells, two external datasets and annotated bone-marrow regions from 99 patients. First, information-saturation stopping, reimplemented from InfoDPP-PAC, stops at the same point however much decision-changing evidence exists. With one critical field among 200, it missed 76% of positive specimens (uniform sampling of equal size: 85%); two other saturation rules behaved alike, and on real marrow tiles it did worse than uniform sampling in low-blast specimens. Second, without location information, any strategy must examine nearly every field (95% at a 5% error level) to certify that rare evidence is absent. Third, certifying that the blast proportion exceeds a 10% or 20% threshold is feasible with design-based, anytime-valid tests, whose cost depends on the margin to the threshold, not on specimen size. Near the threshold, a 100-cell count was wrong in up to 37% of specimens; valid procedures were almost never wrong but mostly undetermined. Fourth, validity held when acquisition shifts cut classifier blast recall from 0.91 to 0.63 and 0.34; the saving from classifier-driven sampling shrank and then reversed. Validity depended on the unit of analysis and the verifier: analysing cells of sampled fields as independent draws exceeded the nominal error in 27 of 75 real specimens, and single-reader labels needed a three-percentage-point margin. Guarantees about unexamined material come from the sampling design, not model confidence.**

***Index Terms*—Adaptive sampling, anytime-valid inference, blast count, blood smear, risk-limiting audit, sequential testing.**

I. Introduction

A peripheral blood smear contains far more cells than any examiner inspects. A manual differential counts 100 or 200 leukocytes, and the variability this implies has long been known [1]. Automated systems add a degree of freedom: they choose which fields to examine and when to stop. For questions that hinge on rare cells, such as the blast proportion relative to a classification threshold [2], [3], what matters is not classifier accuracy on the examined fields but what can be said about the fields that were not examined.

Stopping rules based on *information saturation* answer this question implicitly: they stop when further fields would add little information about the specimen as the selector's embedding represents it. InfoDPP-PAC [4] is a carefully constructed recent instance for whole-slide histopathology, and its authors state that its certificate bounds residual information in the selection objective, not diagnostic performance. That distinction is our starting point: saturation of information about an embedding does not imply that rare, decision-relevant evidence has been seen. We ask four questions. RQ1: does information-saturation stopping fail systematically when decision-changing evidence is rare? RQ2: why does certifying the *absence* of rare evidence require near-exhaustive examination? RQ3: how many cells must be examined to certify a threshold decision under adaptive sampling? RQ4: where do the assumptions of anytime-valid audit methods break on real data?

Our contributions are:

- a pre-registered evaluation showing that saturation stopping is content-blind, that its halting signal decouples from critical evidence as cells are pooled into fields, that two other saturation rules behave alike, and that on real marrow tiles it did worse than uniform sampling in low-blast specimens (RQ1);
- a minimax lower bound showing that near-exhaustive examination is required of *every* strategy without location information, and a proposition that ties a relevance-ranked search to the model's ROC curve (RQ2);
- an evaluation of design-based, anytime-valid certification of blast-proportion assertions [5], [6]: validity, cost from 500 to 4,000 cells, and decisions at fixed budgets (RQ3);
- an empirical examination of the assumptions behind these guarantees (RQ4): classifier error, acquisition shift on two external sources, spatial clustering measured in exhaustively annotated marrow regions, unequal field sizes (with two valid constructions) and verifier error measured from real reader labels.

This is a methodological study. Most specimens are composites of real single-cell images, and no result establishes clinical diagnostic validity.

II. Related Work

Rümke characterised the binomial and finite-population variability of manual differentials [1]; for absence of rare events, the "rule of three" bounds a rate after zero events [7], and Proposition 1 is its design-based finite-population counterpart. InfoDPP-PAC [4], a recent preprint, selects patches greedily under a blended information-gain and relevance objective and stops when the largest information gain among unselected patches falls below a concentration-corrected threshold. Its certificate rests on a stability assumption whose constant and target are assumed rather than derived; our results

Q. Ullah is with the Faculty of Informatics, University of Debrecen, Debrecen, Hungary (e-mail: qudratafridi@mailbox.unideb.hu). This work was supervised by Dr. Balázs Harangi.

do not depend on it. Blast recognition itself is well studied [8]; our question concerns examination and inference.

Risk-limiting audits test assertions about finite populations with a guaranteed bound on confirming a false assertion [9]. ALPHA [5] turns assertions into bounded-mean tests through an *assorter* and builds a test supermartingale for sampling without replacement; betting confidence sequences [10] and Ville's inequality [11] provide the anytime validity. Shekhar et al. [6] extend this to weighted, adaptive sampling without replacement with side information; stratified extensions exist [12]. Prediction-powered inference [13], prediction-powered e-values [14] and active inference [15] combine predictions with a verified subset, mostly as fixed-sample statements about a superpopulation; the tests used here are anytime-valid statements about one finite specimen.

III. Setting and Theory

A. Estimands

A specimen has N fields; field i holds m_i cells, B_i of them blasts, $M = \sum_i m_i$, and $p = \sum_i B_i/M$. We distinguish *detection* (has a critical field, one with at least one blast, been examined?), *estimation* of p, and *threshold certification* ($p > \theta$?). We use $\theta = 0.10$, the blast percentage at which the International Consensus Classification (2022) separates myelodysplastic syndrome with excess blasts from MDS/AML [3], and $\theta = 0.20$, the WHO 5th-edition threshold for acute myeloid leukemia without defining genetic abnormalities [2]. Both count blast equivalents, which our labels do not; the thresholds are analysed separately and are inputs to a procedure, not validated here. An examiner selects fields sequentially, possibly using features x and past labels, and a selected field is *verified*: its cells' labels are revealed. All probabilities are over the examiner's randomisation for a fixed specimen, so the guarantees are finite-population and design-based.

B. Certifying absence (RQ2)

Let C be the set of k critical fields and M_n the event that none is among n examined fields; let $h(N,k,n) = \binom{N-k}{n}/\binom{N}{n}$.

Proposition 1 (Uniform sampling): Under sampling of n fields without replacement, $\mathbb{P}(M_n \mid C) = h(N,k,n)$; for $k = 1$ this is $1 - n/N$, so $\mathbb{P}(M_n) \le \alpha$ iff $n \ge \lceil (1-\alpha)N \rceil$.

Assumption 1 (No location information): Given x, every placement C with $|C| = k$ is possible.

Theorem 1 (Minimax lower bound): Under Assumption 1, every policy, adaptive or not, randomised or not, that examines at most n fields satisfies $\max_{|C|=k} \mathbb{P}_\pi(M_n \mid x, C) \ge h(N,k,n)$. Uniform sampling attains the bound; every deterministic policy has worst-case miss probability 1 if $n \le N-k$. The proof (Appendix) fixes the examiner's randomness: on the all-negative run the policy examines a fixed set, and averaging over a uniformly placed C gives the bound (Yao's principle [16]). We verified all statements exactly in rational arithmetic and, for $N \le 7$, by solving the search game as a linear program. If k is unknown, the worst case is $k = 1$, so certifying absence at level α needs $\lceil (1-\alpha)N \rceil$ fields




Fig. 1. Fraction of fields that any strategy without location information must examine to certify the absence of k critical fields ($N = 1000$; exact values solid, sufficient closed form $1 - \alpha^{1/k}$ dotted).

(Fig. 1). If verification misses an examined critical field with probability β, absence cannot be certified below β even by a census.

Informative features let a search beat the bound only through a model of where evidence lies:

Proposition 2 (Ranked search): Let one field be critical with score $S_c \sim F_1$, and the other $N-1$ scores be independent with distribution F_0. A scan of the n highest-scoring fields misses the critical field with probability $\mathbb{E}_{S_c}[\mathbb{P}(\mathrm{Bin}(N-1, 1-F_0(S_c)) \ge n)]$, which tends to $1 - \mathrm{TPR}(t_r)$ as $N \to \infty$ with $n/(N-1) \to r$, where t_r is the threshold with false-positive rate r.

Given $S_c = s$, the critical field is missed iff at least n others score above s; the limit follows by dominated convergence. With $F_1 = F_0$ the formula returns $1 - n/N$. Certifying absence by ranking thus needs a sensitivity of about $1 - \alpha$ at a false-positive rate of n/N, a property of the model that no sampling design supplies.

C. Certifying a threshold assertion (RQ3)

Making "$p > \theta$" true requires more than θM blasts, which cannot hide in one field, so the bound above does not apply. With the assorter $a_j = b_j/(2\theta)$, $\bar{a} > 1/2 \iff p > \theta$, and the assertion becomes a one-sided bounded-mean test. Under uniform sampling of fields, ALPHA [5] gives a test supermartingale; rejecting when it exceeds $1/\alpha$ controls false certification at α at any data-dependent stopping time. For adaptive sampling, write $p = \sum_i w_i f_i$ with known weights and $f_i \in [0,1]$. If the field I_t is drawn from a predictable distribution q_t positive on all unsampled fields, the observation $Z_t = w_{I_t} f_{I_t}/q_t(I_t)$ has conditional mean equal to the unsampled mass, which under $H_0 : p \le \theta$ is at most $\mu_t = \theta - \sum_{s<t} w_{I_s} f_{I_s}$; a betting process $\prod_s (1 + \lambda_s(Z_s - \mu_s))$ with predictable, non-negative, bounded bets is a test supermartingale whatever the classifier does [6]. We use their prop-MS sampler, $q_t(i) \propto w_i S_i$ with a floor (S_i the field's mean

TABLE I
WHAT EACH GUARANTEE ASSUMES, AND WHAT HAPPENED WHEN THE ASSUMPTION WAS TESTED.

Assumption	Needed for	Test and result
No location information	Theorem 1	Partly fails on composites; ranking helps only through a model (Prop. 2)
Selection probabilities known, positive	Validity	Uncorrected ranking: false certification 0.89–0.99
Analysis unit = sampled unit	Validity	Cells as draws: up to 0.34 per real specimen, 0.33–0.48 under strong clustering
Target is cell-weighted p	Validity	Averaging proportions: 0.32–0.38; Prop. 3 restores ≤ 0.005
Verified label = truth	Validity for true p	Single reader: 0.28 ("above"), 0.63 ("below"); margin 0.03 sufficed for "above"
Classifier accurate, exchangeable errors	Efficiency only	Validity held under shift (≤ 0.014); saving reversed (1.77× cells)

classifier score), and approximate-Kelly bets. Validity requires only known, positive q_t and verified labels.

Averaging field proportions, however, estimates $N^{-1}\sum_i B_i/m_i$, which is not p when field sizes differ.

Proposition 3 (Unequal field sizes): (a) If every m_i is known, $w_i = m_i/M$ and $f_i = B_i/m_i$ give $\sum_i w_i f_i = p$, so the weighted test is valid for $H_0 : p \leq \theta$. (b) If only $m_i \leq m_{\max}$ is known, $a_i = (B_i - \theta m_i + \theta m_{\max})/m_{\max} \in [0,1]$ and $N^{-1}\sum_i a_i > \theta \iff p > \theta$, so equal-weight tests on a_i with null mean θ are valid.
For (b), $0 \leq B_i \leq m_i \leq m_{\max}$ bounds a_i, and $\sum_i a_i = (\sum_i B_i - \theta M)/m_{\max} + N\theta$. The margin shrinks by $\bar{m}/m_{\max}$, so a loose bound costs power.

Remark 1 (Imperfect verification): If the verifier's false blast calls are at most β_0 times the true non-blasts, its proportion satisfies $\tilde{p} \leq p + \beta_0(1-p)$, so testing $\tilde{p} > \theta + \beta_0(1-\theta)$ is valid for $p > \theta$; symmetrically, testing $\tilde{p} < \theta(1-\beta_1)$ is valid for $p < \theta$ if missed blasts are at most β_1 times the true blasts. The bound concerns the verifier, not the design.

We compare, on the same specimen, ALPHA and betting with uniform sampling; betting with classifier-driven sampling, with and without a control variate; an invalid *uncorrected* design that ranks fields by score but analyses them as uniform draws; and conventional 100- and 200-cell counts. Table I lists what each guarantee assumes and where we tested it.

IV. EXPERIMENTAL DESIGN

A. Pre-registration and status of analyses

Hypotheses, decision rules, seeds and scripts were frozen in five git tags, each pushed before the corresponding data were generated; first confirmatory outputs followed the push by 43 s to 18 min (audit table in the repository). "Confirmatory" means fresh Monte Carlo draws on a disjoint seed family over the same cell pool, which protects against analytic flexibility but not against effects specific to that pool; only H4a–c and H7a used data not analysed before. Several hypotheses check the implementation or a theorem rather than an empirical claim (marked V in Table V). All later analyses used new seed families and are labelled exploratory; all deviations are logged in the repository.

B. Data

KU-Optofil [17] (CC BY 4.0): Sysmex DI-60 images of May–Grünwald–Giemsa peripheral blood smears labelled by haematologists; we used 28,280 cells from 275 identified patients (13 classes) in five patient-grouped folds. Blasts come from only 11 patients (489 blasts). *RV-PBS* [18]: 752 annotated cells (153 blasts) from phone-camera fields, used only as an acquisition-shift probe; no licence is stated. *MLL23* [19] (CC BY 4.0): 41,621 peripheral-blood cells (Pappenheim stain, Metafer scanner), 8,606 myeloblasts; we excluded atypical promyelocytes (blast equivalents our labels do not count), smudge cells and normoblasts, leaving 36,529; there are no patient identifiers. *BoneMarrowWSI* [20], [21] (CC BY 4.0): pediatric bone-marrow aspirate slides with 228 exhaustively annotated regions of about 225 μm; we used the annotations, the per-round reader labels, and the image pixels of the annotated regions.

C. Representation, teachers and specimens

Cells were embedded with a frozen DINOv2 ViT-S/14 [22] (224 px); a logistic probe cross-fitted by patient fold reached an out-of-fold AUC of 0.979. The pre-registered *cell-level teacher* scores a field by its largest cell score, which presupposes cell detection; an exploratory *field-level teacher* is a logistic regression on the pooled field embedding, the representation the selector sees. Part I composites have $N = 200$ fields of $m \in \{1, 5, 10, 20\}$ cells (mean-pooled embeddings) with $k \in \{1, 2, 5, 10, 20\}$ critical fields of one blast. Part III composites have 100 fields of 5 cells ($M = 500$) with p fixed exactly, blasts from all 489 blasts and background cells from blast-free patients; 10% of that background are platelets and erythroblasts, so p is the blast share of imaged objects (a leukocyte-only background changed nothing material; Table IV). Exploratory extensions use M up to 4,000 and field sizes drawn from BoneMarrowWSI.

D. InfoDPP-PAC and baselines

No code has been released. We implemented the objective, greedy blended gain and halting rule (Eqs. 3–7 of [4]) with the published weights, set $\rho = 1$, and calibrated τ on blast-free specimens of other folds so that the median stop is 16.3% of all fields. The original runs stopped at 16.3% of a 300-patch budget, about 2.4% of a slide, so our setting gives InfoDPP-PAC about seven times its own examination share; we also report a 2.4% run. Baselines were uniform sampling at the same per-episode cost (paired), a fixed field order, confidence-based stopping (stop at the first field with relevance ≥ 0.9 or after 30 consecutive fields ≤ 0.1), and exhaustive examination.

E. Statistics

Miss rates: Wilson intervals, exact McNemar tests, fold-clustered bootstrap intervals (pre-registered) and, because five folds allow only 126 bootstrap resamples, t intervals on fold

estimates. False certification: Clopper–Pearson intervals and a one-sided exact binomial test of rate ≤ 0.05. Costs: paired Wilcoxon tests with Holm correction and ratios of medians with bootstrap intervals. Real-data analyses bootstrap over patients. $\alpha = 0.05$ unless stated.

V. Results

A. Information-saturation stopping (RQ1)

In 24,000 confirmatory episodes the median stop was 32–33 of 200 fields in every cell, varying by at most one field across rarity levels (H1a): the halting statistic depends on the embeddings and the selected set, not on relevance. The AUC with which the information-gain term separates critical from non-critical fields fell from 0.778 at $m = 1$ to 0.593, 0.552 and 0.525 at $m = 5, 10, 20$, whereas the field-level teacher on the same pooled embeddings kept 0.978, 0.925, 0.882 and 0.827 (Kill-test 1; the pre-registered cell-level teacher gave 0.977–0.896). The evidence survives pooling; the halting signal does not use it.

At $k = 1$, InfoDPP-PAC missed the critical field in 0.315, 0.681, 0.759 and 0.805 of specimens at $m = 1, 5, 10, 20$; uniform sampling of the same size missed 0.822, 0.830, 0.846 and 0.828, matching $1 - n/N$ (H1d; Fig. 2). The advantage shrank with dilution for every k (H1b), but the pre-registered claim of no advantage at $m \geq 10$ failed (H1c): the difference was -0.087 $[-0.107, -0.067]$ at $m = 10$ and -0.023 at $m = 20$, whose fold-level t interval $[-0.050, 0.003]$ is borderline. Dilution, not rarity, governed the gap; rarity drove the absolute miss rate of every method.

Three saturation rules, calibrated to the same cost on 4,000 new specimens, missed within 0.04 of each other in every cell: InfoDPP-PAC, pure information-gain sampling and k-center coverage stopping missed 0.31–0.34 at $m = 1$ and 0.83–0.85 at $m = 20$, against 0.84 and 0.83 for uniform sampling. A scan ranked by the field-level teacher missed 0.05, 0.14, 0.21 and 0.37; Proposition 2 predicted 0.051, 0.146, 0.221 and 0.394. What separates the rules is relevance, not the stopping criterion. At InfoDPP-PAC's own operating point (2.4%), it missed 0.81–0.97 against 0.97–0.98 for uniform sampling.

On real image tiles (BoneMarrowWSI; 3,040 tiles of about $56\,\mu$m from 99 patients, specimens of 16–32 tiles, 200 runs each), InfoDPP-PAC stopped after 5.4 tiles on average. In the 24 low-blast specimens (at most a quarter of tiles critical) it missed every critical tile in 0.80 of runs, against 0.70 for uniform sampling, the exact value of Proposition 1: a difference of $+0.105$ $[0.002, 0.203]$, worse in 18 of 24 specimens. Its failures were specimen-specific: it missed in at least 95% of runs in 15 specimens, as Theorem 1 predicts for a nearly deterministic selector, whereas uniform sampling stayed near $h(N, k, n)$ everywhere. The teacher's tile-level AUC was 0.966 overall but 0.69 within these specimens, so ranking missed 0.54.

B. Certified threshold decisions (RQ3)

In 12,000 confirmatory 500-cell specimens, all four valid designs kept false certification at $p = \theta$ between 0.001 and 0.022 (H3a), whereas the uncorrected design certified falsely in 0.993 ($\theta = 0.10$) and 0.889 ($\theta = 0.20$) of boundary specimens (H3b; Fig. 3). Classifier-driven betting needed fewer cells than uniform ALPHA at every $p > \theta$ (H3c), for example 75 vs. 165 at $p = 0.15$, $\theta = 0.10$ and 145 vs. 250 at $p = 0.25$, $\theta = 0.20$, and cost fell with the margin (H3d). Separating the two changes, the sampler alone saved 27–72% of cells (0.28–0.73 times), whereas the betting test alone needed 1.03–1.83 times the cells of ALPHA.

TABLE II
Median cells to certify $p > \theta$ against specimen size M (exploratory; 400 specimens per cell). U: uniform ALPHA; C: classifier-driven betting; Approx.: $\log(1/\alpha)/\mathrm{KL}(p\|\theta)$. †Blast images reused, which affects only C.

		$M = 500$		$M = 1{,}000$		$M = 4{,}000$		
θ	p	U	C	U	C	U	C	Approx.
0.10	0.12	390	220	655	420	1,583	798	1,425
0.10	0.15	165	80	205	80	245†	85†	245
0.20	0.22	435	335	810	660	2,033†	2,043†	2,455
0.20	0.25	250	145	303	175	420†	185†	406

TABLE III
Decisions after n individually sampled cells (exploratory; $M = 2{,}000$; 2,000 specimens per row). Conv.: share wrong for the 100-cell count; Exact and Seq.: share correct / wrong for valid fixed-n and sequential tests; the rest is "undetermined".

		$n = 100$			$n = 500$	
θ	p	Conv.	Exact	Seq.	Exact	Seq.
0.10	0.08	0.18	0.08 / <0.01	0.04 / <0.01	0.39 / 0	0.15 / <0.01
0.10	0.12	0.33	0.08 / <0.01	0.02 / <0.01	0.34 / 0	0.15 / <0.01
0.10	0.15	0.10	0.30 / <0.01	0.12 / <0.01	0.96 / 0	0.86 / <0.01
0.20	0.18	0.24	0.07 / <0.01	0.02 / <0.01	0.23 / 0	0.09 / <0.01
0.20	0.22	0.37	0.05 / 0.01	0.02 / <0.01	0.25 / <0.01	0.08 / <0.01
0.20	0.25	0.14	0.18 / 0	0.06 / 0	0.87 / 0	0.59 / 0

With specimens of up to 4,000 cells (exploratory; 17,600 specimens), validity was unchanged (false certification ≤ 0.040 at $\alpha = 0.05$, ≤ 0.007 at $\alpha = 0.01$), and cost in cells was set by the margin, not by M (Table II). At a margin of 0.05 or more it was within 20% of Wald's approximation $\log(1/\alpha)/\mathrm{KL}(p\|\theta)$ [23]; within 0.02 of the threshold it grew towards about 1,400 ($\theta = 0.10$) and 2,500 cells ($\theta = 0.20$). The near-census we had seen at $M = 500$ was a small-specimen effect. Lowering α to 0.01 multiplied the cost by 1.0–1.7; the proposal's claim that $\alpha = 0.01$ is unattainable concerns calibration corrections of conformal-risk-control type (negative risk budget below 99 positive calibration episodes), which design-based tests do not use.

At fixed budgets (exploratory; 2,000-cell specimens, cells sampled individually), we compared three-way decisions ("above", "below", "undetermined"; Table III). Within 0.02 of the threshold a 100-cell count was wrong in 18–37% of specimens. Valid procedures, two one-sided sequential ALPHA tests or exact hypergeometric tests at $\alpha/2$ each, were wrong in at most 0.7% of specimens off the threshold, but at those margins returned "undetermined" in 61–98% of specimens at budgets up to 500 cells; the fixed-n test was decisive more often, the price of anytime validity.




Fig. 2. RQ1, confirmatory run. (a) Miss rate with one critical field for InfoDPP-PAC and for uniform sampling of the same size (95% Wilson intervals); dashed: the worst-case bound $1 - n/N$. (b) AUC of the information-gain term and of the cell-level teacher for ranking critical above non-critical fields; the field-level teacher reaches 0.978, 0.925, 0.882 and 0.827.




Fig. 3. RQ3, confirmatory run (500-cell specimens; $\alpha = 0.05$). (a) False certification at $p = \theta$ with 95% Clopper–Pearson intervals (log scale); CV: control variate; the uncorrected design analyses classifier-ranked fields as uniform draws. (b, c) Median cells to certification with interquartile bands.

C. Where the assumptions break (RQ4)

Classifier error. On KU-Optofil, blast recall at 95% specificity varied across the 11 blast patients from 0.39 to 1.00, false-positive rates across blast-free patients were overdispersed 6.6-fold, and errors concentrated in immature granulocytes and lymphoid cells. Certification stayed valid with blasts drawn only from low-recall patients (≤ 0.007), at 2.3 times the cost.

Acquisition shift. Applied unchanged, the KU-trained probe's blast recall fell to 0.340 [0.250, 0.421] on RV-PBS (H4a) and to 0.63 [0.62, 0.64] on MLL23 (AUC 0.786 and 0.915); its false-positive rate barely rose (0.058 and 0.060 against 0.050; H4b not supported). Every design stayed valid (RV-PBS 3 false certifications in 1,000, H4c; MLL23 0.001–0.011). Efficiency did not: classifier-driven sampling needed 0.28–0.73 times the cells of uniform sampling in distribution, 0.76 [0.70, 0.81] and 0.90 [0.82, 1.05] times on MLL23 ($p = 0.15$, 0.20), and 1.77 times on RV-PBS (195 vs. 110 cells at $p = 0.20$; H6d). A 50% uniform mixture stayed valid (H6a), kept 58–73% of the in-distribution saving (H6c) and cut the RV-PBS excess to $+23\%$ [11, 30], missing the pre-registered 20% bound (H6b). MLL23 and RV-PBS lack patient identifiers, so their intervals are too narrow; the three sources differ in more than recall.

Spatial clustering and the unit of analysis. Under strong synthetic clustering (18,000 specimens), field-level designs stayed valid (≤ 0.042, H5a), whereas analysing the cells of sampled fields as independent draws certified falsely in 0.327 ($\theta = 0.10$) and 0.478 ($\theta = 0.20$) of boundary specimens (H5b); clustering doubled the cost of uniform field sampling (H5c). In 116 exhaustively annotated marrow regions of 75 patients, blasts were clustered (H7a; permutation $p = 0.024$ at the quadrant and 0.0005 at the 4×4 scale), but weakly: the excess intraclass correlation over its permutation null was 0.013 [0.002, 0.028] and 0.043 [0.018, 0.067] (exploratory bias correction). Using each patient's regions as a real specimen with 4×4 subregions as fields and the specimen's own proportion as threshold (an exact null; 400 sampling orders per

specimen; exploratory), the weighted test of Proposition 3(a) certified falsely in 0.001 of runs and at most 0.01 in any specimen. The cell-level analysis gave 0.051 overall, close to α, yet exceeded 0.05 in 27 of 75 specimens (21 significantly), up to 0.335: validity is a statement about each specimen, and a pooled rate can hide failures. These specimens are small (median 105 cells) and mostly high-blast.

Unequal field sizes. Marrow quadrants hold 12–29 nucleated cells (interquartile range). With these sizes, averaging field proportions certified falsely in 0.38 [0.35, 0.41] and 0.32 [0.29, 0.35] of boundary specimens even with blasts placed independently of size, and in every specimen with blasts enriched in small fields: the test is valid for the mean of proportions, which is the wrong quantity. Both constructions of Proposition 3 stayed at or below 0.005; with known counts, classifier-driven sampling certified $p = 0.15$ against $\theta = 0.10$ with 297 cells against 646 for uniform sampling, and the bounded assorter needed 631 because $\bar{m}/m_{\max} \approx 0.24$.

Verifier error. BoneMarrowWSI publishes the label of each reading round; which person read which cell is not recorded [20]. The second reader called a blast in 1.1% [0.7, 1.7] of cells the first called a counted non-blast and a non-blast in 1.2% [0.8, 1.6] of the first reader's blasts; in a further 2.7% of cells one reader did not count the cell. With the first reader as verifier and the consensus as truth (83 real specimens, exact nulls), the reader's proportion differed from the truth by a median of 0.005 (maximum 0.075), and the weighted test certified "$p > \theta_s$" falsely in 0.28 and "$p < \theta_s$" in 0.63 of runs. Remark 1 with the readers' disagreement rates was not enough (0.16, 0.42); a fixed margin of 0.03 made "above" valid in every specimen, whereas "below" still failed in three specimens at 0.05. These margins were chosen in-sample, but the direction is clear: one reader's errors are as large as the affordable margins, so a certificate verified by one person certifies that person's count.

D. Robustness

Table IV collects the sensitivity analyses. None changed the direction of a result; the single-host background enlarged InfoDPP-PAC's residual advantage, so "the advantage vanishes by $m = 20$" depends on the background construction. Table V lists all pre-registered verdicts; three of 20 hypotheses were not supported.

TABLE IV
SENSITIVITY AND ROBUSTNESS CHECKS (P: PRE-REGISTERED; X: EXPLORATORY). DIFFERENCES ARE INFODPP-PAC MINUS UNIFORM AT $k = 1$.

Check		Result
Max pooling	P	-0.115 at $m = 10$, -0.056 at $m = 20$; misses still 73–77%
Single-cell representation	P	-0.036 at $m = 10$ (as mean pooling)
Operating point 5–50%	P	$\lvert\Delta\rvert \leq 0.13$ at $m \geq 10$; grows with the operating point
Single-host background	P	-0.27 at $m = 10$, -0.15 at $m = 20$; duplicates make it artificially homogeneous
Operating point 2.4%	X	Misses 0.81–0.97 vs. 0.97–0.98 (uniform)
Field-level teacher	X	InfoDPP-PAC misses change by ≤ 0.04
ALPHA prior guess	X	Default was the cheapest of three fixed guesses for field-level data
Confusable background (10–20%)	X	Valid (≤ 0.038); classifier-driven cost 75→105 cells, still below uniform
Leukocyte-only background	X	Valid (≤ 0.030); median costs within 15 cells

TABLE V
PRE-REGISTERED HYPOTHESES (E: EMPIRICAL CLAIM; V: IMPLEMENTATION OR THEOREM CHECK).

ID		Hypothesis (abridged)	Verdict
H1a	V	Stop point independent of rarity	yes
H1b	E	Advantage shrinks with dilution	yes (4/4)
H1c	E	No advantage (± 0.05) at $m \geq 10$	**no**
H1d	V	Uniform miss rate $= 1 - n/N$	yes
KT1	E	Information gain and relevance separable	yes
H3a	V	Four designs valid at both thresholds	yes
H3b	E	Uncorrected adaptive selection invalid	yes
H3c–d	E	Classifier-driven cheaper; cost falls with margin	yes
H4a	E	Blast recall drops under shift	yes
H4b	E	False-positive rate rises under shift	**no**
H4c	V	Certificate valid with shifted scores	yes
H5a	V	Field-level tests valid under clustering	yes
H5b–c	E	Cell-level analysis invalid; clustering raises cost	yes
H6a	V	Defensive mixture valid	yes
H6b	E	Mixture caps loss under shift below 20%	**no**
H6c–d	E	Mixture keeps $\geq$50% saving; reversal replicates	yes
H7a	E	Blasts clustered in real smears	yes

VI. DISCUSSION

Our results separate three quantities that are often reported together. *Model confidence* about examined fields says nothing about unexamined ones. *Information saturation* concerns the selector's representation of the specimen; its association with decision-relevant evidence disappeared once cells were pooled into fields, although the pooled representation still carried the evidence, and on real tiles saturation-based selection did worse than uniform sampling. *Design-based certification* bounds the probability of a false threshold decision for the specific specimen, provided selection probabilities are known and positive and labels come from verification. Only the third is a guarantee about what was not examined. It held in every condition we tested, specimen by specimen, including a classifier that lost two thirds of its blast recall; the classifier affected only how quickly certification was reached.

Four practical consequences follow. First, certify a proportion against a stated threshold rather than the absence of rare cells, which requires a near-census; the cost is set by the margin, in cells, not by specimen size. Second, record selection probabilities, analyse at the unit that was sampled, and weight fields by their cell counts. Third, allow and report "undetermined": near the threshold it is the honest outcome of a few hundred cells, and a count that forces a call is wrong in up to a third of specimens. Fourth, treat verifier error as part of the claim: a certificate concerns the verifier's count, and relating it to the true proportion needs a margin that




Fig. 4. RQ4. (a) Median cells to certify $p > 0.10$ in distribution (KU-Optofil) and under acquisition shift (RV-PBS); all designs keep false certification ≤ 0.014. (b) False certification at $p = \theta$ when cells of sampled fields are analysed as individual draws: composites with scattered or hot-field arrangements (markers) and the model at the clustering measured in marrow regions (lines; grey band: CI of the raw, upward-biased ICC).

bounds verifier error, established on separate data. A procedure that is valid but usually undetermined near the threshold is statistically sound and operationally limited; making it decisive requires more cells, not a more confident model.

Limitations. Most specimens are composites from one laboratory, and all KU-Optofil blasts come from 11 patients, so cost and miss-rate comparisons are imprecise. The real-data spatial, tile and verifier analyses use pediatric bone-marrow aspirates, not peripheral blood; their specimens are small and mostly high-blast, and specimens near the diagnostic thresholds are barely represented. The external sources lack patient identifiers. Reading rounds are not identified experts, and the verifier margins were chosen in-sample. Many analyses were added after the pre-registered ones and are exploratory. InfoDPP-PAC's unreported hyperparameters were calibrated to a cost, though two other saturation rules gave the same result. We used one frozen encoder and did not implement prediction-powered e-values [14].

VII. Conclusion

Information saturation does not certify what remains unexamined, and without location information certifying the absence of rare evidence requires examining nearly the whole specimen. Threshold decisions about the blast proportion can be certified with finite-sample, anytime-valid guarantees, whose validity rests on the sampling design, the unit of analysis and the verifier rather than on the classifier. Fully annotated peripheral-blood smears with patient identifiers, and verification by identified haematologists, are the most important next steps.

Data and Code Availability

Code, the pre-registration with its git history and audit table, the deviation log and the analysis outputs are available at [repository URL; to be archived on Zenodo with a DOI]. KU-Optofil, BoneMarrowWSI-PediatricLeukemia and MLL23 are public under CC BY 4.0; RV-PBS is distributed by its authors without a stated licence and was used for research only.

Acknowledgment

The author thanks Dr. Balázs Harangi for supervising this work.

References

[1] C. L. Rümke, "The statistically expected variability in differential leukocyte counting," in *Differential Leukocyte Counting (CAP Conference/Aspen 1977)*, J. A. Koepke, Ed. College of American Pathologists, 1977, pp. 39–45.

[2] J. D. Khoury *et al.*, "The 5th edition of the World Health Organization classification of haematolymphoid tumours: Myeloid and histiocytic/dendritic neoplasms," *Leukemia*, vol. 36, pp. 1703–1719, 2022.

[3] D. A. Arber *et al.*, "International consensus classification of myeloid neoplasms and acute leukemias: Integrating morphologic, clinical, and genomic data," *Blood*, vol. 140, no. 11, pp. 1200–1228, 2022.

[4] P. Mittal, A. Srivastava, and J. Chauhan, "InfoDPP-PAC: Principled patch selection for whole slide image analysis," *arXiv preprint arXiv:2608.23574*, 2026, version 1, submitted 7 July 2026; also Preprints.org 202607.0611. Not peer reviewed.

[5] P. B. Stark, "ALPHA: Audit that learns from previously hand-audited ballots," *The Annals of Applied Statistics*, vol. 17, no. 1, 2023.

[6] S. Shekhar, Z. Xu, Z. C. Lipton, P. J. Liang, and A. Ramdas, "Risk-limiting financial audits via weighted sampling without replacement," in *Proceedings of the Thirty-Ninth Conference on Uncertainty in Artificial Intelligence (UAI)*, ser. Proceedings of Machine Learning Research, vol. 216, 2023, pp. 1932–1941, arXiv:2305.06884.

[7] J. A. Hanley and A. Lippman-Hand, "If nothing goes wrong, is everything all right? Interpreting zero numerators," *JAMA*, vol. 249, no. 13, pp. 1743–1745, 1983.

[8] C. Matek, S. Schwarz, K. Spiekermann, and C. Marr, "Human-level recognition of blast cells in acute myeloid leukaemia with convolutional neural networks," *Nature Machine Intelligence*, vol. 1, pp. 538–544, 2019.

[9] M. Lindeman and P. B. Stark, "A gentle introduction to risk-limiting audits," *IEEE Security & Privacy*, vol. 10, no. 5, pp. 42–49, 2012.

[10] I. Waudby-Smith and A. Ramdas, "Estimating means of bounded random variables by betting," *Journal of the Royal Statistical Society Series B: Statistical Methodology*, vol. 86, no. 1, pp. 1–27, 2024.

[11] J. Ville, *Étude critique de la notion de collectif*. Paris: Gauthier-Villars, 1939.

[12] J. V. Spertus, M. Sridhar, and P. B. Stark, "Sequential stratified inference for the mean," *arXiv preprint arXiv:2409.06680*, 2024.

[13] A. N. Angelopoulos, S. Bates, C. Fannjiang, M. I. Jordan, and T. Zrnic, "Prediction-powered inference," *Science*, vol. 382, no. 6671, pp. 669–674, 2023.

[14] D. Csillag, C. J. Struchiner, and G. T. Goedert, "Prediction-powered e-values," in *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 267, 2025, pp. 11 493–11 514, arXiv:2502.04294.
[15] T. Zrnic and E. J. Candès, "Active statistical inference," in *Proceedings of the 41st International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 235, 2024, pp. 62 993–63 010.
[16] A. C.-C. Yao, "Probabilistic computations: Toward a unified measure of complexity," in *18th Annual Symposium on Foundations of Computer Science (FOCS)*, 1977, pp. 222–227.
[17] A. E. Yarıkan, C. Örer, V. Akyıldız, Z. Kuş, M. Aydin, K. E. Palaoğlu, S. İncir, K. Baysal, C. Özçelik, B. Kiraz, and A. Kiraz, "A large-scale peripheral blood cell dataset for automated hematological analysis," *Scientific Data*, vol. 13, p. 417, 2026, data: Zenodo, doi:10.5281/zenodo.17333317.
[18] J. B. Pal, A. Bhattacharyea, D. Banerjee, and T. Maharaj, "Advancing instance segmentation and WBC classification in peripheral blood smear through domain adaptation: A study on PBC and the novel RV-PBS datasets," *Expert Systems with Applications*, vol. 249, p. 123660, 2024.
[19] S. Shetab Boushehri, S. Kazeminia, A. Gruber, C. Matek, K. Spiekermann, C. Pohlkamp, T. Haferlach, and C. Marr, "A large expert-annotated single-cell peripheral blood dataset for hematological disease diagnostics," *Scientific Data*, vol. 12, p. 1773, 2025, dataset MLL23: Zenodo, doi:10.5281/zenodo.14277609, CC BY 4.0.
[20] H. Höfener, F. Kock, M. A. Pontones, T. Ghete, D. Pfrang, N. Dickel, M. Kunz, D. Schacherer, D. A. Clunie, A. Fedorov, M. Westphal, and M. Metzler, "BoneMarrowWSI-PediatricLeukemia: A comprehensive dataset of bone marrow aspirate smear whole slide images with expert annotations and clinical data in pediatric leukemia," Zenodo and NCI Imaging Data Commons, 2026, version distributed via NCI Imaging Data Commons; latest Zenodo version v5, doi:10.5281/zenodo.18499180.
[21] H. Höfener *et al.*, "From data to diagnosis: A large, comprehensive bone marrow dataset and AI methods for childhood leukemia prediction," *arXiv preprint arXiv:2509.15895*, 2025.
[22] M. Oquab *et al.*, "DINOv2: Learning robust visual features without supervision," *Transactions on Machine Learning Research*, 2024, arXiv:2304.07193.
[23] A. Wald, "Sequential tests of statistical hypotheses," *The Annals of Mathematical Statistics*, vol. 16, no. 2, pp. 117–186, 1945.

APPENDIX
PROOF OF THEOREM 1

Fix x and a realisation u of the examiner's randomness. On the run in which every examined field is negative, every input to the policy is determined by (x, u), so the run examines a fixed set $A(u)$ with $|A(u)| \leq n$. If $C \cap A(u) = \emptyset$, the actual run follows this path and misses C; otherwise it follows the path until the first element of C in $A(u)$, which it examines. Hence $\mathbb{P}_\pi(M_n \mid x, C) = \mathbb{P}_U(C \cap A(U) = \emptyset)$. Let C be uniform over k-subsets, independent of U, which Assumption 1 permits. For fixed u, the fraction of k-subsets disjoint from $A(u)$ is at least $\binom{N-n}{k}/\binom{N}{k} = h(N, k, n)$. Averaging over U and noting that the maximum over C is at least the average gives the bound; uniform sampling attains it by Proposition 1. For a deterministic policy A is one set with $|A| \leq N - k$, and placing C outside it gives miss probability 1.