Status	Finished
Started	Tuesday, 15 September 2026, 9:37 PM
Completed	Tuesday, 15 September 2026, 9:51 PM
Duration	13 mins 50 secs
Grade	**11.00** out of 15.00 (**73.33**%)

Question **1**

Complete

Mark 1.00 out of 1.00

What keyword would you use to add an alternative condition to an if statement?

- a. elif
- b. else if
- c. elseif

Question **2**

Complete

Mark 1.00 out of 1.00

What is the output when the following sequence of instructions is carried out in the console?

```
a = 1;a = a + 1;a = a + 2;a = a + 3;print(a)
```

- a. 4
- b. 5
- c. 7
- d. 6

Question **3**

Complete

Mark 1.00 out of 1.00

What is the output of the following code.

```
a="REC"
if a in ("rec"):
    print(a)
print(a)
```

a. REC
REC

b. REC

c. No output
REC

d. false
REC

Question **4**

Complete

Mark 1.00 out of 1.00

Leading whitespace (spaces and tabs) at the beginning of a statement is called _____.

a. **Iteration**

b. **orientation**

c. **None of the above**

d. **indentation**

Question **5**

Complete

Mark 0.00 out of 1.00

Given the nested `if-else` below, what will be the value `x` when the code executed successfully

```
x = 0
a = 5
b = 5
if a > 0:
    if b < 0:
        x = x + 5
    elif a > 5:
        x = x + 4
    else:
        x = x + 3
else:
    x = x + 2
print(x)
```

a. 0
b. 2
c. 3
d. 4

Question **6**

Complete

Mark 1.00 out of 1.00

____ is an empty statement in Python.

a. Jump
b. pass
c. Empty
d. None

Question **7**

Complete

Mark 0.00 out of 1.00

Which of the following is true about the code below?

```
x = 3
if (x > 2):
    x = x * 2;
if (x > 4):
    x = 0;
print(x)
```

a. if x is greater than 2, x will equal 0 after this code executes

b. if x is greater than 2, the value in x will be doubled after this code executes

c. if x is lesser then 0,x will be 0 after this code executes

d. x will always equal 0 after this code executes for any value of x

Question **8**

Complete

Mark 1.00 out of 1.00

Number of elif in a program is dependent on the _____

a. **number of loops in a program**

b. **number of variables in a program**

c. All the Above

d. **number of conditions to be checked**

Question **9**

Complete

Mark 1.00 out of 1.00

What keyword would you use to add an alternative condition to an if statement?

a. None of the above

b. elseif

c. else if

d. elif

Question **10**

Complete

Mark 1.00 out of 1.00

What is the output of the given below program?

```
if 1 + 3 == 7:
   print("Hello")
else:
   print("Know Program")
```

a. Error

b. Hello

c. Know Program

d. Compiled Successfully, No Output.

Question **11**

Complete

Mark 1.00 out of 1.00

Correct syntax of writing 'simple if' statement is _____

a.
```
if condition --
   statements
```

b.
```
if condition
statements
```

c.
```
if condition :
   statements
```

d.
```
if (condition)
   statements
```

Question **12**

Complete

Mark 0.00 out of 1.00

What is the output of the following snippet?

```
s1 = "IIT "  # Remember there is a space after T in IIT
s2 = "Punjab"
s1 = s1 * 2
s2 = "Ropar"
print(s1, s2)
```

a. IIT Ropar

b. IIT IIT Ropar

c. IIT IIT Punjab

d. IIT Punjab

Question **13**

Complete

Mark 1.00 out of 1.00

Which of the following options correctly prints the phrase "Hurry Up!!"?

a. print_sentence(Hurry Up!!!)

b. print("Hurry Up!!")

c. print(Hurry Up!!!)

d. printf("Hurry Up!!")

Question **14**

Complete

Mark 1.00 out of 1.00

Ahaana wants to make a fun program , if user enters any number a "Good" or "funny" message will appear . She is confused that which is the most suitable control to be used to make such program. Help her to choose correct option.

a. if elif

b. Nested if

c. if else

d. If

Question **15**

Complete

Mark 0.00 out of 1.00

Which among the following codes have equivalent logic?

Code 1:

```
if(value3>1000 and value3<1006):
  if(value1=="ABC"):
    if(value2=="A"):
      value4=10
    else:
      value4=8
  elif(value1=="XYZ"):
    if(value2=="A"):
      value4=8
    else:
      value4=6
print(value4)
```

Code 2:

```
if(value3>=1001 and value3<=1005 and value1=="ABC"):
    if(value2=="A"):
        value4=10
    else:
        value4=8
elif(value3>1000 and value3<1006 and value1=="XYZ"):
     if(value2=="A"):
        value4=8
     else:
        value4=6
print(value4)
```

Code 3:

```
if(value3>1000 and value3<1006 or value1=="ABC"):
   if(value2=="A"):
      value4=10
   else:
      value4=8
elif(value3>1000 and value3<1006 or  value1=="XYZ"):
   if(value2=="A"):
      value4=8
   else:
      value4=6
print(value4)
```

a. Code 1, Code 2

b. Code 2, Code 3

c. Code 1, Code 3