

Kaggle Environment and Dataset Setup Guide

1. Import the Notebook into Kaggle

- **Step 1:** Log into Kaggle and click the **Create (+)** button in the left sidebar, then select **New Notebook**.
- **Step 2:** In the top menu bar of your notebook, navigate to **File → Import Notebook**.
- **Step 3:** Click the **Upload** tab, drag and drop your notebook file, and click **Import**.

2. Upload the /data Folder as a Dataset

- **Step 1:** Click **Create (+)** in the top navigation bar and select **New Dataset**.
- **Step 2:** Compress your local **data/** folder into a ZIP file or select the folder directly, name your dataset (e.g., **benchmark-data**), and click **Create**.
- **Step 3:** Wait for Kaggle to finish processing and creating the dataset.

3. Attach the Dataset to Your Notebook

- **Step 1:** Open your imported notebook on Kaggle.
- **Step 2:** On the right-side panel, locate the **Input** section and click **+ Add Input**.
- **Step 3:** Go to **Your Datasets**, find **benchmark-data**, and click the **(+)** icon to attach it.

4. Path Adjustment and Error Resolution

- **Where the error happens:** In `config.yaml` and `src/data_loader.py`, the pipeline searches for data files using the relative path `data/items.jsonl`.
- **Why it gives an error:** Kaggle mounts all attached datasets in a separate read-only input directory located at `/kaggle/input/<your-dataset-name>/`. Because the files are not directly inside `/kaggle/working/data/`, Python throws a `FileNotFoundError`.
- **How to fix it:** Add a setup script at the beginning of your notebook to automatically copy the files from `/kaggle/input/<your-dataset-name>/` directly into `/kaggle/working/data/`. This ensures all relative paths work as expected without altering any pipeline code.