```jsx
import React from 'react';



const LandingPage: React.FC = () => {

return (

  <div className="flex flex-col items-center justify-center h-screen bg-gray-100">

    <h1 className="text-5xl font-bold text-blue-500 mb-4">Welcome to our Landing Page</h1>

    <p className="text-lg text-gray-600 mb-8">This is a sample landing page created using React and Tailwind CSS.</p>

    <button className="bg-blue-500 hover:bg-blue-700 text-white font-bold py-2 px-4 rounded">Get Started</button>

    <div className="flex flex-row justify-center mt-8">

      <div className="bg-white shadow-md rounded px-8 pt-6 pb-8 mb-4 w-1/3 mx-4">

        <h2 className="text-lg font-bold text-gray-600 mb-2">Feature 1</h2>
```

```
    <p className="text-gray-600">This is a sample feature description.</p>

  </div>

  <div className="bg-white shadow-md rounded px-8 pt-6 pb-8 mb-4 w-1/3 mx--4">

    <h2 className="text-lg font-bold text-gray-600 mb-2">Feature 2</h2>

    <p className="text-gray-600">This is a sample feature description.</p>

  </div>

  <div className="bg-white shadow-md rounded px-8 pt-6 pb-8 mb-4 w-1/3 mx--4">

    <h2 className="text-lg font-bold text-gray-600 mb-2">Feature 3</h2>

    <p className="text-gray-600">This is a sample feature description.</p>

  </div>

</div>
```

```
    </div>

  );

};


export default LandingPage;
```