

Q CALCULATOR MAKES STEEL PROCESSING EASIER!

Q calculator allows users to calculate the data, to optimally process Quard & Quend, the quenched and tempered steels produced by NLMK Clabecq. The application offers the ability to quickly and efficiently calculate the best parameters for all possible operations on QT steel (welding, cutting,...)

EASY TO USE STEEL

The QT steel plates of NLMK Clabecq are known for being easy to use and process. That is a great added value for those who work with steel in a workshop. The Q Calculator will only further enhance the ease of use and the rapid processing of Quard and Quend. These parameters were determined by means of tests and a process of trial and error.

LONGER LIFE SPAN

The application can also extend the life of a component. Welded points, for example, are critical. With the correct parameters calculated by the application, the best possible result is achieved, which of course benefits the lifetime.

USEFUL TOOL

The app is a handy tool for the customers. A big advantage of the application is that it offers a direct solution in all circumstances. For example, steel buckets in mines or quarries are usually repaired on site. These are not ideal conditions for carrying out a repair properly and correctly. Thanks to the Q Calculator, this can be done in a more effective way.



or on line on
<https://qt.nlmk.com/en/mobile-app/>



Production site of NLMK Clabecq
Rue de Clabecq, 101 - 1460 Ittre (Belgium)



Q CALCULATOR

**OPTIMIZES THE
WORKABILITY
PARAMETERS OF
QUARD® AND QUEND®!**



Europe - Plate



« CUTTING BENDING WELDING MACHINING »



Welding

Joint type

Double open square butt weld

Single V butt weld

Double V butt weld

Fillet weld lap joint

Double fillet weld T-joint

Single bevel T-joint

Fillet weld corner joint

Single bevel corner joint

Welding type

METAL ACTIVE/INERT GAS (MAG/I)

Consumable type

FERRITIC

First material

QUARD 450

First thickness (mm)

12

Second material

QUARD 450

Second thickness (mm)

12

CALCULATE

Welding

Recommended electrodes to be used for welding have to been chosen according to EN Class EN ISO 14341 G4X & AWS Class A5.28 ER70S

Recommended welding parameters

Diameter of wire

1.2 mm

Intensity (I)

210 A

Tension (U)

25 V

Duration for 100 mm

24 sec

Minimum preheating temperature (TpMin) °C

20

