

Chapter 2

1. **Minimum PHP version required to install Laravel 10?**

- A) PHP 5.6
- B) PHP 7.2
- C) **PHP 8.0**
- D) PHP 7.4

2. **Package manager used to install Laravel via Composer?**

- A) npm
- B) pip
- C) **Composer**
- D) gem

3. **Command to create a new Laravel project?**

- A) composer require laravel/laravel
- B) **composer create-project laravel/laravel**
- C) npm install laravel/laravel
- D) php artisan new

Answer: B) composer create-project laravel/laravel

4. **Purpose of the .env file in a Laravel project?**

- A) **To store environment variables like database credentials**
- B) To configure routes
- C) To store application logs
- D) To manage migrations

5. **Which is NOT a requirement for installing Laravel?**

- A) PHP
- B) Node.js
- C) **MySQL**
- D) Composer

6. **What does the command php artisan serve do?**

- A) It runs database migrations

- B) It compiles the front-end assets
 - C) It starts the Laravel development server**
 - D) It installs Composer dependencies
7. **Tool used to manage Laravel's front-end assets?**
- A) Gulp
 - B) npm
 - C) Yarn
 - D) Webpack Mix**
8. **Default local development URL when running php artisan serve?**
- A) <http://localhost:8000>**
 - B) <http://127.0.0.1:8080>
 - C) <http://localhost:3000>
 - D) <http://127.0.0.1:4000>
9. **Purpose of the composer install command?**
- A) It installs front-end dependencies
 - B) It creates the .env file
 - C) It installs PHP dependencies defined in composer.json**
 - D) It runs the development server
10. **Command to apply pending migrations?**
- A) php artisan rollback
 - B) php artisan migrate**
 - C) php artisan db
 - D) php artisan db

Chapter 3

1. **Default file for defining routes in a Laravel application?**
- A) routes.php
 - B) app/Http/routes.php
 - C) routes/web.php**
 - D) routes/controller.php

2. **HTTP method handled by Route::get()?**

- A) POST
- B) GET**
- C) PUT
- D) DELETE

3. **Command to create a new controller in Laravel?**

- A) php artisan make**
- B) php artisan make
- C) php artisan new
- D) php artisan controller

4. **Passing a route parameter to a controller action?**

- A) Route::get('/user', 'UserController@index');
- B) Route::post('/user/{id}', [UserController::class, 'show']);
- C) Route::get('/user/{id}', 'UserController@index');
- D) Route::get('/user/{id}', [UserController::class, 'show']);**

5. **Method to handle showing a list of resources in a resource controller?**

- A) show()
- B) index()**
- C) store()
- D) update()

6. **Command to create a resource controller?**

- A) php artisan make--resource**
- B) php artisan make--all
- C) php artisan create
- D) php artisan make--res

7. **Purpose of Route::resource() function?**

- A) It generates routes for all controller methods manually.
- B) It creates routes only for the index() and show() methods.
- C) It automatically generates routes for all typical resourceful actions.**

- D) It creates routes for the store() method only.
8. **Correct syntax for naming a route?**
- A) `Route::get('/user', [UserController::class, 'show'])->name('user.show');`
 - B) `Route::name('user.show', '/user')->get([UserController::class, 'show']);`
 - C) `Route::get('/user', [UserController::class, 'show']);`
 - D) `Route::controller('/user', 'show')->name('user.show');`
9. **Which is NOT a valid HTTP method supported by Laravel routes?**
- A) GET
 - B) POST
 - C) **FETCH**
 - D) PUT
10. **How to group multiple routes with common middleware?**
- A) `Route::middleware(['auth'])->group(function () {...});`
 - B) `Route::group('middleware', 'auth', function () {...});`
 - C) `Route::auth('group', ['auth'], function () {...});`
 - D) `Route::group(['auth', 'middleware'], function () {...});`
-

Chapter 4

1. **What is Blade in Laravel?**
- A) A database engine
 - B) A routing tool
 - C) Laravel's templating engine
 - D) **A middleware handler**
2. **How to output a variable in Blade?**
- A) `{{ $variable }}`
 - B) `<% $variable %>`
 - C) `<?php echo $variable; ?>`
 - D) `@output($variable)`
3. **Directive to include a view inside another Blade view?**

- A) @extend
 - B) @include**
 - C) @insert
 - D) @view
4. Directive to check a condition in Blade?
- A) @if**
 - B) @condition
 - C) @check
 - D) @is
5. How to prevent Blade from rendering a variable?
- A) @@{{ \$variable }}
 - B) \{{ \$variable }}
 - C) {{{ \$variable }}}}
 - D) @verbatim {{ \$variable }} @endverbatim**
6. Blade directive to loop through an array or collection?
- A) @loop
 - B) @foreach**
 - C) @forarray
 - D) @iterate
7. Purpose of the @yield directive in Blade?
- A) To extend a layout
 - B) To define a section that can be filled by a child view**
 - C) To include another view
 - D) To display the content of a view
8. How to extend a Blade layout?
- A) @extend('layout')
 - B) @layout('layout')
 - C) @extends('layout')
 - D) @inherit('layout')**

9. **Correct way to define a Blade section?**

- A) **@section('content') ... @endsection**
- B) @define('content') ... @enddefine
- C) @section('content') ... @stop
- D) @block('content') ... @endblock

10. **How to comment in Blade templates?**

- A) **{{-- Comment --}}**
- B) // Comment
- C) /* Comment */
- D) <!-- Comment -->

11. Which framework is mentioned in the passage as offering a custom templating engine? (Page-63)

- A) Django
- B) Ruby on Rails
- C) **Laravel**
- D) Express.js

12. What symbol does Blade use to prefix its custom tags, called "directives"? (Page-63)

- A) #
- B) **@**
- C) \$
- D) &

13. In terms of structure, how do Blade's control structures generally appear? (Page-65)

- A) More verbose than PHP's
- B) **Similar to PHP's in name and structure**
- C) Completely different from PHP's
- D) Limited to simple conditions

14. What is required in the parent template when using Blade stacks? (Page-72)

- A) A database connection
- B) **A defined stack placeholder**
- C) A global CSS file
- D) User authentication

15. What might an example of service injection in a Blade view include? (Page-79)

- A) User input forms
- B) **An instance of an analytics service**
- C) Static content
- D) Inline CSS styles

16. What is an example of a custom directive mentioned in the passage? (Page-80)

- A) @admin
- B) @ifUser

- C) **@ifGuest**
 - D) **@checkAuth**
17. How can you resolve an instance of the Context class in your views? (Page-82)
- A) By creating a new instance directly
 - B) **By using app('context')**
 - C) By including it in every view manually
 - D) By calling Context::getInstance()
18. Where can you configure your database credentials in Laravel? (Page-87)
- A) config/app.php
 - B) **config/database.php and .env**
 - C) routes/web.php
 - D) resources/views
19. What Artisan command is used to run outstanding migrations? (Page-97)
- A) **php artisan migrate**
 - B) php artisan migrate
 - C) php artisan db
 - D) php artisan migrate
20. What is the purpose of the migrate
- command? (Page-97)
- A) To create a new migration
 - B) To roll back migrations
 - C) **To create the database table that tracks migrations**
 - D) To display migration status
21. What is the name of Laravel's templating engine? (Page-63)
- A) Twig
 - B) Smarty
 - C) **Blade**
 - D) Razor
22. What is the core characteristic of Blade's syntax? (Page-64)
- A) Complicated and verbose
 - B) **Clean and concise**
 - C) Only for beginners
 - D) Limited to basic functionality
23. What are Blade's stacks used for? (Page-72)
- A) Managing database queries
 - B) **Adding multiple entries to a section in a template**
 - C) Storing user sessions
 - D) Caching API responses
24. What is the purpose of injecting a service into a view? (Page-79)
- A) To modify the view's layout
 - B) **To generate data or views**
 - C) To handle user authentication
 - D) To connect to a database

25. What are Blade directives like @if and @unless used for? (Page-80)
- A) User authentication
 - B) **Mapping a pattern to PHP output**
 - C) Creating CSS styles
 - D) Generating database queries
26. What is the name of the class that encapsulates multitenancy logic? (Page-82)
- A) UserContext
 - B) Tenant
 - C) **Context**
 - D) MultiTenant
27. What is Eloquent in Laravel? (Page-87)
- A) A file management tool
 - B) **An ActiveRecord ORM (object-relational mapper)**
 - C) A frontend framework
 - D) A testing suite
28. What is the role of Eloquent in a Laravel application? (Page-87)
- A) To manage user sessions
 - B) To handle email sending
 - C) **To retrieve, represent, and persist data for a database table**
 - D) To format data for APIs
29. What does the command php artisan migrate --seed do? (Page-97)
- A) Only runs migrations
 - B) **Runs migrations and seeds the database**
 - C) Resets all migrations
 - D) Deletes the database
30. What does the migrate command do?
- A) Only runs new migrations
 - B) Drops all tables and recreates them
 - C) **Rolls back all migrations and then runs them again**
 - D) Displays the status of migrations
31. What is the primary purpose of Blade templating?
- A) To handle database connections
 - B) **To create dynamic HTML views**
 - C) To manage user authentication
 - D) To perform server-side scripting
32. Which Blade directive is used to include view partials?
- A) @section
 - B) **@include**
 - C) @yield
 - D) @component
33. What does the @section directive do in Blade?
- A) It displays data directly.
 - B) **It defines a section of content that can be displayed in a layout.**
 - C) It loops through an array.
 - D) It injects services into views.

34. Which control structure in Blade is used for conditional statements?
- A) @foreach
 - B) **@if**
 - C) @while
 - D) @loop
35. How do you define a reusable component in Blade?
- A) @include
 - B) **@component**
 - C) @section
 - D) @extend
36. What are view composers used for in Blade?
- A) To format dates
 - B) **To bind data to views**
 - C) To create custom directives
 - D) To handle session data
37. Which directive allows you to define a stack of content in Blade?
- A) @section
 - B) @yield
 - C) **@push**
 - D) @show
38. What is the benefit of using custom Blade directives?
- A) They simplify the routing process.
 - B) **They allow for more complex logic in templates.**
 - C) They increase database performance.
 - D) They enhance security features.
39. In Blade, how do you pass parameters to custom directives?
- A) By using @param
 - B) **By defining parameters in the directive**
 - C) By using @include
 - D) By appending to the directive name
40. What does the @yield directive do in Blade templates?
- A) It includes another view.
 - B) **It defines a section to be filled later.**
 - C) It loops through an array of items.
 - D) It shows a specific content block.
41. What is the primary purpose of defining migrations in Laravel?
- A) To manage user authentication
 - B) **To create and modify database tables**
 - C) To handle HTTP requests
 - D) To manage application routes
42. Which command is used to run migrations in Laravel?
- A) **php artisan migrate**
 - B) php artisan db
 - C) php artisan migrate
 - D) php artisan migrate

43. What is the purpose of a seeder in Laravel?
- A) To perform database backups
 - B) **To insert dummy data into the database**
 - C) To create migrations
 - D) To run raw SQL commands
44. Which of the following is used to interact with the database using Eloquent?
- A) DB Facade
 - B) Query Builder
 - C) **Eloquent Models**
 - D) Seeder
45. How do you define a new Eloquent model in Laravel?
- A) By extending the DB class
 - B) **By extending the Model class**
 - C) By creating a migration file
 - D) By creating a controller
46. What are accessors and mutators used for in Eloquent models?
- A) To define database relationships
 - B) To handle HTTP requests
 - C) **To customize field interactions**
 - D) To run migrations
47. Which feature of Eloquent allows you to perform batch operations on multiple records?
- A) **Eloquent Collections**
 - B) Transactions
 - C) Scopes
 - D) Model Factories
48. What does the Query Builder provide in Laravel?
- A) Only raw SQL execution
 - B) **A way to construct database queries programmatically**
 - C) A way to create Eloquent models
 - D) A method for defining database migrations
49. Which method is used to delete a record using Eloquent?
- A) **delete()**
 - B) remove()
 - C) destroy()
 - D) discard()
50. What is the role of Eloquent events in Laravel?
- A) To manage database transactions
 - B) **To listen for changes in models and perform actions**
 - C) To seed the database with test data
 - D) To define custom queries
51. • Which is the Laravel templating engine?
- A) **Blade**
 - B) Valet
 - C) Homestead
 - D) Lambo

52. • Blade uses ___ for its “echo”.
- A) <?= ?>
 - B) {{ }}
 - C) [[]]
 - D) <? ?>
53. • Blade custom tags are prefixed with an ___
- A) #
 - B) *
 - C) /
 - D) @
54. • Which is used to escape all echoes in Blade?
- A) {{ \$variable }}
 - B) <? htmlentities(\$variable) ?>
 - C) <?= htmlentities(\$variable) ?>
 - D) {!! \$variable !!}
55. • Which syntax is used for compiling PHP conditions in Blade?
- A) #
 - B) *
 - C) @
 - D) !
56. • By which directive do we define that this view should not be rendered?
- A) @section
 - B) @extends
 - C) @parent
 - D) @endsection
57. • Where do we define Blade stacks?
- A) in each child template
 - B) sidebar
 - C) **parent template**
58. • Which is used to make components easier?
- A) Aliasing
 - B) Models
 - C) **Composer**
59. • Which of the following methods can be used to echo data in a Laravel Blade template?
- A) {{ }}
 - B) {!! !!}
 - C) @echo()
 - D) All of the above
60. • Which Blade directive is used to specify the section of a child template that should fill in a parent template's content?
- A) @include
 - B) @extend
 - C) **@section**
 - D) @yield
61. • In Laravel's Blade template system, which directive is used in the parent layout to define where the content from child templates should be inserted?

- A) @section
 - B) **@yield**
 - C) @include
 - D) @extends
62. • What is the primary purpose of Laravel components?
- A) To generate SQL queries
 - B) **To separate frontend code into reusable blocks**
 - C) To create database migrations
 - D) To manage route definitions
63. • Which method is used to define a custom Blade directive in Laravel?
- A) Blade::define()
 - B) Blade::setDirective()
 - C) Blade::registerDirective()
 - D) **Blade::directive()**
64. • How do you access the arguments passed to a custom Blade directive inside the directive's callback function?
- A) As an array passed to the function.
 - B) Using the \$args variable automatically provided by Laravel.
 - C) **As a string passed to the callback function.**
 - D) By directly referencing Blade syntax inside the callback.
65. • Which of the following is used to create custom Blade directives in Laravel?
- A) **Blade::directive()**
 - B) Blade::if()
 - C) Blade::make()
 - D) Blade::create()
66. • What is the primary purpose of using Laravel's custom @if directives in Blade templates?
- A) To directly inject raw SQL queries.
 - B) **To conditionally display sections of HTML.**
 - C) To automatically generate migrations.
 - D) To cache views for performance.
67. • In a multitenant Laravel app, a custom Blade directive @tenant is created to check tenant-specific data. How would you call this directive in a Blade template?
- A) {{@tenant}}
 - B) **@tenant(\$tenantId)**
 - C) {{tenant(\$tenantId)}}
 - D) @ifTenant(\$tenantId)
68. • In Laravel, which method is used to define a custom Blade directive for a multitenant application?
- A) Blade::create()
 - B) **Blade::directive()**
 - C) Blade::add()
 - D) Blade::registerDirective()
69. **What is Blade in Laravel?**
- A) A database management tool
 - B) **A templating engine**

- C) A routing system
 - D) A middleware package
70. **How do you define a Blade template file?**
- A) .php
 - B) .html
 - C) **.blade.php**
 - D) .tpl
71. **Which directive is used to extend a layout in Blade?**
- A) @include
 - B) @section
 - C) **@extends**
 - D) @layout
72. **How do you create a section in a Blade template?**
- A) @define
 - B) @block
 - C) **@section**
 - D) @content
73. **Which directive is used to display content from a section?**
- A) **@yield**
 - B) @content
 - C) @show
 - D) @render
74. **What is the purpose of the @include directive?**
- A) To add CSS styles
 - B) **To include another Blade template**
 - C) To define routes
 - D) To create a new section
75. **What symbol is used for Blade comments?**
- A) <!-- -->
 - B) **{{-- --}}**
 - C) /* */
 - D) //
76. **Which directive is used for conditionals in Blade?**
- A) **@if**
 - B) @when
 - C) @else
 - D) Both A and C
77. **How do you create a loop in Blade?**
- A) **@foreach**
 - B) @loop
 - C) @for
 - D) @each
78. **What is the primary purpose of migrations in Laravel?**
- A) To manage user authentication
 - B) **To define and version control the database schema**

- C) To create Eloquent models automatically
 - D) To handle file uploads
79. **In Laravel's Eloquent ORM, what does each model typically correspond to?**
- A) A database connection
 - B) A controller
 - C) **A database table**
 - D) A middleware
80. **Which of the following methods would you use to create a unique index on the email column in a migration?**
- A) `$table->index('email');`
 - B) `$table->primary('email');`
 - C) **`$table->unique('email');`**
 - D) `$table->foreign('email')->references('id')->on('users');`
81. **What is the primary purpose of using transactions in a database?**
- A) To improve query performance
 - B) **To ensure data integrity by executing a series of queries as a single unit**
 - C) To enable batch processing of large datasets
 - D) To manage database connections efficiently
82. **In Eloquent, which method is used to create a new model instance and immediately save it to the database?**
- A) `make()`
 - B) `new()`
 - C) **`create()`**
 - D) `save()`
83. **What does "ActiveRecord" mean in the context of Eloquent?**
- A) A database abstraction layer that provides multiple interfaces for different database types
 - B) **A pattern where each class represents both a table and an individual row, and can manage its own persistence**
 - C) A design where only table-wide operations are allowed but not on individual rows
 - D) A pattern where configuration is required for every table and model interaction
84. **Which of the following demonstrates Eloquent's focus on simplicity?**
- A) It allows for complex configurations of database models before they can be used
 - B) Each Eloquent model must be configured to specify the table it interacts with
 - C) **It follows a "convention over configuration" approach, requiring minimal code to create models**
 - D) Models must explicitly define all relationships with other models in the database
85. **What is the default behavior for table names in Laravel's Eloquent ORM?**
- A) Class names are kept the same as table names by default
 - B) Class names are converted to lowercase and singular for table names
 - C) **Class names are "snake-cased" and pluralized for table names**
 - D) Class names are automatically prefixed with "tbl_" for table names
86. **How can you modify the primary key of an Eloquent model?**
- A) **Set the `$primaryKey` property to the desired column name**
 - B) Change the `$table` property to match the new key name

- C) Use the public \$keyName property to define the primary key
 - D) Use public \$incrementing = true to modify the primary key
87. **How can you disable the automatic created_at and updated_at timestamps in Eloquent?**
- A) Set the \$dateFormat property to 'U'
 - B) Set the \$timestamps property to true
 - C) **Set the \$timestamps property to false**
 - D) Remove the timestamp columns from the database
88. **How do you retrieve all records from a table using Eloquent?**
- A) Contact::findAll()
 - B) Contact::fetch()
 - C) **Contact::all()**
 - D) Contact::retrieveAll()
89. **What is the purpose of the findOrFail() method in Eloquent?**
- A) It retrieves all records with a specific condition
 - B) It retrieves the first record that matches a condition and returns null if none found
 - C) **It retrieves a record by ID, throwing an exception if no matching record is found**
 - D) It retrieves multiple records by ID, returning an empty array if none are found
90. **What is the main difference between Eloquent's all() and get() methods?**
- A) all() retrieves filtered results, while get() retrieves all records
 - B) **get() allows query modifications, while all() does not**
 - C) all() is used for single record retrieval, while get() is used for multiple records
 - D) get() works only with relationships, while all() does not
91. **Which method is recommended for retrieving data when you want to modify a query?**
- A) first()
 - B) all()
 - C) **get()**
 - D) find()
92. **What is the purpose of the chunk() method in Laravel's Eloquent?**
- A) To lock records while processing a query
 - B) **To split a query into smaller batches for more efficient processing**
 - C) To retrieve a single large record from the database
 - D) To group records by a specific column before retrieving them
93. **When using Model::create() or Model::make() to insert data, what must be considered?**
- A) **All properties need to be approved for "mass assignment"**
 - B) You must always call save() after using create()
 - C) The model needs a custom primary key to work
 - D) Properties cannot be set manually
94. **Which of the following methods automatically saves an Eloquent instance to the database?**
- A) save()
 - B) make()
 - C) **create()**
 - D) new()

95. **What is the difference between make() and create() when inserting a record using Eloquent?**
- A) make() immediately saves the instance, while create() does not
 - B) **create() immediately saves the instance to the database, while make() does not**
 - C) Both make() and create() automatically save the instance to the database
 - D) Neither make() nor create() save the instance automatically
96. **What is one way to insert a new record using Eloquent?**
- A) Use DB::insert() and pass the data array
 - B) Create an instance of the Eloquent class, set properties, and call save()
 - C) **Call insert() directly on the table and pass the data object**
 - D) Use insert() inside a where() condition
97. **Which of the following aggregate functions can be used with Eloquent?**
- A) total(), count(), average()
 - B) **count(), sum(), avg()**
 - C) fetch(), find(), first()
 - D) group(), max(), min()
98. **What happens when you update an existing Eloquent record and call save()?**
- A) The created_at timestamp is updated to the current time
 - B) The id field is reset to a new value
 - C) **The updated_at timestamp is updated to the current time**
 - D) The updated_at and created_at fields remain unchanged
99. **Which method can be used to update multiple Eloquent records with a single query?**
- A) save()
 - B) insert()
 - C) **update()**
 - D) findOrFail()
100. **What is the purpose of Eloquent's "fillable" property?**
- A) To define which fields are automatically filled by the database
 - B) **To specify which fields can be mass-assigned through create() or update()**
 - C) To restrict fields from being displayed in query results
 - D) To specify which fields are encrypted in the database
101. **How can you define a relationship between two Eloquent models?**
- A) By using the relationship() method on the model
 - B) **By defining methods in the model for each relationship type**
 - C) By specifying the related model in the migration file
 - D) Relationships cannot be defined in Eloquent
102. **Which of the following describes a one-to-many relationship in Eloquent?**
- A) A single model can belong to multiple models
 - B) **A single model can have many related models**
 - C) A single model can only relate to a single instance of another model
 - D) A many-to-many relationship between two models
103. **What method is used to define a one-to-many relationship in an Eloquent model?**
- A) belongsToMany()
 - B) **hasMany()**

- C) belongsTo()
 - D) hasOne()
104. **What is the primary purpose of the with() method in Eloquent?**
- A) To retrieve records without applying any conditions
 - B) **To eager load relationships to avoid N+1 query problems**
 - C) To filter records based on specific criteria
 - D) To update related records in a single query
105. **How can you retrieve related models with Eloquent?**
- A) By calling the related model directly
 - B) By using the get() method on the related model
 - C) **By defining a relationship method in the parent model and calling it**
 - D) By creating a new instance of the related model
106. **In Eloquent, how can you retrieve the related model for a belongsTo relationship?**
- A) **By calling the relationship method directly on the model**
 - B) By using the get() method on the relationship
 - C) By accessing the parent model through the related model
 - D) By executing a separate query to find the related model
107. **Which method would you use to count the number of related models in a one-to-many relationship?**
- A) count()
 - B) **count() on the relationship method**
 - C) total()
 - D) sum()
108. **What method is used to define a many-to-many relationship in Eloquent?**
- A) belongsTo()
 - B) hasOne()
 - C) **belongsToMany()**
 - D) hasMany()
109. **What is the primary function of Laravel Mix?**
- A) Database Management
 - B) **Asset Compilation**
 - C) Authentication
 - D) Routing
110. **In which section would you find information about Frontend Presets?**
- A) Pagination
 - B) Running Mix
 - C) **Frontend Presets**
 - D) Testing
111. **What does Auth Scaffolding in Laravel Mix help with?**
- A) **Setting up authentication**
 - B) Compiling CSS
 - C) Creating database migrations
 - D) Paginating results
112. **Which command would you use to run Webpack/Mix once for development purposes?**

- A) npm run build
 - B) **npm run dev**
 - C) npm run start
 - D) npm run serve
113. What command do you run to install the required packages for a Laravel project using Mix?
- A) npm start
 - B) **npm install**
 - C) npm build
 - D) npm setup
114. Which of the following CSS preprocessors can Mix use?
- A) Sass and Java
 - B) **Sass, Less, and PostCSS**
 - C) CSS3 only
 - D) None of the above
115. What is the default frontend preset that comes with every new Laravel installation?
- A) React
 - B) Angular
 - C) **Vue**
 - D) Tailwind CSS
116. How can you access a specific named error bag in your view?
- A) Use \$errors->get('login')
 - B) **Use \$errors->login**
 - C) Use \$errors->bag('login')
 - D) Use \$errors->fetch('login')
117. Which method is used to assert that the session has errors in Laravel tests?
- A) \$this->assertSessionHasMessages()
 - B) **\$this->assertSessionHasErrors(\$bindings = [])**
 - C) \$this->checkSessionErrors()
 - D) \$this->assertHasErrorsInSession()
118. What is the simplest way to test localization in a Laravel application?
- A) Use PHPUnit assertions only
 - B) Directly manipulate the locale setting
 - C) **Set the appropriate context and visit the page using get()**
 - D) Check the database for localized strings
- 119. Chapter 7**
120. What is the primary tool for accessing user data in Laravel?
- A) Global variables
 - B) **Illuminate\Http\Request object**
 - C) Session variables
 - D) Database queries
121. What types of data sources are commonly handled by Laravel applications?
- A) Static content only
 - B) **Complex data sources including user input**

- C) Only data from APIs
 - D) Only data from databases
122. How are segments in a URL indexed when using the `$request->segment($segmentId)` method?
- A) Zero-based index
 - B) **One-based index**
 - C) Random index
 - D) Negative index
123. Where is the newly created form request class typically located?
- A) `app/Http/Controllers/`
 - B) `app/Http/Models/`
 - C) **`app/Http/Requests/`**
 - D) `app/Http/Middleware/`
124. What is the required method that a form request class must implement?
- A) `validate()`
 - B) **`rules()`**
 - C) `authorize()`
 - D) `handle()`
125. What could potentially happen if you don't use mass assignment protection?
- A) Data will not be saved in the database
 - B) **Users could modify fields they shouldn't access, like `author_id`**
 - C) The application will automatically log the user out
 - D) The model will not be created
126. What does the `{!! $stuffToEcho !!}` syntax do in Laravel?
- A) It escapes the output
 - B) It formats the output as JSON
 - C) **It displays raw, unescaped content**
 - D) It generates a URL
127. What should happen if user input is invalid during testing?
- A) The input should be stored in the database
 - B) **The user should be redirected**
 - C) The application should crash
 - D) The user should be logged out
- 128. Chapter 8**
129. What is Artisan in Laravel?
- A) A templating engine
 - B) **A suite of built-in command-line actions**
 - C) A database management tool
 - D) A front-end framework
130. How do you execute an Artisan command in a Laravel application?
- A) `artisan run` command
 - B) **`php artisan` command**
 - C) `laravel` command
 - D) `run artisan` command
131. What is Tinker in Laravel?
- A) A web server

- B) A database migration tool
 - C) **A REPL or interactive shell for your application**
 - D) A routing component
132. Artisan is built on top of which Symfony component?
- A) Symfony Routing
 - B) Symfony Database
 - C) **Symfony Console**
 - D) Symfony Event Dispatcher
133. What does the clear-compiled command do in Laravel?
- A) Starts a new server
 - B) **Removes Laravel's compiled class file**
 - C) Runs database migrations
 - D) Displays the current environment
134. How do you get help for a specific Artisan command?
- A) php artisan --help commandName
 - B) **php artisan help commandName**
 - C) artisan help commandName
 - D) php help commandName
135. What does the serve command do in Laravel?
- A) Displays the current environment
 - B) **Starts a PHP server at localhost:8000**
 - C) Clears and refreshes configuration files
 - D) Runs all database migrations
136. How can you specify which environment an Artisan command should operate in?
- A) --environment
 - B) --mode
 - C) **--env**
 - D) --app
137. Which option would you use to increase the verbosity of output for an Artisan command?
- A) -quiet
 - B) --verbose
 - C) **-v, -vv, and -vvv**
 - D) --debug
138. Laravel is __
- a. Javascript library
 - b. PHP library
 - c. **PHP framework**
 - d. Javascript framework
139. Webpack is __
- a. **Javascript tool**
 - b. PHP tool
 - c. Bootstrap library
140. Which is similar to Webpack?
- a. **Mix**

- b. Gulp
 - c. Grunt
141. HRM full form is ____
- a. Hot Module Replacement**
 - b. Hot Model Replacement
 - c. High Module Replace
 - d. High Model Replacement
142. Which is default js() call handles in Mix?
- a. React
 - b. Js
 - c. Vue**
 - d. Bootstrap
143. Short form of Hot Loading is ____
- a. HAM
 - b. HMR**
 - c. HRM
 - d. HEM
144. Which is allow to define multiple language?
- a. Translationize
 - b. Localization**
 - c. Multipliers
 - d. Applications
145. Which is a layer in front of Webpack?
- a. Vue
 - a. React
 - c. Mix**
 - d. Gulp
146. By which method we test localization?
- a. Get()**
 - b. Post()
 - c. Put()
 - d. Patch()
147. Which is the global helper function?
- a. Str::plural()**
 - b. Str_plural()
 - c. Str_is()
 - d. Str_slug()
148. What is the primary purpose of Laravel Mix in frontend development?
- a. To handle backend routing
 - b. To compile and optimize assets**
 - c. To manage database migrations
 - d. To create RESTful APIs
149. Which command is used to install Laravel Mix in a Laravel project?
- a. npm install laravel-mix**
 - b. composer require laravel-mix

- c. npm install
 - d. mix install
150. Which of the following file types can Laravel Mix compile?
- a. Only JavaScript
 - b. JavaScript, CSS, and SASS**
 - c. Only CSS
 - d. Only HTML
151. In which file do you typically define your asset compilation settings when using Laravel Mix?
- a. webpack.config.js
 - b. package.json
 - c. webpack.mix.js**
 - d. app.js
152. What command do you run to compile your assets for production in Laravel Mix?
- a. npm run dev
 - b. npm run prod**
 - c. npm compile
 - d. npm run build
153. What is the primary purpose of Laravel Collections?
- a. To manage database migrations
 - b. To provide a fluent interface for working with arrays**
 - c. To create RESTful APIs
 - d. To handle user authentication
154. Which method would you use to create a new collection from an array in Laravel?
- a. Collection::make()
 - b. collect()**
 - c. array_to_collection()
 - d. new Collection()
155. Which of the following methods can be used to filter a collection?
- a. map()
 - b. filter()**
 - c. each()
 - d. reduce()
156. How can you retrieve the first element of a collection?
- a. first()**
 - b. head()**
 - c. findFirst()
 - d. Both A and B
157. What method would you use to sort a collection by a specific key?
- a. sort()
 - b. sortBy()**
 - c. orderBy()
 - d. groupBy()
158. Which of the following is NOT a valid method for transforming each item in a collection?
- a. map()

- b. filter()
 - c. reduce()**
 - d. transform()
159. How can you convert a collection back to an array?
- a. toArray()**
 - b. asArray()
 - c. array()
 - d. convertToArray()
160. Which method allows you to group a collection by a specific key?
- a. partition()
 - b. groupBy()**
 - c. splitBy()
 - d. indexBy()
161. In the context of handling user data, which Eloquent method retrieves all records from a model?
- a. findAll()
 - b. getAll()
 - c. all()**
 - d. retrieve()
162. What is the primary purpose of Laravel's validation rules?
- a. To encrypt user data
 - b. To ensure user inputs meet certain criteria before being processed**
 - c. To create database migrations
 - d. To handle user sessions
163. Which of the following is a primary role of frontend components in Laravel?
- a. Managing database migrations
 - b. Handling HTTP requests
 - c. Rendering views and managing user interactions**
 - d. Performing background jobs
164. What templating engine does Laravel use by default?
- a. Twig
 - b. Blade**
 - c. Smarty
 - d. Mustache
165. Which directive is used in Blade to create a section that can be defined in child templates?
- a. @extends
 - b. @section**
 - c. @include
 - d. @yield
166. In Laravel, which method is used to include a partial view in a Blade file?
- a. @section
 - b. @include**
 - c. @extends
 - d. @yield

167. Which of the following is a benefit of using Vue.js with Laravel?
- a. Improved database performance
 - b. Simplified routing
 - c. Reactive components for user interfaces**
 - d. Enhanced security
168. What is the purpose of Laravel Mix?
- a. To create APIs
 - b. To manage CSS and JavaScript assets**
 - c. To handle database queries
 - d. To build RESTful services
169. Which command is used to compile assets with Laravel Mix?
- a. php artisan serve
 - b. npm run dev**
 - c. php artisan migrate
 - d. npm install
170. How can you pass data from a controller to a Blade view?
- a. Using sessions
 - b. By returning a view with an array of data**
 - c. Using global variables
 - d. By using cookies
171. What is the purpose of the @csrf directive in Blade?
- a. To enable caching
 - b. To prevent XSS attacks
 - c. To protect against CSRF attacks**
 - d. To manage sessions
172. Which HTML attribute is commonly used to bind Vue.js data in a Laravel Blade file?
- a. v-bind**
 - b. data-bind
 - c. ng-bind
 - d. bind
173. What method is typically used in a controller to validate incoming request data?
- a. validateRequest()
 - b. validate()**
 - c. request()->validate()
 - d. request()->check()
174. Which validation rule is used to ensure a field is required?
- a. required_if
 - b. required**
 - c. present
 - d. filled
175. What feature in Laravel can be used to handle form submissions and validation in a clean way?
- a. Middleware
 - b. Models

c. Controllers

d. Requests

176. Which method is used to create a new user in a controller after validating the data?
- a. User::create()**
 - b. User::store()
 - c. User::add()
 - d. User::new()
177. What class is used for form requests in Laravel?
- a. FormRequest**
 - b. RequestValidator
 - c. InputRequest
 - d. ValidateRequest
178. How do you retrieve old input data after a validation error?
- a. session('input_name')
 - b. old('input_name')**
 - c. request('input_name')
 - d. input('input_name')
179. What is the purpose of the store() method in resource controllers?
- a. To retrieve a resource
 - b. To show a form for creating a new resource
 - c. To save a new resource to the database**
 - d. To delete a resource
180. Which of the following is a common way to display validation errors in a Blade view?
- a. \$errors->first('field_name')**
 - b. \$errors->get('field_name')
 - c. \$errors->has('field_name')
 - d. \$errors->show('field_name')
181. What method can be used to redirect back with input and error messages after a validation failure?
- a. redirect()->back()**
 - b. back()->withInput()
 - c. redirect()->withErrors()
 - d. All of the above
182. Which method is used to validate multiple inputs at once in Laravel?
- a. validateMultiple()
 - b. validateAll()
 - c. validate()**
 - d. validateRequest()
183. What is the command to create a new Artisan command?
- a. php artisan make**
 - b. php artisan create
 - c. php artisan new
 - d. php artisan command

184. Which command is used to run the database migrations in Laravel?
- a. **php artisan migrate**
 - b. php artisan migrate
 - c. php artisan db
 - d. php artisan migrate
185. What is Laravel Tinker primarily used for?
- a. To compile assets
 - b. To manage migrations
 - c. **To interact with the application via a command line interface**
 - d. To run background jobs
186. Which command starts the Tinker REPL (Read-Eval-Print Loop)?
- a. **php artisan tinker**
 - b. php artisan start tinker
 - c. php artisan start
 - d. php tinker
187. In Tinker, how would you create a new user instance without saving it to the database?
- a. User::new()
 - b. User::create()
 - c. **new User()**
 - d. User::init()
188. What command will show the list of all available Artisan commands?
- a. php artisan commands
 - b. **php artisan list**
 - c. php artisan show
 - d. php artisan help
189. Which of the following can be used in Tinker to test your models and queries?
- a. Simple echo statements
 - b. **Directly calling model methods**
 - c. Running migrations
 - d. None of the above
190. How can you access your application's configuration values in Tinker?
- a. **config('app.name')**
 - b. app('config.name')
 - c. getConfig('app.name')
 - d. configValue('app.name')
191. What is the purpose of the php artisan make command?
- a. To create a new database
 - b. **To create a new migration file for schema changes**
 - c. To run migrations
 - d. To roll back migrations
192. How can you roll back the last batch of migrations in Laravel?
- a. php artisan migrate
 - b. php artisan migrate
 - c. php artisan migrate
 - d. **php artisan migrate**

