



Comment	Description	Footprint	Quantity
BatteryHolder		Battery Holder CR1220-SMD	1
470uF	Polar Capacitor	cap 03	2
100nF	Bipolar Capacitor	SMD_CAP_0805	9
10UF	Bipolar Capacitor	SMD_CAP_0805	2
18pF	Bipolar Capacitor	SMD_CAP_1206	2
·	·	DO-214AC (SMD	
Diodes		Diode)	1
header 27		PCBComponent_1	2
LED RGB	LED 5050 RGB	LED_5050	1
LCD-CH	D1 1/1 1 15D	LCD2-16	1
LED	[NoValue], LED Red	LED0805	9
Screw	Board Screw With Spacer	Board Screw_No Silk	4
NRF24L01+_Modu	эрассі	NRF24L01+_Modu	
le		le	1
programming socket	Header, 6-Pin	HDR1X6	1
jumper	Header, 2-Pin	HDR1X2	4
MCP2551	CAN TRANSCEIVERS	MCP2551	1
0 1		DI 0 1 0D:	
can Connector		PH Connector 2Pin RES 0805	1
330	Resistor	(2012X06L)	4
ArrayResistor9pin		ArrayRes9	1
		RES 0805	
1K	Resistor	(2012X06L) RES 0805	1
120	Resistor	(2012X06L)	2
		RES 0805	
4.7K	Resistor	(2012X06L)	2
	WS-DITV 2.54 mm compact THT with		
=partNo	flat actuator	418117170901	1
Constants DD	Push Button	CW DD	F
Switch PB	Switch	SW-PB	5
usart connector		SerialWireMini	1
LD1117	ARM Cortex-M3 32-	TO-252-reg	1
STM32F103RBT6	bit MCU	STM-LQFP64_N	1
AT24C08BN	Serial EEPROM	8S1_N	1
LM35		LM35	1
	Very low		
USBLC6-2	capacitance ESD protection;	USBLC6-2	1
USB OTG	protection,	USB_Micro	1
10K	Variable Resistor	Pot 00	2
8MHz	XTAL Crystal	XTAL Small	1
11.0592 MHz	XTAL Crystal	XTAL RTC	1