



# HIGH-PERFORMANCE PNEUMATIC POLISHER

**ALPHA®**  
AIR-680

AIR-680



\*No-load 4,000 RPMs

*The Best even got Better with...*

## • OIL PORT

Easy access to execute daily maintenance

## • ENHANCED SPINDLE

Taller wrench slot for easy tool removal with standard spanner (included)

## • 15' FLEXZILLA® AIR AND WATER HOSES

Extreme all weather flexibility (-40° to +140° F)

Specifications:	Equipment Included:
Air Pressure..... 85 PSI Air	• Air Lead Hose - (15ft. / 4.5m)
Consumption..... 15CFM	• Water Hose - (15ft. / 4.5m)
Speed (no load)..... 4,000 RPM	• Side Handle (reversible)
Weight..... 2.64lbs/1.2kg	• Double End Wrench (19mm / 22mm)
Air Inlet..... 1/4" BSPP	• Rust Inhibitor Oil (8oz / 237ml) (AIR-008)
Water Inlet..... 1/8" BSPP	• Screw (w/ O-Ring Seal for Oil Port)
Spindle..... 5/8"-11	• Exhaust Hose with Clamp

PART NO.	DESCRIPTION
AIR-680	Air Polisher
AIR-008	Rust Inhibitor Oil for Pneumatic Tools (8oz / 237ml)

 **Alpha Professional Tools®**

103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114

www.alpha-tools.com

Copyright © 2015 Alpha Professional Tools. All rights reserved.

FL2204-3/15