Material Safety DATA SHEET

DOCUMENT NO.: 517 | DATE PUBLISHED: 05/31/15



For chemical emergency spill, leak, fire, exposure or accident call (CHEMTREC) 800-424-9300. This MSDS complies with 29 CFR 1919.1200 (The Osha Hazard Communication Standard).

Section 1: Identification

Product / Chemical Name: Lubricating Grease

Product Identification No: GLA, NLGI #0 GLB, NLGI #1 GLC, NLGI #2

Chemical Family: N/A **Trade Name and Synonyms:**

High Temperature MP Synthetic Lithium Complex Grease

Molecualar Weight: N/A Chemical Name: N/A Chemical Formula: N/A Material Use: N/A **Distributor Name:** Alpha Professional Tools*

Address:

103 Bauer Drive, Oakland, NJ 07436

Emergency Tel. No.: 800-648-7229

Section 2: Hazard(s) Identification

POTENTIAL HEALTH EFFECTS: Minor eye, inhalation and skin irritant.

*See Section 11 for toxicological information.

Section 3: Composition/Information on Ingredients

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200) This product is not formulated to contain ingredients that have exposure limits exceeding those established by US agencies.

NFPA & HMIS Rating

Red Flammability: 1 Yellow Reactivity: 0 Blue Health: 2 White Special: N/A

*See Section 8 for exposure limits.

Section 4: First-Aid Measures

EYE: Flush with water for 15-20 minutes. Seek medical attention if irritation develops.

SKIN: Wash immediately with soap and water. Remove contaminated clothing and launder before reuse. Discard shoes and leather articles saturated with the product. Obtain medical advice if irritation occurs.

INHALATION: Remove exposed person to fresh air. If breathing is labored give oxygen. If breathing has stopped apply artificial respiration. Get immediate medical attention.

INGESTION: DO NOT INDUCE VOMITING. If conscious, give 2 glasses of water. If vomiting does occur, keep head below hips to reduce risk of aspiration. Get immediate medical attention.

Section 5: Fire-Fighting Measures

Flash Point: 450F(232C) Method: COC ASTM D-92 LFL/UFL: Not Determined

Auto-ignition Temperature: Not Determined

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, and alcohol foam.

FIREFIGHTING EQUIPMENT: Full bunker gear recommended including a positive pressure self-contained

breathing apparatus.

Section 6: Accidental Release Measures

Isolate spill area. Provide adequate ventilation. Wear appropriate personal protection. Recover free product for recycle and/ or disposal. Add sand, earth or other suitable absorbent to spill area. Prevent entry into sewers and waterways. Check under Transportation and Labeling (DOT/CERCLA) and Other Regulator Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spill.

Section 7: Handling and Storage

HANDLING: Keep containers closed. Avoid contact with eyes, skin or clothing. Wash hands after handling. Empty container may retain product residue which may exhibit hazards of product.

STORAGE: Keep away from heat or flame.

Section 8: Exposure Controls/Personal Protection

VENTILATION: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY: Use a NIOSH approved respirator when

necessary.

SKIN: Use Viton or Nitrile gloves to avoid prolonged or repeated skin contact.

EYE: Use splash goggles or face shield where splashing is expected or can occur.

EXPOSURE LIMITS: The Threshold Limit Value (TLV) of 5 mg/m3 is suggested for oil mist.

Section 9: Physical and Chemical Properties

Physical State: Semi-Solid Boiling Point: 600F(316C) Melting Point: 500F(260C)

Vapor Pressure: Not Determined Vapor Density (Air=1): Negligible Evaporation Rate: Not Determined Solubility in Water: Negligible Specific Gravity (Water=1): 0.8900 Volatility (Volume): Negligible

VOC: Unknown

pH: Essentially Neutral **Odor:** Mild, Bland Odor

Odor Threshold: Not Determined **Appearance:** Red Semi-Solid

Viscosity, cSt @ 100C: GLA, NLGI #0: 13 GLB, NLGI #1: 14

GLC, NLGI #2: 18

Viscosity, cSt @ 40C: GLA, NLGI #0: 110 GLB, NLGI #1: 110 GLC, NLGI #2: 155

Section 10: Stability and Reactivity

STABILITY: Stable under moderately elevated temperatures and pressures.

INCOMPATIBILITY: Avoid contact with strong oxidants.

HAZARDOUS POLYMERIZATION: Will not occur. **HAZARDOUS DECOMPOSITION OF PRODUCT:** Toxic oxides of carbon, aldehydes

Section 11: Toxicological Information

ACUTE EXPOSURE

Eye Irritation: Moderate to strong eye irritation. Based on data from components or similar material.

Skin Irritation: Not expected to be a primary skin irritant. Based on data from components or similar material. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, defatting, and cracking of the skin.

Respiratory Irritation: If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practices where all exposure limits are observed, respiratory irritation should not be a problem.

CHRONIC EXPOSURE

Chronic Toxicity: No data available to indicate product present at greater than 1.0% are chronic health hazards. **Carcinogenicity:** No data available to indicate product present at greater than 0.1% are a carcinogenic hazard. **Mutagenicity:** No data available to indicate product present at greater than 1.0% present a mutagenic or genotoxic hazard.

Reproductive Toxicity: No data available to indicate product present at greater than 1.0% present a reproductive hazard.

Teratogenicity: No data available to indicate product present at greater than 1.0% present a teratogenic hazards.

ADDITIONAL INFORMATION

Exposure Limits: Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter.

Section 12: Ecological Information (non-mandatory)

No data available on the adverse effects of this product on the environment.

Section 13: Disposal Considerations (non-mandatory)

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Section 14: Transport Information (non-mandatory)

This product is not classified as hazardous material for DOT shipping. For further information relative to spills resulting from transportation incidents, refer to the latest DOT Emergency Response Guidebook for Hazardous Materials.

Section 15: Regulatory Information (non-mandatory)

U.S. Federal Regulations OSHA Table Z: Synthetic Base Stock (mist)

TSCA: All components of this material are listed on the U.S. TSCA Inventory. **CERCLA 40 CFR 302.4:** Zinc and Compounds@ 0-2%, Statutory RQ 1 lb

SARA Title III

Section 302 Extremely Hazardous: Not Applicable

Section 311/312

Fire Hazard: Yes

Reactive Hazard: No

Release of Pressure: No

Acute Health Hazard: Yes

Chronic Health Hazard: No

Section 313

Toxic Chemical: Not Applicable

U.S. State Regulations California (Prop 65)

Does not contain chemicals known to the state of California to cause cancer.

International Regulations **WHMIS:** All components listed

Section 16: Other Information

The information and recommendations contained herein are, to the best of AMSOIL's knowledge and belief, accurate and reliable as of the date issued. AMSOIL makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and AMSOIL shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with AMSOIL's interpretation of the available data.

Update history:

Date of issue: 17th October, 2005 Date Revised: 9th February, 2012