

HOT-ROD





Marble

Granite

Alpha® developed a revolutionary way to improve the efficiency of fabricators. For years, slab fabricators have employed labor-intensive procedures for creating channels in the underside of countertops to accommodate stainless steel reinforcing rods at sink and cooktop cutouts. Alpha® recognized the opportunity for improvement and developed the Alpha® Hot-Rod. With this blade attached to the Alpha® AWS-110 or AWS-125 Wet Stone Cutter, a fabricator can accomplish the task in one easy pass.

The **Hot-Rod for Granite** blades were created with diamond grits and matrix best suited for all categories of granite, including hard red granites, to assure a long cutting life. With a 3" diameter, the blade allows for easy use and better leverage when cutting 1/4" deep channels, by allowing for better positioning of the stone cutter's handle. This blade is now available in three thicknesses: 1/4" for standard rods, 1/8" for thinner rods and 3/8" for threaded rods.

The **Hot-Rod for Marble** applies the same technology but is designed for softer stones such as marble. This blade is available in 1/4" for standard and 1/8" for thinner rods.

For efficient creation of channels for reinforcing rods, attach this unique blade to our AWS-110 or AWS-125 for a smooth, dust-free operation. Used in this manner, productivity will increase significantly. Although Alpha® recommends wet cutting, these blades may be used wet or dry.

PART NO.	SIZE	MAXIMUM RPM	ARBOR(S)	RECOMMENDED FOR	FOR USE ON
HR03A+	3"	14,500	7/8", 20mm	1/4" Rod	GRANITE
HT03A+	3"	14,500	7/8", 20mm	1/8" Rod	GRANITE
HW03A+	3"	14,500	7/8", 20mm	3/8" Threaded Rod	GRANITE
HM03A+	3"	14,500	7/8", 20mm	1/4" Rod	MARBLE
HS03A+	3"	14,500	7/8", 20mm	1/8" Rod	MARBLE

