MINISTRY OF EDUCATION, CULTURE AND RESEARCH
OF THE REPUBLIC OF MOLDOVA
Technical University of Moldova
Faculty of Computers, Informatics and Microelectronics
Department of Software Engineering and Automation

Report

on laboratory work no. 1

of Techniques and Mechanisms of Software Design

Topic: Creational Design Patterns (Singleton, Builder, Factory Method)

Done by: st. gr. FAF-243, Augustin Carazanu
Checked by: *assist. univ. Daniel Istrati*
FCIM, UTM

Chișinău – 2026

1. Objectives

- Study the creational design patterns: Singleton, Builder, Prototype, Object Pool, Factory Method and Abstract Factory.
- Implement three of them in one Swift project: Singleton, Builder and Factory Method.
- Show with a demo program and unit tests what problem each pattern solves, and know the purpose and structure of the other three.

2. Theoretical background

Design patterns are reusable solutions to problems that keep appearing in object-oriented design. They were catalogued by Gamma, Helm, Johnson and Vlissides (the “Gang of Four”, 1994) and divided into creational, structural and behavioral patterns.

Creational patterns deal with how objects are created. Instead of calling an initializer directly everywhere, the creation logic is placed behind a dedicated class, method or interface. This hides which concrete class is used, controls how many instances exist and how they are assembled, and keeps client code independent of these decisions.

Pattern	Intent	Typical use
Singleton	Ensure a class has exactly one instance and give a global access point to it.	Shared counters, configuration, logger, cache.
Builder	Construct a complex object step by step; the same process can create different representations.	Objects with many optional parts, immutable results, validation before creation.
Prototype	Create new objects by copying an existing, configured instance.	Expensive setup, many similar objects, runtime-defined templates.
Object Pool	Reuse a fixed set of expensive objects instead of creating and destroying them.	Database connections, threads, network sockets.
Factory Method	Define a method for creating an object, but let subclasses (conforming types) decide which class to instantiate.	A framework that knows when to create, but not what exactly.
Abstract Factory	Provide an interface for creating families of related objects without naming their concrete classes.	UI themes, cross-platform widgets, product families.

Table 1 — Creational design patterns

This laboratory work implements Singleton, Builder and Factory Method. Prototype, Object Pool and Abstract Factory are explained with short Swift examples in section 5.

3. Implementation

The project continues the online bookstore domain from the previous laboratory work. It is a Swift Package with three targets: CreationalCore (library with the patterns), CreationalDemo (executable that shows them working together) and CreationalTests (XCTest unit tests). The three

patterns cooperate: the Builder creates orders and takes their numbers from the Singleton, and the Factory Method chooses how those orders are delivered.

```
import Foundation

/// A book sold by the online bookstore (the same domain as Lab 0).
public struct Book: Equatable {
    public let title: String
    public let author: String
    public let price: Double

    public init(title: String, author: String, price: Double) {
        self.title = title
        self.author = author
        self.price = price
    }
}

/// Formats an amount as "123.45 MDL".
public func money(_ amount: Double) -> String {
    String(format: "%.2f MDL", amount)
}
```

Listing 1 — Shared model (Models.swift)

3.1 Singleton — OrderNumberGenerator

Problem

Every order needs a unique number. If the checkout screen and the admin panel each created their own generator, both counters would start at 1001 and the shop would issue duplicate order numbers. The generator must exist exactly once and be reachable from every part of the application.

Solution

OrderNumberGenerator exposes its only instance through static let shared. In Swift a static stored property is initialized lazily, once and thread-safely, so no double-checked locking is required. The initializer is private, which makes OrderNumberGenerator() a compile-time error outside the class. Because next() can be called from several threads at the same time, the counter is protected with an NSLock.

```
import Foundation

// SINGLETON
//
// Every order in the shop needs a unique number (BK-1001, BK-1002, ...).
// If the checkout screen and the admin panel each created their own
// generator, both would start at 1001 and hand out duplicate numbers.
// The generator must therefore exist exactly once, and everyone must use
// that single instance.
//
// How Swift guarantees it:
//   - `static let shared` is created lazily, exactly once, and thread-safely
//     (the runtime wraps it in dispatch_once).
//   - `private init()` stops any other code from writing
```

```
//     `OrderNumberGenerator()`, so a second instance cannot exist.
//   - The NSLock makes `next()` safe when called from many threads at once.

public final class OrderNumberGenerator {

    /// The one and only instance.
    public static let shared = OrderNumberGenerator()

    public let prefix = "BK"
    private var lastNumber = 1000
    private let lock = NSLock()

    /// Private: `OrderNumberGenerator()` does not compile outside this class.
    private init() {}

    /// Returns the next unique order number, e.g. "BK-1001".
    public func next() -> String {
        lock.lock()
        defer { lock.unlock() }
        lastNumber += 1
        return "\(prefix)-\(lastNumber)"
    }
}
```

Listing 2 — Singleton (OrderNumberGenerator.swift)

Drawback: a Singleton is global state. Code that uses OrderNumberGenerator.shared directly is harder to test in isolation, so in larger systems the instance is usually injected through a protocol (the Dependency Inversion Principle from the previous laboratory work).

3.2 Builder — OrderBuilder and OrderDirector

Problem

An order has two required parts (customer and books) and many optional ones: shipping address, gift wrapping, gift message, coupon and notes. A single initializer would require eight arguments, most of them nil or false (the “telescoping constructor” problem). It would also allow invalid combinations, such as a gift message on an order that is not gift-wrapped.

Solution

Order is an immutable struct whose initializer is internal to the module, so client code can only obtain an order through OrderBuilder. The builder collects parts through a fluent interface (every method returns the builder, so calls are chained) and build() validates the combination before creating the order. It throws a typed OrderBuildError for a missing customer, an empty cart or a gift message without wrapping. The order number is taken from the Singleton, so failed builds do not consume numbers.

```
// BUILDER — the product
//
// An order has two required parts (customer, books) and many optional ones
// (shipping address, gift wrap, gift message, coupon, notes). Creating it
// with one initializer would mean a "telescoping" call with eight arguments,
```

```
// most of them nil/false:
//
//   Order(number: "BK-1", customerEmail: "a@b.md", items: [book],
//         shippingAddress: nil, isGiftWrapped: false, giftMessage: nil,
//         couponCode: nil, notes: [])
//
// The initializer is therefore internal: outside this module an Order can
// only be created through OrderBuilder, which also validates it.
// All properties are `let`, so a finished Order is immutable.

public struct Order {
    public let number: String
    public let customerEmail: String
    public let items: [Book]
    public let shippingAddress: String?      // nil = pickup in store
    public let isGiftWrapped: Bool
    public let giftMessage: String?
    public let couponCode: String?
    public let notes: [String]

    public var subtotal: Double { items.reduce(0) { $0 + $1.price } }
    public var discount: Double { couponCode == "FAF10" ? subtotal * 0.10 : 0 }
    public var giftWrapFee: Double { isGiftWrapped ? 25 : 0 }
    public var total: Double { subtotal - discount + giftWrapFee }

    public var summary: String {
        var lines = ["Order \(number) for \(customerEmail)"]
        lines.append("  Items: " + items.map(\.title).joined(separator: ", "))
        lines.append("  Delivery: " + (shippingAddress ?? "pickup in store"))
        if isGiftWrapped {
            lines.append("  Gift wrap: yes" + (giftMessage.map { " (\"\($0)\")" } ?? ""))
        }
        if let couponCode {
            lines.append("  Coupon: \(couponCode)")
        }
        for note in notes {
            lines.append("  Note: \(note)")
        }
        lines.append("  Subtotal \(money(subtotal)), discount \(money(discount)), "
                     + "gift wrap \(money(giftWrapFee)) -> total \(money(total))")
        return lines.joined(separator: "\n")
    }
}
```

Listing 3 — The product (Order.swift)

```
// BUILDER — the builder and the director
//
// OrderBuilder collects the parts of an order step by step through a fluent
// interface (every method returns the builder, so calls can be chained).
// `build()` checks that the combination is valid and only then creates the
// immutable Order, taking its number from the Singleton generator.

public enum OrderBuildError: Error, Equatable, CustomStringConvertible {
    case missingCustomer
    case emptyCart
    case giftMessageWithoutWrap

    public var description: String {
        switch self {
```

```
        case .missingCustomer:        return "customer email is missing or invalid"
        case .emptyCart:              return "the cart is empty"
        case .giftMessageWithoutWrap: return "a gift message requires gift wrapping"
        }
    }
}

public final class OrderBuilder {
    private var customerEmail: String?
    private var items: [Book] = []
    private var shippingAddress: String?
    private var isGiftWrapped = false
    private var giftMessage: String?
    private var couponCode: String?
    private var notes: [String] = []

    public init() {}

    @discardableResult
    public func customer(_ email: String) -> OrderBuilder {
        customerEmail = email
        return self
    }

    @discardableResult
    public func add(_ book: Book, quantity: Int = 1) -> OrderBuilder {
        items += Array(repeating: book, count: quantity)
        return self
    }

    @discardableResult
    public func shipTo(_ address: String) -> OrderBuilder {
        shippingAddress = address
        return self
    }

    @discardableResult
    public func giftWrap() -> OrderBuilder {
        isGiftWrapped = true
        return self
    }

    @discardableResult
    public func giftMessage(_ message: String) -> OrderBuilder {
        giftMessage = message
        return self
    }

    @discardableResult
    public func coupon(_ code: String) -> OrderBuilder {
        couponCode = code
        return self
    }

    @discardableResult
    public func note(_ text: String) -> OrderBuilder {
        notes.append(text)
        return self
    }
```

```
    /// Validates the collected parts and creates the final, immutable Order.
    public func build() throws -> Order {
        guard let email = customerEmail, email.contains("@") else {
            throw OrderBuildError.missingCustomer
        }
        guard !items.isEmpty else {
            throw OrderBuildError.emptyCart
        }
        if giftMessage != nil && !isGiftWrapped {
            throw OrderBuildError.giftMessageWithoutWrap
        }
        return Order(number: OrderNumberGenerator.shared.next(),
                     customerEmail: email,
                     items: items,
                     shippingAddress: shippingAddress,
                     isGiftWrapped: isGiftWrapped,
                     giftMessage: giftMessage,
                     couponCode: couponCode,
                     notes: notes)
    }
}

/// Director: knows the steps for common order types, so client code does
/// not repeat the same chain of builder calls.
public struct OrderDirector {
    public init() {}

    public func birthdayGift(for email: String, book: Book,
                             address: String, message: String) throws -> Order {
        try OrderBuilder()
            .customer(email)
            .add(book)
            .shipTo(address)
            .giftWrap()
            .giftMessage(message)
            .note("Deliver before the weekend")
            .build()
    }

    public func studentPickup(for email: String, books: [Book]) throws -> Order {
        let builder = OrderBuilder()
            .customer(email)
            .coupon("FAF10")
            .note("Pickup at FCIM, UTM")
        for book in books {
            builder.add(book)
        }
        return try builder.build()
    }
}
```

Listing 4 — Builder and Director (OrderBuilder.swift)

OrderDirector plays the Director role from the GoF structure. It stores the sequence of builder steps for common order types (a birthday gift, a student pickup with the FAF10 coupon), so client code does not repeat the same chain of calls.

3.3 Factory Method — DeliveryService

Problem

An order can be delivered by courier, by national post or picked up in the store. The dispatch logic (compute the cost, build the tracking code, produce a message) is the same for all of them. If it contained a switch over the delivery type, every new carrier would require editing and re-testing that code.

Solution

Shipment is the product interface, with CourierShipment, PostShipment and StorePickup as concrete products. DeliveryService is the creator: its dispatch(_:) method contains the shared algorithm but calls the factory method makeShipment() to obtain the product. Each concrete creator (CourierDeliveryService, PostDeliveryService, StorePickupService) implements makeShipment() and decides which shipment to create. In Swift the abstract creator is a protocol, and the shared logic lives in a protocol extension instead of an abstract base class.

```
// FACTORY METHOD — the products
//
// Every way of delivering an order is a Shipment. The rest of the code only
// talks to this protocol, never to the concrete types.

public protocol Shipment {
    var carrier: String { get }
    var estimate: String { get }
    var trackingPrefix: String { get }
    func cost(for order: Order) -> Double
}

/// Courier in Chișinău: 50 MDL, free for orders of 800 MDL or more.
public struct CourierShipment: Shipment {
    public let carrier = "Courier"
    public let estimate = "next day"
    public let trackingPrefix = "CR"
    public init() {}
    public func cost(for order: Order) -> Double { order.subtotal >= 800 ? 0 : 50 }
}

/// National post: flat 35 MDL, slower.
public struct PostShipment: Shipment {
    public let carrier = "Poșta Moldovei"
    public let estimate = "3-5 days"
    public let trackingPrefix = "PM"
    public init() {}
    public func cost(for order: Order) -> Double { 35 }
}

/// The customer picks the order up from the shop.
public struct StorePickup: Shipment {
    public let carrier = "Store pickup"
    public let estimate = "ready in 2 hours"
    public let trackingPrefix = "PU"
    public init() {}
    public func cost(for order: Order) -> Double { 0 }
}
```

Listing 5 — Products (Shipment.swift)

```
// FACTORY METHOD — the creators
//
// DeliveryService (the creator) contains the shared dispatch logic, but it
// does not decide WHICH shipment to create. That decision is delegated to
// the factory method `makeShipment()`, which every concrete service
// implements. In Swift the "abstract creator" is a protocol and the shared
// logic lives in a protocol extension.
//
// Adding a new carrier = one new Shipment + one new service.
// `dispatch(_:)` is never edited (Open/Closed Principle from Lab 0).

public protocol DeliveryService {
    /// The factory method.
    func makeShipment() -> Shipment
}

public extension DeliveryService {
    /// Shared business logic. It works with whatever `makeShipment()` returns.
    func dispatch(_ order: Order) -> String {
        let shipment = makeShipment()
        let cost = shipment.cost(for: order)
        return "\(order.number) -> \(shipment.carrier): shipping \(money(cost)), "
             + "\(shipment.estimate), tracking \(shipment.trackingPrefix)-\(order.number)"
    }
}

public struct CourierDeliveryService: DeliveryService {
    public init() {}
    public func makeShipment() -> Shipment { CourierShipment() }
}

public struct PostDeliveryService: DeliveryService {
    public init() {}
    public func makeShipment() -> Shipment { PostShipment() }
}

public struct StorePickupService: DeliveryService {
    public init() {}
    public func makeShipment() -> Shipment { StorePickup() }
}
```

Listing 6 — Creators and the factory method (DeliveryService.swift)

A new carrier is added by writing one new Shipment and one new DeliveryService; dispatch(_:) is never modified. The unit tests prove this with a DroneDeliveryService defined only in the test file.

4. Testing and results

The CreationalTests target checks each pattern with XCTest:

- Singleton — shared always returns the same instance (===), and 1000 concurrent calls to next() from DispatchQueue.concurrentPerform produce 1000 unique numbers.

- Builder — a complete order is priced correctly (2 × 500 MDL, 10% coupon, 25 MDL gift wrap = 925 MDL); missing customer, empty cart and gift message without wrapping are rejected with the right error; the director creates a gift-wrapped order.
- Factory Method — each service creates its own shipment type, the courier is free from 800 MDL, and a new DroneDeliveryService works with dispatch(_:) without changes.

Running swift run CreationalDemo produces the output below. The order numbers continue from the Singleton section into the Builder section (BK-1004 to BK-1006), which shows that both parts use the same instance. The Factory Method section shows the same order dispatched by three different creators, and then a service chosen automatically for each order.

```
========== SINGLETON - one shared order-number generator ==========
Same instance: true
Checkout gets:    BK-1001
Admin panel gets: BK-1002
Checkout gets:    BK-1003

========== BUILDER - step-by-step order construction ==========
Order BK-1004 for augustin@example.md
  Items: Clean Code, Design Patterns
  Delivery: str. Studenților 7, Chișinău
  Coupon: FAF10
  Subtotal 970.00 MDL, discount 97.00 MDL, gift wrap 0.00 MDL -> total 873.00 MDL

Director presets:
Order BK-1005 for ana@example.md
  Items: Swift Programming
  Delivery: bd. Ștefan cel Mare 168, Chișinău
  Gift wrap: yes ("La mulți ani!")
  Note: Deliver before the weekend
  Subtotal 320.00 MDL, discount 0.00 MDL, gift wrap 25.00 MDL -> total 345.00 MDL
Order BK-1006 for student@utm.md
  Items: Design Patterns, Swift Programming
  Delivery: pickup in store
  Coupon: FAF10
  Note: Pickup at FCIM, UTM
  Subtotal 840.00 MDL, discount 84.00 MDL, gift wrap 0.00 MDL -> total 756.00 MDL

Invalid builds are rejected:
  no customer: customer email is missing or invalid
  empty cart: the cart is empty
  message without wrap: a gift message requires gift wrapping

========== FACTORY METHOD - each service creates its own shipment ==========
BK-1004 -> Courier: shipping 0.00 MDL, next day, tracking CR-BK-1004
BK-1004 -> Poșta Moldovei: shipping 35.00 MDL, 3-5 days, tracking PM-BK-1004
BK-1004 -> Store pickup: shipping 0.00 MDL, ready in 2 hours, tracking PU-BK-1004

Service chosen per order:
BK-1004 -> Courier: shipping 0.00 MDL, next day, tracking CR-BK-1004
BK-1005 -> Courier: shipping 50.00 MDL, next day, tracking CR-BK-1005
BK-1006 -> Store pickup: shipping 0.00 MDL, ready in 2 hours, tracking PU-BK-1006
```

Listing 7 — Program output (swift run CreationalDemo)

5. The other creational patterns

5.1 Prototype

New objects are created by copying an existing, already configured object (the prototype) instead of building them from scratch. In Swift, structs are copied automatically on assignment; classes implement a copy() method. Useful when setup is expensive or when many objects differ only slightly.

```
final class BookTemplate {
    var format: String, language: String, price: Double
    init(format: String, language: String, price: Double) {
        self.format = format; self.language = language; self.price = price
    }
    func clone() -> BookTemplate {          // the prototype copies itself
        BookTemplate(format: format, language: language, price: price)
    }
}

let hardcoverRO = BookTemplate(format: "Hardcover", language: "RO", price: 300)
let copy = hardcoverRO.clone()   // same settings, independent object
copy.price = 280                 // the original still costs 300
```

Listing 8 — Prototype (example)

5.2 Object Pool

A fixed set of expensive objects is created once and reused: a client acquires an object from the pool, uses it and releases it back, instead of creating and destroying it each time. Typical for database connections, threads and sockets.

```
final class ConnectionPool {
    private var available: [DBConnection]
    init(size: Int) { available = (1...size).map { DBConnection(id: $0) } }

    func acquire() -> DBConnection? { available.popLast() }   // nil = pool exhausted
    func release(_ c: DBConnection) { available.append(c) }
}
```

Listing 9 — Object Pool (example)

5.3 Abstract Factory

An interface creates a whole family of related objects, so the objects always match each other. The client chooses one concrete factory and never names the concrete products. Where Factory Method creates one product through a method that is overridden, Abstract Factory is an object with several creation methods for a family of products.

```
protocol StoreThemeFactory {
    func makeButton() -> Button
    func makeBanner() -> Banner
}
struct LightThemeFactory: StoreThemeFactory {
    func makeButton() -> Button { LightButton() }
    func makeBanner() -> Banner { LightBanner() }
}
```

```
struct DarkThemeFactory: StoreThemeFactory {
    func makeButton() -> Button { DarkButton() }
    func makeBanner() -> Banner { DarkBanner() }
}
// The screen receives one factory and gets a matching button + banner.
```

Listing 10 — Abstract Factory (example)

	Factory Method	**Abstract Factory**
Creates	One product	A family of related products
Mechanism	A method overridden / implemented by subtypes	A separate factory object with several methods
Example here	makeShipment()	makeButton() + makeBanner()

Table 2 — Factory Method vs Abstract Factory

Conclusion

In this laboratory work three creational design patterns were implemented in Swift and combined in one bookstore application.

The Singleton guarantees one order-number generator for the whole program, so numbers never repeat, even under concurrent access. Swift makes the pattern short (static let plus a private init), but it remains global state and should be used only where exactly one instance is truly required. The Builder replaced a long, error-prone initializer with readable step-by-step construction, kept the final Order immutable and moved validation to a single place, build(); the Director reuses common construction sequences. The Factory Method separated the dispatch algorithm from the decision of which shipment to create, so new carriers are added without modifying existing code, which applies the Open/Closed Principle from the previous laboratory work.

Prototype, Object Pool and Abstract Factory were also studied. Together, the six patterns show the main ways to control object creation: limiting the number of instances, assembling complex objects, copying, reusing, and delegating the choice of concrete classes.

Bibliography

- Gamma, E., Helm, R., Johnson, R., Vlissides, J. Design Patterns: Elements of Reusable Object-Oriented Software. Addison-Wesley, 1994.
- Shvets, A. Dive Into Design Patterns. refactoring.guru, 2021.
- Apple Inc. The Swift Programming Language — Properties, Protocols, Error Handling. docs.swift.org.

Repository: https://github.com/Afyze/tmps-2026-AugustinCarazanu/tree/main/lab1