



Color Image Processing

Chapter 6



Contents

- Color Models
- RGB Color Model
- HSI Color Model
- Pseudo Color Image Processing





Color Models

- Specification of colors in some standard generally accepted way
- We will consider two very popular models used in color image processing:
 - RGB (**R**ed **G**reen **B**lue)
 - HSI (**H**ue **S**aturation **I**ntensity)

RGB Color Model

- In the RGB model each colour appears in components of red, green and blue
- The model is based on a Cartesian coordinate system
 - RGB values are at 3 corners
 - Cyan magenta and yellow are at three other corners
 - Black is at the origin
 - White is the corner furthest from the origin
 - Different colours are points on or inside the cube represented by RGB vectors

RGB Color Model



RGB Color Model

- Images represented in the RGB color model consist of three component images – one for each color
- The number of bits used to represent each pixel is referred to as the color depth
- A 24-bit image is often referred to as a full-color image as it allows $(2^8)^3 = 16,777,216$ colors

HSI Color Model

- The HSI model uses three measures to describe colors:
 - **Hue:** A color attribute that describes a pure color (pure yellow, orange or red)
 - **Saturation:** Gives a measure of how much a pure color is diluted with white light
 - **Intensity:** Intensity is the same achromatic notion that we have seen in grey level images




HSI Color Model


- Intensity can be extracted from RGB images
- Remember the diagonal on the RGB color cube that we saw previously ran from black to white
- Now consider if we stand this cube on the black vertex and position the white vertex directly above it

HSI Color Model

- The intensity component of any color can be determined by passing a plane *perpendicular* to the intensity axis and containing the color point
- The intersection of the plane with the intensity axis gives us the intensity component of the color




HSI Color Model



HSI Color Model


■ An arbitrary color point

- The hue is determined by an angle from a reference point, usually red
- The saturation is the distance from the origin to the point
- The intensity is determined by how far up the vertical intensity axis this hexagonal plane sits (not apparent from this diagram)




HSI Color Model


Because the only important things are the angle and the length of the saturation vector this plane is also often represented as a circle or a triangle



HSI Color Model



HSI Color Model



Converting from RGB to HSI

$$\theta = \cos^{-1} \left\{ \frac{\frac{1}{2} [(R - G) + (R - B)]}{[(R - G)^2 + (R - B)(G - B)]^{\frac{1}{2}}} \right\}$$

$$H = \begin{cases} \theta & \text{if } B \leq G \\ 360 - \theta & \text{if } B > G \end{cases}$$


$$S = 1 - \frac{3}{(R + G + B)} [\min(R, G, B)]$$

$$I = \frac{1}{3} (R + G + B)$$

HSI Color Model




RGB



HSI




Manipulating Images In The HSI Model

- In order to manipulate an image under the HSI model we:
 - First convert it from RGB to HSI
 - Perform our manipulations under HSI
 - Finally convert the image back from HSI to RGB



Pseudocolor Image Processing


- Pseudocolor (also called false color) image processing consists of assigning colors to grey values based on a specific criterion
- The principle use of pseudocolor image processing is for human visualization



Pseudo Color Image Processing – Intensity Slicing

- Intensity slicing and color coding is one of the simplest kinds of pseudocolor image processing
- First we consider an image as a 3D function mapping spatial coordinates to intensities (that we can consider heights)
- Now consider placing planes at certain levels parallel to the coordinate plane
- If a value is one side of such a plane it is rendered in one color, and a different color if on the other side

Pseudo Color Image Processing – Intensity Slicing



Pseudo Color Image Processing – Intensity Slicing

- In general intensity slicing can be summarized as:
 - Let $[0, L-1]$ represent the grey scale
 - Let I_0 represent black $[f(x, y) = 0]$ and let I_{L-1} represent white $[f(x, y) = L-1]$
 - Suppose P planes perpendicular to the intensity axis are defined at levels I_1, I_2, \dots, I_P
 - Assuming that $0 < P < L-1$ then the P planes partition the grey scale into $P + 1$ intervals V_1, V_2, \dots, V_{P+1}



Pseudo Color Image Processing – Intensity Slicing

- Grey level color assignments can then be made according to the relation:



$$f(x,y) = c_k \quad \text{if } f(x,y) \in V_k$$

- where c_k is the color associated with the k^{th} intensity level V_k defined by the partitioning planes at $l = k - 1$ and $l = k$




Pseudo Color Image Processing – Intensity Slicing



Pseudo Color Image Processing – Intensity Slicing



Pseudo Color Image Processing – Intensity Slicing





References

- Chapter #6: Digital Image Processing by Rafael C. Gonzales & Richard E. Woods