# ROS2 Spring Workshop

Lab 2: Writing Your First Robot Brain

**Project Context: Your First Autonomous Node**

In Lab 1, you drove the turtle by pressing arrow keys. That worked because a *human* was in the loop making decisions 30 times a second. In the Final Project, the tractor will drive itself for minutes at a time with no human input; it needs its own brain.
Today you write the skeleton of every autonomous node you will build this semester: a Python class that wakes up periodically, thinks, and publishes commands. Every lab from here on layers more intelligence onto this pattern.

## Objective

In Lab 1, you drove the turtle manually using your keyboard. In this lab, you will write a **Python node** to drive the turtle automatically.

You will learn:

- **Publishers:** How to send commands to a robot.
- **Timers:** How to make a robot perform actions repeatedly.
- **Package creation:** How to organize your code files.
- **Safe shutdown:** Why every controller must stop cleanly on Ctrl+C.

## Pre-Lab Concept Primer: The Anatomy of a Node

Before writing code, we must understand the structure. We use **Object-Oriented Programming (OOP)** to build robots.

### 1. Class vs. Object

- **The Class (blueprint):** The code file is just a piece of paper. It describes *how* a robot behaves.
- **The Object (the robot):** At the bottom of our script (in `main`), we "instantiate" the class. This is the factory actually building the robot.

### 2. What is "self"? (The Robot's Backpack)

In OOP, `self` represents **this specific robot's memory**.

- If you say `x = 5`, the variable dies when the function ends (amnesia).
- If you say `self.x = 5`, the robot puts it in its backpack and remembers it forever.

### 3. The ROS 2 Toolkit (Pubs, Subs, and Timers)

- **Publisher (the mouth):** Shouts data ("velocity = 2.0") into a topic.
- **Subscriber (the ear):** Listens to a topic. When data arrives, it triggers a function.
- **Timer (the heartbeat):** An alarm clock that wakes the robot up periodically.




Figure 1: Visualizing OOP: the code is just a plan. The `self` variable is the memory inside the actual running robot.




Figure 2: Architecture: the timer wakes the node, the node calculates a move, and sends it to the publisher.

## 4. The Syntax Breakdown (How to Speak ROS)

You will see these three commands constantly. Here is exactly what the inputs mean.

**1. The Publisher (Speaking)**

```
self.create_publisher(MsgType, 'TopicName', QueueSize)
```

- **MsgType (Twist):** The language we are speaking. "Twist" means velocity (linear X, angular Z).
- **'TopicName' (/cmd_vel):** The channel we are shouting on.
- **QueueSize (10):** If we talk too fast, keep the last 10 messages in a buffer before deleting old ones.

**2. The Timer (Waking Up)**

```
self.create_timer(Interval, CallbackFunction)
```

- **Interval (1.0):** How many seconds to wait between ticks (e.g., 1.0 s = 1 Hz).
- **CallbackFunction (self.move_logic):** The specific function to run when the alarm goes off. *Note: do not add () at the end!*

**3. The Logger (Status Updates)**

`self.get_logger().info/warn/error("Message")`

- **info:** General status updates ("Node has started"). These appear as white text in the terminal.
- **warn:** Yellow alerts for when things aren't quite right ("Geofence breached"). Use these for safety boundary triggers.
- **error:** Red alerts for critical failures. These usually stop the process.

---

# Part 1: Workspace Setup

We need to create a structured home for your code. In ROS 2, we don't just make loose files; we make **packages**.

## Step 0: Clean the Workspace

Since we are using a shared repository, it is possible that an old version of this lab already exists. We must delete it to start fresh.

1. Open your terminal in VS Code.
2. Clean the `src` folder:

```
cd /workspaces/agtech_ros2/src
rm -rf lab2_turtlesim_chase

```

## Step 1: Create the Package

Now that the workspace is clean, generate the new package structure:

```
# Still inside the src folder...
ros2 pkg create --build-type ament_python lab2_turtlesim_chase
```

**Why do we do this?**
The flag `--build-type ament_python` tells ROS that we are writing Python scripts, not C++. This sets up the folder structure automatically so we don't have to do it manually.

# Part 2: The "Square Drawer" Script

## Step A: Create the File

In ROS 2, Python scripts must live inside the inner "module" folder. This is the second folder with the same name as your package.

```
# Navigate into the inner python source folder
cd lab2_turtlesim_chase/lab2_turtlesim_chase

# Create and open the python file
code draw_square.py
```

## Step B: Write the Code

Paste the following code into the editor.

```
#!/usr/bin/env python3
import rclpy
from rclpy.node import Node
from geometry_msgs.msg import Twist

class SquareDrawer(Node):
```

```python
    def __init__(self):
        # Give the node a name for the logs
        super().__init__('square_drawer_node')

        # 1. PUBLISHER: Speak "Twist" messages to '/turtle1/cmd_vel'
        self.publisher_ = self.create_publisher(
            Twist, '/turtle1/cmd_vel', 10)

        # 2. TIMER: Wake up 'move_turtle_logic' every 1.0 seconds
        self.timer = self.create_timer(1.0, self.move_turtle_logic)

        self.step = 0
        self.get_logger().info("Square Drawer Node has started!")

    def move_turtle_logic(self):
        # Create a new message to send
        msg = Twist()

        # Logic: Even steps = Drive, Odd steps = Turn
        # This uses the Modulo operator (%) to check for remainders
        if self.step % 2 == 0:
            msg.linear.x = 2.0    # Drive forward (m/s)
            msg.angular.z = 0.0
            self.get_logger().info("Driving forward...")
        else:
            msg.linear.x = 0.0
            msg.angular.z = 1.57  # Turn 90 degrees (approx) in radians
            self.get_logger().info("Turning...")

        # Send the message using the publisher we saved in 'self'
        self.publisher_.publish(msg)
        self.step += 1


def main(args=None):
    rclpy.init(args=args)
    node = SquareDrawer()
    try:
        rclpy.spin(node)
    except KeyboardInterrupt:
        pass
    finally:
        # SAFETY: publish zero velocity on shutdown so the turtle
        # doesn't coast after Ctrl+C. You will use this pattern in
        # every robot controller you write this semester.
        stop_msg = Twist()
        node.publisher_.publish(stop_msg)
        node.destroy_node()
        rclpy.shutdown()


if __name__ == '__main__':
    main()
```

Listing 1: draw_square.py

**Professional Habit: Always Stop On Shutdown**

Notice the `try/except/finally` block in `main()`. When you Ctrl+C, the `finally` block publishes a zero-velocity `Twist` before the node exits.

**Why it matters:** Without this, the turtle (or a real robot in later labs) would keep driving with its last command until something else stops it. On the physical tractor in Lab 8, this is a genuine safety issue.

Get in the habit now, because you will reuse this pattern in Labs 3, 6, 7, 8, 9, and 10.

AgTech Alert: Tank vs. Tractor Physics

**Critical concept for Lab 8:**
In this code, you told the turtle to spin in place:

- `msg.linear.x = 0.0` (stop)
- `msg.angular.z = 1.57` (spin)

**Why this is dangerous later:**
Turtlesim acts like a tank (differential drive). It can spin on a dime. Your physical AgBot (Lab 8) acts like a tractor (Ackermann steering). It **cannot** spin in place. If you try to turn the wheels without moving forward on the real robot, you will burn out the steering servo. On a tractor, a turn must always be an arc (`linear.x` $> 0$).
Today we're in simulation, so the spin-in-place works fine. But remember this when you move to real hardware.

# Part 3: Registration & Build

Creating a file isn't enough. We must "register" the script so ROS 2 can find it, and then "build" it to install it into the system.

## Step A: Modify setup.py

1. Open `src/lab2_turtlesim_chase/setup.py`.
2. Find the `entry_points` section. This works like a **phonebook**. We are telling ROS: *"When I type the command `draw_square`, go look inside the file `draw_square.py` and run the `main` function."*
3. Update it to look like this:

```
entry_points={
    'console_scripts': [
        'draw_square = lab2_turtlesim_chase.draw_square:main',
    ],
},

```

## Step B: Build the Workspace

We must compile the workspace to move our script from the "source" folder to the "install" folder where ROS can see it.

1. Go back to the root folder and run `colcon build`:

```
cd /workspaces/agtech_ros2
colcon build

```

2. **Source the setup file:** This refreshes your terminal so it sees the new program.

```
source install/setup.bash

```

**Stop! Read This Before Building**

By default, ROS 2 creates a *copy* of your python script when you build. If you edit the file in VS Code, ROS 2 keeps running the old copy, and you will think you are going crazy because your changes won't show up.
**The fix:** We use a special flag to create a "live link" (symlink) between your code and ROS.
**Run this command (and memorize it):**

```
cd /workspaces/agtech_ros2
colcon build --symlink-install
source install/setup.bash
```

**What does this do?**

- **Standard build:** Copy/paste file (static). Requires rebuild on every edit.
- **Symlink build:** Creates a shortcut (dynamic). You can edit Python code and run it immediately without rebuilding!

## Part 4: The Test Drive

Now we run the system. We need two terminals: one for the robot (simulator) and one for the brain (your script).

**Linux/Pop!_OS Users Reminder**

If the turtle window does not appear in the next step, remember the fix from Lab 1!

- **Host terminal:** Ensure `xhost +local:root` was run.
- **VS Code terminal:** You may need to run `export DISPLAY=:1` (or `:0`) in **EVERY** new terminal tab you open.

1. Open **Terminal 1** and run the simulator:

```
# Linux Users: export DISPLAY=:1
ros2 run turtlesim turtlesim_node

```

2. Open **Terminal 2** (split terminal) and run your new brain:

```
# Don't forget to source!
source install/setup.bash
ros2 run lab2_turtlesim_chase draw_square

```

You should see the turtle drive forward, turn, drive, turn, tracing a rough square path. Ctrl+C to stop the controller; thanks to the try/finally cleanup, the turtle will stop immediately instead of coasting.

## Part 5: Final Task: The Star Navigator

To complete this lab, you must transition from drawing simple squares to drawing a **5-pointed star**. You will modify `draw_square.py` in place.

### 1. Star Geometry

A 5-pointed star is drawn by moving forward and then turning sharply. The turning angle is **144°** at each corner.

**Why 144°?** Here's the delightful insight: when you draw a 5-pointed star by going point-to-point, you actually rotate through $5 \times 144 = 720$ (two full rotations) by the time you get back to the start. That extra 360 of rotation is what makes the path cross over itself into a star shape instead of closing into a pentagon. Drawing a regular pentagon would be 72° per corner (totalling 360°); drawing a star doubles it.

**Converting to radians:** ROS 2 uses radians. $144 \times (\pi/180) \approx$ **2.51 radians**.



Figure 3: The 5-pointed star path.

### 2. Modifying Your Logic

Edit `draw_square.py` with one change:

- **The turn:** Change `msg.angular.z` from `1.57` to `2.51`.

That's it. The code loops forever alternating drive/turn, so there's nothing to change about step counts, you just let it run and the star traces out.

**Save, then test:** Thanks to `--symlink-install`, you do not need to rebuild. Just re-run:

```
ros2 run lab2_turtlesim_chase draw_square
```

Watch the star emerge. When you've got a clean 5-pointed star, you're done.

**Want More? (Optional)**

Some tuning you might try if you finish early:

- The drive-forward duration is controlled by the `1.0` in `create_timer(1.0, ...)`. Change it to `0.5` and see what happens.
- Change `msg.linear.x = 2.0` to `0.5` for a slower, smaller star.
- Add a step counter that stops the turtle after drawing ONE complete star (10 steps: 5 drives + 5 turns).

These are not required for submission, and they're for students who want to play more.

## Troubleshooting

If your code isn't working, check these common issues first:

- **Why does my square drift/shift?**
  *Answer: Timer jitter.* You are using "open-loop control." You told the robot to turn for 1.0 seconds. If your computer is busy (or the OS lags), the timer might fire at 1.05 seconds.
  - $1.57\ \text{rad/s} \times 0.05\,\text{s} \approx 4.5$ of error per turn!

This accumulates quickly. To fix this, real robots use sensors (closed-loop control) to verify how far they actually turned. You'll do this in Lab 3.

- **Error:** `Package 'lab2_turtlesim_chase' not found.`
  *Solution:* You likely forgot to source your setup file. Run this command in every new terminal:

```
source install/setup.bash

```

- **The turtle just spins in circles!**
  *Solution:* Check your math in `move_turtle_logic`. On odd steps you should be turning with `linear.x = 0.0`; on even steps you should be driving with `angular.z = 0.0`. If both are non-zero on every step, you'll spiral.

- **I pressed Ctrl+C but the turtle kept sliding.**
  *Solution:* Your try/finally cleanup is missing or broken. Re-check the `main()` block matches the code given in Part 2.

## Deliverables

Submit a screenshot of your full desktop showing:

1. The blue Turtlesim window with a clearly drawn **5-pointed star**.
2. The VS Code terminal showing the node successfully running ("Driving forward...", "Turning..." log messages visible).
3. The final "Secret Code" from the Lab 1 Scavenger Hunt (`KERNEL_OF_TRUTH`).

**What's Next: Lab 3**

Your square drifts. Your star drifts. You can see that open-loop control isn't good enough for real robots.
In Lab 3 you'll add **subscribers** so your code can read the turtle's actual position, not just guess where it should be. That closes the loop, and it's the difference between "hoping" and "knowing" where your robot is. Welcome to the next step toward a real autonomous tractor.