



Protocol Audit Report

Version 1.0

Alphonsus.io

Thursday 10th July, 2025

Introduction

Prepared by: [Alphonsus] Lead Auditors: - Alphonsus

Table of Contents

- Table of Contents
- Protocol Summary
- Disclaimer
- Risk Classification
- Audit Details
 - Scope
 - Roles
- Executive Summary
 - Issues found
- Findings
 - High
 - * [H-1] Storing the password on-chain makes it visible to anyone and no longer private
 - * [H-2] `PasswordStore::setPassword` has no access controls, meaning a non-owner could change the password
 - Informational
 - * [I-1] The `PasswordStore::getPassword` natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect.
 - Gas

Protocol Summary

PasswordStore is a protocol dedicated to storage and retrieval of a user's passwords. The protocol is designed to be used by a single user, and is not designed to be used by multiple users. Only the owner should be able to set and access this password.

Disclaimer

The AgentA team makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

Risk Classification

		Impact		
		High	Medium	Low
Likelihood	High	H	H/M	M
	Medium	H/M	M	M/L
	Low	M	M/L	L

We use the CodeHawks severity matrix to determine severity. See the documentation for more details.

Audit Details

The findings described in this document correspond with the following commit hash:

```
1 7d55682ddc4301a7b13ae9413095feffd9924566
```

Scope

```
1 ./src/  
2 |-- PasswordStore.sol
```

Roles

- Owner: The user who can set the password and read the password.
- Outsiders: No one else should be able to set or read the password.

Executive Summary

Issues found

Severity	Number of issues found
High	2
Medium	0
Low	0
Info	1
Total	3

Findings

High

[H-1] Storing the password on-chain makes it visible to anyone and no longer private

Description: All data stored on chain is public and visible to anyone. The `PasswordStore::s_password` variable is intended to be hidden and only accessible by the owner through the `PasswordStore::getPassword` function.

I show one such method of reading any data off chain below.

Impact: Anyone is able to read the private password, severely breaking the functionality of the protocol.

Proof of Concept: The below test case shows how anyone could read directly from the blockchain.

1. Create a locally running chain

```
1 make anvil
```

2. Deploy the contract to the chain

```
1 make deploy
```

3. Run the storage tool

We use 1 because that's the storage slot of `s_password` in the contract.

```
1 cast storage <ADDRESS_HERE> 1 --rpc-url http://127.0.0.1:8545
```

4. You'll get an output that looks like this:

[illegible]

5. You can then parse that hex to a string with:

[illegible]

6. And get an output of:

```
1 myPassword
```

Recommended Mitigation: Due to this, the overall architecture of the contract should be rethought. One could encrypt the password off-chain, and then store the encrypted password on-chain. This would require the user to remember another password off-chain to decrypt the stored password. However, you're also likely want to remove the view function as you wouldn't want the user to accidentally send a transaction with this decryption key.

[H-2] PasswordStore::setPassword has no access controls, meaning a non-owner could change the password

Informational

[I-1] The PasswordStore::getPassword natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect.

Gas