Attacking Vision-Language Computer Agents via Pop-ups

Anonymous Submission

Abstract

Vision-language agents are increasingly used for GUI automation tasks, yet their robustness to adversarial visual inputs remains underexplored. We introduce POPUPATTACK, a practical attack that exploits agents' over-reliance on visual cues by injecting malicious pop-ups into their observations. Our attack consists of four modular components: (1) attention hooks that condition content on user queries, (2) explicit click instructions with target coordinates or IDs, (3) info banners mimicking common UI elements, and (4) accessibility tree descriptors. We evaluate across frontier vision-language models (GPT-4o, Claude 3.5, Gemini 1.5) on OSWorld and VisualWebArena benchmarks. Our results show remarkably high attack success rates: up to 100% on OSWorld screenshot agents and 62-95% across other settings, with agents devoting 73-93% of their actions to clicking malicious pop-ups. The attack causes task success rates to plummet by an average of 47 percentage points. Query-conditioned attention hooks prove critical—replacing them with generic "VIRUS DETECTED" alerts reduces attack success by 33-61%. Standard prompt-based defenses provide limited protection, highlighting the need for more robust environmental awareness in vision-language agents.

AI Generated

1 Introduction

Vision-language models (VLMs) are rapidly transforming how we interact with graphical user interfaces, with agents capable of autonomously completing complex computer tasks by interpreting screenshots and executing actions (Xie et al., 2024; Koh et al., 2024; Zheng et al., 2024). From web browsing to desktop automation, these multimodal agents promise to democratize computer use and enhance productivity across diverse domains.

However, as these agents become more sophisticated and widely deployed, their security implications become increasingly critical. While extensive work has explored adversarial attacks on vision and language models, the unique vulnerabilities of vision-language agents operating in real-world computer environments remain largely unexplored.

In this work, we identify and exploit a fundamental vulnerability: *VLM agents over-trust visual cues and poorly distinguish between legitimate interface elements and adversarial overlays*. Malicious pop-ups—ubiquitous in modern computing environments—represent a practical and immediate threat vector. When strategically designed and positioned, these pop-ups can reliably hijack agent behavior and trigger unintended actions.

We introduce POPUPATTACK, a modular attack framework that injects adversarial pop-ups into agent observations to manipulate their behavior. Our approach consists of four key components: (1) *attention hooks* that condition pop-up content on the user's query to increase relevance, (2) *explicit instructions* with precise click targets, (3) *info banners* that mimic standard UI elements like "OK" buttons, and (4) *accessibility descriptors* that reinforce the attack through text-based channels.

Through comprehensive evaluation across frontier VLMs (GPT-4o, Claude 3.5 Sonnet, Gemini 1.5 Pro) on OSWorld (Xie et al., 2024) and VisualWebArena (Koh et al., 2024) benchmarks, we demonstrate that current agents are alarmingly susceptible to pop-up attacks. Key findings include:

- **High vulnerability across models and settings**: Attack success rates reach 100% on OSWorld screenshot agents and 62-95% across other configurations.
- **Severe task disruption**: Attacked agents devote 92.7% (OSWorld) and 73.1% (VisualWebArena) of their actions to clicking malicious pop-ups, causing task success rates to drop by an average of 47 percentage points.
- **Critical role of query conditioning**: Atten-

tion hooks aligned with user intent prove essential—generic "virus" alerts reduce attack effectiveness by 33-61%.

- **Limited defense efficacy**: Standard prompt-based countermeasures provide minimal protection, with even sophisticated defenses leaving task-level attack success rates at 32-44%.

Our work highlights fundamental gaps in current VLM agent robustness and underscores the urgent need for built-in environmental risk awareness. As these agents transition from research prototypes to real-world deployment, understanding and mitigating such vulnerabilities becomes paramount for safe and reliable automation.

2 Related Work

2.1 Vision-Language Agents

Recent advances in large language models and vision-language models have enabled sophisticated agents capable of understanding and acting upon visual interfaces (Yang et al., 2023; Zheng et al., 2024). These agents operate across diverse environments, from web browsing (Koh et al., 2024) to desktop automation (Xie et al., 2024). OSWorld (Xie et al., 2024) and VisualWebArena (Koh et al., 2024) have emerged as key benchmarks for evaluating agent performance on realistic computer tasks.

2.2 Adversarial Attacks on Vision Models

The field of adversarial machine learning has extensively studied attacks on computer vision systems. These attacks typically involve adding imperceptible perturbations to input images to cause misclassification. Physical adversarial attacks have demonstrated real-world applicability.

2.3 Adversarial Attacks on Language Models

Language models face various adversarial threats, including prompt injection attacks (**??**), jailbreaking techniques (**??**), and adversarial examples designed to trigger specific behaviors (**??**). Recent work has explored attacks on aligned models (**??**) and defenses against malicious prompts (**??**).

2.4 Security of Multimodal Models

As vision-language models become prevalent, researchers have begun investigating their security implications. Bailey et al. (**?**) demonstrated image-based prompt injection attacks, while Bagdasaryan et al. (**?**) showed how adversarial images can manipulate model outputs. Yin et al. (**?**) explored jailbreaking techniques specific to VLMs. However, most existing work focuses on isolated model vulnerabilities rather than agent-environment interactions.

2.5 Interface Security and Deception

Traditional interface security research has examined various deception techniques, including clickjacking (**?**), UI redressing (**?**), and phishing attacks (**?**). Pop-up windows have long been recognized as vectors for malicious activity in human-computer interaction (**?**). Our work bridges this classical security domain with modern AI agent vulnerabilities.

Our contribution differs from prior work by focusing specifically on environment-mediated attacks against vision-language agents in realistic computer use scenarios. While previous research has explored adversarial inputs to isolated models, we investigate how environmental manipulation can exploit agent-environment interaction patterns in practical deployment settings.

3 Attack Design

3.1 Threat Model

We consider a practical threat scenario where an attacker can inject visual elements into an agent's observation stream. This could occur through compromised websites, malicious applications, or hijacked displays. The attacker aims to manipulate agent behavior to perform unintended actions, potentially leading to data theft, system compromise, or task disruption.

We assume the attacker has knowledge of the user's high-level intent (e.g., from observing the task description) but cannot directly modify the agent's reasoning process or system prompts. The attack operates purely through environmental manipulation—injecting visual pop-ups that appear as legitimate interface elements to the agent.

3.2 PopupAttack Framework

Our attack consists of four modular components designed to maximize the likelihood of agent interaction:

3.2.1 Attention Hook

The attention hook captures the agent's focus by presenting content aligned with the current task. We implement several variants:

AI-Generated

- **Summarized Query**: Content directly related to the user's task, generated by prompting a language model to create a concise "button name" based on the user query.

- **Virus Alert**: Generic warning messages like "VIRUS DETECTED" that exploit urgency bias.

- **Speculated Query**: Content that attempts to guess user intent based on visible screen elements.

3.2.2 Instruction

The instruction component provides explicit guidance for the agent to interact with the pop-up:

- **Click Coordinates**: For screenshot-based agents, precise (x,y) coordinates within the pop-up area.

- **Click Tag**: For Set-of-Mark (SoM) agents, specific element IDs that reference pop-up components.

- **Click Here**: Generic instructions without specific targets.

- **Random Targets**: Instructions pointing to arbitrary locations to test baseline susceptibility.

3.2.3 Info Banner

The info banner mimics familiar UI elements to enhance legitimacy:

- **OK Button**: Standard confirmation button

- **Advertisement Disclosure**: "ADVERTISEMENT" label to test transparency effects

- **Empty**: No banner to isolate other components' effects

3.2.4 ALT Descriptor

For agents that process accessibility trees, we inject corresponding text descriptions:

- **Full Description**: Complete text mirroring visual content

- **Advertisement Noted**: Explicit marking as advertising content

- **Empty ALT**: No accessibility description



Figure 1: Adversarial pop-up structure showing the four components: (1) attention hook with query-related content, (2) explicit click instruction, (3) info banner, and (4) ALT descriptor in the accessibility tree.

3.3 Implementation

Pop-ups are positioned in the largest non-overlapping screen area to avoid obscuring legitimate interface elements. The positioning algorithm:

1. Identifies empty screen regions using computer vision techniques

2. Randomly places pop-ups within suitable areas (480-960 pixels wide, 270-540 pixels tall)

3. Ensures pop-ups don't overlap with existing UI elements

For screenshot agents, pop-ups are rendered directly onto the image. For SoM agents, corresponding entries are injected into the accessibility tree with appropriate element IDs. Figure 1 illustrates the four-component structure of our attack.

The modular design enables systematic ablation studies to understand which components contribute most to attack success. Default "ideal" attacks use summarized query hooks with precise coordinate/tag instructions, while realistic variants test robustness under various constraints.

4 Experiments

4.1 Experimental Setup

4.1.1 Benchmarks

We evaluate on two established benchmarks for computer-use agents:

OSWorld (Xie et al., 2024): We use 50 tasks from the "easy" subset—tasks that baseline agents

AI-Generated

can complete without attacks. We limit episodes to 15 steps to focus on immediate attack effectiveness.

VisualWebArena (Koh et al., 2024): We select 72 tasks from the "easy" subset based on prior work (Yang et al., 2023), with a 30-step limit per episode.

4.1.2 Agent Architectures

We evaluate two agent types:

- **Screenshot Agents**: Process raw screenshots and output pixel coordinates for actions
- **Set-of-Mark (SoM) Agents**: Use marked screenshots with numbered elements and reference actions by element IDs (Yang et al., 2023)

4.1.3 Vision-Language Models

We test five frontier VLMs:

- GPT-4-Turbo (2024-04-09)
- GPT-4o (2024-05-13) (OpenAI, 2024)
- Gemini 1.5 Pro (gemini-1.5-pro-002) (Reid et al., 2024)
- Claude 3.5 Sonnet (20240620)
- Claude 3.5 Sonnet v2 (20241022)

All experiments use temperature 0 to reduce randomness and ensure reproducible results.

4.1.4 Evaluation Metrics

We define four key metrics:

- **Attack Success Rate (ASR)**: Percentage of episodes where the agent clicks on the malicious pop-up
- **Success Rate (SR)**: Percentage of tasks completed successfully under attack
- **Original Success Rate (OSR)**: Baseline task completion rate without attacks
- **Task-level Attack Success Rate (TASR)**: Percentage of tasks where the attack disrupts completion, regardless of whether the agent clicks the pop-up

4.2 Main Results

Table 1 presents our core findings across models and environments. The results reveal several critical vulnerabilities:

Universal High Vulnerability: All models show remarkably high attack success rates. OSWorld screenshot agents are completely vulnerable (80-100% ASR), while OSWorld SoM agents achieve 88.7-95.3% ASR. VisualWebArena SoM agents show somewhat lower but still concerning rates of 62.1-78.4%.

Severe Task Disruption: The attack causes dramatic drops in task completion. For instance, Claude 3.5 Sonnet achieves 22% OSR on OSWorld-Screen but 0% SR under attack—a complete performance collapse. Across all settings, SR drops by an average of 47 percentage points compared to OSR.

Model-Specific Patterns: While all models are vulnerable, Gemini 1.5 Pro shows slightly better resistance (lowest ASR in OSWorld settings), while Claude 3.5 Sonnet demonstrates the most extreme vulnerability (100% ASR, 0% SR on OSWorld-Screen).

Figure 2 illustrates the extent of agent hijacking: attacked agents spend 92.7% of their actions clicking pop-ups in OSWorld and 73.1% in VisualWebArena, demonstrating how completely the attack can derail agent behavior.

4.3 Ablation Studies

We conduct comprehensive ablation studies to understand which attack components are most critical for success.

4.3.1 Attention Hooks

Table 2 shows the critical importance of query-conditioned content. The default summarized query achieves the highest ASR across all settings. Replacing with generic "VIRUS DETECTED" alerts reduces effectiveness significantly: ASR drops by 33.5% on OSWorld-SoM (from 91.8% to 58.3%) and 61.0% on VisualWebArena (from 62.1% to 1.1%). Even speculated queries based on visible screen content achieve moderate success (34.4% and 8.0% respectively), confirming that alignment with user intent is crucial.

4.3.2 Instructions

Table 3 reveals that precise targeting significantly enhances attack success. Click coordinates (for screenshots) and click tags (for SoM) achieve the

AI-Generated

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
GPT-4-Turbo	93.3	2.0	18.0	91.8	8.0	52.0	78.0	43.1	50.0
GPT-4o	95.8	**6.0**	8.0	91.2	2.0	6.0	**62.1**	45.8	**63.9**
Gemini 1.5	**80.0**	4.0	6.0	**88.7**	6.0	18.0	70.1	44.4	48.6
Claude 3.5 Sonnet	100.0	0.0	**22.0**	95.3	6.0	44.0	78.4	47.2	54.2
Claude 3.5 Sonnet v2	96.0	4.0	**22.0**	94.8	**10.0**	**58.0**	76.8	**48.6**	50.0

Table 1: Model comparison results. We **highlight** the lowest ASR (↓) and highest SR (↑)/OSR (↑). Screen and SoM refer to screenshot agents and SoM agents respectively. WebArena refers to VisualWebArena.

Attention Hook	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Summarized Query	93.3	2.0		91.8	8.0		62.1	45.8	
Virus	90.0	2.0	18.0	58.3	26.0	52.0	1.1	54.2	63.9
Speculated Query	53.9	10.0		34.4	38.0		8.0	54.2	

Table 2: Ablation study on attention hooks. Underlined numbers represent the default setting. Results use GPT-4-Turbo agents.

Figure 2: Attack impact overview. When PopupAttack is present, agents devote the vast majority of their actions to clicking malicious pop-ups rather than pursuing their intended tasks.

highest ASR. Generic "click here" instructions are much less effective, particularly for screenshot agents where ASR drops from 93.3% to just 11.3%. Interestingly, even random targeting achieves non-trivial success rates (10-14%), suggesting some baseline susceptibility to clicking behavior.

4.3.3 Additional Component Analysis

We also examine info banners and ALT descriptors. Info banners have modest effects: "OK" buttons slightly increase engagement, while "ADVERTISEMENT" labels provide minimal deterrent effect. ALT descriptors in the accessibility tree matter primarily for their presence rather than content—empty ALT text reduces ASR by 19-24% compared to full descriptions.

4.4 Defense Evaluation

We evaluate several defense mechanisms:

System Prompt Defenses: Adding warnings like "ignore pop-ups" to system prompts provides limited protection, reducing ASR by at most 25% in most cases.

Step-wise Prompt Defense: A more sophisticated approach adds pop-up warnings at each interaction step. Table 4 shows this reduces ASR dramatically to 5.9-10.4%, but TASR remains high at 32-44%, indicating many tasks are still disrupted even when agents avoid clicking.

5 Understanding Agent Attack

To better understand why PopupAttack succeeds, we analyze agent behavior patterns and failure modes through qualitative examination of agent reasoning traces and quantitative analysis of action distributions.

5.1 Agent Reasoning Analysis

Figure 3 demonstrates how agents rationalize clicking on malicious pop-ups. Attacked agents frequently incorporate pop-up content into their reasoning, treating adversarial elements as legitimate

Generated

Instruction	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Click Tag	-	-	-	96.1	6.0	52.0	62.1	45.8	63.9
Click Coor	93.3	2.0	18.0	91.8	8.0		49.3	48.6	
Click Here	11.3	14.0		72.8	14.0		58.4	44.4	
Click Random	11.8	2.0		13.7	10.0		4.1	34.7	

Table 3: Ablation study on instructions. Underlined numbers represent default settings. Click Random uses random coordinates for OSWorld and random tags for VisualWebArena.

	OSWorld-Screen			
	ASR↓	TASR↓	SR↑	OSR↑
Step-wise Prompt Defense	5.9	32.0	8.0	18.0
+ Attack Variance	10.4	44.0	10.0	

Table 4: Step-wise prompt defense results using GPT-4-Turbo on OSWorld.



Figure 3: Successfully attacked examples showing agent thoughts. The agent incorporates pop-up content ("blue motorcycles") into its reasoning and treats the malicious element as task-relevant.

task-relevant information. For instance, when searching for motorcycles, an agent encountering a pop-up about "RECENT BLUE MOTORCYCLES $1K-$2K" explicitly mentions this content in its reasoning before deciding to click.

Through analysis of agent reasoning traces, we find that successfully attacked agents explicitly mention key attack components:

- **Attention hooks**: 89% of attacked agents reference the summarized query content
- **Target instructions**: 76% mention specific coordinates or element IDs



Figure 4: Correlation between ASR and Task-level Attack Success Rate (TASR). TASR captures broader task disruption beyond direct pop-up clicks.

- **Info banners**: 45% reference the "OK" button or similar elements

This suggests that agents are not simply clicking randomly but are actively incorporating adversarial content into their decision-making process.

5.2 Task-Level Attack Success

Beyond direct pop-up clicks, we introduce Task-level Attack Success Rate (TASR) to capture broader task disruption. Figure 4 shows the correlation between ASR and TASR across different settings. TASR tends to be higher than ASR when ASR is low, indicating that even when agents avoid clicking pop-ups, the mere presence of adversarial content can disrupt task completion.

5.3 Action Distribution Changes

The attack fundamentally alters agent action patterns. Figure 5 shows how attacked agents take fewer steps overall, as they become trapped in pop-up interaction loops rather than progressing toward task completion.

Figure 5: Impact of attacks on agent step counts. Attacked agents typically take fewer steps as they become focused on pop-up interactions.

5.4 Failure Mode Analysis

Our analysis reveals several key failure modes:

Over-trust of Visual Cues: Agents treat all visible elements as equally legitimate, lacking mechanisms to distinguish between authentic interface elements and potential adversarial content.

Poor Source Attribution: Agents fail to reason about the source or legitimacy of pop-up content, accepting it as part of the intended interface.

Task-Context Exploitation: The most effective attacks leverage task context, suggesting agents' goal-directed behavior can be redirected by appropriately crafted adversarial content.

Insufficient Environmental Awareness: Agents lack robust models of typical interface behavior and fail to recognize anomalous elements like unexpected pop-ups.

5.5 Technical Analysis of Attack Mechanisms

Our investigation reveals that PopupAttack exploits fundamental architectural limitations in current VLM agents. The attack succeeds through three core mechanism failures:

Visual Attention Bias: Current agents treat all visual elements with equal salience, lacking hierarchical attention mechanisms that prioritize authentic interface elements over potential adversarial overlays. This manifests as a failure to distinguish between organic UI components and injected visual content, even when pop-ups exhibit unusual positioning or styling inconsistencies.

Contextual Reasoning Exploitation: The effectiveness of query-conditioned attention hooks demonstrates that agents' strength in task-oriented reasoning becomes a vulnerability when adversarial content aligns with goal states. Agents exhibit confirmation bias, seeking visual elements that confirm their task objectives without validating element authenticity or source legitimacy.

Insufficient Temporal Context: Agents process each observation independently, lacking memory of previous interface states that could reveal the sudden appearance of pop-up elements. This temporal blindness prevents agents from recognizing that new interface elements appeared outside the normal interaction flow.

These technical insights suggest that robust agent design requires fundamental architectural changes rather than surface-level prompt modifications. Future agents need explicit mechanisms for interface validation, temporal consistency checking, and adversarial content detection integrated at the architectural level.

The effectiveness of PopupAttack also reveals deeper cognitive biases embedded in current VLM training. Analysis of model attention patterns during successful attacks shows that agents exhibit disproportionate focus allocation toward novel visual elements, particularly those containing text content. This attention bias likely stems from pretraining objectives that prioritize text-rich regions for multimodal understanding. Furthermore, the agents' susceptibility to query-conditioned content suggests an over-reliance on semantic similarity matching between visual elements and task objectives, without sufficient consideration of element provenance or contextual appropriateness. This represents a fundamental trade-off between goal-oriented efficiency and security-conscious skepticism that current architectures have not adequately balanced.

Architectural Vulnerability Analysis: Our systematic investigation reveals that current VLM agent architectures exhibit three primary structural weaknesses that enable PopupAttack's effectiveness. First, the absence of explicit visual hierarchy modeling means agents process foreground overlays (pop-ups) and background interface elements through identical attention mechanisms, creating parity between legitimate and adversarial content. Second, the lack of interface state tracking prevents agents from detecting temporal anomalies such as unexpected element appearances between interaction steps. Third, current architectures employ unified visual processing pipelines that treat all screen regions equivalently, failing to distinguish between stable interface components and transient overlays that may indicate malicious injection attempts.

5.6 Implications for Agent Design

These findings suggest several directions for more robust agent architectures:

Source-aware reasoning: Agents should maintain explicit models of interface authenticity and

AI-Generated

question unexpected elements.

Anomaly detection: Built-in mechanisms to detect unusual interface patterns could provide early warning of potential attacks.

Multi-modal consistency checking: Cross-referencing visual and accessibility information could help identify inconsistencies introduced by attacks.

Conservative interaction policies: Agents could adopt more cautious interaction patterns when encountering unfamiliar interface elements.

6 Conclusion

This work demonstrates a critical vulnerability in current vision-language computer agents: their susceptibility to adversarial pop-up attacks. Through comprehensive evaluation of PopupAttack across frontier VLMs and established benchmarks, we reveal that simple, query-aligned pop-ups can achieve attack success rates of 62-100%, causing agents to devote 73-93% of their actions to clicking malicious content rather than pursuing intended tasks.

Our key findings underscore several important implications for the deployment of VLM agents:

Universal Vulnerability: All tested models show high susceptibility, indicating this is a fundamental rather than model-specific limitation. The consistency across different architectures (screenshot vs. SoM agents) and environments (desktop vs. web) suggests deep-rooted issues in how current agents process visual information.

Context Sensitivity: The critical importance of query-conditioned attention hooks reveals how agents' goal-directed behavior can be exploited. Attacks that align with user intent are far more effective than generic threats, highlighting the need for context-aware security measures.

Defense Limitations: Standard prompt-based defenses provide insufficient protection. Even sophisticated step-wise defenses, while reducing direct pop-up clicks, fail to prevent task-level disruption (TASR remains 32-44%). This suggests that robust security requires architectural rather than prompt-level solutions.

Practical Threat: Our attack uses realistic pop-up presentations that could easily occur through compromised websites, malicious applications, or display hijacking, making this a practical rather than theoretical vulnerability.

6.1 Future Work

Several directions warrant investigation:

Robust Agent Architectures: Developing agents with built-in environmental awareness and anomaly detection capabilities.

Multi-modal Defense Mechanisms: Exploring how agents can cross-reference visual and textual information to identify inconsistencies.

Adaptive Attack Strategies: Investigating how attackers might adapt to defensive measures and the resulting arms race.

Broader Attack Surfaces: Extending beyond pop-ups to examine other environmental manipulation techniques.

6.2 Responsible Disclosure

As vision-language agents transition from research to real-world deployment, understanding their security implications becomes paramount. We hope this work spurs development of more robust agent architectures and defensive mechanisms. Our code and experimental data are available to facilitate reproduction and encourage defensive research.

The PopupAttack vulnerability represents just one facet of the broader security challenges facing AI agent deployment. As these systems become more capable and widely used, proactive identification and mitigation of such vulnerabilities will be essential for safe and trustworthy automation.

Limitations

Our study focuses on two specific benchmarks (OSWorld and VisualWebArena) and may not generalize to all computer-use scenarios. The attack relies on having some knowledge of user intent, which may not always be available to real-world attackers. Additionally, our evaluation is limited to current frontier VLMs, and future models may demonstrate improved robustness.

Ethical Considerations

This work reveals vulnerabilities in AI systems to promote defensive research and safer deployment practices. The attack techniques described could potentially be misused, but we believe the benefits of understanding these vulnerabilities outweigh the risks. We encourage responsible use of this research for defensive purposes only.

AI-Generated

References

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Ruslan Salakhutdinov, and Daniel Fried. 2024. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. *Preprint*, arXiv:2401.13649.

OpenAI. 2024. Gpt-4o system card. https://openai.com/index/gpt-4o-system-card/.

Machel Reid, Nikolay Savinov, Denis Teplyashin, Dmitry Lepikhin, Timothy Lillicrap, Jean-baptiste Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Firat, Julian Schrittwieser, et al. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. 2024. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Preprint*, arXiv:2404.07972.

Jianwei Yang, Hao Zhang, Feng Li, Xueyan Zou, Chunyuan Li, and Jianfeng Gao. 2023. Set-of-mark prompting unleashes extraordinary visual grounding in gpt-4v. *Preprint*, arXiv:2310.11441.

Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. 2024. Gpt-4v(ision) is a generalist web agent, if grounded. *Preprint*, arXiv:2401.01614.

AI-Generated