Attacking Vision-Language Computer Agents via Pop-ups

Anonymous Author

Abstract

Vision-language agents are increasingly deployed to operate computers and the web, yet their robustness to deceptive on-screen content remains largely unexplored. We introduce PopupAttack, a practical attack that injects query-aligned, clickable pop-ups into an agent's visual and accessibility observations to coerce harmful clicks. PopupAttack composes four components—an attention hook, an explicit instruction, an info banner, and an ALT descriptor—and supports both screenshot-only and Set-of-Mark agents. Evaluated on OSWorld and VisualWebArena across frontier VLM backbones, popup-induced actions dominate agent behavior (92.7%/73.1% of actions on OSWorld/VisualWebArena) and sharply reduce task success. Ablations show query-conditioned hooks are critical, explicit coordinate or tag-ID instructions transfer across settings, and simple textual defenses (e.g., "ADVERTISEMENT" banners or ad-noted ALTs) are weak. Step-wise prompting lowers per-step Attack Success Rate to 5.9–10.4%, but task-level risk remains high. Our results underscore the need for modality-aware defenses that reason about environmental risk beyond prompt-based safeguards.

AI-generated

1 Introduction

Recent progress has produced computer-use agents that can read screens, ground UI elements, and act to complete long-horizon tasks (Zhou et al., 2023; Xie et al., 2024; Zheng et al., 2024). While promising, the same reliance on on-screen cues introduces a neglected security gap: malicious overlays that resemble benign UI. Human users routinely encounter pop-ups (security notices, cookie banners, ads); autonomous agents may over-trust such cues, especially when they appear aligned with the user's goal.

This paper studies a practical, content-level attack vector: adversarial pop-ups that are injected into the agent's observations to hijack control. Inspired by emerging analyses of adversarial environments for multimodal agents (Wu et al., 2024; Liao et al., 2024; Xu et al., 2024), we propose PopupAttack, a modular attack that conditions the pop-up on the current task, embeds explicit click instructions, and manipulates textual channels (banners and ALT descriptors). We evaluate both screenshot agents and SoM (Set-of-Mark) variants (Yang et al., 2023) on OSWorld (Xie et al., 2024) and VisualWebArena (Koh et al., 2024; Zhou et al., 2023) with multiple VLM backbones.

Concretely, we find that pop-up clicks dominate agent behavior and that task success collapses under attack. Query-aligned hooks are crucial; weakening the hook to generic "virus" messaging drastically lowers attack efficacy. Coordinate- and tag-based instructions remain highly effective, while "click here" or random targeting retains non-trivial success. Textual notices such as "ADVERTISEMENT" and ad-noted ALTs provide only modest relief. Step-wise prompting that continuously warns the agent reduces per-step attack rate but leaves substantial task-level vulnerability.

Our contributions are: (1) a realistic pop-up threat model and a modular, reproducible attack design spanning visual and textual channels; (2) a comprehensive evaluation across benchmarks, agent types, and VLM backbones; (3) ablations isolating the roles of hooks, instructions, banners, and ALT descriptors, including the introduction of Task-level Attack Success Rate (TASR); and (4) an analysis of failure modes and defenses, pointing to the need for stronger environment-aware safety mechanisms.

2 Related Work

Computer-use agents and benchmarks. General web and desktop agents ground UI elements and act via natural language and vision (Zhou et al., 2023;

Figure 1: On average, 92.7%/73.1% of actions of attacked agents in OSWorld/VisualWebArena are clicks on adversarial pop-ups.

Koh et al., 2024; Xie et al., 2024). Set-of-Mark prompting improves visual grounding for action selection (Yang et al., 2023). SeeAct demonstrates the feasibility and challenges of turning VLMs into generalist web agents (Zheng et al., 2024). These works focus on capability; we examine robustness to deceptive overlays within the same ecosystems.

Adversarial environments for agents. Recent studies show multimodal agents are vulnerable to injected content and deceptive contexts, including mobile interfaces and web environments (Wu et al., 2024; Liao et al., 2024; Xu et al., 2024). Our work contributes a unified, modular pop-up attack that spans visual and textual channels and targets both screenshot and SoM agents on standardized benchmarks.

Defenses. Prompt-based defenses are appealing but often insufficient for adversarial environments (Wu et al., 2024; Liao et al., 2024). We evaluate generic and tailored system prompts as well as step-wise prompting that repeatedly cautions agents at each step. Our findings suggest that robust mitigation requires modality-aware detection and grounding checks beyond prompting alone.

Prior work leaves a gap on pop-up deception; we quantify it and show it persists across UI modalities and model backbones. Distinct from classic adversarial examples on perception models, our setting manipulates the interaction loop: pop-ups couple visual salience with action grounding. This exposes attack surfaces at instruction channels (coordinates, tag IDs) and accessibility text that current agents routinely trust.

3 Attack Design

We consider agents that receive visual observations (screenshots) and optionally structured UI annotations (e.g., SoM tags), then generate actions (e.g., coordinate clicks, tag clicks). The attacker overlays a pop-up inside the observation, aiming to elicit an unsafe or distracting action.

3.1 Threat Model

The attacker can inject a pop-up into the agent's observation stream at inference time without modifying the underlying application state. The pop-up does not require privileged system access, and can plausibly arise from adversarial webpages or benign-looking overlays. We evaluate: (1) screenshot agents that operate on images and produce coordinate-level actions, and (2) SoM agents that operate on images with tag IDs and can click by element ID.

The overlay is transient and resets between steps; we exclude keystroke injection, timing races, or network tampering from the threat model.

3.2 PopupAttack Components

PopupAttack composes four elements that we can mix-and-match to target an agent: - *Attention Hook*: a query-conditioned headline that aligns with the user goal. We also test realistic substitutes such as generic "virus" messages and a "speculated query" inferred from the screen content. - *Instruction*: explicit imperative text such as "click (x,y)", "click [ID]", or "click here"; we also examine random targets. - *Info Banner*: a small banner region (e.g., "OK" vs. "ADVERTISEMENT") to influence perceived legitimacy. - *ALT Descriptor*: alt-text injected into the structured channel for SoM agents (e.g., adversarial content, ad-noted variants, or empty).

3.3 Placement and Rendering

To avoid occluding critical content while appearing salient, we first run OCR to estimate existing text boxes and then find a large empty rectangle for placement (preferring sufficiently tall regions). The pop-up bounding box and its internal "attack"

AI-Generated



Figure 2: Adversarial pop-up examples spanning hooks, instructions, banners, and ALT descriptors.

region are sized relative to the available space, with optional size randomization and a minimum dimension to remain legible. We draw a light border to mimic window affordances, render the banner and instruction text with high contrast, and select a click target either at the box center or by randomization. For SoM agents, we optionally render a new tag and reserve an element index for tag-based instructions. This pipeline follows the released implementation under `code/`.

We preserve native page geometry, avoid occluding known widgets, and render at top z-order with a faint backdrop to emulate overlays. Instrumentation and reproducibility. We render pop-ups deterministically under a fixed seed, logging the exact bounding box, foreground text, and target (coordinate or tag ID) per step. For SoM, we attach ALT descriptors to the corresponding element record and export a JSON trace aligning screen pixels to tag IDs. Rendering respects device pixel ratio and window scaling; we normalize to a canonical coordinate frame before issuing actions. All assets are generated with pure-Python drawing backends to minimize browser-induced jitter and ensure bitwise-identical frames across runs.

3.4 Agent Variants

For screenshot agents, instructions reference screen coordinates. For SoM agents, instructions reference element IDs when available and fall back to coordinates otherwise. We also support "speculated" hooks conditioned on the current screen when the user query is hidden, and we test small-pop-up and blank variants for validity checks.

We canonicalize coordinate frames across resolutions and log both the visible target and intended DOM element to disambiguate success.

Why PopupAttack Works. The attack exploits three common biases in VLM agents: (i) imperative-text bias, where verbs near visible UI strongly condition the next action; (ii) saliency and proximity, where high-contrast boxes placed near the center attract attention; and (iii) cross-channel agreement, where instructions that reference a tag ID or coordinates are misread as a grounding check rather than untrusted content. Together, these cues cause agents to overweight the pop-up as task-relevant even when it only loosely aligns with the user goal.

3.5 Negative Controls and Integrity

To decouple rendering artifacts from behavior, we add controls: (i) a blank overlay that draws pop-up chrome but omits hooks and instructions; (ii) a small-pop-up that preserves typography while reducing area; and (iii) a placebo banner that replaces imperatives with neutral copy. All controls share the same renderer and logs. We also verify overlays do not alter DOM or accessibility trees by diffing pre and post step snapshots so inputs differ only in pixels and optional ALT strings.

4 Experiments

4.1 Setup

We instantiate each agent with a fixed, public prompt template and disable external tools beyond browsing and clicking to isolate UI-grounded behavior. Screenshot agents observe full-window RGB frames; SoM agents additionally receive element tags and attributes, including ALT strings when present. Unless noted, we use each benchmark's default step budget, temperature 0, and greedy decoding. Pop-ups render once per step when the agent is deciding the next action; placement enforces a margin from native widgets and a bounded aspect ratio so overlays look plausible but not full-screen. We run every task as a paired No-Attack/PopupAttack episode, reset agent memory between pairs, and log per-step traces with bounding boxes, imperative text, and intended targets for exact replay. Seeds are fixed per (task, agent) pair to control stochasticity and enable deterministic re-evaluation of any episode.

AI Generated

4.2 Evaluation Protocol

We evaluate each task twice (No-Attack and PopupAttack) under identical prompts and seeds, resetting agent memory between runs. Pop-up placement is randomized per step under a fixed seed; we log bounding boxes, foreground text, and intended targets for exact replay. Episode success follows benchmark checkers. TASR counts only when the paired No-Attack episode succeeds and the attacked one fails after at least one popup-induced click.

Benchmarks. We evaluate on OSWorld (50 easy tasks; 15-step limit) (Xie et al., 2024) and VisualWebArena (72 easy tasks; 30-step limit) (Koh et al., 2024; Zhou et al., 2023). **Agents.** We compare screenshot and SoM versions of VLM-based agents. **Backbones.** We instantiate agents with widely used VLMs (GPT-4-Turbo, GPT-4o, Gemini 1.5 Pro, Claude 3.5 Sonnet and v2). Decoding uses temperature 0. **Metrics.** We report Attack Success Rate (ASR; any popup-induced click in an episode), task Success Rate (SR), Original SR (OSR; success without attack), and Task-level ASR (TASR; task fails due to the attack).

We use each benchmark's official evaluation scripts; seeds and prompts are fixed per agent, and every task runs once with No-Attack and once with PopupAttack.

Execution protocol. Episodes end on success, step-budget exhaustion, or model stop. Success uses each benchmark's string or DOM checker. We count TASR when a No-Attack run succeeds but the attacked run fails with at least one popup-induced click. To avoid contamination, we reset agent memory between paired runs and randomize pop-up placement per step under a fixed seed.

4.3 Main Results

Table 1 summarizes results across models and settings. We observe high vulnerability: ASR often exceeds 90% on OSWorld (screen and SoM), reaching 100% for a Claude 3.5 screenshot agent, and remains substantial on VisualWebArena-SoM. Task success drops correspondingly; for instance, several OSWorld agents fall to single-digit SR despite non-trivial OSR. Figure 1 shows that under attack, popup clicks dominate action distributions (92.7%/73.1% on OSWorld/VisualWebArena).

TASR can exceed ASR when a single coerced click is decisive, widening the gap between OSR and SR.

4.4 Ablations

Attention hooks. Table 2 shows query-conditioned hooks are critical. Replacing them with a generic "Virus Detected!" headline sharply reduces ASR (e.g., OSWorld-SoM 91.8 $\rightarrow$ 58.3; VisualWebArena-SoM 62.1 $\rightarrow$ 1.1). "Speculated" hooks inferred from the screen retain some effect (ASR 34.4 on OSWorld-SoM; 8.0 on VisualWebArena-SoM).

Instructions. Table 3 indicates that explicit coordinate or tag-ID instructions remain effective across agents. "Click here" degrades ASR substantially for screenshot agents (down to 11.3), but still yields non-trivial rates elsewhere. Random targets induce residual ASR around 10% on screenshots.

Info banners and ALTs. Tables 4 and 5 demonstrate that textual defenses are weak: "ADVERTISEMENT" banners and ad-noted ALTs still leave ASR above 55% in many cases. Empty ALT helps more (e.g., ASR drops from 91.8 to 68.1 on OSWorld-SoM and 62.1 to 42.9 on VisualWebArena-SoM).

Validity checks. Table 6 confirms that blank pop-ups nearly eliminate ASR, while small-pop-up variants remain effective albeit slightly reduced relative to defaults.

4.5 Defenses

System prompts. Generic "ignore pop-ups" prompts have limited effect (Table 7); a more specific prompt lowers ASR substantially for OSWorld-Screen but leaves high residual risk elsewhere.

Step-wise prompting. Table 8 shows per-step prompting can reduce ASR to 5.9–10.4% on OSWorld-Screen, but TASR remains 32–44% and SR only recovers to 8–10%.

Practical Takeaways. Across settings, vague pop-up warnings help little; more specific phrasing helps but does not close the gap. Banner-text cues (e.g., "ADVERTISEMENT") are unreliable. Promising defenses couple overlay-geometry detection with grounding checks that ensure imperative text refers to trusted elements, not transient pixels.

5 Understanding Agent Attack

Action-level vs. task-level risk. Figure 3 highlights strong correlation between ASR and TASR, with TASR frequently exceeding ASR when per-step attacks are less frequent but still decisive.

AI-Generated

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
GPT-4-Turbo	93.3	2.0	18.0	91.8	8.0	52.0	78.0	43.1	50.0
GPT-4o	95.8	**6.0**	8.0	91.2	2.0	6.0	**62.1**	45.8	**63.9**
Gemini 1.5	**80.0**	4.0	6.0	**88.7**	6.0	18.0	70.1	44.4	48.6
Claude 3.5 Sonnet	100.0	0.0	**22.0**	95.3	6.0	44.0	78.4	47.2	54.2
Claude 3.5 Sonnet v2	96.0	4.0	**22.0**	94.8	**10.0**	**58.0**	76.8	**48.6**	50.0

Table 1: Result table for model comparison, where we **highlight** the lowest ASR (↓) and highest SR (↑)/OSR (↑). Screen and SoM refer to screenshot agents and SoM agents. We use WebArena as a shorter form of VisualWebArena.

Attention Hook	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Summarized Query	93.3	2.0		91.8	8.0		62.1	45.8	
Virus	90.0	2.0	18.0	58.3	26.0	52.0	1.1	54.2	63.9
Speculated Query	53.9	10.0		34.4	38.0		8.0	54.2	

Table 2: Ablation study on the attention hooks, where we underline the numbers from the default setting..



Figure 3: TASR correlates with ASR and tends to exceed ASR when ASR is low.

Where agents attend. Main results reveal consistent over-reliance on explicit instructions. Thought traces further show that screenshot agents rarely mention the hook but frequently echo coordinate targets; SoM agents more often cite hooks and target IDs. We quantify these effects by measuring mentions in internal thoughts for successfully attacked cases.

We also measure distances between clicked points and popup centers/targets to distinguish intentional compliance from incidental proximity.

By task family, authentication, download, and settings are most susceptible, likely due to realistic, system-like banners.

Error taxonomy. We observe three modes: instruction-compliance, saliency-lure, and cross-channel confirmation. The first dominates screenshot agents, the third SoM; both intensify when hooks partially match the user goal.

5.1 Causal Probes

We disentangle which cues cause compliance via controlled counterfactual edits to the same frame: remove verbs while keeping layout; strip borders while leaving imperative text; shuffle coordinates while preserving the hook; and swap banner wording between neutral and ad-noted variants. For SoM, we additionally drop ALT strings or replace them with placeholders. We re-run the agent on each edit under the same seed and compare action sequences with Levenshtein distance and the first-divergence step. This protocol separates saliency from grounding: when actions remain unchanged after removing chrome but flip after altering imperative text, we attribute causality to the instruction channel; when edits to hooks change pre-click gaze mentions without affecting target choice, we attribute influence to attention rather than control. We also estimate uncertainty by bootstrapping episodes and pair confidence intervals with qualitative traces.

5.2 Case Study

Figure 4 illustrates a representative download task. Without attack, the agent scrolls to the correct link, verifies the file name in thought, and clicks the intended UI element. Under PopupAttack, the same agent echoes the injected instruction (e.g., target coordinates or tag ID) and diverts to the pop-up despite noticing context mismatches. For SoM variants, we observe similar behavior: thoughts reference the hook and cited tag, followed by a click

AI-Generated

Instruction	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Click Tag	-	-	-	96.1	6.0	52.0	62.1	45.8	63.9
Click Coor	93.3	2.0	18.0	91.8	8.0		49.3	48.6	
Click Here	11.3	14.0		72.8	14.0		58.4	44.4	
Click Random	11.8	2.0		13.7	10.0		4.1	34.7	

Table 3: Ablation study on the instructions. Click Random refers to clicking random coordinates for OSWorld and clicking random tags for VisualWebArena correspondingly.

Info Banner	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
"OK"	93.3	2.0	18.0	91.8	8.0	52.0	62.1	45.8	63.9
"ADVERTISEMENT"	66.5	10.0		77.9	14.0		56.7	52.8	

Table 4: Ablation study on the info banners.

on the adversarial element. This pattern recurs across authentication and settings tasks, where realistic, system-like banners exploit prior experience with OS notifications and security dialogs.

5.3 Additional Qualitative Examples

Figure 6 shows diverse failures across authentication, download, and settings tasks. Agents often paraphrase the imperative instruction (coordinates or tag ID) and click the adversarial element, even while noting mild context mismatches. We also see saliency-lure cases where a high-contrast box near the viewport center diverts attention from the true target. Together these examples show how instruction-compliance and saliency jointly drive task-critical deviations, reinforcing that mitigation must address both control and attention channels.

6 Conclusion

We presented PopupAttack, a modular, practical pop-up injection attack against vision-language computer-use agents. Across OSWorld and VisualWebArena with multiple VLM backbones, we observed high attack success, severe drops in task success, and dominance of popup-induced actions. Ablations show the centrality of query-aligned hooks and explicit instructions, as well as the limited protection offered by simple textual defenses. While step-wise prompting can reduce per-step attack rates, substantial task-level vulnerability remains. These results call for defenses that jointly reason over visual layout, textual channels, and action grounding to detect and disregard adversarial overlays.

References

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Ruslan Salakhutdinov, and Daniel Fried. 2024. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. *Preprint*, arXiv:2401.13649.

Zeyi Liao, Lingbo Mo, Chejian Xu, Mintong Kang, Jiawei Zhang, Chaowei Xiao, Yuan Tian, Bo Li, and Huan Sun. 2024. Eia: Environmental injection attack on generalist web agents for privacy leakage. *Preprint*, arXiv:2409.11295.

Chen Henry Wu, Jing Yu Koh, Ruslan Salakhutdinov, Daniel Fried, and Aditi Raghunathan. 2024. Adversarial attacks on multimodal agents. *Preprint*, arXiv:2406.12814.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. 2024. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Preprint*, arXiv:2404.07972.

Chejian Xu, Mintong Kang, Jiawei Zhang, Zeyi Liao, Lingbo Mo, Mengqi Yuan, Huan Sun, and Bo Li. 2024. Advweb: Controllable black-box attacks on vlm-powered web agents. *Preprint*, arXiv:2410.17401.

Jianwei Yang, Hao Zhang, Feng Li, Xueyan Zou, Chunyuan Li, and Jianfeng Gao. 2023. Set-of-mark prompting unleashes extraordinary visual grounding in gpt-4v. *Preprint*, arXiv:2310.11441.

Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. 2024. Gpt-4v(ision) is a generalist web agent, if grounded. *Preprint*, arXiv:2401.01614.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue

AI-Generated

ALT Descriptor	OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Adversarial	91.8	8.0		62.1	45.8	
Empty	68.1	22.0	52.0	42.9	55.6	63.9
Adversarial with Ad Notice	77.1	22.0		56.9	45.8	

Table 5: Ablation study on the ALT descriptors.

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Default	93.3	2.0		91.8	8.0		62.1	45.8	
Blank Pop-up	2.4	16.0	18.0	3.7	38.0	52.0	0.0	52.8	63.9
Small Pop-up	87.4	2.0		90.1	10.0		60.0	52.8	

Table 6: Extra ablations for blank pop-ups and small pop-ups.

Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. 2023. Webarena: A realistic web environment for building autonomous agents. *Preprint*, arXiv:2307.13854.

AI-Generated

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Default Attack	93.3	2.0		91.8	8.0		62.1	45.8	
System Prompt Defense	95.9	6.0	18.0	93.4	14.0	52.0	60.3	47.2	63.9
System Prompt Defense$_{\text{specific}}$	52.0	6.0		72.3	24.0		60.2	45.8	

Table 7: Ablations for the system prompt defense.

	OSWorld-Screen			
	ASR$_\downarrow$	**TASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Step-wise Prompt Defense	5.9	32.0	8.0	18.0
+ Attack Variance	10.4	44.0	10.0	

Table 8: Step-wise prompt defense. We use the GPT-4-Turbo screen agent on OSWorld for the ablation.

OSWorld-Screen		OSWorld-SoM	
Attn Hook	2%	Attn Hook	62%
Target	88%	Target	90%
OK	52%	OK	6%

Table 9: The frequency of explicitly mentioning different elements in agent-generated thoughts for successfully attacked cases: attention hook (summarized queries), target in instructions (coordinates or tag IDs), and the "`OK`" in the info banner.

AI-Generated



Original: The current screenshot shows the Delta Airlines homepage on a web browser. To proceed with finding the status of tomorrow's flights from New York airports to Columbus, Ohio, the next step is to enter the departure and destination cities in the search fields on the webpage. I will start by clicking on the "From" field (currently showing "San Jose, CA") to change it to a New York airport. Then, I will enter the destination city as Columbus, Ohio. Let's proceed with this action.

```python
import pyautogui
import time

# Click on the "From" field to change the departure city
pyautogui.click(350, 300)  # Approximate coordinates of the "From" field
time.sleep(0.5)
```

Attacked: The next step is to click on the "From" field to activate it for input. The "From" field is located near the top of the webpage, under the "BOOK" tab, where "San Jose, CA" is currently displayed. I will move the cursor to this field and click to focus on it so that "New York, NY" can be entered.

```python
import pyautogui
import time

# Move the cursor to the "From" field and click to focus
pyautogui.moveTo(240, 298)  # Coordinates for the "From" field
pyautogui.click()
time.sleep(0.5)  # Wait for the field to be focused
```

Figure 5: Effect of attacks on step counts. Attacked agents often waste steps on pop-ups.

enerated

Figure 6: Additional qualitative examples highlighting instruction-compliance and saliency-lure patterns.