PopupAttack: Attacking Vision-Language Computer Agents via Pop-ups

Anonymous Authors

Abstract

Vision-language computer agents increasingly interact with real operating systems and websites, but their robustness to deceptive interface elements remains poorly understood. We study a practical attack surface: malicious pop-ups injected into the agent's observation stream. We propose PopupAttack, a modular attack that overlays a clickable pop-up with four controllable components: a query-aligned attention hook, an explicit click instruction, an info banner, and a textual descriptor that can also enter accessibility-based observations. Across 50 OSWorld tasks and 72 VisualWebArena tasks, using screenshot and Set-of-Mark agents with five frontier multimodal models, PopupAttack reaches an average attack success rate of 86.2 while reducing attacked task success from 34.7 to 18.5 on average, a 46.8% relative drop. The strongest attacks are query-conditioned and instruction-bearing, while simple text disclosures such as "ADVERTISEMENT" only partially help. Prompt-only defenses are weak, and even a stronger step-wise defense lowers per-step attack success without removing substantial task-level risk. These results show that query-aligned pop-ups are a realistic and effective control channel for hijacking computer-use agents, and that robust deployment will require defenses that reason explicitly about the trustworthiness of on-screen content.

AI-Generated

1 Introduction

Vision-language agents are starting to act directly on computers and websites, turning screenshots, accessibility trees, and web markup into concrete actions such as clicking, typing, and navigating (Xie et al., 2024; Koh et al., 2024; Zheng et al., 2024; Cheng et al., 2024; Agashe et al., 2024; Qin et al., 2025; Xu et al., 2024b). This setting makes progress on grounded autonomy visible, but it also changes the attack surface. Unlike a pure chatbot, a computer-use agent consumes a dynamic environment that may itself contain deceptive visual or textual content.

This paper studies a simple but consequential instance of that threat: adversarial pop-ups. Pop-ups are common in everyday browsing and desktop use, and they often solicit an immediate click. For humans, such overlays are a familiar source of scams and coercion. For agents, they are especially dangerous because they appear in the same modality as the task-relevant interface, can mimic ordinary UI affordances, and can be aligned to the user's goal. If an agent treats an attacker-controlled pop-up as trusted task guidance, the environment can redirect behavior without modifying the user prompt or the agent's internal prompt.

Prior work has shown that agents are vulnerable to environment injection, indirect prompt injection, and broader environmental distractions (Wu et al., 2024; Liao et al., 2024; Xu et al., 2024a; Zhan et al., 2024; Ma et al., 2024; Wallace et al., 2024). However, existing studies largely focus on mobile agents, text-centric web manipulations, or generic distracting content. We target a more practical and lower-friction vector for GUI agents: a visually salient, clickable pop-up that simultaneously exploits screenshot observations and, when available, structured textual channels such as Set-of-Mark (SoM) tags and accessibility text.

We propose PopupAttack, a modular attack that injects a malicious pop-up into the agent observation. The attack has four components. An *attention hook* aligns the pop-up with the user's intent; an *instruction* tells the agent what to click; an *info banner* makes the overlay resemble a benign or urgent UI widget; and an *ALT descriptor* lets the attack transfer into text-augmented observation pipelines. The implementation in the provided code places the pop-up in a large unoccupied region of the screen, randomizes its size within feasible bounds, and targets either coordinates or a reserved SoM tag. This

Figure 1: Overview of PopupAttack. The injected pop-up captures the agent's action stream; attacked agents spend 92.7% of actions on OSWorld and 73.1% on VisualWebArena clicking it on average.

design supports both "ideal" attacks with explicit query summaries and precise targets, and more realistic variants such as virus warnings, guessed intent, vague "click here" prompts, random targets, and ad disclosures.

We evaluate PopupAttackon OSWorld (Xie et al., 2024) and VisualWebArena (Koh et al., 2024), using screenshot and SoM agents with GPT-4-Turbo, GPT-4o, Gemini 1.5 Pro, Claude 3.5 Sonnet, and Claude 3.5 Sonnet v2 (Achiam et al., 2023; OpenAI, 2024; Reid et al., 2024; Anthropic, 2024). The attack is consistently effective: the average attack success rate (ASR) across benchmark-model settings is 86.2, with OSWorld screenshot ASR reaching 100.0 and OSWorld SoM ASR remaining above 88 for all tested models. These action-level failures translate into large task degradation: average attacked success rate drops by 46.8% relative to the original success rate, and OSWorld success falls to at most 10.0 under attack.

Our contributions are:

- We formulate a practical pop-up threat model for vision-language computer agents and propose PopupAttack, a modular attack spanning both visual and text-augmented observation channels.
- We provide a broad empirical evaluation across OSWorld and VisualWebArena, screenshot and SoM agents, and five frontier multimodal backbones, showing consistently high vulnerability.
- We analyze which pop-up components matter, introduce task-level ASR (TASR) to complement

action-level ASR, and show that prompt-only defenses leave substantial residual risk.

2 Related Work

2.1 Vision-Language Computer Agents

Recent work has rapidly expanded agentic interaction with graphical interfaces. OSWorld provides a general computer benchmark spanning desktop and web tasks (Xie et al., 2024); WebArena and VisualWebArena study realistic web interaction in reproducible environments (Zhou et al., 2023; Koh et al., 2024); and systems such as SeeAct, SeeClick, Agent S, UI-TARS, and Aguvis explore different tradeoffs between textual structure, screenshot grounding, and end-to-end visual control (Zheng et al., 2024; Cheng et al., 2024; Agashe et al., 2024; Qin et al., 2025; Xu et al., 2024b). Our work is orthogonal to these efforts: instead of improving capability, we test whether high-performing computer agents can distinguish trustworthy interface content from attacker-controlled overlays.

2.2 Prompt Injection and Environment Attacks on Agents

Security work on agents has emphasized indirect prompt injection and environment-based manipulation. InjecAgent benchmarks text-based prompt injections for tool-using LLM agents (Zhan et al., 2024), and the instruction hierarchy line of work argues that robustness requires models to distinguish privileged instructions from untrusted external content (Wallace et al., 2024). For multimodal or embodied agents, Wu et al. study adversarial attacks on Android agents through active environment injection (Wu et al., 2024); Liao et al. introduce Environmental Injection Attack for privacy leakage in web agents (Liao et al., 2024); and AdvWeb studies controllable black-box attacks on VLM-powered web agents (Xu et al., 2024a). Our threat model is narrower and more deployable: we focus on a single injected pop-up that appears as ordinary GUI content, requires no access to the agent prompt, and can simultaneously target screenshot and SoM-style observations.

2.3 Environmental Distraction and Deceptive UI

Concurrent work shows that multimodal agents can be distracted by irrelevant environmental context even when the environment is not malicious (Ma et al., 2024). Outside agent security, deceptive interface elements such as fake alerts and misleading ads are a long-standing web security and usability problem, and advertising disclosures have been studied precisely because users can mistake promotional content for ordinary UI (Commission et al., 2013). Our results extend these concerns to autonomous agents: when the deceptive content is explicitly aligned to the user objective and contains an action instruction, agents often treat it as legitimate guidance rather than suspicious external content.

3 PopupAttack

3.1 Threat Model

We consider a user who gives a benign task instruction to a computer-use agent. The attacker cannot modify the user request or the model weights, but can inject a pop-up into the environment seen by the agent. Depending on the agent interface, the pop-up may appear only in the screenshot, or in both the screenshot and a text-augmented channel such as a linearized accessibility tree or SoM listing. The attacker succeeds if the agent follows the malicious pop-up rather than the intended task, measured at the action level (ASR) and the task level (TASR).

This threat model is realistic for both desktop and web settings. Pop-ups can be rendered by a compromised webpage, advertisement slot, extension, or untrusted application window. Importantly, the attack does not require privileged access to the agent internals; it only exploits the fact that the environment is part of the model input.

3.2 Attack Construction

The released implementation injects a bordered rectangular pop-up into a large non-overlapping region of the current observation. For screenshot agents, it first tags the current screen to estimate occupied regions, then places the pop-up in a large empty rectangle. For SoM agents, the attack also reserves an additional tag index and updates the text representation so that the pop-up becomes actionable through the structured channel as well.

Each pop-up is built from four components:

- **Attention hook.** A short title designed to capture the agent's attention. In the default setting, the hook is a summarized version of the user query generated by a helper model. The code also supports a guessed-intent variant based on current

AI-Generated



Figure 2: Examples of adversarial pop-ups used by PopupAttack, varying the hook, instruction, banner text, and textual descriptor.

screen content and a generic "Virus Detected!" hook.

- **Instruction.** The pop-up tells the agent what to do next, such as clicking specific coordinates, clicking a reserved SoM tag, clicking "here," or moving to a target. The default attack uses explicit click targets.
- **Info banner.** A narrow banner makes the overlay resemble a regular widget. The default banner says "OK," while a disclosure-style variant says "ADVERTISEMENT."
- **ALT descriptor.** For text-augmented pipelines, the pop-up can be inserted into the structured observation with adversarial text, an empty descriptor, or an ad-noted descriptor such as "ADVERTISEMENT: ...".

The injected target is normally the center of the pop-up box for screenshot agents or a reserved tag for SoM agents. The implementation also supports randomized targets as a realism check. To avoid degenerate placements, the code skips attack rounds when the available empty region is too small or when the screen appears to be a uniform color image.

3.3 Default and Realistic Variants

Our default attack is intentionally strong: it uses a query-conditioned attention hook, an explicit click target, an "OK" banner, and an adversarial textual descriptor when a text channel is available. We then study more realistic variants that weaken one component at a time: a virus-warning hook instead of query alignment, guessed intent instead of true intent, vague instructions such as "Please click here," random targets, disclosure-style banners, and less helpful ALT text. These variants let us separate what is essential for attack transfer from what merely improves the attack.

3.4 Metrics

We report four metrics. **ASR** is the action-level attack success rate, computed from logs as the fraction of attack opportunities in which the agent actually selects the adversarial pop-up. **TASR** is the task-level attack success rate, i.e., the fraction of tasks with at least one successful adversarial click. **SR** is the end-to-end task success rate under attack, and **OSR** is the original task success rate without attack on the same evaluation setting. ASR captures how often the pop-up successfully redirects an action; TASR captures how often a task is compromised at least once, even if the per-step ASR is low.

4 Experimental Setup

4.1 Benchmarks and Agents

We evaluate on the released easy-task subsets for OSWorld and VisualWebArena. OSWorld contains 50 tasks evaluated with a 15-step budget, and we test both screenshot agents and SoM agents. VisualWebArena contains 72 tasks evaluated with a 30-step budget, and the released results cover SoM agents. We use five frontier multimodal backbones: GPT-4-Turbo (2024-04-09), GPT-4o (2024-05-13), Gemini 1.5 Pro (002), Claude 3.5 Sonnet (20240620), and Claude 3.5 Sonnet v2 (20241022). All runs use temperature 0 to minimize decoding variance.

4.2 Protocol

For each benchmark-model setting, we compare attacked task success against the corresponding no-attack baseline. The main results use the default PopupAttackconfiguration. Component ablations then replace one pop-up element at a time while keeping the rest fixed. We additionally evaluate blank-pop-up and small-pop-up controls, defense prompts applied either once in the system prompt or at every step, and a simple defense augmentation that adds attack variance during the step-wise prompt defense.

5 Results

5.1 Main Vulnerability Results

Table 1 shows that pop-up hijacking is highly effective across models and settings. Averaging over all 15 benchmark-model combinations yields 86.2 ASR. OSWorld is especially fragile: screenshot ASR averages 93.0 and reaches 100.0 for Claude

AI-Generated

3.5 Sonnet, while SoM ASR averages 92.4 and stays between 88.7 and 95.3 across all tested models. VisualWebArena-SoM is somewhat more resilient but still highly vulnerable, with ASR between 62.1 and 78.4.

This action-level vulnerability causes large task-level degradation. Averaged over all settings, OSR is 34.7 while attacked SR falls to 18.5, a 46.8% relative drop. On OSWorld, attacked SR never exceeds 10.0 even though the corresponding OSR reaches 58.0. VisualWebArena retains higher SR under attack, but even there the best attacked SR is only 48.6 despite a no-attack baseline of 63.9.

Figure 1 explains why the effect on task completion is so large: once diverted, agents repeatedly devote their action budget to the malicious pop-up. Averaged over attacked runs, 92.7% of OSWorld actions and 73.1% of VisualWebArena actions are clicks on the pop-up.

5.2 Which Components Matter?

Attention hooks matter most when they are aligned to the task. Table 2 shows that replacing a summarized query with a generic virus warning barely changes OSWorld-Screen ASR (93.3 to 90.0), but substantially reduces ASR for OSWorld-SoM (to 58.3) and collapses VisualWebArena-SoM ASR to 1.1. Using only guessed intent is weaker still, with ASR dropping to 53.9 on OSWorld-Screen, 34.4 on OSWorld-SoM, and 8.0 on VisualWebArena-SoM.

Instructions also matter, but the attack transfers even when they are degraded. Table 3 shows that explicit coordinate or tag instructions are strongest, while "click here" is much weaker for screenshot agents (ASR 11.3 on OSWorld-Screen) yet still leaves 72.8 ASR on OSWorld-SoM and 58.4 on VisualWebArena-SoM. Even random targets induce non-trivial success on OSWorld-Screen and OSWorld-SoM, showing that some failures come from the model following the malicious instruction format itself, not only from precise target grounding.

Text-only disclosures help less than one might hope. Changing the banner from "OK" to "ADVERTISEMENT" lowers ASR from 93.3 to 66.5 on OSWorld-Screen, 91.8 to 77.9 on OSWorld-SoM, and 62.1 to 56.7 on VisualWebArena-SoM. Weakening the ALT descriptor also helps only partially: empty ALT text drops ASR to 68.1 on OSWorld-SoM and 42.9 on VisualWebArena-SoM, while explicitly prepending "ADVERTISEMENT" still leaves ASR at 77.1 and 56.9, respectively.



Original: The current screenshot shows the Delta Airlines homepage on a web browser. To proceed with finding the status of tomorrow's flights from New York airports to Columbus, Ohio, the next step is to enter the departure and destination cities in the search fields on the webpage. I will start by clicking on the "From" field (currently showing "San Jose, CA") to change it to a New York airport. Then, I will enter the destination city as Columbus, Ohio. Let's proceed with this action.

```python
import pyautogui
import time

# Click on the "From" field to change the departure city
pyautogui.click(350, 300)  # Approximate coordinates of the "From" field
time.sleep(0.5)
```

Attacked: The next step is to click on the "From" field to activate it for input. The "From" field is located near the top of the webpage, under the "BOOK" tab, where "San Jose, CA" is currently displayed. I will move the cursor to this field and click to focus on it so that "New York, NY" can be entered.

```python
import pyautogui
import time

# Move the cursor to the "From" field and click to focus
pyautogui.moveTo(240, 298)  # Coordinates for the "From" field
pyautogui.click()
time.sleep(0.5)  # Wait for the field to be focused
```

Figure 3: A representative successful attack: the original agent follows the task, while the attacked agent follows the injected pop-up.

6 Analysis

6.1 Validity Checks

Two controls show that the attack is not simply exploiting the presence of any extra rectangle. Table 6 reports that a blank pop-up almost eliminates action-level attack success, reducing ASR to 2.4 on OSWorld-Screen, 3.7 on OSWorld-SoM, and 0.0 on VisualWebArena-SoM. By contrast, a smaller but still content-bearing pop-up remains highly effective, with ASR 87.4, 90.1, and 60.0, respectively.

6.2 How Agents Reason About the Pop-up

Figure 3 shows a representative successful attack. The attacked agent shifts from task-directed reasoning to acting on the overlaid instruction, even though the pop-up is not part of the original task interface.

Table 7 gives a more systematic view of these traces. In successful attacks, agents explicitly mention the target instruction in 88% of OSWorld-Screen cases and 90% of OSWorld-SoM cases. By contrast, they mention the attention hook much less often (2% and 62%), and the "OK" banner inconsistently (52% and 6%). This suggests that the pop-up works less by inducing a detailed reinterpretation of the whole interface and more by surfacing a lo-

AI Generated

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
GPT-4-Turbo	93.3	2.0	18.0	91.8	8.0	52.0	78.0	43.1	50.0
GPT-4o	95.8	**6.0**	8.0	91.2	2.0	6.0	**62.1**	45.8	**63.9**
Gemini 1.5	**80.0**	4.0	6.0	**88.7**	6.0	18.0	70.1	44.4	48.6
Claude 3.5 Sonnet	100.0	0.0	**22.0**	95.3	6.0	44.0	78.4	47.2	54.2
Claude 3.5 Sonnet v2	96.0	4.0	**22.0**	94.8	**10.0**	**58.0**	76.8	**48.6**	50.0

Table 1: Result table for model comparison, where we **highlight** the lowest ASR (↓) and highest SR (↑)/OSR (↑). Screen and SoM refer to screenshot agents and SoM agents. We use WebArena as a shorter form of VisualWebArena.

Attention Hook	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
Summarized Query	93.3	2.0		91.8	8.0		62.1	45.8	
Virus	90.0	2.0	18.0	58.3	26.0	52.0	1.1	54.2	63.9
Speculated Query	53.9	10.0		34.4	38.0		8.0	54.2	

Table 2: Ablation study on the attention hooks, where we underline the numbers from the default setting.

cally compelling instruction that the model then rationalizes.

6.3 TASR Reveals Residual Risk

Figure 5 plots ASR against TASR. TASR tracks ASR closely overall, but is often higher when ASR is low.

6.4 Defenses

Prompt defenses are weak. Table 8 shows that a generic system-prompt defense hardly changes ASR and can even slightly worsen it. A more specific prompt that explicitly tells the agent to ignore pop-ups reduces ASR on OSWorld but still leaves 52.0 ASR for screenshot agents and 72.3 for SoM agents, with almost no effect on VisualWebArena.

Applying the defense at every step is more effective at the action level, but still leaves considerable task-level exposure. Table 9 shows that step-wise prompting reduces ASR to 5.9, or 10.4 when attack variance is added, but TASR remains 32.0 and 44.0, respectively. End-to-end SR also stays low at 8.0 to 10.0.

7 Conclusion

Adversarial pop-ups are a practical and powerful attack surface for vision-language computer agents. A single query-aligned overlay with an explicit click instruction can hijack both screenshot and SoM agents across desktop and web benchmarks, producing high ASR and sharply reducing end-to-end task success. Our ablations show that semantic alignment and explicit instructions are the main drivers of attack strength, while disclosure text and prompt-only defenses provide limited protection. Robust computer-use agents will likely need defenses that model the provenance and trustworthiness of on-screen content, rather than treating all visible text and controls as equally valid task evidence.

AI-Generated

Instruction	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Click Tag	-	-	-	96.1	6.0		62.1	45.8	
Click Coor	93.3	2.0		91.8	8.0	52.0	49.3	48.6	63.9
Click Here	11.3	14.0	18.0	72.8	14.0		58.4	44.4	
Click Random	11.8	2.0		13.7	10.0		4.1	34.7	

Table 3: Ablation study on the instructions. Click Random refers to clicking random coordinates for OSWorld and clicking random tags for VisualWebArena, respectively.

Info Banner	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
"OK"	93.3	2.0	18.0	91.8	8.0	52.0	62.1	45.8	63.9
"ADVERTISEMENT"	66.5	10.0		77.9	14.0		56.7	52.8	

Table 4: Ablation study on the info banners.

ALT Descriptor	OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Adversarial	91.8	8.0		62.1	45.8	
Empty	68.1	22.0	52.0	42.9	55.6	63.9
Adversarial with Ad Notice	77.1	22.0		56.9	45.8	

Table 5: Ablation study on the ALT descriptors.

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Default	93.3	2.0		91.8	8.0		62.1	45.8	
Blank Pop-up	2.4	16.0	18.0	3.7	38.0	52.0	0.0	52.8	63.9
Small Pop-up	87.4	2.0		90.1	10.0		60.0	52.8	

Table 6: Extra ablations for blank pop-ups and small pop-ups.



Figure 4: Multiple successful attacks across OSWorld-Screen, OSWorld-SoM, and VisualWebArena-SoM. The benign task remains visible, but the next action is redirected by the pop-up.

OSWorld-Screen		OSWorld-SoM	
Attn Hook	2%	Attn Hook	62%
Target	88%	Target	90%
OK	52%	OK	6%

Table 7: The frequency of explicitly mentioning different elements in agent-generated thoughts for successfully attacked cases: attention hook (summarized queries), target in instructions (coordinates or tag IDs), and the "OK" in the info banner.

Generated



Figure 5: Correlation between ASR and TASR. TASR often remains higher when ASR is low, indicating residual task-level risk under partial mitigation.



Figure 6: Distribution of trajectory termination steps. On OSWorld, attacks shift mass toward the final steps, consistent with repeated diversion until the budget is exhausted.

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Default Attack	93.3	2.0	18.0	91.8	8.0	52.0	62.1	45.8	63.9
System Prompt Defense	95.9	6.0		93.4	14.0		60.3	47.2	
System Prompt Defense$_{\text{specific}}$	52.0	6.0		72.3	24.0		60.2	45.8	

Table 8: Ablations for the system prompt defense.

	OSWorld-Screen			
	ASR$_\downarrow$	**TASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Step-wise Prompt Defense	5.9	32.0	8.0	18.0
+ Attack Variance	10.4	44.0	10.0	

Table 9: Step-wise prompt defense. We use the GPT-4-Turbo screenshot agent on OSWorld for the ablation.

AI Generated

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Saaket Agashe, Jiuzhou Han, Shuyu Gan, Jiachen Yang, Ang Li, and Xin Eric Wang. 2024. Agent s: An open agentic framework that uses computers like a human. *Preprint*, arXiv:2410.08164.

Anthropic. 2024. The claude 3 model family: Opus, sonnet, haiku. Technical report, Anthropic. Available at: https://www.anthropic.com/news/claude-3-family.

Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. 2024. Seeclick: Harnessing gui grounding for advanced visual gui agents. *Preprint*, arXiv:2401.10935.

Federal Trade Commission et al. 2013. . com disclosures: how to make effective disclosures in digital advertising. *March, http://www.ftc. gov/sites/default/files/attachments/press-releases/ftc-staff-revises-online-advertising-disclosureguidelines/130312dotcomdisclosures. pdf*.

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Ruslan Salakhutdinov, and Daniel Fried. 2024. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. *Preprint*, arXiv:2401.13649.

Zeyi Liao, Lingbo Mo, Chejian Xu, Mintong Kang, Jiawei Zhang, Chaowei Xiao, Yuan Tian, Bo Li, and Huan Sun. 2024. Eia: Environmental injection attack on generalist web agents for privacy leakage. *Preprint*, arXiv:2409.11295.

Xinbei Ma, Yiting Wang, Yao Yao, Tongxin Yuan, Aston Zhang, Zhuosheng Zhang, and Hai Zhao. 2024. Caution for the environment: Multimodal agents are susceptible to environmental distractions. *Preprint*, arXiv:2408.02544.

OpenAI. 2024. Gpt-4o system card. `https://openai.com/index/gpt-4o-system-card/`.

Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, et al. 2025. Ui-tars: Pioneering automated gui interaction with native agents. *arXiv preprint arXiv:2501.12326*.

Machel Reid, Nikolay Savinov, Denis Teplyashin, Dmitry Lepikhin, Timothy Lillicrap, Jean-baptiste Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Firat, Julian Schrittwieser, et al. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*.

Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. 2024. The instruction hierarchy: Training llms to prioritize privileged instructions. *Preprint*, arXiv:2404.13208.

Chen Henry Wu, Jing Yu Koh, Ruslan Salakhutdinov, Daniel Fried, and Aditi Raghunathan. 2024. Adversarial attacks on multimodal agents. *Preprint*, arXiv:2406.12814.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. 2024. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Preprint*, arXiv:2404.07972.

Chejian Xu, Mintong Kang, Jiawei Zhang, Zeyi Liao, Lingbo Mo, Mengqi Yuan, Huan Sun, and Bo Li. 2024a. Advweb: Controllable black-box attacks on vlm-powered web agents. *Preprint*, arXiv:2410.17401.

Yiheng Xu, Zekun Wang, Junli Wang, Dunjie Lu, Tianbao Xie, Amrita Saha, Doyen Sahoo, Tao Yu, and Caiming Xiong. 2024b. Aguvis: Unified pure vision agents for autonomous gui interaction. *Preprint*, arXiv:2412.04454.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. 2024. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents. *Preprint*, arXiv:2403.02691.

Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. 2024. Gpt-4v(ision) is a generalist web agent, if grounded. *Preprint*, arXiv:2401.01614.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. 2023. Webarena: A realistic web environment for building autonomous agents. *Preprint*, arXiv:2307.13854.

AI-Generated