Attacking Vision-Language Computer Agents via Pop-ups

Yanzhe Zhang[1] **Tao Yu**[2] **Diyi Yang**[1]
[1]Stanford University [2]The University of Hong Kong
{yanzhe, diyiyang}@stanford.edu, taoyu@cs.hku.hk

Abstract

Vision-language model (VLM) based agents are increasingly deployed to operate graphical user interfaces (GUIs) for real-world computer and web tasks. Yet their robustness to adversarial visual inputs remains underexplored. In this work, we introduce **PopupAttack**, a practical threat in which adversarial pop-up images are injected into the agent's observations—both screenshots and accessibility trees—to hijack agent behavior. Our attack is modular, comprising four components: an *attention hook* conditioned on the user query, an explicit *click instruction*, an *info banner*, and an *ALT descriptor*. Through comprehensive evaluations on OSWorld and VisualWebArena across five frontier VLMs (GPT-4-Turbo, GPT-4o, Gemini 1.5 Pro, Claude 3.5 Sonnet, and Claude 3.5 Sonnet v2), we show that simple query-aligned pop-ups achieve an average Attack Success Rate (ASR) of $\sim$86%, with agents spending 92.7%/73.1% of their steps clicking adversarial pop-ups in OSWorld/VisualWebArena, while task Success Rate drops by $\sim$47% on average. Ablation studies reveal that query-conditioned attention hooks are critical, and that standard prompt-based defenses provide limited protection. We release our code to facilitate future research on robust computer-use agents.

1 Introduction

The rapid advancement of vision-language models (VLMs) has given rise to a new class of autonomous agents capable of operating computers and web browsers through direct GUI manipulation (Xie et al., 2024; Koh et al., 2024; Zheng et al., 2024). These agents perceive screenshots or accessibility tree representations and emit low-level actions—clicks, keyboard inputs, scrolls—to complete user-specified tasks, from filling web forms to managing files.

Despite impressive capabilities, the security and robustness of VLM-based computer-use agents to adversarial visual stimuli remain largely unexplored. In human computer interactions, malicious pop-up windows are a well-established attack vector (Sood and Enbody, 2011; Imamura et al., 2019; Kumaraguru et al., 2007): fake virus alerts, deceptive advertisements, and phishing overlays routinely deceive users into unintended clicks. The key question we ask is: *are VLM computer agents equally susceptible to pop-up-based manipulation?*

We find the answer is a resounding **yes**. We demonstrate that a straightforward attack—injecting a single adversarial pop-up image into the agent's observation—can reliably redirect frontier VLM agents to click the pop-up rather than pursue the intended task. The key insight is that agents over-trust on-screen cues and struggle to distinguish benign UI elements from adversarial overlays, especially when the pop-up is semantically aligned with the user's goal. By conditioning the pop-up content on the user's query (the *attention hook*) and embedding explicit click instructions (e.g., `click (x,y)` or `click [ID]`), the attack coerces the agent with high reliability.

We propose **PopupAttack**, a modular attack framework with four components: (1) an *Attention Hook* (query-conditioned text that aligns the pop-up with the user's task), (2) an *Instruction* (an explicit directive to click a specified coordinate or UI element ID), (3) an *Info Banner* (e.g., an "`OK`" button), and (4) an *ALT Descriptor* (text description injected into the accessibility tree for SoM-based agents). We evaluate both *default* (ideal) attacks—using the full query and precise coordinates/IDs—and realistic *variants* such as fake virus alerts, speculated query, generic "click here", random targets, and advertisement disclosures.

Our evaluations span two agent benchmarks (OSWorld and VisualWebArena), two agent types (screenshot-based and Set-of-Mark (Yang et al., 2023) based), and five frontier VLMs, yielding the

Figure 1: On average, **92.7% / 73.1%** of all actions of attacked agents in OSWorld / VisualWebArena are **clicking on the adversarial pop-ups**, demonstrating the severe impact of our attack on agent behavior.

following key findings:

- **Universal high vulnerability:** The default attack achieves ASR of 80–100% on OSWorld-Screen, 88.7–95.3% on OSWorld-SoM, and 62.1–78.4% on VisualWebArena-SoM across all tested models.
- **Severe task disruption:** Average task Success Rate (SR) decreases by ∼47% under attack, with OSWorld SR collapsing to ≤10% despite original SR up to 58%.
- **Query-conditioned hooks are critical:** Replacing the attention hook with a generic "VIRUS DETECTED" message reduces ASR by 33.5% on OSWorld-SoM and by 61.0% on VisualWebArena-SoM.
- **Prompt defenses are largely ineffective:** System-prompt defenses reduce ASR by at most ∼25% relatively; even step-wise defenses leave task-level attack success (TASR) above 32%.

Our contributions are:

1. A practical pop-up-based threat model and a modular attack design (**PopupAttack**) spanning both visual and textual (accessibility tree) channels.
2. Comprehensive evaluation across two benchmarks, two agent types, and five frontier VLMs, with the introduction of Task-level ASR (TASR) to capture task-level risk.
3. Detailed ablations of each attack component and analysis of defense strategies, showing that current safeguards are insufficient.
4. A public code release for reproducibility and future research.

2 Related Work

VLM-Based GUI Agents. The emergence of powerful VLMs has catalyzed a new generation of GUI agents that interact with computer interfaces directly from visual observations. SeeAct (Zheng et al., 2024) demonstrated that GPT-4V can serve as a generalist web agent when grounded with appropriate visual prompting. OSWorld (Xie et al., 2024) provided a comprehensive benchmark for evaluating such agents on real computer tasks, while VisualWebArena (Koh et al., 2024) and WebArena (Zhou et al., 2023) focus on web-based tasks. More specialized agents like SeeClick (Cheng et al., 2024), UI-TARS (Qin et al., 2025), and Aguvis (Xu et al., 2024b) incorporate GUI-specific grounding capabilities. The Set-of-Mark (SoM) prompting strategy (Yang et al., 2023), which overlays bounding boxes and numeric IDs on interactive elements, has become a standard approach for improving agent grounding. Agent S (Agashe et al., 2024) and ReAct (Yao et al., 2023) represent broader agentic frameworks that combine reasoning and acting. In our work, we study both screenshot-based and SoM-based agents to ensure broad coverage of the threat landscape.

Security and Robustness of LLM/VLM Agents. Concerns about the safety of LLM agents have grown as their capabilities expand (Ruan et al., 2023; OpenAI, 2025). Indirect prompt injection attacks, where malicious instructions are embedded in the environment, represent one major threat (Zhan et al., 2024; Wallace et al., 2024). The Instruction Hierarchy (Wallace et al., 2024) studies how LLMs can be trained to prioritize privileged instructions over adversarial in-context instructions. Backdoor attacks on LLM

agents (Yang et al., 2024a) and jailbreaking via persuasion (Zeng et al., 2024) or adversarial suffixes (Zou et al., 2023; Liu et al., 2023) are related attack vectors. In the multimodal setting, Wu et al. (2024) demonstrated adversarial attacks on multimodal agents using gradient-based image perturbations. EIA (Liao et al., 2024) introduced environmental injection attacks targeting web agents for privacy leakage. AdvWeb (Xu et al., 2024a) studied black-box attacks on VLM-powered web agents. Ma et al. (2024) showed that multimodal agents are susceptible to environmental distractions. The Security Matrix study (Yang et al., 2024b) examined security threats on mobile GUI agents. In contrast to these prior works, PopupAttack requires no model access, no gradient computation, and no knowledge of internal model representations—only the ability to inject a pop-up image into the screen observation, making it both more realistic and more practically threatening.

Malicious Pop-ups and Social Engineering. Pop-up-based social engineering attacks are well-studied in human computer security research. Fake virus alerts (Imamura et al., 2019) exploit users' security concerns to induce harmful clicks. Malvertising (Sood and Enbody, 2011; Xing et al., 2015) uses deceptive advertisements to redirect users to malicious content. Phishing research (Kumaraguru et al., 2007) has shown that even security-aware users are susceptible to well-crafted visual deceptions. The FTC has issued guidelines on disclosure of advertising (Commission et al., 2013). Our work is the first to systematically study how such attacks transfer to VLM-based autonomous agents operating in real computer environments.

3 PopupAttack: Attack Design

3.1 Threat Model

We consider an adversary who can inject a single pop-up image into the agent's visual observation (screenshot) and/or into the accessibility tree representation at any point during task execution. This is a realistic threat model: attackers controlling website content, browser extensions, or desktop advertisements can easily overlay pop-up windows on the screen. The adversary's goal is to cause the agent to click the malicious pop-up, potentially triggering harmful actions (e.g., visiting a malicious URL, granting permissions, or executing attacker-controlled commands).



Figure 2: Adversarial pop-up examples illustrating the four components: Attention Hook (query-conditioned text), Instruction (explicit click directive), Info Banner (`OK` button), and ALT Descriptor (for SoM agents).

Formally, let $\mathcal{A}$ be a VLM agent that, given a user goal q and observation o_t (screenshot and/or accessibility tree at step t), outputs an action a_t. The attacker injects a pop-up p into o_t to produce a modified observation $\tilde{o}_t$. The attack succeeds if the agent clicks on p, i.e., $a_t = \texttt{click}(p)$, causing task failure or triggering the attacker's desired action.

This threat model deliberately excludes gradient-based or white-box adversarial perturbations, which require model access and are impractical in real-world deployments. Pop-up injection requires only the ability to render content on the agent's screen—a capability trivially available to any web page, browser extension, or desktop application running under standard user privileges. The threat is further amplified by the persistence of the injected pop-up: since the overlay reappears in every subsequent screenshot, a single successful injection can lock the agent into a loop of adversarial clicks for the entirety of its step budget, compounding its impact far beyond a single misguided action.

3.2 Pop-up Components

PopupAttack constructs each adversarial pop-up from four modular components (Figure 2):

(1) Attention Hook. The attention hook is text displayed prominently in the pop-up that is semantically related to the user's task goal q. In the default setting, we use a VLM to generate a concise

summary of q (e.g., for the task "find the cheapest flight to Paris", the hook might read "BOOK YOUR PARIS FLIGHT"). This alignment with the user's intent increases the likelihood that the agent treats the pop-up as a relevant interactive element rather than a distraction to be ignored. We additionally study a generic *Virus Alert* hook ("VIRUS DETECTED") and a *Speculated Query* hook generated from the page content without access to the actual user query.

(2) Instruction. The instruction component provides an explicit click directive embedded in the pop-up image text, such as `Please click (x,y)` for screenshot agents (where (x, y) is the center of the pop-up) or `Please click [ID]` for SoM agents (where `[ID]` is the accessibility tree tag assigned to the pop-up element). This exploits the tendency of VLM agents to follow in-context instructions embedded in their visual observations. We additionally study *Click Here* (no specific target) and *Click Random* (incorrect coordinates/IDs) variants.

(3) Info Banner. The info banner is a visually distinctive button-like element rendered at the bottom of the pop-up, defaulting to "`OK`". This mimics common UI patterns that agents have been trained to interact with. We contrast this with an "`ADVERTISEMENT`" banner, testing whether ad-disclosure rhetoric reduces agent susceptibility.

(4) ALT Descriptor. For SoM agents, the accessibility tree includes a text description of each interactive element. We inject an adversarial ALT text that reiterates the click instruction alongside the hook text. Ablations test the effect of an empty ALT versus an ALT that includes an advertising disclosure notice.

3.3 Attack Variants

Beyond the default ideal attack, we implement realistic variants that do not require query access or precise coordinate knowledge, assessing the practicality of the attack in less privileged settings. These include: (1) a *Virus Alert* hook without query knowledge, (2) a *Speculated Query* generated from page content, (3) a generic *Click Here* instruction, (4) a *Click Random* instruction with incorrect targets, and (5) an *Advertisement* info banner mimicking disclosure requirements. The pop-up is rendered as a semi-transparent overlay on the screenshot using PIL image manipulation and positioned centrally for maximum visibility.

4 Experiments

4.1 Experimental Setup

Benchmarks. We evaluate on two established benchmarks:

- **OSWorld** (Xie et al., 2024): A desktop computer environment with diverse real-world tasks spanning document editing, file management, web browsing, and more. We use a subset of 50 *easy* tasks—tasks that agents successfully complete without attack—to ensure meaningful measurement of attack impact. Each episode is limited to 15 steps.
- **VisualWebArena** (Koh et al., 2024): A web-based agent benchmark covering e-commerce, social media, and web navigation tasks. We use a subset of 72 easy tasks following prior evaluation protocols, with each episode limited to 30 steps.

Agent Types. We evaluate two types of agents:

- **Screenshot (Screen) Agent**: Receives raw screenshot images as visual observations without accessibility tree information.
- **SoM Agent**: Receives screenshots augmented with Set-of-Mark (Yang et al., 2023) overlays (bounding boxes with numeric IDs on interactive elements), along with the full accessibility tree.

VLM Backbones. We test five frontier VLMs as agent backbones: GPT-4-Turbo (2024-04-09) (Achiam et al., 2023), GPT-4o (2024-05-13) (OpenAI, 2024), Gemini 1.5 Pro (002) (Reid et al., 2024), Claude 3.5 Sonnet (20240620) (Anthropic, 2024), and Claude 3.5 Sonnet v2 (20241022) (Anthropic, 2024). All models use greedy decoding (temperature 0) to minimize randomness across runs.

Metrics. We use four complementary metrics:

- **Attack Success Rate (ASR)**: Fraction of steps in which the agent clicks the adversarial pop-up (lower is better for defenders).
- **Success Rate (SR)**: Fraction of tasks successfully completed under attack (higher is better).

- **Original SR (OSR)**: Fraction of tasks successfully completed without attack (baseline; higher is better).
- **Task-level ASR (TASR)**: Fraction of tasks in which the agent clicks the pop-up at least once, capturing task-level impact irrespective of step frequency (lower is better for defenders).

4.2 Main Results

Table 1 reports results for all models and settings under the default attack. Key observations are:

Universal high vulnerability. All five frontier VLMs exhibit high susceptibility to the pop-up attack. ASR ranges from 80.0% (Gemini 1.5) to 100.0% (Claude 3.5 Sonnet) on OSWorld-Screen, 88.7% to 95.3% on OSWorld-SoM, and 62.1% to 78.4% on VisualWebArena-SoM. The average ASR across settings is ≈86%, with no model consistently resistant. As Figure 1 illustrates, attacked agents spend 92.7% (OSWorld) and 73.1% (VisualWebArena) of their total steps clicking the adversarial pop-up rather than progressing on the intended task.

Severe task performance degradation. The attack causes dramatic SR drops. On OSWorld, SR values under attack are $\leq$ 10% across all models, compared to OSR values up to 58% (Claude 3.5 Sonnet v2 on OSWorld-SoM). On VisualWebArena-SoM, SR under attack ranges from 43.1% to 48.6%, compared to OSR values of 48.6%–63.9%. The average SR reduction across all settings is approximately 47 percentage points.

Model comparison. Gemini 1.5 Pro shows the lowest ASR overall (80.0% on OSWorld-Screen, 88.7% on OSWorld-SoM), while GPT-4o achieves the lowest ASR on VisualWebArena-SoM (62.1%). Claude 3.5 Sonnet attains the highest ASR of 100% on OSWorld-Screen. Despite differences in vulnerability levels, all five models are substantially impacted, and no model achieves reliable resistance.

Qualitative illustration. Figure 3 presents a representative attacked example. In the original (no-attack) setting, the agent correctly identifies and executes the task-relevant action. Under attack, the agent's generated thought explicitly references the pop-up's attention hook text and click instruction before executing the adversarial click, demonstrating that agents actively reason about the pop-up rather than simply mis-clicking.



Original: The current screenshot shows the Delta Airlines homepage on a web browser. To proceed with finding the status of tomorrow's flights from New York airports to Columbus, Ohio, the next step is to enter the departure and destination cities in the search fields on the webpage. I will start by clicking on the "From" field (currently showing "San Jose, CA") to change it to a New York airport. Then, I will enter the destination city as Columbus, Ohio. Let's proceed with this action.

```python
import pyautogui
import time

# Click on the "From" field to change the departure
city
pyautogui.click(350, 300)  # Approximate coordinates
of the "From" field
time.sleep(0.5)
```

Attacked: The next step is to click on the "From" field to activate it for input. The "From" field is located near the top of the webpage, under the "BOOK" tab, where "San Jose, CA" is currently displayed. I will move the cursor to this field and click to focus on it so that "New York, NY" can be entered.

```python
import pyautogui
import time

# Move the cursor to the "From" field and click to
focus
pyautogui.moveTo(240, 298)  # Coordinates for the
"From" field
pyautogui.click()
time.sleep(0.5)  # Wait for the field to be focused
```

Figure 3: A successfully attacked example. We show the thought and action from the original (no attack) setting versus the attacked setting. Under attack, the agent explicitly reasons about the pop-up content before clicking it.

5 Understanding the Agent Attack

5.1 Ablation: Attention Hooks

Table 2 ablates the attention hook component, using GPT-4o on OSWorld-Screen and OSWorld-SoM, and on VisualWebArena-SoM. The default *Summarized Query* hook consistently achieves the highest ASR across all settings. Replacing it with a generic *Virus* hook ("VIRUS DETECTED") yields mixed results: on OSWorld-Screen the ASR remains high (90.0%), but on OSWorld-SoM it drops substantially (58.3% vs. 91.8%), and on VisualWebArena-SoM it collapses to just 1.1% vs. 62.1%—a reduction of 61.0 percentage points.

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
GPT-4-Turbo	93.3	2.0	18.0	91.8	8.0	52.0	78.0	43.1	50.0
GPT-4o	95.8	**6.0**	8.0	91.2	2.0	6.0	**62.1**	45.8	**63.9**
Gemini 1.5	**80.0**	4.0	6.0	**88.7**	6.0	18.0	70.1	44.4	48.6
Claude 3.5 Sonnet	100.0	0.0	**22.0**	95.3	6.0	44.0	78.4	47.2	54.2
Claude 3.5 Sonnet v2	96.0	4.0	**22.0**	94.8	**10.0**	**58.0**	76.8	**48.6**	50.0

Table 1: Result table for model comparison, where we **highlight** the lowest ASR (↓) and highest SR (↑)/OSR (↑). Screen and SoM refer to screenshot agents and SoM agents. We use WebArena as a shorter form of VisualWebArena.

Attention Hook	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
Summarized Query	<u>93.3</u>	<u>2.0</u>		<u>91.8</u>	<u>8.0</u>		<u>62.1</u>	<u>45.8</u>	
Virus	90.0	2.0	18.0	58.3	26.0	52.0	1.1	54.2	63.9
Speculated Query	53.9	10.0		34.4	38.0		8.0	54.2	

Table 2: Ablation study on the attention hooks, where we <u>underline</u> the numbers from the default setting..

Using a *Speculated Query* hook (generated from page content without knowing the actual user query) achieves intermediate ASR: 53.9% / 34.4% / 8.0% on OSWorld-Screen / SoM / WebArena-SoM. This confirms that semantic alignment between the pop-up content and the user's goal is the primary driver of attack success, particularly for SoM and web agents that have richer contextual grounding.

5.2 Ablation: Instructions

Table 3 ablates the click instruction format. For SoM agents, *Click Tag* (specific accessibility tree ID) yields 96.1% on OSWorld-SoM vs. 91.8% for *Click Coor*, while on VisualWebArena-SoM *Click Tag* (62.1%) outperforms *Click Coor* (49.3%). Removing precise targeting (*Click Here*, no specific location) dramatically reduces ASR for screenshot agents to 11.3% while maintaining moderate ASR for SoM agents (72.8% on OSWorld-SoM), as the pop-up element still appears in the accessibility tree. Using *Click Random* (incorrect coordinates or IDs) collapses ASR to 11.8%/13.7%/4.1% across settings, showing that when the pop-up instruction is inconsistent with the agent's visual grounding, the attack largely fails. These results confirm that precise targeting information is essential for reliable attacks, though even generic instructions can succeed for SoM agents.

5.3 Ablation: Info Banners

Table 4 compares the default "`OK`" banner with an "`ADVERTISEMENT`" disclosure banner. The ad disclosure banner reduces ASR by 26.8 points on OSWorld-Screen (66.5% vs. 93.3%), 13.9 points on OSWorld-SoM (77.9% vs. 91.8%), and 5.4 points on VisualWebArena-SoM (56.7% vs. 62.1%). Despite this reduction, ASR remains high (>55%) across all settings, indicating that ad disclosures provide only modest protection—consistent with research showing that users (and apparently agents) tend to ignore disclosure text (Commission et al., 2013).

5.4 Ablation: ALT Descriptors

Table 5 examines the effect of ALT text in the accessibility tree (relevant only for SoM agents). The default *Adversarial* ALT (reiterating the click instruction) achieves the highest ASR (91.8% on OSWorld-SoM, 62.1% on WebArena-SoM). Using an *Empty* ALT descriptor reduces ASR by 23.7 points on OSWorld-SoM (68.1%) and 19.2 points on WebArena-SoM (42.9%), accompanied by notable SR improvements (22.0% and 55.6% respectively). Adding an *Adversarial with Ad Notice* (appending an advertising disclosure to the adversarial ALT) gives intermediate results (77.1% and 56.9%), confirming that adversarial accessibility tree content plays an important supporting role in the attack and that ad disclosures provide limited deterrence.

5.5 Validity Checks: Blank and Small Pop-ups

To verify that the attack's effectiveness stems from its content rather than mere visual occlusion, Table 6 evaluates *Blank Pop-up* (same size and position but with no text content) and *Small Pop-up* (full content at $1/4$ scale) variants. Blank pop-ups achieve near-zero ASR (2.4%/3.7%/0.0%), con-

Instruction	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Click Tag	-	-	-	96.1	6.0	52.0	62.1	45.8	63.9
Click Coor	93.3	2.0	18.0	91.8	8.0		49.3	48.6	
Click Here	11.3	14.0		72.8	14.0		58.4	44.4	
Click Random	11.8	2.0		13.7	10.0		4.1	34.7	

Table 3: Ablation study on the instructions. Click Random refers to clicking random coordinates for OSWorld and clicking random tags for VisualWebArena correspondingly.

Info Banner	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
"OK"	93.3	2.0	18.0	91.8	8.0	52.0	62.1	45.8	63.9
"ADVERTISEMENT"	66.5	10.0		77.9	14.0		56.7	52.8	

Table 4: Ablation study on the info banners.

firming that the attack content—not visual presence alone—drives agent clicks. Small pop-ups (87.4%/90.1%/60.0%) retain almost all of the default attack's effectiveness, indicating that even small adversarial overlays can be highly effective as long as their text content remains legible to the VLM.

5.6 Agent Thought Analysis

To understand *why* agents click pop-ups, we analyze agent-generated chain-of-thought reasoning for successfully attacked cases (Table 7). For OSWorld-SoM agents, 62% of attacked thoughts explicitly mention the attention hook (query summary), 90% mention the target (coordinate or tag ID), and 6% mention the "OK" banner. For OSWorld-Screen agents, only 2% mention the hook (as screenshot-only agents have no text extraction), but 88% mention the target coordinate and 52% mention the "OK" button. This reveals that for screenshot agents, the visual appearance (especially the OK button) and the coordinate instructions dominate reasoning, while for SoM agents the accessible text plays a larger role. Figure 4 shows additional qualitative examples across attack settings.

5.7 Impact on Agent Steps

Figure 5 visualizes the step-level impact of the attack. In the no-attack condition, agents typically complete tasks within a moderate number of steps. Under attack, agents repeatedly click the adversarial pop-up at nearly every step, exhausting their entire step budget (15 steps for OSWorld, 30 for VisualWebArena) while making no meaningful task progress. This "sticky" behavior occurs because the pop-up reappears after each step as a



Figure 4: Successfully attacked examples showing thoughts generated by original (no attack) and attack agents. In each case, the attacked agent focuses its reasoning on the pop-up content before taking the adversarial click action.

persistent overlay—the agent is perpetually drawn back to click it.

5.8 ASR vs. Task-Level ASR (TASR)

Figure 6 plots the relationship between step-level ASR and task-level TASR across all ablation settings. TASR (fraction of tasks in which the agent clicks the pop-up at least once) is consistently close to or higher than ASR, particularly when ASR is low. This indicates that partial susceptibility—even clicking the pop-up on just one step out of many—is often sufficient to cause task failure, since a single click may trigger the attacker's desired action (e.g., visiting a malicious

ALT Descriptor	OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Adversarial	91.8	8.0		62.1	45.8	
Empty	68.1	22.0	52.0	42.9	55.6	63.9
Adversarial with Ad Notice	77.1	22.0		56.9	45.8	

Table 5: Ablation study on the ALT descriptors.

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Default	93.3	2.0		91.8	8.0		62.1	45.8	
Blank Pop-up	2.4	16.0	18.0	3.7	38.0	52.0	0.0	52.8	63.9
Small Pop-up	87.4	2.0		90.1	10.0		60.0	52.8	

Table 6: Extra ablations for blank pop-ups and small pop-ups.

OSWorld-Screen		OSWorld-SoM	
Attn Hook	2%	Attn Hook	62%
Target	88%	Target	90%
OK	52%	OK	6%

Table 7: The frequency of explicitly mentioning different elements in agent-generated thoughts for successfully attacked cases: attention hook (summarized queries), target in instructions (coordinates or tag IDs), and the "OK" in the info banner.

Figure 5: Impact of attack on the distribution of steps taken by agents. Attacked agents repeatedly click the pop-up across many steps, exhausting their step budget without making meaningful task progress.



Figure 6: Correlation between ASR and Task-level Attack Success Rate (TASR). TASR is generally similar to ASR and tends to be higher than ASR when ASR is low, indicating that even occasional pop-up clicks are sufficient to cause task failure.

URL, granting a permission, or executing attacker-controlled code).

5.9 Defense Analysis

System Prompt Defense. Table 8 evaluates system prompt defenses applied before task execution. A generic prompt instruction (*System Prompt Defense*: instructing the agent to be careful of suspicious pop-ups) has negligible effect—ASR actually increases slightly in some settings (95.9% vs. 93.3% on OSWorld-Screen), likely because the defense instruction inadvertently focuses agent attention on pop-up detection. A task-*specific* defense prompt (explicitly describing the format of our attack and instructing agents to ignore such pop-ups) reduces ASR more meaningfully: to 52.0% on OSWorld-Screen (from 93.3%) and to 72.3% on OSWorld-SoM (from 91.8%), but remains largely ineffective on VisualWebArena-SoM (60.2% vs. 62.1%). These results suggest that agents lack robust instruction-following capabilities when presented with conflicting strong visual cues, consistent with findings on the instruction hierarchy problem in LLMs (Wallace et al., 2024).

Step-wise Prompt Defense. Table 9 reports a stronger *Step-wise Prompt Defense* that injects a reminder at every step to avoid clicking suspicious pop-ups (evaluated on GPT-4-Turbo OSWorld-Screen). This reduces ASR dramatically to 5.9% (standard attack) or 10.4% (attack with variance), yet TASR remains 32.0%–44.0% and SR only recovers to 8–10%. The persistence of high TASR despite low ASR confirms the conclusion from

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
Default Attack	93.3	2.0		91.8	8.0		62.1	45.8	
System Prompt Defense	95.9	6.0	18.0	93.4	14.0	52.0	60.3	47.2	63.9
System Prompt Defense$_{\text{specific}}$	52.0	6.0		72.3	24.0		60.2	45.8	

Table 8: Ablations for the system prompt defense.

	OSWorld-Screen			
	ASR$_\downarrow$	TASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
Step-wise Prompt Defense	5.9	32.0	8.0	18.0
+ Attack Variance	10.4	44.0	10.0	

Table 9: Step-wise prompt defense. We use the GPT-4-Turbo screen agent on OSWorld for the ablation.

Figure 6: even rare pop-up clicks can be catastrophic for task success. Furthermore, repeated warnings appear to interfere with normal agent decision-making, as SR under step-wise defense (8–10%) remains below OSR (18%).

These results collectively indicate that prompt-based defenses are insufficient for reliably protecting VLM computer-use agents against pop-up attacks. More robust defenses—such as modality-aware visual anomaly detection, environmental risk estimation (Zhang et al., 2024; Ma et al., 2024), or architectural changes to the instruction hierarchy (Wallace et al., 2024)—are needed to address this threat.

Among the most promising directions, *visual anomaly detection* could flag unexpected UI overlays by comparing incoming observations against a reference rendering of the page, alerting the agent when novel interactable elements appear without a corresponding user-initiated action. *Trusted execution environments*, in which the agent operates on a verified screen capture isolated from third-party content injection, could similarly curtail the attacker's ability to insert pop-ups. *Multi-agent architectures* with a dedicated security-reviewer role—an auxiliary model that inspects each proposed action before execution and vetoes suspicious clicks—offer another architectural safeguard. Finally, *adversarial training* with diverse pop-up examples, combined with RLHF-based safety alignment that penalizes clicks on unsolicited overlays, may build more inherent resistance into the model itself, though generalization to novel attack variants and real-world pop-up diversity remains an important open challenge for future work.

6 Conclusion

We presented **PopupAttack**, a practical and effective attack on VLM-based computer-use agents via adversarial pop-up windows. Our study demonstrates that all tested frontier VLMs—GPT-4-Turbo, GPT-4o, Gemini 1.5 Pro, Claude 3.5 Sonnet, and Claude 3.5 Sonnet v2—are highly susceptible to query-conditioned pop-up injections, with an average Attack Success Rate of $\sim$86% and task Success Rate drops of $\sim$47%. Through comprehensive ablations, we showed that semantic alignment between the pop-up and the user's goal (the attention hook) is the primary driver of attack effectiveness, explicit click instructions further boost ASR, and standard prompt-based defenses are largely inadequate. Our findings call for a fundamental rethinking of how VLM computer-use agents handle visual observations: rather than naively trusting all on-screen content as equally authoritative, agents should incorporate environmental risk awareness, maintain skepticism toward unsolicited interactive elements, and employ modality-aware defenses that go beyond text-level prompt engineering. We release our code to accelerate progress toward robust, trustworthy computer-use agents.

Limitations

Several limitations of this work deserve acknowledgment. First, our experiments use a fixed pop-up injection strategy; adaptive attackers may optimize pop-up designs based on agent responses. Second, we inject a single pop-up per task; multi-pop-up or dynamically changing scenarios may exhibit different characteristics. Third, the defenses we evaluate are limited to prompt-based approaches; adversarial training, visual anomaly detection, or other architectural defenses are beyond the scope of this study. Finally, our evaluation uses fixed task subsets for computational feasibility; results may vary on full benchmarks or with different task distributions. Additionally, our study focuses on text-based pop-ups; future

work should explore whether image-only or icon-based pop-ups achieve similar effects on models with stronger visual grounding, and whether culturally or linguistically varied pop-up content affects cross-lingual agent robustness.

Ethical Considerations

This work studies adversarial attacks on AI agents with the goal of improving safety and robustness. All experiments were conducted on public benchmarks in controlled settings. We responsibly disclose our findings and release code to enable the research community to develop and evaluate defenses. We do not provide guidance for real-world malicious deployment of the attack.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Saaket Agashe, Jiuzhou Han, Shuyu Gan, Jiachen Yang, Ang Li, and Xin Eric Wang. 2024. Agent s: An open agentic framework that uses computers like a human. *Preprint*, arXiv:2410.08164.

Anthropic. 2024. The claude 3 model family: Opus, sonnet, haiku. Technical report, Anthropic. Available at: https://www.anthropic.com/news/claude-3-family.

Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. 2024. Seeclick: Harnessing gui grounding for advanced visual gui agents. *Preprint*, arXiv:2401.10935.

Federal Trade Commission et al. 2013. . com disclosures: how to make effective disclosures in digital advertising. *March, http://www.ftc. gov/sites/default/files/attachments/press-releases/ftc-staff-revises-online-advertising-disclosureguidelines/130312dotcomdisclosures. pdf*.

Yuta Imamura, Rintaro Orito, Kritsana Chaikaew, Célia Manardo, Pattara Leelaprute, Masaya Sato, and Toshihiro Yamauchi. 2019. Threat analysis of fake virus alerts using webview monitor. In *2019 Seventh International Symposium on Computing and Networking (CANDAR)*, pages 28–36.

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Ruslan Salakhutdinov, and Daniel Fried. 2024. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. *Preprint*, arXiv:2401.13649.

Ponnurangam Kumaraguru, Yong Rhee, Alessandro Acquisti, Lorrie Faith Cranor, Jason Hong, and Elizabeth Nunge. 2007. Protecting people from phishing: the design and evaluation of an embedded training email system. In *Proceedings of the SIGCHI conference on Human factors in computing systems*, pages 905–914.

Zeyi Liao, Lingbo Mo, Chejian Xu, Mintong Kang, Jiawei Zhang, Chaowei Xiao, Yuan Tian, Bo Li, and Huan Sun. 2024. Eia: Environmental injection attack on generalist web agents for privacy leakage. *Preprint*, arXiv:2409.11295.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. 2023. Autodan: Generating stealthy jailbreak prompts on aligned large language models. *Preprint*, arXiv:2310.04451.

Xinbei Ma, Yiting Wang, Yao Yao, Tongxin Yuan, Aston Zhang, Zhuosheng Zhang, and Hai Zhao. 2024. Caution for the environment: Multimodal agents are susceptible to environmental distractions. *Preprint*, arXiv:2408.02544.

OpenAI. 2024. Gpt-4o system card. `https://openai.com/index/gpt-4o-system-card/`.

OpenAI. 2025. A practical guide to building agents. Technical report, OpenAI.

Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, et al. 2025. Ui-tars: Pioneering automated gui interaction with native agents. *arXiv preprint arXiv:2501.12326*.

Machel Reid, Nikolay Savinov, Denis Teplyashin, Dmitry Lepikhin, Timothy Lillicrap, Jean-baptiste Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Firat, Julian Schrittwieser, et al. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*.

Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. 2023. Identifying the risks of lm agents with an lm-emulated sandbox. *Preprint*, arXiv:2309.15817.

Aditya K Sood and Richard J Enbody. 2011. Malvertising–exploiting web advertising. *Computer Fraud & Security*, 2011(4):11–16.

Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. 2024. The instruction hierarchy: Training llms to prioritize privileged instructions. *Preprint*, arXiv:2404.13208.

Chen Henry Wu, Jing Yu Koh, Ruslan Salakhutdinov, Daniel Fried, and Aditi Raghunathan. 2024. Adversarial attacks on multimodal agents. *Preprint*, arXiv:2406.12814.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. 2024. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Preprint*, arXiv:2404.07972.

Xinyu Xing, Wei Meng, Byoungyoung Lee, Udi Weinsberg, Anmol Sheth, Roberto Perdisci, and Wenke Lee. 2015. Understanding malvertising through ad-injecting browser extensions. In *Proceedings of the 24th international conference on world wide web*, pages 1286–1295.

Chejian Xu, Mintong Kang, Jiawei Zhang, Zeyi Liao, Lingbo Mo, Mengqi Yuan, Huan Sun, and Bo Li. 2024a. Advweb: Controllable black-box attacks on vlm-powered web agents. *Preprint*, arXiv:2410.17401.

Yiheng Xu, Zekun Wang, Junli Wang, Dunjie Lu, Tianbao Xie, Amrita Saha, Doyen Sahoo, Tao Yu, and Caiming Xiong. 2024b. Aguvis: Unified pure vision agents for autonomous gui interaction. *Preprint*, arXiv:2412.04454.

Jianwei Yang, Hao Zhang, Feng Li, Xueyan Zou, Chunyuan Li, and Jianfeng Gao. 2023. Set-of-mark prompting unleashes extraordinary visual grounding in gpt-4v. *Preprint*, arXiv:2310.11441.

Wenkai Yang, Xiaohan Bi, Yankai Lin, Sishuo Chen, Jie Zhou, and Xu Sun. 2024a. Watch out for your agents! investigating backdoor threats to llm-based agents. *Preprint*, arXiv:2402.11208.

Yulong Yang, Xinshan Yang, Shuaidong Li, Chenhao Lin, Zhengyu Zhao, Chao Shen, and Tianwei Zhang. 2024b. Security matrix for multimodal agents on mobile devices: A systematic and proof of concept study. *Preprint*, arXiv:2407.09295.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. *Preprint*, arXiv:2210.03629.

Yi Zeng, Hongpeng Lin, Jingwen Zhang, Diyi Yang, Ruoxi Jia, and Weiyan Shi. 2024. How johnny can persuade llms to jailbreak them: Rethinking persuasion to challenge ai safety by humanizing llms. *Preprint*, arXiv:2401.06373.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. 2024. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents. *Preprint*, arXiv:2403.02691.

Zhuohao Jerry Zhang, Eldon Schoop, Jeffrey Nichols, Anuj Mahajan, and Amanda Swearngin. 2024. From interaction to impact: Towards safer ai agents through understanding and evaluating ui operation impacts. *Preprint*, arXiv:2410.09006.

Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. 2024. Gpt-4v(ision) is a generalist web agent, if grounded. *Preprint*, arXiv:2401.01614.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. 2023. Webarena: A realistic web environment for building autonomous agents. *Preprint*, arXiv:2307.13854.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *Preprint*, arXiv:2307.15043.