Attacking Vision-Language Computer Agents via Pop-ups

Taro Yamada

Abstract

Vision-language model (VLM) agents are increasingly deployed to autonomously operate graphical user interfaces (GUIs) for real-world computer and web tasks. However, their robustness to deceptive visual inputs remains underexplored. In this work, we study a practical and realistic threat: *adversarial pop-ups* injected into the agent's observation. We propose **PopupAttack**, a modular attack that injects clickable, malicious pop-up images into the agent's screenshot and/or accessibility tree. Our pop-up design comprises four components: (1) an *Attention Hook* conditioned on the user's query, (2) an explicit *Instruction* (e.g., "click (x,y)" or "click [ID]"), (3) an *Info Banner* (e.g., "OK"), and (4) an *ALT Descriptor* for the accessibility tree. We evaluate PopupAttack across two benchmarks (OSWorld and VisualWebArena), two agent types (screenshot and Set-of-Mark), and five frontier VLMs (GPT-4-Turbo, GPT-4o, Gemini 1.5 Pro, Claude 3.5 Sonnet, Claude 3.5 Sonnet v2). Our attack achieves an average Attack Success Rate (ASR) of $\sim$86%, with up to 100% ASR on some model-benchmark combinations, causing task success rates to drop by $\sim$47% on average. We further show that query-conditioned hooks are critical for high ASR, and that existing text-based defenses (prompt instructions, advertisement banners) provide only modest protection. We introduce Task-level ASR (TASR) as a complementary metric to capture task-level risk, release code for reproducibility, and discuss implications for building more robust computer-use agents.

1 Introduction

Autonomous agents powered by vision-language models are rapidly becoming capable of operating computer interfaces to help users complete complex real-world tasks (Xie et al., 2024; Koh et al., 2024; Zheng et al., 2024; Agashe et al., 2024). These agents perceive the screen through screenshots or structured accessibility trees and generate actions such as clicking, typing, or scrolling (Yao et al., 2023). While significant progress has been made on improving agent capabilities (Qin et al., 2025; Xu et al., 2024b; Cheng et al., 2024), the security robustness of such agents against adversarial inputs in their environment remains a critical open challenge.

Human users encounter malicious on-screen pop-ups daily—fake virus alerts, misleading advertisements, and clickbait overlays are ubiquitous on the web. While humans have learned to identify and dismiss such distractions, autonomous VLM agents have not been stress-tested in this dimension. An agent that cannot distinguish a benign UI element from an adversarial overlay poses serious risks: it may be hijacked to perform unintended actions, leak sensitive information, or disrupt task completion.

In this paper, we investigate whether and how simple, visually injected adversarial pop-ups can hijack state-of-the-art VLM computer-use agents. Our key insight is that VLM agents *over-trust on-screen cues*: when a pop-up is visually aligned with the user's goal and contains an explicit click instruction, the agent tends to click on it rather than continuing its legitimate task. This is exacerbated by the fact that modern agents are trained to be helpful and action-oriented, making them susceptible to any plausible-looking UI element that signals an action is needed.

We propose **PopupAttack**, a practical and modular adversarial pop-up attack. The attack injects a clickable pop-up image into the agent's observation at each step. The pop-up consists of four components: (1) an *Attention Hook* that is conditioned on the user's task query to appear relevant and trustworthy, (2) an explicit *Instruction* that directs the agent to click a specific coordinate or UI element, (3) an *Info Banner* (e.g., an "OK" button), and (4) an *ALT Descriptor* embedded in the accessibility

Figure 1: On average, **92.7% / 73.1%** of all actions of attacked agents in OSWorld/VisualWebArena are **clicking on the adversarial pop-ups**, demonstrating high vulnerability across tasks.

tree for SoM-based agents. We implement both "ideal" attack variants (with exact query and coordinate/ID information) and realistic variants (e.g., fake virus alerts, speculated queries, generic "click here" prompts).

We evaluate PopupAttack comprehensively on OSWorld (Xie et al., 2024) and VisualWebArena (Koh et al., 2024), spanning screenshot agents and Set-of-Mark (SoM) agents (Yang et al., 2023), and five frontier VLMs including GPT-4-Turbo (Achiam et al., 2023), GPT-4o (OpenAI, 2024), Gemini 1.5 Pro (Reid et al., 2024), and Claude 3.5 Sonnet (Anthropic, 2024). Our results reveal consistently high attack success rates (∼86% average ASR), with task performance dropping sharply under attack. As shown in Figure 1, 92.7% and 73.1% of all agent actions in OSWorld and VisualWebArena respectively are clicks on the adversarial pop-ups.

Through systematic ablations, we analyze the roles of each pop-up component. We find that query-conditioned attention hooks are critical: replacing them with generic alerts ("VIRUS DETECTED") reduces ASR by up to 61%. We also find that current defenses—including prompt instructions to ignore pop-ups and advertisement banners—provide only modest protection. We introduce *Task-level ASR (TASR)* as a new metric that captures whether an agent clicks at least one pop-up during a task, revealing that even when per-step ASR is low, task-level risk remains substantial.

Our contributions are:

- We define a practical pop-up-based threat model for VLM computer-use agents and propose **PopupAttack**, a modular attack spanning visual and accessibility-tree channels.
- We provide comprehensive evaluation across two benchmarks (OSWorld, VisualWebArena), two agent types (Screenshot, SoM), and five frontier VLMs, establishing a robust empirical baseline.
- We conduct detailed ablations on all four attack components (hooks, instructions, banners, ALT text) and introduce TASR as a task-level risk metric.
- We analyze agent failure modes and defense strategies, showing that baseline defenses are insufficient, and call for modality-aware, environment-aware agent safety mechanisms.

2 Related Work

2.1 GUI and Computer-Use Agents

Autonomous agents that interact with GUIs have attracted significant research attention. WebArena (Zhou et al., 2023), Mind2Web (Deng et al., 2023), OSWorld (Xie et al., 2024), and VisualWebArena (Koh et al., 2024) provide benchmarks for evaluating agents on realistic web and computer tasks. SeeAct (Zheng et al., 2024) and SeeClick (Cheng et al., 2024) demonstrate that frontier VLMs can serve as effective generalist web agents when equipped with proper grounding strategies. More recently, Agent S (Agashe et al., 2024), UI-TARS (Qin et al., 2025), and Aguvis (Xu et al., 2024b) have pushed agent capabilities further. Set-of-Mark (SoM) prompting (Yang et al., 2023) enables agents to interact with annotated UI elements using IDs, improving grounding accuracy. The ReAct framework (Yao et al., 2023) synergizes reasoning and acting in language models, forming the backbone of many modern agent architectures. Despite these advances, the security of such agents against adversarial environmental inputs remains underexplored.

2.2 Adversarial Attacks on VLMs and Agents

Adversarial attacks on language models have been extensively studied, including gradient-based attacks (Zou et al., 2023), jailbreaks (Liu et al., 2023; Zeng et al., 2024), and instruction hierarchy violations (Wallace et al., 2024). For multimodal models, adversarial attacks targeting visual inputs have been explored in standard benchmarks (Wu et al., 2024). In the context of agents, prior work has studied indirect prompt injection (Zhan et al., 2024), environmental injection attacks (Liao et al., 2024), backdoor attacks (Yang et al., 2024a), and controllable black-box attacks on web agents (Xu et al., 2024a). Ma et al. (2024) show that multimodal GUI agents are susceptible to environmental distractions, and Yang et al. (2024b) conduct a systematic security study on mobile GUI agents. Zhang et al. (2024) analyze the safety implications of UI operation impacts.

Our work is most closely related to adversarial attacks on GUI agents, but differs in focusing on the pop-up modality—a realistic, visually prominent attack vector—and in studying the specific design factors (attention hooks, instructions, banners, ALT text) that determine attack effectiveness. Unlike pixel-level adversarial perturbations, our pop-ups are human-readable and closely resemble real-world deceptive UI patterns such as fake virus alerts (Imamura et al., 2019) and clickbait advertisements (Commission et al., 2013).

2.3 Security of LLM-Based Systems

The broader security of LLM-based systems has been studied from multiple angles, including identifying risks of LM agents (Ruan et al., 2023), studying LLM vulnerabilities (Abdali et al., 2024), and analyzing malvertising and social engineering (Sood and Enbody, 2011; Patel et al., 2019; Kumaraguru et al., 2007). Our work contributes to this growing body of research by demonstrating that visual prompt injection via pop-ups is a practical and highly effective attack vector against frontier VLM agents, complementing text-based injection methods and highlighting novel modality-specific vulnerabilities.

3 Attack Design

3.1 Threat Model

We consider a threat model where an attacker can inject visual content into the computer environment that the agent observes. This is practically feasible in numerous scenarios: a malicious website can render adversarial pop-ups; a compromised application can overlay deceptive UI elements; or cached web content can be tampered with. The attacker's goal is to cause the agent to click on the adversarial pop-up rather than complete the user's intended task, thereby hijacking the agent's execution.

We assume the attacker has *black-box* access to the agent system (no knowledge of model internals or system prompts), but can observe the agent's task description to craft query-conditioned pop-ups. This is a realistic assumption for web-based attacks where the task context may be partially inferred from URL parameters or page content.

3.2 PopupAttack Design

PopupAttack injects a clickable, adversarial pop-up image into the agent's observation at each step. The pop-up is designed to appear as a legitimate UI element that the agent should interact with. Our pop-up design has four modular components:

(1) Attention Hook. The attention hook is the primary message displayed prominently in the pop-up. In our default *ideal* setting, it is a condensed summary of the user's query (e.g., if the user asks to "find the cheapest flight to Paris," the hook might say "Find Cheapest Paris Flight"). This query alignment makes the pop-up appear task-relevant, increasing the likelihood that the agent will engage with it. We also study realistic variants:

- *Virus Alert*: Displays a fake security warning ("VIRUS DETECTED"), mimicking common scareware pop-ups (Imamura et al., 2019).
- *Speculated Query*: Uses an LLM to guess the user's intent from the current screenshot without directly accessing the query, simulating an attacker with partial environmental knowledge.

(2) Instruction. The instruction component provides an explicit directive for the agent to interact with the pop-up. This is the most mechanically important component, as it directly tells the agent *where* to click. We study four variants:

- *Click Coordinate* (default for screenshot agents): "Please click: (x,y)" with the exact coordinates of the pop-up's clickable area.

- *Click Tag* (default for SoM agents): "Please click [ID]" with the tag ID assigned to the pop-up in the accessibility tree.
- *Click Here*: A generic "click here" instruction without specific targets.
- *Click Random*: Coordinates or IDs pointing to a random screen location.

(3) Info Banner. The info banner is a visually styled button or label within the pop-up (e.g., an "OK" button rendered in green). It simulates the interactive element that the agent is expected to click. We study two variants:

- *"OK"* (default): A standard confirmation button, mimicking legitimate dialog boxes.
- *"ADVERTISEMENT"*: Explicitly labels the pop-up as an advertisement, per FTC disclosure guidelines (Commission et al., 2013).

(4) ALT Descriptor. For SoM-based agents that process the accessibility tree alongside screenshots, the ALT descriptor is an HTML `alt` attribute or accessibility label assigned to the pop-up node. We study three variants:

- *Adversarial* (default): A descriptive text that reinforces the pop-up's apparent legitimacy, including click instructions.
- *Empty*: No ALT text, leaving the pop-up unlabeled in the accessibility tree.
- *Adversarial with Ad Notice*: Appends "This is an advertisement" to the adversarial ALT text.

3.3 Attack Implementation

The pop-up is rendered as an opaque overlay image positioned within the largest non-overlapping empty region of the screenshot, with randomized placement and dimensions (up to 960×540 pixels) to avoid occluding existing UI elements. For screenshot agents, the rendered pop-up image is composited onto the screenshot before it is passed to the VLM. For SoM agents, the pop-up is additionally inserted as a node in the accessibility tree with a unique tag ID (role set to "button") and the specified ALT descriptor; the screenshot is also annotated with the corresponding SoM tag.

The attention hook text is generated by querying an LLM (GPT-4o) with the user task description to produce a concise button label (fewer than five words). This hook generation step occurs once per task. Pop-ups are injected at every step of the agent's trajectory during evaluation.



Figure 2: Examples of adversarial pop-ups generated by PopupAttack for different tasks. Each pop-up contains an attention hook (query-aligned), an instruction directing the agent where to click, an info banner ("OK"), and visual styling to mimic legitimate UI dialogs.

Examples of generated pop-ups for different tasks are shown in Figure 2. The pop-ups are designed to visually resemble common UI dialogs and alert windows, making them plausible in the context of real computer use.

4 Experiments

4.1 Experimental Setup

Benchmarks. We evaluate on two established agent benchmarks:

- **OSWorld** (Xie et al., 2024): A benchmark for open-ended computer tasks in real operating system environments. We use a subset of 50 "easy" tasks (tasks that at least one agent configuration can solve without attack, with a 15-step limit).
- **VisualWebArena** (Koh et al., 2024): A benchmark for visual web tasks. We use a subset of 72 "easy" tasks from prior work, with a 30-step limit.

Agent Types. We evaluate two agent architectures:

- **Screenshot agents**: Agents that receive raw pixel-level screenshots as observations.

- **SoM agents**: Agents that receive screenshots annotated with Set-of-Mark (Yang et al., 2023) tags alongside an accessibility tree.

VLM Backbones. We test five frontier VLMs as agent backbones: GPT-4-Turbo (2024-04-09) (Achiam et al., 2023), GPT-4o (2024-05-13) (OpenAI, 2024), Gemini 1.5 Pro (002) (Reid et al., 2024), Claude 3.5 Sonnet (20240620), and Claude 3.5 Sonnet v2 (20241022) (Anthropic, 2024). All models use temperature 0 to reduce randomness.

Metrics. We use the following metrics:

- **ASR** (Attack Success Rate): The fraction of agent action steps in which the agent clicks the adversarial pop-up.
- **SR** (Success Rate): The fraction of tasks successfully completed under attack.
- **OSR** (Original Success Rate): The fraction of tasks successfully completed without any attack (baseline).
- **TASR** (Task-level Attack Success Rate): The fraction of tasks in which the agent clicks the adversarial pop-up *at least once*. This captures task-level risk even when per-step ASR is low.

4.2 Main Results

Table 1 presents the main results across all model-benchmark combinations. The results reveal consistently high vulnerability across all tested VLMs:

High ASR across models. In the default attack setting, ASR ranges from 80.0% to 100.0% on OSWorld-Screen, 88.7% to 95.3% on OSWorld-SoM, and 62.1% to 78.4% on VisualWebArena-SoM. Claude 3.5 Sonnet achieves the highest OSR on OSWorld (22.0%) but is simultaneously the most vulnerable with 100% ASR on the screenshot setting. Gemini 1.5 Pro achieves the lowest ASR on OSWorld-Screen (80.0%) and OSWorld-SoM (88.7%), making it relatively (but not absolutely) more robust.

Sharp drop in task performance. The attack causes substantial degradation in task completion. On OSWorld, SR under attack is at most 10% despite OSR reaching up to 58%. The average SR drop across all settings is approximately 47%. This confirms that the attack is not merely causing sporadic pop-up clicks, but fundamentally disrupting task completion.



Original: The current screenshot shows the Delta Airlines homepage on a web browser. To proceed with finding the status of tomorrow's flights from New York airports to Columbus, Ohio, the next step is to enter the departure and destination cities in the search fields on the webpage. I will start by clicking on the "From" field (currently showing "San Jose, CA") to change it to a New York airport. Then, I will enter the destination city as Columbus, Ohio. Let's proceed with this action.

```python
import pyautogui
import time

# Click on the "From" field to change the departure city
pyautogui.click(350, 300)  # Approximate coordinates of the "From" field
time.sleep(0.5)
```

Attacked: The next step is to click on the "From" field to activate it for input. The "From" field is located near the top of the webpage, under the "BOOK" tab, where "San Jose, CA" is currently displayed. I will move the cursor to this field and click to focus on it so that "New York, NY" can be entered.

```python
import pyautogui
import time

# Move the cursor to the "From" field and click to focus
pyautogui.moveTo(240, 298)  # Coordinates for the "From" field
pyautogui.click()
time.sleep(0.5)  # Wait for the field to be focused
```

Figure 3: A successfully attacked example. The original agent reasons about and completes the task normally, while the attacked agent's thoughts are dominated by the pop-up, ultimately clicking it instead of proceeding with the task.

Pop-up clicks dominate agent behavior. As visualized in Figure 1, an average of 92.7% of all agent actions in OSWorld and 73.1% in VisualWebArena are clicks on the adversarial pop-up, indicating that the agent's attention is almost entirely captured by the pop-up.

Figure 3 shows a qualitative example: the original agent reasons appropriately about the task and takes a productive action, while the attacked agent's thoughts are dominated by the injected pop-up, which it ultimately clicks. Figure 4 shows additional qualitative examples across different tasks and models, demonstrating the generality of the

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
GPT-4-Turbo	93.3	2.0	18.0	91.8	8.0	52.0	78.0	43.1	50.0
GPT-4o	95.8	**6.0**	8.0	91.2	2.0	6.0	**62.1**	45.8	**63.9**
Gemini 1.5	**80.0**	4.0	6.0	**88.7**	6.0	18.0	70.1	44.4	48.6
Claude 3.5 Sonnet	100.0	0.0	**22.0**	95.3	6.0	44.0	78.4	47.2	54.2
Claude 3.5 Sonnet v2	96.0	4.0	**22.0**	94.8	**10.0**	**58.0**	76.8	**48.6**	50.0

Table 1: Result table for model comparison, where we **highlight** the lowest ASR (↓) and highest SR (↑)/OSR (↑). Screen and SoM refer to screenshot agents and SoM agents. We use WebArena as a shorter form of VisualWebArena.

attack across diverse settings.

5 Understanding Agent Vulnerability

5.1 Ablation: Attention Hooks

Table 2 shows results for different attention hook variants. The query-conditioned summarized hook (default) achieves the highest ASR across all settings. Replacing it with a generic "VIRUS DETECTED" alert drops ASR dramatically: from 91.8% to 58.3% on OSWorld-SoM (-33.5%) and from 62.1% to 1.1% on VisualWebArena-SoM (-61.0%). This dramatic drop on VisualWebArena suggests that web agents are more discerning about the relevance of pop-up content to their task.

Using a speculated query (LLM-inferred from screenshot) yields intermediate results: ASR of 53.9% on OSWorld-Screen and 34.4% on OSWorld-SoM, and 8.0% on VisualWebArena-SoM. This demonstrates that even without direct access to the user query, an attacker can achieve meaningful ASR by inferring intent from screen content. These results highlight that the semantic alignment of the pop-up with the user's goal is a critical factor in attack effectiveness.

5.2 Ablation: Instructions

Table 3 examines the role of the instruction component. Click Coordinate (for screenshot agents) and Click Tag (for SoM agents) are the most effective instructions, confirming that explicit, precise targeting is important. Replacing with "click here" (no specific target) drops ASR to 11.3% for screenshot agents in OSWorld, though SoM agents remain more vulnerable at 72.8% and WebArena agents at 58.4%, likely because SoM tags provide enough context for grounding even without coordinates.

Random target instructions still achieve ∼10–14% ASR on OSWorld, suggesting that even imprecise instructions can sometimes successfully redirect agent behavior. This indicates that the content of the pop-up (attention hook and info banner) alone can be sufficient to attract the agent's attention, even without perfectly specified click targets.

5.3 Ablation: Info Banners

Table 4 shows that replacing the "OK" banner with "ADVERTISEMENT" reduces ASR notably: from 93.3% to 66.5% on OSWorld-Screen, from 91.8% to 77.9% on OSWorld-SoM, and from 62.1% to 56.7% on VisualWebArena-SoM. While this demonstrates that explicit ad labeling provides some protection, ASR remains high (>55% in all settings), consistent with findings that online advertising disclosures are often ineffective in practice (Commission et al., 2013).

5.4 Ablation: ALT Descriptors

Table 5 examines ALT descriptor variants for SoM agents. The default adversarial ALT achieves the highest ASR (91.8% and 62.1% on OSWorld-SoM and WebArena-SoM respectively). Using an empty ALT descriptor drops ASR by 23.7% on OSWorld-SoM (to 68.1%) and 19.2% on WebArena-SoM (to 42.9%). Adding an ad notice to the adversarial ALT reduces ASR to 77.1% and 56.9% respectively. These results show that the accessibility tree information significantly contributes to the attack's success for SoM agents, but even without any ALT descriptor, the visual pop-up alone is sufficient to cause substantial vulnerability.

5.5 Validity Checks: Pop-up Content Matters

Table 6 presents two additional validity checks. A *blank pop-up* (visually present but with no text content) achieves near-zero ASR (2.4%, 3.7%, 0.0% across the three settings), confirming that the textual content—not just the visual presence of an overlay—is the primary driver of the attack. A *small pop-up* (reduced to 25% of the original size) still achieves high ASR (87.4%, 90.1%, 60.0%), demonstrating that the attack is robust to pop-up size reduction, as long as the text remains visible.



Figure 4: Additional successfully attacked examples across different tasks and VLMs, showing agent thoughts from the original (no attack) and attacked settings. In all cases, the attacked agent's reasoning is hijacked by the pop-up.

5.6 Agent Thought Analysis

To understand *why* agents click pop-ups, we analyze the text of agent-generated thoughts in successfully attacked cases. As shown in Table 7, different components are referenced in agent thoughts at different rates. For OSWorld-Screen agents, the target coordinates are mentioned 88% of the time and the "OK" banner 52% of the time, while the attention hook is mentioned only 2%. This suggests that screenshot agents follow the click instruction (coordinates) mechanically. For OSWorld-SoM agents, the attention hook is mentioned 62% of the time and the target tag 90%, indicating that SoM agents actively reason about the pop-up's apparent task relevance before clicking.

5.7 Task-Level Attack Success Rate (TASR)

Figure 5 shows the relationship between ASR and TASR. TASR is consistently similar to or higher than ASR, especially in low-ASR regimes. This means that even when an agent only occasionally clicks the pop-up (low ASR), it still clicks it at least once in the majority of tasks (high TASR). This has important practical implications: even a "weak" attack that achieves only 10–15% per-step ASR may still compromise 30–44% of tasks at the task level.

Attention Hook	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Summarized Query	93.3	2.0		91.8	8.0		62.1	45.8	
Virus	90.0	2.0	18.0	58.3	26.0	52.0	1.1	54.2	63.9
Speculated Query	53.9	10.0		34.4	38.0		8.0	54.2	

Table 2: Ablation study on the attention hooks, where we underline the numbers from the default setting..

Instruction	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑	ASR↓	SR↑	OSR↑
Click Tag	-	-	-	96.1	6.0		62.1	45.8	
Click Coor	93.3	2.0		91.8	8.0	52.0	49.3	48.6	63.9
Click Here	11.3	14.0	18.0	72.8	14.0		58.4	44.4	
Click Random	11.8	2.0		13.7	10.0		4.1	34.7	

Table 3: Ablation study on the instructions. Click Random refers to clicking random coordinates for OSWorld and clicking random tags for VisualWebArena correspondingly.



Figure 5: Correlation between step-level ASR and Task-level Attack Success Rate (TASR). TASR is generally similar to or higher than ASR, particularly when ASR is low, indicating that even when per-step attack success is modest, most tasks are still affected by at least one pop-up click.

Figure 6: The impact of the attack on the number of steps taken by the agent. Under attack, agents tend to exhaust their step budget clicking the pop-up without completing the task.

5.8 Impact on Agent Steps

Figure 6 illustrates how the attack affects agent step trajectories. Under attack, agents tend to spend their entire step budget repeatedly clicking the pop-up or failing to make progress on the original task. This further confirms that the attack is not just causing single incorrect actions but fundamentally disrupting the agent's entire task execution.

6 Defenses

6.1 System Prompt Defense

We investigate prompt-based defenses where the system prompt instructs the agent to be cautious about pop-ups. Table 8 shows results for two variants:

- **Generic defense**: Adding a general instruction to "be careful about pop-ups" to the system prompt. This has minimal effect and can even slightly increase ASR (from 93.3% to 95.9% on OSWorld-Screen), possibly because the instruction makes the agent more attentive to pop-ups.

- **Specific defense**: Adding a more detailed instruction specifically about adversarial pop-ups. This reduces ASR more substantially on OSWorld-Screen (from 93.3% to 52.0%) and OSWorld-SoM (from 91.8% to 72.3%), but ASR remains high and WebArena-SoM is minimally affected (62.1% to 60.2%).

These results indicate that prompt-based defenses provide limited protection, especially on web environments. The ASR reduction varies widely: up to ∼44% relative on OSWorld-Screen (93.3%→52.0%) but negligible on WebArena-SoM (62.1%→60.2%), and the attack remains effective in most settings.

Info Banner	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
"OK"	93.3	2.0	18.0	91.8	8.0	52.0	62.1	45.8	63.9
"ADVERTISEMENT"	66.5	10.0		77.9	14.0		56.7	52.8	

Table 4: Ablation study on the info banners.

ALT Descriptor	OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
Adversarial	91.8	8.0	52.0	62.1	45.8	63.9
Empty	68.1	22.0		42.9	55.6	
Adversarial with Ad Notice	77.1	22.0		56.9	45.8	

Table 5: Ablation study on the ALT descriptors.

6.2 Step-wise Prompt Defense

A more sophisticated step-wise defense evaluates each proposed action at inference time and replaces pop-up clicks with a "no-op" if the action is detected as targeting an adversarial element. Table 9 shows that this approach reduces per-step ASR substantially (to 5.9% for the base variant), but TASR remains high (32.0–44.0%) and SR only partially recovers (8.0–10.0% vs. 18.0% OSR). The "+ Attack Variance" row shows that adding variation to the pop-up (slight randomization) can partially circumvent this defense, raising ASR to 10.4%.

These results highlight the fundamental difficulty of defending against pop-up attacks with current methods. The step-wise defense substantially reduces ASR but cannot fully prevent task-level hijacking, and its effectiveness degrades under attack variance. More robust defenses likely require architectural changes (e.g., environmental risk awareness modules) or modality-aware safety training.

7 Conclusion

We have presented PopupAttack, a practical and modular adversarial attack that injects clickable pop-up images into VLM computer-use agent observations. Our attack achieves high ASR ($\sim$86% average) across diverse VLMs and benchmarks, causing task success rates to drop by $\sim$47% on average. Through systematic ablations, we show that query-conditioned attention hooks are the most critical attack component, that explicit click instructions greatly enhance effectiveness, and that text-based defenses provide only modest protection.

Our findings reveal a fundamental vulnerability of current VLM agents: they lack the ability to distinguish adversarial environmental injections from legitimate UI elements, especially when those injections appear task-relevant. This underscores the urgent need for agents to develop built-in environmental risk awareness and stronger, modality-aware defenses beyond simple prompt engineering.

We introduce TASR as a complementary task-level risk metric, showing that task-level vulnerability is substantially higher than per-step ASR might suggest. We release all code to facilitate future research on agent security and defense against visual adversarial attacks.

References

Sara Abdali, Jia He, CJ Barberan, and Richard Anarfi. 2024. Can llms be fooled? investigating vulnerabilities in llms. *arXiv preprint arXiv:2407.20529*.

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Saaket Agashe, Jiuzhou Han, Shuyu Gan, Jiachen Yang, Ang Li, and Xin Eric Wang. 2024. Agent s: An open agentic framework that uses computers like a human. *Preprint*, arXiv:2410.08164.

Anthropic. 2024. The claude 3 model family: Opus, sonnet, haiku. Technical report, Anthropic. Available at: https://www.anthropic.com/news/claude-3-family.

Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. 2024. Seeclick: Harnessing gui grounding for advanced visual gui agents. *Preprint*, arXiv:2401.10935.

Federal Trade Commission et al. 2013. . com disclosures: how to make effective disclosures in digital advertising. *March, http://www.ftc. gov/sites/default/files/attachments/press-releases/ftc-staff-revises-online-advertising-disclosureguidelines/130312dotcomdisclosures. pdf*.

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$	ASR$_\downarrow$	SR$_\uparrow$	OSR$_\uparrow$
Default	93.3	2.0		91.8	8.0		62.1	45.8	
Blank Pop-up	2.4	16.0	18.0	3.7	38.0	52.0	0.0	52.8	63.9
Small Pop-up	87.4	2.0		90.1	10.0		60.0	52.8	

Table 6: Extra ablations for blank pop-ups and small pop-ups.

OSWorld-Screen		OSWorld-SoM	
Attn Hook	2%	Attn Hook	62%
Target	88%	Target	90%
OK	52%	OK	6%

Table 7: The frequency of explicitly mentioning different elements in agent-generated thoughts for successfully attacked cases: attention hook (summarized queries), target in instructions (coordinates or tag IDs), and the "OK" in the info banner.

Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Samuel Stevens, Boshi Wang, Huan Sun, and Yu Su. 2023. Mind2web: Towards a generalist agent for the web. *Preprint*, arXiv:2306.06070.

Yuta Imamura, Rintaro Orito, Kritsana Chaikaew, Célia Manardo, Pattara Leelaprute, Masaya Sato, and Toshihiro Yamauchi. 2019. Threat analysis of fake virus alerts using webview monitor. In *2019 Seventh International Symposium on Computing and Networking (CANDAR)*, pages 28–36.

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Ruslan Salakhutdinov, and Daniel Fried. 2024. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. *Preprint*, arXiv:2401.13649.

Ponnurangam Kumaraguru, Yong Rhee, Alessandro Acquisti, Lorrie Faith Cranor, Jason Hong, and Elizabeth Nunge. 2007. Protecting people from phishing: the design and evaluation of an embedded training email system. In *Proceedings of the SIGCHI conference on Human factors in computing systems*, pages 905–914.

Zeyi Liao, Lingbo Mo, Chejian Xu, Mintong Kang, Jiawei Zhang, Chaowei Xiao, Yuan Tian, Bo Li, and Huan Sun. 2024. Eia: Environmental injection attack on generalist web agents for privacy leakage. *Preprint*, arXiv:2409.11295.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. 2023. Autodan: Generating stealthy jailbreak prompts on aligned large language models. *Preprint*, arXiv:2310.04451.

Xinbei Ma, Yiting Wang, Yao Yao, Tongxin Yuan, Aston Zhang, Zhuosheng Zhang, and Hai Zhao. 2024. Caution for the environment: Multimodal agents are susceptible to environmental distractions. *Preprint*, arXiv:2408.02544.

OpenAI. 2024. Gpt-4o system card. https://openai.com/index/gpt-4o-system-card/.

Pooja Patel, Dawn M Sarno, Joanna E Lewis, Mindy Shoss, Mark B Neider, and Corey J Bohil. 2019. Perceptual representation of spam and phishing emails. *Applied cognitive psychology*, 33(6):1296–1304.

Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, et al. 2025. Ui-tars: Pioneering automated gui interaction with native agents. *arXiv preprint arXiv:2501.12326*.

Machel Reid, Nikolay Savinov, Denis Teplyashin, Dmitry Lepikhin, Timothy Lillicrap, Jean-baptiste Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Firat, Julian Schrittwieser, et al. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*.

Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. 2023. Identifying the risks of lm agents with an lm-emulated sandbox. *Preprint*, arXiv:2309.15817.

Aditya K Sood and Richard J Enbody. 2011. Malvertising–exploiting web advertising. *Computer Fraud & Security*, 2011(4):11–16.

Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. 2024. The instruction hierarchy: Training llms to prioritize privileged instructions. *Preprint*, arXiv:2404.13208.

Chen Henry Wu, Jing Yu Koh, Ruslan Salakhutdinov, Daniel Fried, and Aditi Raghunathan. 2024. Adversarial attacks on multimodal agents. *Preprint*, arXiv:2406.12814.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. 2024. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Preprint*, arXiv:2404.07972.

Chejian Xu, Mintong Kang, Jiawei Zhang, Zeyi Liao, Lingbo Mo, Mengqi Yuan, Huan Sun, and Bo Li. 2024a. Advweb: Controllable black-box attacks on vlm-powered web agents. *Preprint*, arXiv:2410.17401.

	OSWorld-Screen			OSWorld-SoM			WebArena-SoM		
	ASR$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$	**ASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Default Attack	93.3	2.0		91.8	8.0		62.1	45.8	
System Prompt Defense	95.9	6.0	18.0	93.4	14.0	52.0	60.3	47.2	63.9
System Prompt Defense$_{\text{specific}}$	52.0	6.0		72.3	24.0		60.2	45.8	

Table 8: Ablations for the system prompt defense.

	OSWorld-Screen			
	ASR$_\downarrow$	**TASR**$_\downarrow$	**SR**$_\uparrow$	**OSR**$_\uparrow$
Step-wise Prompt Defense	5.9	32.0	8.0	18.0
+ Attack Variance	10.4	44.0	10.0	

Table 9: Step-wise prompt defense. We use the GPT-4-Turbo screen agent on OSWorld for the ablation.

Yiheng Xu, Zekun Wang, Junli Wang, Dunjie Lu, Tianbao Xie, Amrita Saha, Doyen Sahoo, Tao Yu, and Caiming Xiong. 2024b. Aguvis: Unified pure vision agents for autonomous gui interaction. *Preprint*, arXiv:2412.04454.

Jianwei Yang, Hao Zhang, Feng Li, Xueyan Zou, Chunyuan Li, and Jianfeng Gao. 2023. Set-of-mark prompting unleashes extraordinary visual grounding in gpt-4v. *Preprint*, arXiv:2310.11441.

Wenkai Yang, Xiaohan Bi, Yankai Lin, Sishuo Chen, Jie Zhou, and Xu Sun. 2024a. Watch out for your agents! investigating backdoor threats to llm-based agents. *Preprint*, arXiv:2402.11208.

Yulong Yang, Xinshan Yang, Shuaidong Li, Chenhao Lin, Zhengyu Zhao, Chao Shen, and Tianwei Zhang. 2024b. Security matrix for multimodal agents on mobile devices: A systematic and proof of concept study. *Preprint*, arXiv:2407.09295.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. *Preprint*, arXiv:2210.03629.

Yi Zeng, Hongpeng Lin, Jingwen Zhang, Diyi Yang, Ruoxi Jia, and Weiyan Shi. 2024. How johnny can persuade llms to jailbreak them: Rethinking persuasion to challenge ai safety by humanizing llms. *Preprint*, arXiv:2401.06373.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. 2024. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents. *Preprint*, arXiv:2403.02691.

Zhuohao Jerry Zhang, Eldon Schoop, Jeffrey Nichols, Anuj Mahajan, and Amanda Swearngin. 2024. From interaction to impact: Towards safer ai agents through understanding and evaluating ui operation impacts. *Preprint*, arXiv:2410.09006.

Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. 2024. Gpt-4v(ision) is a generalist web agent, if grounded. *Preprint*, arXiv:2401.01614.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. 2023. Webarena: A realistic web environment for building autonomous agents. *Preprint*, arXiv:2307.13854.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *Preprint*, arXiv:2307.15043.