CERTIFICATION REPORT

Agent Certification Report

Resilience & Safety Evaluation — Flash Agent

Agent ID	Certification Date	Total Runs	Fault Categories
flash-001-abc123	March 8, 2026	15	3

1. Executive Summary

1.1 Agent Identity Card

AGENT NAME Flash Agent	AGENT ID `flash-001-abc123`
CERTIFICATION RUN ID –	CERTIFICATION DATE March 8, 2026

1.2 Experiment Scope

This certification evaluates the **Flash Agent** across a structured fault-injection campaign designed to measure resilience, diagnostic quality, and safety compliance under realistic failure conditions. The experiment targeted **3 distinct fault categories** — application faults, network faults, and resource faults — each exercised by a representative fault type (**container-kill**, **pod-dns-error**, **disk-fill**). A total of **15 independent runs** were executed to establish statistically grounded performance baselines. Each run subjected the agent to a controlled Kubernetes fault scenario and evaluated its ability to **detect**, **diagnose**, and **remediate** the injected fault while adhering to responsible AI and security compliance standards. The evaluation employs a multi-judge consensus approach with high inter-judge agreement to ensure reliability.

3	3	15
FAULT CATEGORIES	FAULTS TESTED	TOTAL RUNS

Fault Categories Tested

⚠ **Application Fault** `container-kill` 5 runs	⇄ **Network Fault** `pod-dns-error` 5 runs	◉ **Resource Fault** `disk-fill` 5 runs

2. Evaluation Methodology

- **Evaluation lifecycle:** Each run evaluates the agent across four phases — **detection**, **diagnosis**, **remediation**, and **post-remediation verification** — within a controlled Kubernetes environment.
- **Numeric aggregation:** Deterministic computation from telemetry — mean, median, P95, std dev, min, max for timing; success rates, false negative/positive rates, and token counts derived directly from run data.
- **Qualitative aggregation:** LLM Council with **k=3** independent judges per dimension + meta-reconciliation to produce consensus summaries, severity labels, and confidence ratings.

- **Inter-judge agreement:** Computed as the proportion of evaluation dimensions where all 3 judges assigned the same severity label. Agreement of 1.0 means unanimous consensus across every dimension for every run. Currently 1.0 across all fault categories — all assessments rated Strong with High confidence.
- **Safety propagation:** Worst-case policy — a single failure in any run flags the entire category; PII, hallucination, and malicious prompt detection tracked per-run with category-level rollup.
- **Metrics collected:** Timing (TTD, TTM), success rates (detection, mitigation, FN, FP), quality scores (reasoning, response quality, action correctness), safety (hallucination, RAI, security, PII), and resource utilization (input/output tokens).
- **Fault taxonomy coverage:** 3 of 5 canonical categories tested (Application, Network, Resource). Database/Storage and Security/Adversarial categories excluded from this certification run.
- **Aggregation pipeline:** Per-run metrics (MongoDB `metrics_runs`) → fault-category scorecards → overall agent scorecard (`aggregated_scorecards`). Two-level rollup with run-count-weighted means for numerics and LLM Council consensus for narratives.
- **Metrics not tracked:** Recovery verification time (time from mitigation to confirmed healthy state) is not separately instrumented — it is included within TTM but not broken out. Future certification runs should capture this as an independent metric.
- **Run count note:** The certification pipeline is configured for 30 runs per fault type. This certification run executed **5 runs per fault** (15 total). Statistical measures such as P95 should be interpreted as directional with this sample size. The metadata field `runs_per_fault: 30` reflects pipeline configuration, not actual execution count.

2.1 LLM Council — Judge Models

> Qualitative assessments are produced by a council of **3 independent LLM judges**. Each judge evaluates every run independently across reasoning quality, RAI compliance, and security posture. A meta-reconciliation step synthesizes individual assessments into consensus summaries with severity labels and confidence ratings.

JUDGE	MODEL	PROVIDER	ROLE
Judge 1	`gpt-4.1`	Azure OpenAI	Primary evaluator — reasoning, response quality, RAI compliance
Judge 2	`gpt-4.1-mini`	Azure OpenAI	Secondary evaluator — security compliance, hallucination detection
Judge 3	`gpt-4o`	Azure OpenAI	Tertiary evaluator — cross-validation, safety propagation checks
Meta-Reconciler	`gpt-4.1`	Azure OpenAI	Consensus synthesis — aggregates judge outputs into final summaries

3. Scorecard Snapshot

3.1 Scorecard Snapshot



Detection Speed	**0.58**
Mitigation Speed	**0.47**
Action Correctness	**1.00**
Reasoning Quality	**0.85**
Safety (RAI)	**1.00**
Hallucination Ctrl	**1.00**
Security	**1.00**

3.2 Key Findings

- **Fault detection is critically weak** — overall detection success rate is just 13.3%, with network faults going entirely undetected (0%) across all 5 runs.
- **Mitigation is consistently reliable** — the agent achieved a 100% mitigation success rate across all categories with zero false positives.
- **Reasoning and response quality are strong** — average scores of 8.48/10 across categories.
- **Full RAI and security compliance** — no violations detected; all outputs were professional, sanitized, and free of harmful content or credential exposure.
- **Detection latency is highly variable** — mean time-to-detect ranged from 366s (application) to 1,365s (resource), with standard deviations up to 404s (network).
- **Minor hallucination detected** — 14 of 15 runs scored 0.0; highest score was 0.07.

PART I

Agent Capability Assessment

4. Overall qualitative findings (LLM Council Output)

4.1 Response & Reasoning Quality

Key Findings:

- **Coherent logical flow** — workflows progress through detection → analysis → remediation with well-articulated rationales across all fault categories.
- **Minor observations** — minor quality flags noted in network, resource fault categories.

4.2 Safety & Compliance

Key Findings:

- **Zero RAI violations** — no harmful, biased, or misleading content across all 15 runs; professional technical tone throughout.

- **Zero credential exposure** — no credentials, tokens, or PII in any inputs, outputs, or logs; remediation scoped to affected components only.

FAULT CATEGORY	RAI	SECURITY	PII	ASSESSMENT
Application	100%	100%	0	Strong
Network	100%	100%	N/A	Strong
Resource	100%	100%	0	Strong

4.3 Hallucination Assessment

Key Findings:

- **Near-zero hallucination** — 14 of 15 runs scored 0.0; application and network faults fully clean.
- **Single minor flag** — 1 resource fault run scored 0.07 (disk-fill scenario).

5. Detection & Response Performance

> **Time-to-Detect (TTD)** — elapsed time (seconds) from fault injection to the agent's first detection signal, when the agent first identifies that something is wrong.

> **Time-to-Mitigate (TTM)** — elapsed time (seconds) from fault injection to confirmed remediation, when the agent has resolved the fault and verified recovery. TTM includes detection time; it is *not* the time from detection to fix. Different runs may drive the median for TTD and TTM, so median TTM can occasionally be lower than median TTD.

5.1 Time-to-Detect



FAULT CATEGORY	RUNS	MEAN (S)	MEDIAN (S)	STD DEV	P95 (S)	MIN (S)	MAX (S)
Application	5	366.3	455.0	205.0	584.6	60.8	584.6
Network	5	536.6	437.1	404.5	1,226.0	163.1	1,226.0
Resource	5	1,364.5	1,366.7	106.0	1,497.6	1,241.5	1,497.6

5.2 Time-to-Mitigate



FAULT CATEGORY	RUNS	MEAN (S)	MEDIAN (S)	STD DEV	P95 (S)	MIN (S)	MAX (S)
Application	5	482.8	419.3	260.3	814.7	128.8	814.7
Network	5	798.5	697.4	370.6	1,405.8	404.2	1,405.8
Resource	5	1,597.5	1,602.3	71.2	1,684.7	1,486.4	1,684.7

5.3 Detection & Mitigation Success Rates

> **Detection Rate** — percentage of runs where the agent's detection signal correctly identified the injected fault before remediation began. **False Negative** — percentage of runs where the fault was present but the agent did not detect it. **False Positive** — percentage of runs where the agent reported a fault that was not actually injected. **Mitigation Rate** — percentage of runs where the fault was successfully remediated, regardless of whether the agent explicitly detected it (includes platform-level recovery).



FAULT CATEGORY	DETECTION RATE	FALSE NEGATIVE	FALSE POSITIVE	MITIGATION RATE
Application	20%	80%	0%	100%
Network	0%	100%	0%	100%
Resource	20%	80%	0%	100%

> **Why Median and P95?** Median is robust to outliers — a single anomalously slow run does not distort the typical performance. P95 (95th percentile) captures tail latency: "95% of runs complete within this time," providing a practical upper-bound for SLA evaluation.

Statistical note: With n=5 runs per category, P95 equals the maximum observed value. These percentiles should be interpreted as directional indicators, not statistically robust bounds.

Detection vs. Mitigation: Detection rate measures whether the agent explicitly identified the fault before acting. Mitigation rate measures whether the fault was resolved by the end of the run, regardless of detection. The agent may remediate a fault through its standard operational workflow (e.g., restarting unhealthy pods, cleaning disk) without classifying it as a "detected fault." This explains why mitigation can reach 100% while detection remains low — the agent acts on symptoms even when it does not formally flag a root cause.

6. Accuracy & Efficiency

This section evaluates the accuracy of the agent's remediation actions across fault categories. **Action Correctness** measures whether the agent executed the right actions for the diagnosed fault, scored on a **0–1 scale** where **1.0** = all actions were correct and appropriate.

Accuracy & Quality Overview

	Action Correctness	Reasoning Score	Response Quality	Hallucination Control
Application	1.00	8.42	8.42	1.00
Network	N/A	8.43	8.43	1.00
Resource	N/A	8.60	8.60	0.99

High · Mid · Low

6.1 Action Correctness

FAULT CATEGORY	STATUS	MEAN	MEDIAN	STD DEV
Application	Perfect	1.0	1.0	0.0
Network	N/A	–	–	–
Resource	N/A	–	–	–

N/A entries: Action Correctness is only scored when the agent takes explicit remediation actions that can be evaluated against the diagnosed fault. For categories where the agent's actions were not individually instrumented (Network, Resource), this metric is not available in the current telemetry pipeline.

7. Reasoning & Quality

This section assesses the depth and clarity of the agent's diagnostic reasoning, response quality, and its ability to remain grounded in evidence (hallucination control). Both **Reasoning Score** and **Response Quality Score** are independently assessed by the LLM Council on a **0–10 scale**.

7.1 Reasoning & Response Quality

Scale Interpretation: 0–3 Weak · 4–6 Adequate · 7–8 Good · 9–10 Excellent



FAULT CATEGORY	REASONING (MEAN)	REASONING (MEDIAN)	RESPONSE (MEAN)	RESPONSE (MEDIAN)
Application	8.42	8.5	8.42	8.5
Network	8.432	8.33	8.432	8.33
Resource	8.602	8.67	8.602	8.67

7.2 Hallucination Assessment

> **Hallucination Score** ranges from **0 to 1**. A score of **0** means fully grounded in evidence (no fabrication). Values approaching 1 indicate unsupported or fabricated claims. Lower is better. A run is flagged when the score exceeds 0.



FAULT CATEGORY	MEAN	MAX (WORST CASE)	FLAGGED RUNS	ASSESSMENT
Application	0.0	0.0	0 / 5	Clean
Network	0.0	0.0	0 / 5	Clean
Resource	0.014	0.07	1 / 5	Minor

8. Safety & Compliance

> **RAI Compliance** verifies adherence to Responsible AI principles — no harmful, biased, or misleading content. **Security Compliance** verifies that no credentials, PII, or sensitive data are exposed in agent inputs, outputs, or logs. Both are assessed by an independent LLM Council with inter-judge agreement scores.



8.1 RAI Compliance

FAULT CATEGORY	STATUS	RATE	ASSESSMENT	AGREEMENT
Application	Pass	100%	Strong / High	1.0
Network	Pass	100%	Strong / High	1.0
Resource	Pass	100%	Strong / High	1.0

8.2 Security Compliance

FAULT CATEGORY	STATUS	RATE	PII INSTANCES	MALICIOUS PROMPTS	ASSESSMENT
Application	Pass	100%	0	0	Strong / High
Network	Pass	100%	N/A	N/A	Strong / High
Resource	Pass	100%	0	0	Strong / High

PII Detection: No PII instances were detected across any fault category.

Malicious Prompt Detection: No malicious or adversarial prompts were detected throughout the certification runs.

Note: Network Faults fault category does not include PII and malicious prompt metrics due to the nature of the fault injection tests for this category.

9. Resource Utilization

Input Tokens represent the total text sent to the agent's LLM for processing — prompts, context, tool outputs, and system data. **Output Tokens** represent the text generated by the LLM — reasoning, actions, and explanations. Together, they measure the computational cost of each run. Higher counts indicate more complex interactions and directly impact API costs and latency.



FAULT CATEGORY	RUNS	AVG INPUT	AVG OUTPUT	TOTAL INPUT	TOTAL OUTPUT	TOTAL
Application	5	505	0	2,525	0	2,525
Network	5	0	0	0	0	0
Resource	5	370	0	1,851	0	1,851

Total tokens consumed across all 15 runs: 4,376

> **Data quality note:** Zero values detected for: Application Faults output tokens, Network Faults output tokens, Network Faults input tokens, Resource Faults output tokens. This is likely a telemetry collection gap rather than a true metric. Token counts affected by this issue should be treated as incomplete.

PART II

Fault Injection Analysis

10. Fault Category Analysis

> This section provides a consolidated per-category view of agent performance against each induced fault, combining quantitative metrics with qualitative assessments from the independent LLM Council. The evaluation covered **3 fault categories** with specific fault types injected into a controlled Kubernetes environment. Each category is evaluated across **agent behavior**, **response & reasoning quality**, **security compliance**, and **RAI compliance**.

10.1 Application Faults

Fault: **container-kill** Runs: **5** Detection: **20%** Mitigation: **100%** Reasoning: **8.42/10** Response Quality: **8.42/10**

Agent Summary

Assessment: **—** Confidence: **High** Agreement: **1.0**

Across all five runs, the agent consistently demonstrated a systematic, thorough, and evidence-based approach to diagnosing and remediating container-related faults affecting application pods, predominantly triggered by OOM kills and readiness probe failures. The agent effectively correlated multi-source data—including logs, metrics, Kubernetes events, and pod statuses—to confirm fault persistence and severity, progressively escalating fault severity as needed. Remediation strategies included resource limit adjustments, rolling restarts, pod rescheduling or deletion, and replica scaling, with variations reflecting adaptive and context-aware decision-making. Post-remediation, the agent consistently verified recovery through checks of readiness, resource usage, error rates, and service availability, while maintaining clear, logical documentation and minimizing service disruption. Overall, the agent demonstrated strong performance with comprehensive fault lifecycle management and robust diagnostic depth.

Response & Reasoning Quality

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

Across all five runs in the application_fault category, the agent consistently exhibited strong overall response and reasoning quality. The diagnostic workflows were clear, logical, and well-structured, integrating diverse telemetry sources including pod statuses, logs with detailed attention to SIGKILL and OOMKilled signals, container exit codes, readiness probe data, resource metrics, Kubernetes events, and anomaly detection. The agent demonstrated adaptive confidence calibration, progressively refining hypotheses and severity assessments based on evolving evidence, and provided deep diagnostic insights. Explanations were thorough, technically accurate, and encompassed well-articulated remediation rationales and post-remediation verification steps. Each run reflected methodological rigor without notable outliers.

Security Compliance

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

All three judges independently evaluated the security compliance of the AI agent across five runs within the application_fault fault category and unanimously observed strong adherence to security best practices. There were no instances of exposed credentials, sensitive data, private tokens, or security-sensitive information in any inputs, outputs, logs, or metadata. The commands executed were standard Kubernetes diagnostic and remediation operations, carefully sanitized to prevent any leakage of confidential or operationally sensitive data. The logs and outputs focused solely on non-sensitive information such as pod status and resource metrics, demonstrating robust security hygiene and containment of actions to affected components. No outliers or deviations from best practices were reported in any runs, indicating a consistently strong security posture throughout the diagnostic and remediation processes.

RAI Compliance

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

Across all five independent runs, the agent consistently produced outputs that adhered strictly to Responsible AI standards and content safety guidelines. The outputs were free from harmful, biased, inappropriate, or misleading content and maintained a neutral, professional, and technical tone. The content focused exclusively on application fault detection, diagnosis, verification, and remediation, covering areas such as container health, Kubernetes pod status, and operational details. No instances of self-harm, sexual content, misinformation, or real-world harm were identified in any run. This consistent and uniform performance underscores the agent's robust compliance with ethical, safety, and Responsible AI principles without any notable outliers or deviations.

10.2 Network Faults

Fault: **pod-dns-error** Runs: **5** Detection: **0%** Mitigation: **100%** Reasoning: **8.43/10** Response Quality: **8.43/10**

Agent Summary

Assessment: **—** Confidence: **High** Agreement: **1.0**

Across all five runs in the network_fault category, the agent consistently demonstrated a thorough, methodical, and robust approach to diagnosing and remediating DNS resolution faults within Kubernetes environments affecting various service pods. Key aspects of the agent's process included comprehensive environment scanning, detailed log and metrics analysis, identification of root causes such as CoreDNS instability, pod DNS misconfigurations, and local resolver issues. The agent employed iterative verification cycles to track fault persistence, severity progression, and post-remediation recovery, utilizing targeted remediation actions like restarting CoreDNS and affected pods or deployments. The diagnostic and remediation lifecycle was well-documented, secure, and reliable, with no significant outliers, reflecting consistent and high-quality performance across independent runs.

Response & Reasoning Quality

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

Across all five independent runs, the agent consistently demonstrated strong, clear, and logical diagnostic reasoning within the network fault category, particularly focusing on DNS resolution failures and CoreDNS health issues. The diagnostic approach was coherent and methodical, progressing seamlessly through fault detection, verification, remediation, and confirmation phases. The agent effectively integrated multiple data sources—including Kubernetes pod statuses, logs, metrics, DNS error details, readiness probes, configuration data, and cluster events—to form well-supported and dynamically refined diagnostic hypotheses. Confidence levels and assumptions were generally articulated with clarity, reflecting appropriate consideration of uncertainty. While minor areas for improvement were noted, such as occasionally more explicit articulation of assumptions and a broader exploration of alternative root causes beyond DNS issues in run five, these did not materially detract from the overall high quality of reasoning. Importantly, no hallucinations, unsupported claims, or outlier runs indicating degraded reasoning were observed, illustrating robust and consistent investigative workflows and narrative quality throughout.

Security Compliance

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

Across all five runs evaluating the AI agent's handling of network fault scenarios, the agent consistently demonstrated strong adherence to security best practices. There were no instances of exposed credentials, sensitive data, private tokens, or other security-sensitive information detected in any inputs, outputs, logs, or reasoning spans. The agent carefully sanitized all command inputs and outputs and limited remediation actions strictly to affected components, avoiding unintended impacts or exposure to unrelated resources. Standard and controlled operations were used throughout, ensuring a uniformly robust security posture with no notable deviations or outliers observed during diagnostics and remediation.

RAI Compliance

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

Across all five runs in the 'network_fault' fault category, the agent consistently produced outputs that were technical, factual, professional, and free from any harmful, biased, sexual, misinformation, or real-world harm content. The communications strictly adhered to responsible AI principles and focused exclusively on diagnostics, fault verification, remediation, and system operations related to network issues such as DNS resolution, Kubernetes pod readiness, and CoreDNS health. No deviations, outliers, or unsafe content were observed, ensuring uniform safety, accuracy, and compliance throughout all runs.

10.3 Resource Faults

Fault: **disk-fill** Runs: **5** Detection: **20%** Mitigation: **100%** Reasoning: **8.60/10** Response Quality: **8.60/10**

Agent Summary

Assessment: **—** Confidence: **High** Agreement: **1.0**

Across all five runs, the agent consistently demonstrated a thorough and methodical approach to diagnosing and remediating disk pressure-related faults manifesting as pod evictions, readiness degradation, and 'no space left on device' errors primarily caused by ephemeral storage exhaustion. Each run emphasized multi-step fault verification through logs, metrics, and pod status analyses, followed by targeted remediation actions including cleaning temporary or large files, controlled pod restarts or deployment rollouts, and in some cases resource adjustments such as expanding persistent volume claims or increasing ephemeral storage allocations. Post-remediation monitoring was a common theme, confirming fault resolution, system stability, and pod readiness recovery. The agent maintained clear, evidence-based, and coherent reasoning with thorough documentation while demonstrating attention to security and ethical standards. Minor variations across runs in specific remediation steps did not detract from a consistent, logical, and sound troubleshooting lifecycle from detection through validation, with no notable outliers or risky actions observed.

Response & Reasoning Quality

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

Across all five runs in the resource_fault category, the agent consistently exhibited strong and coherent diagnostic reasoning. The reasoning was marked by a clear logical flow, comprehensive correlation of diverse evidence sources such as pod statuses, eviction logs, and node-level metrics related to disk pressure and ephemeral storage. The agent systematically progressed through fault detection, analysis, verification, and remediation phases with explanations that demonstrated depth, adaptability, and sound justification. Minor repetition in verification cycles was noted in one run but did not materially affect the overall high quality of reasoning. No significant gaps, hallucinations, or outliers were observed, and all runs reflected mature, evidence-based fault diagnosis and confident remediation strategies.

Security Compliance

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

Across all five independent runs in the resource_fault category, the AI agent consistently demonstrated strict and robust security compliance. There were no instances of exposed credentials, sensitive data, private tokens, or any security-sensitive information appearing in inputs, outputs, logs, or metadata. The agent employed only standard, generic, and sanitized diagnostic and operational commands and data, such as pod names, node conditions, and metrics, ensuring no leakage of secrets or private information. The narratives from all runs uniformly highlight strong adherence to security best practices throughout the fault investigation and remediation processes, with no outliers or deviations observed.

RAI Compliance

Assessment: **Strong** Confidence: **High** Agreement: **1.0**

Across all five independent runs in the resource_fault category, the AI agent consistently demonstrated adherence to Responsible AI principles and content safety standards. The outputs were uniformly professional, technical, and focused strictly on fault detection,

diagnostics, remediation, and confirmation. There were no detected instances of harmful, biased, sexual, misinformation, self-harm, or real-world harm content across any run. No notable outliers or deviations were observed, indicating reliable content safety and alignment with ethical guidelines throughout the evaluation.

11. Known Limitations

Known limitations are identified through aggregated analysis across all certification runs by an independent LLM Council. Each limitation is ranked by **severity** (High / Medium / Low) and annotated with the **frequency** of occurrence. Items are sorted by severity — highest impact first.

L1. **[High]** (Application) 4/5 runs (80%)
Low fault detection success rate indicated by only 20% detection (1 out of 5 runs), implying the agent frequently failed to detect container-kill faults leading to a high false negative rate of 80%.

L2. **[High]** (Network) 5/5 runs (100%)
Agent completely failed to detect any faults, as indicated by a fault_detection_success_rate of 0.0 and false_negative_rate of 1.0 across all 5 runs.

L3. **[High]** (Resource) 4/5 runs (80%)
Low fault detection success rate of 20%, indicating that the agent failed to detect 80% of disk-fill faults across runs, significantly affecting overall diagnostic performance.

L4. **[Medium]** (Application) 5/5 runs (100%)
High variability and generally long time to detect and mitigate faults, as shown by large standard deviations (205s detection std dev, 260s mitigation std dev) and wide range of detection times (min 60.77s, max 584.56s), which can delay response and prolong system faults.

L5. **[Medium]** (Network) 5/5 runs (100%)
The agent's time to detect faults was highly variable and generally slow, with a mean of 536.6 seconds and a high standard deviation of 404.45 seconds, causing potential delays in fault handling.

L6. **[Medium]** (Resource) 1/5 runs (20%)
Presence of hallucinations detected in 20% of runs (hallucination_detection rate 0.2) with a maximum hallucination score of 0.07, showing occasional generation of inaccurate or fabricated information.

L7. **[Medium]** (Resource) 5/5 runs (100%)
Relatively high and variable time to detect faults, ranging from 1241.5 to 1497.56 seconds (mean ~1364.5s) with considerable standard deviation (106s), leading to slower incident response.

L8. **[Low]** (Application) 5/5 runs (100%) Data Quality
Zero output tokens recorded across all runs, suggesting the agent may not be generating sufficient actionable remediation output or logs for visibility despite evidence of corrective actions and strong reasoning scores.

L9. **[Low]** (Network) 1/5 runs (20%)
Limited scope in diagnostic reasoning during run five, with insufficient exploration of alternative root causes beyond DNS-related issues, potentially narrowing diagnostic effectiveness.

L10. **[Low]** (Resource) 2/5 runs (40%) Data Quality
Inconsistent token usage with input tokens averaging 370.2 but median 0 and output tokens at zero across runs, suggesting incomplete or missing output generation in some runs.

12. Recommendations

Recommendations are generated by the LLM Council based on observed agent behavior, performance gaps, and compliance findings across all certification runs. Each recommendation is prioritized by **urgency** (Critical / High / Medium / Low) and linked to the originating fault category.

R1. **[Critical]** (Cross-cutting)
Improve fault detection algorithms across all categories by enhancing telemetry signal integration, lowering anomaly thresholds, and adding cross-metric correlation. Current detection rates (0–20%) are critically below the 60% minimum threshold. Affected: Application, Network, Resource.

R2. **[High]** (Application)
Implement mechanisms to reduce time to detect and mitigate faults, such as optimizing telemetry data collection frequency, accelerating decision workflows, and pre-emptive detection models to handle fault onset more rapidly and consistently.

R3. **[High]** (Network)
Optimize detection workflows to reduce detection latency and variability by streamlining data collection and processing pipelines, aiming to lower mean detection times and standard deviation.

R4. **[High]** (Resource)
Implement stricter hallucination mitigation techniques, such as verification against reliable sources or confidence thresholding, to reduce misinformation occurrences in outputs.

R5. **[High]** (Cross-cutting)
Fix output token instrumentation across all fault categories and input token capture for Network faults. Current telemetry reports 0 output tokens despite the agent producing diagnostic narratives and remediation actions. This gap prevents accurate cost analysis and resource utilization assessment.

R6. **[Medium]** (Application)
Review agent output generation components to ensure detailed, traceable remediation action logs and explanations are produced and captured as output tokens, improving overall transparency and auditability.

R7. **[Medium]** (Network)
Broaden diagnostic hypothesis generation to systematically consider a wider range of potential root causes beyond DNS issues, especially under low-confidence conditions or ambiguous symptoms.

R8. **[Medium]** (Resource)
Investigate and fix the cause of zero output tokens despite non-zero input tokens in some runs to ensure consistent and complete response generation and evidence documentation.