SCALE 35 MESSES: SENIOR NON-COMMISSIONED OFFICERS' - SINGLE SLEEPING QUARTERS

- 1 This scale is to be read in conjunction with Scale 1.
- 2 SNCOs' single quarters will normally be built as part of the main mess building and sited away from the public rooms wherever possible to ensure maximum privacy and quietness for the occupants. Where it is not possible for these quarters to form part of the main building, they should be sited near to, and easily accessible from, it, to reduce the necessity for covered ways, which will be provided only where economically possible.
- 3 Curtain rods or runners with valance rails or pelmet boards are to be provided in rooms where curtains are authorised. In addition fittings for privacy net curtains are to be provided in bedrooms on ground floors and those that are easily overlooked.
- 4 Provision will not in all cases be for 100% of the establishment and requirements are to be justified at project brief stage. Units of a size comparable to an Infantry battalion, or larger, will be entitled to an additional quarter for use by the Orderly Sergeant.

SUB-TROPICAL AND TROPICAL INCREMENTS

5 In areas of high humidity provision may be made for a low wattage heater, with guard, to be fitted in wardrobes.

LOCKS AND KEYS

6 Locks will be provided for all bedroom doors. Keys will be provided as required to the scale of one key for each room occupant, with two spare, which will be held by the unit/station.

TV/FM/SATELLITE AERIALS AND SOCKETS

7 Refer to Scale 1, Serials 88-89. The scale of provision of socket outlets is:
Bed-sitting rooms - one per room

WHITE GOODS

8a A commercial model washing machine and tumble dryer, together with their necessary plumbing and extracts, are to be provided on a scale of one of each machine for every 6 persons. This will usually be in the utility room, but exceptionally may be provided as a central laundrette as described in Scale 56.

8b The utility room will also be equipped with a commercial grade microwave oven (designed for heavy duty use) and a refrigerator on a scale of one for every 6 persons

UTILITY FACILITIES

- 9 Where the Mess is occupied by Royal Marine Commandos, Army Training Units, units of the RAF Regiment, and other units undergoing intensive field training, the scaled drying area is to be supplemented by a further 0.3m² per person for heavy clothing and equipment. Consideration may be given to the provision of an externally accessed washdown to enable the heaviest soiling to be removed before personnel enter the accommodation.
- 10 Wiring and ducting should be provided to enable the installation of private internet broadband capable telephone connections to each bedsitting room.

11 Heating is to be in accordance with CSBE recommendations.

STORAGE

12 The storage allowance of 2m² per person is intended primarily for bulky items such as polystyrene packaging, suitcases etc

CEREMONIAL UNITS

- 13 A special case is to be made for additional bedroom furniture for ceremonial units and others having specialist uniform storage requirements.
- 14 20 Spare

Accommodation	Area	M & E Services	Planning Notes, Special Fittings, etc.
(a)	(b)	(c)	(d)
21 Entrances, Corridors and Staircases	To be provided out of area addition	Illumination - 175 lux for entrances, 100 lux for corridors, 50 lux for dustbin area. External light over entrances where street lighting insufficient. Supplementary lighting over mirrors and notice board. Electric Power - One 13A double socket outlet to every 37.0m² of floor space, or to every 12.0m run of corridor.	To suit planning requirement. External doors to be self closing. Draught proof lobby. One mirror, 1360 x 460mm at each entrance. Notice board. A separate entrance hall may only be authorised for the main entrance to sleeping accommodation that is sited separately from the public rooms. If so authorised, an enclosed ventilated space for dustbins with access from the entrance hall is to be provided.

SCALE 35 3 Edition 3/July 1999

(a)	(b)	(c)	(d)
22a Bed-Sitting Room	19.0m ²	Illumination - 125 lux Electric power - Five 13A double socket outlets. Telephone - Jack point.	Design to allow for built-in furniture and fittings as detailed in Annex A and at least 4ft bed. For TV/FM sockets see Serial 7.
b Toilet Area	3.75m ² Shower, WC and Vanity unit en-suite per bed-sitting room	Illumination - 125 lux Supplementary lighting over mirror with shaver socket. Electric Power - Supply to heated towel rail. Water Supply - Hot and cold.	One fixed seat, two clothes hooks, soap holder, shelf and heated towel rail. Soiled linen container. Toilet roll holder Provision of sanitary disposal facilities to be determined at project brief stage. Baths - see Serial 23.
c Baggage Store	2.0m ²	Illumination – 100 lux	See Serial 12. Shelving as required.
23 Bathrooms	To be provided out of area addition One bath per floor or per 10 bed-sitting rooms	Illumination - 125 lux Electric Power - Supply to heated towel rail. Water Supply - Hot and cold.	One fixed seat, two clothes hooks, soap holder, shelf and heated towel rail to each bath.

(a)	(b)	(c)	(d)
24 Utility Area	1.4m ² per person	Illumination - 225 lux Electric Power Four 13A double socket outlets per 6 persons. Power supply as necessary for washing machine, tumble dryer, refrigerator and microwave. Ventilation - Where adequate natural ventilation is not available, mechanical extraction is to be provided. Ventilation for drying area - circulation, and extract fans all as required. Extractor to be positioned over snack preparation area Water Supply - Hot and cold. Service connections for washing and drying machines.	To be sited to serve the various groups of quarters. One washing sink with draining board to a scale of one to six persons. One washing machine and tumble dryer for every six persons. Cupboards, worktop. Ceiling clothes dryer. Plastic covered hanging rails at 0.6m run per person. Drainage channels in floor under drip-dry rails. Shoe rails at 0.3m run per person; slat shelving, plastic covered hanging rail. Airing space off ironing area. Extract fan linked to timer. Work top, 1800mm run with small sink unit and two (250mm) hob heaters inset. Storage cupboards over worktop to provide option of individually lockable space of 0.06m³ per person. One drinking water tap. Refrigerator and microwave.

SCALE 35 5 Edition 3/July 1999 Amendment No 18/September 2007

(a)	(b)	(c)	(d)
25 Laundry Receipt and Dispatch Room	7.0m ²	Illumination - 175 lux Supplementary lighting over counter.	On ground floor, one per block, with access from road to permit access of laundry (bed linen) trolley. Slat shelves 0.8m deep. Stable type door to corridor with folding shelf to lower half as issue counter.
26 Cleaners Room			Refer to Scale 1 Annex B.
27 Calorifier Room (if required)			Refer to Scale 1 Annex B.

SCHEDULE OF FITTED FURNITURE

ANNEX A

Serial	Item and Size	Details
1	Double Wardrobe 1000 x 600 x 1800mm	doors fitted with 270° heavy duty semi-concealed hinges & wooden
		inset handles, full width hanging rail, fitted with internal four drawer
		unit 560x480x565mm, includes for tie rail
2	Double Top Box (2 no) 1000 x 600 x 500mm	doors fitted with 270° heavy duty semi-concealed hinges & wooden
		inset handles for fitting over Serials 1 and 3
3	Double Wardrobe 1000 x 600 x 1800mm	doors fitted with 270° heavy duty semi-concealed hinges & wooden
		inset handles, full width hanging rail, fitted with internal four drawer
		unit 560x480x565mm, includes for robe door mirror,1050mm x 250mm
		x 4mm
4*	Deep Wide Drawer Chest 1000 x 600 x 730mm	four drawers fitted with wooden inset handles
5	Wall Bookshelf 1000 x 230 x 9 00mm	with three shelves
6*	<u>Cupboard</u> 500 x 600 x 730mm	single door fitted with270° heavy duty semi-concealed hinges &
		wooden inset handles
7*	Narrow Drawer Chest with No Top 500 x 600 x	four drawers fitted with wooden inset handles, top drawer fitted with
	700mm	cylinder lock.
8	Curved Desk Top 2100 x 600 x 1200 x 500 x	,
	30mm	supported by slab end panel with bearers to back & side to fit over
		Serial 7
9*	Wide Deep Double Cupboard 1000 x 600 x	, ,
	730mm	inset handles, includes for fixed shelf.
10*	Bedside Unit 450 x 450 x 565mm	open shelf with cupboard below, door fitted with 270° heavy duty semi-
		concealed hinges & wooden inset handle.
12	Sundeala Pinboard 1200 x 800mm	Hessian Covered, If required
13	Infill panel pieces	As required

Carcases, drawers and doors to be 18mm thickness
All dimensions are in millimetres, and should be the manufacturer's closest standard product
* May be free standing

8