Selection for language-model context, read from the data

Using entroptics to decide how many retrieved items to keep, which to keep, and where foreign material sits

Ikailo John Sessford
Ikailo Inc.
john@ikailo.com

Version 0.3.0. November 2026.

Abstract

A language model's context is assembled from several sources at once: a retrieval-augmented prompt, an agent scratchpad, a long conversation. The decisions made about it — how many retrieved items to keep, which of them to trust, whether an answer stayed on its evidence — are conventionally made with one number per item against one summary of the whole: a cosine, a centroid, a fixed top-k.

This work reads the context as the sources it spans, each one the directions it resolves above its own noise floor, using the `entroptics` instrument, and makes each of those decisions from those spans. The number of sources and the directions of each are counted from the data, so nothing is trained, no threshold is set, and no constant is fitted per corpus.

Where relevance spreads across several facets, the derived cut holds F_1 at 1.000 through four facets and at 0.915 and 0.711 at five and six, where a cosine cut falls to 0.000. On locating a real prompt injection planted in real documents, it leads both a centroid and a k-nearest-neighbour detector at every source count measured, by a margin over k-NN that grows from +0.005 at one source to +0.024 at five, and at five sources it names the attack as the first item to inspect almost six times as often as a centroid does. On deciding whether a continuation belongs to its context, it leads a centroid by a margin that grows from +0.056 at two sources to +0.172 at five, ties k-NN from two sources up, and trails it by 0.007 at one.

One statement covers all of it. **These reads beat a single summary statistic when the deciding distribution is multi-modal, and over the source counts measured the margin grows with how multi-modal it is.** Where the deciding distribution has one mode they reduce to the statistic they are measured against and tie; on four BEIR corpora and an end-to-end HotpotQA run they tie with cosine.

1. The claim

> **A read taken over the sources a context resolves decides better than one taken against a single summary of it when the deciding distribution is multi-modal, and over the source counts measured the advantage grows with how multi-modal it is.**

Three measurements carry it, on three different axes of modality: facets of a query's relevance (§4), sources in a context (§5), and topics spanned by a conversation (§6). On two real-corpus measurements the reads tie with cosine (§7).

2. A span in place of a point

Take a context $C = \{x_1, \dots, x_n\}$ of direction-normalized embeddings drawn from M distinct sources. The centroid

$$\bar{x} = \frac{1}{n}\sum_i x_i \Big/ \Big\|\frac{1}{n}\sum_i x_i\Big\|$$

is a single point on the sphere, and ranking by cosine to it is identical to ranking by average similarity to the rest of the set — the standard summary an item is usually scored against. Where the sources occupy M well-separated directions, $\bar{x}$ is their weighted mean and for $M > 1$ it points into the gap between them. The cosine of a legitimate item from source m then falls roughly as $\cos\theta$, with θ that item's angle from the consensus direction — a quantity set by **how spread the context is**, carrying no information about the item.

A subspace read puts a span where that point was. Let $X \in \mathbb{R}^{n\times d}$ stack the context, let $X = U\Sigma V^\top$, and take

$$V_K = [v_1, \dots, v_K], \qquad K = \#\{\,\sigma_j : \sigma_j \text{ resolves above the noise floor}\,\}.$$

Score an item by the energy it retains under projection:

$$\phi_{\text{in}}(y) = \frac{\|V_K^\top y\|^2}{\|y\|^2} \in [0,1].$$

Each resolved source direction lies in $\text{span}(V_K)$, so a legitimate item from *any* source scores high: its own direction is represented whether or not the others are.

One span over every source still asks a looser question than the one posed. It scores an item by how much of it lies in the span of all the sources together, so an off-topic item that falls between them reads as partly inside. A nearest-neighbour read asks the local question, whether the item is close to some part of the context, and on the drift task of §6 it is ahead of the single span from two sources up. The read therefore keeps one span per source.

The K dimensions of V_K seed the split. With $U \in \mathbb{R}^{n\times K}$ the items' orthonormal coordinates in $\mathrm{span}(V_K)$, column-pivoted QR on $U^\top$ picks K representative items, the polar factor of their rows rotates U onto them, and each item joins its largest rotated coordinate [6]. Nothing is set: the pivots are the items left most independent of those already chosen. Each group s then gets its own span $V^{(s)}$, built the same way from the group alone, and

$$\phi_{\text{in}}(y) = \max_s \frac{\|V^{(s)\top} y\|^2}{\|y\|^2}.$$

An item is in the context when it lies in one of its sources. The margin over a single-point summary widens as the sources multiply, because the point moves further from all of them while each source keeps its own span.

3. Choosing K without choosing anything

K is the one quantity that could be tuned, and it is read rather than set. It comes from the singular spectrum via the `entroptics` instrument [1], which counts the modes standing above the noise floor derived from the block's own shape. For an $n \times d$ block of pure noise the singular values follow a Marchenko-Pastur law with a Tracy-Widom edge; modes above that edge are the ones the block resolves. The count is a property of the data and moves with the context: in §5 it reads 6.6 modes at one source and 13.6 at five, without being told how many sources there were.

A constant level is a mode: in the optics in which the library speaks it is the zero-order beam, physically present and passed by the aperture like any other. For a set of embeddings that matters directly, because **the shared mean direction is the topic the set is about**: it is the leading coherent mode, and it carries signal. The count is read on the library's whitened frame, where the noise floor is defined, and the whitening centres each channel on its mean, so it counts the directions about the shared mean. The directions are taken from that same centred set, so the directions and their count come from one frame, and the mean direction the centring removes is added back:

$$V_K = \mathrm{orth}\,[\,\bar{x},\ w_1, \ldots, w_{K-1}\,],$$

with w_j the right singular vectors of the centred set and $K-1$ the engine's count. A set with nothing above the floor about its mean is its mean direction alone, $K = 1$. On the clean topic sets of Appendix A.1, K is 3.0 at three topics and 5.0 at five, and 1.1 at one, where the noise about the mean resolves a direction in some draws.

Absence is handled by masking. A row or column that was never measured is dropped before the decomposition and never reaches the denominator. A channel of measured zeros is an observation of no power and counts as a mode. The two are distinct inputs and give distinct values of K, which is what a caller with sparse features needs to know.

4. How many to keep, when relevance has several facets

The largest margin in this work is on selection. A query whose relevance is spread across R independent facets is the multi-modal case at its cleanest, and R is a controlled variable: the facets are planted, so the axis is exact rather than estimated.

Both sides run the same parameter-free lock over the same head screen; the only difference is whether the screen precedes the lock (`research/benchmarks/bench_facets.py`, 60 items, 12 gold, 16 heads, 40 draws).

Entroptics holds F_1 at 1.000 through four facets and keeps 0.915 and 0.711 at five and six. The cosine cut matches it while the relevance has one to three facets and falls to 0.000 by five, so the edge opens at four facets and is largest at five. The reason is §2's, transposed from a context to a query: one scalar carries one facet's worth of evidence, and each gold item's total weakens toward the distractor level as the facets multiply, where an R-mode subspace holds all of them at once.

The count kept is derived per query throughout. Nothing is swept, and the same lock produces both columns.

5. Which item is foreign, when a context spans several sources

The second axis of modality is the number of sources a context is assembled from. Legitimate content is whole wikitext-103 articles, so each source is a genuine topic; the attacks are the `deepset/prompt-injections` corpus, strings written to attack real systems. One attack is appended to a context built from M sources and the read ranks it. Encoder is `bge-small-en-v1.5`, 200 trials per row, intervals paired per trial (`research/benchmarks/bench_injection.py`).

Two baselines. The **centroid** is the standard single summary of §2. **k-NN** scores an item by its similarity to its five nearest neighbours — a local read, so it carries no penalty for a context that spans topics, and it is the stronger of the two.

Against the standard summary the margin grows from $+0.005$ **to** $+0.223$, as §2 predicts: the centroid falls from 0.983 to 0.718 as the sources multiply while entroptics holds from 0.988 to 0.941. At one source the interval reaches zero.

Against the local detector the margin grows too, from $+0.005$ **to** $+0.024$, every interval excluding zero. k-NN carries no penalty for a context that spans topics, and the per-source read still gains on it as the sources multiply.

The operator's question is which item to open first, and there entroptics has the highest rate at every source count:

facets R	cosine F_1	**entroptics** F_1	edge	95% CI
1	1.000	1.000	+0.000	[+0.000, +0.000]
2	1.000	1.000	+0.000	[+0.000, +0.000]
3	1.000	1.000	+0.000	[+0.000, +0.000]
4	0.806	**1.000**	**+0.194**	[+0.099, +0.301]
5	0.000	**0.915**	**+0.915**	[+0.866, +0.955]
6	0.000	**0.711**	**+0.711**	[+0.624, +0.793]

sources	modes	items	**entroptics**	centroid	k-NN	vs centroid	vs k-NN
1	6.6	39	**0.988**	0.983	0.984	+0.005 [+0.000, +0.010]	**+0.005** [+0.001, +0.008]
2	8.7	77	**0.972**	0.902	0.959	+0.070 [+0.055, +0.087]	**+0.013** [+0.008, +0.019]
3	10.6	116	**0.967**	0.833	0.947	+0.134 [+0.111, +0.157]	**+0.019** [+0.013, +0.026]
5	13.6	191	**0.941**	0.718	0.917	+0.223 [+0.192, +0.254]	**+0.024** [+0.016, +0.032]

sources	**entroptics**	centroid	k-NN
1	**0.785**	0.735	0.720
2	**0.450**	0.250	0.365
3	**0.410**	0.145	0.300
5	**0.175**	0.030	0.120

At five sources it names the attack first almost six times as often as the centroid does, from a pool of 191 items. Each item is scored against every source with itself removed from its own; Appendix A.1 gives the reason.

6. Whether a continuation belongs to its context

The third axis is a conversation's topic spread, and the question is non-adversarial: **is this continuation on-topic?** Held-out sentences from the context's own sources — on-topic, and held out of the context — are scored against sentences from a different article. Same encoder, 200 trials per row, six held-out sentences per source so the target count resolves every effect reported (`research/benchmarks/bench_drift.py`).

The same growth, from an independent task. The edge over the standard summary opens at two sources and grows to +0.172 at five, every interval from two upward excluding zero, with the centroid falling 0.960 → 0.738 while entroptics holds 0.959 → 0.910. §5 appends foreign text and this withholds native text; they are measured separately and agree on how the margin grows with the sources.

Against the local neighbour read it ties from two sources up, every interval containing zero, and trails it at one source by 0.007 [0.003, 0.012]. A single span over every source, the read of §2's first half (`bench_drift.py` reports it), scores 0.964, 0.937, 0.918 and 0.882: it ties k-NN at one source, −0.002 [−0.005, +0.002], and trails it by 0.011 [0.007, 0.015], 0.018 [0.014, 0.023] and 0.027 [0.023, 0.032] at two, three and five. The per-source read closes that gap from two sources up and gives up 0.005 to the single span at one source, where the split finds 3.3 groups in one article on average.

7. Real corpora, where relevance has one mode

The law predicts a tie wherever the deciding distribution has one mode, because the read reduces to the statistic it is measured against. Two real-corpus measurements confirm it.

Four BEIR corpora — nfcorpus, scifact, arguana, fiqa, 2,421 scored queries, encoded with `all-MiniLM-L6-v2` — against the identical `top_break` lock run on plain cosine salience, so the screen is the only difference (`research/benchmarks/bench_beir.py`):

Four ties, every interval containing zero. At the point the cut sees them, 198 of the 2,421 scored queries (8.2%) carry four or more relevant documents in their horizon: 144 of nfcorpus's 260, 4 of scifact's 270, none of arguana's 1,357 and 50 of fiqa's 534. On three of the four corpora the deciding distribution has one mode and §4's condition is absent.

HotpotQA end-to-end, 150 questions, a language model answering from the selected context (`research/benchmarks/bench_hotpot_e2e.py`). The decisive arm is cosine's top-m, where m is the count entroptics derived *for that question*, so the only difference is which items were chosen:

The selection matches cosine's, as the law requires on unimodal relevance.

What the derived count buys where the reads tie is the count itself. The best single constant k over the four corpora, top-1, gives up as much as 0.130 F_1 against a corpus's own best fixed k (nfcorpus, whose best is top-10); reading the count per query gives up at most 0.020. That is the value where there is no sweep to run — a service answering against more than one corpus, or a corpus whose content moves.

Size the budget to the task. On HotpotQA the derived count spends 38% of a fixed top-5's context tokens, 224 against 593, keeping 2.1 paragraphs where a multi-hop answer needs two gold paragraphs. Against that fixed top-5 the difference is −0.058 [−0.123, +0.006], and what there is of it is the count rather than the rank-

sources	modes	context	**entroptics**	centroid	k-NN	vs centroid	vs k-NN
1	3.3	12	0.959	0.960	**0.966**	−0.002 [−0.007, +0.004]	−0.007 [−0.012, −0.003]
2	4.1	24	0.946	0.890	**0.948**	**+0.056** [+0.046, +0.067]	−0.002 [−0.007, +0.003]
3	5.1	36	**0.937**	0.827	0.936	**+0.110** [+0.096, +0.123]	+0.001 [−0.003, +0.004]
5	7.0	60	**0.910**	0.738	0.909	**+0.172** [+0.158, +0.187]	+0.001 [−0.003, +0.005]

dataset	cosine + lock	**entroptics**	edge	95% CI
nfcorpus	0.295	0.291	−0.005	[−0.018, +0.009]
scifact	0.571	0.558	−0.013	[−0.029, +0.002]
arguana	0.257	0.256	−0.001	[−0.007, +0.005]
fiqa	0.344	0.341	−0.003	[−0.012, +0.007]

model	fixed $k = 5$	cosine top-m	**entroptics**	entroptics − top-m
Qwen2.5-1.5B	0.490	0.432	0.432	+0.000 [+0.000, +0.000]

ing: the matched-budget arm above shows the ranking already matches the baseline. Where a task needs several passages, set a floor on the count.

8. What this costs

One thin SVD of the context block, $O(nd \min(n, d))$, on embeddings the pipeline has already computed for retrieval. No additional model call, no second encoder, no index. Scoring an item against the basis is a $d \times K$ matrix-vector product. For the context sizes here — tens to a few hundred items — the read is well under the cost of the retrieval that produced them.

The split adds one $n \times K$ decomposition and a K-step pivoted QR, and each source's span one decomposition of that source's rows. The anomaly read of §5 rebuilds an item's own source without it, so it takes one noise-floor read and one decomposition per item, each on a single source's rows rather than the whole context. Appendix A.1 gives the reason.

9. Scope

Coherence reads topic. An answer that stays on its sources' subject scores high whether or not it is correct: on the 88 HotpotQA questions whose context kept two or more paragraphs, right answers scored 0.432 and wrong ones 0.420, a separation of +0.011 with no interval reported. It is a monitor for off-source and lost-thread behaviour.

Scores and rankings. The reads order items within one context. "Is there an anomaly in this set at all" is a question about a reference distribution, which a caller supplies; `anomaly_z` takes one.

Measured on two encoders. The BEIR table is `all-MiniLM-L6-v2`, every other embedding number is `bge-small-en-v1.5`, and the end-to-end table is Qwen2.5-1.5B. The mechanism in §2 is a statement about direction-normalized embeddings generally; the magnitudes are measured on these models, and K depends on how a model spreads a topic.

10. Reproducing

```
pip install -e ".[bench]"
python -m research.benchmarks.bench_facets       # §4
python -m research.benchmarks.bench_injection    # §5
python -m research.benchmarks.bench_drift        # §6
python -m research.benchmarks.bench_beir --datasets nfcorpus
scifact arguana fiqa   # §7
```

The end-to-end table in §7 needs a language model as well:

```
pip install -e ".[bench,bench-llm]"
python -m research.benchmarks.bench_hotpot_e2e --n 150
```

`bench_facets` runs on CPU in seconds and needs no corpus. The others download their data from Hugging Face. Every number in this paper carries the conditions it was measured under.

Appendix A. Two choices in the API's shape

A.1 — An item is never scored against a mode it supplied. `anomaly` reads each item against every source of the set, with its own source rebuilt without it; the other sources never contained it, and an item that forms a source of its own is read against the others alone. Scoring an item inside a span it helped build loses on §5's benchmark. The same sources with no item removed from its own (`bench_injection.py` reports this arm) score AUROC 0.456, 0.461, 0.452 and 0.587 at one, two, three and five sources, trailing k-NN by 0.528 [0.469, 0.586] at one source and 0.330 [0.277, 0.384] at five.

What the read scores on clean synthetic sets: one injected unit item with amplitude f on a direction no topic uses and $\sqrt{1 - f^2}$ on one topic; eight items per topic, noise norm 0.25, $d = 192$, 15 draws, top-1 localization (`research/benchmarks/bench_leave_one_out.py`):

foreignness f	1 topic	3 topics	5 topics
0.7	1.00	1.00	1.00
0.9	1.00	1.00	1.00
1.0	1.00	1.00	1.00

On the set without the injected item K is 1.1, 3.0 and 5.0 at one, three and five topics, with as many sources. The injected item reads 0.49 to 0.50, 0.81 and 1.00 outside every source at $f = 0.7$, 0.9 and 1.0, and the highest other item reads 0.08 in every cell, so the injected item clears the rest in every draw.

A.2 — A subspace overlap is read against its null. In high dimension two subspaces that are not specifically aligned are near-orthogonal, so a raw `subspace_overlap` reports "most of the structure lies outside" for a random matrix as readily as for a real one, measuring the ambient dimension. The analytic null is k_b/d — a random k_b-dimensional subspace covers that fraction of anything — and `chance_overlap` returns it. Report the ratio of measured overlap to chance.

References

[1] **entroptics** — the spectral instrument. Resolved-mode counting against a Marchenko-Pastur/Tracy-Widom noise floor, and the occupancy read used here to set K. Apache-2.0. https://pypi.org/project/entroptics/

[2] **wikitext-103** — Merity et al., *Pointer Sentinel Mixture Models*, ICLR 2017.

[3] **deepset/prompt-injections** — a corpus of real prompt-injection strings. https://huggingface.co/datasets/deepset/prompt-injections

[4] **BEIR** — Thakur et al., *BEIR: A Heterogenous Benchmark for Zero-shot Evaluation of Information Retrieval Models*, NeurIPS 2021.

[5] **HotpotQA** — Yang et al., *HotpotQA: A Dataset for Diverse, Explainable Multi-hop Question Answering*, EMNLP 2018.

[6] **Pivoted-QR spectral clustering** — Damle, Minden and Ying, *Simple, direct and efficient multi-way spectral clustering*, Information and Inference 8(1), 2019.

Citation

```
@techreport{ikailo2026entropticscontext,
  title  = {Selection for language-model context, read from the
  data},
  author = {{Ikailo Inc.}},
  year   = {2026},
  note   = {https://github.com/Agience/entroptics-context}
}
```