Source / destination / synapse: what the labels mean

II_tib_ant names one type-II afferent neuron, not one globally fixed synapse.

A connection is defined by its source, destination, conductance, reversal, and presynaptic window.

The same afferent can therefore have different parameters at different destinations.

The checked left/right homologues below match; diagram labels omit the side suffix.

Source → destination	g (uS)	Erev (mV)	Io / hi (mV)	L = R
II_tib_ant → RG_F	0.0278947	8.0	0 / 5	yes
II_tib_ant → InF	0.0278947	8.0	0 / 5	yes
II_tib_ant → PF_HIP-F	0.0278947	8.0	0 / 5	yes
II_tib_ant → PF_KNEE-F	0.0278947	8.0	0 / 5	yes
II_tib_ant → IIX_tib_ant	1	8.0	0 / 5	yes
II_tib_ant → IIIN_tib_ant	1	8.0	0 / 5	yes
IIIN_tib_ant → MN_med_gas	0.133333	-5.0	0 / 5	yes
IIIN_tib_ant → MN_lat_gas	0.133333	-5.0	0 / 5	yes
IIIN_tib_ant → MN_soleus	0.133333	-5.0	0 / 5	yes
IIIN_tib_ant → MN_tib_post	0.133333	-5.0	0 / 5	yes
IIIN_tib_ant → MN_flex_dig	0.133333	-5.0	0 / 5	yes
IIIN_tib_ant → MN_flex_hal	0.133333	-5.0	0 / 5	yes
IIX_tib_ant → MN_tib_ant	0.4	8.0	0 / 5	yes
IIIN_tib_ant → MN_per_brev	0.133333	-5.0	0 / 5	yes
IIIN_tib_ant → MN_per_long	0.133333	-5.0	0 / 5	yes
IIIN_tib_ant → MN_per_tert	0.133333	-5.0	0 / 5	yes

A ×N line bundles N separately parameterized connections; it is not a single summed synapse.

Ankle channels are included in the muscle bundles where present. Complete members and edge IDs accompany the drawings.