Table 1: Saved transmission configurations behind Table 4.12 (selected side of each of the 27 actuator sites). Routing is inherited from the masters-era attachment geometry at every site; only transmission configuration and actuator/tendon sizes were re-solved. Resting and tendon lengths are the saved design values in m. Δ columns are selected minus baseline. The eight nominal-40 mm sites (marked †) had a baseline of four parallel 20 mm actuators; the selected side retains the inherited 40 mm specification. G is the tackle line-part count (travel multiplier), not a sheave count.

ID	Site	dia (mm)	N_{BPA}	G	rest (m)	tendon (m)	Δrest (mm)	Δtendon (mm)
1	ercspn_r†	40	1	1	0.5390	0.0500	-144.5	-63.8
2	intobl_r	20	3	2	0.0708	0.0415	-7.8	+17.6
3	extobl_r	20	2	1	0.0926	0.0867	-88.7	+52.3
4	bifemlh_r	20	2	2	0.7628	0.0200	+15.6	+0.0
5	semimem_r†	40	2	2	0.4015	0.0344	-388.2	-16.9
6	sar_r	10	3	1	0.8442	0.0200	-15.6	+0.0
7	tfl_r	10	3	3	0.7524	0.0278	+31.2	+7.8
8	rect_fem_r	20	3	2	0.6733	0.0249	+31.2	-2.9
9	grac_r	10	3	1	0.7682	0.0200	+0.0	+0.0
10	bifemsh_r	20	3	2	0.2871	0.0200	+69.7	-53.4
11	vas_int_r†	40	1	1	0.7943	0.0200	+0.0	+0.0
12	soleus_r†	40	2	1	0.2234	0.0676	+0.0	+9.8
13	med_gas_r†	40	3	1	0.1390	0.0200	-277.9	+0.0
14	lat_gas_r	20	3	1	0.2743	0.0266	-131.3	+6.6
15	tib_post_r†	40	1	1	0.2435	0.1125	+0.0	+31.2
16	tib_ant_r	20	2	1	0.2689	0.0891	+0.0	+17.1
17	per_brev_r	10	3	2	0.3588	0.0200	+31.2	-4.9
18	per_long_r	20	3	1	0.4059	0.0239	+0.0	-11.7
19	per_tert_r	10	3	2	0.3553	0.0200	+31.2	-19.5
20	flex_dig_r	10	3	2	0.4825	0.0200	+10.7	-4.2
21	flex_hal_r	10	2	1	0.5153	0.0200	+23.4	-3.9
22	ext_dig_r	10	3	3	0.4648	0.0239	+31.2	-28.3
23	ext_hal_r	10	3	1	0.4799	0.0200	-23.4	+0.0
24	glut_max_r†	40	3	1	0.1845	0.0200	-184.5	-92.5
25	add_mag_r†	40	3	1	0.1694	0.0200	-169.4	-49.5
26	iliacus_r	20	3	1	0.4331	0.0395	+0.0	+2.0
27	psoas_r	20	3	1	0.3327	0.0969	+0.0	+2.0