Effective synaptic types: full fields (page 1)

Key	Source type name	Gmax (µS)	Erev (mV)	Pre-thr (mV)	Pre-sat (mV)
T01	PF to MN Excite	0.8120247	-10	-60	-50
T02	AnkleZ AEbE-5	0.5	-10	-60	-40
T03	AnkleZ AFbE-6	0.5	-10	-60	-40
T04	MN to RE Excite	0.5	-40	-100	-10
T05	RE to MN Inhibit	0.5	-70	-60	-40
T06	Ia to Ia Inhibit	0.5	-70	-60	-40
T07	Ia to MN Inhibit	2	-100	-60	-40
T08	Hip_Ia_ext_Excite	0.59	-10	-60	-40
T09	RE to Ia Inhibit	0.5	-70	-60	-40
T10	RE Inhibit	0.5	-70	-60	-40
T11	Homonymous Type II excitation, weak	0.005	-10	-60	-40
T12	Knee Ext MN Excite	1.456268	-10	-60	-50
T13	Knee Flx MN Excite	0.4478099	-10	-60	-50
T14	Knee KFbE-6	0.5	-10	-60	-40

Full precision remains in JSON/CSV and editor edge tags. Runtime calibration can create several effective variants of one source-named type.

Effective synaptic types: full fields (page 2)

Key	Source type name	Gmax (µS)	Erev (mV)	Pre-thr (mV)	Pre-sat (mV)
T15	Knee KEbE-5	0.589	-10	-60	-40
T16	PF Inhibit	2.749	-70	-60	-25
T17	PF Excite	2.749	-40	-60	-25
T18	PF to Ia Excite	0.5	-40	-60	-55
T19	Hip_Ib_flx_Excite	1	-10	-60	-40
T20	PF to MN Excite	0.4872148	-10	-60	-50
T21	PF to MN Excite	0.2436074	-10	-60	-50
T22	Ia_HipFlx_to_HipPFflx_Ex te	0.01	-40	-60	-40
T23	Ib_HipExt_to_HipPFext_E te	0.01	-40	-60	-40
T24	II_HipFlx_to_HipPFflx_Exc te	0.01	-40	-60	-40
T25	Hip_Ib_ext_Excite	0.59	-10	-60	-40
T26	Heel_Ipsi_AnkMNext_Exci	0.5	-40	-60	-40
T27	Toe_Ipsi_AnkMNext_Excit	0.03183985	-40	-60	-40
T28	Heel_Ipsi_RGext_Excite	0.01	-40	-60	-40

Full precision remains in JSON/CSV and editor edge tags. Runtime calibration can create several effective variants of one source-named type.

Effective synaptic types: full fields (page 3)

Key	Source type name	Gmax (µS)	Erev (mV)	Pre-thr (mV)	Pre-sat (mV)
T29	Heel_Ipsi_HipPFext_Excit	0.01	-40	-60	-40
T30	Heel_Ipsi_KneePFext_Exc	0.01	-40	-60	-40
T31	Heel_Ipsi_HipMNext_Excit	0.01	-40	-60	-40
T32	Heel_Ipsi_KneeMNext_Ex	0.01	-40	-60	-40
T33	RG Excite	2.749	-40	-60	-25
T34	RG Inhibit	2.749	-70	-60	-25
T35	RG to RG Excite	0.1	-40	-65	-40
T36	RG_HIP_EX	0.176	-40	-60	-40
T37	RG_K&A_EX	0.333	-50	-60	-50
T38	RG to PF Excite	0.1	-40	-60	-40
T39	Ia_HipFlx_to_RGflx_Excite	0.01	-40	-60	-40
T40	Ia_KneeFlx_to_RGflx_Exc	0.01	-40	-60	-40
T41	Ib_HipExt_to_RGext_Excit	0.01	-40	-60	-40
T42	Ib_KneeExt_to_RGext_Ex	0.01	-40	-60	-40

Full precision remains in JSON/CSV and editor edge tags. Runtime calibration can create several effective variants of one source-named type.

Effective synaptic types: full fields (page 4)

Key	Source type name	Gmax (µS)	Erev (mV)	Pre-thr (mV)	Pre-sat (mV)
T43	II_HipFlx_to_RGflx_Excite	0.01	-40	-60	-40
T44	II_KneeFlx_to_RGflx_Exci	0.01	-40	-60	-40
T45	Ia_KneeFlx_to_KneePFflx_ cite	0.01	-40	-60	-40
T46	Ib_KneeExt_to_KneePFex cite	0.01	-40	-60	-40
T47	II_KneeFlx_to_KneePFflx_ cite	0.01	-40	-60	-40
T48	Heel_Contra_RGflx_Excite	0.01	-40	-60	-40
T49	V3 contralateral RG ext IN, weak positive	0.02749	-40	-60	-25

Full precision remains in JSON/CSV and editor edge tags. Runtime calibration can create several effective variants of one source-named type.