

Introduction to Computer Networks

TCP Ack Clocking (§6.5.10)




David Wetherall (djw@uw.edu)

Professor of Computer Science & Engineering

UNIVERSITY *of* WASHINGTON


Topic

- The self-clocking behavior of sliding windows, and how it is used by TCP
 - The “ACK clock”




Sliding Window ACK Clock

- Each in-order ACK advances the sliding window and lets a new segment enter the network
 - ACKs “clock” data segments




Benefit of ACK Clocking

- Consider what happens when sender injects a burst of segments into the network




Benefit of ACK Clocking (2)

- Segments are buffered and spread out on slow link




Benefit of ACK Clocking (3)

- ACKs maintain the spread back to the original sender



Benefit of ACK Clocking (4)

- Sender clocks new segments with the spread
 - Now sending at the bottleneck link without queuing!




Benefit of ACK Clocking (4)

- Helps the network run with low levels of loss and delay!
- The network has smoothed out the burst of data segments
- ACK clock transfers this smooth timing back to the sender
- Subsequent data segments are not sent in bursts so do not queue up in the network

TCP Uses ACK Clocking

- TCP uses a sliding window because of the value of ACK clocking
- Sliding window controls how many segments are inside the network
 - Called the congestion window, or cwnd
 - Rate is roughly cwnd/RTT
- TCP only sends small bursts of segments to let the network keep the traffic smooth

END



© 2013 D. Wetherall

Slide material from: TANENBAUM, ANDREW S.; WETHERALL, DAVID J., COMPUTER NETWORKS, 5th Edition, © 2011.
Electronically reproduced by permission of Pearson Education, Inc., Upper Saddle River, New Jersey