Copyright Notice


These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

Stanford
ONLINE

DeepLearning.AI



Linear Regression with Multiple Variables

Multiple Features

Multiple features (variables)

one feature →

Size in feet^2 (x)	Price ($) in 1000's (y) ←
2104	400
1416	232
1534	315
852	178
…	…

$$f_{w,b}(x) = wx + b$$

Multiple features (variables)

	Size in feet²	Number of bedrooms	Number of floors	Age of home in years	Price ($) in $1000's
	x_1	x_2	x_3	x_4	
	2104	5	1	45	460
$i=2$	1416	3	2	40	232
	1534	3	2	30	315
	852	2	1	36	178
	...	...	...	...	...

$j = 1 \ldots 4$

$n = 4$

x_j = j^{th} feature

n = number of features

$\vec{x}^{(i)}$ = features of ith training example

$x_j^{(i)}$ = value of feature j in i^{th} training example

$\vec{x}^{(2)} = [1416 \quad 3 \quad 2 \quad 40]$

$x_3^{(2)} = 2$

Model:

Previously: $f_{w,b}(x) = wx + b$

$$f_{w,b}(X) = w_1 X_1 + w_2 X_2 + w_3 X_3 + w_4 X_4 + b$$

example

$$f_{w,b}(X) = 0.1 X_1 + 4 X_2 + 10 X_3 + -2 X_4 + 80$$

X_1: size

X_2: #bedrooms

X_3: #floors

X_4: years

80: base price

$$f_{w,b}(x) = w_1 x_1 + w_2 x_2 + \cdots + w_n x_n + b$$

$$f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x_2 + \cdots + w_n x_n + b$$

$\vec{w} = [w_1 \; w_2 \; w_3 \ldots w_n]$ parameters of the model

b is a number

vector $\vec{x} = [x_1 \; x_2 \; x_3 \ldots x_n]$

$$f_{\vec{w},b}(\vec{x}) = \vec{w} \cdot \vec{x} + b = w_1 x_1 + w_2 x_2 + w_3 x_3 + \cdots + w_n x_n + b$$


dot product

multiple linear regression

(not multivariate regression)

Stanford
ONLINE

DeepLearning.AI



Linear Regression with Multiple Variables

Vectorization Part 1

Parameters and features

$\vec{w} = [w_1 \quad w_2 \quad w_3]$ $n=3$

b is a number

$\vec{x} = [x_1 \quad x_2 \quad x_3]$

linear algebra: count from 1

NumPy

w[0] w[1] w[2]

```
w = np.array([1.0,2.5,-3.3])
b = 4
x = np.array([10,20,30])
```

x[0] x[1] x[2]

code: count from 0

Without vectorization

$$f_{\vec{w},b}(\vec{x}) = \left(\sum_{j=1}^{n} w_j x_j\right) + b$$

$\sum_{j=1}^{n} \rightarrow j = 1 \ldots n$ → 1, 2, 3

range(0, n) → j = 0 ... n-1

```
f = 0
for j in range(0,n):
    f = f + w[j] * x[j]
f = f + b
```

range(n)



Without vectorization $n = 100{,}000$

$$f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x_2 + w_3 x_3 + b$$

```
f = w[0] * x[0] +
    w[1] * x[1] +
    w[2] * x[2] + b
```



Vectorization


$$f_{\vec{w},b}(\vec{x}) = \vec{w} \cdot \vec{x} + b$$

```
f = np.dot(w,x) + b
```



Stanford
ONLINE

DeepLearning.AI



Linear Regression with Multiple Variables

Vectorization Part 2

Without vectorization

```
for j in range(0,16):
    f = f + w[j] * x[j]
```

t_0
```
f + w[0] * x[0]
```


t_1
```
f + w[1] * x[1]
```

…

t_{15}
```
f + w[15] * x[15]
```

Vectorization

```
np.dot(w,x)
```



efficient → scale to large datasets

Gradient descent

$\vec{w} = (w_1 \quad w_2 \quad \cdots \quad w_{16})$ ~~b~~ parameters

derivatives $\vec{d} = (d_1 \quad d_2 \quad \cdots \quad d_{16})$

```
w = np.array([0.5, 1.3, … 3.4])
d = np.array([0.3, 0.2, … 0.4])
```

learning rate α

compute $w_j = w_j - 0.1 d_j$ for $j = 1 \ldots 16$

Without vectorization

$w_1 = w_1 - 0.1 d_1$

$w_2 = w_2 - 0.1 d_2$


$\vdots$

$w_{16} = w_{16} - 0.1 d_{16}$

```
for j in range(0,16):
    w[j] = w[j] - 0.1 * d[j]
```

With vectorization


$\vec{w} = \vec{w} - 0.1\vec{d}$




```
w = w - 0.1 * d
```

Stanford
ONLINE

DeepLearning.AI



Linear Regression with Multiple Variables

Gradient Descent for Multiple Regression

Previous notation

Parameters $w_1, \cdots, w_n$

b

Model $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + \cdots + w_n x_n + b$

Cost function $J(w_1, \cdots, w_n, b)$

Gradient descent

repeat {

$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(w_1, \cdots, w_n, b)$

$b = b - \alpha \frac{\partial}{\partial b} J(w_1, \cdots, w_n, b)$

}

Vector notation

vector of length n

$\vec{w} = [w_1 \quad \cdots \quad w_n]$

b still a number

$f_{\vec{w},b}(\vec{x}) = \vec{w} \cdot \vec{x} + b$

dot product

$J(\vec{w}, b)$

$\vec{w} = (w_1, w_2 \cdots w_n)$

repeat {

$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(\vec{w}, b)$

$b = b - \alpha \frac{\partial}{\partial b} J(\vec{w}, b)$

}

Gradient descent

One feature

repeat {

$$w = w - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{w,b}\left(x^{(i)}\right) - y^{(i)}\right)x^{(i)}$$

$$\frac{\partial}{\partial w}J(w,b)$$

$$b = b - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{w,b}\left(x^{(i)}\right) - y^{(i)}\right)$$

simultaneously update w, b

}

n features ($n \geq 2$)

repeat {

$j = 1$

$$w_1 = w_1 - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right) - y^{(i)}\right)x_1^{(i)}$$

$$\frac{\partial}{\partial w_1}J(\vec{w},b)$$

$\vdots$

$j = n$

$$w_n = w_n - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right) - y^{(i)}\right)x_n^{(i)}$$

$$b = b - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right) - y^{(i)}\right)$$

simultaneously update w_j (for $j = 1, \cdots, n$) and b

}

An alternative to gradient descent


Normal equation
- Only for linear regression
- Solve for w, b without iterations

Disadvantages
- Doesn't generalize to other learning algorithms.
- Slow when number of features is large (> 10,000)

What you need to know
- Normal equation method may be used in machine learning libraries that implement linear regression.
- Gradient descent is the recommended method for finding parameters w,b

Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Feature Scaling Part 1

Feature and parameter values

$\widehat{price} = w_1 x_1 + w_2 x_2 + b$

size #bedrooms

x_1: size (feet^2)
range: $300 - 2{,}000$
large

x_2: # bedrooms
range: $0 - 5$
small

House: $x_1 = 2000$, $x_2 = 5$, $price = \$500\text{k}$ one training example

size of the parameters w_1, w_2?

$w_1 = 50, \quad w_2 = 0.1, \quad b = 50$

$\widehat{price} = \underbrace{50 * 2000}_{100{,}000\text{k}} + \underbrace{0.1 * 5}_{0.5\text{k}} + \underbrace{50}_{50\text{k}}$

$\widehat{price} = \$100{,}050.5\text{k} = \$100{,}050{,}500$

$w_1 = 0.1, \quad w_2 = 50, \quad b = 50$


small large


$\widehat{price} = \underbrace{0.1 * 2000k}_{200\text{k}} + \underbrace{50 * 5}_{250\text{k}} + \underbrace{50}_{50\text{k}}$

$\widehat{price} = \$500\text{k}$ more reasonable


Feature size and parameter size

	size of feature x_j	size of parameter w_j
size in feet^2	⟷	⟷
#bedrooms	⟷	⟷






Feature size and gradient descent



Stanford
ONLINE

DeepLearning.AI




Practical Tips for Linear Regression

Feature Scaling Part 2

Feature scaling

(最大值缩放)





$$300 \le x_1 \le 2000 \qquad 0 \le x_2 \le 5$$


$$x_{1,scaled} = \frac{x_1}{2000} \qquad x_{2,scaled} = \frac{x_2}{5}$$

max max

$$0.15 \le x_{1,scaled} \le 1 \qquad 0 \le x_{2,scaled} \le 1$$

Mean normalization

mean 归一化



所有training data的平均值.

$$300 \le x_1 \le 2000$$

$$x_1 = \frac{x_1 - \mu_1}{2000 - 300}$$

max-min

$$-0.18 \le x_1 \le 0.82$$


$$0 \le x_2 \le 5$$

$$x_2 = \frac{x_2 - \mu_2}{5 - 0}$$

max-min

$$-0.46 \le x_2 \le 0.54$$

Z-score normalization



$300 \le x_1 \le 2000$ $\quad$ $0 \le x_2 \le 5$

$$x_1 = \frac{x_1 - \mu_1}{\sigma_1} \qquad x_2 = \frac{x_2 - \mu_2}{\sigma_2}$$

$-0.67 \le x_1 \le 3.1$ $\quad$ $-1.6 \le x_2 \le 1.9$

Feature scaling

使让特征更有效.

aim for about $-1 \leq x_j \leq 1$ for each feature x_j

$-3 \leq x_j \leq 3$

$-0.3 \leq x_j \leq 0.3$

} acceptable ranges

$0 \leq x_1 \leq 3$ okay, no rescaling

$-2 \leq x_2 \leq 0.5$ okay, no rescaling


$-100 \leq x_3 \leq 100$ too large → rescale

$-0.001 \leq x_4 \leq 0.001$ too small → rescale

$98.6 \leq x_5 \leq 105$ too large → rescale

Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Checking Gradient Descent for Convergence

Gradient descent


$$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(\vec{w}, b)$$

$$b = b - \alpha \frac{\partial}{\partial b} J(\vec{w}, b)$$

Make sure gradient descent is working correctly

objective: $\min_{\vec{w},b} J(\vec{w}, b)$

$J(\vec{w}, b)$ should decrease after every iteration



iterations needed varies 30 1,000 100,000

Automatic convergence test


Let ε "epsilon" be 10^{-3}. 0.001

If $J(\vec{w}, b)$ decreases by $\leq \varepsilon$ in one iteration, declare convergence.

(found parameters $\vec{w}, b$ to get close to global minimum)

Stanford
ONLINE


DeepLearning.AI




Practical Tips for Linear Regression

Choosing the Learning Rate

Identify problem with gradient descent







or learning rate is too large


$w_1 = w_1 + \alpha d_1$

use a minus sign


$w_1 = w_1 - \alpha d_1$

Adjust learning rate

α is too big



Use smaller α



With a small enough α, $J(\vec{w}, b)$ should decrease on every iteration


If α is too small, gradient descent takes a lot more iterations to converge


如果梯度下降不管用，则考虑先把α设的变化较小

Values of α to try:

… 0.001 0.003 0.01 0.03 0.1 0.3 1 …


3X ≈3X 3X ≈3X 3X ≈3X





Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Feature Engineering

Feature engineering

$$f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x_2 + b$$

frontage depth


$$area = frontage \times depth$$

$x_3 = x_1 x_2$

new feature

构造了新特征


$$f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x_2 + w_3 x_3 + b$$



Feature engineering:
Using intuition to design new features, by transforming or combining original features.

Stanford
ONLINE

DeepLearning.AI




Practical Tips for Linear Regression

Polynomial Regression

多项式回归

Polynomial regression



$f_{\vec{w},b}(x) = w_1 x + w_2 x^2 + w_3 x^3 + b$

size $1-10^3$


size^2 $1-10^6$

size^3 $1-10^9$

feature scaling

important

Choice of features



$$f_{\vec{w},b}(x) = w_1 x + w_2 \sqrt{x} + b$$

size

√size

what features to use?

↳ course 2