Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

Stanford
ONLINE

DeepLearning.AI



Machine Learning

Welcome!


eddy

aarti

geoff

Ivy

kin

robert

andres

daniel

Re: Urgent Information :) External Spam ×

Congratulations! You've won a million dollars!



Gmail

Compose

Mail

Inbox

Starred

Snoozed

Sent

Drafts 42

Stanford
ONLINE

DeepLearning.AI



Machine Learning

Applications of Machine Learning

Stanford
ONLINE

DeepLearning.AI



Machine Learning Overview

What is Machine Learning?

Machine learning

"Field of study that gives computers the ability to learn without being explicitly programmed."

Arthur Samuel (1959)



Question

If the checkers program had been allowed to play only ten games (instead of tens of thousands) against itself, a much smaller number of games, how would this have affected its performance?

- Would have made it better
- Would have made it worse

Machine learning algorithms

rapid advancements

used most in real-world applications

- Supervised learning ← course 1, 2
- Unsupervised learning ← course 3
- Recommender systems
- Reinforcement learning

Practical advice for applying learning algorithms

Stanford
ONLINE

DeepLearning.AI



Machine Learning Overview

Supervised Learning Part 1

Supervised learning



Learns from being given "right answers"

predic

Input (X)	Output (Y)	Application
email	spam? (0/1)	spam filtering
audio	text transcripts	speech recognition
English	Spanish	machine translation
ad, user info	click? (0/1)	online advertising
image, radar info	position of other cars	self-driving car
image of phone	defect? (0/1)	visual inspection

Regression: Housing price prediction



Regression

Predict a number

infinitely many possible outputs

Stanford
ONLINE

DeepLearning.AI



Machine Learning Overview

Supervised Learning Part 2

Classification: Breast cancer detection



Classification: Breast cancer detection

benign

malignant type1

malignant type 2



class category

Classification

predict categories cat dog benign malignant 0, 1, 2

small number of possible outputs

Two or more inputs



Supervised learning

Learns from being given "right answers"

Regression

Predict a number

infinitely many possible outputs

Classification

predict categories

small number of possible outputs

Stanford
ONLINE

DeepLearning.AI



Machine Learning Overview

Unsupervised Learning Part 1

Previous: Supervised learning

Now: Unsupervised learning



Supervised learning
Learn from data labeled with the "right answers"



Unsupervised learning
Find something interesting in unlabeled data.



Clustering: Google news

Clustering: DNA microarray



Clustering: Grouping customers



growing skills and knowledge

develop career

stay updated with AI

Stanford
ONLINE

DeepLearning.AI



Machine Learning Overview

Unsupervised Learning Part 2

Unsupervised learning

Data only comes with inputs x, but not output labels y.
Algorithm has to find structure in the data.

Pattern, feature

降维

Clustering
Group similar data points together.

Dimensionality reduction
Compress data using fewer numbers.

Anomaly detection
Find unusual data points.

001

Question

Of the following examples, which would you address using an unsupervised learning algorithm?

- [ ] Given email labeled as spam/not spam, learn a spam filter.
- [x] Given a set of news articles found on the web, group them into sets of articles about the same story.
- [x] Given a database of customer data, automatically discover market segments and group customers into different market segments.
- [ ] Given a dataset of patients diagnosed as either having diabetes or not, learn to classify new patients as having diabetes or not

Stanford
ONLINE

DeepLearning.AI



Machine Learning Overview

Jupyter Notebooks

Stanford
ONLINE

DeepLearning.AI



Linear Regression with One Variable

Linear Regression Model Part 1



Regression model
Predicts numbers
Infinitely many possible outputs

Supervised learning model
Data has "right answers"

Classification model
Predicts categories
Small number of possible outputs

House sizes and prices

Data table

size in feet²	price in $1000's
2104	400
1416	232
1534	315
852	178
...	...
3210	870

Terminology

Training set: Data used to train the model

	x size in feet^2	y price in \$1000's
(1)	2104	400
(2)	1416	232
(3)	1534	315
(4)	852	178
…	…	…
(47)	3210	870

$m = 47$

$x^{(1)} = 2104$ $y^{(1)} = 400$

$(x^{(1)}, y^{(1)}) = (2104, 400)$

$x^{(2)} = 1416$ $y^{(2)} \neq x^2$ not exponent

Notation:

x = "input" variable
feature

y = "output" variable
"target" variable

m = number of training examples

(x, y) = single training example

$(x^{(i)}, y^{(i)})$

$(x^{(i)}, y^{(i)})$ = i^{th} training example

index (1^{st}, 2^{nd}, 3^{rd} …)

Stanford
ONLINE

DeepLearning.AI



Linear Regression with One Variable

Linear Regression Model Part 2



How to represent f?

$f_{w,b}(x) = wx + b$

$f(x)$



$f_{w,b}(x) = wx + b$

$f(x) = wx + b$

linear

single feature x

Linear regression with one variable.

size

Univariate linear regression.

one variable

Stanford
ONLINE

DeepLearning.AI



Linear Regression with One Variable

Cost Function

Training set

features

targets

size in feet^2 (x)	price \$1000's (y)
2104	460
1416	232
1534	315
852	178
...	...

Model: $f_{w,b}(x) = wx + b$

w, b: parameters

coefficients

weights

What do w, b do?

$$f_{w,b}(x) = wx + b$$

$f(x)$



→ $w = 0$

→ $b = 1.5$ (y-intercept)



→ $w = 0.5$

→ $b = 0$



→ $w = 0.5$

→ $b = 1$



$$\hat{y}^{(i)} = f_{w,b}(x^{(i)})$$

$$f_{w,b}(x^{(i)}) = wx^{(i)} + b$$

Cost function: Squared error cost function

$$J(w,b) = \frac{1}{2m}\sum_{i=1}^{m}\left(\hat{y}^{(i)} - y^{(i)}\right)^2$$

$\hat{y}^{(i)}$ − $y^{(i)}$: error

m = number of training examples

$$J(w,b) = \frac{1}{2m}\sum_{i=1}^{m}\left(f_{w,b}(x^{(i)}) - y^{(i)}\right)^2$$

$J(w,b)$: intuition (next!)

Find w, b:

$\hat{y}^{(i)}$ is close to $y^{(i)}$ for all $(x^{(i)}, y^{(i)})$.

Stanford
ONLINE

DeepLearning.AI



Linear Regression with One Variable

Cost Function Intuition

model:

$$f_{w,b}(x) = wx + b$$

parameters:

w, b



cost function:

$$J(w,b) = \frac{1}{2m}\sum_{i=1}^{m}(f_{w,b}(x^{(i)}) - y^{(i)})^2$$

goal:

$$\underset{w,b}{\text{minimize}}\, J(w,b)$$

simplified

$$f_w(x) = wx$$

$b = 0$

w



$$J(w) = \frac{1}{2m}\sum_{i=1}^{m}(f_w(x^{(i)}) - y^{(i)})^2$$

$wx^{(i)}$

$$\underset{w}{\text{minimize}}\, J(w)$$





$$J(w) = \frac{1}{2m}\sum_{i=1}^{m}(f_w(x^{(i)}) - y^{(i)})^2 = \frac{1}{2m}\sum_{i=1}^{m}(wx^{(i)} - y^{(i)})^2 = \frac{1}{2m}(0^2 + 0^2 + 0^2) = 0$$



$$J(0.5) = \frac{1}{2m}\left[(0.5-1)^2+(1-2)^2+(1.5-3)^2\right] = \frac{1}{2\times 3}[3.5] = \frac{3.5}{6} \approx 0.58$$



$f(x) = -0.5x$



$$J(0) = \frac{1}{2m}\left(1^2+2^2+3^2\right) = \frac{1}{6}[14] \approx 2.3$$

how to choose w?

goal of linear regression:

$$\underset{w}{\text{minimize}}\, J(w)$$

general case:

$$\underset{w,b}{\text{minimize}}\, J(w,b)$$



Stanford
ONLINE

DeepLearning.AI



Linear Regression with One Variable

Visualizing the Cost Function

Model $f_{w,b}(x) = wx + b$

~~before: $b = 0$~~

Parameters w, b

Cost Function $J(w,b) = \frac{1}{2m}\sum_{i=1}^{m}(f_{w,b}(x^{(i)}) - y^{(i)})^2$

Objective $\underset{w,b}{\text{minimize}}\, J(w,b)$

$f_{w,b}$

(function of x)



$f_{w,b}(x) = 0.06x + 50$

J

(function of w, b)



w , b


$J_{(w,b)}$
800
700
600
500
400
300
200
100
$J(w,b)$
20
15
10
5
0
b
−5
−10
−15
−20
−20
−15
−10
−5
0
5
10
15
20
w
$J(w=-10, b=-15)$

3D surface plot



Alternative contour plot


Mount Fuji
Legend
Contour
Mount Fuji
Mount Fuji
Google Earth
Image Landsat / Copernicus
Data SIO, NOAA, U.S. Navy, NGA, GEBCO
Data Japan Hydrographic Association
3000 ft


Mount Fuji
Legend
Contour
Mount Fuji
Mount Fuji
Google Earth
1 mi


$f_{w,b}$
price in $1000's
size in feet^2
J
click within this plot to add points
b
w
minimum
same J


Mount Fuji
Google Earth


J
you can rotate this figure
J(w, b)
1e8
b
w
minimum


Mount Fuji
Google Earth

Stanford
ONLINE

DeepLearning.AI



Linear Regression with One Variable

Visualization examples


800
$f_{w,b}$
price in $1000's
size in feet^2
$f(x) = -0.15x + 800$
slope
J
click within this plot to add points
800
-0.15
w
b


J
you can rotate this figure
1e8
J(w, b)
b
w


$f_{w,b}$
price in $1000's
size in feet^2
f(x) = 0x + 360
J
click within this plot to add points
360
0
b
w
J
you can rotate this figure
1e8
J(w, b)
b
w



you can rotate this figure




$f_{w,b}$
price in $1000's
size in feet^2
error
$f(x) = 0.13x + 71$
J
click within this plot to add points
71
0.13
minimum
w
b
you can rotate this figure
1e8
J(w, b)

Stanford
ONLINE

DeepLearning.AI



Training Linear Regression

Gradient Descent

Have some function $J(w,b)$

for linear regression or any function

Want $\min_{w,b} J(w,b)$

$\min_{w_1, \ldots, w_n, b} J(w_1, w_2, \ldots, w_n, b)$

Outline:

- Start with some w, b (set $w=0, b=0$)
- Keep changing w, b to reduce $J(w,b)$
- Until we settle at or near a minimum

J not always



may have >1 minimum

gradient descent

$J(w, b)$

not squared error cost

not linear regression



local minima

Stanford
ONLINE

DeepLearning.AI



Training Linear Regression

Implementing Gradient Descent

Gradient descent algorithm

Repeat until convergence

$$w = w - \alpha \frac{d}{dw} J(w,b)$$

$$b = b - \alpha \frac{d}{db} J(w,b)$$

Learning rate

Derivative 导数

Simultaneously update w and b

Assignment

$a = c$

$a = a + 1$

Code 赋值语句

Truth assertion

$a = c$

$a = a + 1$ ✗

Math

a==c

Correct: Simultaneous update

$$tmp_w = w - \alpha \frac{\partial}{\partial w} J(w,b)$$

$$tmp_b = b - \alpha \frac{\partial}{\partial b} J(w,b)$$

$$w = tmp_w$$

$$b = tmp_b$$

Incorrect

$$tmp_w = w - \alpha \frac{\partial}{\partial w} J(w,b)$$

$$w = tmp_w$$

用了未定义的 w

$$tmp_b = b - \alpha \frac{\partial}{\partial b} J(w,b)$$

$$b = tmp_b$$

Stanford
ONLINE

DeepLearning.AI



Training Linear Regression

Gradient Descent Intuition

Gradient descent algorithm

repeat until convergence {

learning rate

$$w = w - \alpha \frac{\partial}{\partial w} J(w, b)$$

derivative

$$b = b - \alpha \frac{\partial}{\partial b} J(w, b)$$

}

$J(w)$

$$w = w - \alpha \frac{\partial}{\partial w} J(w)$$

$$\min_{w} J(w)$$



$$w = w - \alpha \underbrace{\frac{d}{dw} J(w)}_{>0}$$

$$w = w - \alpha \cdot (positive\ number)$$

$$\underbrace{\frac{d}{dw} J(w)}_{<0}$$

$$w = w - \alpha \cdot (negative\ number)$$

Stanford
ONLINE

DeepLearning.AI



Training Linear Regression

Learning Rate

$$w = w - \alpha \frac{d}{dw} J(w)$$

If α is too small…

Gradient descent may be slow.

If α is too large…

Gradient descent may:

- Overshoot, never reach minimum
- Fail to converge, diverge







$$w = w - \alpha \frac{d}{dw} J(w)$$

0.1

$=0$

$5 - 0.1 \cdot 0$

$w = w - \alpha \cdot 0$

$w = w$

Can reach local minimum with fixed learning rate

$$w = w - \alpha \frac{d}{dw} J(w)$$

smaller

not as large

large



Near a local minimum,
- Derivative becomes smaller
- Update steps become smaller

Can reach minimum without decreasing learning rate α

Stanford
ONLINE

DeepLearning.AI



Training Linear Regression

Gradient Descent for Linear Regression

Linear regression model

$$f_{w,b}(x) = wx + b$$

Cost function

$$J(w,b) = \frac{1}{2m}\sum_{i=1}^{m}(f_{w,b}(x^{(i)}) - y^{(i)})^2$$

Gradient descent algorithm

repeat until convergence {

$$w = w - \alpha \frac{\partial}{\partial w} J(w,b) \rightarrow \frac{1}{m}\sum_{i=1}^{m}(f_{w,b}(x^{(i)}) - y^{(i)})x^{(i)}$$

$$b = b - \alpha \frac{\partial}{\partial b} J(w,b) \rightarrow \frac{1}{m}\sum_{i=1}^{m}(f_{w,b}(x^{(i)}) - y^{(i)})$$

}

next slide is optional!

(Optional)

$$\frac{\partial}{\partial w} J(w,b) = \frac{d}{dw} \frac{1}{2m} \sum_{i=1}^{m} \left(f_{w,b}(x^{(i)}) - y^{(i)}\right)^2 = \frac{d}{dw} \frac{1}{2m} \sum_{i=1}^{m} \left(wx^{(i)} + b - y^{(i)}\right)^2$$

$$= \frac{1}{2m} \sum_{i=1}^{m} \left(wx^{(i)} + b - y^{(i)}\right) 2x^{(i)} = \frac{1}{m} \sum_{i=1}^{m} \left(f_{w,b}(x^{(i)}) - y^{(i)}\right) x^{(i)}$$

$$\frac{\partial}{\partial b} J(w,b) = \frac{d}{db} \frac{1}{2m} \sum_{i=1}^{m} \left(f_{w,b}(x^{(i)}) - y^{(i)}\right)^2 = \frac{d}{db} \frac{1}{2m} \sum_{i=1}^{m} \left(wx^{(i)} + b - y^{(i)}\right)^2$$

$$= \frac{1}{2m} \sum_{i=1}^{m} \left(wx^{(i)} + b - y^{(i)}\right) 2 = \frac{1}{m} \sum_{i=1}^{m} \left(f_{w,b}(x^{(i)}) - y^{(i)}\right)$$

no $x^{(i)}$

Gradient descent algorithm

$\frac{\partial}{\partial w} J(w,b)$

repeat until convergence {

$$w = w - \alpha \frac{1}{m} \sum_{i=1}^{m} \left(f_{w,b}\left(x^{(i)}\right) - y^{(i)} \right) x^{(i)}$$

$$b = b - \alpha \frac{1}{m} \sum_{i=1}^{m} \left(f_{w,b}\left(x^{(i)}\right) - y^{(i)} \right)$$

}

Update w and b simultaneously

$\frac{\partial}{\partial b} J(w,b)$

$f_{w,b}(x^{(i)}) = wx^{(i)} + b$

More than one local minimum



squared error cost



bowl shape

convex function

Stanford
ONLINE

DeepLearning.AI



Training Linear Regression

Running Gradient Descent


$f_{w,b}(size)$
$J(w,b)$
f(x) = -0.1 x + 900
cost: 77237
b = 900
w = -0.1
price in $1000's
size in feet²
$J(w,b)$
$J(w,b)$
b
w


$f_{w,b}(size)$
price in $1000's
size in feet²
$J(w,b)$
Cost: 77237
Cost: 45401
b
w
$J(w,b)$
log
b
w


$f_{w,b}(size)$
800
600
400
200
0
1000
2000
3000
4000
5000
b
$J(w,b)$
1000
750
500
250
0
−250
−500
−750
−1000
Cost: 77237
Cost: 45401
Cost: 29109
−0.4
−0.2
0.0
0.2
0.4
w
$J(w,b)$
log
3.0
2.5
2.0
1.5
1.0
0.5
0.0
$J(w,b)$
1000
750
500
250
0
−250
−500
−750
−1000
b
−0.4
−0.2
0.0
0.2
0.4
w


$f_{w,b}(size)$
price in $1000's
size in feet²
$J(w,b)$
Cost: 77237
Cost: 45401
Cost: 29109
Cost: 19076
$J(w,b)$


$f_{w,b}(size)$
price in $1000's
size in feet^2
$J(w,b)$
Cost: 77237
Cost: 45401
Cost: 29109
Cost: 19076
Cost: 13318
w
b
$J(w,b)$
log
3.0
2.5
2.0
1.5
1.0
0.5
0.0


$f_{w,b}(size)$
price in $1000's
size in feet^2
$J(w,b)$
Cost: 77237
Cost: 45401
Cost: 29109
Cost: 19076
Cost: 13318
Cost: 9460
$J(w,b)$


$f_{w,b}(size)$
price in $1000's
size in feet²
$J(w,b)$
Cost: 77237
Cost: 45401
Cost: 29109
Cost: 19076
Cost: 13318
Cost: 9460
Cost: 5729
w
b
$J(w,b)$
log
$J(w,b)$


$f_{w,b}(size)$
price in $1000's
size in feet²
$J(w,b)$
Cost: 77237
Cost: 45401
Cost: 29109
Cost: 19076
Cost: 13318
Cost: 9460
Cost: 5729
Cost: 3559
$J(w,b)$
log
$J(w,b)$
b
w


$f_{w,b}(size)$
price in $1000's
$250K
1250
size in feet²
$J(w,b)$
Cost: 77237
Cost: 45401
Cost: 29109
Cost: 19076
Cost: 13318
Cost: 9460
Cost: 5729
Cost: 3559
Cost: 2311
$J(w,b)$

"Batch" gradient descent

DeepLearning.AI
THE BATCH

"Batch": Each step of gradient descent uses all the training examples.

other gradient descent: subsets

	x size in feet^2	y price in \$1000's
(1)	2104	400
(2)	1416	232
(3)	1534	315
(4)	852	178
...	...	...
(47)	3210	870

$m = 47$

$$\sum_{i=1}^{m} (f_{w,b}(x^{(i)}) - y^{(i)})^2$$



Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

Stanford
ONLINE

DeepLearning.AI



Linear Regression with Multiple Variables

Multiple Features

Multiple features (variables)

one feature →

Size in feet^2 (x)	Price ($) in 1000's (y) ←
2104	400
1416	232
1534	315
852	178
…	…

$$f_{w,b}(x) = wx + b$$

Multiple features (variables)

Size in feet²	Number of bedrooms	Number of floors	Age of home in years	Price ($) in $1000's
x_1	x_2	x_3	x_4	
2104	5	1	45	460
1416	3	2	40	232
1534	3	2	30	315
852	2	1	36	178
...	...	...	...	...

$j = 1 \ldots 4$

$n = 4$

$i = 2$

x_j = j^{th} feature

n = number of features

$\vec{x}^{(i)}$ = features of i^{th} training example

$x_j^{(i)}$ = value of feature j in i^{th} training example

$\vec{x}^{(2)} = [1416 \quad 3 \quad 2 \quad 40]$

$x_3^{(2)} = 2$

Model:

Previously: $f_{w,b}(x) = wx + b$

$$f_{w,b}(X) = w_1 X_1 + w_2 X_2 + w_3 X_3 + w_4 X_4 + b$$

example

$$f_{w,b}(X) = 0.1 X_1 + 4 X_2 + 10 X_3 + -2 X_4 + 80$$

X_1: size
X_2: #bedrooms
X_3: #floors
X_4: years
80: base price

$$f_{w,b}(x) = w_1 x_1 + w_2 x_2 + \cdots + w_n x_n + b$$

$$f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x_2 + \cdots + w_n x_n + b$$

$\vec{w} = [w_1 \; w_2 \; w_3 \ldots w_n]$ parameters of the model

b is a number

vector $\vec{x} = [x_1 \; x_2 \; x_3 \ldots x_n]$

$$f_{\vec{w},b}(\vec{x}) = \vec{w} \cdot \vec{x} + b = w_1 x_1 + w_2 x_2 + w_3 x_3 + \cdots + w_n x_n + b$$

dot product

multiple linear regression

(not multivariate regression)

Stanford
ONLINE

DeepLearning.AI



Linear Regression with Multiple Variables

Vectorization Part 1

Parameters and features

$\vec{w} = [w_1 \quad w_2 \quad w_3]$ $n = 3$

b is a number

$\vec{x} = [x_1 \quad x_2 \quad x_3]$

linear algebra: count from 1

w[0] w[1] w[2]

```
w = np.array([1.0,2.5,-3.3])
b = 4
x = np.array([10,20,30])
```

x[0] x[1] x[2]

code: count from 0

Without vectorization

$$f_{\vec{w},b}(\vec{x}) = \left(\sum_{j=1}^{n} w_j x_j\right) + b$$

$\sum_{j=1}^{n} \rightarrow j = 1 \ldots n$ 1, 2, 3

range(0, n) → j = 0 ... n-1

```
f = 0          range(n)
for j in range(0,n):
    f = f + w[j] * x[j]
f = f + b
```

Without vectorization $n = 100{,}000$

$$f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x_2 + w_3 x_3 + b$$

```
f = w[0] * x[0] +
    w[1] * x[1] +
    w[2] * x[2] + b
```

Vectorization

$$f_{\vec{w},b}(\vec{x}) = \vec{w} \cdot \vec{x} + b$$

```
f = np.dot(w,x) + b
```



Stanford
ONLINE

DeepLearning.AI



Linear Regression with Multiple Variables

Vectorization Part 2

Without vectorization

```
for j in range(0,16):
    f = f + w[j] * x[j]
```

t_0
```
f + w[0] * x[0]
```

t_1
```
f + w[1] * x[1]
```

...

t_{15}
```
f + w[15] * x[15]
```

Vectorization

```
np.dot(w,x)
```



efficient → scale to large datasets

Gradient descent

$\vec{w} = (w_1 \quad w_2 \quad \cdots \quad w_{16})$ ~~b~~ parameters

derivatives $\vec{d} = (d_1 \quad d_2 \quad \cdots \quad d_{16})$

```
w = np.array([0.5, 1.3, … 3.4])
d = np.array([0.3, 0.2, … 0.4])
```

learning rate α

compute $w_j = w_j - 0.1 d_j$ for $j = 1 \ldots 16$

Without vectorization

$w_1 = w_1 - 0.1 d_1$

$w_2 = w_2 - 0.1 d_2$

$\vdots$

$w_{16} = w_{16} - 0.1 d_{16}$

```
for j in range(0,16):
    w[j] = w[j] - 0.1 * d[j]
```

With vectorization

$\vec{w} = \vec{w} - 0.1\vec{d}$




```
w = w - 0.1 * d
```

Stanford
ONLINE

DeepLearning.AI



Linear Regression with Multiple Variables

Gradient Descent for Multiple Regression

Previous notation

Parameters $w_1, \cdots, w_n$

b

Model $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + \cdots + w_n x_n + b$

Cost function $J(w_1, \cdots, w_n, b)$

Gradient descent

repeat {

$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(w_1, \cdots, w_n, b)$

$b = b - \alpha \frac{\partial}{\partial b} J(w_1, \cdots, w_n, b)$

}

Vector notation

vector of length n

$\vec{w} = [w_1 \quad \cdots \quad w_n]$

b still a number

$f_{\vec{w},b}(\vec{x}) = \vec{w} \cdot \vec{x} + b$

dot product

$J(\vec{w}, b)$

$\vec{w} = (w_1, w_2 \cdots w_n)$

repeat {

$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(\vec{w}, b)$

$b = b - \alpha \frac{\partial}{\partial b} J(\vec{w}, b)$

}

Gradient descent

One feature

repeat {

$$w = w - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{w,b}\left(x^{(i)}\right) - y^{(i)}\right)x^{(i)}$$

$$\frac{\partial}{\partial w}J(w,b)$$

$$b = b - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{w,b}\left(x^{(i)}\right) - y^{(i)}\right)$$

simultaneously update w, b

}

n features ($n \geq 2$)

repeat {

$j = 1$

$$w_1 = w_1 - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right) - y^{(i)}\right)x_1^{(i)}$$

$$\frac{\partial}{\partial w_1}J(\vec{w},b)$$

$\vdots$

$j = n$

$$w_n = w_n - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right) - y^{(i)}\right)x_n^{(i)}$$

$$b = b - \alpha \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right) - y^{(i)}\right)$$

simultaneously update w_j (for $j = 1, \cdots, n$) and b

}

An alternative to gradient descent

Normal equation
- Only for linear regression
- Solve for w, b without iterations

Disadvantages
- Doesn't generalize to other learning algorithms.
- Slow when number of features is large (> 10,000)

What you need to know
- Normal equation method may be used in machine learning libraries that implement linear regression.
- Gradient descent is the recommended method for finding parameters w,b

Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Feature Scaling Part 1

Feature and parameter values

$\widehat{price} = w_1 x_1 + w_2 x_2 + b$

size #bedrooms

x_1: size (feet^2)
range: $300 - 2{,}000$
large

x_2: # bedrooms
range: $0 - 5$
small

House: $x_1 = 2000$, $x_2 = 5$, $price = \$500\text{k}$

one training example

size of the parameters w_1, w_2?

$w_1 = 50, \quad w_2 = 0.1, \quad b = 50$

$\widehat{price} = \underbrace{50 * 2000}_{100{,}000\text{k}} + \underbrace{0.1 * 5}_{0.5\text{k}} + \underbrace{50}_{50\text{k}}$

$\widehat{price} = \$100{,}050.5\text{k} = \$100{,}050{,}500$

$w_1 = 0.1, \quad w_2 = 50, \quad b = 50$

small large

$\widehat{price} = \underbrace{0.1 * 2000k}_{200\text{k}} + \underbrace{50 * 5}_{250\text{k}} + \underbrace{50}_{50\text{k}}$

$\widehat{price} = \$500\text{k}$ more reasonable

Feature size and parameter size

	size of feature x_j	size of parameter w_j
size in feet^2	⟷	⟷
#bedrooms	⟷	⟷





Feature size and gradient descent





Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Feature Scaling Part 2

Feature scaling

(最大值缩放)



$$300 \le x_1 \le 2000 \qquad 0 \le x_2 \le 5$$

$$x_{1,scaled} = \frac{x_1}{2000} \quad \text{max} \qquad x_{2,scaled} = \frac{x_2}{5} \quad \text{max}$$

$$0.15 \le x_{1,scaled} \le 1 \qquad 0 \le x_{2,scaled} \le 1$$

Mean normalization

mean 归一化



所有training data 的平均值.

$$300 \le x_1 \le 2000$$

$$x_1 = \frac{x_1 - \mu_1}{2000 - 300}$$

max-min

$$-0.18 \le x_1 \le 0.82$$

$$0 \le x_2 \le 5$$

$$x_2 = \frac{x_2 - \mu_2}{5 - 0}$$

max-min

$$-0.46 \le x_2 \le 0.54$$

Z-score normalization



$300 \le x_1 \le 2000$ $\quad$ $0 \le x_2 \le 5$

$$x_1 = \frac{x_1 - \mu_1}{\sigma_1} \qquad x_2 = \frac{x_2 - \mu_2}{\sigma_2}$$

$-0.67 \le x_1 \le 3.1$ $\quad$ $-1.6 \le x_2 \le 1.9$

Feature scaling → 能让算法更有效.

aim for about $-1 \le x_j \le 1$ for each feature x_j

$-3 \le x_j \le 3$

$-0.3 \le x_j \le 0.3$

} acceptable ranges

$0 \le x_1 \le 3$ okay, no rescaling

$-2 \le x_2 \le 0.5$ okay, no rescaling

$-100 \le x_3 \le 100$ too large → rescale

$-0.001 \le x_4 \le 0.001$ too small → rescale

$98.6 \le x_5 \le 105$ too large → rescale

Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Checking Gradient Descent for Convergence

Gradient descent

$$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(\vec{w}, b)$$

$$b = b - \alpha \frac{\partial}{\partial b} J(\vec{w}, b)$$

Make sure gradient descent is working correctly

objective: $\min_{\vec{w},b} J(\vec{w}, b)$

$J(\vec{w}, b)$ should decrease after every iteration



iterations needed varies 30 1,000 100,000

Automatic convergence test

Let ε "epsilon" be 10^{-3}. 0.001

If $J(\vec{w}, b)$ decreases by $\leq \varepsilon$ in one iteration, declare convergence.

(found parameters $\vec{w}, b$ to get close to global minimum)

Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Choosing the Learning Rate

Identify problem with gradient descent





or learning rate is too large

$w_1 = w_1 + \alpha d_1$

use a minus sign

$w_1 = w_1 - \alpha d_1$

Adjust learning rate

α is too big



Use smaller α



With a small enough α, $J(\vec{w}, b)$ should decrease on every iteration

If α is too small, gradient descent takes a lot more iterations to converge

如果梯度下降不管用，则考虑先把α设的变化较小

Values of α to try:

… 0.001 0.003 0.01 0.03 0.1 0.3 1 …

3x ≈3x 3x ≈3x 3x ≈3x





Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Feature Engineering

Feature engineering

$$f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x_2 + b$$

frontage depth

$$area = frontage \times depth$$

$x_3 = x_1 x_2$

new feature

构造了新特征

$$f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x_2 + w_3 x_3 + b$$



Feature engineering:
Using intuition to design new features, by transforming or combining original features.

Stanford
ONLINE

DeepLearning.AI



Practical Tips for Linear Regression

Polynomial Regression

多项式回归

Polynomial regression



$f_{\vec{w},b}(x) = w_1 x + w_2 x^2 + w_3 x^3 + b$

size $1-10^3$

size^2 $1-10^6$

size^3 $1-10^9$

feature scaling

important

Choice of features



$$f_{\vec{w},b}(x) = w_1 x + w_2 \sqrt{x} + b$$

size

√size

what features to use?

↳ course 2

Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

Stanford
ONLINE

DeepLearning.AI



Classification

why

Motivations

Classification

Question	Answer "y"	
Is this email spam?	no	yes
Is the transaction fraudulent?	no	yes
Is the tumor malignant?	no	yes

y can only be one of two values

"binary classification"

class = category

false true

0 1

useful for classification

"negative class"

≠ "bad"

absence

"positive class"

≠ "good"

presence


(yes) 1
malignant?
(no) 0
tumor size x
(diameter in cm)
benign
malignant


decision boundary
$f_{w,b}(x) = wx + b$
$f_{w,b}(x) = wx + b$
(yes) 1
threshold
malignant?
0.5
(no) 0
$\hat{y} = 1$
$\hat{y} = 0$
1
0
1
0
tumor size x
(diameter in cm)
worse: misclassified
if $f_{w,b}(x) < 0.5 \rightarrow \hat{y} = 0$
if $f_{w,b}(x) \geq 0.5 \rightarrow \hat{y} = 1$
next: logistic regression
classification

Stanford
ONLINE

DeepLearning.AI



Classification

Logistic Regression



Want outputs between 0 and 1



sigmoid function

logistic function

outputs between 0 and 1

$$g(z) = \frac{1}{1+e^{-z}} \qquad 0 < g(z) < 1$$

Want outputs between 0 and 1



sigmoid function

logistic function

outputs between 0 and 1

$$g(z) = \frac{1}{1+e^{-z}} \qquad 0 < g(z) < 1$$

$f_{\vec{w},b}(\vec{x})$

$\vec{w} \cdot \vec{x} + b$

z

$g(z) = \frac{1}{1+e^{-z}}$

$$f_{\vec{w},b}(\vec{x}) = g(\underbrace{\vec{w} \cdot \vec{x} + b}_{z}) = \frac{1}{1 + e^{-(\vec{w} \cdot \vec{x} + b)}}$$

"logistic regression"

$e \approx 2.7$

Interpretation of logistic regression output

$$f_{\vec{w},b}(\vec{x}) = \frac{1}{1 + e^{-(\vec{w}\cdot\vec{x}+b)}}$$

"probability" that class is 1

$$f_{\vec{w},b}(\vec{x}) = P(y = 1|\vec{x}; \vec{w}, b)$$

Probability that y is 1, given input $\vec{x}$, parameters $\vec{w}, b$

Example:

x is "tumor size"

y is 0 (not malignant) or 1 (malignant)

$$P(y = 0) + P(y = 1) = 1$$

$f_{\vec{w},b}(\vec{x}) = 0.7$

70% chance that y is 1

Stanford
ONLINE

DeepLearning.AI



Classification

Decision Boundary



$$f_{\vec{w},b}(\vec{x}) = g(\vec{w} \cdot \vec{x} + b)$$

$$= P(y = 1 \mid \vec{x}; \vec{w}, b)$$

$$= \frac{1}{1 + e^{-(\vec{w} \cdot \vec{x} + b)^z}}$$

0 or 1?

threshold

Is $f_{\vec{w},b}(\vec{x}) \geq 0.5$?

Yes: $\hat{y} = 1$ No: $\hat{y} = 0$

When is $f_{\vec{w},b}(\vec{x}) \geq 0.5$?

$g(z) \geq 0.5$

$z \geq 0$

$\vec{w} \cdot \vec{x} + b \geq 0$

$\hat{y} = 1$

$z < 0$

$\vec{w} \cdot \vec{x} + b < 0$

$\hat{y} = 0$

Decision boundary

$$f_{\vec{w},b}(\vec{x}) = g(z) = g(w_1 x_1 + w_2 x_2 + b)$$

1 1 -3

Decision boundary $z = \vec{w} \cdot \vec{x} + b = 0$ (决策边界)

$z = x_1 + x_2 - 3 = 0$

$x_1 + x_2 = 3$



$x_1 + x_2 \geq 3$

$x_1 + x_2 < 3$

Non-linear decision boundaries 非线性决策边界



$x_1^2 + x_2^2 \geq 1$

$\hat{y} = 1$

$x_1^2 + x_2^2 < 1$

$\hat{y} = 0$

z

$w_1 x_1^2 + w_2 x_2^2 + b$

1 1 -1

decision boundary $z = x_1^2 + x_2^2 - 1 = 0$

$x_1^2 + x_2^2 = 1$

Non-linear decision boundaries



椭圆



$$f_{\vec{w},b}\left(\vec{x}\right) = g(z) = g(w_1x_1 + w_2x_2 + w_3x_1^2 + w_4x_1x_2 + w_5x_2^2 + w_6x_1^3 + \cdots + b)$$

多次式特征可以构造复杂决策边界

Stanford
ONLINE

DeepLearning.AI



Cost Function

Cost Function for Logistic Regression

Training set

	tumor size (cm) x_1	…	patient's age x_n	malignant? y
$i=1$	10		52	1
	2		73	0
	5		55	0
	12		49	1
$i=m$	…		…	…

$i = 1, \ldots, m$ ← training examples

$j = 1, \ldots, n$ ← features

target y is 0 or 1

$$f_{\vec{w},b}(\vec{x}) = \frac{1}{1 + e^{-(\vec{w} \cdot \vec{x} + b)}}$$

How to choose $\vec{w} = [w_1 \quad w_2 \quad \cdots \quad w_n]$ and b?

Squared error cost

cost

$$J(\vec{w}, b) = \frac{1}{m}\sum_{i=1}^{m}\frac{1}{2}\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right) - y^{(i)}\right)^2$$

average of training set

loss

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right)$$

linear regression

$$f_{\vec{w},b}(\vec{x}) = \vec{w} \cdot \vec{x} + b$$

logistic regression

$$f_{\vec{w},b}(\vec{x}) = \frac{1}{1 + e^{-(\vec{w}\cdot\vec{x}+b)}}$$





Logistic loss function

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = \begin{cases} -\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 1 \\ -\log\left(1 - f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 0 \end{cases}$$





As $f_{\vec{w},b}\left(\vec{x}^{(i)}\right) \to 1$ then loss $\to 0$

As $f_{\vec{w},b}\left(\vec{x}^{(i)}\right) \to 0$ then loss $\to \infty$

Loss is lowest when $f_{\vec{w},b}\left(\vec{x}^{(i)}\right)$ predicts close to true label $y^{(i)}$.

Logistic loss function

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = \begin{cases} -\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 1 \\ -\log\left(1 - f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 0 \end{cases}$$

As $f_{\vec{w},b}\left(\vec{x}^{(i)}\right) \to 0$ then loss $\to 0$



As $f_{\vec{w},b}\left(\vec{x}^{(i)}\right) \to 1$ then loss $\to \infty$



The further prediction $f_{\vec{w},b}\left(\vec{x}^{(i)}\right)$ is from target $y^{(i)}$, the higher the loss.

Cost

MSE 损失不适合 logistic 函数

cost

$$J(\vec{w}, b) = \frac{1}{m}\sum_{i=1}^{m} L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right)$$

loss

$$= \begin{cases} -\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 1 \\ -\log\left(1 - f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 0 \end{cases}$$

convex
↳ can reach a global minimum

find w, b that minimize cost J

Stanford
ONLINE

DeepLearning.AI



Cost Function

Simplified Cost Function for Logistic Regression

Simplified loss function

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = \begin{cases} -\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 1 \\ -\log\left(1 - f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 0 \end{cases}$$

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = -y^{(i)}\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) - \left(1 - y^{(i)}\right)\log\left(1 - f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right)$$

1 (1 − 1)

if $y^{(i)} = 1$:

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = -1\log\left(f(\vec{x})\right)$$

$y^{(i)}$ 只能取值为 0 或者 1

Simplified loss function

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = \begin{cases} -\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 1 \\ -\log\left(1 - f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) & \text{if } y^{(i)} = 0 \end{cases}$$

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = -y^{(i)}\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) - \left(1 - y^{(i)}\right)\log\left(1 - f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right)$$

$y^{(i)}$ → 0 ; $(1 - y^{(i)})$ → $(1 - 0)$

if $y^{(i)} = 1$:

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = -1 \log\left(f(\vec{x})\right)$$

if $y^{(i)} = 0$:

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = -(1-0)\log\left(1 - f(\vec{x})\right)$$

Simplified cost function

loss

$$L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right) = -y^{(i)}\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) - \left(1-y^{(i)}\right)\log\left(1-f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right)$$

convex (single global minimum)

cost

$$J(\vec{w},b) = \frac{1}{m}\sum_{i=1}^{m}\left[L\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right), y^{(i)}\right)\right]$$

$$= -\frac{1}{m}\sum_{i=1}^{m}\left[y^{(i)}\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) + \left(1-y^{(i)}\right)\log\left(1-f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right)\right]$$

maximum likelihood (don't worry about it!) (最大似然)

Stanford
ONLINE

DeepLearning.AI



Gradient Descent

Gradient Descent Implementation

Training logistic regression

Find $\vec{w}, b$

Given new $\vec{x}$, output $f_{\vec{w},b}(\vec{x}) = \frac{1}{1+e^{-(\vec{w}\cdot\vec{x}+b)}}$

$P(y = 1|\vec{x}; \vec{w}, b)$

Gradient descent

n个特征，m个样本

cost

$$J(\vec{w}, b) = -\frac{1}{m}\sum_{i=1}^{m}\left[y^{(i)}\log\left(f_{\vec{w},b}(\vec{x}^{(i)})\right) + (1-y^{(i)})\log\left(1-f_{\vec{w},b}(\vec{x}^{(i)})\right)\right]$$

repeat {

$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(\vec{w}, b)$ 　　$\frac{\partial}{\partial w_j} J(\vec{w}, b) = \frac{1}{m}\sum_{i=1}^{m}(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)})x_j^{(i)}$

$b = b - \alpha \frac{\partial}{\partial b} J(\vec{w}, b)$ 　　$\frac{\partial}{\partial b} J(\vec{w}, b) = \frac{1}{m}\sum_{i=1}^{m}(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)})$

} simultaneous updates

同时运行时，同时更新

Gradient descent for logistic regression

repeat {

looks like linear regression!

$$w_j = w_j - \alpha \left[\frac{1}{m} \sum_{i=1}^{m} (f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}) x_j^{(i)} \right]$$

$$b = b - \alpha \left[\frac{1}{m} \sum_{i=1}^{m} (f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}) \right]$$

} simultaneous updates

Same concepts:

- Monitor gradient descent (learning curve)
- Vectorized implementation 向量化
- Feature scaling → 让梯度下降更快

Linear regression $f_{\vec{w},b}(\vec{x}) = \vec{w} \cdot \vec{x} + b$

Logistic regression $f_{\vec{w},b}(\vec{x}) = \frac{1}{1 + e^{(-\vec{w} \cdot \vec{x} + b)}}$

loss function 不一样，所以 logistic 和 linear regression 不一样

Stanford
ONLINE

DeepLearning.AI



Regularization to Reduce Overfitting

The Problem of Overfitting

Regression example



underfit

- Does not fit the training set well

high bias



just right

- Fits training set pretty well

generalization



overfit

- Fits the training set extremely well

high variance

Classification

决策边界



$$z = w_1 x_1 + w_2 x_2 + b$$

$$f_{\vec{w},b}(\vec{x}) = g(z)$$

g is the sigmoid function

underfit high bias



$$z = w_1 x_1 + w_2 x_2 + w_3 x_1^2 + w_4 x_2^2 + w_5 x_1 x_2 + b$$

二次项

just right



$$z = w_1 x_1 + w_2 x_2 + w_3 x_1^2 x_2 + w_4 x_1^2 x_2^2 + w_5 x_1^2 x_2^3 + w_6 x_1^3 x_2 + \cdots + b$$

overfit

Stanford
ONLINE

DeepLearning.AI



Regularization to Reduce Overfitting

Addressing Overfitting

Collect more training examples

收集更多训练数据





Select features to include/exclude

不要用那么多多项式特征



all features

+

insufficient data

↓

overfit

selected features

size
bedrooms
age
just right

feature selection

disadvantage

↓

useful features could be lost

course 2

使用直觉使用合适的特

Regularization 正则化.

Reduce the size of parameters w_j



$$f(x) = 28x - 385x^2 + 39x^3 - 174x^4 + 100$$

$-174x^4 \approx 0$

large values for w_j

eliminate feature

尽一个特征为0，消除特征



$$f(x) = 13x - 0.23x^2 + 0.000014x^3 - 0.0001x^4 + 10$$

small values for w_j

小一点的参数数值.

b（正则化b）

Addressing overfitting

Options

1. Collect more data (比较困难)

2. Select features
   - Feature selection in course 2

3. Reduce size of parameters
   - "Regularization" next videos!

Stanford
ONLINE

DeepLearning.AI



Regularization to Reduce Overfitting

Cost Function with Regularization

Intuition

quadratic (二次函数)



$w_1 x + w_2 x^2 + b$



tiny contribution to

$w_1 x + w_2 x^2 + w_3 x^3 + w_4 x^4 + b$

$w_3 \approx 0$ $w_4 \approx 0$ w_3, w_4 趋近于0

make w_3, w_4 really small (≈ 0)

$$\min_{\vec{w},b} \frac{1}{2m} \sum_{i=1}^{m} \left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)^2 + 1000 w_3^2 + 1000 w_4^2$$

$w_3 \approx 0.001$ $w_4 \approx 0.002$

您的模型，如果

Penalize

Regularization

small values $w_1, w_2, \cdots, w_n, b$

simpler model

less likely to overfit

$w_3 \approx 0$

$w_4 \approx 0$

size	bedrooms	floors	age	avg income	...	distance to coffee shop	price
x_1	x_2	x_3	x_4	x_5		x_{100}	y

$w_1, w_1, w_2, \cdots, w_{100}, b$

n features n = 100

一开始没有选特征，所以建立一个包含100个特征的模型

regularization term

$$J(\vec{w}, b) = \frac{1}{2m}\left[\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)^2 + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2 + \frac{\lambda}{2m} b^2\right]$$

一般不惩罚b

can include or exclude b

"lambda"

regularization parameter

$\lambda > 0$

除以2m，

随着m的增大，模型更可以工作

试着减小

Regularization

mse

正则项

mean squared error

regularization term

$$\min_{\vec{w},b} J(\vec{w},b) = \min_{\vec{w},b} \left[\frac{1}{2m} \sum_{i=1}^{m} \left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)} \right)^2 + \frac{\lambda}{2m} \sum_{j=1}^{n} w_j^2 \right]$$

fit data

Keep w_j small

λ balances both goals



choose $\lambda = 10^{10}$

$$f_{\vec{w},b}(\vec{x}) = \underset{\approx 0}{w_1 x} + \underset{\approx 0}{w_2 x^2} + \underset{\approx 0}{w_3 x^3} + \underset{\approx 0}{w_4 x^4} + b$$

$f(x) = b$

Choose λ 很重要

Stanford
ONLINE

DeepLearning.AI



Regularization to Reduce Overfitting

Regularized Linear Regression

Regularized linear regression

$$\min_{\vec{w},b} J(\vec{w},b) = \min_{\vec{w},b}\left[\frac{1}{2m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)^2 + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2\right]$$

Gradient descent

repeat {

$$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(\vec{w},b) \qquad j = 1,\ldots,n$$

$$= \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right) x_j^{(i)} + \frac{\lambda}{m} w_j$$

$$b = b - \alpha \frac{\partial}{\partial b} J(\vec{w},b)$$

$$= \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)$$

don't have to regularize b

} simultaneous update

Implementing gradient descent

repeat {

- $w_j = w_j - \alpha \left[\frac{1}{m} \sum_{i=1}^{m} \left[\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)} \right) x_j^{(i)} \right] + \frac{\lambda}{m} w_j \right]$

$$b = b - \alpha \frac{1}{m} \sum_{i=1}^{m} \left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)} \right)$$

} simultaneous update $j = 1 \ldots n$

Implementing gradient descent

repeat {

$$w_j = w_j - \alpha \left[\frac{1}{m} \sum_{i=1}^{m} \left[\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)} \right) x_j^{(i)} \right] + \frac{\lambda}{m} w_j \right]$$

$$b = b - \alpha \frac{1}{m} \sum_{i=1}^{m} \left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)} \right)$$

} simultaneous update $j = 1 \ldots n$

$$w_j = \underbrace{1 w_j - \alpha \frac{\lambda}{m} w_j}_{w_j \left(1 - \alpha \frac{\lambda}{m}\right)} - \underbrace{\alpha \frac{1}{m} \sum_{i=1}^{m} \left(f_{w,b}(\vec{x}^{(i)}) - y^{(i)} \right) x_j^{(i)}}_{\text{usual update}}$$

shrink w_j 缩放 w_j

$\alpha = 0.01$

$m = 5$

$\alpha \frac{\lambda}{m}$

$0.01 \frac{1}{50} = 0.0002$

$w_j (1 - 0.0002)$

0.9998

How we get the derivative term (optional)

$$\frac{\partial}{\partial w_j} J(\vec{w}, b) = \frac{d}{dw_j}\left[\frac{1}{2m}\sum_{i=1}^{m}\left(\underbrace{f(\vec{x}^{(i)})}_{\vec{w}\cdot\vec{x}^{(i)}+b} - y^{(i)}\right)^2 + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2\right]$$

$$= \frac{1}{2m}\sum_{i=1}^{m}\left[\left(\vec{w}\cdot\vec{x}^{(i)} + b - y^{(i)}\right) 2x_j^{(i)}\right] + \frac{\lambda}{2m} 2w_j \quad \text{No } \sum_{j=1}^{n}$$

$$= \frac{1}{m}\sum_{i=1}^{m}\left[\left(\underbrace{\vec{w}\cdot\vec{x}^{(i)} + b}_{f(\vec{x})} - y^{(i)}\right) x_j^{(i)}\right] + \frac{\lambda}{m} w_j$$

$$= \frac{1}{m}\sum_{i=1}^{m}\left[\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)x_j^{(i)}\right] + \frac{\lambda}{m} w_j$$

Stanford
ONLINE

DeepLearning.AI



Regularization to Reduce Overfitting

Regularized Logistic Regression

Regularized logistic regression



$$z = w_1x_1 + w_2x_2 + w_3x_1^2x_2 + w_4x_1^2x_2^2 + w_5x_1^2x_2^3 + \cdots + b$$

$$f_{\vec{w},b}(\vec{x}) = \frac{1}{1+e^{-z}}$$

$$\frac{1}{1+e^{-wx+b}}$$

Cost function

$$J(\vec{w},b) = -\frac{1}{m}\sum_{i=1}^{m}\left[y^{(i)}\log\left(f_{\vec{w},b}(\vec{x}^{(i)})\right) + (1-y^{(i)})\log\left(1-f_{\vec{w},b}(\vec{x}^{(i)})\right)\right] + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2$$

$$\min_{\vec{w},b} J(\vec{w},b) \rightarrow w_j \downarrow$$

Regularized logistic regression

$$J(\vec{w}, b) = -\frac{1}{m}\sum_{i=1}^{m}\left[y^{(i)}\log\left(f_{\vec{w},b}(\vec{x}^{(i)})\right) + (1-y^{(i)})\log\left(1 - f_{\vec{w},b}(\vec{x}^{(i)})\right)\right] + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2$$

$\min_{\vec{w},b}$

Gradient descent

repeat {

$$w_j = w_j - \alpha\frac{\partial}{\partial w_j}J(\vec{w}, b)$$

$j = 1 \ldots n$

$$b = b - \alpha\frac{\partial}{\partial b}J(\vec{w}, b)$$

}

Looks same as for linear regression!

$$= \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)x_j^{(i)} + \frac{\lambda}{m}w_j$$

logistic regression

$$= \frac{1}{m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)$$

don't have to regularize b

Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

DeepLearning.AI

Stanford
ONLINE



Advanced Learning Algorithms

Welcome!

Advanced learning algorithms

Neural Networks
  inference (prediction)
  training
Practical advice for building machine learning systems
Decision Trees

DeepLearning.AI

Stanford
ONLINE



Neural Networks Intuition

Neurons and the brain

Neural networks

Origins: Algorithms that try to mimic the brain.

Used in the 1980's and early 1990's.
Fell out of favor in the late 1990's.

Resurgence from around 2005.

speech → images → text (NLP) → ...

Neurons in the brain



[Credit: US National Institutes of Health, National Institute on Aging]

Biological neuron

inputs outputs



Simplified mathematical model of a neuron

inputs outputs



image source: https://biologydictionary.net/sensory-neuron/

Why Now?


Faster computer processors
GPUs
large neural network
medium neural network
small neural network
traditional AI
performance
amount of data
Big Data

DeepLearning.AI

Stanford
ONLINE



Neural Network Intuition

Demand Prediction

Demand Prediction



$x = price$ input

$a = f(x) = \frac{1}{1 + e^{-(wx+b)}}$ output

activation

激活



Demand Prediction



Demand Prediction



Demand Prediction

feature engineering

x_1 x_2

神经网络

$\vec{x}$ (x, y)

input layer

price

shipping cost

marketing

material

4 numbers

"hidden layer"

layer ← can have multiple neurons

"activations"

affordability ←

awareness ←

perceived quality ←

$\vec{a}$

layer ← output layer

a

probability of being a top seller

activation values

3 numbers

1 number

Multiple hidden layers



neural network architecture

DeepLearning.AI

Stanford
ONLINE



Neural Networks Intuition

Example:
Recognizing Images

Face recognition

1000 pixels

1000 pixels 像素

1000 columns

1000 rows

197	185	203	...	...
...	57	64	92	...
⋮				
		...	187	214

$\vec{x} =$

197
185
203
⋮
57
64
92
⋮
187
214

1 million

展开成一个

Face recognition



$\vec{x}$
input



source: Convolutional Deep Belief Networks for Scalable Unsupervised Learning of Hierarchical Representations by Honglak Lee, Roger Grosse, Ranganath Andrew Y. Ng

Car classification



source: Convolutional Deep Belief Networks for Scalable Unsupervised Learning of Hierarchical Representations by Honglak Lee, Roger Grosse, Ranganath Andrew Y. Ng

DeepLearning.AI

Stanford
ONLINE



Neural network model

Neural network layer

Neural network layer



Neural network layer



Neural network layer



Neural network layer



DeepLearning.AI

Stanford
ONLINE



Neural Network Model

More complex neural networks

More complex neural network



More complex neural network



Notation



Question:
Can you fill in the superscripts and subscripts for the second neuron?

Notation



$a_2^{[3]} = g(\vec{w}_2^{[3]} \cdot \vec{a}^{[2]} + b_2^{[3]})$

Activation value of layer l, unit(neuron) j

output of layer $l-1$ (previous layer)

$$a_j^{[l]} = g(\vec{w}_j^{[l]} \cdot \vec{a}^{[l-1]} + b_j^{[l]})$$

一个通用的形式

sigmoid "activation function"

Parameters w & b of layer l, unit j

DeepLearning.AI

Stanford
ONLINE



Neural Network Model

Inference: making predictions (forward propagation)

Handwritten digit recognition



Handwritten digit recognition



Handwritten digit recognition

forward propagation



$$\vec{a}^{[3]} = \left[g\left(\vec{w}_1^{[3]} \cdot \vec{a}^{[2]} + b_1^{[3]} \right) \right]$$

is $a_1^{[3]} \geq 0.5$?

yes → $\hat{y} = 1$ image is digit 1

no → $\hat{y} = 0$ image isn't digit 1

multiple perception

DeepLearning.AI

Stanford
ONLINE



TensorFlow implementation

Inference in Code

Coffee roasting






```
x = np.array([[200.0, 17.0]])
layer_1 = Dense(units=3, activation='sigmoid')
a1 = layer_1(x)
```

Build the model using TensorFlow




```
x = np.array([[200.0, 17.0]])
layer_1 = Dense(units=3, activation='sigmoid')
a1 = layer_1(x)
```

```
layer_2 = Dense(units=1, activation='sigmoid')
a2 = layer_2(a1)
```

Build the model using TensorFlow






```
x = np.array([[200.0, 17.0]])
layer_1 = Dense(units=3, activation='sigmoid')
a1 = layer_1(x)
```

```
layer_2 = Dense(units=1, activation='sigmoid')
a2 = layer_2(a1)
```

```
if a2 >= 0.5:
  yhat = 1
else:
  yhat = 0
```

Model for digit classification




```
x = np.array([[0.0,...245,...240...0]])
layer_1 = Dense(units=25, activation='sigmoid')
a1 = layer_1(x)
```

Model for digit classification




```
x = np.array([[0.0,...245,...240...0]])
layer_1 = Dense(units=25, activation='sigmoid')
a1 = layer_1(x)
```

```
layer_2 = Dense(units=15, activation='sigmoid')
a2 = layer_2(a1)
```

Model for digit classification




```
x = np.array([[0.0,...245,...240...0]])
layer_1 = Dense(units=25, activation='sigmoid')
a1 = layer_1(x)

layer_2 = Dense(units=15, activation='sigmoid')
a2 = layer_2(a1)

layer_3 = Dense(units=1, activation='sigmoid')
a3 = layer_3(a2)
```

Model for digit classification




```
x = np.array([[0.0,...245,...240...0]])
layer_1 = Dense(units=25, activation='sigmoid')
a1 = layer_1(x)

layer_2 = Dense(units=15, activation='sigmoid')
a2 = layer_2(a1)

layer_3 = Dense(units=1, activation='sigmoid')
a3 = layer_3(a2)
```

$is\ a_1^{[3]} \geq 0.5?$

$\hat{y} = 1$ ✗ $\hat{y} = 0$ ○

```
if a3 >= 0.5:
  yhat = 1
else:
  yhat = 0
```

DeepLearning.AI

Stanford
ONLINE



TensorFlow implementation

Data in TensorFlow

Feature vectors

temperature (Celsius)	duration (minutes)	Good coffee? (1/0)
200.0	17.0	1
425.0	18.5	0
…	…	…

```
x = np.array([[200.0, 17.0]])
```

```
[[200.0, 17.0]]
```

Why?

Note about numpy arrays




```
x = np.array([[1, 2, 3],
              [4, 5, 6]])
```

```
[[1, 2, 3],
 [4, 5, 6]]
```




```
x = np.array([[0.1, 0.2],
              [-3.0, -4.0,],
              [-0.5, -0.6,],
              [7.0, 8.0,]])
```

```
[[0.1, 0.2],
 [-3.0, -4.0,],
 [-0.5, -0.6,],
 [7.0, 8.0,]]
```

2D array

2 x 3

4 x 2

1 x 2

2 x 1

Note about numpy arrays

```
x = np.array([[200, 17]])
```

$\begin{bmatrix} 200 & 17 \end{bmatrix}$

1 x 2

```
x = np.array([[200],
              [17]])
```

$\begin{bmatrix} 200 \\ 17 \end{bmatrix}$

2 x 1

```
x = np.array([200,17])
```

1D
"Vector"

Feature vectors

temperature (Celsius)	duration (minutes)	Good coffee? (1/0)
200.0	17.0	1
425.0	18.5	0
…	…	…

```
x = np.array([[200.0, 17.0]])
```

```
[[200.0, 17.0]]
```

1 x 2

$$\begin{bmatrix} 200.0 & 17.0 \end{bmatrix}$$

Activation vector




```
x = np.array([[200.0, 17.0]])
layer_1 = Dense(units=3, activation='sigmoid')
a1 = layer_1(x)
```

[0.2, 0.7, 0.3] 1 x 3 matrix

```
tf.Tensor([[0.2 0.7 0.3]], shape=(1, 3), dtype=float32)
```

```
a1.numpy()
```

```
array([[1.4661001, 1.125196 , 3.2159438]], dtype=float32)
```

Activation vector




```
layer_2 = Dense(units=1, activation='sigmoid')
a2 = layer_2(a1)
```

[[0.8]]

1 x 1

```
tf.Tensor([[0.8]], shape=(1, 1), dtype=float32)
```

```
a2.numpy()
```

```
array([[0.8]], dtype=float32)
```

DeepLearning.AI

Stanford
ONLINE



TensorFlow implementation

Building a neural network

What you saw earlier




```
x = np.array([[200.0, 17.0]])
layer_1 = Dense(units=3, activation="sigmoid")
a1 = layer_1(x)

layer_2 = Dense(units=1, activation="sigmoid")
a2 = layer_2(a1)
```

Building a neural network architecture



		y
200	17	1
120	5	0
425	20	0
212	18	1

layer1

```
layer_1 = Dense(units=3, activation="sigmoid")
layer_2 = Dense(units=1, activation="sigmoid")
model = Sequential([layer_1, layer_2])
```

layer2

```
x = np.array([[200.0, 17.0],
              [120.0, 5.0],
              [425.0, 20.0],
              [212.0, 18.0]])
```

4 x 2

targets

```
y = np.array([1,0,0,1])

model.compile(...)
model.fit(x,y)

model.predict(x_new)
```

parameter

more about this next week!

infer.

Digit classification model




```
layer_1 = Dense(units=25, activation="sigmoid")
layer_2 = Dense(units=15, activation="sigmoid")
layer_3 = Dense(units=1, activation="sigmoid")
model = Sequential([layer_1, layer_2, layer_3])
model.compile(...)

x = np.array([[0..., 245, ..., 17],
              [0..., 200, ..., 184]])
y = np.array([1,0])

model.fit(x,y)
model.predict(x_new)
```

more about this next week!

Digit classification model




```
model = Sequential([
    Dense(units=25, activation="sigmoid"),
    Dense(units=15, activation="sigmoid"),
    Dense(units=1, activation="sigmoid")])

model.compile(...)

x = np.array([[0..., 245, ..., 17],
              [0..., 200, ..., 184])
y = np.array([1,0])

model.fit(x,y)

model.predict(x_new)
```

DeepLearning.AI

Stanford
ONLINE



Neural network implementation in Python

Forward prop in a single layer

forward prop (coffee roasting model)



$a_1^{[2]} = g(\vec{w}_1^{[2]} \cdot \vec{a}^{[1]} + b_1^{[2]})$

```
w2_1 = np.array([-7, 8])
b2_1 = np.array([3])
z2_1 = np.dot(w2_1,a1)+b2_1
a2_1 = sigmoid(z1_1)
```

$w_1^{[2]}$ w2_1

```
x = np.array([200, 17])
```

1D arrays

$a_1^{[1]} = g(\vec{w}_1^{[1]} \cdot \vec{x} + b_1^{[1]})$ $a_2^{[1]} = g(\vec{w}_2^{[1]} \cdot \vec{x} + b_2^{[1]})$ $a_3^{[1]} = g(\vec{w}_3^{[1]} \cdot \vec{x} + b_3^{[1]})$

以2的维度

```
w1_1 = np.array([1, 2])      w1_2 = np.array([-3, 4])     w1_3 = np.array([5, -6])
b1_1 = np.array([-1])        b1_2 = np.array([1])         b1_3 = np.array([2])
z1_1 = np.dot(w1_1,x)+ b     z1_2 = np.dot(w1_2,x)+b      z1_3 = np.dot(w1_3,x)+b
a1_1 = sigmoid(z1_1)         a1_2 = sigmoid(z1_2)         a1_3 = sigmoid(z1_3)

a1   = np.array([a1_1, a1_2, a1_3])
```

DeepLearning.AI

Stanford
ONLINE



Neural network implemenation in Python

General implementation of forward propagation

Forward prop in NumPy



$\vec{w}_1^{[1]} = \begin{bmatrix} 1 \\ 2 \end{bmatrix}$ $\vec{w}_2^{[1]} = \begin{bmatrix} -3 \\ 4 \end{bmatrix}$ $\vec{w}_3^{[1]} = \begin{bmatrix} 5 \\ -6 \end{bmatrix}$

```
W = np.array([
    [1, -3, 5]
    [2, 4, -6]])
```
2 by 3

$b_1^{[1]} = -1 \quad b_2^{[1]} = 1 \quad b_3^{[1]} = 2$

```
b = np.array([-1, 1, 2])
```

$\vec{a}^{[0]} = \vec{x}$

```
a_in = np.array([-2, 4])
```
1×2 × 2×1

定义了 forward

```
def dense(a_in,W,b, g):
    units = W.shape[1]
    a_out = np.zeros(units)
    for j in range(units):
        w = W[:,j]
        z = np.dot(w,a_in) + b[j]
        a_out[j] = g(z)
    return a_out
```
3 多少列 [0,0,0] 0,1,2

搭建 framework

$a^{[1]}$ $a^{[2]}$

```
def sequential(x):
    a1 = dense(x,W1,b1,g)
    a2 = dense(a1,W2,b2,g)
    a3 = dense(a2,W3,b3,g)
    a4 = dense(a3,W4,b4,g)
    f_x = a4
    return f_x
```

capital W refers to a matrix

DeepLearning.AI

Stanford
ONLINE



Speculations on artificial general intelligence (AGI)

Is there a path to AGI?


AI
ANI
(artificial narrow intelligence)
E.g., smart speaker,
self-driving car, web search,
AI in farming and factories
AGI
(artificial general intelligence)
Do anything a human can do

Biological neuron

inputs outputs



Simplified mathematical model of a neuron

inputs outputs



image source: https://biologydictionary.net/sensory-neuron/

Neural network and the brain

Can we mimic the human brain?



vs



We have (almost) no idea how the brain works

The ”one learning algorithm” hypothesis



[Roe et al., 1992]

The ”one learning algorithm” hypothesis



[Metin & Frost, 1989]

Sensor representations in the brain

Seeing with your tongue

Human echolocation (sonar)

Haptic belt: Direction sense

Implanting a 3rd eye

[BrainPort; Welsh & Blasch, 1997; Nagel et al., 2005; Constantine-Paton & Law, 2009]

DeepLearning.AI

Stanford
ONLINE



Vectorization (optional)

How neural networks are implemented efficiently

For loops vs. vectorization

```
x = np.array([200, 17])

W = np.array([[1, -3, 5],
              [-2, 4, -6]])

b = np.array([-1, 1, 2])

def dense(a_in,W,b):
    a_out = np.zeros(units)
    for j in range(units):
      w = W[:,j]
      z = np.dot(w,x) + b[j]
      a[j] = g(z)
  return a
```

forward propagation

```
[1,0,1]
```

Vectorized

```
X = np.array([[200, 17]])

W = np.array([[1, -3, 5],
              [-2, 4, -6]])

B = np.array([[-1, 1, 2]])

def dense(A_in,W,B):
    Z = np.matmul(A_in,W) + B
    A_out = g(Z)
    return A_out

[[1,0,1]]
```

2D array

same

1x3 2D array

all 2D arrays

matrix multiplication

numpy里面矩阵乘法的写法

DeepLearning.AI

Stanford
ONLINE



Vectorization (optional)

Matrix multiplication

Dot products

example

$\begin{bmatrix}1\\2\end{bmatrix} \cdot \begin{bmatrix}3\\4\end{bmatrix}$

$z = (1 \times 3) + (2 \times 4)$

$3 + 8$

11

in general

$\begin{bmatrix}\uparrow\\ \vec{a} \\ \downarrow\end{bmatrix} \cdot \begin{bmatrix}\uparrow\\ \vec{w} \\ \downarrow\end{bmatrix}$

$z = \vec{a} \cdot \vec{w}$

transpose

$\vec{a} = \begin{bmatrix}1\\2\end{bmatrix}$

$\vec{a}^T = [1 \quad 2]$

vector vector multiplication

$[\leftarrow \ \vec{a}^T \ \rightarrow] \begin{bmatrix}\uparrow\\ \vec{w} \\ \downarrow\end{bmatrix}$

$1 \times 2 \qquad 2 \times 1$

$z = \vec{a}^T \vec{w}$

equivalent

useful for understanding matrix multiplication

Vector matrix multiplication

$$\vec{a} = \begin{bmatrix} 1 \\ 2 \end{bmatrix} \qquad \vec{a}^T = \begin{bmatrix} 1 & 2 \end{bmatrix} \qquad W = \begin{bmatrix} 3 & 5 \\ 4 & 6 \end{bmatrix}$$

$$Z = \vec{a}^T W \quad \begin{bmatrix} \leftarrow & \vec{a}^T & \rightarrow \end{bmatrix} \begin{bmatrix} \uparrow & \uparrow \\ \vec{w}_1 & \vec{w}_2 \\ \downarrow & \downarrow \end{bmatrix}$$

1 by 2

$$Z = \begin{bmatrix} \vec{a}^T \vec{w}_1 & a^T \vec{w}_2 \end{bmatrix}$$

$$(1 * 3) + (2 * 4) \qquad (1 * 5) + (2 * 6)$$

$3 + 8$ $\quad$ $5 + 12$

11 $\quad$ 17

$$Z = [11 \quad 17]$$

matrix matrix multiplication

$$A = \begin{bmatrix} 1 & -1 \\ 2 & -2 \end{bmatrix} \quad A^T = \begin{bmatrix} 1 & 2 \\ -1 & -2 \end{bmatrix} \quad W = \begin{bmatrix} 3 & 5 \\ 4 & 6 \end{bmatrix} \quad Z = A^T W = \begin{bmatrix} \leftarrow & \vec{a}_1^T & \rightarrow \\ \leftarrow & \vec{a}_2^T & \rightarrow \end{bmatrix} \begin{bmatrix} \uparrow & \uparrow \\ \vec{w}_1 & \vec{w}_2 \\ \downarrow & \downarrow \end{bmatrix}$$

rows

columns

$$= \begin{bmatrix} \vec{a}_1^T \vec{w}_1 & \vec{a}_1^T \vec{w}_2 \\ \vec{a}_2^T \vec{w}_1 & \vec{a}_2^T \vec{w}_2 \end{bmatrix}$$

row 1 col 1

row 2 col 1

row 1 col 2

row 2 col 2

$(-1 \times 3) + (-2 \times 4)$

$-3 + -8$

-11

$(-1 \times 5) + (-2 \times 6)$

$-5 + -12$

-17

$$= \begin{bmatrix} 11 & 17 \\ -11 & -17 \end{bmatrix}$$

general rules for matrix multiplication
↳ next video!

DeepLearning.AI

Stanford
ONLINE



Vectorization (optional)

Matrix multiplication rules

Matrix multiplication rules

$$\mathbf{A} = \begin{bmatrix} 1 & -1 & 0.1 \\ 2 & -2 & 0.2 \end{bmatrix} \quad \mathbf{A}^T = \begin{bmatrix} 1 & 2 \\ -1 & -2 \\ 0.1 & 0.2 \end{bmatrix} \quad \mathbf{W} = \begin{bmatrix} 3 & 5 & 7 & 9 \\ 4 & 6 & 8 & 0 \end{bmatrix}$$

$\vec{a}_1^T$ $\vec{a}_2^T$ $\vec{a}_3^T$

$\vec{w}_1$ $\vec{w}_2$ $\vec{w}_3$ $\vec{w}_4$

$$Z = \mathbf{A}^T\mathbf{W} = \begin{bmatrix} & & & \\ & & & \\ & & & \end{bmatrix}$$

Matrix multiplication rules

$$A = \begin{bmatrix} 1 & -1 & 0.1 \\ 2 & -2 & 0.2 \end{bmatrix} \quad A^T = \begin{bmatrix} 1 & 2 \\ -1 & -2 \\ 0.1 & 0.2 \end{bmatrix} \quad W = \begin{bmatrix} 3 & 5 & 7 & 9 \\ 4 & 6 & 8 & 0 \end{bmatrix} \quad Z = A^T W = \begin{bmatrix} & & & \\ & & & \\ & & & \end{bmatrix}$$

3 by 4 matrix

$$\vec{a}_1^T \vec{w}_1 = (1 \times 3) + (2 \times 4) = 11$$

row 3 column 2

$$\vec{a}_3^T \vec{w}_2 = (0.1 \times 5) + (0.2 \times 6) = 1.7$$

0.5 + 1.2

row 2 column 3?

$$\vec{a}_2^T \vec{w}_3 = (-1 \times 7) + (-2 + 8) = -23$$

-7 + -16

Matrix multiplication rules

$$A = \begin{bmatrix} 1 & -1 & 0.1 \\ 2 & -2 & 0.2 \end{bmatrix} \quad A^T = \begin{bmatrix} 1 & 2 \\ -1 & -2 \\ 0.1 & 0.2 \end{bmatrix} \quad W = \begin{bmatrix} 3 & 5 & 7 & 9 \\ 4 & 6 & 8 & 0 \end{bmatrix} \quad Z = A^T W = \begin{bmatrix} 11 & 17 & 23 & 9 \\ -11 & -17 & -23 & -9 \\ 1.1 & 1.7 & 2.3 & 0.9 \end{bmatrix}$$

3 by 4 matrix

$\vec{a}_1^T \vec{w}_1 = (1 \times 3) + (2 \times 4) = 11$

row 3 column 2

$\vec{a}_3^T \vec{w}_2 = (0.1 \times 5) + (0.2 \times 6) = 1.7$

$0.5 + 1.2$

row 2 column 3?

$\vec{a}_2^T \vec{w}_3 = (-1 \times 7) + (-2 + 8) = -23$

$-7 + -16$

Matrix multiplication rules

$$\mathbf{A} = \begin{bmatrix} 1 & -1 & 0.1 \\ 2 & -2 & 0.2 \end{bmatrix} \quad \mathbf{A}^T = \begin{bmatrix} 1 & 2 \\ -1 & -2 \\ 0.1 & 0.2 \end{bmatrix} \quad \mathbf{W} = \begin{bmatrix} 3 & 5 & 7 & 9 \\ 4 & 6 & 8 & 0 \end{bmatrix} \quad \mathbf{Z} = \mathbf{A}^T\mathbf{W} = \begin{bmatrix} 11 & 17 & 23 & 9 \\ -11 & -17 & -23 & -9 \\ 1.1 & 1.7 & 2.3 & 0.9 \end{bmatrix}$$

3 x 2 2 x 4

can only take dot products of vectors that are same length

[0.1 0.2] length 2

$\begin{bmatrix} 5 \\ 6 \end{bmatrix}$ length 2

3 by 4 matrix

↳ same # rows as A^T

same # columns as W

DeepLearning.AI

Stanford
ONLINE



Vectorization (optional)

Matrix multiplication code

Matrix multiplication in NumPy

$$A = \begin{bmatrix} 1 & -1 & 0.1 \\ 2 & -2 & 0.2 \end{bmatrix} \quad A^T = \begin{bmatrix} 1 & 2 \\ -1 & -2 \\ 0.1 & 0.2 \end{bmatrix} \quad W = \begin{bmatrix} 3 & 5 & 7 & 9 \\ 4 & 6 & 8 & 0 \end{bmatrix} \quad Z = A^T W = \begin{bmatrix} 11 & 17 & 23 & 9 \\ -11 & -17 & -23 & -9 \\ 1.1 & 1.7 & 2.3 & 0.9 \end{bmatrix}$$

```
A=np.array([1,-1,0.1],
           [2,-2,0.2]])
```

```
W=np.array([3,5,7,9],
           [4,6,8,0])
```

```
Z = np.matmul(AT,W)
```

or

```
Z = AT @ W
```

```
AT=np.array([1,2],
            [-1,-2],
            [0.1,0.2])
```

result

```
[[11,17,23,9],
 [-11,-17,-23,-9],
 [1.1,1.7,2.3,0.9]
]
```

```
AT=A.T
```

transpose

Dense layer vectorized



$$\mathbf{A}^T = [200 \quad 17] \qquad 1 \times 2$$

$$\mathbf{W} = \begin{bmatrix} 1 & -3 & 5 \\ -2 & 4 & -6 \end{bmatrix} \qquad 2 \times 3$$

$$\vec{\mathbf{b}} = [-1 \quad 1 \quad 2] \qquad 1 \times 3$$

$$\mathbf{Z} = \mathbf{A}^T\mathbf{W} + \mathbf{B}$$

$$[165 \quad -531 \quad 900]$$

$$z_1^{[1]} \quad z_2^{[1]} \quad z_3^{[1]}$$

$$\mathbf{A} = g(\mathbf{Z})$$

$$[1 \quad 0 \quad 1]$$

A

```
AT = np.array([[200, 17]])
W = np.array([[1, -3, 5],
              [-2, 4, -6]])
b = np.array([[-1, 1, 2]])
```

a_in

```
def dense(AT,W,b,g):
  z = np.matmul(AT,W) + b
  a_out = g(z)
  return a_out
```

a_in

```
[[1,0,1]]
```

Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

Neural Network Training

TensorFlow implementation

Train a Neural Network in TensorFlow



Given set of (x,y) examples

How to build and train this in code?

```
import tensorflow as tf
from tensorflow.keras import Sequential
from tensorflow.keras.layers import Dense
   model = Sequential([
     Dense(units=25, activation='sigmoid')
     Dense(units=15, activation='sigmoid')
     Dense(units=1, activation='sigmoid')
                              )]
from tensorflow.keras.losses import
BinaryCrossentropy
   model.compile(loss=BinaryCrossentropy())

   model.fit(X,Y,epochs=100)
```

epochs: number of steps in gradient descent

Neural Network Training

Training Details

Model Training Steps

TensorFlow

1. specify how to compute output given input x and parameters w,b (define model)

   $f_{\vec{w},b}(\vec{x})$ =?

2. specify loss and cost

   $L\left(f_{\vec{w},b}(\vec{x}), y\right)$ 1 example

   $J(\vec{w}, b) = \frac{1}{m}\sum_{i=1}^{m} L\left(f_{\vec{w},b}(\vec{x}^{(i)}), y^{(i)}\right)$

3. Train on data to minimize $J(\vec{w}, b)$

logistic regression

```
z = np.dot(w,x) + b

f_x = 1/(1+np.exp(-z))
```

logistic loss

```
loss = -y * np.log(f_x)
   -(1-y) * np.log(1-f_x)
```

梯度下降

```
w = w - alpha * dj_dw
b = b - alpha * dj_db
```

neural network

```
model = Sequential([
          Dense(...)
          Dense(...)
          Dense(...)
                    ])
```

binary cross entropy

```
model.compile(
loss=BinaryCrossentropy())
```

二元交叉熵

```
model.fit(X,y,epochs=100)
```

1. Create the model

define the model

$f(\vec{x}) = ?$




```
import tensorflow as tf
from tensorflow.keras import Sequential
from tensorflow.keras.layers import Dense

model = Sequential([
  Dense(units=25, activation='sigmoid')
  Dense(units=15, activation='sigmoid')
  Dense(units=1, activation='sigmoid')
                    ])
```

2. Loss and cost functions

Mnist digit classification problem — binary classification

$$L(f(\vec{x}), y) = -y\log(f(\vec{x})) - (1-y)\log(1-f(\vec{x}))$$

Compare prediction vs. target

logistic loss

also known as binary cross entropy

$$J(\mathbf{W}, \mathbf{B}) = \frac{1}{m}\sum_{i=1}^{m} L(f(\vec{x}^{(i)}), y^{(i)})$$

$\mathbf{W}^{[1]}, \mathbf{W}^{[2]}, \mathbf{W}^{[3]}$ $\vec{b}^{[1]}, \vec{b}^{[2]}, \vec{b}^{[3]}$

都是 vector

$f_{\mathbf{W},\mathbf{B}}(\vec{x})$

```
model.compile(loss= BinaryCrossentropy())
```

```
from tensorflow.keras.losses import
  BinaryCrossentropy
```

Keras

regression (predicting numbers and not categories)

mean squared error

```
model.compile(loss= MeanSquaredError())
```

回归我学用 MSE

```
from tensorflow.keras.losses import
  MeanSquaredError
```

3. Gradient descent



repeat {

$$w_j^{[l]} = w_j^{[l]} - \alpha \frac{\partial}{\partial w_j} J(\vec{w}, b)$$

$$b_j^{[l]} = b_j^{[l]} - \alpha \frac{\partial}{\partial b} J(\vec{w}, b)$$

}

Compute derivatives for gradient descent using "back propagation"

```
model.fit(X,y,epochs=100)
```

Neural network libraries

Use code libraries instead of coding ”from scratch”

Good to understand the implementation
(for tuning and debugging).

Activation Functions

Alternatives to the sigmoid activation

Demand Prediction Example



$$a_2^{[1]} = g(\vec{w}_2^{[1]} \cdot \vec{x} + b_2^{[1]}) \quad (z)$$

Sigmoid



$0 < g(z) < 1$

ReLU Rectified Linear Unit



if $z < 0$, $g(z)$ is 0

if $z \geq 0$, $g(z)$ is z

Examples of Activation Functions

"No activation function"

Linear activation function



$a = g(z) = \vec{w} \cdot \vec{x} + b$ (z)

$a_2^{[1]} = g(\vec{w}_2^{[1]} \cdot \vec{x} + b_2^{[1]})$ (z)

Sigmoid



$0 < g(z) < 1$

Later: softmax activation

ReLU Rectified Linear Unit



Activation Functions

Choosing activation functions

Output Layer



Choosing $g(z)$ for output layer?

Binary classification
Sigmoid
y=0/1



Regression
Linear activation function
y = +/-



Regression
ReLU
Y = 0 or +



Hidden Layer



Choosing $g(z)$ for hidden layer

Sigmoid





most common choice

ReLU

faster (更快)



Choosing Activation Summary



ReLU hidden layers 用 ReLu

binary classification
activation='sigmoid'

regression y negative/positive
activation='linear'

regression $y \geq 0$
activation='relu'

在最后一个 output layer

```
from tf.keras.layers import Dense
model = Sequential([
  Dense(units=25, activation='relu'),
  Dense(units=15, activation='relu'),
  Dense(units=1,  activation='sigmoid')
])
```

layer1, layer2 } hidden layer
layer3 output layer

or 'linear'
or 'relu'

Activation Functions

Why do we need activation functions?

Why do we need activation functions?





if all $g(z)$ are linear...



...no different than linear regression

Linear Example



$g(z) = z$

假设没有做注意力

$$a^{[1]} = w_1^{[1]} x + b_1^{[1]}$$

$$a^{[2]} = w_1^{[2]} a^{[1]} + b_1^{[2]}$$

$$= w_1^{[2]} (w_1^{[1]} x + b_1^{[1]}) + b_1^{[2]}$$

$$\vec{a}^{[2]} = (\underbrace{\vec{w}_1^{[2]} \vec{w}_1^{[1]}}_{w}) x + \underbrace{w_1^{[2]} b_1^{[1]} + b_1^{[2]}}_{b}$$

$$\vec{a}^{[2]} = w x + b$$

$f(x) = wx + b$ linear regression

Example



$g(z) = z$

$$\vec{a}^{[4]} = \vec{w}_1^{[4]} \cdot \vec{a}^{[3]} + b_1^{[4]}$$

all linear (including output)
↳ equivalent to linear regression

$$\vec{a}^{[4]} = \frac{1}{1+e^{-(\vec{w}_1^{[4]} \cdot \vec{a}^{[3]} + b_1^{[4]})}}$$

output activation is sigmoid
(hidden layers still linear)
↳ equivalent to logistic regression

因为多个线性关起来，
还原单个层没区别了。
变了模型就相当于logistic回归
一个

Don't use linear activations in hidden layers (use ReLU)

Multiclass Classification

Multiclass

MNIST example



$y = 0$ 1 2 3 4 5 6 7 8 9

$y = 7$

multiclass classification problem:
target y can take on more than two possible values

Multiclass classification example





Multiclass Classification

Softmax

Logistic regression
(2 possible output values)

$z = \vec{w} \cdot \vec{x} + b$

$a_1 = g(z) = \frac{1}{1+e^{-z}} = P(y=1|\vec{x})$ 0.71

$a_2 = 1 - a_1 = P(y=0|\vec{x})$ 0.29

Softmax regression
(N possible outputs) $y = 1, 2, 3, \ldots, N$

$z_j = \vec{w}_j \cdot \vec{x} + b_j \quad j = 1, \ldots, N$

parameters $w_1, w_2, \ldots, w_N$ $b_1, b_2, \ldots, b_N$

$$a_j = \frac{e^{z_j}}{\sum_{k=1}^{N} e^{z_k}} = P(y=j|\vec{x})$$

Note: $a_1 + a_2 + \ldots + a_N = 1$

Softmax regression (4 possible outputs) $y = 1, 2, 3, 4$

$z_1 = \vec{w}_1 \cdot \vec{x} + b_1$

$$a_1 = \frac{e^{z_1}}{e^{z_1} + e^{z_2} + e^{z_3} + e^{z_4}} = P(y=1|\vec{x})$$ 0.30

$z_2 = \vec{w}_2 \cdot \vec{x} + b_2$

$$a_2 = \frac{e^{z_2}}{e^{z_1} + e^{z_2} + e^{z_3} + e^{z_4}} = P(y=2|\vec{x})$$ 0.20

$z_3 = \vec{w}_3 \cdot \vec{x} + b_3$

$$a_3 = \frac{e^{z_3}}{e^{z_1} + e^{z_2} + e^{z_3} + e^{z_4}} = P(y=3|\vec{x})$$ 0.15

$z_4 = \vec{w}_4 \cdot \vec{x} + b_4$

$$a_4 = \frac{e^{z_4}}{e^{z_1} + e^{z_2} + e^{z_3} + e^{z_4}} = P(y=4|\vec{x})$$ 0.35

Cost

Logistic regression

$$z = \vec{w} \cdot \vec{x} + b$$

$$a_1 = g(z) = \frac{1}{1 + e^{-z}} = P(y = 1|\vec{x})$$

$$a_2 = 1 - a_1 = P(y = 0|\vec{x})$$

$$loss = -y \log a_1 - (1 - y) \log(1 - a_1)$$

if $y = 1$ if $y = 0$

$$J(\vec{w}, b) = \text{average loss}$$

Softmax regression

$$a_1 = \frac{e^{z_1}}{e^{z_1} + e^{z_2} + \cdots + e^{z_N}} = P(y = 1|\vec{x})$$

$$\vdots$$

$$a_N = \frac{e^{z_N}}{e^{z_1} + e^{z_2} + \cdots + e^{z_N}} = P(y = N|\vec{x})$$

Crossentropy loss

$$loss(a_1, \ldots, a_N, y) = \begin{cases} -\log a_1 & \text{if } y = 1 \\ -\log a_2 & \text{if } y = 2 \\ \vdots & \\ -\log a_N & \text{if } y = N \end{cases}$$



Multiclass Classification

Neural Network with Softmax output

Neural Network with Softmax output



$$z_1 = \vec{w}_1 \cdot \vec{a}^{[2]} + b_1 \qquad a_1 = \frac{e^{z_1}}{e^{z_1} + \cdots + e^{z_{10}}} = P(y = 1|\vec{x})$$

$$\vdots$$

$$z_{10} = \vec{w}_{10} \cdot \vec{a}^{[2]} + b_{10} \qquad a_{10} = \frac{e^{z_{10}}{e^{z_1} + \cdots + e^{z_{10}}} = P(y = 10|\vec{x})$$

logistic regression

$$a_1^{[3]} = g\left(z_1^{[3]}\right) \quad a_2^{[3]} = g\left(z_2^{[3]}\right)$$

softmax

$$\vec{a}^{[3]} = \left(a_1^{[3]}, \ldots a_{10}^{[3]}\right) = g\left(z_1^{[3]}, \ldots, z_{10}^{[3]}\right)$$

hidden layer 用 ReLu
output layer 用 softmax

MNIST with softmax

1. specify the model

$f_{\vec{w},b}(\vec{x})$ =?

2. specify loss and cost

$L\left(f_{\vec{w},b}(\vec{x}), y\right)$

3. Train on data to minimize $J(\vec{w}, b)$

```
import tensorflow as tf
from tensorflow.keras import Sequential
from tensorflow.keras.layers import Dense
model = Sequential([
  Dense(units=25, activation='relu')
  Dense(units=15, activation='relu')
  Dense(units=10, activation='softmax')
                  )]
from tensorflow.keras.losses import
  SparseCategoricalCrossentropy
model.compile(loss= SparseCategoricalCrossentropy() )
model.fit(X,Y,epochs=100)
```

稀疏类别交叉熵

Note: better (recommended) version later.

Don't use the version shown here!

Multiclass Classification

Improved implementation of softmax

Numerical Roundoff Errors

option 1

$$x = \frac{2}{10{,}000}$$

option 2

$$x = \left(1 + \frac{1}{10{,}000}\right) - \left(1 - \frac{1}{10{,}000}\right) =$$

Numerical Roundoff Errors

More numerically accurate implementation of logistic loss:

Logistic regression:

$$a = g(z) = \frac{1}{1+e^{-z}}$$

Original loss

$$loss = -y\log(a) - (1-y)\log(1-a)$$

More accurate loss (in code)

$$loss = -y\log\left(\frac{1}{1+e^{-z}}\right) - (1-y)\log(1-\frac{1}{1+e^{-z}})$$

```
model = Sequential([
    Dense(units=25, activation='relu')
    Dense(units=15, activation='relu')
    Dense(units=10, activation='sigmoid')
])
model.compile(loss=BinaryCrossEntropy() )
```

```
model.compile(loss=BinaryCrossEntropy(from_logits=True) )
```

More numerically accurate implementation of softmax

Softmax regression

$$(a_1, \ldots, a_{10}) = g(z_1, \ldots, z_{10})$$

$$\text{Loss} = L(\vec{a}, y) = \begin{cases} -\log a_1 & \text{if } y = 1 \\ \vdots & \\ -\log a_{10} & \text{if } y = 10 \end{cases}$$

```
model = Sequential([
  Dense(units=25, activation='relu')
  Dense(units=15, activation='relu')
  Dense(units=10, activation='softmax')
```

'linear'

```
model.compile(loss=SparseCategoricalCrossEntropy() )
```

More Accurate

$$L(\vec{a}, y) = \begin{cases} -\log \dfrac{e^{z_1}}{e^{z_1} + \cdots + e^{z_{10}}} & \text{if } y = 1 \\ \vdots & \\ -\log \dfrac{e^{z_{10}}{e^{z_1} + \cdots + e^{z_{10}}} & \text{if } y = 10 \end{cases}$$

四舍五入一次比分别计算几次(如此次四舍五入)更精确

```
model.compile(loss=SparseCrossEntropy(from_logits=True) )
```

MNIST (more numerically accurate)

model

```
import tensorflow as tf
from tensorflow.keras import Sequential
from tensorflow.keras.layers import Dense
model = Sequential([
  Dense(units=25, activation='relu')
  Dense(units=15, activation='relu')
  Dense(units=10, activation='linear') )]
```

loss

```
from tensorflow.keras.losses import
  SparseCategoricalCrossentropy
model.compile(...,loss=SparseCategoricalCrossentropy(from_logits=True) )
```

fit

```
model.fit(X,Y,epochs=100)
```

predict

```
logits = model(X)
f_x = tf.nn.softmax(logits)
```

not is $a_1 \dots a_{10}$ $z_1 \dots z_{10}$ 输出是z，激活后是a.

logistic regression (more numerically accurate)

model

```
model = Sequential([
  Dense(units=25, activation='sigmoid')
  Dense(units=15, activation='sigmoid')
  Dense(units=1, activation='linear')
from tensorflow.keras.losses import
  BinaryCrossentropy
```

loss

```
model.compile(..., BinaryCrossentropy(from_logits=True)) )
```

```
model.fit(X,Y,epochs=100)
```

fit

```
logit = model(X)
```

predict

```
f_x = tf.nn.sigmoid(logit)
```

Multi-label Classification

Classification with multiple outputs (Optional)

Multi-label Classification

x

Is there a car?
Is there a bus?
Is there a pedestrian

yes
no
yes

$y = \begin{bmatrix} 1 \\ 0 \\ 1 \end{bmatrix}$

no
no
yes

$y = \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix}$

yes
yes
no

$y = \begin{bmatrix} 1 \\ 1 \\ 0 \end{bmatrix}$

Multiple classes



Alternatively, train one neural network with three outputs



$$\vec{a}^{[3]} = \begin{bmatrix} a_1^{[3]} \\ a_2^{[3]} \\ a_3^{[3]} \end{bmatrix}$$

car
bus
pedestrian

Additional Neural Network Concepts

Advanced Optimization

Gradient Descent

$$w_j = w_j - \alpha \frac{\partial}{\partial w_j} J(\vec{w}, b)$$

learning rate



Go faster – increase α



Go slower – decrease α

Adam Algorithm Intuition

为不同参数用不同的 α.

Adam: Adaptive Moment estimation

not just one α

$$w_1 = w_1 - \alpha_1 \frac{\partial}{\partial w_1} J(\vec{w}, b)$$
$$\vdots$$
$$w_{10} = w_{10} - \alpha_{10} \frac{\partial}{\partial w_{10}} J(\vec{w}, b)$$
$$b = b - \alpha_{11} \frac{\partial}{\partial b} J(\vec{w}, b)$$

Adam Algorithm Intuition



If w_j (or b) keeps moving in same direction, increase α_j.

在大致相同的方向下降，则加速



If w_j (or b) keeps oscillating, reduce α_j.

振荡

MNIST Adam

model

```
model = Sequential([
        tf.keras.layers.Dense(units=25, activation='sigmoid')
        tf.keras.layers.Dense(units=15, activation='sigmoid')
        tf.keras.layers.Dense(units=10, activation='linear')
])
```

compile

$\alpha = 10^{-3} = 0.001$

```
model.compile(optimizer=tf.keras.optimizers.Adam(learning_rate=1e-3),
  loss=tf.keras.losses.SparseCategoricalCrossentropy(from_logits=True))
```

fit

```
model.fit(X,Y,epochs=100)
```

Additional Neural Network Concepts

dense layer 全连接层

Additional Layer Types

Dense Layer



Each neuron output is a function of all the activation outputs of the previous layer.

$$\vec{a}_1^{[2]} = g\left(\vec{w}_1^{[2]} \cdot \vec{a}^{[1]} + b_1^{[2]}\right)$$

Convolutional Layer





Each Neuron only looks at part of the previous layer's inputs.

Why?

- Faster computation
- Need less training data (less prone to overfitting)

Convolutional Neural Network



Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

Advice for applying machine learning

Deciding what to try next

Debugging a learning algorithm

You've implemented regularized linear regression on housing prices

$$J(\vec{w}, b) = \frac{1}{2m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)^2 + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2$$

But it makes unacceptably large errors in predictions. What do you try next?

- Get more training examples
- Try smaller sets of features
- Try getting additional features
- Try adding polynomial features $(x_1^2, x_2^2, x_1x_2, etc)$
- Try decreasing λ
- Try increasing λ

Machine learning diagnostic

Diagnostic: A test that you run to gain insight into what is/isn't working with a learning algorithm, to gain guidance into improving its performance.

Diagnostics can take time to implement but doing so can be a very good use of your time.

Evaluating and
choosing models

Evaluating a model

Evaluating your model



→ Model fits the training data well but will fail to generalize to new examples not in the training set.

$x = x_1$

$f_{\vec{w},b}(\vec{x}) = w_1 x + w_2 x^2 + \cdots + w_n x^n + b$

$w_n x^4$

just x

- → x_1 = size in feet^2
- → x_2 = no. of bedrooms
- → x_3 = no. of floors
- → x_4 = age of home in years

$f(\vec{x})$

Evaluating your model

Dataset:

	size	price
70%	2104	400
	1600	330
	2400	369
	1416	232
	3000	540
	1985	300
	1534	315
30%	1427	199
	1380	212
	1494	243

training set

test set

$(x^{(1)}, y^{(1)})$
$(x^{(2)}, y^{(2)})$
$\vdots$
$(x^{(m_{train})}, y^{m_{train}})$

m_{train} = no. training examples = 7

$(x_{test}^{(1)}, y_{test}^{(1)})$
$\vdots$
$(x_{test}^{(m_{test})}, y_{test}^{(m_{test})})$

m_{test} = no. test examples = 3

Train/test procedure for linear regression (with squared error cost)

Fit parameters by minimizing cost function $J(\vec{w}, b)$

$$J(\vec{w}, b) = \min_{\vec{w}, b} \left[\frac{1}{2m_{train}} \sum_{i=1}^{m_{train}} \left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)} \right)^2 + \frac{\lambda}{2m_{train}} \sum_{j=1}^{n} w_j^2 \right]$$

Compute test error:

$$J_{test}(\vec{w}, b) = \frac{1}{2m_{test}} \left[\sum_{i=1}^{m_{test}} \left(f_{\vec{w},b}(\vec{x}^{(i)}_{test}) - y^{(i)}_{test} \right)^2 \right]$$

Compute training error:

$$J_{train}(\vec{w}, b) = \frac{1}{2m_{train}} \left[\sum_{i=1}^{m_{train}} \left(f_{\vec{w},b}(\vec{x}^{(i)}_{train}) - y^{(i)}_{train} \right)^2 \right]$$

Train/test procedure for linear regression (with squared error cost)

Fit parameters

$J(\vec{w}, b) = \min_{\vec{w}, b}$

Compute test e

J_t

Compute traini

J_t



$b)$

$\frac{1}{ain}\left[\sum_{j=1}^{n} w_j^2\right]$

$\left(i\right)_{est}\Big)^2\Big]$ + $\sum w^2$

$-\ y_{train}^{(i)}\Big)^2\Big]$

Train/test procedure for classification problem

0/1

Fit parameters by minimizing $J(\vec{w}, b)$ to find $\vec{w}, b$

E.g.,

$$J(\vec{w}, b) = -\frac{1}{m}\sum_{i=1}^{m}\left[y^{(i)}\log\left(f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right) + \left(1-y^{(i)}\right)\log\left(1-f_{\vec{w},b}\left(\vec{x}^{(i)}\right)\right)\right] + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2$$

Compute test error:

$$J_{test}(\vec{w}, b) = -\frac{1}{m_{test}}\sum_{i=1}^{m_{test}}\left[y_{test}^{(i)}\log\left(f_{\vec{w},b}\left(\vec{x}_{test}^{(i)}\right)\right) + \left(1-y_{test}^{(i)}\right)\log\left(1-f_{\vec{w},b}\left(\vec{x}_{test}^{(i)}\right)\right)\right]$$

Compute train error:

$$J_{train}(\vec{w}, b) = -\frac{1}{m_{train}}\sum_{i=1}^{m_{train}}\left[y_{train}^{(i)}\log\left(f_{\vec{w},b}\left(\vec{x}_{train}^{(i)}\right)\right) + \left(1-y_{train}^{(i)}\right)\log\left(1-f_{\vec{w},b}\left(\vec{x}_{train}^{(i)}\right)\right)\right]$$

Train/test procedure for classification problem

0/1

Fit parameters by minimizing $J(\vec{w}, b)$ to find $\vec{w}, b$

E.g.,

$$J(\vec{w}, b) = -\frac{1}{m}\sum_{i=1}^{m}\left[y^{(i)}\log\left(f_{\vec{w},b}(\right.\right.$$

Compute test error:

$$J_{test}(\vec{w}, b) = -\frac{1}{m_{test}}\sum_{i=1}^{m_{test}}\left[y\right.$$

Compute train error:

$$J_{train}(\vec{w}, b) = -\frac{1}{m_{train}}\sum_{i=1}^{m_{train}}$$

fraction of the test set and the fraction of the train set that the algorithm has misclassified.

$$\hat{y} = \begin{cases} 1 \text{ if } f_{\vec{w},b}(\vec{x}^{(i)}) \geq 0.5 \\ 0 \text{ if } f_{\vec{w},b}(\vec{x}^{(i)}) < 0.5 \end{cases}$$

count $\hat{y} \neq y$

$J_{test}(\vec{w}, b)$ is the fraction of the test set that has been misclassified.

$J_{train}(\vec{w}, b)$ is the fraction of the train set that has been misclassified.

Evaluating and choosing models

Model selection and training/cross validation/test sets

Model selection (choosing a model)



$$f_{\vec{w},b}(\vec{x}) = w_1x_1 + w_2x^2 + w_3x^3 + w_4x^4 + b$$

Once parameters $\vec{w}, b$ are fit to the training set, the training error $J_{train}(\vec{w}, b)$ is likely lower than the actual generalization error.

$J_{test}(\vec{w}, b)$ is better estimate of how well the model will generalize to new data than $J_{train}(\vec{w}, b)$.

Model selection (choosing a model)

d=1 1. $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + b$ → $w^{<1>}, b^{<1>}$ → $J_{test}(w^{<1>}, b^{<1>})$

d=2 2. $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x^2 + b$ → $w^{<2>}, b^{<2>}$ → $J_{test}(w^{<2>}, b^{<2>})$

d=3 3. $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x^2 + w_3 x^3 + b$ → $w^{<3>}, b^{<3>}$ → $J_{test}(w^{<3>}, b^{<3>})$

⋮

d=10 10. $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x^2 + \cdots + w_{10} x^{10} + b$ → $J_{test}(w^{<10>}, b^{<10>})$

Choose $w_1 x_1 + \cdots + w_5 x^5 + b$ d=5 $J_{test}(w^{<5>}, b^{<5>})$

How well does the model perform? Report test set error $J_{test}(w^{<5>}, b^{<5>})$?

The problem is $J_{test}(w^{<5>}, b^{<5>})$ is likely to be an optimistic estimate of generalization error. Ie: An extra parameter d (degree of polynomial) was chosen using the test set.

w,b

Training/cross validation/test set

size	price
2104	400
1600	330
2400	369
1416	232
3000	540
1985	300
1534	315
1427	199
1380	212
1494	243

validation set
development set
dev set

training set 60%

cross validation 20%

test set 20%

$(x^{(1)}, y^{(1)})$
$\vdots$
$(x^{(m_{train})}, y^{(m_{train})})$

$m_{train} = 6$

$(x_{cv}^{(1)}, y_{cv}^{(1)})$
$\vdots$
$(x_{cv}^{(m_{cv})}, y_{cv}^{(m_{cv})})$

cross validation

$m_{cv} = 2$

$(x_{test}^{(1)}, y_{test}^{(1)})$
$\vdots$
$(x_{test}^{(m_{test})}, y_{test}^{(m_{test})})$

$m_{test} = 2$

Training/cross validation/test set

Training error: $J_{train}(\vec{w}, b) = \frac{1}{2m_{train}}\left[\sum_{i=1}^{m_{train}} \left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)^2\right]$

Cross validation error: $J_{cv}(\vec{w}, b) = \frac{1}{2m_{cv}}\left[\sum_{i=1}^{m_{cv}} \left(f_{\vec{w},b}\left(\vec{x}_{cv}^{(i)}\right) - y_{cv}^{(i)}\right)^2\right]$ (validation error, dev error)

Test error: $J_{test}(\vec{w}, b) = \frac{1}{2m_{test}}\left[\sum_{i=1}^{m_{test}} \left(f_{\vec{w},b}\left(\vec{x}_{test}^{(i)}\right) - y_{test}^{(i)}\right)^2\right]$

Model selection

d 为 dimension

1. $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + b$ — d=1
2. $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x^2 + b$ — d=2
3. $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x^2 + w_3 x^3 + b$ — d=3

⋮

10. $f_{\vec{w},b}(\vec{x}) = w_1 x_1 + w_2 x^2 + \cdots + w_{10} x^{10} + b$ — d=10

$w^{<1>}, b^{<1>}$ → $J_{cv}(w^{<1>}, b^{<1>})$

$J_{cv}(w^{<2>}, b^{<2>})$

⋮

$J_{cv}(w^{<10>}, b^{<10>})$

按 lowest error

→ Pick $w_1 x_1 + \cdots + w_4 x^4 + b$ $(J_{cv}(w^{<4>}, b^{<4>}))$

我们是从 cross validation 报告 → J test 的结果

Estimate generalization error using test the set: $J_{test}(w^{<4>}, b^{<4>})$

Model selection – choosing a neural network architecture

不同模型的选择

1. 

$w^{(1)}, b^{(1)}$ $J_{cv}(\mathbf{W}^{(1)}, \mathbf{B}^{(1)})$

2. 

$w^{(2)}, b^{(2)}$ $J_{cv}(\mathbf{W}^{(2)}, \mathbf{B}^{(2)})$

3. 

$w^{(3)}, b^{(3)}$ $J_{cv}(\mathbf{W}^{(3)}, \mathbf{B}^{(3)})$

用交叉验证集选择模型
用测试集报告误差
以免 train set 容易取得过小

Train, CV

J_{cv} (Cross Validation)
根据 J_{cv} 来报告最后的泛化误差
选择对应的 test set

Pick $\mathbf{W}^{(2)}, \mathbf{B}^{(2)}$

Estimate generalization error using the test set: $J_{test}(\mathbf{W}^{(2)}, \mathbf{B}^{(2)})$

Bias and variance

Diagnosing bias and variance

Bias/variance



$f_{\vec{w},b}(x) = w_1 x + b$

High bias (underfit)

$d = 1$

J_{train} is high

J_{cv} is high



$f_{\vec{w},b}(x) = w_1 x + w_2 x^2 + b$

"Just right"

$d = 2$

J_{train} is low

J_{cv} is low



$f_{\vec{w},b}(x) = w_1 x + w_2 x^2 + w_3 x^3 + w_4 x^4 + b$

High variance (overfit)

$d = 4$

J_{train} is low

J_{cv} is high

Understanding bias and variance



Diagnosing bias and variance

How do you tell if your algorithm has a bias or variance problem?



High bias (underfit)

J_{train} will be high

($J_{train} \approx J_{cv}$)

High variance (overfit)

$J_{cv} \gg J_{train}$

(J_{train} may be be low)

High bias and high variance

J_{train} will be high

and $J_{cv} \gg J_{train}$

Bias and variance

Regularization and bias/variance

Linear regression with regularization

Model: $f_{\vec{w},b}(x) = w_1x + w_2x^2 + w_3x^3 + w_4x^4 + b$

$$J(\vec{w},b) = \frac{1}{2m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)^2 + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2$$



Large λ
High bias (underfit)
$\lambda = 10{,}000$ $w_1 \approx 0, w_2 \approx 0$
$f_{\vec{w},b}(\vec{x}) \approx b$

Intermediate λ

λ

Small λ
High variance (overfit)
$\lambda = 0$

Choosing the regularization parameter λ

Model: $f_{\vec{w},b}(x) = w_1 x + w_2 x^2 + w_3 x^3 + w_4 x^4 + b$

1. Try $\lambda = 0$ → $\min_{\vec{w},b} J(\vec{w},b)$ → $w^{<1>}, b^{<1>}$ → $J_{cv}(w^{<1>}, b^{<1>})$
2. Try $\lambda = 0.01$ → $\min_{\vec{w},b} J(\vec{w},b)$ → $w^{<2>}, b^{<2>}$ → $J_{cv}(w^{<2>}, b^{<2>})$
3. Try $\lambda = 0.02$ → $J_{cv}(w^{<3>}, b^{<3>})$
4. Try $\lambda = 0.04$
5. Try $\lambda = 0.08$ → $J_{cv}(w^{<5>}, b^{<5>})$

⋮

12. Try $\lambda \approx 10$ → $w^{<12>}, b^{<12>}$ → $J_{cv}(w^{<12>}, b^{<12>})$

Pick $w^{<5>}, b^{<5>}$

Report test error: $J_{test}(w^{<5>}, b^{<5>})$

Bias and variance as a function of regularization parameter λ

$$J(\vec{w}, b) = \frac{1}{2m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)^2 + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2$$





Bias and variance

Establishing a baseline level of performance

Speech recognition example

Human level performance : 10.6%

Training error J_{train} : 10.8%

Cross validation error J_{cv} : 14.8%

0.2%

4.0%

Establishing a baseline level of performance

What is the level of error you can reasonably hope to get to?

- Human level performance
- Competing algorithms performance (看竞争算法)
- Guess based on experience

Bias/variance examples

Baseline performance : 10.6%
Training error (J_{train}) : 10.8%
Cross validation error (J_{cv}) : 14.8%

0.2%
4.0%

high variance

因为

10.6%
4.4%
15.0%
0.5%
15.5%

high bias

10.6%
4.4%
15.0%
4.7%
19.7%

high bias
high variance

所以要对比validation set/train set

Bias and variance

Learning curves

Learning curves

J_{train}= training error

J_{cv}= cross validation error



$f_{\vec{w},b}(x) = w_1 x + w_2 x^2 + b$



High bias





if a learning algorithm suffers from high bias, getting more training data will not (by itself) help much.

High variance → 偏差小 但没有很好



base line.

human level performance

if a learning algorithm suffers from high variance, getting more training data is likely to help.

$f_{\vec{w},b}(x) = w_1x + w_2x^2 + w_3x^3 + w_4x^4 + b$

(with small λ)





Bias and variance

Deciding what to try next revisited

Debugging a learning algorithm

You've implemented regularized linear regression on housing prices

$$J(\vec{w}, b) = \frac{1}{2m}\sum_{i=1}^{m}\left(f_{\vec{w},b}(\vec{x}^{(i)}) - y^{(i)}\right)^2 + \frac{\lambda}{2m}\sum_{j=1}^{n} w_j^2$$

But it makes unacceptably large errors in predictions. What do you try next?

→ Get more training examples	fixes high variance
→ Try smaller sets of features $x, x^2, x^3, x^4, x^5 \ldots$	fixes high variance
→ Try getting additional features	fixes high bias
→ Try adding polynomial features $(x_1^2, x_2^2, x_1x_2, etc)$	fixes high bias
→ Try decreasing λ (步子跨小一点)	fixes high bias
→ Try increasing λ (步子跨大一点 (给更多灵活性))	fixes high variance

Bias and variance

Bias/variance and neural networks

The bias variance tradeoff

$f_{\vec{w},b}(x) = w_1x + b$

Simple model

High bias

$f_{\vec{w},b}(x) = w_1x + w_2x^2 + b$

$f_{\vec{w},b}(x) = w_1x + w_2x^2 + w_3x^3 + w_4x^4 + b$

Complex model

High variance



Neural networks and bias variance

Large neural networks are low bias machines



go round and round
抱怨ing 循环

Neural networks and regularization



A large neural network will usually do as well or better than a smaller one so long as regularization is chosen appropriately.

Neural network regularization

$$J(\mathbf{W},\mathbf{B}) = \frac{1}{m}\sum_{i=1}^{m} L\left(f\left(\vec{\mathrm{x}}^{(i)}\right), y^{(i)}\right) + \frac{\lambda}{2m}\sum_{\text{all weights } \mathbf{W}} \left(w^2\right)$$

b

Unregularized MNIST model

```
layer_1 = Dense(units=25, activation="relu")
layer_2 = Dense(units=15, activation="relu")
layer_3 = Dense(units=1, activation="sigmoid")
model = Sequential([layer_1, layer_2, layer_3])
```

Regularized MNIST model

```
layer_1 = Dense(units=25, activation="relu", kernel_regularizer=L2(0.01))
layer_2 = Dense(units=15, activation="relu", kernel_regularizer=L2(0.01))
layer_3 = Dense(units=1, activation="sigmoid", kernel_regularizer=L2(0.01))
model = Sequential([layer_1, layer_2, layer_3])
```

λ

适当正则化，
能拥有一个更大的神经网络是可行的
但越深 → 算法变慢

Machine learning development process

Iterative loop of ML development

Iterative loop of ML development



Spam classification example

From: cheapsales@buystufffromme.com
To: Andrew Ng
Subject: Buy now!

Deal of the week! Buy now!
Rolex w4tchs - $100
Med1cine (any kind) - £50
Also low cost M0rgages
available.

可以开始考虑我们来
筛选器

From: Alfred Ng
To: Andrew Ng
Subject: Christmas dates?

Hey Andrew,
Was talking to Mom about plans
for Xmas. When do you get off
work. Meet Dec 22?
Alf

Building a spam classifier

Supervised learning: $\vec{x}$ = features of email
y = spam (1) or not spam (0)

Features: list the top 10,000 words to compute $x_1, x_2, \cdots, x_{10,000}$

$$\vec{x} = \begin{bmatrix} 0 \\ 1 \\ 1 \\ 1 \\ 0 \\ \vdots \end{bmatrix} \begin{matrix} a \\ andrew \\ buy \\ deal \\ discount \\ \vdots \end{matrix}$$

```
From: cheapsales@buystufffromme.com
To: Andrew Ng
Subject: Buy now!

Deal of the week! Buy now!
Rolex w4tchs - $100
Med1cine (any kind) - £50
Also low cost M0rgages
available.
```

那张左边的问表是存出现，判断0或1.

Building a spam classifier

How to try to reduce your spam classifier's error?

- Collect more data. E.g., "Honeypot" project.
- Develop sophisticated features based on email routing (from email header).
- Define sophisticated features from email body. E.g., should "discounting" and "discount" be treated as the same word.
- Design algorithms to detect misspellings. E.g., w4tches, med1cine, m0rtgage.

Iterative loop of ML development



Machine learning development process

Error analysis

E sis

m_{cv} = ~~500~~ 5000 example set.

Algorithm misclass

Manually examine ategorize them
based on common

- Pharma: 21
- Deliberate mis
- Unusual email
- Steal passwor
- Spam messag

med1cine): 3

ge: 5

more data features

Building a spam classifier

How to try to reduce your spam classifier's error?

- Collect more data. E.g., "Honeypot" project.
- Develop sophisticated features based on email routing (from email header).
- Define sophisticated features from email body. E.g., should "discounting" and "discount" be treated as the same word.
- Design algorithms to detect misspellings. E.g., w4tches, med1cine, m0rtgage.

Iterative loop of ML development



Machine learning development process

Adding data

Adding data

- Add more data of everything. E.g., “Honeypot” project.
- Add more data of the types where error analysis has indicated it might help.

  Pharma spam

  E.g., Go to unlabeled data and find more examples of Pharma related spam.

Data augmentation

数据增强

Augmentation: modifying an existing training example to create a new training example.



Data augmentation by introducing distortions



Data augmentation for speech

Speech recognition example

Original audio (voice search: "What is today's weather?")

+ Noisy background: Crowd

增加了嘈杂的背景音

+ Noisy background: Car

变音

+ Audio on bad cellphone connection

信号不好

增强(数据加噪声

Data augmentation by introducing distortions

Distortion introduced should be representation of the type of noise/distortions in the test set.



Audio:
Background noise,
bad cellphone connection

Usually does not help to add purely random/meaningless noise to your data.

尽量用有意义的噪声



[Adam Coates and Tao Wang]

x_i = intensity (brightness) of pixel i

$x_i \leftarrow x_i$ + random noise

Data synthesis

Synthesis: using artificial data inputs to create a new training example.

Artificial data synthesis for photo OCR

[http://www.publicdomainpictures.net/view-image.php?image=5745&picture=times-square]

Artificial data synthesis for photo OCR



Real data

[Adam Coates and Tao Wang]

Artificial data synthesis for photo OCR

Real data

Synthetic data

[Adam Coates and Tao Wang]

Engineering the data used by your system

Conventional model-centric approach:



Data-centric approach:



DeepLearning.AI

Stanford
ONLINE



Machine learning development process

Transfer learning: using data from a different task

Transfer learning



Option 1: only train output layers parameters.

Option 2: train all parameters.

但保持前面层的参数不变

Why does transfer learning work?



intuition behind 共同点检测不同特征

use the same input type

detects edges

detects corners

detects curves/basic shapes



Edges



Corners



Curves / basic shapes

Transfer learning summary

1. Download neural network parameters pretrained on a large dataset with same input type (e.g., images, audio, text) as your application (or train your own).

2. Further train (fine tune) the network on your own data.



DeepLearning.AI

Stanford
ONLINE



Machine learning development process

Full cycle of a machine learning project

Full cycle of a machine learning project



Deployment



→ Software engineering may be needed for:

- Ensure reliable and efficient predictions
- Scaling
- Logging
- System monitoring
- Model updates

部署，software engineering

MLOps

machine learning operations

机器学习操作

Machine learning development process

Fairness, bias, and ethics

Bias

Hiring tool that discriminates against women.

Facial recognition system matching dark skinned individuals to criminal mugshots.

Biased bank loan approvals.

Toxic effect of reinforcing negative stereotypes.

Adverse use cases

Deepfakes

传播有毒攻击

Spreading toxic/incendiary speech through optimizing for engagement.

发布虚假评论

Generating fake content for commercial or political purposes.

Using ML to build harmful products, commit fraud etc.

Spam vs anti-spam : fraud vs anti-fraud.

Guidelines

Get a diverse team to brainstorm things that might go wrong, with emphasis on possible harm to vulnerable groups.

多元化团队，考虑弱势群体

Carry out literature search on standards/guidelines for your industry.

文献研究

Audit systems against possible harm prior to deployment.

潜在伤害



Develop mitigation plan (if applicable), and after deployment, monitor for possible harm.

Skewed datasets (optional)

Error metrics for skewed datasets

Rare disease classification example

Train classifier $f_{\vec{w},b}(\vec{x})$ ($y = 1$ if disease present, $y = 0$ otherwise)

Find that you've got 1% error on test set
(99% correct diagnoses) 二元分类

Only 0.5% of patients have the disease

```
print("y=0")
```

99.5% accuracy, 0.5% error ←
1%
1.2%

Precision/recall

$y = 1$ in presence of rare class we want to detect.



Precision:
(of all patients where we predicted $y = 1$, what fraction actually have the rare disease?)

$$\frac{\text{True positives}}{\#\text{predicted positive}} = \frac{\text{True positives}}{\text{True pos} + \text{False pos}} = \frac{15}{15+5} = 0.75$$

Recall:
(of all patients that actually have the rare disease, what fraction did we correctly detect as having it?)

$$\frac{\text{True positives}}{\#\text{actual positive}} = \frac{\text{True positives}}{\text{True pos} + \text{False neg}} = \frac{15}{15+10} = 0.6$$

```
print("y=0")
```

Skewed datasets (optional)

Trading off precision and recall

high precision — 如果诊断出
某种疾病，你有可能患有这种疾病
（很确诊的）

Trading off precision and recall

Logistic regression: $0 < f_{\vec{w},b}(\vec{x}) < 1$

Predict 1 if $f_{\vec{w},b}(\vec{x}) \geq 0.5$ ~~0.7~~ ~~0.9~~ 0.3

Predict 0 if $f_{\vec{w},b}(\vec{x}) < 0.5$ ~~0.7~~ ~~0.9~~ 0.3

$$\text{precision} = \frac{\text{true positives}}{\text{total predicted positive}}$$

$$\text{recall} = \frac{\text{true positives}}{\text{total actual positive}}$$

Suppose we want to predict $y = 1$ (rare disease) only if very confident.

→ higher precision, lower recall.

Suppose we want to avoid missing too many cases of rare disease (when in doubt predict $y = 1$)

→ lower precision, higher recall.

More generally predict 1 if: $f_{\vec{w},b}(\vec{x}) \geq$ threshold.



F1 score

How to compare precision/recall numbers?

	Precision (P)	Recall (R)	Average	F_1 score
Algorithm 1	0.5	0.4	0.45	0.444
Algorithm 2	0.7	0.1	0.4	0.175
Algorithm 3	0.02	1.0	0.501	0.0392

不能直接取平均值

只能一个一个进行比较

print("y=1")

$$\text{Average} = \frac{P+R}{2}$$

$$\text{F1 score} = \frac{1}{\frac{1}{2}\left(\frac{1}{P}+\frac{1}{R}\right)} = 2\frac{PR}{P+R}$$

计算方式，取个F1-Score高的

Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

DeepLearning.AI

Stanford
ONLINE



Decision Trees

Decision Tree Model

Cat classification example

二分类任务

	Ear shape (x_1)	Face shape (x_2)	Whiskers (x_3)	Cat
	Pointy	Round	Present	1
	Floppy	Not round	Present	1
	Floppy	Round	Absent	0
	Pointy	Not round	Present	0
	Pointy	Round	Present	1
	Pointy	Round	Absent	1
	Floppy	Not round	Absent	0
	Pointy	Round	Absent	1
	Floppy	Round	Absent	0
	Floppy	Round	Absent	0

Categorical (discrete values)

X

y

Decision Tree





New test example



Ear shape: Pointy
Face shape: Round
Whiskers: Present

Decision Tree

找为一个决策树
在训练数据上的表现如何泛化.









DeepLearning.AI

Stanford
ONLINE



Decision Trees

Learning Process

Decision Tree Learning

Decision Tree Learning



Decision Tree Learning



Decision Tree Learning



Decision Tree Learning



4/4 cats

Decision Tree Learning



Decision Tree Learning



Decision Tree Learning



Decision Tree Learning



Decision Tree Learning



Decision Tree Learning



Decision Tree Learning

Decision 1: How to choose what feature to split on at each node?

选择纯度高的决策树节点

Maximize purity (or minimize impurity)

Decision Tree Learning

Decision 1: How to choose what feature to split on at each node?

Maximize purity (or minimize impurity)





Decision Tree Learning

Decision 2: When do you stop splitting?

- When a node is 100% one class
- When splitting a node will result in the tree exceeding a maximum depth



Decision Tree Learning

Decision 2: When do you stop splitting?

- When a node is 100% one class
- When splitting a node will result in the tree exceeding a maximum depth



Decision Tree Learning

Decision 2: When do you stop splitting?

- When a node is 100% one class
- When splitting a node will result in the tree exceeding a maximum depth
- When improvements in purity score are below a threshold
- When number of examples in a node is below a threshold



Decision Tree Learning

Decision 2: When do you stop splitting?

- When a node is 100% one class
- When splitting a node will result in the tree exceeding a maximum depth
- When improvements in purity score are below a threshold
- When number of examples in a node is below a threshold



DeepLearning.AI

Stanford
ONLINE



Decision Tree Learning

Measuring purity

Entropy as a measure of impurity

p_1 = fraction of examples that are cats



$p_1 = 0 \quad H(p_1) = 0$

$p_1 = 2/6 \quad H(p_1) = 0.92$

$p_1 = 3/6 \quad H(p_1) = 1$

$p_1 = 5/6 \quad H(p_1) = 0.65$

$p_1 = 6/6 \quad H(p_1) = 0$

Entropy as a measure of impurity

p_1 = fraction of examples that are cats



$$p_0 = 1 - p_1$$

$$H(p_1) = -p_1 log_2(p_1) - p_0 log_2(p_0)$$

$$= -p_1 \ log_2(p_1) - (1 - p_1) log_2(1 - p_1)$$

Note: "0 log(0)" = 0

DeepLearning.AI

Stanford
ONLINE



Decision Tree Learning

Choosing a split: Information Gain

Choosing a split

$p_1 = {}^5/_{10} = 0.5$

$H(0.5) = 1$



$p_1 = {}^4/_5 = 0.8$ $p_1 = {}^1/_5 = 0.2$

$H(0.8) = 0.72$ $H(0.2) = 0.72$

$$H(0.5) - \left(\frac{5}{10}H(0.8) + \frac{5}{10}H(0.2)\right)$$

$= 0.28$

$H(0.5) = 1$



$p_1 = {}^4/_7 = 0.57$ $p_1 = {}^1/_3 = 0.33$

$H(0.57) = 0.99$ $H(0.33) = 0.92$

entropy of rootnode

$$H(0.5) - \left(\frac{7}{10}H(0.57) + \frac{3}{10}H(0.33)\right)$$

相减/分类 (熵的减小)

$= 0.03$

将2个数字结合起来

$H(0.5) = 1$



$p_1 = {}^3/_4 = 0.75$ $p_1 = {}^2/_6 = 0.33$

$H(0.75) = 0.81$ $H(0.33) = 0.92$

$$H(0.5) - \left(\frac{4}{10}H(0.75) + \frac{6}{10}H(0.33)\right)$$

$= 0.12$

Information Gain

$p_1^{\text{root}} = 5/10 = 0.5$



进行了这次决策后，获得的纯度增加了多少

纯度量不确定度

加权熵

Information gain

$$= \mathrm{H}(p_1^{\text{root}}) - \left(w^{\text{left}} H\left(p_1^{\text{left}}\right) + w^{\text{right}} H\left(p_1^{\text{right}}\right) \right)$$

DeepLearning.AI

Stanford
ONLINE



Decision Tree Learning

Putting it together

Decision Tree Learning

- Start with all examples at the root node
- Calculate information gain for all possible features, and pick the one with the highest information gain
- Split dataset according to selected feature, and create left and right branches of the tree
- Keep repeating splitting process until stopping criteria is met:
  - When a node is 100% one class
  - When splitting a node will result in the tree exceeding a maximum depth
  - Information gain from additional splits is less than threshold
  - When number of examples in a node is below a threshold

Recursive splitting

Recursive splitting

Recursive splitting

Recursive splitting



Recursive splitting

Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive splitting



Recursive algorithm

integrate sub decision tre

try different depth. find th

cross validation subset which have

DeepLearning.AI

Stanford
ONLINE



Decision Tree Learning

Using one-hot encoding of categorical features

Features with three possible values

	Ear shape (x_1)	Face shape (x_2)	Whiskers (x_3)	Cat (y)
	Pointy	Round	Present	1
	Oval	Not round	Present	1
	Oval	Round	Absent	0
	Pointy	Not round	Present	0
	Oval	Round	Present	1
	Pointy	Round	Absent	1
	Floppy	Not round	Absent	0
	Oval	Round	Absent	1
	Floppy	Round	Absent	0
	Floppy	Round	Absent	0



3 possible values

One hot encoding

	~~Ear shape~~	Pointy ears	Floppy ears	Oval ears	Face shape	Whiskers	Cat
	~~Pointy~~	1	0	0	Round	Present	1
	~~Oval~~	0	0	1	Not round	Present	1
	~~Oval~~	0	0	1	Round	Absent	0
	~~Pointy~~	1	0	0	Not round	Present	0
	~~Oval~~	0	0	1	Round	Present	1
	~~Pointy~~	1	0	0	Round	Absent	1
	~~Floppy~~	0	1	0	Not round	Absent	0
	~~Oval~~	0	0	1	Round	Absent	1
	~~Floppy~~	0	1	0	Round	Absent	0
	~~Floppy~~	0	1	0	Round	Absent	0

One hot encoding

If a categorical feature can take on k values, create k binary features (0 or 1 valued).

One hot encoding

	~~Ear shape~~	Pointy ears	Floppy ears	Oval ears	Face shape	Whiskers	Cat
	~~Pointy~~	1	0	0	Round	Present	1
	~~Oval~~	0	0	1	Not round	Present	1
	~~Oval~~	0	0	1	Round	Absent	0
	~~Pointy~~	1	0	0	Not round	Present	0
	~~Oval~~	0	0	1	Round	Present	1
	~~Pointy~~	1	0	0	Round	Absent	1
	~~Floppy~~	0	1	0	Not round	Absent	0
	~~Oval~~	0	0	1	Round	Absent	1
	~~Floppy~~	0	1	0	Round	Absent	0
	~~Floppy~~	0	1	0	Round	Absent	0

One hot encoding and neural networks

	Pointy ears	Floppy ears	Round ears	Face shape	Whiskers	Cat
	1	0	0	~~Round~~ 1	~~Present~~ 1	1
	0	0	1	~~Not round~~ 0	~~Present~~ 1	1
	0	0	1	~~Round~~ 1	~~Absent~~ 0	0
	1	0	0	~~Not round~~ 0	~~Present~~ 1	0
	0	0	1	~~Round~~ 1	~~Present~~ 1	1
	1	0	0	~~Round~~ 1	~~Absent~~ 0	1
	0	1	0	~~Not round~~ 0	~~Absent~~ 0	1
	0	0	1	~~Round~~ 1	~~Absent~~ 0	1
	0	1	0	~~Round~~ 1	~~Absent~~ 0	1
	0	1	0	~~Round~~ 1	~~Absent~~ 0	1

DeepLearning.AI

Stanford
ONLINE



Decision Tree Learning

Continuous valued features

Continuous features

	Ear shape	Face shape	Whiskers	Weight (lbs.)	Cat
	Pointy	Round	Present	7.2	1
	Floppy	Not round	Present	8.8	1
	Floppy	Round	Absent	15	0
	Pointy	Not round	Present	9.2	0
	Pointy	Round	Present	8.4	1
	Pointy	Round	Absent	7.6	1
	Floppy	Not round	Absent	11	0
	Pointy	Round	Absent	10.2	1
	Floppy	Round	Absent	18	0
	Floppy	Round	Absent	20	0

Splitting on a continuous variable







$$\mathrm{H}(0.5) - \left(\frac{2}{10} H\left(\frac{2}{2}\right) + \frac{8}{10} H\left(\frac{3}{8}\right)\right) = 0.24$$

$$\mathrm{H}(0.5) - \left(\frac{4}{10} H\left(\frac{4}{4}\right) + \frac{6}{10} H\left(\frac{1}{6}\right)\right) = 0.61$$

$$\mathrm{H}(0.5) - \left(\frac{7}{10} H\left(\frac{5}{7}\right) + \frac{3}{10} H\left(\frac{0}{3}\right)\right) = 0.40$$

DeepLearning.AI

Stanford
ONLINE



Decision Tree Learning

Regression Trees (optional)

Regression with Decision Trees: Predicting a number

	Ear shape	Face shape	Whiskers	Weight (lbs.)
	Pointy	Round	Present	7.2
	Floppy	Not round	Present	8.8
	Floppy	Round	Absent	15
	Pointy	Not round	Present	9.2
	Pointy	Round	Present	8.4
	Pointy	Round	Absent	7.6
	Floppy	Not round	Absent	11
	Pointy	Round	Absent	10.2
	Floppy	Round	Absent	18
	Floppy	Round	Absent	20

X y

Regression with Decision Trees



Choosing a split



Variance at root node: 20.51

Weights: 7.2, 9.2, 8.4,7.6, 10.2

Variance: 1.47

Weights: 8.8, 15, 11, 18, 20

Variance: 21.87

$w^{\text{left}} = 5/10$

$w^{\text{right}} = 5/10$

$$20.51 - \left(\frac{5}{10} * 1.47 + \frac{5}{10} * 21.87\right)$$

$$= 8.84$$



Variance at root node: 20.51

Weights: 7.2, 15, 8.4, 7.6,10.2, 18, 20

Variance: 27.80

Weights: 8.8,9.2,11

Variance: 1.37

$w^{\text{left}} = 7/10$

$w^{\text{right}} = 3/10$

$$20.51 - \left(\frac{7}{10} * 27.80 + \frac{3}{10} * 1.37\right)$$

$$= 0.64$$



Variance at root node: 20.51

Weights: 7.2, 8.8, 9.2, 8.4

Variance: 0.75

Weights: 15, 7.6, 11, 10.2, 18, 20

Variance: 23.32

$w^{\text{left}} = 4/10$

$w^{\text{right}} = 6/10$

$$20.51 - \left(\frac{4}{10} * 0.75 + \frac{6}{10} * 23.32\right)$$

$$= 6.22$$

DeepLearning.AI

Stanford
ONLINE



树集成

Tree ensembles

Using multiple decision trees

Trees are highly sensitive to small changes of the data



仅改变一个训练样本.
导致 information gain
和 feature 会改变

Tree ensemble



Prediction: Cat



Prediction: Not cat



Prediction: Cat

New test example

Ear shape: Pointy
Face shape: Not Round
Whiskers: Present

Final prediction: Cat

DeepLearning.AI

Stanford
ONLINE



Tree ensembles

Sampling with replacement

Sampling with replacement



Sampling with replacement



Ear shape	Face shape	Whiskers	Cat
Pointy	Round	Present	1
Floppy	Not round	Absent	0
Pointy	Round	Absent	1
Pointy	Not round	Present	0
Floppy	Not round	Absent	0
Pointy	Round	Absent	1
Pointy	Round	Present	1
Floppy	Not round	Present	1
Floppy	Round	Absent	0
Pointy	Round	Absent	1

DeepLearning.AI

Stanford
ONLINE



Tree ensembles

Random forest algorithm

Generating a tree sample

Given training set of size m

For $b = 1$ to B:

Use sampling with replacement to create a new training set of size m

Train a decision tree on the new dataset

Ear shape	Face shape	Whiskers	Cat
Pointy	Round	Present	Yes
Floppy	Round	Absent	No
Floppy	Round	Absent	No
Pointy	Round	Present	Yes
Pointy	Not Round	Present	Yes
Floppy	Round	Absent	No
Floppy	Round	Present	Yes
Pointy	Not Round	Absent	No
Pointy	Not Round	Absent	No
Pointy	Not Round	Present	Yes



Ear shape	Face shape	Whiskers	Cat
Pointy	Round	Present	Yes
Pointy	Round	Absent	Yes
Floppy	Not Round	Absent	No
Floppy	Not Round	Absent	No
Pointy	Round	Absent	Yes
Floppy	Round	Absent	No
Floppy	Round	Absent	No
Floppy	Round	Absent	No
Pointy	Not Round	Absent	No
Pointy	Round	Present	Yes



...

Bagged decision tree

Randomizing the feature choice

At each node, when choosing a feature to use to split, if n features are available, pick a random subset of $k < n$ features and allow the algorithm to only choose from that subset of features.



Random forest algorithm

DeepLearning.AI

Stanford
ONLINE



Tree ensembles

XGBoost

Boosted trees intuition

Given training set of size m

For $b = 1$ to B:

Use sampling with replacement to create a new training set of size m

But instead of picking from all examples with equal (1/m) probability, make it more likely to pick examples that the previously trained trees misclassify

Train a decision tree on the new dataset

Ear shape	Face shape	Whiskers	Cat
Pointy	Round	Present	Yes
Floppy	Round	Absent	No
Floppy	Round	Absent	No
Pointy	Round	Present	Yes
Pointy	Not Round	Present	Yes
Floppy	Round	Absent	No
Floppy	Round	Present	Yes
Pointy	Not Round	Absent	No
Pointy	Not Round	Absent	No
Pointy	Not Round	Present	Yes



Ear shape	Face shape	Whiskers	Prediction
Pointy	Round	Present	Cat ✓
Floppy	Not Round	Present	Not cat ✗
Floppy	Round	Absent	Not cat ✓
Pointy	Not Round	Present	Not cat ✓
Pointy	Round	Present	Cat ✓
Pointy	Round	Absent	Not cat ✗
Floppy	Not Round	Absent	Not cat ✓
Pointy	Round	Absent	Not cat ✗
Floppy	Round	Absent	Not cat ✓
Floppy	Round	Absent	Not cat ✓



XGBoost (eXtreme Gradient Boosting)

- Open source implementation of boosted trees
- Fast efficient implementation
- Good choice of default splitting criteria and criteria for when to stop splitting
- Built in regularization to prevent overfitting
- Highly competitive algorithm for machine learning competitions (eg: Kaggle competitions)

为不同训练样本分配不同的权重

Using XGBoost

Classification

```
from xgboost import XGBClassifier

model = XGBClassifier()

model.fit(X_train, y_train)
y_pred = model.predict(X_test)
```

Regression

```
from xgboost import XGBRegressor

model = XGBRegressor()

model.fit(X_train, y_train)
y_pred = model.predict(X_test)
```

DeepLearning.AI

Stanford
ONLINE



Conclusion

When to use decision trees

Decision Trees vs Neural Networks

Decision Trees and Tree ensembles

- Works well on tabular (structured) data
- Not recommended for unstructured data (images, audio, text)
- Fast



Decision Trees vs Neural Networks

Decision Trees and Tree ensembles

- Works well on tabular (structured) data
- Not recommended for unstructured data (images, audio, text)
- Fast
- Small decision trees may be human interpretable

Neural Networks

- Works well on all types of data, including tabular (structured) and unstructured data
- May be slower than a decision tree
- Works with transfer learning
- When building a system of multiple models working together, it might be easier to string together multiple neural networks

Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

DeepLearning.AI

Stanford
ONLINE



Unsupervised learning, recommender systems and reinforcement learning

Welcome!

Beyond Supervised Learning

- Unsupervised Learning
  - Clustering
  - Anomaly detection
- Recommender Systems
- Reinforcement Learning

DeepLearning.AI

Stanford
ONLINE



Clustering

What is clustering?

Supervised learning



Training set: $\{(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), (x^{(3)}, y^{(3)}), \ldots, (x^{(m)}, y^{(m)})\}$?

Unsupervised learning



Clustering

Training set: $\{x^{(1)}, x^{(2)}, x^{(3)}, \ldots, x^{(m)}\}$

Applications of clustering



Grouping similar news

- Growing skills
- Develop career
- Stay updated with AI, understand how it affects your field of work



Market segmentation



DNA analysis



Image credit: NASA/JPL-Calte
ch/E. Churchwell (Univ. of Wisconsin, Madison)

Astronomical data analysis

DeepLearning.AI

Stanford ONLINE



Clustering

K-means intuition

Step 1: Assign each point to its closest centroid



Step 2:
Recompute the centroids

$\{x^{(1)}, x^{(2)}, x^{(3)}, \ldots, x^{(30)}\}$



Step 1:
Assign each point to its closest centroid



$\{x^{(1)}, x^{(2)}, x^{(3)}, \ldots, x^{(30)}\}$

离哪个质心更近
就分配去哪个

Step 1: Assign each point to its closest centroid



$\{x^{(1)}, x^{(2)}, x^{(3)}, \ldots, x^{(30)}\}$

Step 2:
Recompute the centroids

$\{x^{(1)}, x^{(2)}, x^{(3)}, \ldots, x^{(30)}\}$



Step 1: Assign each point to its closest centroid



$\{x^{(1)}, x^{(2)}, x^{(3)}, \ldots, x^{(30)}\}$

Step 2:
Recompute the centroids



DeepLearning.AI

Stanford
ONLINE



Clustering

K-means algorithm

K-means algorithm

Randomly initialize K cluster centroids $\mu_1, \mu_2, \ldots, \mu_K$

μ_1 μ_2 $x^{(1)}, x^{(2)}, \ldots, x^{(30)}$

$n=2$ $K=2$



K-means algorithm

Randomly initialize K cluster centroids $\mu_1, \mu_2, \ldots, \mu_K$

Repeat {

 # Assign points to cluster centroids

for i = 1 to m

$c^{(i)}$:= index (from 1 to K) of cluster centroid closest to $x^{(i)}$



K-means algorithm

Randomly initialize K cluster centroids $\mu_1, \mu_2, \ldots, \mu_K$

Repeat {

 # Assign points to cluster centroids

for i = 1 to m

$c^{(i)}$:= index (from 1 to K) of cluster centroid closest to $x^{(i)}$

$\min_K \|x^{(i)} - \mu_K\|^2$

 # Move cluster centroids

for k = 1 to K

μ_k := average (mean) of points assigned to cluster k

}

$$\mu_1 = \frac{1}{4}\left[x^{(1)} + x^{(5)} + x^{(6)} + x^{(10)}\right]$$

training example

每个example都是一个vector

$\mu_1 \mu_2$ $x^{(1)}, x^{(2)}, \ldots, x^{(30)}$ $n=2$ $K=2$



K-means algorithm

Randomly initialize k cluster centroids, $\mu_1, \mu_1, \ldots \mu_k$

Repeat {

 # Assign points to cluster centroids

for i = 1 to m

$c^{(i)}$:= index (from 1 to K) of cluster centroid closest to $x^{(i)}$

 # Move cluster centroids

for k = 1 to K

μ_k := average (mean) of points assigned to cluster k

}



K-means for clusters that are not well separated





DeepLearning.AI

Stanford
ONLINE



Clustering

Optimization objective

K-means optimization objective

$c^{(i)}$ = index of cluster $(1, 2, \ldots, K)$ to which example $x^{(i)}$ is currently assigned

μ_k = cluster centroid k vector

$\mu_{c^{(i)}}$ = cluster centroid of cluster to which example $x^{(i)}$ has been assigned

$x^{(10)}$ $c^{(10)}$ $\mu_c^{(10)}$

Cost function

$$J(c^{(1)}, \ldots, c^{(m)}, \mu_1, .., \mu_K) = \frac{1}{m} \sum_{i=1}^{m} \| x^{(i)} - \mu_{c^{(i)}} \|^2$$

$$\min_{\substack{c^{(1)}, \ldots, c^{(m)} \\ \mu_1, \ldots, \mu_K}} J(c^{(1)}, \ldots, c^{(m)}, \mu_1, .., \mu_K)$$

distortion


$J(c^{(1)}, \ldots, c^{(30)}, \mu_1, \mu_2)$

Cost function for K-means

$$J\left(c^{(1)}, \ldots, c^{(m)}, \mu_1, \ldots, \mu_K\right) = \frac{1}{m}\sum_{i=1}^{m}\left\|x^{(i)} - \mu_{c^{(i)}}\right\|^2$$

分配的质心

Repeat {

 # Assign points to cluster centroids

for i = 1 to m:

$c^{(i)}$ = index of cluster centroid closest to $x^{(i)}$

分配质心

 # Move cluster centroids

移动质心

for i = 1 to K:

μ_k = average of points in cluster

}



Moving the centroid



DeepLearning.AI

Stanford
ONLINE



Clustering

Initializing K-means

K-means algorithm

- Step 0: Randomly initialize K cluster centroids $\mu_1, \mu_1, \ldots, \mu_k$

Repeat {

Step 1: Assign points to cluster centroids

Step 2: Move cluster centroids

}

Random initialization

Choose $K < m$

Randomly pick K training examples.

随机选择K个.

Set μ_1, μ_1,..., μ_k equal to these K examples.

不同初始化 → 不同聚类结果



K=3

$$J(c^{(1)}, \ldots, c^{(m)}, \mu_1, .., \mu_K)$$







Random initialization

better than running K-means once

50-1000

For $i = 1$ to 100 {

pick K random examples
set as cluster centroids

Randomly initialize K-means.
Run K-means. Get $c^{(1)}, \ldots, c^{(m)}, \mu_1, \mu_1, \ldots, \mu_k$
Compute $J(c^{(1)}, \ldots, c^{(m)}, \mu_1, \mu_1, \ldots, \mu_k)$

distortion
(cost function)

}

Pick set of clusters that gave lowest cost J

DeepLearning.AI

Stanford
ONLINE



Clustering

Choosing the Number of Clusters

What is the right value of K?



没有对-正确解释

Choosing the value of K

Elbow method

the right "K" is often ambiguous

Don't choose K just to minimize cost J



Choosing the value of K

根据后续的表现再评估效果

Often, you want to get clusters for some later (downstream) purpose.
Evaluate K-means based on how well it performs on that later purpose.







practice lab: image compression!

make sense for your 决策

DeepLearning.AI

Stanford
ONLINE



Anomaly Detection

Finding unusual events

Anomaly detection example

Aircraft engine features:
x_1 = heat generated
x_2 = vibration intensity
…

Dataset: $\{x^{(1)}, x^{(2)}, \ldots, x^{(m)}\}$

New engine: x_{test}



Density estimation

Dataset: $\{x^{(1)}, x^{(2)}, \ldots, x^{(m)}\}$

probability of x being seen in dataset

Model $p(x)$ 越往外概率越大

Is x_{test} anomalous?



Anomaly detection example

Fraud detection:

- $x^{(i)}$ = features of user i's activities
- Model $p(x)$ from data.
- Identify unusual users by checking which have $p(x) < \varepsilon$

① how often log in?
② how many web pages visited?
③ transactions?
④ posts? typing speed?

additional check
→ check fake account

perform additional checks to identify real fraud vs. false alarms

Manufacturing:

$x^{(i)}$ = features of product i

airplane engine
circuit board
smartphone

硬件

ratios

Monitoring computers in a data center:

$x^{(i)}$ = features of machine i

- x_1 = memory use,
- x_2 = number of disk accesses/sec,
- x_3 = CPU load,
- x_4 = CPU load/network traffic.

DeepLearning.AI

Stanford
ONLINE



Anomaly Detection

Gaussian (Normal) Distribution

Gaussian (Normal) distribution

σ standard deviation

σ^2 variance

Say x is a number.
Probability of x is determined by a Gaussian with mean μ, variance σ^2.

$\pi = 3.14$

$$p(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{\frac{-(x-\mu)^2}{2\sigma^2}}$$





Gaussian distribution example

$\mu = 0, \sigma = 1$



$\mu = 0, \sigma = 0.5$



$\sigma^2 = 0.25$

$\mu = 0, \sigma = 2$



$\sigma^2 = 4$

$\mu = 3, \sigma = 0.5$



Parameter estimation

Dataset: $\{x^{(1)}, x^{(2)}, \ldots, x^{(m)}\}$

maximum likelihood for μ, σ



DeepLearning.AI

Stanford
ONLINE



Anomaly Detection

Algorithm

Density estimation

Training set: $\{\vec{x}^{(1)}, \vec{x}^{(2)}, \ldots, \vec{x}^{(m)}\}$

Each example $\vec{x}^{(i)}$ has n features

每个特征的状态



$$\vec{x} = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix}$$

$$p(\vec{x}) = p(x_1; \mu_1, \sigma_1^2) * p(x_2; \mu_2, \sigma_2^2) * p(x_3; \mu_3, \sigma_3^2) * \cdots * p(x_n; \mu_n, \sigma_n^2)$$

$$= \prod_{j=1}^{n} p(x_j; \mu_j, \sigma_j^2)$$

$\sum$ "add" $\prod$ "multiply"

$p(x_1 = \text{high temp}) = 1/10$

$p(x_2 = \text{high vibra}) = 1/20$

$p(x_1, x_1) = p(x_1) * p(x_2)$

$= \frac{1}{10} \times \frac{1}{20} = \frac{1}{200}$

Anomaly detection algorithm

1. Choose n features x_i that you think might be indicative of anomalous examples.
2. Fit parameters $\mu_1, \ldots, \mu_n, \sigma_1^2, \ldots, \sigma_n^2$

$$\mu_j = \frac{1}{m}\sum_{i=1}^{m} x_j^{(i)} \qquad \sigma_j^2 = \frac{1}{m}\sum_{i=1}^{m}(x_j^{(i)} - \mu_j)^2$$

Vectorized formula

$$\vec{\mu} = \frac{1}{m}\sum_{i=1}^{m} \vec{x}^{(i)} \qquad \vec{\mu} = \begin{bmatrix} \mu_1 \\ \mu_2 \\ \cdots \\ \mu_n \end{bmatrix}$$

3. Given new example x, compute $p(x)$:

$$p(x) = \prod_{j=1}^{n} p(x_j; \mu_j, \sigma_j^2) = \prod_{j=1}^{n} \frac{1}{\sqrt{2\pi}\sigma_j} exp(-\frac{(x_j - \mu_j)^2}{2\sigma_j^2})$$

Anomaly if $p(x) < \varepsilon$



Anomaly detection example







$\mu_1 = 5,\ \sigma_1 = 2$

$p(x_1; \mu_1, \sigma_1^2)$

$\mu_2 = 3,\ \sigma_2 = 1$

$p(x_2; \mu_2, \sigma_2^2)$

$\varepsilon = 0.02$

$p\left(x_{test}^{(1)}\right) = 0.0426$ → "ok"

$p\left(x_{test}^{(2)}\right) = 0.0021$ → anomaly

DeepLearning.AI

Stanford
ONLINE



Anomaly Detection

Developing and evaluating an anomaly detection system

The importance of real-number evaluation

When developing a learning algorithm (choosing features, etc.),
making decisions is much easier if we have a way of evaluating our learning algorithm.

Assume we have some labeled data, of anomalous and non-anomalous examples.

$y = 1$ $y = 0$

Training set: $x^{(1)}, x^{(2)}, \ldots, x^{(m)}$ (assume normal examples/not anomalous)

$y = 0$ for all training examples

Cross validation set: $\left(x_{cv}^{(1)}, y_{cv}^{(1)}\right), \ldots, \left(x_{cv}^{(m_{cv})}, y_{cv}^{(m_{cv})}\right)$

Test set: $\left(x_{test}^{(1)}, y_{test}^{(1)}\right), \ldots, \left(x_{test}^{(m_{test})}, y_{test}^{(m_{test})}\right)$

include a few anomalous examples $y = 1$

mostly normal examples $y = 0$

Aircraft engines monitoring example

10000 good (normal) engines
20 flawed engines (anomalous)

2 to 50

y=1

2

y=0

Training set: 6000 good engines

train algorithm on training set

CV: 2000 good engines ($y = 0$) 10 anomalous ($y = 1$)

use cross validation set

tune ε tune x_j

Test: 2000 good engines ($y = 0$), 10 anomalous ($y = 1$)

Alternative: No test set

Use if very few labeled anomalous examples

higher risk of overfitting

Training set: 6000 good engines

2

CV: 4000 good engines ($y = 0$), 20 anomalous ($y = 1$)

tune ε tune x_j

Algorithm evaluation

course 2 week 3

skewed datasets

Fit model $p(x)$ on training set $x^{(1)}, x^{(2)}, \ldots, x^{(m)}$

On a cross validation/test example x, predict

$$y = \begin{cases} 1 & if\ p(x) < \varepsilon\ (anomaly) \\ 0 & if\ p(x) \geq \varepsilon\ (normal) \end{cases}$$

10

2000

Possible evaluation metrics:

- True positive, false positive, false negative, true negative
- Precision/Recall
- F_1-score

Can also use cross validation set to choose parameter ε

DeepLearning.AI

Stanford
ONLINE



Anomaly Detection

Anomaly detection vs. supervised learning

Anomaly detection vs. Supervised learning

Very small number (0 to 20) of positive examples $y = 1$,
large number of negative examples ($y = 0$);
Model $p(x)$ with just negative examples.
Use positive examples for cv and test sets

有很多种异常样本，无法覆盖

Many different "types" of anomalies.
Hard for any algorithm to learn (from just positive examples) what the anomalies look like.
Future anomalies may look nothing like any of the anomalous examples seen so far.

financial fraud

每几年/几月都会出现新的类型

Large number of positive and negative examples.

≥ 20 positive examples

Enough positive examples for algorithm to get a sense of what positive examples are like.
Future positive examples likely to be similar to ones in training set.

assume

email spam (垃圾邮件)

Anomaly detection vs. Supervised learning

- Fraud detection

- Manufacturing:
Finding new previously unseen defects.
(e.g. aircraft engines)

- Monitoring machines in a data center
- Security applications

- Email spam classification

- Manufacturing:
Finding known, previously seen defects
(e.g. scratches on smartphones, $y = 1$)

- Weather prediction (sunny/rainy/etc.)

- Diseases classification

DeepLearning.AI

Stanford
ONLINE



Anomaly Detection

Choosing what features to use

选择使用特征

Non-gaussian features



$p(x_1; \mu_1, \sigma_1^2)$

```
plt.hist(x)
```

$x_1 \leftarrow \log(x_1)$ or C

$x_2 \leftarrow \log(x_2 + 1)$

$x_3 \leftarrow \sqrt{x_3} = x_3^{1/2}$

$x_4 \leftarrow x_4^{1/3}$




```
np.log(x)
```




70
60
50
40
30
20
10
0
-4
-3
-2
-1
0
1
2
3
4
0.150331, -15.3991
Octave-3.2.4
1000 1
octave-3.2.4.exe:6> hist(x)
octave-3.2.4.exe:7> hist(x,50)
octave-3.2.4.exe:8> hist(x.^0.5, 50)
octave-3.2.4.exe:9> hist(x.^0.2, 50)
octave-3.2.4.exe:10> hist(x.^0.1, 50)
octave-3.2.4.exe:11> hist(x.^0.05, 50)
octave-3.2.4.exe:12> xNew = x.^0.05;
octave-3.2.4.exe:13> hist(log(x),50)
octave-3.2.4.exe:14> xNew = log(x);

Error analysis for anomaly detection

Want $p(x) \geq \varepsilon$ large for normal examples x.
$p(x) < \varepsilon$ small for anomalous examples x.

Most common problem:
$p(x)$ is comparable for normal and anomalous examples.
($p(x)$ is large for both)





x_1 num transactions x_2 typing speed

Monitoring computers in a data center

Choose features that might take on unusually large or small values in the event of an anomaly.

x_1 = memory use of computer

x_2 = number of disk accesses/sec

x_3 = CPU load

x_4 = network traffic

high low

not unusual

$$x_5 = \frac{\text{CPU load}}{\text{network traffic}}$$

create new feature x_6

$$x_6 = \frac{(\text{CPU load})^2}{\text{network traffic}}$$

Deciding feature choice based on $p(x)$

Large for normal examples;

Becomes small for anomaly in the cross validation set

Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

DeepLearning.AI

Stanford
ONLINE



Recommender Systems

DeepLearning.AI

Stanford
ONLINE



Recommender System

Making recommendations

Predicting movie ratings

User rates movies using one to five stars

Movie	Alice(1)	Bob(2)	Carol(3)	Dave(4)
Love at last	5	5	0	0
Romance forever	5	?	?	0
Cute puppies of love	?	4	0	?
Nonstop car chases	0	0	5	4
Swords vs. karate	0	0	5	?



n_u = no. of users

n_m = no. of movies

r(*i*,*j*)=1 if user *j* has rated movie *i*

$y^{(i,j)}$ = rating given by user *j* to movie *i* (defined only if r(*i*,*j*)=1)

$n_u = 4$

$n_m = 5$

$r(1,1) = 1$

$r(3,1) = 0$

$y^{(3,2)} = 4$

DeepLearning.AI

Stanford ONLINE



Collaborative Filtering

Using per-item features

What if we have features of the movies?

$n_u = 4$
$n_m = 5$
$n = 2$

Movie	Alice(1)	Bob(2)	Carol(3)	Dave(4)	x_1 (romance)	x_2 (action)
Love at last	5	5	0	0	0.9	0
Romance forever	5	?	?	0	1.0	0.01
Cute puppies of love	?	4	0	?	0.99	0
Nonstop car chases	0	0	5	4	0.1	1.0
Swords vs. karate	0	0	5	?	0	0.9

$x^{(1)} = \begin{bmatrix} 0.9 \\ 0 \end{bmatrix}$

$x^{(3)} = \begin{bmatrix} 0.99 \\ 0 \end{bmatrix}$

For user 1: Predict rating for movie i as: $w^{(1)} \cdot x^{(i)} + b^{(1)}$

just linear regression

$w^{(1)} = \begin{bmatrix} 5 \\ 0 \end{bmatrix}$ $b^{(1)} = 0$ $x^{(3)} = \begin{bmatrix} 0.9 \\ 0 \end{bmatrix}$

$w^{(1)} \cdot x^{(3)} + b^{(1)} = 4.95$

假设的权重 Alice对romance感兴趣，对action不太感兴趣

For user j: Predict user j's rating for movie i as $w^{(j)} \cdot x^{(i)} + b^{(j)}$ = Parameter

Cost function

Notation:

- $r(i,j) = 1$ if user j has rated movie i (0 otherwise)
- $y^{(i,j)}$ = rating given by user j on movie i (if defined)
- $w^{(j)}$, $b^{(j)}$ = parameters for user j
- $x^{(i)}$ = feature vector for movie i

For user j and movie i, predict rating: $w^{(j)} \cdot x^{(i)} + b^{(j)}$

$m^{(j)}$ = no. of movies rated by user j

To learn $w^{(j)}$, $b^{(j)}$

$$\min_{w^{(j)}, b^{(j)}} J\left(w^{(j)}, b^{(j)}\right) = \frac{1}{2m^{(j)}} \sum_{i:r(i,j)=1} \left(w^{(j)} \cdot x^{(i)} + b^{(j)} - y^{(i,j)}\right)^2 + \frac{\lambda}{2m^{(j)}} \sum_{k=1}^{n} \left(w_k^{(j)}\right)^2$$

j = user

i = movie

MSE

number of features

cost function

对i求和，只对r(i,j)=1的求和

对于机器学习，消除$m^{(j)}$此项

Cost function

To learn parameters $w^{(j)}, b^{(j)}$ for user j :

$$J\left(w^{(j)}, b^{(j)}\right) = \frac{1}{2} \sum_{i:r(i,j)} \left(w^{(j)} \cdot x^{(i)} + b^{(j)} - y^{(i,j)}\right)^2 + \frac{\lambda}{2} \sum_{k=1}^{n} \left(w_k^{(j)}\right)^2$$

To learn parameters $w^{(1)}, b^{(1)}, w^{(2)}, b^{(2)}, \cdots w^{(n_u)}, b^{(n_u)}$ for all users :

$$J\begin{pmatrix} w^{(1)}, & \ldots, w^{(n_u)} \\ b^{(1)}, & \ldots, b^{(n_u)} \end{pmatrix} = \frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} \underbrace{\left(w^{(j)} \cdot x^{(i)} + b^{(j)}\right)}_{f(x)} - y^{(i,j)}\Big)^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^{n} \left(w_k^{(j)}\right)^2$$

DeepLearning.AI

Stanford
ONLINE



Collaborative Filtering

Collaborative filtering algorithm

Problem motivation

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	x_1 (romance)	x_2 (action)
Love at last	5	5	0	0	0.9	0
Romance forever	5	?	?	0	1.0	0.01
Cute puppies of love	?	4	0	?	0.99	0
Nonstop car chases	0	0	5	4	0.1	1.0
Swords vs. karate	0	0	5	?	0	0.9

Problem motivation

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	x_1 (romance)	x_2 (action)
Love at last	5	5	0	0	?	?
Romance forever	5	?	?	0 ←	?	? $x^{(2)}$
Cute puppies of love	?	4	0	? ←	?	? $x^{(3)}$
Nonstop car chases	0	0	5	4 ←	?	?
Swords vs. karate	0	0	5	? ←	?	?

预测评分的参数

$w^{(1)}=\begin{bmatrix}5\\0\end{bmatrix}$, $w^{(2)}=\begin{bmatrix}5\\0\end{bmatrix}$, $w^{(3)}=\begin{bmatrix}0\\5\end{bmatrix}$, $w^{(4)}=\begin{bmatrix}0\\5\end{bmatrix}$

$b^{(1)}=0$, $b^{(2)}=0$, $b^{(3)}=0$, $b^{(4)}=0$ ←

using $w^{(j)} \cdot x^{(i)} + b^{(j)}$

$w^{(1)} \cdot x^{(1)} \approx 5$

$w^{(2)} \cdot x^{(1)} \approx 5$

$w^{(3)} \cdot x^{(1)} \approx 0$

$w^{(4)} \cdot x^{(1)} \approx 0$

→ $x^{(1)}=\begin{bmatrix}1\\0\end{bmatrix}$

求解 $x^{(1)}$ 特征向量

Cost function

Given $w^{(1)}, b^{(1)}, w^{(2)}, b^{(2)}, \cdots, w^{(n_u)}, b^{(n_u)}$

to learn $x^{(i)}$:

$$J\left(x^{(i)}\right) = \frac{1}{2} \sum_{j:r(i,j)=1} \left(w^{(j)} \cdot x^{(i)} + b^{(j)} - y^{(i,j)}\right)^2 + \frac{\lambda}{2} \sum_{k=1}^{n} \left(x_k^{(i)}\right)^2$$

→ To learn $x^{(1)}, x^{(2)}, \cdots, x^{(n_m)}$:

$$J\left(x^{(1)}, x^{(2)}, \ldots, x^{(n_m)}\right) = \frac{1}{2} \sum_{i=1}^{n_m} \sum_{j:r(i,j)=1} \left(w^{(j)} \cdot x^{(i)} + b^{(j)} - y^{(i,j)}\right)^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^{n} \left(x_k^{(i)}\right)^2$$

Collaborative filtering

	$j=1$ Alice	$j=2$ Bob	$j=3$ Carol
$i=1$ Movie1	5	5	?
$i=2$ Movie2	?	2	3

Cost function to learn $w^{(1)}, b^{(1)}, \cdots w^{(n_u)}, b^{(n_u)}$:

$$\min_{w^{(1)},b^{(1)},\cdots,w^{(n_u)},b^{(n_u)}} \frac{1}{2}\sum_{j=1}^{n_u}\sum_{i:r(i,j)=1}\left(w^{(j)}\cdot x^{(i)}+b^{(j)}-y^{(i,j)}\right)^2 + \frac{\lambda}{2}\sum_{j=1}^{n_u}\sum_{k=1}^{n}\left(w_k^{(j)}\right)^2$$

对 j 求和

Cost function to learn $x^{(1)},\cdots,x^{(n_m)}$:

$$\min_{x^{(1)},\cdots,x^{(n_m)}} \frac{1}{2}\sum_{i=1}^{n_m}\sum_{j:r(i,j)=1}\left(w^{(j)}\cdot x^{(i)}+b^{(j)}-y^{(i,j)}\right)^2 + \frac{\lambda}{2}\sum_{i=1}^{n_m}\sum_{k=1}^{n}\left(x_k^{(i)}\right)^2$$

对 i 求和

Put them together:

$$\min_{\substack{w^{(1)},\ldots,w^{(n_u)}\\ b^{(1)},\ldots,b^{(n_u)}\\ x^{(1)},\ldots,x^{(n_m)}}} J(w,b,x) = \frac{1}{2}\sum_{(i,j):r(i,j)=1}\left(w^{(j)}\cdot x^{(i)}+b^{(j)}-y^{(i,j)}\right)^2 + \frac{\lambda}{2}\sum_{j=1}^{n_u}\sum_{k=1}^{n}\left(w_k^{(j)}\right)^2 + \frac{\lambda}{2}\sum_{i=1}^{n_m}\sum_{k=1}^{n}\left(x_k^{(i)}\right)^2$$

all pairs

Gradient Descent

collaborative filtering

协同过滤，从大部分人收藏

Linear regression (course 1)

repeat {

$$w_i = w_i - \alpha \frac{\partial}{\partial w_i} J(w,b)$$

$$b = b - \alpha \frac{\partial}{\partial b} J(w,b)$$

$$w_i^{(j)} = w_i^{(j)} - \alpha \frac{\partial}{\partial w_i^{(j)}} J(w,b,x)$$

$$b^{(j)} = b^{(j)} - \alpha \frac{\partial}{\partial b^{(j)}} J(w,b,x)$$

$$x_k^{(i)} = x_k^{(i)} - \alpha \frac{\partial}{\partial x_k^{(i)}} J(w,b,x)$$

这三个都是参数 w, b, x

}

parameters w, b, x

x is also a parameter

DeepLearning.AI

Stanford
ONLINE



Collaborative Filtering

Binary labels:
favs,
likes and clicks

Binary labels

Movie	Alice(1)	Bob(2)	Carol(3)	Dave(4)
Love at last	1	1	0	0
Romance forever	1	?	?	0
Cute puppies of love	?	1	0	?
Nonstop car chases	0	0	1	1
Swords vs. karate	0	0	1	?

1
0
?

Example applications

1. Did user j purchase an item after being shown? 1, 0, ?
2. Did user j fav/like an item? 1, 0, ?
3. Did user j spend at least 30sec with an item? 1, 0, ?
4. Did user j click on an item? 1, 0, ?

Meaning of ratings:
- 1 - engaged after being shown item
- 0 - did not engage after being shown item
- ? - item not yet shown

From regression to binary classification

Previously:

Predict $y^{(i,j)}$ as $w^{(j)} \cdot x^{(i)} + b^{(j)}$

For binary labels:

Predict that the probability of $y^{(i,j)} = 1$ is given by $g(w^{(j)} \cdot x^{(i)} + b^{(j)})$

where $g(z) = \frac{1}{1+e^{-z}}$

Cost function for binary application

Previous cost function:

$$\frac{1}{2}\sum_{(i,j):r(i,j)=1}\left(w^{(j)}\cdot x^{(i)}+b^{(j)}-y^{(i,j)}\right)^2+\frac{\lambda}{2}\sum_{i=1}^{n_m}\sum_{k=1}^{n}\left(x_k^{(i)}\right)^2+\frac{\lambda}{2}\sum_{j=1}^{n_u}\sum_{k=1}^{n}\left(w_k^{(j)}\right)^2$$

$w^{(j)}\cdot x^{(i)}+b^{(j)}$: $f(x)$

Loss for binary labels $y^{(i,j)}$: $f_{(w,b,x)}(x)=g(w^{(j)}\cdot x^{(i)}+b^{(j)})$

$$L\left(f_{(w,b,x)}(x),y^{(i,j)}\right)=-y^{(i,j)}\log\left(f_{(w,b,x)}(x)\right)-\left(1-y^{(i,j)}\right)\log\left(1-f_{(w,b,x)}(x)\right)$$

Loss for single example

$$J(w,b,x)=\sum_{(i,j):r(i,j)=1}L\left(f_{(w,b,x)}(x),y^{(i,j)}\right)$$

$g(w^{(j)}\cdot x^{(i)}+b^{(j)})$

cost for all examples

DeepLearning.AI

Stanford
ONLINE



Recommender Systems implementation

Mean normalization

Users who have not rated any movies

Movie	Alice(1)	Bob (2)	Carol (3)	Dave (4)	Eve (5)	
Love at last	5	5	0	0	?	
Romance forever	5	?	?	0	?	
Cute puppies of love	?	4	0	?	?	
Nonstop car chases	0	0	5	4	?	
Swords vs. karate	0	0	5	?	?	

compact..

$$\begin{bmatrix} 5 & 5 & 0 & 0 & ? \\ 5 & ? & ? & 0 & ? \\ ? & 4 & 0 & ? & ? \\ 0 & 0 & 5 & 4 & ? \\ 0 & 0 & 5 & 0 & ? \end{bmatrix}$$

$$\min_{\substack{w^{(1)},\ldots w^{(n_u)} \\ b^{(1)},\ldots b^{(n_u)} \\ x^{(1)},\ldots x^{(n_m)}}} \frac{1}{2} \sum_{(i,j):r(i,j)=1} \left(w^{(j)} \cdot x^{(i)} + b^{(j)} - y^{(i,j)}\right)^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^{n} \left(w_k^{(j)}\right)^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^{n} \left(x_k^{(i)}\right)^2$$

$w^{(5)} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$ $b^{(5)} = 0$ $w^{(5)} \cdot x^{(i)} + b^{(5)}$

Eve电影评分没有对数的选

Mean Normalization

将每行评分减去 μ

$$\begin{bmatrix} 5 & 5 & 0 & 0 & ? \\ 5 & ? & ? & 0 & ? \\ ? & 4 & 0 & ? & ? \\ 0 & 0 & 5 & 4 & ? \\ 0 & 0 & 5 & 0 & ? \end{bmatrix} \quad \begin{matrix} 2.5 \\ 2.5 \\ 2 \\ 2.25 \\ 1.25 \end{matrix}$$

求平均值

$$\mu = \begin{bmatrix} 2.5 \\ 2.5 \\ 2 \\ 2.25 \\ 1.25 \end{bmatrix}$$

$$\begin{bmatrix} 2.5 & 2.5 & -2.5 & -2.5 & ? \\ 2.5 & ? & ? & -2.5 & ? \\ ? & 2 & -2 & ? & ? \\ -2.25 & -2.25 & 2.75 & 1.75 & ? \\ -1.25 & -1.25 & 3.75 & -1.25 & ? \end{bmatrix}$$

For user j, on movie i predict:

$$w^{(j)} \cdot x^{(i)} + b^{(j)} + \mu_i$$

mean normalization step

$y^{(i,j)}$ 也可以

但可能不

$w^{(j)}, b^{(j)}, x^{(i)}$

User 5 (Eve):

$$w^{(5)} = \begin{bmatrix} 0 \\ 0 \end{bmatrix} \quad b^{(5)} = 0$$

$$\underbrace{w^{(5)} \cdot x^{(1)} + b^{(5)}}_{0} + \mu_1 = 2.5$$

更合理

DeepLearning.AI

Stanford
ONLINE



Recommender Systems implementational detail

TensorFlow implementation

Derivatives in ML

Gradient descent algorithm

Repeat until convergence

$w = w - \alpha \frac{d}{dw} J(w,b)$

$b = b - \alpha \frac{d}{db} J(w,b)$ ← $b = 0$

Learning rate

Derivative



Custom Training Loop

$$J = (wx - 1)^2$$

Gradient descent algorithm

Repeat until convergence

$$w = w - \alpha \frac{d}{dw} J(w,b)$$

Fix b = 0 for this example




```
w = tf.Variable(3.0)
x = 1.0
y = 1.0 # target value
alpha = 0.01

iterations = 30
for iter in range(iterations):
    # Use TensorFlow's Gradient tape to record the steps
    # used to compute the cost J, to enable auto differentiation.
    with tf.GradientTape() as tape:
        fwb = w*x
        costJ = (fwb - y)**2

    # Use the gradient tape to calculate the gradients
    # of the cost with respect to the parameter w.
    [dJdw] = tape.gradient( costJ, [w] )

    # Run one step of gradient descent by updating
    # the value of w to reduce the cost.
    w.assign_add(-alpha * dJdw)
```

Tf.variables are the parameters we want to optimize

Auto Diff

Auto Grad

tf.variables require special function to modify

$$\frac{\partial}{\partial w} J(w)$$

Implementation in TensorFlow

Gradient descent algorithm

Repeat until convergence

$$w = w - \alpha \frac{\partial}{\partial w} J(w,b,X)$$

$$b = b - \alpha \frac{\partial}{\partial b} J(w,b,X)$$

$$X = X - \alpha \frac{\partial}{\partial x} J(w,b,X)$$

```
# Instantiate an optimizer.
optimizer = keras.optimizers.Adam(learning_rate=1e-1)

iterations = 200
for iter in range(iterations):
    # Use TensorFlow's GradientTape
    # to record the operations used to compute the cost
    with tf.GradientTape() as tape:

      # Compute the cost (forward pass is included in cost)
      cost_value = cofiCostFuncV(X, W, b, Ynorm, R,
          num_users, num_movies, lambda)

    # Use the gradient tape to automatically retrieve
    # the gradients of the trainable variables with respect to
          the loss
    grads = tape.gradient( cost_value, [X,W,b] )

    # Run one step of gradient descent by updating
    # the value of the variables to minimize the loss.
    optimizer.apply_gradients( zip(grads, [X,W,b]) )
```

n_u n_m

指定为哪些

重新排列

Dataset credit: Harper and Konstan. 2015. The MovieLens Datasets: History and Context

DeepLearning.AI

Stanford
ONLINE



Collaborative Filtering

Finding related items

Finding related items

The features $x^{(i)}$ of item i are quite hard to interpret.

To find other items related to it, find item k with $x^{(k)}$ similar to $x^{(i)}$

i.e. with smallest distance

$$\sum_{l=1}^{n} \left(x_l^{(k)} - x_l^{(i)} \right)^2$$

$$\left\| x^{(k)} - x^{(i)} \right\|^2$$

Limitations of Collaborative Filtering

Cold start problem. How to

- rank new items that few users have rated?
- show something reasonable to new users who have rated few items?

Use side information about items or users:

- Item: Genre, movie stars, studio, ….
- User: Demographics (age, gender, location), expressed preferences, …

DeepLearning.AI

Stanford
ONLINE



Content-based Filtering

Collaborative filtering
vs
Content-based filtering

Collaborative filtering vs Content-based filtering

- Collaborative filtering:
  Recommend items to you based on rating of users who gave similar ratings as you

- Content-based filtering:
  Recommend items to you based on features of user and item to find good match

$r(i,j)=1$ if user j has rated item i

$y^{(i,j)}$ rating given by user j on item i (if defined)

保持

Examples of user and item features

User features:

- Age
- Gender
- Country
- Movies watched
- Average rating per genre
- …

Movie features:

- Year
- Genre/Genres
- Reviews
- Average rating
- …



Vector size could be different



Content-based filtering: Learning to match

Predict rating of user j on movie i as

$w^{(j)} \cdot x^{(i)} + b^{(j)}$

$v_u^{(j)} \cdot v_m^{(i)}$

computed from $x_u^{(j)}$

computed from $x_m^{(i)}$



DeepLearning.AI

Stanford
ONLINE



Content-based Filtering

Deep learning for content-based filtering

Neural network architecture

$x_u \rightarrow v_u$ User network



$x_m \rightarrow v_m$ Movie network



Prediction : $v_u^{(j)} \cdot v_m^{(i)}$

$g\left(v_u^{(j)} \cdot v_m^{(i)}\right)$ ***to predict the probability that*** $y^{(i,j)}$ ***is*** 1

Neural network architecture



Cost function

$$J = \sum_{(i,j):r(i,j)=1} \left(v_u{}^{(j)} \cdot v_m{}^{(i)} - y^{(i,j)}\right)^2 + \text{NN regularization term}$$

cost function

Learned user and item vectors:

$v_u^{(j)}$ is a vector of length 32 that describes user j with features $x_u^{(j)}$

$v_m^{(i)}$ is a vector of length 32 that describes movie i with features $x_m^{(i)}$

To find movies similar to movie i:

$$\| v_m^{(k)} - v_m^{(i)} \|^2 \quad \text{small}$$

$$\| x^{(k)} - x^{(i)} \|^2$$

Note: This can be pre-computed ahead of time

DeepLearning.AI

Stanford
ONLINE



Advanced implementation

Recommending from a large catalogue

How to efficiently find recommendation from a large set of items?

- Movies 1000+
- Ads 1m+
- Songs 10m+
- Products 10m+



Two steps: Retrieval & Ranking

Retrieval:

- Generate large list of plausible item candidates ~100s

  e.g.

  - 1) For each of the last 10 movies watched by the user, find 10 most similar movies

    $\| v_m^{(k)} - v_m^{(i)} \|^2$

  - 2) For most viewed 3 genres, find the top 10 movies
  - 3) Top 20 movies in the country

- Combine retrieved items into list, removing duplicates and items already watched/purchased

Two steps: Retrieval & ranking

Ranking:

- Take list retrieved and rank using learned model



- Display ranked items to user

Retrieval step

- Retrieving more items results in better performance, but slower recommendations.
- To analyse/optimize the trade-off, carry out offline experiments to see if retrieving additional items results in more relevant recommendations (i.e., $p\left(y^{(i,j)}\right) = 1$ of items displayed to user are higher).

100 500

DeepLearning.AI

Stanford
ONLINE



Advanced implementation

Ethical use of recommender systems

What is the goal of the recommender system?

Recommend:

- Movies most likely to be rated 5 stars by user
- Products most likely to be purchased
- Ads most likely to be clicked on
- Products generating the largest profit
- Video leading to maximum watch time

+high bid

Ethical considerations with recommender systems

Travel industry

Good travel experience to more users



Payday loans

Squeeze customers more



Amelioration: Do not accept ads from exploitative businesses

Other problematic cases:

- Maximizing user engagement (e.g. watch time) has led to large social media/video sharing sites to amplify conspiracy theories and hate/toxicity

  - Amelioration : Filter out problematic content such as hate speech, fraud, scams and violent content

- Can a ranking system maximize your profit rather than users' welfare be presented in a transparent way?

  - Amelioration : Be transparent with users

DeepLearning.AI

Stanford
ONLINE



Content-based Filtering

TensorFlow Implementation




```
user_NN = tf.keras.models.Sequential([
    tf.keras.layers.Dense(256, activation='relu'),
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(32)
])
```

```
item_NN = tf.keras.models.Sequential([
    tf.keras.layers.Dense(256, activation='relu'),
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(32 )
])
```

```
# create the user input and point to the base network
input_user = tf.keras.layers.Input(shape=(num_user_features))
vu = user_NN(input_user)
vu = tf.linalg.l2_normalize(vu, axis=1)

# create the item input and point to the base network
input_item = tf.keras.layers.Input(shape=(num_item_features))
vm = item_NN(input_item)
vm = tf.linalg.l2_normalize(vm, axis=1)

# measure the similarity of the two vector outputs
output = tf.keras.layers.Dot(axes=1)([vu, vm])

# specify the inputs and output of the model
model = Model([input_user, input_item], output)

# Specify the cost function
cost_fn = tf.keras.losses.MeanSquaredError()
```



Copyright Notice

These slides are distributed under the Creative Commons License.

DeepLearning.AI makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite DeepLearning.AI as the source of the slides.

For the rest of the details of the license, see https://creativecommons.org/licenses/by-sa/2.0/legalcode

DeepLearning.AI

Stanford ONLINE



Reinforcement Learning Introduction

What is Reinforcement Learning?

Autonomous Helicopter



How to fly it?

Autonomous Helicopter

[Thanks to Pieter Abbeel, Adam Coates and Morgan Quigley]

→ For more videos: http://heli.stanford.edu.

Reinforcement Learning

position of helicopter → how to move control sticks

state s → action a

reward function

positive reward : helicopter flying well +1

negative reward : helicopter flying poorly −1000

Robotic Dog Example

[Thanks to Zico Kolter]

Applications

- Controlling robots
- Factory optimization
- Financial (stock) trading
- Playing games (including video games)

DeepLearning.AI

Stanford ONLINE



Reinforcement Learning formalism

Mars rover example

Mars Rover Example

可以在任何6个位置之一

terminal state (终端状态)

terminal state



reward

state 1 2 3 4 5 6

每一步可以选择

left right

state 4 3 2 1

0 0 0 100

0 0 40

0 0 0 0 0 100

某个状态 动作 奖励 new state

$\rightarrow (s, a, R(s), s')$

reward

$(4, \leftarrow, 0, 3)$

[Credit: Jagriti Agrawal, Emma Brunskill]

DeepLearning.AI

Stanford ONLINE



Reinforcement Learning formalism

The Return in reinforcement learning

Return



discount factor折扣因子 / 折扣率

Return $= 0 + (0.9)0 + (0.9)^2 0 + (0.9)^3 100 = 0.729 \times 100 = 72.9$

Return $= R_1 + \gamma R_2 + \gamma^2 R_3 + \cdots$ (until terminal state)

Discount Factor $\gamma = 0.9 \quad 0.99 \quad 0.999$

$\gamma = 0.5$

Return $= 0 + (0.5)0 + (0.5)^2 0 + (0.5)^3 100 = 12.5$

利率

Example of Return



$\gamma = 0.5$

The return depends on the actions you take.



$0+(0.5)0+(0.5)^2 40=10$

为什么在走不一定总优于为当前在走



$0+(0.5)40=20$

DeepLearning.AI

Stanford ONLINE



Reinforcement Learning formalism

Making decisions: Policies in reinforcement learning

Policy



$\pi(5) = \rightarrow$

A policy is a function $\pi(s) = a$ mapping from states to actions, that tells you what action a to take in a given state s.

The goal of reinforcement learning



Find a policy π that tells you what action ($a = \pi(s)$) to take in every state (s) so as to maximize the return.

也许是一系列对应的决策.

DeepLearning.AI

Stanford ONLINE



Reinforcement Learning formalism

Review of key concepts

	Mars rover	Helicopter	Chess
states	6 states	position of helicopter	pieces on board
actions	← →	how to move control stick	possible move
rewards	100, 0, 40	+1, −1000	+1, 0, −1
discount factor γ	0.5	0.99	0.995
return	$R_1 + \gamma R_2 + \gamma^2 R_3 + \cdots$	$R_1 + \gamma R_2 + \gamma^2 R_3 + \cdots$	$R_1 + \gamma R_2 + \gamma^2 R_3 + \cdots$
policy π		Find $\pi(s) = a$	Find $\pi(s) = a$

Markov Decision Process (MDP)

马尔可夫决策
(未来只取决于你现在所处的位置)



DeepLearning.AI

Stanford ONLINE



State-action value function

State-action value function definition

State action value function (Q-function)

$Q(s,a)$ = Return if you

- start in state s.
- take action a (once).
- then behave optimally after that.

只取一次行动的回报

$Q(s,a)$



- ← return
- ← action
- ← reward

$Q(2,\rightarrow) = 12.5$

$0+(0.5)0+(0.5)^2 0+(0.5)^3 100$

$Q(2,\leftarrow) = 50$

$0+(0.5)100$

$Q(4,\leftarrow) = 12.5$

$0+(0.5)0+(0.5)^2 0+(0.5)^3 100$

当前状态下执行某一步行动后，
假设这之后都采取执行最佳步骤，所能获得的最佳回报

Picking actions



$\max_a Q(s,a)$

$\rightarrow \pi(s) = a$

$Q(s,a)$ = Return if you
- start in state s.
- take action a (once).
- then behave optimally after that.

The best possible return from state s is $\max_a Q(s,a)$.

The best possible action in state s is the action a that gives $\max_a Q(s,a)$.

Q^*

Optimal Q function

DeepLearning.AI

Stanford ONLINE



State-action value function

State-action value function example

Jupyter Notebook

DeepLearning.AI

Stanford ONLINE



State-action value function

Bellman Equation

Bellman Equation

$Q(s, a) =$ Return if you
- start in state s.
- take action a (once).
- then behave optimally after that.



s : current state
a : current action

$R(s)$ = reward of current state

s' : state you get to after taking action a
a' : action that you take in state s'

折扣因子

$$Q(s,a) = R(s) + \gamma \max_{a'} Q(s',a')$$

Bellman Equation

$$Q(s,a) = R(s) + \gamma \max_{a'} Q(s',a')$$

$Q(s,a) = R(s)$

终端状态

$s = 2$
$a = \rightarrow$
$s' = 3$



$Q(2,\rightarrow) = R(2) + 0.5 \max_{a'} Q(3,a')$
$= 0 + (0.5)25 = 12.5$

$s = 4$
$a = \leftarrow$
$s' = 3$

$Q(4,\leftarrow) = R(4) + 0.5 \max_{a'} Q(3,a')$
$= 0 + (0.5)25 = 12.5$

Explanation of Bellman Equation

$Q(s, a)$ = Return if you
- start in state s.
- take action a (once).
- then behave optimally after that.

$s \rightarrow s'$

The best possible return from state s' is $\max_{a'} Q(s', a')$

$$Q(s, a) = R(s) + \gamma \max_{a'} Q(s', a')$$

Reward you get right away

Return from behaving optimally starting from state s'.

$R_1 + \gamma R_2 + \gamma^2 R_3 + \gamma^3 R_4 + \cdots$

$Q(s, a) = R_1 + \gamma [R_2 + \gamma R_3 + \gamma^2 R_4 + \cdots]$

多次式结合

Explanation of Bellman Equation

$$Q(s,a) = R(s) + \gamma \max_{a'} Q(s',a')$$

100	100	50	12.5	25	6.25	12.5	10	6.25	20	40	40
100		0		0		0		0		40	
1		2		3		4		5		6	

$Q(4, \leftarrow)$

$= 0 + (0.5)0 + (0.5)^2 0 + (0.5)^3 100$

$= R(4) + (0.5)[0 + (0.5)0 + (0.5)^2 100]$

$= R(4) + (0.5) \max_{a'} Q(3, a')$

DeepLearning.AI

Stanford ONLINE



State-action value function

Random (stochastic) environment (Optional)

Stochastic Environment

随机环境



Expected Return



0 0 0 100 0 100
0 0 0 0
0 0 40

Expected Return = Average($R_1 + \gamma R_2 + \gamma^2 R_3 + \gamma^3 R_4 + \cdots$)

$= \mathrm{E}[R_1 + \gamma R_2 + \gamma^2 R_3 + \gamma^3 R_4 + \cdots]$

Expected Return

Goal of Reinforcement Learning:

Choose a policy $\pi(s) = a$ that will tell us what action a to take in state s so as to maximize the expected return.

随机学习决策

Bellman Equation:

$$Q(s,a) = R(s) + \gamma E[\max_{a'} Q(s',a')]$$

3 ←

2 or 4

Jupyter Notebook

DeepLearning.AI

Stanford ONLINE



Continuous State Spaces

Example of continuous state applications

Discrete vs Continuous State

Discrete State: $S = 1, 2, 3, 4, 5, 6$



Continuous State:

不只一个数字

$$S = \begin{bmatrix} x \\ y \\ \theta \\ \dot{x} \\ \dot{y} \\ \dot{\theta} \end{bmatrix}$$

方向. $0-360^\circ$

$\dot{x}$ x方向的速度

$\dot{y}$ y方向的速度

Autonomous Helicopter

$$s = \begin{bmatrix} x \\ y \\ z \\ \phi \\ \theta \\ \omega \\ \dot{x} \\ \dot{y} \\ \dot{z} \\ \dot{\phi} \\ \dot{\theta} \\ \dot{\omega} \end{bmatrix}$$

roll
pitch
yaw

DeepLearning.AI

Stanford ONLINE



Continuous State Spaces

Lunar Lander

Lunar Lander





Lunar Lander



actions:

- do nothing
- left thruster
- main thruster
- right thruster

$s = \begin{bmatrix} x \\ y \\ \dot{x} \\ \dot{y} \\ \theta \\ \dot{\theta} \\ l \\ r \end{bmatrix}$ 有多个

0 or 1 左、右

Reward Function

- Getting to landing pad: 100 – 140
- Additional reward for moving toward/away from pad.
- Crash: -100
- Soft landing: +100
- Leg grounded: +10
- Fire main engine: -0.3
- Fire side thruster: -0.03



Lunar Lander Problem

Learn a policy π that, given

$$s = \begin{bmatrix} x \\ y \\ \dot{x} \\ \dot{y} \\ \theta \\ \dot{\theta} \\ l \\ r \end{bmatrix}$$



picks action $a = \pi(s)$ so as to maximize the return.

$$\gamma = 0.985$$

DeepLearning.AI

Stanford ONLINE



Continuous State Spaces

Learning the state-value function

Deep Reinforcement Learning





In a state s, use neural network to compute

$Q(s, \text{nothing})$, $Q(s, \text{left})$, $Q(s, \text{main})$, $Q(s, \text{right})$

Pick the action a that maximizes $Q(s,a)$

Bellman Equation

$$Q(s,a) = R(s) + \gamma \max_{a'} Q(s',a')$$

x $\quad$ y

$f_{w,b}(x) \approx y$

$y^{(1)} = R(s^{(1)}) + \gamma \max_{a'} Q(s'^{(1)}, a')$

$y^{(2)} = R(s^{(2)}) + \gamma \max_{a'} Q(s'^{(2)}, a')$

$(s, a, R(s), s')$

$(s^{(1)}, a^{(1)}, R(s^{(1)}), s'^{(1)})$ ← 用Bellman方程计算

$(s^{(2)}, a^{(2)}, R(s^{(2)}), s'^{(2)})$ ←

$(s^{(3)}, a^{(3)}, R(s^{(3)}), s'^{(3)})$ ←

x	y
$x^{(1)} = (s^{(1)}, a^{(1)})$	$y^{(1)}$
$x^{(2)} = (s^{(2)}, a^{(2)})$	$y^{(2)}$
$x^{(10,000)}$	$y^{(10,000)}$

Learning Algorithm



Initialize neural network randomly as guess of $Q(s,a)$.

Repeat {

Take actions in the lunar lander. Get $(s,a,R(s),s')$.

Store 10,000 most recent $(s,a,R(s),s')$ tuples.

缓冲放置区

replay buffer

Train neural network:

Create training set of 10,000 examples using

$x = (s,a)$ and $y = R(s) + \gamma \max_{a'} Q(s',a')$

Train Q_{new} such that $Q_{new}(s,a) \approx y$.

Set $Q = Q_{new}$.

$f_{w,b}(x) \approx y$

近似函数

$x^{(1)}, y^{(1)}$

x, y

$x^{(100000)}, y^{(100000)}$

[Mnih et al., 2015, Human-level control through deep reinforcement learning]

DeepLearning.AI

Stanford ONLINE



Continuous State Spaces

Algorithm refinement: Improved neural network architecture

Deep Reinforcement Learning

$$\vec{x} = \begin{bmatrix} s \\ a \end{bmatrix} \begin{bmatrix} x \\ y \\ \dot{x} \\ \dot{y} \\ \theta \\ \dot{\theta} \\ l \\ r \\ 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$



In a state s, use neural network to compute

$Q(s, \text{nothing})$, $Q(s, \text{left})$, $Q(s, \text{main})$, $Q(s, \text{right})$

Pick the action a that maximizes $Q(s,a)$



Deep Reinforcement Learning



In a state s, input s to neural network.

Pick the action a that maximizes $Q(s, a)$. $R(s) + \gamma \max_{a'} Q(s', a')$



DeepLearning.AI

Stanford ONLINE



Continuous State Spaces

Algorithm refinement: ε-greedy policy

Learning Algorithm



Initialize neural network randomly as guess of $Q(s,a)$.

Repeat {

Take actions in the lunar lander. Get $(s,a,R(s),s')$.

Store 10,000 most recent $(s,a,R(s),s')$ tuples.

Train model:

Create training set of 10,000 examples using

$x = (s,a)$ and $y = R(s) + \gamma \max_{a'} Q(s',a')$.

Train Q_{new} such that $Q_{new}(s,a) \approx y$. $f_{w,b}(x) \approx y$

Set $Q = Q_{new}$.

How to choose actions while still learning?

what if init $Q(s, \text{main})$ to be low?
↳ will never fire main thrusters!

In some state s

Option 1: → will never try other actions

Pick the action a that maximizes $Q(s,a)$.

Option 2:

With probability 0.95, pick the action a that maximizes $Q(s,a)$. greedy exploitation

With probability 0.05, pick an action a randomly. exploration

ε-greedy policy ($\varepsilon = 0.05$)

greedy 95% of the time

exploring 5% of the time

Start ε high

gradually decrease

1.0 → 0.01

DeepLearning.AI

Stanford ONLINE



Continuous State Spaces

Algorithm refinement: Mini-batch and soft update (optional)

How to choose actions while still learning?

x	y
2104	400
1416	232
1534	315
852	178
...	...
3210	870

100,000,000

$$J(w,b) = \frac{1}{2m}\sum_{i=1}^{m}\left(f_{w,b}\left(x^{(i)}\right) - y^{(i)}\right)^2$$

$m = 100,000,000$

$m' = 1,000$

repeat {

$$w = w - \alpha \frac{\partial}{\partial w} \frac{1}{2m'}\sum_{i=1}^{m'}\left(f_{w,b}\left(x^{(i)}\right) - y^{(i)}\right)^2$$

$$b = b - \alpha \frac{\partial}{\partial b} \frac{1}{2m'}\sum_{i=1}^{m'}\left(f_{w,b}\left(x^{(i)}\right) - y^{(i)}\right)^2$$

}

Mini-batch

每次取不同的实例(不重复)

x	y
2104	400
1416	232
1534	315
852	178
...	...
3210	870

batch

iteration 1

iteration 2

iteration 3



Mini-batch

x	y
2104	400
1416	232
1534	315
852	178
...	...
3210	870



Learning Algorithm



Initialize neural network randomly as guess of $Q(s,a)$

Repeat {

Take actions in the lunar lander. Get $(s, a, R(s), s')$.

Store 10,000 most recent $(s, a, R(s), s')$ tuples.

Replay Buffer

Train model:

Create training set of ~~10,000~~ 1,000 examples using

$x = (s, a)$ and $y = R(s) + \gamma \max_{a'} Q(s', a')$

Train Q_{new} such that $Q_{new}(s, a) \approx y$.

Set $Q = Q_{new}$.

$x^{(1)}, y^{(1)}$

$x^{(1000)}, y^{(1000)}$

Soft Update

mini batching

Set $Q = Q_{new}$.

W, B W_{new}, B_{new}

$Q(s,a)$

减缓下降的速度

$$W = 0.01 W_{new} + 0.99 W$$
$$B = 0.01 B_{new} + 0.99 B$$

$W = 1 W_{new} + 0 W$

DeepLearning.AI

Stanford ONLINE



Continuous State Spaces

The state of reinforcement learning

Limitations of Reinforcement Learning

- Much easier to get to work in a simulation than a real robot!
- Far fewer applications than supervised and unsupervised learning.
- But … exciting research direction with potential for future applications.

DeepLearning.AI

Stanford
ONLINE



Conclusion

Summary and
Thank you

Courses

- Supervised Machine Learning: Regression and Classification

  Linear regression, logistic regression, gradient descent

- Advanced Learning Algorithms

  Neural networks, decision trees, advice for ML

- Unsupervised Learning, Recommenders, Reinforcement Learning

  Clustering, anomaly detection, collaborative filtering, content-based filtering, reinforcement learning


Thank you
Andrew Ng.