Output

#	Time	Action	Message	Duration / Fetch
✓ 13	23:14:40	CREATE DATABASE Sales	1 row(s) affected	0.015 sec
✓ 14	23:15:05	USE Sales	0 row(s) affected	0.000 sec
✓ 15	23:15:10	CREATE TABLE Orders (Order_Id INT PRIMARY KEY, Customer_name VARCHAR(100) NOT NULL, ...	0 row(s) affected	0.031 sec
✓ 16	23:15:15	ALTER TABLE Orders ADD order_quantity INT	0 row(s) affected Records: 0 Duplicates: 0 Warnings: 0	0.016 sec
✓ 17	23:15:19	ALTER TABLE Orders RENAME TO sales_orders	0 row(s) affected	0.015 sec
✓ 18	23:15:33	INSERT INTO sales_orders (Order_Id, Customer_name, Product_Category, Ordered_item, Contact_No, order...	10 row(s) affected Records: 10 Duplicates: 0 Warnings: 0	0.000 sec
✓ 19	23:15:39	SELECT Customer_name, Ordered_item FROM sales_orders LIMIT 0, 1000	10 row(s) returned	0.000 sec / 0.000 sec
✓ 20	23:16:47	UPDATE sales_orders SET Ordered_item = 'Gaming Laptop' WHERE Order_Id = 1	1 row(s) affected Rows matched: 1 Changed: 1 Warnings: 0	0.015 sec
✓ 21	23:16:54	UPDATE sales_orders SET Ordered_item = 'Gaming Laptop' WHERE Order_Id = 1	0 row(s) affected Rows matched: 1 Changed: 0 Warnings: 0	0.000 sec
✓ 22	23:16:56	UPDATE sales_orders SET Ordered_item = 'Gaming Laptop' WHERE Order_Id = 1	0 row(s) affected Rows matched: 1 Changed: 0 Warnings: 0	0.000 sec
✓ 23	23:17:00	DROP TABLE sales_orders	0 row(s) affected	0.016 sec

Local instance MySQL80 ×

File   Edit   View   Query   Database   Server   Tools   Scripting   Help

Navigator

SCHEMAS

Q Filter objects

▶ 🗄 entry_d41
▼ 🗄 sales
   🗊 Tables
   🗊 Views
   🗊 Stored Procedures
   🗊 Functions
▼ 🗄 school
   🗊 Tables
   🗊 Views
   🗊 Stored Procedures
   🗊 Functions
▶ 🗄 sys
▶ 🗄 testdb

Query 1   School   SQL File 4* ×

SQLAdditions

◀ ▶ | 🔢 🔢 | Jump to

Automatic context help is disabled. Use
the toolbar to manually get help for
the current caret position or to toggle
automatic help.

Limit to 1000 rows

```
28      (7, 'Grace', 'Electronics', 'Tablet', '9876543216', 2),
29      (8, 'Henry', 'Furniture', 'Chair', '9876543217', 4),
30      (9, 'Ivy', 'Books', 'Biography', '9876543218', 2),
31      (10, 'Jack', 'Groceries', 'Sugar', '9876543219', 10);
32
33      -- Retrieve Customer_name and Ordered_item
34 •    SELECT Customer_name, Ordered_item FROM sales_orders;
```

Result Grid | 🔢 | 🔁 Filter Rows: | Export: 🔢 | Wrap Cell Content: 𝐴

Customer_name	Ordered_item
Alice	Laptop
Bob	T-Shirt
Charlie	Smartphone
Diana	Fiction Novel
Eve	Rice
Frank	Jeans
Grace	Tablet
Henry	Chair
Ivy	Biography
Jack	Sugar

Administration   Schemas

Information

Schema: sales

sales_orders 1 ×

🛈 Read Only   Context Help   Snippets

Output

🗊 Action Output   ▾

#	Time	Action	Message	Duration / Fetch
✓	17	23:15:19	ALTER TABLE Orders RENAME TO sales_orders	0 row(s) affected	0.015 sec
✓	18	23:15:33	INSERT INTO sales_orders (Order_Id, Customer_name, Product_Category, Ordered_item, Contact_No, order...	10 row(s) affected Records: 10 Duplicates: 0 Warnings: 0	0.000 sec
✓	19	23:15:39	SELECT Customer_name, Ordered_item FROM sales_orders LIMIT 0, 1000	10 row(s) returned	0.000 sec / 0.000 sec

Object Info   Session