

Not quite what you are looking for? You may want to try:

- Test Driven / First Development by Example
- Designing Application Using Test Driven Development



highlights off

12,347,255 members (73,899 online)

Sign in



CODE  
PROJECT®  
For those who code

articles

Q&A

forums

lounge

test driven development



# Developing Factorial Application Using **Test Driven Development**



Bayram Üçüncü, 28 Jan 2012

CPOL



4.78 (8 votes)


Rate this:



The aim of this article is developing a Factorial Application using **Test Driven Development**



Download project source code - 58.96 KB



## Introduction

In this article, we have a look at **Test Driven Development** with an example. The example is **Factorial** calculator application. This simple application shows us how to develop an application by **test driven development**. I will write the "**Test Driven Development**" as "TDD" in article.

## Background

When I first faced the **Test Driven Development**, I thought "it is unnecessary". But later, I read the articles about it and I show that TDD prevents the errors and problems before the delivered projects. It also creates reliable products, shows code coverages. These benefits were enough for me to begin TDD.

In this article, we will use the Visual Studio default Unit **Test** Framework. But if you don't want to use default framework, you have more choices in the market of Unit **Tests**.

## Before You Start

Before writing your code, you should determine the requirements of the application. We will be developing a **Factorial** application in this article. So we should determine the **Factorial** requirements. Later, we can determine the **test** methods. If you want, you can directly begin writing **tests** and skip these steps. But making is worth it.


### Requirements

1. Factorial calculates the multiplication of the all positive numbers less than or equal Target Number(n).
2. Target Number(n) is a non-negative integer.

### Unit Tests

1. Zero factorial is One  $0! = 1$
2. One factorial is One  $1! = 1*0! = 1$
3. Two factorial is Two  $2! = 2*1! = 2$
4. Three factorial is Six  $3! = 3*2! = 6$

First step is creating a solution named **FactorialApplication**. And add a **test** project named **FactorialCalculatorTests** and a class library named **FactorialCalculator** in solution.



And now create a new class and write the first **test** method.


### Test 1: Zero Factorial is One

Hide Copy Code

```
[TestMethod]
public void ZeroFactorialIsOne()
{
    Factorial calculator = new Factorial();
}
```

As you can see above, I created a **calculator** object that is of type **Factorial** but there is no class named **Factorial**. And you will get a lot of red squiggly lines under **Factorial** word.

```
[TestMethod]
public void ZeroFactorialIsOne()
{
    Factorial calculator = new Factorial();
```



Let's create a class using options menu under the **Factorial** Word.

[Hide](#) [Copy Code](#)

```
[TestMethod]
public void ZeroFactorialIsOne()
{
    Factorial calculator = new Factorial();
    float result = calculator.GetFactorialOf(0);

    Assert.AreEqual(1, result);
}
```


Yes, now I added a new **result** variable and assigned a **calculator.GetFactorialOf(0)** method result in it. But there is no method of **Factorial** in such. And I created a method in **Factorial** class.

Now we can have a look at the **Factorial** class.

[Hide](#) [Copy Code](#)

```
public class Factorial
{
    public float GetFactorialOf(int p)
    {
        throw new NotImplementedException();
    }
}
```

And now let's run the **test** method and see the result.



The **test** failed because we created method **GetFactorialOf(int p)** but did not implement it as seen above. Now we should do minimum intervention to pass the **test**.

[Hide](#) [Copy Code](#)

```
public class Factorial
{
    public float GetFactorialOf(int p)
    {
        return 1;
    }
}
```

The **test** method can pass now. Because assertion has verified.

Test Results				
<div> <div>pc@PC</div> <div>Run Debug</div> </div>				
<div> <div>Test run completed</div> <div>Results: 1/1 passed; Item(s) checked: 0</div> </div>				
Result	Test Name	Project	Error Message	
Passed	ZeroFactorialIsOne	FactorialCalculato		

## Test 2: One Factorial is One

And now, we can create our second method. New assertion is "One Factorial is One". The new **test** method is as follows:

[Hide](#) [Copy Code](#)

```
[TestMethod]
public void OneFactorialIsOne()
{
    Factorial calculator = new Factorial();
    float result = calculator.GetFactorialOf(1);

    Assert.AreEqual(1, result);
}
```

This method has passed as well because `GetFactorialOf(int p)` method still supports our assertion.

## Test 3: Two Factorial is Two

The third assertion is "Two factorial is Two".

[Hide](#) [Copy Code](#)

```
[TestMethod]
public void TwoFactorialIsTwo()
{
    Factorial calculator = new Factorial();
    float result = calculator.GetFactorialOf(2);

    Assert.AreEqual(2, result);
}
```

This method failed as follows:

Test Results				
<div> <div>pc@PC-</div> <div>Run Debug</div> </div>				
<div> <div>Test run failed</div> <div>Results: 0/1 passed; Item(s) checked: 1</div> </div>				
Result	Test Name	Project	Error Message	
Failed	TwoFactorialIsTwo	FactorialCalculato	Assert.AreEqual failed. Expected:<2> . Actual:<1>.	

Assert exception is shown, expected value is Two but method returned One. Now we should make minimum modification on `GetFactorialOf(int p)` method to pass the method. The modification shouldn't affect the other **test** results.

[Hide](#) [Copy Code](#)

```
public class Factorial
{
    public float GetFactorialOf(int p)
    {
        if (p < 2)
            return 1;

        return p;
    }
}
```

Test Results				
<div>    pc@PC- </div> <div>  Run  Debug </div>				
<b>Test run completed</b> Results: 3/3 passed; Item(s) checked: 0				
	Result	Test Name	Project	Error Message
<input type="checkbox"/>	Passed	OneFactorialIsOne	FactorialCalculatorTests	
<input type="checkbox"/>	Passed	TwoFactorialIsTwo	FactorialCalculatorTests	
<input type="checkbox"/>	Passed	ZeroFactorialIsOne	FactorialCalculatorTests	

## Test 4: Three Factorial is Six

Hide Copy Code

```
[TestMethod]
public void ThreeFactorialIsSix()
{
    Factorial calculator = new Factorial();
    float result = calculator.GetFactorialOf(3);

    Assert.AreEqual(6, result);
}
```

But now this assertion failed.

Test Results				
<div>    pc@PC- </div> <div>  Run  Debug </div>				
<b>Test run failed</b> Results: 0/1 passed; Item(s) checked: 1				
	Result	Test Name	Project	Error Message
<input checked="" type="checkbox"/>	Failed	ThreeFactorialIsSix	FactorialCalculatorTests	Assert.AreEqual failed. Expected:<6>. Actual:<3>.

New modification is required on `GetFactorialOf(int p)` method.


Hide Copy Code

```
public float GetFactorialOf(int p)
{
    if (p < 2)
        return 1;

    return p * GetFactorialOf(p-1);
}
```

Test Results				
<div>    pc@PC </div> <div>  Run  Debug </div>				
<b>Test run completed</b> Results: 4/4 passed; Item(s) checked: 0				
	Result	Test Name	Project	Error Message
<input type="checkbox"/>	Passed	ThreeFactorialIsSix	FactorialCalculatorTests	
<input type="checkbox"/>	Passed	OneFactorialIsOne	FactorialCalculatorTests	
<input type="checkbox"/>	Passed	TwoFactorialIsTwo	FactorialCalculatorTests	
<input type="checkbox"/>	Passed	ZeroFactorialIsOne	FactorialCalculatorTests	


And the solution is as follows. Now we can use this `FactorialCalculator` library anywhere we want. I used in a class library named `Calculator`.



[Hide](#) [Copy Code](#)

```
class Program
{
    static void Main(string[] args)
    {
        Factorial calculator = new Factorial();

        for (int i = 0; i < 14; i++)
        {
            Console.WriteLine(calculator.GetFactorialOf(i));
        }
    }
}
```



## Points of Interest

The most impressive aspect of TDD for me is that initially, there is no code and while **test** methods developing the required codes are created automatically. There is no need for planning the classes, no need to plan the variables and so on. Unnecessary operations are not implemented. We implement only requirements specification as needed. Everything is determined during the **test** period.

The other point is any **test** should not affect any other. And method implementations should not affect **test** results. For example, if one method is working correctly for one **test**, but working wrong other methods, then this is an undesired result.

Any changes of product methods require the running the **tests**. We did this during the application.

## History

This article shows us how to create unit **tests** and steps of the unit **testing** simply. And we developed an Factorial application. After the **test** methods, the mainclass generated and it is ready to use. If you can see the shortcomings of the application, you can modify the methods. But any change of application requires the running **tests** to be on.

## License

This article, along with any associated source code and files, is licensed under [The Code Project Open License \(CPOL\)](#)

## Share



## About the Author



**Bayram Üçüncü** <http://www.bayramucuncu.com>  
Software Developer  
Turkey 

## You may also be interested in...

[Test Driven / First Development by Example](#)

[Microsoft's Guide to Modern Dev/Test](#)

[Designing Application Using Test Driven Development](#)

[SAPrefs - Netscape-like Preferences Dialog](#)

[Learning Test Driven Development with TDD Katas](#)

[Generate and add keyword variations using AdWords API](#)

# Comments and Discussions

You must [Sign In](#) to use this message board.

Search Comments

Go

[First](#) [Prev](#) [Next](#)

## My vote of 4

**pradiprenushe** 27-Aug-12 1:42

good

[Sign In](#) · [View Thread](#) · [Permalink](#)

## Harika!

**Erol Esen** 7-Feb-12 11:19

Şahane bir makale olmuş. Hem Visual Studio'da unit test nasıl yazılır, hem de unit test ile algoritma'nın kendisini evrimsel bir şekilde yazımını gösteriyorsunuz. Büyük bir zevkle okudum. Tebrikler, ve teşekkürler.

Erol

*modified 7-Feb-12 17:34pm.*

[Sign In](#) · [View Thread](#) · [Permalink](#)

5.00/5 (1 vote)

## Re: Harika!

**Bayram Üçüncü** 7-Feb-12 19:11

Teşekkürler Erol Bey

[Sign In](#) · [View Thread](#) · [Permalink](#)

## Re: Harika!

**Bayram Üçüncü** 24-Jul-12 21:22

Teşekkürler Erol Bey Faydalı olabildiysem ne mutlu.

[Sign In](#) · [View Thread](#) · [Permalink](#)

## Re: Harika!

**Erol Esen** 1-Aug-12 3:54

Test driven yazılım hem yazılan programı doğrulamaya çalışıyor, hem de gereklileri. Verdiğiniz örnekte özyinelemeli mantığı TDD'nin ne kadar tabii bir şekilde yazıldığını da gösteriyor. Tekrar teşekkür ederim.



Erol

*modified 1-Aug-12 16:05pm.*

[Sign In](#) · [View Thread](#) · [Permalink](#)

---

## A few comments

**PeteBarber** 29-Jan-12 22:43

1. The first test should really be "can I create an instance of Factorial?" rather than assuming you can.
2. In the final program use prefix increment. Only ever use postfix increment when you need too, i.e. when the consumer of the return value needs the pre-incremented value.

[Sign In](#) · [View Thread](#) · [Permalink](#)

---

## Re: A few comments

**Bayram Üçüncü** 30-Jan-12 20:13

Thanks PereBarber.

Yes the first test could be "Can I create an instance of factorial". But I think the consumer program can be any name, or it can be a part of a Math class or so on....

[Sign In](#) · [View Thread](#) · [Permalink](#)

---

## My vote of 5

**Shahin Khorshidnia** 29-Jan-12 9:22

Noteworthy solution.

[Sign In](#) · [View Thread](#) · [Permalink](#)

---

## Re: My vote of 5

**Bayram Üçüncü** 30-Jan-12 20:09

Thanks Shahin

[Sign In](#) · [View Thread](#) · [Permalink](#)

5.00/5 (1 vote)

---

## Re: My vote of 5

**Shahin Khorshidnia** 30-Jan-12 21:40

sağ ol 😊

Do not criticise, if you don't have a better idea.

[Sign In](#) · [View Thread](#) · [Permalink](#)

1.00/5 (1 vote)

---

## real tips

**moiurbd** 27-Jan-12 18:52

this really useful and informative tips , for more details information . you can check here .

small business technology

Sign In · View Thread · Permalink

1.00/5 (7 votes)

Refresh

1

 General  News  Suggestion  Question  Bug  Answer  Joke  Praise  Rant  Admin

[Permalink](#) | [Advertise](#) | [Privacy](#) | [Terms of Use](#) | [Mobile](#)  
Web02 | 2.8.160621.1 | Last Updated 28 Jan 2012

Layout: [fixed](#) | [fluid](#)

Article Copyright 2012 by Bayram Üçüncü  
Everything else Copyright © [CodeProject](#), 1999-2016