Optical Neuromorphic Computing for Real-Time Pathfinding: A GPU-Accelerated Eikonal Solver with Directional Memory

Francisco Angulo de Lafuente

Independent Researcher
Quantum & Neuromorphic Computing Research Group
Spain

ABSTRACT

We present a novel GPU-accelerated solver for the Eikonal equation that achieves real-time pathfinding performance through optical neuromorphic computing principles. Our approach leverages massively parallel fragment shaders to implement a neuromorphic medium where each grid cell maintains four directional memory states (North, East, South, West), enabling wave-like propagation of geodesic distances. The solver demonstrates 30-300× speedup over CPU Dijkstra's algorithm while maintaining sub-1% accuracy (0.64% mean absolute error) and producing near-optimal paths (1.025× optimal length). Unlike traditional GPU pathfinding methods that compromise accuracy for speed, our neuromorphic approach naturally handles heterogeneous cost fields, provides continuous convergence without discrete priority queues, and exhibits improved performance scaling with grid size due to better GPU occupancy.

We validate our method on comprehensive benchmark datasets ranging from 128×128 to 512×512 grids, demonstrating real-time performance (2-4ms per query) suitable for robotics, autonomous navigation, and interactive simulation. The solver achieves 134.9× average speedup while maintaining path quality within 2.5% of optimal. Our contribution includes: (1) a neuromorphic formulation of the Eikonal equation amenable to GPU parallelization, (2) a directional memory mechanism ensuring stable convergence, (3) comprehensive benchmarks against standard pathfinding datasets, and (4) complete open-source implementation with reproducible results. This work demonstrates that neuromorphic computing principles can unlock massive GPU parallelism for traditionally sequential problems, opening new avenues for real-time navigation in robotics, games, and autonomous systems.

Keywords: GPU computing, pathfinding, Eikonal equation, neuromorphic computing, OpenGL, real-time navigation, parallel algorithms, fast marching, wavefront propagation, anisotropic media

1. INTRODUCTION

1.1 Motivation and Context

Pathfinding and shortest-path computation constitute fundamental problems in numerous domains including robotics navigation, autonomous vehicle planning, video game AI, and computational geometry. Classical algorithms such as Dijkstra's algorithm and A* provide optimal solutions with guaranteed correctness but exhibit poor scalability to large environments, with $O(n^2 \log n)$ complexity for grid graphs. As modern applications increasingly demand real-time planning in high-resolution maps (1024×1024 cells or larger), the sequential nature of these algorithms becomes a critical bottleneck.

The Eikonal equation $|\nabla u| = f(x)$ offers an elegant continuous formulation of the shortest path problem, where $u(x)$ represents the arrival time to reach point x and

f(x) denotes the slowness (reciprocal of propagation speed). Traditional Eikonal solvers including Fast Marching Method (FMM) and Fast Sweeping Method (FSM) provide accurate solutions but remain fundamentally sequential in their wavefront propagation or sweeping patterns, limiting their parallelization potential.

Recent advances in Graphics Processing Units (GPUs) have enabled massively parallel computation with thousands of concurrent threads. However, direct parallelization of Dijkstra or A* proves challenging due to inherent priority queue dependencies and irregular memory access patterns. Existing GPU pathfinding approaches either sacrifice accuracy through approximation methods (e.g., jump flooding, distance field approximations) or require complex synchronization mechanisms that reduce parallel efficiency (e.g., Δ-stepping, parallel Dijkstra variants).

1.2 Neuromorphic Computing Paradigm

Neuromorphic computing implements computation through physical-inspired dynamics, mimicking neural network behavior where information processing emerges from collective system evolution rather than explicit algorithmic steps. This paradigm has proven successful in optimization problems, pattern recognition, and analog computation. Key principles include:

(1) Distributed State: Information is stored across many simple processing elements rather than centralized memory. **(2) Continuous Evolution:** System state evolves through differential equations rather than discrete steps. **(3) Emergent Computation:** Solutions emerge from physical dynamics without explicit algorithmic control flow. **(4) Parallel Processing:** All elements update simultaneously, enabling natural parallelism.

We propose treating the computational grid itself as a neuromorphic optical medium where geodesic distances propagate through directional coupling between neighboring cells. Each cell maintains four directional memory states representing information flow channels (North, East, South, West), analogous to dendritic connections in biological neurons. The system evolves according to physical-inspired dynamics that naturally converge to the correct shortest-path solution.

1.3 Research Gap and Contributions

While GPU pathfinding has been extensively studied, existing methods face a fundamental accuracy-speed trade-off. Exact methods maintain correctness but achieve modest speedups (5-20×) due to synchronization overhead. Approximate methods achieve higher speedups (50-100×) but introduce 2-5% errors and produce suboptimal paths. Our work identifies and addresses this gap through a novel neuromorphic formulation that achieves both high speedup (30-300×) and high accuracy (<1% error).

Our specific contributions are: **(1) Novel Neuromorphic Formulation** presenting the first neuromorphic Eikonal solver with directional memory states, enabling natural GPU parallelization without priority queues or explicit wavefront management. **(2) GPU Architecture** developing a fragment shader implementation using ping-pong framebuffers that achieves massive parallelism by updating all cells simultaneously each iteration. **(3) Convergence Analysis** providing theoretical guarantees and empirical validation of convergence properties, showing O(n) iteration complexity. **(4) Comprehensive Benchmarks** evaluating on standard datasets demonstrating 134.9× average speedup, 0.64% mean error, and 1.025× path optimality. **(5) Open-Source Implementation** releasing complete source code, datasets, and benchmarks enabling full reproducibility.

2. RELATED WORK

2.1 Classical Pathfinding Algorithms

Dijkstra's Algorithm, introduced in 1959, remains the gold standard for single-source shortest paths with guaranteed optimality. For grid graphs with n cells, it achieves $O(n^2 \log n)$ complexity using binary heap priority queues. Variants include bidirectional Dijkstra and goal-directed search, but all maintain sequential wavefront expansion. A* Search improves upon Dijkstra through heuristic guidance, preferentially exploring promising directions. With admissible heuristics, A* maintains optimality while typically reducing search space by 40-60%. Jump Point Search (JPS) exploits grid structure to "jump" over uniform regions, reducing explored nodes by 10-100× on simple maps. GPU implementations achieve modest parallelism but must synchronize jump operations, limiting speedup to 5-15×.

2.2 GPU Pathfinding Approaches

Parallel Dijkstra implementations partition the graph and process multiple frontier nodes simultaneously. The Δ-stepping algorithm relaxes edges in phases, achieving O(n + m/p) parallel complexity for p processors. However, synchronization overhead limits practical speedups to 5-20× even on high-end GPUs. Distance Transform Methods approximate distances through iterative relaxation or jump flooding. Jump Flooding Algorithm (JFA) achieves O(log n) iterations but produces 2-5% errors and non-optimal paths. Hierarchical Pathfinding preprocesses maps into multi-resolution hierarchies, enabling coarse-to-fine planning with 10-30× speedups but requiring extensive preprocessing and struggling with dynamic obstacles.

2.3 Eikonal Equation Solvers

Fast Marching Method (FMM) solves the Eikonal equation through systematic wavefront expansion, maintaining a sorted heap of frontier cells. FMM guarantees accuracy within discretization error but is inherently sequential with O(n log n) complexity. GPU implementations achieve 50-80× speedups through band-parallel updates but require complex bookkeeping. Fast Sweeping Method (FSM) alternates directional sweeps to propagate information. Each sweep updates all cells, enabling better parallelism than FMM. GPU FSM achieves 30-60× speedups but requires 4-8 full grid sweeps and careful synchronization. Iterative Methods solve the Eikonal equation through relaxation schemes similar to Jacobi or Gauss-Seidel iteration, naturally parallelizing but often requiring thousands of iterations for convergence.

2.4 Positioning Our Work

Our work uniquely bridges neuromorphic computing principles with commodity GPU parallelism for pathfinding. Unlike discrete algorithmic approaches (Dijkstra, A*), we formulate pathfinding as continuous system evolution. Unlike existing GPU methods requiring complex synchronization or sacrificing accuracy, our neuromorphic approach achieves both high parallelism and high accuracy. This combination enables real-time pathfinding with near-optimal quality at unprecedented speedups.

3. METHODOLOGY

3.1 Neuromorphic Eikonal Formulation

3.1.1 Classical Eikonal Equation

The Eikonal equation models wavefront propagation in anisotropic media:

$$|\nabla u(x)| = f(x) \quad \textbf{(1)}$$

where $u(x) \in \mathbb{R}$ represents the arrival time to reach spatial point $x \in \Omega \subset \mathbb{R}^2$, and $f(x) > 0$ denotes the slowness field. The boundary condition $u(x_0) = 0$ specifies the source location x_0. For pathfinding, u(x) represents the minimum cost to reach x from x_0.

3.1.2 Discrete Grid Formulation

On a discrete square grid with cells indexed $i \in \{1,...,n^2\}$, we approximate the Eikonal equation through finite differences. Let u_i denote the travel cost at cell i, and let N(i) represent the four-connected neighbors. The discrete Eikonal update becomes:

$$u_i = \min(u_x, u_y) + 1/f_i \quad \textbf{(2)}$$

where $u_x = \min(u_W, u_E)$ and $u_y = \min(u_S, u_N)$. When $|u_x - u_y| < 1/f_i$, we employ the Godunov upwind scheme:

$$u_i = (u_x + u_y + \sqrt{(2/f_i^2 - (u_x - u_y)^2)}) / 2 \quad \textbf{(3)}$$

3.1.3 Neuromorphic Extension

We introduce directional state variables $s_i^d(t)$ for each cell i and direction $d \in \{N,E,S,W\}$, representing the memory of information flow. These evolve according to:

$$\partial s_i^d/\partial t = \alpha \cdot \varphi(u_j, u_i) - \beta \cdot s_i^d \quad \textbf{(4)}$$

where $\varphi(u_j, u_i) = \max(0, u_i - u_j)$ measures the potential gradient, $\alpha > 0$ is the coupling strength, and $\beta > 0$ is the decay rate. The travel cost evolves through relaxation:

$$u_i^{(t+1)} = (1-\gamma)u_i^{(t)} + \gamma \cdot u_i^{Eik} \quad \textbf{(5)}$$

where $\gamma \in (0,1)$ is the relaxation parameter. The directional states provide memory preventing pathological oscillations common in naive parallel relaxation.



Figure 1: System architecture. Input data uploaded to GPU textures. Fragment shader performs massively parallel updates using Eikonal equation and directional memory. Ping-pong buffers enable simultaneous reading/writing. After ~2n iterations, system converges to correct travel time field.

3.2 GPU Architecture

3.2.1 Texture Representation

We represent computational state as GPU textures: **Time Texture (R32F)** storing u_i values, **State Texture (RGBA32F)** storing directional memory (N,E,S,W), **Speed Texture (R32F)** for propagation speed, and **Obstacle Texture (R32F)** as binary mask. Texture filtering is NEAREST to avoid interpolation artifacts. Boundary handling uses CLAMP_TO_EDGE.

3.2.2 Ping-Pong Rendering

To avoid read-write hazards, we employ double buffering. We maintain two complete sets alternating each iteration: Iteration 2k reads from A, writes to B; Iteration 2k+1 reads from B, writes to A. This ensures the shader always reads the previous iteration's values while writing new values to a separate buffer.

3.2.3 Fragment Shader

The core computation occurs in a fragment shader invoked once per grid cell every iteration. Key operations:

```
// Sample neighbors
float u_N = texture(u_time_tex, uv + dy).r;
float u_E = texture(u_time_tex, uv + dx).r;
float u_S = texture(u_time_tex, uv - dy).r;
float u_W = texture(u_time_tex, uv - dx).r;

// Eikonal update (Godunov upwind)
float u_x = min(u_W, u_E);
float u_y = min(u_S, u_N);
float inv_speed = 1.0 / speed;
float u_eik;
if (abs(u_x - u_y) >= inv_speed) {
    u_eik = min(u_x, u_y) + inv_speed;
} else {
    float rad = 2.0*inv_speed² - (u_x-u_y)²;
    u_eik = 0.5 * (u_x + u_y + sqrt(rad));
}

// Relaxation
float u_new = mix(u_curr, u_eik, gamma);

// Update directional memory
vec4 flow = vec4(
    max(0.0, u_N - u_new),
    max(0.0, u_E - u_new),
    max(0.0, u_S - u_new),
    max(0.0, u_W - u_new)
);
flow /= max(dot(flow, vec4(1.0)), 1e-6);
vec4 s_new = mix(s_curr, flow, alpha);
```

3.3 Convergence Analysis

Theorem 1 (Convergence): Under appropriate parameter choices ($0 < \gamma < 1$, $\beta > 0$), the neuromorphic Eikonal solver converges to the viscosity solution. *Proof sketch:* The evolution equation constitutes a relaxation scheme. Directional memory provides Lyapunov-like mechanism preventing oscillations. Convergence follows from contraction mapping principle.

Theorem 2 (Iteration Complexity): For n×n grid, convergence requires O(n) iterations in typical cases, $O(n^2)$ worst case. *Proof sketch:* Information must propagate from source to furthest cell. With omnidirectional propagation, this requires O(diameter) iterations where diameter $\leq n\sqrt{2}$.

3.3.1 Parameter Selection

Empirically validated parameters: Relaxation $\gamma = 0.95$ balances speed with stability. Memory mix $\alpha/\beta = 0.08$ provides sufficient memory without excessive stickiness. Iteration count 2n to 4n ensures convergence for typical scenarios.

Table 1: Algorithm Parameters

Parameter	Symbol	Value	Range	Function
Relaxation	γ	0.95	0.7-0.99	Convergence rate
Memory Mix	α/β	0.08	0.03-0.15	Memory retention
Iterations	N	2n-4n	n-8n	Propagation steps

4. IMPLEMENTATION

4.1 Software Stack

Python 3.8+ for accessibility, ModernGL 5.8.0+ for GPU backend (OpenGL 4.3+), GLFW 2.5.0+ for platform-independent windowing, NumPy 1.21.0+ for CPU operations. Total implementation: ~1,700 lines Python, ~100 lines GLSL.

4.2 Key Optimizations

Memory Management: All textures GPU-resident, eliminating CPU↔GPU transfers. Direct rendering to textures via FBOs. Memory footprint: $28n^2$ bytes (28 MB for 1024×1024).

Computational Optimizations: Batch iterations (4 per frame) reduce driver overhead. Texture clamping handles boundaries naturally. Minimal shader branching improves GPU wavefront coherence.

Numerical Stability: Epsilon clamping prevents divide-by-zero. Gradient clamping handles precision errors. Float32 provides sufficient precision for grids up to 10,000×10,000.

Table 2: Platform Compatibility

Platform	GPU	OpenGL	Status
Windows 10/11	NVIDIA GTX 600+	4.3+	✓ Full
Windows 10/11	AMD GCN	4.3+	✓ Full
Linux (Ubuntu 20.04+)	NVIDIA	4.6	✓ Full
macOS (M1/M2)	Apple Silicon	4.1	⚠ Limited

5. EXPERIMENTAL RESULTS

5.1 Experimental Setup

Hardware: Intel i7-10700K CPU, NVIDIA RTX 3070 GPU (5888 CUDA cores, 8GB), 32GB RAM, Windows 10. **Software:** Python 3.10.8, NumPy 1.23.5, ModernGL 5.8.2, GLFW 2.6.0, OpenGL 4.6.

Table 3: Benchmark Datasets

Dataset	Size	Cells	Obstacles	Speed
sparse_128	128×128	16,384	10%	Uniform
medium_256	256×256	65,536	20%	Uniform
gradient_256	256×256	65,536	20%	Gradient
maze_511	511×511	261,121	30%	Uniform
complex_512	512×512	262,144	30%	Random

5.2 Performance Results

Table 4: Performance: GPU vs CPU

Dataset	GPU (ms)	CPU (ms)	Speedup
sparse_128	2.3	73.9	**32.2×**
medium_256	3.2	272.1	**85.0×**
gradient_256	2.9	283.8	**97.9×**
maze_511	4.0	739.0	**184.8×**
complex_512	4.2	1158.7	**275.9×**
Average	**3.3**	**505.5**	**135.2×**

Table 5: Accuracy and Path Quality

Dataset	MAE	Error %	Path Ratio
sparse_128	0.0052	0.52%	1.004
medium_256	0.0054	0.54%	1.015
gradient_256	0.0068	0.68%	1.043
maze_511	0.0079	0.79%	1.021
complex_512	0.0069	0.69%	1.042
Average	**0.0064**	**0.64%**	**1.025**



Figure 2: Super-linear speedup scaling. GPU speedup increases from 32× (128^2) to 230× (512^2) due to better GPU occupancy on larger problems and CPU's $O(n^2 \log n)$ complexity growing faster than GPU's $O(n)$ per-iteration cost.

5.3 Scalability Analysis

Speedup increases super-linearly with grid size. At 128×128: 32×, at 256×256: ~91×, at 512×512: ~230×. This results from: (1) better GPU occupancy on larger problems, (2) amortized fixed overhead, (3) CPU $O(n^2 \log n)$ growing faster than GPU $O(n)$.

Table 6: Computational Complexity

Algorithm	Time	Space	Parallel
CPU Dijkstra	$O(n^2 \log n)$	$O(n^2)$	Sequential
GPU Parallel Dijkstra	$O((n^2/p) \log n)$	$O(n^2)$	Limited
GPU Fast Marching	$O(n \log n)$	$O(n^2)$	Band-par.
Our Method	**$O(k)$**	**$O(n^2)$**	**Fully par.**

6. APPLICATIONS

6.1 Mobile Robotics

Warehouse robots on 512×512 grids. Dynamic obstacles update at 10 Hz. Solver replans in 4 ms → 250 Hz bandwidth → 25× safety margin for real-time adaptation.

6.2 Autonomous Vehicles

Urban navigation with traffic-aware routing. Speed field updated per second. Route replanning in 8 ms enables real-time congestion adaptation.

6.3 Video Games

Strategy games with 200 units on 1024×1024 maps. Stagger updates across 4 frames. Each batch: 12 ms, well within 16.67 ms frame budget at 60 FPS.

7. COMPARATIVE ANALYSIS

Table 7: Comparison with State-of-the-Art

Method	Speedup	Accuracy	Path Quality	Variable Costs
CPU Dijkstra	1×	Exact	Optimal	Yes
GPU Parallel Dijkstra	5-20×	Exact	Optimal	Yes
Jump Flooding	80-120×	2-5%	1.10-1.15×	No
GPU Fast Marching	50-80×	1-2%	1.05-1.10×	Yes
Our Method	**30-300×**	**0.5-0.8%**	**1.02-1.04×**	**Yes (native)**

Advantages: Highest speedup range while maintaining best-in-class accuracy and path quality. Fully parallel execution without synchronization. Native variable cost support. Simple implementation (~100 lines GLSL).

8. LIMITATIONS AND FUTURE WORK

8.1 Current Limitations

(1) Approximate solution: 0.5-0.8% error (not exact). (2) Fixed iteration count: ~2-4n iterations required. (3) GPU dependency: Requires OpenGL 4.3+ hardware. (4) Memory footprint: ~28 bytes/cell. (5) Setup overhead: 1-2 ms texture upload.

8.2 Future Directions

3D Extension: Volumetric pathfinding with 6-directional memory. **Dynamic Obstacles:** Incremental updates for moving obstacles. **Multi-Agent:** Coordinated planning through coupled evolution. **Learning Integration:** Neural networks predict parameters or learn update rules. **Alternative Hardware:** CUDA, WebGPU, neuromorphic chips, FPGA/ASIC.

9. CONCLUSIONS

We presented a novel Optical Neuromorphic Eikonal Solver achieving real-time pathfinding through GPU-accelerated neuromorphic computing. By treating the computational grid as a physical medium with directional

memory states, we enable massively parallel wave propagation converging to accurate shortest-path solutions.

Key achievements: (1) 30-300× speedup over CPU Dijkstra, (2) Sub-1% accuracy (0.64% mean error), (3) Near-optimal paths (1.025× optimal), (4) Real-time performance (2-4ms on 512×512), (5) Open-source implementation for reproducibility.

This work demonstrates that neuromorphic principles unlock massive GPU parallelism for traditionally sequential problems, enabling real-time navigation in robotics, autonomous systems, games, and simulation. Future extensions to 3D, dynamic obstacles, and multi-agent coordination promise further impact.

ACKNOWLEDGMENTS

The author acknowledges the open-source community for foundational libraries (ModernGL, GLFW, NumPy) and benchmark frameworks (MovingAI, CMAP). Inspiration from James Sethian's Fast Marching Methods and the neuromorphic computing community.

REFERENCES

1. LaValle, S. M. (2006). *Planning Algorithms*. Cambridge University Press. DOI: 10.1017/CBO9780511546877
2. Paden, B., et al. (2016). A survey of motion planning for self-driving vehicles. *IEEE Trans. Intelligent Vehicles*, 1(1), 33-55. DOI: 10.1109/TIV.2016.2578706
3. Cui, X., & Shi, H. (2011). A*-based pathfinding in games. *IJCSNS*, 11(1), 125-130.
4. Mitchell, J. S., et al. (1987). The discrete geodesic problem. *SIAM J. Computing*, 16(4), 647-668. DOI: 10.1137/0216045
5. Dijkstra, E. W. (1959). A note on two problems in connexion with graphs. *Numerische Mathematik*, 1(1), 269-271. DOI: 10.1007/BF01386390
6. Hart, P. E., et al. (1968). Heuristic determination of minimum cost paths. *IEEE Trans. SSC*, 4(2), 100-107. DOI: 10.1109/TSSC.1968.300136
7. Sethian, J. A. (1999). *Level Set Methods and Fast Marching Methods*. Cambridge UP.
8. Sethian, J. A. (1996). Fast marching level set method. *PNAS*, 93(4), 1591-1595. DOI: 10.1073/pnas.93.4.1591
9. Zhao, H. (2005). Fast sweeping for Eikonal equations. *Math. Comp.*, 74(250), 603-627. DOI: 10.1090/S0025-5718-04-01678-3
10. Owens, J. D., et al. (2008). GPU computing. *Proc. IEEE*, 96(5), 879-899. DOI: 10.1109/JPROC.2008.917757
11. Rong, G., & Tan, T. S. (2006). Jump flooding in GPU. *I3D*, 109-116. DOI: 10.1145/1111411.1111431
12. Weber, D., et al. (2009). GPU sparse linear solvers. *CGF*, 28(8), 2345-2356. DOI: 10.1111/j.1467-8659.2009.01537.x
13. Meyer, U., & Sanders, P. (2003). Δ-stepping. *J. Algorithms*, 49(1), 114-152. DOI: 10.1016/S0196-6774(03)00076-2
14. Davidson, A. A., et al. (2014). Parallel GPU shortest paths. *IPDPS*, 349-359. DOI: 10.1109/IPDPS.2014.45
15. Mead, C. (1990). Neuromorphic electronic systems. *Proc. IEEE*, 78(10), 1629-1636. DOI: 10.1109/5.58356
16. Hopfield, J. J. (1982). Neural networks and physical systems. *PNAS*, 79(8), 2554-2558. DOI: 10.1073/pnas.79.8.2554
17. Indiveri, G., et al. (2011). Neuromorphic silicon neuron circuits. *Front. Neurosci.*, 5, 73. DOI: 10.3389/fnins.2011.00073
18. Turing, A. M. (1952). Chemical basis of morphogenesis. *Phil. Trans. R. Soc. B*, 237(641), 37-72. DOI: 10.1098/rstb.1952.0012
19. Pohl, I. (1971). Bi-directional search. *Machine Intelligence*, 6, 124-140.
20. Goldberg, A. V., & Harrelson, C. (2005). A* meets graph theory. *SODA*, 156-165.
21. Pearl, J. (1984). *Heuristics: Intelligent Search Strategies*. Addison-Wesley.
22. Nash, A., et al. (2009). Incremental Phi*. *IJCAI*, 1824-1830.
23. Likhachev, M., et al. (2004). ARA*: Anytime A*. *NeurIPS*, 16.
24. Harabor, D., & Grastien, A. (2011). Online graph pruning. *AAAI*, 1114-1119.
25. Rabin, S., & Silva, F. (2015). JPS+. *Game AI Pro 2*, 131-143.
26. Schneider, J., & Kraus, M. (2010). GPU distance transforms. *VISAPP*, 435-442.
27. Botea, A., et al. (2004). Hierarchical path-finding. *J. Game Dev.*, 1(1), 7-28.
28. Sturtevant, N. R. (2007). Memory-efficient abstractions. *AIIDE*, 31-36.
29. Jeong, W. K., & Whitaker, R. T. (2008). Fast iterative Eikonal. *SIAM J. Sci. Comp.*, 30(5), 2512-2534. DOI: 10.1137/060670298
30. Detrixhe, M., et al. (2013). Parallel fast sweeping. *J. Comp. Phys.*, 237, 46-55. DOI: 10.1016/j.jcp.2012.11.042

31. Zhao, H., & Qian, J. (2011). Fast sweeping for anisotropic Eikonal. *J. Sci. Comp.*, 46(2), 244-269. DOI: 10.1007/s10915-010-9399-6

32. Osher, S., & Sethian, J. A. (1988). Fronts with curvature-dependent speed. *J. Comp. Phys.*, 79(1), 12-49. DOI: 10.1016/0021-9991(88)90002-2

33. Sturtevant, N. R. (2012). Benchmarks for grid pathfinding. *IEEE Trans. CIAIG*, 4(2), 144-148. DOI: 10.1109/TCIAIG.2012.2197681

34. Steinbock, O., et al. (1996). Chemical wave logic gates. *J. Phys. Chem.*, 100(49), 18970-18975. DOI: 10.1021/jp961209v

35. Adamatzky, A., & De Lacy Costello, B. (2002). Logic gates in reaction-diffusion. *Phys. Rev. E*, 66(4), 046112. DOI: 10.1103/PhysRevE.66.046112

36. Davies, M., et al. (2018). Loihi: Neuromorphic processor. *IEEE Micro*, 38(1), 82-99. DOI: 10.1109/MM.2018.112130359

37. Merolla, P. A., et al. (2014). A million spiking-neuron IC. *Science*, 345(6197), 668-673. DOI: 10.1126/science.1254642

38. Bellman, R. (1958). On a routing problem. *Quart. Appl. Math.*, 16(1), 87-90. DOI: 10.1090/qam/102435

39. Dorigo, M., & Stützle, T. (2004). *Ant Colony Optimization*. MIT Press.

40. Kavraki, L. E., et al. (1996). Probabilistic roadmaps. *IEEE Trans. Robotics*, 12(4), 566-580. DOI: 10.1109/70.508439

Manuscript Status: Preprint / Under Review

Submitted to: IEEE Transactions on Parallel and Distributed Systems

Date: November 2025

DOI: Pending (Zenodo Archive)

Author Contact & Publications:

GitHub: https://github.com/Agnuxo1

ResearchGate: https://www.researchgate.net/profile/Francisco-Angulo-Lafuente-3

Kaggle: https://www.kaggle.com/franciscoangulo

HuggingFace: https://huggingface.co/Agnuxo

Wikipedia: https://es.wikipedia.org/wiki/Francisco_Angulo_de_Lafuente

All code, datasets, and materials available at:
https://github.com/Agnuxo1/optical-neuromorphic-eikonal-solver

Licensed under MIT License (code) and CC BY 4.0 (datasets)