

## Content

<b>Traffic Shifting</b> .....	2
<b>Request Routing</b> .....	4
<b>Fault Injection</b> .....	7
Fix bug: transfer all traffics to reviews:v3 .....	9
Injecting an HTTP abort fault .....	10
Clean up .....	11
<b>Circuit Breaking</b> .....	12

# Traffic Shifting

## 1. Preparation: install Kubernetes Gateway API CRDs

```
kubectl apply --server-side -f https://github.com/kubernetes-sigs/gateway-api/releases/download/v1.4.0/experimental-install.yaml
```

```
PS D:\istio-1.28.1> kubectl apply --server-side -f gateway-api/experimental-install.yaml
customresourcedefinition.apiextensions.k8s.io/backendtlspolicies.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/gatewayclasses.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/gateways.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/grpcroutes.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/httproutes.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/referencegrants.gateway.networking.k8s.io serverside-applied
Warning: unrecognized format "int32"
Warning: unrecognized format "int64"
customresourcedefinition.apiextensions.k8s.io/tcproutes.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/tlsroutes.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/udproutes.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/xbackendtrafficpolicies.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/xlistenersets.gateway.networking.k8s.io serverside-applied
customresourcedefinition.apiextensions.k8s.io/xmeshes.gateway.networking.k8s.io serverside-applied
```

## 2. Apply weight-based routing

### 2.1. Route all traffic to the v1 version

```
kubectl apply -f samples/bookinfo/gateway-api/route-reviews-v1.yaml
```

### 2.2. Transfer 50% of the traffic from reviews:v1 to reviews:v3

```
kubectl apply -f samples/bookinfo/gateway-api/route-reviews-50-v3.yaml
```

```
PS D:\istio-1.28.1> kubectl apply -f samples/bookinfo/gateway-api/route-reviews-v1.yaml
httproute.gateway.networking.k8s.io/reviews configured
PS D:\istio-1.28.1> kubectl apply -f samples/bookinfo/gateway-api/route-reviews-50-v3.yaml
httproute.gateway.networking.k8s.io/reviews configured
```


### 2.3. Wait a few seconds for the new rules to propagate and then confirm the rule was replaced

```
kubectl get httproute reviews -o yaml
```

```

PS D:\istio-1.28.1> kubectl get httproute reviews -o yaml
apiVersion: gateway.networking.k8s.io/v1
kind: HTTPRoute
metadata:
  annotations:
    kubernetes.io/last-applied-configuration: |
      {"apiVersion":"gateway.networking.k8s.io/v1","kind":"HTTPRoute","metadata":{"annotations":{"name":"reviews","namespace":"default"},"spec":{"parentRefs":[{"group":"","kind":"Service","name":"reviews","port":9080}], "rules":[{"backendRefs":[{"name":"reviews-v1","port":9080,"weight":50}, {"name":"reviews-v3","port":9080,"weight":50}]}]}}}
      creationTimestamp: "2025-12-16T09:13:38Z"
      generation: 2
      name: reviews
      namespace: default
      resourceVersion: "133396"
      uid: e28512bd-3eb4-4e57-b5e2-a68e13af10fc
spec:
  parentRefs:
  - group: ""
    kind: Service
    name: reviews
    port: 9080
  rules:
  - backendRefs:
    - group: ""
      kind: Service
      name: reviews-v1
      port: 9080
      weight: 50
    - group: ""
      kind: Service
      name: reviews-v3
      port: 9080
      weight: 50
  matches:
  - path:
      type: PathPrefix
      value: /
status:
  parents:
  - conditions:
    - lastTransitionTime: "2025-12-17T15:24:19Z"
      message: Route was valid
      observedGeneration: 2
      reason: Accepted
      status: "True"
      type: Accepted
    - lastTransitionTime: "2025-12-17T15:52:49Z"
      message: All references resolved
      observedGeneration: 2
      reason: ResolvedRefs
      status: "True"
      type: ResolvedRefs
    controllerName: istio.io/gateway-controller
  parentRef:
    group: ""
    kind: Service
    name: reviews
    port: 9080

```



## The Comedy of Errors

Wikipedia Summary: The Comedy of Errors is one of **William Shakespeare's** early plays. It is his shortest and one of his most farcical comedies, with a major part of the humour coming from slapstick and mistaken identity, in addition to puns and word play.

[Learn more about Istio](#) →

### Book Details

ISBN-10	Publisher	Pages	Type	Language
1234567890	PublisherA	200	paperback	English

### Book Reviews

★★★★★

"An extremely entertaining play by Shakespeare. The slapstick humour is refreshing!"



Reviewer1

Reviews served by: reviews-v3-d587fc9d7-magpl

★★★★☆

"Absolutely fun and entertaining. The play lacks thematic depth when compared to other plays by Shakespeare."



Reviewer2

Reviews served by: reviews-v3-d587fc9d7-magpl

## 2.4. Route 100% of the traffic to reviews:v3

```
kubectl apply -f samples/bookinfo/gateway-api/route-reviews-v3.yaml
```

```

PS D:\istio-1.28.1> kubectl apply -f samples/bookinfo/gateway-api/route-reviews-v3.yaml
httproute.gateway.networking.k8s.io/reviews configured

```

```


```

# Request Routing

## 1. Route to version 1

### 1.1. Apply virtual services that will route all traffic to v1 of each microservice

```
kubectl apply -f samples/bookinfo/networking/virtual-service-all-v1.yaml
```

```
PS D:\istio-1.28.1> kubectl apply -f samples/bookinfo/networking/virtual-service-all-v1.yaml
virtualservice.networking.istio.io/productpage created
virtualservice.networking.istio.io/reviews created
virtualservice.networking.istio.io/ratings created
virtualservice.networking.istio.io/details created
```

### 1.2. Display the defined routes

```
kubectl get virtualservices -o yaml
```

```
PS D:\istio-1.28.1> kubectl get virtualservices -o yaml
apiVersion: v1
items:
- apiVersion: networking.istio.io/v1
  kind: VirtualService
  metadata:
    annotations:
      kubectl.kubernetes.io/last-applied-configuration: |
        {"apiVersion":"networking.istio.io/v1","kind":"VirtualService","metadata":{"annotations":{},"name":"details","namespace":"default"},"spec":{"hosts":["details"],"http":[{"route":[{"destination":{"host":"details","subset":"v1"}}]}]}}
    creationTimestamp: "2025-12-24T15:01:52Z"
    generation: 1
    name: details
    namespace: default
    resourceVersion: "2311"
    uid: 40deb4a2-e0cb-476d-bf0c-94ebdac3aa8a
  spec:
    hosts:
    - details
    http:
    - route:
        - destination:
            host: details
            subset: v1
- apiVersion: networking.istio.io/v1
  kind: VirtualService
  metadata:
    annotations:
      kubectl.kubernetes.io/last-applied-configuration: |
        {"apiVersion":"networking.istio.io/v1","kind":"VirtualService","metadata":{"annotations":{},"name":"productpage","namespace":"default"},"spec":{"hosts":["productpage"],"http":[{"route":[{"destination":{"host":"productpage","subset":"v1"}}]}]}}
    creationTimestamp: "2025-12-24T15:01:52Z"
    generation: 1
    name: productpage
    namespace: default
    resourceVersion: "2308"
    uid: 91b18747-2bbd-4230-999c-c27f2fabe5a0
  spec:
    hosts:
    - productpage
    http:
    - route:
        - destination:
            host: productpage
            subset: v1
- apiVersion: networking.istio.io/v1
  kind: VirtualService
  metadata:
    annotations:
      kubectl.kubernetes.io/last-applied-configuration: |
        {"apiVersion":"networking.istio.io/v1","kind":"VirtualService","metadata":{"annotations":{},"name":"ratings","namespace":"default"},"spec":{"hosts":["ratings"],"http":[{"route":[{"destination":{"host":"ratings","subset":"v1"}}]}]}}
    creationTimestamp: "2025-12-24T15:01:52Z"
    generation: 1
    name: ratings
    namespace: default
    resourceVersion: "2310"
    uid: 24a800f0-a3d5-408f-9cf7-788d31f9e7a3
  spec:
    hosts:
    - ratings
    http:
    - route:
        - destination:
            host: ratings
            subset: v1
```

```

- apiVersion: networking.istio.io/v1
  kind: VirtualService
  metadata:
    annotations:
      ons: {}, "name": "reviews", "namespace": "default"}, "spec": [{"hosts": ["reviews"], "http": [{"route"
: [{"destination": {"host": "reviews", "subset": "v1"}}]}]}]}
    creationTimestamp: "2025-12-24T15:01:52Z"
    generation: 1
    name: reviews
    namespace: default
    resourceVersion: "2309"
    uid: 0ea145a2-c244-448b-9108-8fdc9f12df1a
  spec:
    hosts:
    - reviews
    http:
    - route:
        - destination:
            host: reviews
            subset: v1
  kind: List
  metadata:
    resourceVersion: ""

```

## 2. Test the new routing configuration

Notice that the reviews part of the page displays with no rating stars, no matter how many times we refresh. This is because we configured Istio to route all traffic for the reviews service to the version reviews:v1 and this version of the service does not access the star ratings service.

BookInfo Sample [Sign In](#)

## The Comedy of Errors

Wikipedia Summary: The Comedy of Errors is one of **William Shakespeare's** early plays. It is his shortest and one of his most farcical comedies, with a major part of the humour coming from slapstick and mistaken identity, in addition to puns and word play.

[Learn more about Istio](#)

### Book Details

ISBN-10	Publisher	Pages	Type	Language
1234567890	PublisherA	200	paperback	English

### Book Reviews

**"An extremely entertaining play by Shakespeare. The slapstick humour is refreshing!"**

**Reviewer1**  
Reviews served by: reviews-v1-8cf7b9cc5-9wfwk

**"Absolutely fun and entertaining. The play lacks thematic depth when compared to other plays by Shakespeare."**

**Reviewer2**  
Reviews served by: reviews-v1-8cf7b9cc5-9wfwk

## 3. Route based on user identity

### 3.1. Enable user-based routing

```
kubectl apply -f samples/bookinfo/networking/virtual-service-reviews-test-v2.yaml
```

```

PS D:\istio-1.28.1> kubectl apply -f samples/bookinfo/networking/virtual-service-reviews-test-v2.yaml
virtualservice.networking.istio.io/reviews configured

```

### 3.2. Confirm the rule is created

```
kubectl get virtualservice reviews -o yaml
```

```
PS D:\istio-1.28.1> kubectl get virtualservice reviews -o yaml
apiVersion: networking.istio.io/v1
kind: VirtualService
metadata:
  annotations: {}
  name: reviews
  namespace: default
  spec:
    hosts:
    - reviews
    http:
    - match:
      - headers:
          end-user:
            exact: jason
        route:
          destination:
            host: reviews
            subset: v2
      - route:
          destination:
            host: reviews
            subset: v1
    creationTimestamp: "2025-12-24T15:01:52Z"
    generation: 2
    name: reviews
    namespace: default
    resourceVersion: "2964"
    uid: 0ea145a2-c244-448b-9108-8fdc9f12df1a
spec:
  hosts:
  - reviews
  http:
  - match:
    - headers:
        end-user:
          exact: jason
      route:
        destination:
          host: reviews
          subset: v2
    - route:
        destination:
          host: reviews
          subset: v1
```

3.3. On the /productpage of the Bookinfo app, log in as user jason. The star ratings appear next to each review.

Bookinfo Sample

jason  
Signed out

## The Comedy of Errors

Wikipedia Summary: The Comedy of Errors is one of **William Shakespeare's** early plays. It is his shortest and one of his most farcical comedies, with a major part of the humour coming from slapstick and mistaken identity, in addition to puns and word play.

[Learn more about Istio](#)

ISBN-10	Publisher	Pages	Type	Language
1234567890	PublisherA	200	paperback	English

### Book Reviews

★★★★★

"An extremely entertaining play by Shakespeare. The slapstick humour is refreshing!"

Reviewer1  
Reviews served by: reviews-v2-67d565655f-1c7pm

★★★★☆

"Absolutely fun and entertaining. The play lacks thematic depth when compared to other plays by Shakespeare."

Reviewer2  
Reviews served by: reviews-v2-67d565655f-1c7pm

3.4. Log in as another user and the stars are gone. This is because traffic is routed to reviews:v1 for all users except Jason.

Bookinfo Sample

alice  
Signed out

## The Comedy of Errors

Wikipedia Summary: The Comedy of Errors is one of **William Shakespeare's** early plays. It is his shortest and one of his most farcical comedies, with a major part of the humour coming from slapstick and mistaken identity, in addition to puns and word play.

[Learn more about Istio](#)

ISBN-10	Publisher	Pages	Type	Language
1234567890	PublisherA	200	paperback	English

### Book Reviews

"An extremely entertaining play by Shakespeare. The slapstick humour is refreshing!"

Reviewer1  
Reviews served by: reviews-v1-8cf708cc3-9afak

"Absolutely fun and entertaining. The play lacks thematic depth when compared to other plays by Shakespeare."

Reviewer2  
Reviews served by: reviews-v1-8cf708cc3-9afak

# Fault Injection

## 1. Injecting an HTTP delay fault

### 1.1. Create a fault injection rule to delay traffic coming from the test user jason

```
kubectl apply -f samples/bookinfo/networking/virtual-service-ratings-test-delay.yaml
```

### 1.2. Confirm the rule was created

```
kubectl get virtualservice ratings -o yaml
```

```
PS D:\istio-1.28.1> kubectl apply -f samples/bookinfo/networking/virtual-service-ratings-test-delay.yaml
virtualservice.networking.istio.io/ratings configured
PS D:\istio-1.28.1> kubectl get virtualservice ratings -o yaml
apiVersion: networking.istio.io/v1
kind: VirtualService
metadata:
  annotations:
    kubectl.kubernetes.io/last-applied-configuration: |
      {"apiVersion":"networking.istio.io/v1","kind":"VirtualService","metadata":{"annotations":{},"name":"ratings","namespace":"default"},"spec":
  creationTimestamp: "2025-12-24T15:01:52Z"
  generation: 2
  name: ratings
  namespace: default
  resourceVersion: "3550"
  uid: 24a800f0-a3d5-408f-9cf7-788d31f9e7a3
spec:
  hosts:
  - ratings
  http:
  - fault:
      delay:
        fixedDelay: 7s
        percentage:
          value: 100
      match:
      - headers:
          end-user:
            exact: jason
        route:
        - destination:
            host: ratings
            subset: v1
      - route:
        - destination:
            host: ratings
            subset: v1
PS D:\istio-1.28.1> []
```

## 2. Testing the delay configuration

On the /productpage web page, log in as user Jason. There is a problem that the Reviews section displays an error message: “Sorry, product reviews are currently unavailable for this book.”

Open the *Developer Tools* menu and open the Network tab. It can be seen that the page actually loads in about 6 seconds.

BookInfo Sample

Sign out

# The Comedy of Errors

Wikipedia Summary: The Comedy of Errors is one of **William Shakespeare's** early plays. It is his shortest and one of his most farcical comedies, with a major part of the humour coming from slapstick and mistaken identity, in addition to puns and word play.

[Learn more about Istio](#)

Book Details

ISBN-10	Publisher	Pages	Type	Language
1234567890	PublisherA	200	paperback	English

Error fetching product reviews  
Sorry, product reviews are currently unavailable for this book.

Fetch/XHR

文档

CSS

JS

字体

Img

媒体

渲染

子资源

Wasm

其他

1,000 ms

2,000 ms

3,000 ms

4,000 ms

5,000 ms

6,000 ms

7,000 ms

名称	状态	类型	发起程序	大小	时间	操作者
productpage	200	docu...	其他	8.1 k	6.01 秒	
izy.png	304	png	productpage:4	232 B	14 ms	
tailwind.css	304	script	productpage:9	238 B	10 ms	

While logging in as any other user, there is no problem.



# The Comedy of Errors

Wikipedia Summary: The Comedy of Errors is one of **William Shakespeare's** early plays. It is his shortest and one of his most farcical comedies, with a major part of the humour coming from slapstick and mistaken identity, in addition to puns and word play.

[Learn more about Istio](#) →

## Book Details

ISBN-10	Publisher	Pages	Type	Language
1234567890	PublisherA	200	paperback	English

## Book Reviews

"An extremely entertaining play by Shakespeare. The slapstick humour is refreshing!"

"Absolutely fun and entertaining. The play lacks thematic depth when compared to other plays."


Reason: As expected, the 7s delay I introduced doesn't affect the reviews service because the timeout between the reviews and ratings service is hard-coded at 10s. However, there is also a hard-coded timeout between the productpage and the reviews service, coded as 3s + 1 retry for 6s total. As a result, the productpage call to reviews times out prematurely and throws an error after 6s.



## Fix bug: transfer all traffics to reviews:v3

```
kubectl apply -f samples/bookinfo/networking/virtual-service-reviews-v3.yaml
```

```
kubectl apply -f samples/bookinfo/networking/virtual-service-reviews-v3.yaml
virtualservice.networking.istio.io/reviews configured
```



Then delete the following rules and add necessary rules to make preparation for another way.

```
kubectl delete -f samples/bookinfo/networking/virtual-service-reviews-v3.yaml
```

```
kubectl delete -f samples/bookinfo/networking/virtual-service-ratings-test-delay.yaml
```

```
PS D:\istio-1.28.1> kubectl delete -f samples/bookinfo/networking/virtual-service-reviews-v3.yaml
virtualservice.networking.istio.io "reviews" deleted from default namespace
```

```
PS D:\istio-1.28.1> kubectl delete -f samples/bookinfo/networking/virtual-service-ratings-test-delay.yaml
virtualservice.networking.istio.io "ratings" deleted from default namespace
```

```
kubectl apply -f samples/bookinfo/networking/virtual-service-all-v1.yaml
```

```
kubectl apply -f samples/bookinfo/networking/virtual-service-reviews-test-v2.yaml
```

# Injecting an HTTP abort fault

1. Create a fault injection rule to send an HTTP abort for user jason

```
kubectl apply -f samples/bookinfo/networking/virtual-service-ratings-test-abort.yaml
```

2. Confirm the rule was created

```
kubectl get virtualservice ratings -o yaml
```

```
PS D:\istio-1.28.1> kubectl apply -f samples/bookinfo/networking/virtual-service-ratings-test-abort.yaml
virtualservice.networking.istio.io/ratings configured
PS D:\istio-1.28.1> kubectl get virtualservice ratings -o yaml
apiVersion: networking.istio.io/v1
kind: VirtualService
metadata:
  annotations:
    kubectl.kubernetes.io/last-applied-configuration: |
      {"apiVersion":"networking.istio.io/v1","kind":"VirtualService","metadata":{"annotations":{},"name":"ratings","namespace":"
default"},"spec":{"hosts":["ratings"],"http":[{"fault":{"abort":{"httpStatus":500,"percentage":{"value":100}}},"match":[{"header
aders":{"end-user":{"exact":"jason"}}}],{"route":[{"destination":{"host":"ratings","subset":"v1"}}]}]}]}
creationTimestamp: "2025-12-24T15:38:09Z"
generation: 2
name: ratings
namespace: default
resourceVersion: "5601"
uid: 3c477996-20d4-4c37-9fea-d8e2991810c4
spec:
  hosts:
  - ratings
  http:
  - fault:
      abort:
        httpStatus: 500
        percentage:
          value: 100
      match:
      - headers:
          end-user:
            exact: jason
      route:
      - destination:
          host: ratings
          subset: v1
    - route:
        destination:
          host: ratings
          subset: v1
PS D:\istio-1.28.1> 
```

3. Test the abort configuration

On the /productpage, log in as user jason. The page loads immediately and the “Ratings service is currently unavailable” message appears. However, while logging in another user, there is no problem.

# The Comedy of Errors

Wikipedia Summary: The Comedy of Errors is one of **William Shakespeare's** early plays. It is his shortest and one of his most farcical comedies, with a major part of the humour coming from slapstick and mistaken identity, in addition to puns and word play.

[Learn more about Istio](#) →

## Book Details

ISBN-10	Publisher	Pages	Type	Language
1234567890	PublisherA	200	paperback	English

## Book Reviews

Ratings service is currently unavailable

Ratings service is currently unavailable

"An extremely entertaining play by Shakespeare. The slapstick

"Absolutely fun and entertaining. The play lacks thematic depth when

# The Comedy of Errors

Wikipedia Summary: The Comedy of Errors is one of **William Shakespeare's** early plays. It is his shortest and one of his most farcical comedies, with a major part of the humour coming from slapstick and mistaken identity, in addition to puns and word play.

[Learn more about Istio](#) →

## Book Details

ISBN-10	Publisher	Pages	Type	Language
1234567890	PublisherA	200	paperback	English

## Book Reviews

"An extremely entertaining play by Shakespeare. The slapstick humour is refreshing!"

"Absolutely fun and entertaining. The play lacks thematic depth when compared to other plays"

## Clean up

Remove the application routing rules

```
kubectrl delete -f samples/bookinfo/networking/virtual-service-ratings-test-abort.yaml
```

```
kubectrl delete -f samples/bookinfo/networking/virtual-service-all-v1.yaml
```

```
kubectrl delete -f samples/bookinfo/networking/virtual-service-reviews-test-v2.yaml
```

# Circuit Breaking

1. Preparation: deploy the httpbin service

```
kubectl apply -f samples/httpbin/httpbin.yaml
```

```
PS D:\istio-1.28.1> kubectl apply -f samples/httpbin/httpbin.yaml
serviceaccount/httpbin created
service/httpbin created
deployment.apps/httpbin created
```

2. Configuring the circuit breaker

- 2.1. Create a destination rule to apply circuit breaking settings when calling the httpbin service

```
@
apiVersion: networking.istio.io/v1
kind: DestinationRule
metadata:
  name: httpbin
spec:
  host: httpbin
  trafficPolicy:
    connectionPool:
      tcp:
        maxConnections: 1
      http:
        http1MaxPendingRequests: 1
        maxRequestsPerConnection: 1
    outlierDetection:
      consecutive5xxErrors: 1
      interval: 1s
      baseEjectionTime: 3m
      maxEjectionPercent: 100
"@ | kubectl apply -f -
```

```
> @
>> apiVersion: networking.istio.io/v1
>> kind: DestinationRule
>> metadata:
>>   name: httpbin
>> spec:
>>   host: httpbin
>>   trafficPolicy:
>>     connectionPool:
>>       tcp:
>>         maxConnections: 1
>>       http:
>>         http1MaxPendingRequests: 1
>>         maxRequestsPerConnection: 1
>>     outlierDetection:
>>       consecutive5xxErrors: 1
>>       interval: 1s
>>       baseEjectionTime: 3m
>>       maxEjectionPercent: 100
>> "@ | kubectl apply -f -
destinationrule.networking.istio.io/httpbin created
```

## 2.2. Verify the destination rule was created correctly

```
kubectl get destinationrule httpbin -o yaml
```

```
PS D:\istio-1.28.1> kubectl get destinationrule httpbin -o yaml
kind: DestinationRule
metadata:
  annotations:
    kubectl.kubernetes.io/last-applied-configuration: |
      {"apiVersion":"networking.istio.io/v1","kind":"DestinationRule","metadata":{"annotations":{},"name":"httpbin","namespace":"default"},"spec":{"host":"httpbin","trafficPolicy":{"connectionPool":{"http":{"http1MaxPendingRequests":1,"maxRequestsPerConnection":1},"tcp":{"maxConnections":1}},"outlierDetection":{"baseEjectionTime":"3m","consecutive5xxErrors":1,"interval":"1s","maxEjectionPercent":100}}}}
  creationTimestamp: "2025-12-24T15:50:46Z"
  generation: 1
  name: httpbin
  namespace: default
  resourceVersion: "6669"
  uid: c76493f7-3b66-4399-9e8c-47b3c82db8e8
spec:
  host: httpbin
  trafficPolicy:
    connectionPool:
      http:
        http1MaxPendingRequests: 1
        maxRequestsPerConnection: 1
      tcp:
        maxConnections: 1
    outlierDetection:
      baseEjectionTime: 3m
      consecutive5xxErrors: 1
      interval: 1s
      maxEjectionPercent: 100
```

## 3. Add a client

### 3.1. Deploy the fortio service

```
kubectl apply -f samples/httpbin/sample-client/fortio-deploy.yaml
```

```
PS D:\istio-1.28.1> kubectl apply -f samples/httpbin/sample-client/fortio-deploy.yaml
service/fortio created
deployment.apps/fortio-deploy created
```

3.2. Log in to the client pod and use the fortio tool to call httpbin. Pass in curl to indicate that you just want to make one call

```
$FORTIO_POD = kubectl get pods -l app=fortio -o jsonpath="{.items[0].metadata.name}"
```

```
kubectl exec $FORTIO_POD -c fortio -- `
```

```
  /usr/bin/fortio curl -quiet http://httpbin:8000/get
```

```
PS D:\istio-1.28.1> $FORTIO_POD = kubectl get pods -l app=fortio -o jsonpath="{.items[0].metadata.name}"
```

```
PS D:\istio-1.28.1> kubectl exec $FORTIO_POD -c fortio -- `
>> /usr/bin/fortio curl -quiet http://httpbin:8000/get
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-origin: *
content-type: application/json; charset=utf-8
date: Wed, 24 Dec 2025 15:54:14 GMT
content-length: 621
x-envoy-upstream-service-time: 17

{
  "args": {},
  "headers": {
    "Host": [
      "httpbin:8000"
    ],
    "User-Agent": [
      "fortio.org/fortio-1.69.5"
    ],
    "X-Envoy-Attempt-Count": [
      "1"
    ],
    "X-Forwarded-Client-Cert": [
      "By=spiffe://cluster.local/ns/default/sa/httpbin;Hash=6792d6efa59395298146472044962944fdb72b966c1959546d2c2fc90d227b9;Subject=\"\";URI=s
      piffe://cluster.local/ns/default/sa/default"
    ],
    "X-Forwarded-Proto": [
      "http"
    ],
    "X-Request-Id": [
      "9a38ec56-b8a9-92f9-b338-7268c0221671"
    ]
  },
  "method": "GET",
  "origin": "127.0.0.6:58799",
  "url": "http://httpbin:8000/get"
}
```

#### 4. Tripping the circuit breaker

##### 4.1. Call the service with two concurrent connections (-c 2) and send 20 requests (-n 20)

```
kubectrl exec $FORTIO_POD -c fortio -- /usr/bin/fortio load -c 2 -qps 0 -n 20 -loglevel
```

```
Warning http://httpbin:8000/get
```

```
PS D:\istio-1.28.1> kubectrl exec $FORTIO_POD -c fortio -- /usr/bin/fortio load -c 2 -qps 0 -n 20 -loglevel Warning http://httpbin:8000/get
{"ts":1766591791.020536,"level":"info","r":1,"file":"logger.go","line":298,"msg":"Log level is now 3 Warning (was 2 Info)"}
Fortio 1.69.5 running at 0 queries per second, 16->16 procs, for 20 calls: http://httpbin:8000/get
Starting at max qps with 2 thread(s) [gomax 16] for exactly 20 calls (10 per thread + 0)
{"ts":1766591791.031570,"level":"warn","r":24,"file":"http_client.go","line":1151,"msg":"Non ok http code","code":503,"status":"HTTP/1.1 503",
thread":1,"run":0}
{"ts":1766591791.049417,"level":"warn","r":23,"file":"http_client.go","line":1151,"msg":"Non ok http code","code":503,"status":"HTTP/1.1 503",
thread":0,"run":0}
{"ts":1766591791.054960,"level":"warn","r":24,"file":"http_client.go","line":1151,"msg":"Non ok http code","code":503,"status":"HTTP/1.1 503",
thread":1,"run":0}
{"ts":1766591791.059391,"level":"warn","r":23,"file":"http_client.go","line":1151,"msg":"Non ok http code","code":503,"status":"HTTP/1.1 503",
thread":0,"run":0}
{"ts":1766591791.064635,"level":"warn","r":24,"file":"http_client.go","line":1151,"msg":"Non ok http code","code":503,"status":"HTTP/1.1 503",
thread":1,"run":0}
{"ts":1766591791.067886,"level":"warn","r":23,"file":"http_client.go","line":1151,"msg":"Non ok http code","code":503,"status":"HTTP/1.1 503",
thread":0,"run":0}
{"ts":1766591791.070397,"level":"warn","r":24,"file":"http_client.go","line":1151,"msg":"Non ok http code","code":503,"status":"HTTP/1.1 503",
thread":1,"run":0}
Ended after 55.16757ms : 20 calls. qps=362.53
Aggregated Function Time : count 20 avg 0.0051633463 +/- 0.004388 min 0.000534812 max 0.01750904 sum 0.103266926
# range, mid point, percentile, count
>= 0.000534812 <= 0.001 , 0.000767406 , 20.00, 4
> 0.002 <= 0.003 , 0.0025 , 25.00, 1
> 0.003 <= 0.004 , 0.0035 , 55.00, 6
> 0.004 <= 0.005 , 0.0045 , 60.00, 1
> 0.005 <= 0.006 , 0.0055 , 70.00, 2
> 0.006 <= 0.007 , 0.0065 , 80.00, 2
> 0.007 <= 0.008 , 0.0075 , 90.00, 2
> 0.016 <= 0.017509 , 0.0167545 , 100.00, 2
# target 50% 0.00383333
# target 99% 0.0173581
# target 99.9% 0.0174939
Error cases : count 7 avg 0.0024938977 +/- 0.002266 min 0.000534812 max 0.007262156 sum 0.017457284
# range, mid point, percentile, count
>= 0.000534812 <= 0.001 , 0.000767406 , 57.14, 4
> 0.003 <= 0.004 , 0.0035 , 85.71, 2
> 0.007 <= 0.00726216 , 0.00713108 , 100.00, 1
# target 50% 0.000922469
# target 75% 0.003625
# target 90% 0.00707865
# target 99% 0.00724381
# target 99.9% 0.00726032
# Socket and IP used for each connection:
[0] 4 socket used, resolved to 10.96.231.194:8000, connection timing : count 4 avg 0.00018458125 +/- 5.097e-05 min 0.00010723 max 0.000248875
sum 0.000738325
[1] 5 socket used, resolved to 10.96.231.194:8000, connection timing : count 5 avg 0.0002621546 +/- 8.394e-05 min 0.000142467 max 0.000377875
sum 0.001310773
Connection time (s) : count 9 avg 0.00022767756 +/- 8.096e-05 min 0.00010723 max 0.000377875 sum 0.002049098
Sockets used: 9 (for perfect keepalive, would be 2)
Uniform: false, Jitter: false, Catchup allowed: true
IP addresses distribution:
10.96.231.194:8000: 9
Code 200 : 13 (65.0 %)
Code 503 : 7 (35.0 %)
Response Header Sizes : count 20 avg 159.3 +/- 116.9 min 0 max 246 sum 3186
Response Body/Total Sizes : count 20 avg 647.3 +/- 298.1 min 241 max 867 sum 12946
All done 20 calls (plus 0 warmup) 5.163 ms avg, 362.5 qps
```

##### 4.2. Bring the number of concurrent connections up to 3

```
kubectrl exec $FORTIO_POD -c fortio -- /usr/bin/fortio load -c 3 -qps 0 -n 30 -loglevel
```

```
Warning http://httpbin:8000/get
```

```
kubectl exec $FORTIO POD -c istio-proxy --
```



```
pilot-agent request GET stats |
```

```
Select-String httpbin |
```

```
Select-String pending
```

```
PS D:\istio-1.28.1> kubectl exec $FORTIO_POD -c istio-proxy -- `
>> pilot-agent request GET stats |
>> Select-String httpbin |
>> Select-String pending
```

```
cluster.outbound|8000||httpbin.default.svc.cluster.local;.circuit_breakers.default.re
maining_pending: 1
cluster.outbound|8000||httpbin.default.svc.cluster.local;.circuit_breakers.default.rq
_pending_open: 0
cluster.outbound|8000||httpbin.default.svc.cluster.local;.circuit_breakers.high.rq_pe
nding_open: 0
cluster.outbound|8000||httpbin.default.svc.cluster.local;.upstream_rq_pending_active:
0
cluster.outbound|8000||httpbin.default.svc.cluster.local;.upstream_rq_pending_failure
_eject: 0
cluster.outbound|8000||httpbin.default.svc.cluster.local;.upstream_rq_pending_overflow:
26
cluster.outbound|8000||httpbin.default.svc.cluster.local;.upstream_rq_pending_total:
25
```

It shows 26 for the `upstream_rq_pending_overflow` value which means 26 calls so far have been flagged for circuit breaking.

## 5. Clean up

### 5.1. Remove the rules:

```
kubectl delete destinationrule httpbin
```

### 5.2. Shutdown the httpbin service and client:

```
kubectl delete -f samples/httpbin/sample-client/fortio-deploy.yaml
```

```
kubectl delete -f samples/httpbin/httpbin.yaml
```

```
PS D:\istio-1.28.1> kubectl delete destinationrule httpbin
destinationrule.networking.istio.io "httpbin" deleted from default namespace
PS D:\istio-1.28.1> kubectl delete -f samples/httpbin/sample-client/fortio-deploy.yaml
service "fortio" deleted from default namespace
deployment.apps "fortio-deploy" deleted from default namespace
PS D:\istio-1.28.1> kubectl delete -f samples/httpbin/httpbin.yaml
serviceaccount "httpbin" deleted from default namespace
service "httpbin" deleted from default namespace
deployment.apps "httpbin" deleted from default namespace
```