

Database Tables

Product groups

ANALYSIS	16
BDE	27
CAQ	178
HLS	324
KERNEL	334
LLE	451
MDE	477
MLE	531
MPL	547
PDV	614
PEP	658
PZE	662
WRM	761
ZKS	812

Tables

ade_aas_lz	833
ade_agst_lz	833
ade_arbplanfolgen	27
ade_auftragmengen	28
ade_auftragsarten	29
ade_auftragsfolgen	38
ade_auftragsgruppe	40
ade_auftragsnetz	41
ade_grund_texte	43
ade_grund_zuord	44
ade_lst_codes	45
ade_ortsgrpwechsel	46
ade_pers_komp	47
ade_prot_zusatz	833
ade_protokoll	48

ade_seriennummern	59
ade_status_texte	60
ade_status_zuord	61
ade_verarb_codes	68
ana_datasup	16
ana_operat	17
ana_order	18
ana_pdatref	19
ana_pdatref_pparam	614
ana_pdatref_pparam_datasup	615
ana_pdatref_pparam_last_spec	616
ana_pdatref_pparam_spec	617
ana_pdatref_pparam_spec_change	618
ana_pdatref_sequence_spec	619
ana_pparam	620
ana_process_comp_curve_fine	20
ana_process_comp_curve_rough	21
ana_process_data_char	621
ana_process_data_decimal	622
ana_serial	623
ana_serial_test	624
ana_stad_wplace_operat_perio	22
ana_stat_wplace_operat_perio	23
ana_tag	625
ana_tag_process_data_char	626
ana_tag_process_data_decimal	627
ana_tag_value	628
ana_unit	24
ana_wplace	25
ana_wplace_operat_perio	26
anmeld_tab	833
antritt	662
arbeitsmittel	663
arbplan_bestand	77

arbplan_hyinfo	84
arbplan_leistung	85
arbplan_mlst_hy	88
arbplan_verwalt	92
arbplan_zusatz	94
auftrag_status	95
auftrags_bestand	105
auftrags_leistung	124
auftrags_zusatz	129
bearb_masch	833
bedienpos	131
bm_konten	132
buffer_tab	833
caq_abteilung	178
caq_analaus_eint	180
caq_analauswahl	181
caq_analkat	182
caq_artikel	183
caq_ausw_param	188
caq_auswertung	189
caq_bereich	190
caq_bew_ausw_grp	191
caq_bew_auswahl	192
caq_bew_bewert	193
caq_bew_element	195
caq_bew_kat_fir	197
caq_bew_katalog	198
caq_bew_klasse	199
caq_ctrl_freig	200
caq_ctrl_plan	201
caq_ctrl_pplan	203
caq_dokuliste	834
caq_dokus	204
caq_dyhis_ppktmm	207

caq_dynn_aql	208
caq_dynn_methode	209
caq_dynn_pniveau	210
caq_dynn_stprein	211
caq_dynnorm	212
caq_dynprfscharf	213
caq_dynps_eint	214
caq_dynueb_eint	215
caq_dynuebergang	216
caq_einheit	217
caq_fhlanal	218
caq_fhlanalbaum	221
caq_firma	222
caq_formular	224
caq_gis	834
caq_kosten	225
caq_kostenart	226
caq_masskat	228
caq_massn	229
caq_mdi_channel	231
caq_mdi_res_zuord	233
caq_mengabh_prf	834
caq_merk_zusatz	234
caq_merkmal	236
caq_msa_statistics	248
caq_mst_wechsel	249
caq_nest	834
caq_numpool	250
caq_pan_zusatz	253
caq_pauanmeld	255
caq_paukonf	256
caq_paukop	257
caq_paumm_ausp	629
caq_paumwert	261

caq_paunumm	264
caq_paustich	265
caq_person	271
caq_pma_bestand	834
caq_pma_lager	835
caq_pma_sollkonto	835
caq_pma_vorgang	835
caq_pmv_arbeitspl	835
caq_pmv_einsatz	835
caq_pmv_pruefm	835
caq_pmv_pruefung	836
caq_ppktm_info	273
caq_ppktm_info_afo	274
caq_ppktm_interv	275
caq_ppktm_iv_afo	276
caq_pplkop	277
caq_pplzert	836
caq_pplzmer	836
caq_prplatz	280
caq_pruefanf	281
caq_prueffreq	836
caq_pruefmatrix	286
caq_pzustand	836
caq_qails_vormerk	287
caq_qm_mnr	289
caq_rek_zuord	290
caq_rekauft	291
caq_rekdetail	293
caq_sammelanf	836
caq_spezliste	296
caqstattyp	304
caq_status	305
caq_usr_zuord	837
caq_verantwortl	306

caq_vert_eint	308
caq_verteiler	309
caq_werkzzuord	837
caq_wf_conn_point	837
caq_wf_connect	837
caq_wf_element	837
caq_wf_formel	838
caq_workflow	838
caq_zusatz_feld	310
change_log	311
cons_masch	838
ereig_komp	838
ereignis	477
esk_event_cfg	334
esk_event_msg	338
esk_event_msgdet	340
esk_event_msgext	342
esk_event_reg	343
esk_event_reg_res	345
esk_event_reg_var	346
esk_function	347
esk_setup	348
event_adea	133
event_adep	146
event_dlg_data	349
event_los	547
event_mde	482
event_mlb	555
event_pdv	838
event_pp	562
event_res	761
fehlgr_berecht	664
fehlgruende	665
fehlgrund_gruppe	666

fehlzeiten	667
fehlzeiten_prio	669
fkt_profil	350
fkt_tab	351
fmea_eval_nbr_catalog	312
fmea_eval_nbr_entry	313
fmea_master	314
fmea_net	317
fmea_risk_matrix	318
fmea_structure_element	319
glzeitjhresmodell	671
glzeittagestyp	672
hls_pers_schichtm	324
hls_rwmatrix	325
hls_setup	326
hy_db_bench	352
hy_dd_prot	353
hy_forms	838
hy_gruppen	159
hy_gruppen_zuord	161
hy_ih_meldcode	839
hy_ih_meldung	839
hy_ih_person	839
hy_path	355
hy_protokoll	356
hy_size_stats	357
hy_usr_prop	839
hy_usr_table	839
hy_zykl	492
hybuch	358
hybuch_zusatz	369
hyd_datamanagement	371
hyd_einheiten	373
hyd_einheiten_umr	374

hyd_expr	375
hyd_history	376
hyd_ini	377
hyd_ini_data	378
hyd_license_status	379
hyd_lock	380
hyd_logging	381
hyd_logging_cfg	383
hyd_logging_data	384
hyd_logging_keys	385
hyd_nummernkreise	386
hyd_parklayout	387
hyd_printdesign	388
hyd_prn_schema	389
hyd_prn_schema_det	390
hyd_prndesign_cfg	391
hyd_prnlayout	393
hyd_product	840
hyd_scheduler	395
hyd_userdata	397
hyd_userexit	398
hyd_userfieldcfg	399
hyd_userfielddef	400
hyd_userfieldelem	402
hyd_vwe_stat	570
hydialog	403
hydialogbuttons	405
hydialogfields	406
hydialogwf	409
hydra_user	840
hyinfo	411
hymeld	675
hysap_dist_mod	531
hysap_inbound_ctrl	533

hysap_inbound_data	535
hysap_logsys	536
hysap_logsys_cfg	537
hysap_out_ctrl	539
hysap_out_data	541
hysap_pm_object	840
hysap_protokoll	542
hysap_status	543
hysap_tidmgt	544
hz_atgen	572
hz_tpe	574
hz_typen	575
jahranwes	676
jahrfehl	677
kategorien	678
kfg_dialog_event	840
kfg_erfassung	840
konsolen_status	840
kontoaenderung	679
kontogrenze	680
kostenstellen	682
kstst_tab	841
la_beziehung	683
lager_hz	841
lbz_term_zuord	580
lhnstatusjhrmod	684
lle_lart_regel	451
lle_leist_grp	453
lle_leistberzuord	457
lle_leistgrp_tag	458
lle_lstgrp_zuord	460
lle_pnr_tag	461
lle_tls	463
lle_tls_ag	465

lle_zuschlaege	468
llesetup	470
lohnarten	685
lohnarten_aw	688
lohnarten_zuord	689
lohnartengruppe	695
lohnartenliste	696
lohnstat_familie	697
los_attribute	581
los_bestand	584
los_status	593
los_zuordnung	594
masch_linien_zuord	493
masch_lohngruppen	162
masch_term_zuord	494
maschinen	495
maschinen_detail	510
maschinen_status	511
maschinen_zaeher	515
mat_matpuf	596
mat_mattyp	597
mat_puffer	598
mat_verw_einschr	600
mat_zul_ein_material	601
material_arten	603
mde_feiertage	517
meister_prot	163
meldeliste	698
meldungen	699
mlst_hy	604
moaw_per_par	700
moaw_periode	702
monat_aw	703
monatlohnarten_aw	707

mpl_beziehungen	609
mpl_setup	611
mz_stklasse	518
pdv_eingriff	841
pdv_event_cfg	632
pdv_event_prot	633
pdv_logic_chan	635
pdv_merkmal	841
pdv_messinfo	841
pdv_messinfo_ausw	841
pdv_messkanal	842
pdv_messreihe	842
pdv_messreihe_ausw	842
pdv_messreihe_imp	842
pdv_messreihe_qse	842
pdv_messwert	843
pdv_messwert_ausw	843
pdv_messwert_imp	843
pdv_messwert_komp	843
pdv_messwert_qse	843
pdv_messzusatz	843
pdv_protokoll	844
pdv_pruefmerkmal	844
pdv_pruefplan	844
pdv_pruefplan_idx	844
pdv_spc	638
pdv_status	844
pep_masch_belegung	658
pep_qual_maschine	659
pep_qual_person	660
pep_qualifikation	661
pers_merken	164
persauswertparm	708
persfkt_profil	413

persfkt_tab	414
personalakte	712
personalstamm	845
personen	415
pnr_change	474
pps_bestand	165
pps_leistung	172
pps_zusatz	175
produkt_merkmal	845
prozess_param	519
pze_az_intervalle	713
pze_bez_pause	715
pze_entlohnung	716
pze_feiertage	718
pze_info_par	719
pze_konten	721
pze_pers_daten	722
pze_perstagtyp	724
pze_pst_var_kfg	726
pze_tnr_info_konfig	732
pze_ubez_pause	734
pze_url_anspruch	735
pze_ztnw_liste	736
pze_ztnw_spalte	738
pzebuchung	739
pzt_kenn	741
r_los_zuordnung	612
res_attribute	769
res_bedarfszuord	770
res_belege	771
res_bestand	774
res_familien	780
res_fertigung_var	327
res_masch_dncfam	781

res_massnahmen	782
res_ress_artikel	845
res_ress_belegung	783
res_ress_typen	784
res_status	785
res_status_assign	788
res_status_booking	790
res_status_recording	793
res_status_text	796
res_status_type	798
res_status_zuord	800
res_stueckliste	802
res_typen	803
res_wartungen	806
sap_pp_conf	176
sap_setup	545
schichtrythmus	744
setup	423
software_status	430
st_attribut	745
status_zusatz	177
stempelsaetze	747
stg_ir_multiple_assessed	322
stg_ir_single_measured	323
stg_process_data_block_id	640
stg_process_data_block_id_ps	641
stg_process_data_single_id	642
stg_process_data_tag_block_id	643
stg_process_data_tag_single_id	644
stg_process_spec_block_id	645
stg_process_spec_block_id_ps	646
stg_process_spec_single_id	647
stoer_tab_hierarc	521
stoer_tabelle	522

stoertexte	525
sys_service	431
sys_service_periodic_log	432
system_a_index	845
system_j_kap_mod	845
system_j_mod	526
system_p_index	845
system_t_kap_mod	846
system_t_mod	527
tagesauswertung	750
terminal_status	433
terminals	438
tnt_columns	648
tnt_headers	652
tnt_table_repo	656
user_profil	332
user_profil_zuord	333
user_setup	443
user_tab	445
user_tab_history	447
v_res_status_booking	809
vab_berechtigung	448
vab_profil	449
vab_tab	450
woaw_per_par	753
woaw_periode	754
zeit_kto	755
zeitspanne_aw	756
zeitumstellung	846
zks_ausweis	812
zks_ausweis_gruppe	815
zks_ausweis_zuord	816
zks_ereignis	817
zks_feiertag	818

zks_freischaltung	819
zks_kalender	820
zks_konf_azz	821
zks_konf_zzz	822
zks_raumzonen	823
zks_raumzonen_prot	824
zks_status	825
zks_zeitzonen	827
zks_zugang	828
zks_zugang_gruppe	831
zks_zz_bereich	832
zugberechtigung	759
zuggruppe	760
zuschlags_kfg	476

1. ANALYSIS

1.1. ana_datasup

Table name: ana_datasup		Product: ANALYSIS	
Designation: Data suppliers (analysis data)		Description: This table contains data suppliers of the analysis data pool. * Notes Data suppliers are used to differ the data origin. * Keys id (technical key) data_supplier_name (business key)	
Column name	Column designation	Type	Description
data_supplier_name	Data supplier name	char(50)	
id	Technical ID	serial	

1.2. ana_operat

Table name: ana_operat		Product: ANALYSIS	
Designation: Operations (analysis data)		Description: This table contains operations of the analysis data pool.	
		* Keys id (technical key) mes_operation_name (business key)	
Column name	Column designation	Type	Description
id	Technical ID	bigserial	
mes_operation_name	MES operation name	char(50)	
operation_id	Operation ID	bigint	
operation_name	Operation name	char(50)	
order_id	Reference to process data - order- (analysis data)	bigint	

1.3. ana_order

Table name: ana_order		Product: ANALYSIS	
Designation: Orders (analysis data)		Description: This table contains orders of the analysis data pool.	
		* Keys id (technical key) mes_operation_name (business key)	
Column name	Column designation	Type	Description
id	Technical ID	bigserial	
order_id	Order ID	bigint	
order_name	Order name	char(50)	

1.4. ana_pdatref

Table name: ana_pdatref		Product: ANALYSIS	
Designation: Process data reference (analysis data)		Description: This table contains process data references of the analysis data pool. * Notes Process data reference are used to abstract places, where process data is captured. With this feature you can simple add other informations as the workplace. Example: Combination of workplace, robot cell and cavity. * Keys id (technical key) wplace_id (business key) *logical connection to other tables ana_wplace (ana_wplace.id = ana_pdatref.wplace_id)	
Column name	Column designation	Type	Description
id	Technical ID	serial	
wplace_id	Reference to workplace (analysis data)	integer	

1.5. ana_process_comp_curve_fine

Table name: ana_process_comp_curve_fine		Product: ANALYSIS	
Designation: Fine compressed process data curve		Description: This table contains fine compressed curve of numerical process parameters of the analysis data pool. * Keys acquisition_time, pdatref_pparam_id (business key) *logical connection to other tables ana_pdatref_pparam(ana_pdatref_pparam.id = ana_process_comp_curve_fine.process_param_id)	
Column name	Column designation	Type	Description
acquisition_time	Acquisition time	datetime	
decimal_value	Numeric process value	float	
pdatref_pparam_id	Reference to process data reference - process parameter	bigint	

1.6. ana_process_comp_curve_rough

Table name: ana_process_comp_curve_rough		Product: ANALYSIS	
Designation: Rough compressed process data curve		Description: This table contains rough compressed curve of numerical process parameters of the analysis data pool. * Keys acquisition_time, pdatref_pparam_id (business key) *logical connection to other tables ana_pdatref_pparam(ana_pdatref_pparam.id = ana_process_comp_curve_rough.process_param_id)	
Column name	Column designation	Type	Description
acquisition_time	Acquisition time	datetime	
decimal_value	Numeric process value	float	
pdatref_pparam_id	Reference to process data reference - process parameter	bigint	

1.7. ana_stad_wplace_operat_perio

Table name: ana_stad_wplace_operat_perio		Product: ANALYSIS	
Designation: Compressed statistical values of the work processes		Description: This table contains compressed statistical values of the work processes .	
		*Note	
		* Keys id(technical key) wplace_operat_perio_id (business key)	
		*logical connection to other tables	
Column name	Column designation	Type	Description
aggregation_status	Compression status	smallint	0 compressed
aggregation_time_end	Compression end time	datetime	
aggregation_time_start	Compression start time	datetime	
id	Technical ID	bigserial	
wplace_operat_perio_id	Reference to refrence process data - workplace - operation - registered time (Analysis Data)	bigint	

1.8. ana_stat_wplace_operat_perio

Table name: ana_stat_wplace_operat_perio		Product: ANALYSIS	
Designation: Statistical values of the work processes		Description: This table contains statistical values of the work processes .	
		*Note	
		* Keys	
		stad_wplace_operat_perio_id, pparam_id (business key)	
		stad_wplace_operat_perio_id (business key)	
		pparam_id(business key)	
		*logical connection to other tables	
		TODO	
Column name	Column designation	Type	Description
pparam_id	ref	int	
stad_wplace_operat_perio_id	ref	bigint	
stat_average	Average	float	TODO
stat_count	Number of	integer	TODO
stat_maximum	Maximum of	float	TODO
stat_minimum	Minimum of	float	TODO
stat_sum	Sum of	float	TODO
stat_sum2	Sum of	float	TODO

1.9. ana_unit

Table name: ana_unit		Product: ANALYSIS	
Designation: Units (analysis data)		Description: This table contains units of the analysis data pool. * Keys id (technical key) unit name (business key) *logical connection to other tables hyd_einheiten (hyd_einheiten.id = ana_unit.unit_id)	
Column name	Column designation	Type	Description
id	Technical ID	serial	
unit_id	Reference to unit (master data)	integer	
unit_name	Unit name	char(50)	

1.10. ana_wplace

Table name: ana_wplace		Product: ANALYSIS	
Designation: Workplaces (analysis data)		Description: This table contains workplaces of the analysis data pool. * Keys id (technical key) workplace_name (business key) *logical connection to other tables res_bestand (res_bestand.res_id = ana_workplace.workplace_id)	
Column name	Column designation	Type	Description
id	Technical ID	serial	
workplace_id	Technical ID of workplace masterdata	integer	
workplace_name	Workplace name	char(50)	

1.11. ana_wplace_operat_perio

Table name: ana_wplace_operat_perio		Product: ANALYSIS	
Designation: Work processes (analysis data)		Description: This table contains work processes of the analysis data pool.	
		*Note	
		* Keys	
		id (technical key)	
		logon_time, operat_id,wplace_id (business key)	
		data_supplier_id (business key)	
		operat_id (business key)	
		wplace_id_id (business key)	
		*logical connection to other tables	
		TODO	
Column name	Column designation	Type	Description
data_supplier_id	Reference to datasupplier master data	integer	
external_reference	Reference to	bigint	TODO
id	Technical ID	serial	
logoff_time	Registered logoff time	datetime	
logon_time	Registered logon time	datetime	
operat_id	Reference to operation master data	bigint	
workplace_id	Reference to workplace masterdata	integer	

2. BDE

2.1. ade_arbplanfolgen

Table name: ade_arbplanfolgen		Product: BDE	
Designation: Work plans - order sequences			
Column name	Column designation	Type	Description
absprung	Branch OP	char(40)	Analogous to ADE_AUFTRAGSFOLGEN
aend_nr	Version	char(12)	Analogous to ADE_AUFTRAGSFOLGEN
aenderungsnr		char(12)	Analogous to ADE_AUFTRAGSFOLGEN
afolg	Sequence	char(10)	Analogous to ADE_AUFTRAGSFOLGEN
aktiv	Active	char(1)	Analogous to ADE_AUFTRAGSFOLGEN
aunr	Work plan	char(40)	Analogous to ADE_AUFTRAGSFOLGEN
ausrichtung	Alignment	char(1)	Analogous to ADE_AUFTRAGSFOLGEN
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
bezugsfolge	Referen. seq.	char(10)	Analogous to ADE_AUFTRAGSFOLGEN
folgenart	Sequence category	char(1)	Analogous to ADE_AUFTRAGSFOLGEN
kurztext	Designation	char(40)	Analogous to ADE_AUFTRAGSFOLGEN
ruecksprung	Return OP	char(40)	Analogous to ADE_AUFTRAGSFOLGEN

2.2. ade_auftragmengen

Table name: ade_auftragmengen		Product: BDE	
Archive table: a_ade_auftragmeng		Reload table: r_ade_auftragmeng	
Designation: Order status - quantity reasons			
Column name	Column designation	Type	Description
a_typ		char(4)	AU -> orders (header information) AG -> operations UAG -> sub operations SPL -> split SAG -> collective operations (PDM field ID: ANRMENGE.ATYP)
auftrag_nr		char(40)	Total key of the object Distribution according to SETUP (PDM field ID: ANRMENGE.ANR)
grund		integer	Describing the quantity reason Reference: ADE_GRUNDZUORD
grund_text		integer	The reference to the reason text is also posted here for an optimum access. Reference: ADE_GRUNDTEXTE
ist_bas	Actual quantity (base quantity unit)	decimal(18,6)	Actual quantity (base quantity unit) (PDM field ID: ANRMENGE.EGR:B)
ist_pri	Actual quantity (primary)	decimal(18,6)	Actual quantity (prim.) (PDM field ID: ANRMENGE.EGR:P)
ist_sek	Actual quantity (secondary)	decimal(18,6)	Actual quantity (sec.) (PDM field ID: ANRMENGE.EGR:S)
ist_ter	Actual quantity (tertiary)	decimal(18,6)	Actual quantity (tert.) (PDM field ID: ANRMENGE.EGR:T)
meinheit_bas		char(3)	Quantity unit basis (PDM field ID: ANRMENGE.EGE:B)
meinheit_pri		char(3)	Quantity unit primary (PDM field ID: ANRMENGE.EGE:P)
meinheit_sek		char(3)	Quantity unit secondary (PDM field ID: ANRMENGE.EGE:S)
meinheit_ter		char(3)	Quantity unit tertiary (PDM field ID: ANRMENGE.EGE:T)
mengen_art		char(1)	Kind of quantity: A = scrap P = problem quantity N = rework quantity

2.3. ade_auftragsarten

Table name: ade_auftragsarten		Product: BDE	
Designation: Order types		Description: Order types Order types are issued to structure the orders in accordance with their use. Each order type includes various control information that is decisive when managing orders. # Key auftrag_art # Connections to other tables auftrags_bestand, ade_status_zuord, hybuch	
Column name	Column designation	Type	Description
a_an_sk_beginn	Logging OP on again at shift start	char(1)	This identifier defines operation logon behavior at the start of a shift. J: Interrupt operation and automatically log operation back on at start of shift. N: Do not log an operation back on at start of shift. Interrupt only. X: The processing depends on the appropriate setting in the workplace/ machine configuration (PDM field ID: AUART.OPT:AANSKBAUTO)
a_p_an	Combined order logon	char(1)	Combined order logon This identifier is used for displaying "overhead cost operations". J: With this order type operation and person are firmly connected with each other. The performance (posting of operation and person) is as it is the case when logging on to a group workplace The person is not connected with other operations at the machine The booked manual quantity is always posted onto the reporting person The reporting person (A_TR/A_UN/A_AB) also has to be logged on to the operation IMPORTANT: with this option pers_abmeld always has to be = "N" to prevent the operation from being continued without person! T: No overhead cost processing. Use terminal or machine settings (PDM field ID: AUART.OPT:APAN)
aend_rueckmeld	Change after upload	char(1)	Change after upload This identifier defines how changes/ corrections to postings uploaded to the ERP/PPS system are handled. The identifier is evaluated during posting maintenance as well as during event maintenance. J: Changes/ corrections are allowed to already uploaded postings; changes are also uploaded to the PPS system. E: Changes/ corrections are allowed to already uploaded postings; however, these corrections are not uploaded to the PPS system. N: No more changes/ corrections are allowed to already uploaded postings. Previously: setup.bde_kz: [6] J = suppress correction booking for superior system HYDRA.OPT:KORRRMNGEN [7] J = Maintenance function blocked for uploaded data HYDRA.OPT:EDITBRMSPERR (PDM field ID: AUART.OPT:EDITRM)
aktiv	Active	char(1)	If this indicator is set, then this order type is available and can be used. The indicator is checked when an order is first created or modified. J: indicator is set N: indicator is not set (PDM field ID: AUART.AKTIV)
ap_gedruckt	Check that shop floor papers are printed	char(1)	This setting can activate a validation check during login of operations depending on the print status of the time tickets. Under the proper conditions, this function can help prevent erroneous postings or rather can "guide" production. J: An operation may only be logged on if its shop floor papers were printed before (if AUFTRAGS_STATUS.AP_GEDRUCKT = "J") N: No validation check (PDM field ID: AUART.OPT:APPRN)
auftrag_art	Order type	char(5)	Definition of the order type. Order types are configured as it is the case in SAP. The parameters of this configuration control, among other things, performance within the system. (PDM field ID: AUART.AUART)

auftragsverbuchung	Not used at the moment	char(4)	Not used at the moment
auto_a_ab_vanr_l	Milestone processing	char(1)	Milestone processing for the last operation only - according to the configuration in the corresponding processing code. J: operation is finished automatically only if it is the last operation within this order (ab.last_afo =J) N: all operations up to next milestone are finished automatically (PDM field ID: AUART.OPT:AUTOAABVANRL)
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time letzter Bearbeitungszeitpunkt
beendbar	May operations of the order be finished	char(1)	May operations of the order be finished J: Yes, operations may be finished S: Checking the status of predecessor operation. In this case, the status of the predecessor operation must have the identifier "successor can be logged off" set. N: No, operations may not be finished. A validation check is done when an operation is logged off. (PDM field ID: AUART.OPT:ABE)
berecht_pflege	Authorization key for editing recorded data	char(4)	This authorization key allows to control which user may edit recorded data for which order type. Add this key to a user in user administration in order to control if this user is allowed to edit recorded data for specific order types only. If no key is assigned to a user, this user can edit stock data for all order types. To avoid collisions with existing authorization keys it is recommended to use a prefix which is definitely not used in function authorizations yet (e.g. \$) (PDM field ID: AUART.FKT:EDIT)
berecht_stufe	Authorization key for editing stock data	char(4)	This authorization key allows to control which user may edit stock data for which order type. Add this key to a user in user administration in order to control if this user is allowed to edit stock data for specific order types only. If no key is assigned to a user, this user can edit stock data for all order types. To avoid collisions with existing authorization keys it is recommended to use a prefix which is definitely not used in function authorizations yet (e.g. \$) (PDM field ID: AUART.FKT)
bereich	CAQ area	char(15)	Not used at the moment (PDM field ID: AUART.BER)
bezeichnung	Designation	char(60)	Designation of the order type (PDM field ID: AUART.BEZZL)
dialogsteuerung	Dialog control	char(10)	Dialog control that deviates from how the system typically behaves and it can be referenced accordingly in the dynamic dialog. This makes it possible to show or hide situation specific input fields at the terminal. Please note: This setting can also be defined at the workplace (machine/ workplace configuration). When a terminal dialog is opened, dialog control for both order type and workplace are considered. For this reason, we recommend that dialog control be defined either in the order type or at the workplace. (PDM field ID: AUART.DLGSTRG)
erfassbar	Recordable	char(1)	This identifier defines whether operations for orders of this order type can be recorded, i.e. posted. J: Yes, operations can be recorded. Whether an operation is really recordable also depends on the setting with the same name in the processing code. N: No; Operations may not be recorded. An attempt to log any such operation on is rejected with a validation error. (PDM field ID: AUART.OPT:ERF)

ermittlung_fertvar	Consider production variants	char(2)	Consider production variants [1,1] when transferring an operation E: The system determines whether a valid production variant exists at the time the operation is transferred/ created. P: At the time an operation is transferred/ created, the data transferred is checked only to verify that it matches a valid production variant (validation check). N: No determination/ validation check [2,2] in planning (shop floor scheduling / HLS) E: Determination. A valid production variant is determined at the time an operation is planned in graphic planning. P: Checking only. At the time of planning, the data transferred is checked only to verify that it matches a valid production variant (validation check). Default values are not taken over from the production variant. G: Group-specific testing. At the time of planning, the data transferred is checked to verify that it matches a valid production variant (validation check). But the checking is only performed within the group defined for the operation. Default values are not taken over from the production variant. N: Not used. (PDM field ID: AUART.OPT:FERTVAR)
kategorie	Category	char(2)	Mandatory field Classification is a logical term for similar order types FA: Production order. Standard production orders created e.g. by an interface. PJ: Project order. Projects are, among others, characterized by their uniqueness. The project steps that are to be performed as a part of a project can be combined in a project order PM: Maintenance order. Orders that have been designed for the planning or collection of maintenance measures KP: Capacity order. Orders that have been designed for capacity reservations in the shop floor scheduling module (HLS). GK: Overhead cost order. Orders for the collection of overhead costs. They may also be included in evaluations. ATTENTION: No processing or posting using these values. For this purpose use the configurations at order type or processing code. (PDM field ID: AUART.KAT)
keine_au_abmeld	Order is not logged off automatically	char(1)	Processing can take place subject to the termination of the order (header). Using this identifier can prevent the order from being set to finished if the last recordable operation was finished. N: Finishing all recordable operations automatically sets the order to finished (setting order status using the control indicator "E") J: Order is not logged off automatically, i.e. finishing all recordable operations does not automatically set the order to finished. (PDM field ID: AUART.OPT:NAUTOABAU)
masch_plaus	Check for specifications in backlog of orders	char(1)	Check for specifications in backlog of orders The fields from SETUP get to the order type configuration: setup.masch_plaus: J: An operation logon is only allowed at the planned workplace G: An operation logon is allowed only to the planned workplace, to a workplace belonging to the group or to a workplace planned for the group. K: An operation logon is possible either to the planned workplace or to a workplace of the same category N: No validation check S: Group control ATTENTION: "planned" has been redefined in version 7.2 (PDM field ID: AUART.PLAUS:MNR)
max_pers_plaus	Check against M/O relation when person logs on	char(1)	Check against M/O relation when person logs on J: Machine/operator relation (MB_VERHAELTNIS). When a person logs on to an operation, a check is run to determine if the maximum number of employees has already been reached. If this is the case, this personnel logon is rejected. N: No check K: Component list of requirements to be transferred (planned, currently not used) (PDM field ID: AUART.PLAUS:PNR)

opt_erfassung	Miscellaneous flags regarding capturing	char(10)	[1,1] Only OPs of the same order type can be logged on simultaneously J/N [3,3] Posting through captured project time J: Order may be captured in the web, console and the project time recording terminal N/empty/null: Order cannot be captured via project time recording [4,4] Show operation info when logging on. if notes or text exist for displaying at the terminal empty: no action T: Show order info with tab "order text" N: Show order info with tab "order note" [5,5] Evaluate the "Logoff operation when reaching target quantity" option at workplace J: check workplace characteristics N: check operation / processing code characteristics [6,6] Order type for composition C: Charging order M: Melting order N: None [7,7] Parallel order posting 1: Parallel logon of operation 2: Parallel interrupt / logoff of operation 4: Automatic logon / logoff / interruption N: None (PDM field ID: (Composed of several acronyms))
opt_planung	Miscellaneous flags regarding planning	char(10)	[1,1] Use setup time indicated in shop floor scheduling empty: Target setup time R : Remaining setup time B : Target setup time 0, when operation is started F: Formula; not used at the moment [2,3] Formula for calculating the demand Any two digit formula [4,4]: Scheduling without implicit order release. Prevent the order from being released during scheduling run. J/N
pers_abmeld	Pers_abmelden	char(1)	Persons are logged off automatically when the shift ends J: Always log staff off at the end of the shift N: Always save staff when the shift ends, except for manual logoff X: The processing depends on the relevant setting in the workplace/ machine configuration (PDM field ID: AUART.OPT:PANSKBAUTO)
pflge_tr	Editing of scrap incl. reason in maintenance of postings	char(1)	Keeping scrap explanation in the booking maintenance (PDM field ID: AUART.EDITTR)
planen	Planning	char(1)	Decides whether or how orders of this type are relevant for detailed scheduling. N: No planning (not transferred to planning component) T: Scheduling only. The order is scheduled, that is the lead time is calculated based on the process times and the dates are set accordingly. No competitive situations are considered during (lead time) scheduling. F: Scheduling and detailed scheduling (dispatching). The order is relevant for detailed planning and is consequently - in addition to scheduling - considered during automatic and/ or interactive planning. Please note: During automatic dispatch (detailed scheduling), operations are dispatched to a workplace. In the process, the situation pertaining to capacity and assignment is considered for the workplace, which may result in the inability to dispatch by the planned date determined from lead time scheduling. (PDM field ID: AUART.OPT:PLAN)

plantermine	Planning dates	char(1)	Performance of planning dates when it comes to (re)scheduling O: Planning dates remain as they are (default) T: Planning dates are overwritten by scheduling I: not used at the moment (PDM field ID: AUART.OPT:PLANTERM)
pr_vorg_mind_menge	Check minimum send-ahead qty. of preceding OP	char(1)	Check minimum send-ahead qty. of preceding OP This identifier defines whether a validation check for the minimum send-ahead quantity should be run during operation logon. M: Check for minimum send-ahead quantity during operation logon. In this case, a minimum send-ahead quantity (yield) must have been posted to the preceding operation so that the succeeding operation can be logged on. The minimum send-ahead quantity is defined at the preceding operation. N / empty: No check (PDM field ID: AUART.PLAUS:MINMENGEV)
pr_vorg_status	Check status of predecessor OP	char(1)	Check status of predecessor OP S: Checking status of predecessor operation. In this case, the status of the preceding operation must have the identifier "Successor can be logged on" set. N / empty: No checking ATTENTION: the predecessor does NOT result from afo_lfd_nr, but ONLY from the relations in ADE_AUFTRAGSNETZ So far setup.aus_plaus: J/N, J: Activates plausibility checks whether predecessor OP has at least started (Status != "V") à check for AG-AN - HYDRA.OPT:VAGNRSTART (PDM field ID: AUART.PLAUS:STAV)
pr_weiterg_menge	Quantity check of send-ahead quantity	char(1)	Quantity check of send-ahead quantity G: Checking yield against yield of preceding operation S: Checking total quantity against yield of preceding operation N / empty: No validation check (PDM field ID: AUART.PLAUS:WEIGMENGE)
prio_steuerung	Priority control	char(2)	Priority control [1,1]: Priority Control U: Priority control is order-related, i.e. the priority is set in the order (header) and has an impact on all OPs. G: Priority control is operation related [2,2]: Activation of priority management J: Orders of this order type are taken into account for priority management, i.e. when changing/creating an order it is checked whether the assigned priority is admissible or not and in case the maximum number is violated, the action is rejected (affects the console). The "order group" field is a mandatory field in this case. N: Orders of this order type are not considered during priority management. Prioritätsteuerung PRIO_STEUERUNG[1,1]: U = Priorität wird Auftragsbezogen geführt, d.h. die Priorität wird am Auftrag gesetzt und schlägt sich auf alle AGs nieder. G = Priorität wird Vorgangs-/AG-bezogen geführt à Standard PRIO_STEUERUNG[2,2]: Aktivieren der Prioritätsverwaltung J = Aufträge dieser Auftragsart werden bei der Prioritätenverwaltung berücksichtigt. D.h. beim Ändern/ Neuanlegen eines Auftrags wird geprüft, ob die vergebene Priorität zulässig ist und bei Verletzung der maximalen Anzahl die Aktion abgelehnt (betrifft die Konsole). Das Feld "Auftragsgruppe" ist in diesem Fall ein Pflichtfeld N = Aufträge dieser Auftragsart werden bei der Prioritätenverwaltung nicht berücksichtigt; das Feld "Auftragsgruppe" ist in diesem Fall ein Kannfeld. Mögliche Werte OPT:PRIOVRW= "UJ", "UN", "GN" (PDM field ID: AUART.OPT:PRIOSTRG)

pruefauf_nr_gen	Generate CAQ inspection steps	char(1)	Generate CAQ inspection orders automatically for this order type. Not used at the moment. I - CAQ inspection orders are generated/modified when creating and changing the ADE order and deleted when the ADE order is deleted. (PDM field ID: AUART.OPT:PAUNRGEN)
-----------------	-------------------------------	---------	---

rueckmelden	Upload of recorded data to PPS	char(40)	This option defines whether recorded data is to be uploaded to the PPS system or not for this order type. RUECKMELDENDEN[1,1] J: Postings are uploaded. Which postings are uploaded and/or how they are uploaded is defined by the following digits within this db column. N: Postings are not uploaded. In this case the following digits within this db column are irrelevant RUECKMELDENDEN[2,2] Upload of partial confirmations (T records) J/N RUECKMELDENDEN[3,3] Upload of operation logons (A records) J/N RUECKMELDENDEN[4,4] Flag is currently not in use RUECKMELDENDEN[5,5] Upload of personnel postings (B records) J/N RUECKMELDENDEN[6,6] Upload company of current workplace J/N RUECKMELDENDEN[7,7] For batch bookings upload U/E records only (no H records) J/N RUECKMELDENDEN[8,8] Upload order postings only when they are approved i.e. upload only if ade_protokoll.sign_flag == 'J' or if the expiration date is exceeded J/N RUECKMELDENDEN[9,9] Upload personnel postings (B records) only when they are approved J/N RUECKMELDENDEN[10,10] Cancellation message job end first J/N RUECKMELDENDEN[11,11] Upload of personnel waiting periods (ade_protokoll.karenz = 'P' or 'M') J/N RUECKMELDENDEN[12,12] Upload scrap from partial confirmations. Yield, rework quantity and problem quantity are transferred from the postings of record type U and/or E. J/N RUECKMELDENDEN[13,13] Upload orders from the PPS system only J/N RUECKMELDENDEN[14,14] Upload delayed operations only J/N RUECKMELDENDEN[15,15] Upload only operations having a deviating machine assignment (auftrags_bestand.mnr != pps_bestand.mnr) J/N RUECKMELDENDEN[16,16] Upload B records to the PPS only J/N
-------------	--------------------------------	----------	---

			RUECKMELDEN[17,17] Upload of batch bookings via HY72PPS uplad interface (G records) This option is approved for uploads using the HY72PPS interface only and may not be set in conjunction with the PP-PDC, KK3, KK4 or HY71PPS interfaces J/N RUECKMELDEN[18,18] U/E-records should be signed (ADE 7.3) J/N RUECKMELDEN[19,19] B-records should be signed (ADE 7.3) J/N (PDM field ID: AUART.OPT:RM)
rueckmeldetyp	Upload type	char(10)	Upload type (PDM field ID: AUART.RMTYP)
seriennr_pflichtig	Serial number obligation	char(1)	Serial numbers obligation This identifier defines whether an order requires a serial number, and if so, how the serial number should be entered. +: Serial number obligation, "positive" entry, i.e. the yield is entered with serial numbers. -: Serial number obligation, "negative" entry, i.e. the scrap or problem quantities are entered with serial numbers. N / empty: No serial number requirement E: Manual entry of serial number G: Automatic generation of serial number S: Generation of serial numbers using number ranges A: Collection of serial numbers U: Merge serial numbers The identifier "Serial number obligation" determines at the processing code or the operation directly as of which operation the serial number must be entered. (PDM field ID: AUART.OPT:SNR)
seriennr_vergabe	Assignment of serial numbers	char(1)	This identifier is only relevant if the identifier "Serial number obligation" is not set to "N". It defines how serial numbers are allocated This field is only relevant if SERIENNR_PFLICHTIG <> " " / "N" P: Serial numbers are transferred/ expected from the PPS system. N: Irrelevant H: Serial numbers are generated by the system according to the number range configuration. Not supported at the moment. (PDM field ID: AUART.OPT:SNRVERG)
symbol	Symbol	char(12)	Image / icon that can optionally be assigned to the order type. It is displayed in several functions/reports (PDM field ID: AUART.ICON)
system	Internal field	char(1)	Internal field; if it is set this entry may not be deleted; is always "J" for the types to be delivered (PDM field ID: AUART.OPT:SYS)
user_c_07	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_08	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_09	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_10	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_11	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_12	Alphanumeric user field	char(10)	Alphanumeric field reserved for user specific data
user_c_13	Alphanumeric user field	char(10)	Alphanumeric field reserved for user specific data
user_c_14	Alphanumeric user field	char(20)	Alphanumeric field reserved for user specific data
user_c_15	Alphanumeric user field	char(20)	Alphanumeric field reserved for user specific data
user_c_16	Alphanumeric user field	char(40)	Alphanumeric field reserved for user specific data
user_code	User field key	char(8)	User field key Reference to the configuration of the user field key or its user fields in the HYD_USERFIELDCFG table
user_f_05	Decimal user field	decimal(18,6)	Decimal field reserved for user specific data
user_f_06	Decimal user field	decimal(18,6)	Decimal field reserved for user specific data

user_n_01	Numeric user field	integer	Numeric field reserved for user specific data
user_n_02	Numeric user field	integer	Numeric field reserved for user specific data
user_n_03	Numeric user field	integer	Numeric field reserved for user specific data
user_n_04	Numeric user field	integer	Numeric field reserved for user specific data
visual_code	Visualization code	char(6)	Visualization code This flag is used as control information for the console. It controls the console display (e.g. showing/hiding of tabs at the console). Which information is displayed at the console is defined via respective entries in REFLISTE.DAT in a first step. (PDM field ID: AUART.VISCODE)
vorgabeliste	Sequencing list	char(1)	This setting determines whether operations for orders of this order type are displayed in the sequencing list at the terminal. J: Yes, display N: No, do not display F: Operations that were fixed are displayed. The fixing indicator can be set manually in shop floor scheduling. (PDM field ID: AUART.OPT:VLIST)

2.4. ade_auftragsfolgen

Table name: ade_auftragsfolgen		Product: BDE	
Archive table: a_ade_auftragsfolg		Reload table: r_ade_auftragsfolg	
Designation: Order sequences			
Column name	Column designation	Type	Description
absprung	Branch OP	char(40)	OP, from which it is "branched off"; as stored in SAP Number of the OP · where a parallel sequence branches off · from which an alternative sequence can replace the standard sequence. Plausibility check: · the ANR must exist in auftrags_bestand (field auftrag_nr) · mandatory field in case of parallel and alternative sequences. This field always remains empty in case of the standard sequence. (PDM field ID: AFOLG.ANRA)
aend_nr	Change number	char(12)	Change number/version, only for your information (PDM field ID: AFOLG.VER)
aenderungsnr		char(12)	---
afolg	Sequence number	char(10)	Sequence number (PDM field ID: AFOLG.AFOLG)
aktiv	Active	char(1)	J/N only relevant for alternative sequences · is always set to "J" in case of FOLGENART = 'P' or 'S'. · in case of INSERT of an alternative sequence the indicator is set to "N" if it is not transferred (PDM field ID: AFOLG.AKTIV)
aunr	Check if order exists	char(40)	Order of A_TYP = "AU" BAPI: Plausibility check Check if order exists in auftrags_bestand. There has to be an entry with AUFTRAG_NR = this number and A_TYP = "AU". (PDM field ID: AFOLG.AUNR)
ausrichtung	Alignment	char(1)	Key by means of which you can control how a parallel sequence is scheduled with respect to the date. If there are several parallel sequences the lead times differ in length. Thus, temporal buffers result in the sequences. Due to the alignment, it is controlled whether these buffers are at the beginning or the end of the sequence. Possible values: "F" alignment at the earliest date (buffer lies at the end of the sequence) "S" alignment at the latest date (buffer lies at the beginning of the sequence) "N" not relevant SAP: AUSCHL CHAR(1) Plausibility check: · only relevant in case of parallel sequence; "F" or "S" has to be entered. · in case of a standard sequence and alternative sequences, a transferred value is ignored and "N" is entered. (PDM field ID: AFOLG.AUSR)
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing date	integer	Last editing date
bezugsfolge	Reference sequence	char(10)	Sequence, to which branch/return are referring. Plausibility check: · the sequence already has to exist in this table for this order (AUNR). · mandatory field for parallel and alternative sequences · HCH 06.08.2003: Only 0 is allowed as parallel and alternative sequences always refer to the standard sequence and this one is always identified with 0. This field always remains empty in case of the standard sequence. (PDM field ID: AFOLG.BZGFOLG)

folgenart	Sequence type	char(1)	S standard sequence - there may only be 1 P parallel sequence - there can be several sequences per AU A alternative sequence - there can be several sequences per AU SAP: FLGAT CHAR(1) · Plausibility check in the BAPI for these three values · It is not allowed to delete the standard sequence!! · There may be only 1 standard sequence at most. Note "alternative sequence" (from SAP help): A sequence of operations that can be used as an alternative to a number of consecutive operations from the standard sequence. Alternative sequences are used, for example, if the production process differs according to lot size. (PDM field ID: AFOLG.FOLGART)
kurztext	Designation	char(40)	Designation (PDM field ID: AFOLG.BEZK)
ruecksprung	Return OP	char(40)	OP, to which it is "branched back". Number of the OP · after which a parallel sequence branches back · up to which an alternative sequence can replace the standard sequence Plausibility check: · the ANR must exist in auftrags_bestand (field auftrag_nr). · mandatory field in case of parallel and alternative sequences This field always remains empty in case of the standard sequence. (PDM field ID: AFOLG.ANRR)

2.5. ade_auftragsgruppe

Table name: ade_auftragsgruppe		Product: BDE	
Designation: Order groups		Description: Order groups Each order can be assigned to an order group. Based on this order group, the priorities are managed. # Key auftragsgruppe, a_prio # Connections to other tables auftrags_zusatz	
Column name	Column designation	Type	Description
a_prio	Priority	char(4)	Priority steps "0" to "9" (PDM field ID: AUGRP.PRIO)
anteil_prozent	Proportion	float	Percentage proportion permissible for this priority in relation to the number of orders in this order group. (PDM field ID: AUGRP.PROZANT)
auftragsgruppe	Order group	char(4)	Unique order group number (PDM field ID: AUGRP.AUGRP)
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
bemerkung	Comment	char(40)	Designation and/or description of the order group (PDM field ID: AUGRP.BEM)
obergrenze	Upper limit	integer	Absolute upper limit relating to the number of orders (PDM field ID: AUGRP.ANZAU:OG)
untergrenze	Lower limit	integer	Absolute lower limit relating to the number of orders (PDM field ID: AUGRP.ANZAU:UG)

2.6. ade_auftragsnetz

Table name: ade_auftragsnetz		Product: BDE	
Archive table: a_ade_auftragsnetz		Reload table: r_ade_auftragsnetz	
Designation: Order network			
Column name	Column designation	Type	Description
afolg_n		char(10)	If info is defined in SETUP how it is divided (PDM field ID: ANETZ.AFOLGN)
afolg_v		char(10)	It is easier to carry out a sequence change if the fields are separately available again. (PDM field ID: ANETZ.AFOLGV)
agnr_n		char(20)	Successor OP no. (PDM field ID: ANETZ.AGNRN)
agnr_v		char(20)	Predecessor OP no. (PDM field ID: ANETZ.AGNRV)
aktiv		char(1)	In case of alternative or reference sequences: J/N, otherwise J Meaning: please see field of the same name in ADE_AUFTRAGSFOLGEN (PDM field ID: ANETZ.AKTIV)
aob	Relationship	char(2)	Relationship SS = Start start SE = Start end ES = End start EE = End end HCH 01.08.2003: only "ES" relationships are considered (till somebody says that other relationships have also to be taken into account) for the collection (e.g. send-ahead quantity, target quantity comparison). The other relationships are only considered when planning. HCH 09.10.2003: Change The relationship is set to "SS" if lead time > 0 or minimum send-ahead quantity > 0. (PDM field ID: ANETZ.AOB)
auftrag_nr_n	Successor OP	char(40)	Successor ANETZ..ANRN (PDM field ID: ANETZ.ANRN)
auftrag_nr_v	Predecessor OP	char(40)	Predecessor (PDM field ID: ANETZ.ANRV)
aunr_n		char(40)	Successor order header no. (PDM field ID: ANETZ.AUNRN)
aunr_v		char(40)	Predecessor order header no. (PDM field ID: ANETZ.AUNRV)
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing date	integer	Last editing date
herkunft		char(1)	S = implicitly via sequence AOB (relationship) is: ES P = implicitly via parallel sequence AOB (relationship) is: ES A = implicitly via alternative sequence AOB (relationship) is: ES E = explicitly (via interface) (PDM field ID: ANETZ.HERK)

liege_zeit_max	Max. synchronization time	integer	Max. synchronization time; from auftrags_bestand.LIEGE_ZEIT_MAX -> only relevant for planning (PDM field ID: ANETZ.LIEZ:MAX)
relevanz		char(1)	Relevance != P/X is only of interest for the collection (HYMW)
splnr_n		char(10)	Successor split no.
splnr_v		char(10)	Predecessor split no.
uagmr_n		char(20)	Successor sub operation no. (PDM field ID: ANETZ.UAGNRN)
uagmr_v		char(20)	Predecessor sub operation no. (PDM field ID: ANETZ.UAGNRV)
ueberlappung		char(1)	"N" = No, no overlap "S" = Target overlap "K" = Optional overlap "M" = Mandatory overlap Explanation: please see field of the same name in processing code -> only relevant for planning (PDM field ID: ANETZ.OPT:UEBLAP)
vorlaufzeit	Lead time	integer	Lead time; from auftrags_bestand.VORLAUFZEIT VORLAUFZEIT (lead time) and WEITERGABEMENGE (send-ahead quantity) are mutually exclusive -> only relevant for planning (PDM field ID: ANETZ.VLZ)
weitergabemenge		decimal(18,6)	Minimum send-ahead quantity; from auftrags_bestand.WEITERGABEMENGE VORLAUFZEIT (lead time) and WEITERGABEMENGE (send-ahead quantity) are mutually exclusive Is kept in a redundant way to AUFTRAGS_BESTAND. Planning and collection access this. (PDM field ID: ANR.WEIGMENGE)
weitergabemenge_z	Send-ahead quantity converted into time	integer	Converted send-ahead quantity in time (bearb_zeit) / soll_menge_pri) * anetz->weitergabemenge); Is calculated in ANETZ -BAPI

2.7. ade_grund_texte

Table name: ade_grund_texte		Product: BDE	
Designation: Reason texts		Description: Reason texts # Key grundtext_nr # Connections to other tables ade_grund_zuord, ade_seriennummern	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
grundtext	Reason text	char(30)	Designation of the reason text (PDM field ID: GRTXT.GRTXT)
grundtext_nr	Reason text number	integer	Unique number to identify the text (PDM field ID: GRTXT.GRTXTNR)

2.8. ade_grund_zuord

Table name: ade_grund_zuord		Product: BDE	
Designation: Assignment of quantity reasons			
Column name	Column designation	Type	Description
art	Type	char(1)	A = Scrap N = Rework P = Problem quantity G = Yield L = Batch logs R= Reduce partitioning E= Raise partitioning (PDM field ID: GR.ART)
artikel	Scrap material	char(40)	--- --- (PDM field ID: GR.ATK)
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
ext_referenz	External reference	char(5)	An alphanumeric - CHAR(5) - representation, which can be uploaded e.g. at the interface, is intended for each assignment. (PDM field ID: GR.BEZX)
grund	Reason	integer	That is the actual reason (PDM field ID: GR.GR)
grundtext_nr	Reason text number	integer	Reference to ADE_GRUND_TEXTE (PDM field ID: GR.GRTXTNR)
lle_bezahlt	Payed in LLE J/N	char	Payed in LLE J/N (PDM field ID: GR.LLEBEZAHLT)
m_grund	Mother reason	integer	"Mother reason" The assignment to a superior reason can always only be made within the same quantity type and machine (PDM field ID: GR.MGR)
masch_nr	Machine number	char(20)	If SYSTEM, then it is a cross-system assignment (PDM field ID: GR.MNR)
opt_defaultartikel	Scrap material	char(1)	--- --- (PDM field ID: GR.OPT:ATKVORG)

2.9. ade_lst_codes

Table name: ade_lst_codes		Product: BDE	
Designation: Activity codes			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
bezeichnung		char(20)	---
erfassungsart	Input type	char(2)	Input type for actual - ZE = Recording due to time events (for time activities/RPA (resource performance accounts) only) - Dx = Discrete recording (e.g. like entry of quantities) - DR = Relative - DA = Absolute - Xx = Calculated (via formula) - XU = Per posting - XE = At the end when logging the OP off Note: A "target=actual" processing can also be mapped via this. - " "K" = No recording (PDM field ID: LSTCODE.ERFART)
expr	Formula for actual	char(6)	Formula for actual if ERFASSUNGSART = XU or XE -> reference to valid (available) formula in the formula management (table HYD_EXPR) (PDM field ID: LSTCODE.EXPR)
expr_soll	Formula for target	char(6)	Formula for target --> Reference to valid (available) formula in the formula management (table HYD_EXPR)
leistung	Activity	char(6)	Activities: BMK01 ...BMK12 Personal activities: PBMK01 ...PBMK12 Alternative activities: LST01 ...LST10 (PDM field ID: LSTCODE.LST)
leistung_max	Allowed overdelivery	float	Allowed overdelivery (for this activity) in percent must be >0 and > LEISTUNG_MIN (PDM field ID: LSTCODE.LST:MAX)
leistung_min	Allowed underdelivery	float	Allowed underdelivery (for this activity) in percent must be > 0 (PDM field ID: LSTCODE.LST:MIN)
leistungscode	Activity code	char(6)	--- (PDM field ID: LSTCODE.LSTCODE)
ref_kenn	Reference to field definition	char(20)	-> Reference to field definition (table HYD_USERFIELDDEF) (PDM field ID: LSTCODE.KENN)
uebli	Reaction to overdelivery	char(1)	Reaction to overdelivery (PDM field ID: LSTCODE.OPT:UEBLI)
untli	Reaction to underdelivery	char(1)	Reaction to underdelivery (PDM field ID: LSTCODE.OPT:UNTLI)

2.10. ade_ortsgrpwechsel

Table name: ade_ortsgrpwechsel		Product: BDE	
Designation: Location group matrix			
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time		integer	Last editing time
bemerkung	Comment	char(40)	--- (PDM field ID: OGRW.BEM)
ortgr_nach	Location group to	char(4)	Location group of target machine (PDM field ID: OGRW.OGRP:N)
ortgr_von	Location group from	char(4)	Location group of origin machine Location group = key, by means of which the workplace is assigned to a spacial area SAP: ORTGR CHAR(4) (PDM field ID: OGRW.OGRP:V)
schichtmod	Shift model	smallint	Shift model
transp_zeit_kaltyp	Calendar type	char(1)	Calendar which the transport time is based on G = Gregorian calendar The scheduling of the transport time is based on the Gregorian calendar. S = Shift calendar With this option, the shift calendar of the origin machine is used for the scheduling. (PDM field ID: OGRW.TPZ:KALTYP)
transp_zeit_min	Minimum transport time	integer	Minimum transport time in hours, up to which it can be reduced according to the stages of the reduction strategy. External: Display in HH:MM Internal: Filing in seconds (PDM field ID: OGRW.TPZ:MIN)
transp_zeit_normal	Transport time normal	integer	Normal transport time in hours. External: Display in HH:MM Internal: Storing in seconds (PDM field ID: OGRW.TPZ:NORM)

2.11. ade_pers_komp

Table name: ade_pers_komp		Product: BDE	
Designation: Compressed personnel messages (Obsolete)		Description: This table is obsolete on systems installed since 04/2017 service pack 11. The information was only used in application "Labor time comparison". Up to now this information ist taken direkltly from tables tagesauswertung and ade_prot koll or v_ade_protokoll. This table contains working times per person and day form ADE and PZE. The purpose is to compare both times to match ADE times to PZE time. * Notes - * Keys 1) person_nr,schicht_dat 2) verweis * logical connection to other tables -	
Column name	Column designation	Type	Description
gk_dauer	Time recorded on overhead cost orders	integer	Time recorded on overhead cost orders
person_nr	Personnel number	char(10)	Personnel number
prod_dauer	Productive time (time recorded on orders	integer	Productive time (time recorded on orders)
reale_az	Real working time according to PZE	integer	Real working time according to PZE
schicht_dat	Shift date	date	Shift date
verweis	Reference	serial	Internal reference

2.12. ade_protokoll

Table name: ade_protokoll		Product: BDE	
Archive table: a_ade_protokoll		Reload table: r_ade_protokoll	
Designation: Operation-related result record		Description: This table contains all registrations based on operations and people. For operations subj. to batch management also the batch-related registrations are included. For batch related data sets the log records of the record type "G"=logon of batches, H=logoff of batches are relevant.	
Column name	Column designation	Type	Description
a_typ		char(4)	AU -> orders (header information) AG -> operations UAG -> suboperations SPL -> split SAG -> collective operations (PDM field ID: ANR.ATYP)
abbr_grund		integer	Status text number Machine status (text) number that was active or set at the machine when interrupting the OP (PDM field ID: ADEPRO.MST)
abmeld_dat		date	Logoff time of the order (PDM field ID: ADEPRO.DATE)
abmeldzeit		integer	Logoff time (PDM field ID: ADEPRO.ZEIE)
anmeld_dat		date	Logon time of the order (PDM field ID: ADEPRO.DATB)
anmeldzeit		integer	Logon time (PDM field ID: ADEPRO.ZEIB)
auftrag_nr	Order number	char(40)	BDE order number Total key of the object Distribution according to SETUP (PDM field ID: ADEPRO.ANR)
aus_bas	Scrap quantity (base quantity unit)	decimal(18,6)	Scrap quantity (base quantity unit) (PDM field ID: ADEPRO.EGR:AUSB)
aus_grund	Scrap reason	integer	Scrap reason Reference: ADE_GRUND_ZUORD (PDM field ID: ADEPRO.EGG:AUSB)
aus_grund_text	Reason text number	integer	Reason text number of the scrap quantity (not the text itself!!) Reference: ADE_GRUND_TEXTE (PDM field ID: ADEPRO.EGT:AUSB)
aus_pri	Scrap quantity (primary)	decimal(18,6)	Scrap quantity (prim.) (PDM field ID: ADEPRO.EGR:AUSP)
aus_sek	Scrap quantity (secondary)	decimal(18,6)	Scrap quantity (sec.) (PDM field ID: ADEPRO.EGR:AUSS)
aus_ter	Scrap quantity (tertiary)	decimal(18,6)	Scrap quantity (tert.) (PDM field ID: ADEPRO.EGR:AUST)
auto		char(1)	Empty, except for the case a system program has changed the data record (e.g. subsequent posting, PZE/ADE comparison)
auto_dat		date	---
auto_zeit		integer	---
bearb		char(10)	Abbreviation of the user who changes manually from usr_tab.usr (PDM field ID: ADEPRO.BEARB)
bearb_date		date	Date of the manual change (PDM field ID: ADEPRO.BEARBDAT)

bearb_time		integer	Last editing time (PDM field ID: ADEPRO.BEARBZEI)
begin_ts	Start	datetime	Timestamp for anmeld_dat,anmeldzeit
bmk_01	Posted activity in RPA 01	integer	Recorded time split on resource performance accounts Current remaining activity RPA 1 ATTENTION: it must be possible to reference to the IST and REST fields for the formula for the RLZ (remaining run time). Posted activity in RPA 01 (PDM field ID: ADEPRO.EGR:BMK01)
bmk_02	Posted activity in RPA 02	integer	Posted activity in RPA 02 (PDM field ID: ADEPRO.EGR:BMK02)
bmk_03	Posted activity in RPA 03	integer	Posted activity in RPA 03 (PDM field ID: ADEPRO.EGR:BMK03)
bmk_04	Posted activity in RPA 04	integer	Posted activity in RPA 04 (PDM field ID: ADEPRO.EGR:BMK04)
bmk_05	Posted activity in RPA 05	integer	Posted activity in RPA 05 (PDM field ID: ADEPRO.EGR:BMK05)
bmk_06	Posted activity in RPA 06	integer	Posted activity in RPA 06 (PDM field ID: ADEPRO.EGR:BMK06)
bmk_07	Posted activity in RPA 07	integer	Posted activity in RPA 07 (PDM field ID: ADEPRO.EGR:BMK07)
bmk_08	Posted activity in RPA 08	integer	Posted activity in RPA 08 (PDM field ID: ADEPRO.EGR:BMK08)
bmk_09	Posted activity in RPA 09	integer	Posted activity in RPA 09 (PDM field ID: ADEPRO.EGR:BMK09)
bmk_10	Posted activity in RPA 10	integer	Posted activity in RPA 10 (PDM field ID: ADEPRO.EGR:BMK10)
bmk_11	Posted activity in RPA 11	integer	Posted activity in RPA 11 (PDM field ID: ADEPRO.EGR:BMK11)
bmk_12	Posted activity in RPA 12	integer	Posted activity in RPA 12 (PDM field ID: ADEPRO.EGR:BMK12)
bpos	Operator position	char(10)	Operator position (PDM field ID: ADEPRO.BPOS)
buch_dat		date	Posting time - currently not in use (PDM field ID: ADEPRO.BUCHDAT)
buch_zeit		integer	Posting time - currently not in use (PDM field ID: ADEPRO.BUCHZEI)
certify_flag		char(1)	for future use
chargen_nr	Batch no.	char(20)	Batch no. (PDM field ID: ADEPRO.CNR)
chargen_nr_intern		char(20)	Internal use
chargen_typ		char(1)	A = output batch E = input batch (for future purposes) (PDM field ID: ADEPRO.CNR:TYP)
dauer		integer	Total duration of the logon, compared to the shift calendar (PDM field ID: ADEPRO.EGR:DAUER)
dlg_data_verweis		integer	RW 7.1->7.2: transfer from table ade_protokoll from field: param_01
ebdf		char(1)	Decision requirement J/N
end_ts	Last logoff	datetime	Timestamp for abmeld_dat,abmeldzeit
erw_status01		char(1)	nicht belegt
erw_status02		char(1)	Assigned if the log record has been created manually via the function "maintenance of bookings" at the console M : created manually via the console P: automatically generated by PZE. The data record must not be changed in the maintenance of bookings A: automatically generated by PZE-ADE comparison ANP-000700 (PDM field ID: ADEPRO.ERWSTA:2)

erw_status03		char(1)	---
erw_status04		char(1)	"T" = team logon
erw_status05		char(1)	"B" = generated by package logon
erw_status06		char(1)	
gut_bas	Yield (base quantity unit)	decimal(18,6)	Yield (base quantity unit) (PDM field ID: ADEPRO.EGR:GUTB)
gut_grund	Deviation reason	integer	Deviation reason Reference: ADE GRUND_ZUORD (PDM field ID: ADEPRO.EGG:GUTB)
gut_grund_text	Reason text number	integer	Reason text number of the yield (not the text itself!!) Reference: ADE GRUND_TEXTE (PDM field ID: ADEPRO.EGT:GUTB)
gut_pri	Yield (primary)	decimal(18,6)	Yield (prim.) (PDM field ID: ADEPRO.EGR:GUTP)
gut_sek	Yield (secondary)	decimal(18,6)	Yield (sec.) (PDM field ID: ADEPRO.EGR:GUTS)
gut_ter	Yield (tertiary)	decimal(18,6)	Yield (tert.) (PDM field ID: ADEPRO.EGR:GUTT)
herkunft		char(3)	"Blank": original data record from collecting O: original data record if maintained E: manually generated data record (edited) S: cancellation for PPS (posting is deleted by upload) data records of the HERKUNFT = " ", E and S are uploaded (PDM field ID: ADEPRO.ERFART)
hub_gesamt		decimal(18,6)	Recorded strokes, total (PDM field ID: ADEPRO.GGR:HUB)
hub_gut		decimal(18,6)	Yiels STROKES (PDM field ID: ADEPRO.EGR:HUBG)
ist_lst_01	Posted free activity 1	decimal(18,6)	Posted free activity 1 (PDM field ID: ADEPRO.EGR:LST01)
ist_lst_02	Posted free activity 2	decimal(18,6)	Posted free activity 2 (PDM field ID: ADEPRO.EGR:LST02)
ist_lst_03	Posted free activity 3	decimal(18,6)	Posted free activity 3 (PDM field ID: ADEPRO.EGR:LST03)
ist_lst_04	Posted free activity 4	decimal(18,6)	Posted free activity 4 (PDM field ID: ADEPRO.EGR:LST04)
ist_lst_05	Posted free activity 5	decimal(18,6)	Posted free activity 5 (PDM field ID: ADEPRO.EGR:LST05)
ist_lst_06	Posted free activity 6	decimal(18,6)	Posted free activity 6 (PDM field ID: ADEPRO.EGR:LST06)
ist_lst_07	Posted free activity 7	decimal(18,6)	Posted free activity 7 (PDM field ID: ADEPRO.EGR:LST07)
ist_lst_08	Posted free activity 8	decimal(18,6)	Posted free activity 8 (PDM field ID: ADEPRO.EGR:LST08)
ist_lst_09	Posted free activity 9	decimal(18,6)	Posted free activity 9 (PDM field ID: ADEPRO.EGR:LST09)
ist_lst_10	Posted free activity 10	decimal(18,6)	Posted free activity 10 (PDM field ID: ADEPRO.EGR:LST10)
karenz		char(1)	"P" = waiting period record of personnel "M" = waiting period record of machines otherwise empty
kostenart		char(10)	--- (PDM field ID: ANR.KART)
kostenstelle		char(10)	Cost center of the machine (PDM field ID: ADEPRO.KST)

kostentraeger		char(40)	--- (PDM field ID: ADEPRO.KSTTR)
lle_kz		char(1)	J/N, indicates whether the log record has been processed by LLE
lohnart		char(4)	Wage type. (PDM field ID: ADEPRO.LART)
lpkz	Wage/premium indicator	char(10)	Wage/premium indicator (PDM field ID: ADEPRO.LPKZ)
lst_einh_01		char(3)	Unit of recorded activity 1 (PDM field ID: ADEPRO.EGE:LST01)
lst_einh_02		char(3)	Unit of recorded activity 2 (PDM field ID: ADEPRO.EGE:LST02)
lst_einh_03		char(3)	Unit of recorded activity 3 (PDM field ID: ADEPRO.EGE:LST03)
lst_einh_04		char(3)	Unit of recorded activity 4 (PDM field ID: ADEPRO.EGE:LST04)
lst_einh_05		char(3)	Unit of recorded activity 5 (PDM field ID: ADEPRO.EGE:LST05)
lst_einh_06		char(3)	Unit of recorded activity 6 (PDM field ID: ADEPRO.EGE:LST06)
lst_einh_07		char(3)	Unit of recorded activity 7 (PDM field ID: ADEPRO.EGE:LST07)
lst_einh_08		char(3)	Unit of recorded activity 8 (PDM field ID: ADEPRO.EGE:LST08)
lst_einh_09		char(3)	Unit of recorded activity 9 (PDM field ID: ADEPRO.EGE:LST09)
lst_einh_10		char(3)	Unit of recorded activity 10 (PDM field ID: ADEPRO.EGE:LST10)
masch_nr	Machine that is posting	char(20)	Machine that is posting (PDM field ID: ADEPRO.MNR)
meinheit_bas	Quantity unit	char(3)	Quantity unit (PDM field ID: ADEPRO.EGE:GUTB)
meinheit_pri	Quantity unit	char(3)	Quantity unit (PDM field ID: ADEPRO.EGE:GUTP)
meinheit_sek	Quantity unit	char(3)	Quantity unit (PDM field ID: ADEPRO.EGE:GUTS)
meinheit_ter	Quantity unit	char(3)	Quantity unit (PDM field ID: ADEPRO.EGE:GUTT)
nacharb_bas	Rework quantity (base quantity unit)	decimal(18,6)	Rework quantity (base quantity unit) (PDM field ID: ADEPRO.EGR:NCHB)
nacharb_grund	Rework reason	integer	Rework reason Reference: ADE GRUND_ZUORD (PDM field ID: ADEPRO.EGG:NCHB)
nacharb_grund_text	Reason text number	integer	Reason text number of the rework quantity (not the text itself!!) Reference: ADE GRUND_TEXTE (PDM field ID: ADEPRO.EGT:NCHB)
nacharb_pri	Rework quantity (primary)	decimal(18,6)	Rework quantity (prim.) (PDM field ID: ADEPRO.EGR:NCHP)
nacharb_sek	Rework quantity (secondary)	decimal(18,6)	Rework quantity (sec.) (PDM field ID: ADEPRO.EGR:NCHS)
nacharb_ter	Rework quantity (tertiary)	decimal(18,6)	Rework quantity (tert.) (PDM field ID: ADEPRO.EGR:NCHT)
p_dauer_bmk01		integer	Posted personnel activity in RPA 1 (PDM field ID: ADEPRO.EGR:PBK01)

p_dauer_bmk02		integer	Posted personnel activity in RPA 2 (PDM field ID: ADEPRO.EGR:PBMK02)
p_dauer_bmk03		integer	Posted personnel activity in RPA 3 (PDM field ID: ADEPRO.EGR:PBMK03)
p_dauer_bmk04		integer	Posted personnel activity in RPA 4 (PDM field ID: ADEPRO.EGR:PBMK04)
p_dauer_bmk05		integer	Posted personnel activity in RPA 5 (PDM field ID: ADEPRO.EGR:PBMK05)
p_dauer_bmk06		integer	Posted personnel activity in RPA 6 (PDM field ID: ADEPRO.EGR:PBMK06)
p_dauer_bmk07		integer	Posted personnel activity in RPA 7 (PDM field ID: ADEPRO.EGR:PBMK07)
p_dauer_bmk08		integer	Posted personnel activity in RPA 8 (PDM field ID: ADEPRO.EGR:PBMK08)
p_dauer_bmk09		integer	Posted personnel activity in RPA 9 (PDM field ID: ADEPRO.EGR:PBMK09)
p_dauer_bmk10		integer	Posted personnel activity in RPA 10 (PDM field ID: ADEPRO.EGR:PBMK10)
p_dauer_bmk11		integer	Posted personnel activity in RPA 11 (PDM field ID: ADEPRO.EGR:PBMK11)
p_dauer_bmk12		integer	Posted personnel activity in RPA 12 (PDM field ID: ADEPRO.EGR:PBMK12)
p_divisor		decimal(18,6)	Valid pulse factor (divisor analogous to partitioning) (PDM field ID: ADEPRO.DIV)
p_teiligkeit	Partitioning	decimal(18,6)	Valid partitioning of the posting (PDM field ID: ADEPRO.TLG)
pause		smallint	Shift break in seconds (PDM field ID: ADEPRO.SKPAUSE)
pers_dauer		integer	Posted labor time (PDM field ID: ADEPRO.EGR:PDAUER)
person_anz		smallint	Customer-specific number of persons (PDM field ID: ADEPRO.PANZ)
person_nr1		char(10)	Person who initiated the log record (PDM field ID: ADEPRO.PNR)
pgruppe		char(20)	--- (PDM field ID: ADEPRO.PGRP)
prgrp	Premium/wage group	char(10)	Premium/wage group (PDM field ID: ADEPRO.LEISTGRP)
problem_bas	Problem quantity (base quantity unit)	decimal(18,6)	Problem quantity (base quantity unit) (PDM field ID: ADEPRO.EGR:PRBB)
problem_grund	Problem reason	integer	Problem reason Reference: ADE_GRUND_ZUORD (PDM field ID: ADEPRO.EGG:PRBB)
problem_grund_text	Reason text number	integer	Reason text number of the problem quantity (not the text itself!!) Reference: ADE_GRUND_TEXTE (PDM field ID: ADEPRO.EGT:PRBB)
problem_pri	Problem quantity (primary)	decimal(18,6)	Problem quantity (prim.) (PDM field ID: ADEPRO.EGR:PRBP)
problem_sek	Problem quantity (secondary)	decimal(18,6)	Problem quantity (sec.) (PDM field ID: ADEPRO.EGR:PRBS)
problem_ter	Problem quantity (tertiary)	decimal(18,6)	Problem quantity (tert.) (PDM field ID: ADEPRO.EGR:PRBT)
pze_aw_tag		date	Evaluation date PZE (PDM field ID: ADEPRO.ABREDAT)

rck_01		char(1)	Customer-specific (PDM field ID: ADEPRO.RCK:01)
rck_01_dat	Confirmation date	date	Confirmation date (PDM field ID: ADEPRO.RCKDAT:01)
rck_01_zeit	Confirmation time	integer	Confirmation time (PDM field ID: ADEPRO.RCKZEI:01)
rck_02		char(1)	Customer-specific (PDM field ID: ADEPRO.RCK:02)
rck_02_dat	Confirmation date	date	Confirmation date (PDM field ID: ADEPRO.RCKDAT:01)
rck_02_zeit	Confirmation time	integer	Confirmation time (PDM field ID: ADEPRO.RCKZEI:02)
rck_dat	Confirmation date	date	Confirmation date (PDM field ID: ADEPRO.RCKDAT)
rck_zeit	Confirmation time	integer	Confirmation time (PDM field ID: ADEPRO.RCKZEI)
rest_bmk_01	Current remaining activity RPA 1	integer	Current remaining activity RPA 1 ATTENTION: it must be possible to reference to the IST and REST fields for the formula for the RLZ (remaining run time) (PDM field ID: ADEPRO.RGR:BMK01)
rest_bmk_02	Current remaining activity RPA 2	integer	Current remaining activity RPA 2 (PDM field ID: ADEPRO.RGR:BMK02)
rest_bmk_03	Current remaining activity RPA 3	integer	Current remaining activity RPA 3 (PDM field ID: ADEPRO.RGR:BMK03)
rest_bmk_04	Current remaining activity RPA 4	integer	Current remaining activity RPA 4 (PDM field ID: ADEPRO.RGR:BMK04)
rest_bmk_05	Current remaining activity RPA 5	integer	Current remaining activity RPA 5 (PDM field ID: ADEPRO.RGR:BMK05)
rest_bmk_06	Current remaining activity RPA 6	integer	Current remaining activity RPA 6 (PDM field ID: ADEPRO.RGR:BMK06)
rest_bmk_07	Current remaining activity RPA 7	integer	Current remaining activity RPA 7 (PDM field ID: ADEPRO.RGR:BMK07)
rest_bmk_08	Current remaining activity RPA 8	integer	Current remaining activity RPA 8 (PDM field ID: ADEPRO.RGR:BMK08)
rest_bmk_09	Current remaining activity RPA 9	integer	Current remaining activity RPA 9 (PDM field ID: ADEPRO.RGR:BMK09)
rest_bmk_10	Current remaining activity RPA 10	integer	Current remaining activity RPA 10 (PDM field ID: ADEPRO.RGR:BMK10)
rest_bmk_11	Current remaining activity RPA 11	integer	Current remaining activity RPA 11 (PDM field ID: ADEPRO.RGR:BMK11)
rest_bmk_12	Current remaining activity RPA 12	integer	Current remaining activity RPA 12 (PDM field ID: ADEPRO.RGR:BMK12)
rest_dauer		integer	Remaining run time (PDM field ID: ADEPRO.RGR:DAUER)
rest_lst_01	Current remaining activity 1	decimal(18,6)	Current remaining activity 1 (PDM field ID: ADEPRO.RGR:LST01)
rest_lst_02	Current remaining activity 2	decimal(18,6)	Current remaining activity 2 (PDM field ID: ADEPRO.RGR:LST02)
rest_lst_03	Current remaining activity 3	decimal(18,6)	Current remaining activity 3 (PDM field ID: ADEPRO.RGR:LST03)
rest_lst_04	Current remaining activity 4	decimal(18,6)	Current remaining activity 4 (PDM field ID: ADEPRO.RGR:LST04)
rest_lst_05	Current remaining activity 5	decimal(18,6)	Current remaining activity 5 (PDM field ID: ADEPRO.RGR:LST05)
rest_lst_06	Current remaining activity 6	decimal(18,6)	Current remaining activity 6 (PDM field ID: ADEPRO.RGR:LST06)

rest_lst_07	Current remaining activity 7	decimal(18,6)	Current remaining activity 7 (PDM field ID: ADEPRO.RGR:LST07)
rest_lst_08	Current remaining activity 8	decimal(18,6)	Current remaining activity 8 (PDM field ID: ADEPRO.RGR:LST08)
rest_lst_09	Current remaining activity 9	decimal(18,6)	Current remaining activity 9 (PDM field ID: ADEPRO.RGR:LST09)
rest_lst_10	Current remaining activity 10	decimal(18,6)	Current remaining activity 10 (PDM field ID: ADEPRO.RGR:LST10)
rest_p_dauer		integer	Current remaining labor duration (PDM field ID: ADEPRO.RGR:PDAUER)
rest_p_dauer_bmk01		integer	Current remaining activity of staff RPA 1 (PDM field ID: ADEPRO.RGR:PBMK01)
rest_p_dauer_bmk02		integer	Current remaining activity of staff RPA 2 (PDM field ID: ADEPRO.RGR:PBMK02)
rest_p_dauer_bmk03		integer	Current remaining activity of staff RPA 3 (PDM field ID: ADEPRO.RGR:PBMK03)
rest_p_dauer_bmk04		integer	Current remaining activity of staff RPA 4 (PDM field ID: ADEPRO.RGR:PBMK04)
rest_p_dauer_bmk05		integer	Current remaining activity of staff RPA 5 (PDM field ID: ADEPRO.RGR:PBMK05)
rest_p_dauer_bmk06		integer	Current remaining activity of staff RPA 6 (PDM field ID: ADEPRO.RGR:PBMK06)
rest_p_dauer_bmk07		integer	Current remaining activity of staff RPA 7 (PDM field ID: ADEPRO.RGR:PBMK07)
rest_p_dauer_bmk08		integer	Current remaining activity of staff RPA 8 (PDM field ID: ADEPRO.RGR:PBMK08)
rest_p_dauer_bmk09		integer	Current remaining activity of staff RPA 9 (PDM field ID: ADEPRO.RGR:PBMK09)
rest_p_dauer_bmk10		integer	Current remaining activity of staff RPA 10 (PDM field ID: ADEPRO.RGR:PBMK10)
rest_p_dauer_bmk11		integer	Current remaining activity of staff RPA 11 (PDM field ID: ADEPRO.RGR:PBMK11)
rest_p_dauer_bmk12		integer	Current remaining activity of staff RPA 12 (PDM field ID: ADEPRO.RGR:PBMK12)
rueckgemeldet		char(1)	J/N, indicates whether the log record has been uploaded to the PPS system (PDM field ID: ADEPRO.RCK)
satz_art	Record type	char(3)	Record type: A: order logons U: interruption of order, partial completion confirmation E: end of order B: logoff of persons T: partial completion confirmations of orders G: batch logon H: batch logoff (PDM field ID: ADEPRO.SART)
schicht_dat		date	Date of beginning of shift (determined on the basis of the date when reported as finished in case of cross-shift ADE records) (PDM field ID: ADEPRO.SKDAT)
schichtanf	Beginning of shift of the assigned shift	integer	Beginning of shift of the assigned shift (PDM field ID: ADEPRO.SKZEIB)
schichtart		char(1)	Shift identification (F/N/S) of the assigned shift (PDM field ID: ADEPRO.SKART)
schichtend	End of shift of the assigned shift	integer	End of shift of the assigned shift (PDM field ID: ADEPRO.SKZEIE)
schichtmodell		smallint	Underlying shift model (PDM field ID: ADEPRO.SKMOD)

schichtnr	Shift number	smallint	Employees belonging to the shift: only if MDE is used Shift number Assignment to the shift that "logs off" (PDM field ID: ADEPRO.SKNR)
sign_dat	Date of approving	date	approved (PDM field ID: ADEPRO.SIGNDAT)
sign_flag		char(1)	Indicator whether the record is signed or not
sign_zeit	Time of approving	integer	Time of approving (PDM field ID: ADEPRO.SIGNZEI)
soll_te		decimal(18,6)	Target Te from table Auftrags_Bestand (PDM field ID: ADEPRO.EGR:TE)
soll_teb		decimal(18,6)	Target TEB from table Auftrags_Bestand (PDM field ID: ADEPRO.EGR:TEB)
soll_tr		decimal(18,6)	Target TR from AB (PDM field ID: ADEPRO.EGR:TR)
soll_trb		decimal(18,6)	Target TRB from AB (PDM field ID: ADEPRO.EGR:TRB)
terminalnr		smallint	Terminal at which the logon was triggered (PDM field ID: ADEPRO.TNR)
user_c_29		char(1)	User-specific field (PDM field ID: ADEPRO.FU:29)
user_c_30		char(1)	User-specific field (PDM field ID: ADEPRO.FU:30)
user_c_31		char(1)	User-specific field (PDM field ID: ADEPRO.FU:31)
user_c_32		char(1)	User-specific field (PDM field ID: ADEPRO.FU:32)
user_c_33		char(1)	User-specific field (PDM field ID: ADEPRO.FU:33)
user_c_34		char(1)	User-specific field (PDM field ID: ADEPRO.FU:34)
user_c_35		char(1)	User-specific field (PDM field ID: ADEPRO.FU:35)
user_c_36		char(1)	User-specific field (PDM field ID: ADEPRO.FU:36)
user_c_37		char(1)	User-specific field (PDM field ID: ADEPRO.FU:37)
user_c_38		char(1)	User-specific field (PDM field ID: ADEPRO.FU:38)
user_c_39		char(1)	User-specific field (PDM field ID: ADEPRO.FU:39)
user_c_40		char(1)	User-specific field (PDM field ID: ADEPRO.FU:40)
user_c_41		char(1)	User-specific field (PDM field ID: ADEPRO.FU:41)
user_c_42		char(1)	User-specific field (PDM field ID: ADEPRO.FU:42)
user_c_43		char(1)	User-specific field (PDM field ID: ADEPRO.FU:43)
user_c_44		char(1)	User-specific field (PDM field ID: ADEPRO.FU:44)

user_c_45		char(10)	Transfer from ade_protokoll.arbeitsgang RW 7.1->7.2: transfer from table ade_protokoll from field: arbeitsgang (PDM field ID: ADEPRO.FU:45)
user_c_46		char(10)	Transfer from ade_protokoll.param_str01 RW 7.1->7.2: transfer from table ade_protokoll from field: param_str01 (PDM field ID: ADEPRO.FU:46)
user_c_47		char(10)	User-specific field (PDM field ID: ADEPRO.FU:47)
user_c_48		char(10)	User-specific field (PDM field ID: ADEPRO.FU:48)
user_c_49		char(10)	User-specific field (PDM field ID: ADEPRO.FU:49)
user_c_50		char(10)	User-specific field (PDM field ID: ADEPRO.FU:50)
user_c_51		char(20)	User-specific field (PDM field ID: ADEPRO.FU:51)
user_c_52		char(20)	User-specific field (PDM field ID: ADEPRO.FU:52)
user_c_53		char(20)	User-specific field (PDM field ID: ADEPRO.FU:53)
user_c_54		char(20)	User-specific field (PDM field ID: ADEPRO.FU:54)
user_c_55		char(20)	User-specific field (PDM field ID: ADEPRO.FU:55)
user_c_56		char(20)	User-specific field (PDM field ID: ADEPRO.FU:56)
user_c_57		char(20)	User-specific field (PDM field ID: ADEPRO.FU:57)
user_c_58		char(20)	User-specific field (PDM field ID: ADEPRO.FU:58)
user_c_59		char(20)	User-specific field (PDM field ID: ADEPRO.FU:59)
user_c_60		char(20)	User-specific field (PDM field ID: ADEPRO.FU:60)
user_c_61		char(20)	User-specific field (PDM field ID: ADEPRO.FU:61)
user_c_62		char(20)	User-specific field (PDM field ID: ADEPRO.FU:62)
user_c_63		char(20)	User-specific field (PDM field ID: ADEPRO.FU:63)
user_c_64		char(20)	User-specific field (PDM field ID: ADEPRO.FU:64)
user_c_65		char(40)	RW 7.1->7.2: transfer from table ade_protokoll from field: param_str02 (PDM field ID: ADEPRO.FU:65)
user_c_66		char(40)	User-specific field (PDM field ID: ADEPRO.FU:66)
user_code		char(8)	User field key Object "ADEPRO"; in a first step the user field configuration is configured cross-system per "SYSTEM"
user_d_01		date	User-specific field (PDM field ID: ADEPRO.FU:1)
user_d_02		date	User-specific field (PDM field ID: ADEPRO.FU:2)

user_d_03		date	User-specific field (PDM field ID: ADEPRO.FU:3)
user_d_04		date	User-specific field (PDM field ID: ADEPRO.FU:4)
user_d_05		date	User-specific field (PDM field ID: ADEPRO.FU:5)
user_d_06		date	User-specific field (PDM field ID: ADEPRO.FU:6)
user_f_23		decimal(18,6)	RW 7.1->7.2: transfer from ade_protokoll from field: param_02 (PDM field ID: ADEPRO.FU:23)
user_f_24		decimal(18,6)	User-specific field (PDM field ID: ADEPRO.FU:24)
user_f_25		decimal(18,6)	User-specific field (PDM field ID: ADEPRO.FU:25)
user_f_26		decimal(18,6)	User-specific field (PDM field ID: ADEPRO.FU:26)
user_f_27		decimal(18,6)	User-specific field (PDM field ID: ADEPRO.FU:27)
user_f_28		decimal(18,6)	User-specific field (PDM field ID: ADEPRO.FU:28)
user_n_07		integer	Transfer from ade_protokoll.mstck RW 7.1->7.2: transfer from table ade_protokoll from field: mstck (PDM field ID: ADEPRO.FU:7)
user_n_08		integer	User-specific field (PDM field ID: ADEPRO.FU:8)
user_n_09		integer	User-specific field (PDM field ID: ADEPRO.FU:9)
user_n_10		integer	User-specific field (PDM field ID: ADEPRO.FU:10)
user_n_11		integer	User-specific field (PDM field ID: ADEPRO.FU:11)
user_n_12		integer	User-specific field (PDM field ID: ADEPRO.FU:12)
user_n_13		integer	User-specific field (PDM field ID: ADEPRO.FU:13)
user_n_14		integer	User-specific field (PDM field ID: ADEPRO.FU:14)
user_n_15		integer	User-specific field (PDM field ID: ADEPRO.FU:15)
user_n_16		integer	User-specific field (PDM field ID: ADEPRO.FU:16)
user_n_17		integer	User-specific field (PDM field ID: ADEPRO.FU:17)
user_n_18		integer	User-specific field (PDM field ID: ADEPRO.FU:18)
user_n_19		integer	User-specific field (PDM field ID: ADEPRO.FU:19)
user_n_20		integer	User-specific field (PDM field ID: ADEPRO.FU:20)
user_n_21		integer	User-specific field (PDM field ID: ADEPRO.FU:21)
user_n_22		integer	User-specific field (PDM field ID: ADEPRO.FU:22)

verw_merk		integer	Marker for editing log records, reference to a correction data record
verweis		serial	Unique indicator for log record, important for editing log records (PDM field ID: ADEPRO.VERWEIS)

2.13. ade_seriennummern

Table name: ade_seriennummern		Product: BDE	
Archive table: a_ade_seriennummer		Reload table: r_ade_seriennummer	
Designation: Serial numbers of the order		Description: <Description of the content of the table> * Notes <special notes for acting with the table. Drop line if not needed> * Keys <key fields with unique access> * logical connection to other tables <description of tables, to which logical connections exist > <incl. description of the join to the foreign table and columns>	
Column name	Column designation	Type	Description
a_typ	Order type	char(4)	Order type AU = order header AG = OP (PDM field ID: SNR.ATYP)
auftrag_nr	Order no.	char(40)	Order for AU: order number for AGNR = OP Plausibility check for INSERT, UPDATE if available in auftrags_bestand (PDM field ID: SNR.ANR)
bearb	Last editor	char(10)	Last changed is logged here, i.e. even if the indicator BELEGT has been changed.
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
belegt	Allocated	char(2)	Allocated F = Free G = Yield A = Scrap P = Problem N = Rework [X = Blocked) "F" is preallocated if no BELEGT is transferred for INSERT. At first, there is no plausibility check for a valid value range (PDM field ID: SNR.BEL)
grund	Reason	integer	---
grundtext_nr	Reason text number	integer	Reason text number In case of A/P/N: Reason text number of the assignment; this is the respective reason, which has been entered. Plausibility check at INSERT, UPDATE (PDM field ID: SNR.GRTXTNR)
serien_nr	Serial number	char(20)	Serial number SAP: EQNR CHAR(18) (PDM field ID: SNR.SNR)
verweis	Reference	serial	--- (PDM field ID: SNR.VERWEIS)

2.14. ade_status_texte

Table name: ade_status_texte		Product: BDE	
Designation: Order status texts		Description: Order status texts Descriptive texts that can be used as descriptions for order status assignment. The goal is to use standard status texts for all order types. # Key statustext_nr, a_typ # Connections to other tables ade_status_zuord	
Column name	Column designation	Type	Description
a_typ	Status text type	char(2)	Status text type There is only one valid value in this column: AU = Status texts based on orders (PDM field ID: ASTTXT.ATYP)
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
statustext	Status text	char(20)	Status text (PDM field ID: ASTTXT.ASTTXT)
statustext_nr	Status text number	integer	Status text number (PDM field ID: ASTTXT.ASTTXTNR)

2.15. ade_status_zuord

Table name: ade_status_zuord		Product: BDE	
Designation: Assignment of order status		Description: Order status assignment Assignment of different order statuses to the various order types. # Key status, statustyp, auftrag_art # Connections to other tables ade_auftragsarten, ade_status_texte	
Column name	Column designation	Type	Description
a_stufe	Authorization level	char(3)	Required authorization (level) to set a status manually. This is especially required for setting the preparation status manually but can also be used for other status. (PDM field ID: AST.ASTUFE)
aend_s_status	Change of secondary status allowed	char(1)	Change of secondary status allowed (J/N) May the secondary status of an operation be changed if this order or operation status is available? While checking, the order status indicator as well as the operation status indicator have to be taken into account (for both statuses the flags have to be set to "J") This flag has to be considered for the processing of the preparation status (PDM field ID: AST.OPT:ASTS)
aenderbar	Alterable	char(1)	With this status the order or OP may be/may no longer be changed manually or by the PPS system. If this status is set, the order or the operation may either be altered by the PPS system or manually or it may no longer be altered. J: office client and MLE interface (PPS=J) alterable N: office client and MLE interface not alterable K: Only office client alterable (not via the MLE interface) M: Only MLE interface alterable (not via the console) This option does not refer to the priority, notes, long texts, secondary statuses. (PDM field ID: AST.PLAUS:EDIT)
aktion	Action used for the status	char(10)	Action used for the status e.g. L = Log on operation Status can be set optionally when login on an operation empty: default L: Running S: Other Not used at the moment. (PDM field ID: AST.AKTION)
aktion_vererben	Inheritance action for dependent operations	char(1)	Inheritance rule for dependent operations Not processed at the moment. (PDM field ID: AST.OPT:AKTIONVERERB)
anmeldbar	Can be logged on	char(1)	Can be logged on (J/N) Check to assure if the CURRENT status has set this indicator. If the operation is interrupted/ finished, the field is ignored. Please note: If an OP or an order have been set with the flag "locked", then the OP may not be logged on under any circumstances (irrespective of this setting) (PDM field ID: AST.OPT:AAN)
auftrag_art	Order type	char(5)	Order type the status is configured for. The order status is configured based on the order type. This means that for each order type the relevant order and operation statuses must be defined. Enter a valid order type in this field, for which the status should apply. (PDM field ID: AST.AUART)
bearb	Last editor	char(10)	Last editor

bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
bmk_nr	Posting RPA	smallint	RPA the order duration is posted to if VERBUCHUNG = A (1-12) The RPA of the status that is currently available at the machine does not play a role in this context. Currently not used (PDM field ID: AST.BMKNR)
farbe	Color	smallint	Color of the relevant status (text). At this time, this color is only used in shop floor scheduling (HLS). (PDM field ID: AST.COLOR)
folgentausch	Sequence change	char(1)	Sequence change allowed (J/N) Definition whether sequences may be changed for this order status or whether it is no longer allowed. Only relevant if sequences are in use. Currently not used (PDM field ID: AST.OPT:FOLG)
freigabe_nachf_ag	Release of subsequent operation	char(1)	Release of subsequent OP (J/N) If this indicator is set, then setting the status will result in the status of the subsequent OP(s) being set to the release status, i.e. set to the status assigned with the control indicator "V". This only happens if the subsequent OP(s) has (have) not yet been run, was (were) interrupted or has (have) been finished. Thus, this option only makes sense if new operations are not created/ transferred using the status with the control indicator "V". Please note: As opposed to processing up to ADE 7.1, the release is no longer given as a result of automatically scheduling the operation to a planned workplace, but instead only by setting the aforementioned release status. (PDM field ID: AST.OPT:ANRNFREIG)
init	Initial status during creation	char(1)	Initial status during creation (J/N) The status having this flag is marked as the initial status that is to be set when a new order (A) or OP (G, S, R) is created. Exactly one status must be set using this indicator for both the order as well as the operation. Please note: If the initial status is not the status with the control indicator "V", then the status of the first operation as well as that of the order is set using the control indicator "V" after the first scheduling, provided that the indicator "Scheduling without implicit order release" is not set at the order type. Status can be set manually (PDM field ID: AST.EAST)

loeschaktion	Delete action	char(1)	Behavior indicating how the order or the operation should respond during the deletion process, i.e. at the time of deletion (now) or when a deletion flag is triggered: ORDER L: If something is physically deleted and all operations are physically deleted as well (order header controls the behavior) E: Order is set to the status with the control indicator "E". WARNING: Only the order header, i.e. for the OPs the indicator must also be set! D: Order is set to status with control indicator "D" and is deleted/ archived using the archiving/ deletion program (data management) after the set period. How the operations are treated is described via the indicator RESET ACTION (LOESCHAKTION) at the status of each OP. X: If the action was triggered by the MLE interface: Order is set to the status with the control indicator "E". WARNING: Only the order header, i.e. for the OPs the indicator must also be set! If the action was NOT triggered by the MLE interface: If something is physically deleted and all operations are physically deleted as well (order header controls the behavior) OPERATION L: Is physically deleted. D: Is set to the status with the control indicator "D". E: OP is set to the status with the control indicator "E" (fixed). X: If the action was triggered by the MLE interface: OP is set to the status with the control indicator "E" (fixed). If the action was NOT triggered by the MLE interface: OP is physically deleted. The reset/deletion action should be the same for both the order header as well as for the OPs, because currently the settings each relate to the order or to OPs and the OPs do not "inherit" anything from their order header. To assure that an order or an operation can no longer be deleted as of a certain status, the indicator must be set at all corresponding statuses. (PDM field ID: AST.DELVERB)
loeschbar	Deletable	char(1)	May the order or the operation be deleted in this status (manually, via PPS system)? (J/N) ORDER J: Yes, BUT only if the operations can be deleted, i.e. at no operation may a status be set that has a control indicator "L" AND for which the "deletable" indicator is set to "N". N: No deletion allowed OPERATION J: If the OP is running, then the deletion flag is set. N: No deletion allowed Please note: Operations with a current status with a control indicator "L" or "F" may as a rule not be deleted, irrespective of this setting. (PDM field ID: AST.PLAUS:DEL)
manuell_setzbar	Status can be set manually	char(1)	Status can be set manually (J/N) The status can/may be changed manually, i.e. set. J is only allowed if "SO" (blank) is entered in the production indicator (PROD_KENN) field of the operation; otherwise the field is to be assigned to "N" and read-only!! For the preparation status the field is always assigned to "J" and read-only! To be considered for manual status changes. (PDM field ID: AST.OPT:MANU)
mat_bmk_nr	RPA for material bookings	smallint	RPA for material bookings (1-12) Currently not used (PDM field ID: AST.MAT:BMK)

nachfolg_abmeldbar	Successor can be logged off	char(1)	Successor can be logged off (J/N) If the indicator "Can be finished" ("Entry" index tab) is set to "S" = status at the order type, then this indicator is used to check whether the subsequent OP can be logged off. The indicator relates to the preceding OP! Example 1: If an OP logoff of the subsequent OP is not to be allowed until the preceding OP has also at least begun, then this indicator must be set to "J" (y – yes) if the status is "running", "interrupted" or "finished". Example 2: If an OP logoff of the subsequent OP is not to be allowed until the preceding OP has finished, then this indicator needs only to be set if the status is "finished" . All preceding OPs resulting from relationships in ADE_AUFTRAGSNETZ, are checked in this regard. (PDM field ID: AST.OPT:ANRNAAB)
nachfolg_anmeldbar	Successor can be logged on	char(1)	Successor can be logged on (J/N) If the indicator "Check of preceding OP" ("Plausibilities" index tab) is set to "S" = status at the order type, then this indicator is used to check whether the subsequent OP can be logged on. The indicator relates to the preceding OP! If, for example, an OP logon of the subsequent OP is not to be allowed until the preceding OP has at least begun, then this indicator must be set if the status is "running", "interrupted", "finished" (possibly "deleted"). If, for example, an OP logon of the subsequent OP is not to be allowed until the preceding OP has finished, then this indicator needs only to be set if the status is "finished" (possibly "deleted"). All preceding OPs resulting from relationships in ADE_AUFTRAGSNETZ, are checked in this regard. (PDM field ID: AST.OPT:ANRNAAN)
opt_erfassung		char(10)	free
opt_planung		char(10)	free
p_bmk_nr	RPA for person bookings	smallint	RPA for person bookings (1-12) (PDM field ID: AST.PNR:BMK)
planen	Planning	char(1)	Planning N: No planning (no transfer to the planning component) T: Scheduling only F: Scheduling and detailed planning (dispatching) - also includes the simulation The indicator "N" at the order overrides the indicator at the operations. Conversely, the indicators at the operations override the indicator "J" at the order --> to be considered for: shop floor scheduling / Detailed scheduling (PDM field ID: AST.OPT:PLAN)
prio_pruefung	Check for priority	char(1)	Check for priority (J/N) When an order is newly created/ modified, the system checks it against priority management (order group). For this evaluation, all orders with statuses assigned to this indicator are checked. Please note: The priority check is only performed for order/ operation modifications if the priority was actually changed during the modification process. (PDM field ID: AST.PLAUS:PRIO)

prod_kenn	Control indicator	char(2)	Control / Production indicator Status type A (order status) V: Prepared. Release (for automatic release) L: In process. At least one OP was started E: Finished. All OPs are finished or deleted. S: None. All others Status type G (OP status) V: Prepared. "Release indicator" for status; before OP is edited for the first time L: Running. Is set automatically once OP is logged on U: Interrupted. Is set automatically once OP is interrupted F: Autom. interrupted. Is set by the server if you want the OP to be interrupted automatically at the time of a shift change (when using the MDE function at the terminal) E: Finished. Is set automatically once OP is finished S: None. Other status; not automatically set. Means that no work has yet been done on the OP An OP has not yet begun if its status is set with a control indicator: "V" or "S". Explicitly setting an order to the status using the control indicator "E" will result in all OPs being set to the status with the control indicator "E". The control indicator "A" means "archived"; it is not set via configuration, but is instead a fixed setting made at the time the data are transferred into the long-term table. Except for "S", there must be exactly 1 status with this indicator for each order type To be considered for - automatic setting of predecessor status (e.g. A_AN, A_UN) - manual setting of predecessor status - Automatic finishing of predecessor OP - Automatic release (after lead time scheduling) - deletion processing (as a precaution) (PDM field ID: AST.OPT:PKENN)
res_bmk_nr	RPA for resource bookings	smallint	RPA for resource bookings (1-12) Currently not used. (PDM field ID: AST.RES:BMK)
res_check	Resource check	char(1)	Resource check (J/N) No resource check is required provided that this processign status is active at the operation, i.e.: Resource check results are ignored. Currently not used in standard (PDM field ID: AST.OPT:RESPLAUS)
status	Status	char(5)	This is the externally valid status (PDM field ID: AST.AST)
status_vererben	Inheritance rule for dependent operations	char(1)	Inheritance rule for dependent OPs e.g. automatic log on by predecessor operation (PDM field ID: AST.OPT:STAVERRERB)
statustext_nr	Status text No.	integer	Reference to the order status text table (PDM field ID: AST.ASTTXTNR)
statustyp	Status type	char(1)	Status type A: Status refers to the (entire) order G: Status refers to the operation S: This is the preparation status (=secondary status) at the operation. (PDM field ID: AST.ASTTYP)

symbol	Symbol	char(12)	Symbol assigned to the status. It is displayed in different functions/ evaluations (e.g. order overview). The following values are allowed (case sensitive): l.bmp: light green led e.bmp: dark green led v.bmp: gray led u.bmp: yellow led f.bmp: yellow and light green led n.bmp: pink led a.bmp: black led p.bmp: blue led x.bmp: red led (PDM field ID: AST.ICON)
user_c_07	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_08	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_09	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_10	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_11	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_12	Alphanumeric user field	char(10)	Alphanumeric field reserved for user specific data
user_c_13	Alphanumeric user field	char(10)	Alphanumeric field reserved for user specific data
user_c_14	Alphanumeric user field	char(20)	Alphanumeric field reserved for user specific data
user_c_15	Alphanumeric user field	char(20)	Alphanumeric field reserved for user specific data
user_c_16	Alphanumeric user field	char(40)	Alphanumeric field reserved for user specific data
user_code	User field key	char(8)	User field key Reference to the configuration of the user field key or its user fields in the HYD_USERFIELDCFG table (PDM field ID: AST.USRFLD)
user_f_05	Decimal user field	decimal(18,6)	Decimal field reserved for user specific data
user_f_06	Decimal user field	decimal(18,6)	Decimal field reserved for user specific data
user_n_01	Numeric user field	integer	Numeric field reserved for user specific data
user_n_02	Numeric user field	integer	Numeric field reserved for user specific data
user_n_03	Numeric user field	integer	Numeric field reserved for user specific data
user_n_04	Numeric user field	integer	Numeric field reserved for user specific data
verbuchung	Posting	char(1)	Posting M: Posting to the RPA of the workplace status A: Posting to the RPA of the operation is made using the RPA of the status currently active at the workplace (default). Examples: - OP is started with "setup"; but the machine is stopped - Maintenance - Times do not refer to the machine - OP is interrupted but is still logged on to the machine; the machine itself does something else Logon to terminal: without explicit indication of the OP status: the status configured with PROD_KENNZ = .AN is taken automatically including explicit indication of the OP status (possibly with list selection of all OP statuses with VERBUCHUNG = A): the OP status is set (OP status should be displayed at the terminal) (PDM field ID: AST.OPT:VERB)
verbuchung_mat	Posting on material	char(1)	Posting of durations on material (J/N) Currently not used (PDM field ID: AST.MAT:VERBDAUER)
verbuchung_mengen	Posting of quantities	char(1)	Posting of automatic quantities and cycles Currently not used (PDM field ID: AST.ANR:VERBMENGE)

verbuchung_mng_mat	Posting of quantities on material	char(1)	Posting of automatic quantities and cycles on material (J/N) Currently not used (PDM field ID: AST.MAT:VERBMENGE)
verbuchung_mng_res	Posting of quantites on resources	char(1)	Posting of automatic quantities and cycles on resources (J/N) Currently not used (PDM field ID: AST.RES:VERBMENGE)
verbuchung_pdauer	Posting of person durations	char(1)	Posting of labor time (M/P) - person RPAs an labor time in U/E/B records - person RPAs and labor time in operation status (PDM field ID: AST.PNR:VERBDAUER)
verbuchung_res	Posting on resources	char(1)	Posting of durations on resources (J/N) (PDM field ID: AST.RES:VERBDAUER)
vorgabeliste	Sequencing list	char(1)	Sequencing list (J/N) If this status is set, the operation is displayed in the sequencing list at the terminal Please note: If an OP or an order are assigned to the "blocked" flag, the OP is by no means displayed (irrespective of this setting) (PDM field ID: AST.OPT:VLIST)

2.16. ade_verarb_codes

Table name: ade_verarb_codes		Product: BDE	
Designation: Processing codes		Description: Processing codes A processing code is a collection of options that are used to control the operations. Each operation references this kind of processing code, and as a result its performance is defined in relation to planning, collection or posting. # Key verarb_code # Connections to other tables auftrags_bestand, arbplan_bestand	
Column name	Column designation	Type	Description
aend_s_status	Change of secondary status	char(1)	Change of secondary status (J/N) The secondary status may be set for OPs with this processing code Default = J (PDM field ID: VACODE.OPT:ASTS)

auto_a_ab_menge	Terminate OP when reaching target quantity	char(4)	An OP is automatically logged off from the workplace when the produced quantity equals the target quantity. In case of operations that are logged on to several workplaces, the operation cannot be logged off automatically when the target quantity is reached. This means that the operation is only logged off from the workplace at which you identified that the target quantity is reached. The operation is not logged off from other workplaces (that are logged on in parallel). [1,1] Automatic Logoff When calculating the quantity produced, the items of the option "Consider additionally when terminating" (see below --> [2,2]-[4,4]) are taken into account. If none of the options is set, the quantity produced is derived from the yield only (primary quantity unit). Corresponds to value in auftrags_bestand.abmeldopt[3,3] Possible values: N: No automatic logoff when target quantity is reached (default) J: Automatic logoff when target quantity is reached U: Automatic interruption when target quantity is reached F: Automatic logoff and logon of subsequent OP with identical article number. The operation that should be logged on is the operation that is planned next at this workplace (the selection criterion is the planned start of the operation at the workplace). If the article number is identical to the article number of the logged off operation, this operation is logged on to the workplace. If the article number of the operation planned next is not identical to the article number of the logged off operation, the operation is not logged on. K: Campaign control. Automatic logoff and logon of subsequent OP of the same campaign (only relevant in connection with the grouping function of Shop Floor Scheduling, license HLS-KPG). [2,2] Consider additionally when terminating: scrap Scrap is additionally taken into account when an operation is finished. This option is integrated in both options "Terminate OP when reaching target quantity" and "Terminate preceding OP". A subsequent change of this option in the processing code has no effect on already existing operations. Possible Values: J/N [3,3] Consider additionally when terminating: rework The rework quantity is additionally taken into account when an operation is finished This option is integrated in both options "Terminate OP when reaching target quantity" and "Terminate preceding OP". A subsequent change of this option in the processing code has no effect on already existing operations. Possible Values: J/N [4,4] Consider additionally when terminating: open quantity The open quantity is additionally taken into account when an operation is finished This option is integrated in both options "Terminate OP when reaching target quantity" and "Terminate preceding OP". A subsequent change of this option in the processing code has no effect on already existing operations. Possible Values: J/N (PDM field ID: VACODE.OPT:AUTOAABMENGE)
-----------------	--	---------	--

auto_a_ab_vanr	Terminate predecessor OP	char(1)	Termination of predecessor OPs until the next start of a milestone (included) ("milestone processing") If an operation with the enabled option "Terminate preceding OP" in the processing code is logged off (posting A_AB) or terminated (posting A_BE), all directly preceding operations within the order network of the operation are terminated. It depends on the respective status, if the preceding operations are logged off. · Logged on operations are logged off (posting A_AB) · Interrupted operations are terminated (posting A_BE) J: All preceding OPs are automatically terminated when the OP is logged off without quantity posting (logged on OPs only if "External processing" is set). M: All preceding OPs are automatically terminated when the OP is logged off while the remaining quantity is automatically posted. When calculating the quantity produced, the items of the option "Consider additionally when terminating" (see below) are taken into account. If none of the options is set, then the remaining quantity is derived from the difference of target quantity minus yield (primary quantity unit in each case). N: No automatic finish j_ : All preceding OPs are terminated automatically when the OP is logged off without quantity posting (including logged on OPs). m_ : All preceding OPs are finished automatically when the OP is logged off while the remaining quantity is automatically posted (including logged on OPs). All preceding operations are logged off or terminated up to the operation that has the option "Beginning of milestone" set in the processing code. If the option is not checked, the processing continues up to the first operation of the order. The processing is performed asynchronously. (PDM field ID: VACODE.OPT:AUTOAABVANR)
auto_a_an_vanr	Automatic logon by predecessor OP	char(1)	Automatic logon by predecessor OP (J/N) During OP logon, the system automatically logs on all direct subsequent OPs to the planned workplace that include this enabled option. If the operation has not yet been planned for a workplace, the operation is logged on to the first workplace of the group (workplace with the lowest number). Please note: A subsequent change of this option in the processing code has no effect on already existing operations. (PDM field ID: VACODE.OPT:AUTOAANVANR)
auto_a_un_ab	Interrupt/terminate OP	char(1)	Interrupt OP instead of terminating it U: When the OP is manually logged off, it is not terminated, but instead it is simply interrupted B: Terminate OP instead of interrupting it E/N/empty: No use This option should not be used in combination with the options "Terminate preceding OPs". If this option is used in combination with the option "Terminate OP when reaching target quantity", the option "Interrupt OP instead of terminating it" will take priority, i.e. the OP/OPs is/are not terminated but are simply interrupted. A subsequent change of this option in the processing code has no effect on already existing operations. This is because when creating a new operation, the value is initialized with value in auftrags_bestand.abmeldopt[1,1] (PDM field ID: VACODE.OPT:AUTOAUNAB)
auto_a_un_vanr	Automatic transfer of interruption to preceding OP	char(1)	Automatic transfer of an interruption to the preceding OPs up to the next beginning of milestone. A subsequent change of this option in the processing code has no effect on already existing operations. U: Automatic interruption of all predecessor OPs when interrupting the OP N: No automatic interruption of predecessor OP All predecessor OPs are interrupted or finished until that OP for which the "milestone start" indicator is set to "J" within the processing code. If it is not set, processing continues to the first OP. (PDM field ID: VACODE.OPT:AUTOAUNVANR)
auto_caq_ab	Logoff by main OP	char(1)	Logoff by main OP This parameter is only available with operations that are linked to a main operation. J: The moment the main operation is logged off or interrupted, the system automatically tries to log off or interrupt all linked operations. N: The moment the main operation is logged off or interrupted, the system does not try to log off or interrupt all linked operations. (PDM field ID: VACODE.OPT:AUTOCAQAB)

auto_caq_an	Logon by main OP	char(1)	Logon by main OP This parameter is only available with operations that are linked to a main operation. J: The moment the main operation is logged on, the system automatically tries to log on all linked operations. The configurations of the variable workplaces are taken into account when the workplaces to which the linked operations should be logged on to are identified. N: The moment the main operation is logged on, the linked operations are automatically logged on as well. (PDM field ID: VACODE.OPT:AUTOCAQAN)
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
bemerkung	Designation	char(40)	Designation or description of the processing code (PDM field ID: VACODE:AUGRP.BEM)
buch_pruef_masch	Booking onto additional workplace	char(1)	V booking onto additional machine (J/N) (PDM field ID: VACODE.OPT:VERBPMNR)
caq_ag	Inspection OP	char(1)	Inspection OP (J/N) This field identifies a QM operation. This kind of operation is not uploaded to a leading system once finished. And if configured accordingly, the system automatically finishes such operations once a related inspection step is finished. J: Operations assigned to this processing code are pure inspection operations. These operations only have quality control purposes and do not generate output of semi-finished or finished products. N: Operations assigned to this processing code are not pure inspection operations. These operations generate output of semi-finished or finished products. (PDM field ID: VACODE.CAQAG)
chargen_pflcht	Batch management requirement	char(1)	Batch management requirement (J/N) If this option is checked, the batch management is required for this OP (only relevant for ADE-CHV or MPL). Please note: This information is redundantly stored in the operation. Only the information stored in the operation is relevant for processing. (PDM field ID: VACODE.OPT:CNR)
erfassbar	Recordable	char(1)	This identifier defines whether operations for orders of this order type can be recorded or not, i.e. posted as defined in BDE (shop floor data collection). J: Yes, operations can be recorded as defined in BDE. Whether an operation is really recordable also depends on the setting with the same name in the Order types. N: The operation is for information purposes only ("info operation") and may not be posted as defined in BDE. An attempt to log on any such operation is rejected with a validation error. Please note: 1) To ensure that an operation does not appear in the sequencing list on the terminal, the option sequencing list (see below) should be disabled. 2) An info OP is automatically finished with the end of the subsequent OP. Requirement: the operation is planned for a machine that "may be posted". (PDM field ID: VACODE.OPT:ERF)
freigabe	Release of rework OP	char(1)	Release of the rework operation (P/N) If this option is enabled, the initial status in status assignment is ignored and the status of the operation is set to the control indicator "V" when an operation is initially created or transferred from the PPS system. Necessary PRE-CONDITION: The preceding operation in the sequence must be finished; i.e. it currently is assigned a status with control indicator "E" If this flag is explicitly set to "P" (like problem) the initial status is ignored within status configuration when ANR.INSERT and the OP is set to the status with production characteristic = "V" BUT ONLY IF the predecessor OP has not yet been finished in the sequence, i.e. its prod_kenn is <> "E". (PDM field ID: VACODE.OPT:FREIG)

fremdbearbeitung	External processing OP	char(1)	This identifier defines whether the operation is an internal or external processing operation. J: The operation is processed externally. If this option is active, detailed scheduling is automatically INACTIVE. For such operations the lead time is only scheduled from the delivery time. N: The operation is processed in-house. For such operations capacity requirements result from process times: -> setup time (fixed and dynamic setup time) -> processing time -> teardown time All process times listed in the following are considered for lead time scheduling: -> waiting time -> setup time (fixed and dynamic setup time) -> processing time -> inspection time -> teardown time -> wait time -> transport time -> both, to avoid differentiation Please note: If this option is active, the identifier Planning should be set to either "T" or "N". (PDM field ID: VACODE.OPT:FREMDFERT)
mehrfach_kz	Parallel logon possible	char(1)	Parallel logon possible for this OP J: Multiple/parallel logons are possible for an operation with this processing code N: An operation with this processing code may be logged on only once (PDM field ID: VACODE.OPT:MULTIMNR)
meilensteinbeginn	Beginning of milestone	char(1)	This option is relevant in connection with the option "Terminate preceding OPs" (DB field AUTO_A_AB_VANR). Therefore the processing logic is described below with this DB field. Please note: A subsequent change of this option in the processing code has no effect on already existing operations. This flag is relevant in connection with the following "terminate preceding OPs" flags BAPI: transfered to auftrags_bestand.abmeldopt[8,8] (PDM field ID: VACODE.OPT:MLSB)
menge_pri_uebli	Overdelivery	float	Overdelivery is allowed for this operation. The value entered is a percentage of the target quantity. Whether overdelivery is allowed or not, results from MENGE_PRI_UEBLI_R and the percentage. The values in field MNGENPRUEFUNG define which values should be included besides yield. Example: For a target quantity of 100 pieces and an allowed overdelivery of a maximum of 120 pieces, the value 120 must be entered here. Overdelivery is checked when the operation is logged off or interrupted, and also when a partial quantity is confirmed/uploaded. (PDM field ID: VACODE.MENGEPROZ:UEBLI)
menge_pri_uebli_r	Reaction to overdelivery	char(1)	Reaction to overdelivery empty: Tolerance is not checked X; Error which is created if the tolerance quantity defined as percentage in the above-mentioned field Overdelivery is not reached or exceeded. This validation check may not be overridden by a mandatory posting. W: Warning if tolerance quantity is exceeded or not reached. This validation check may be overridden by a mandatory posting (PDM field ID: VACODE.OPT:UEBLIR)

menge_pri_untli	Underdelivery	float	Underdelivery is allowed for this operation. The value entered is a percentage of the target quantity. Whether overdelivery is allowed or not, results from MENGE_PRI_UNTLI_R and the percentage. The fields described below in the section Consider additionally in case of inspections define which values should be included besides yield. Example: For a target quantity of 100 pieces and an allowed underdelivery of at least 80 pieces, the value 80 must be entered here. Underdelivery is only checked when the operation is logged off. (PDM field ID: VACODE.MENGEPROZ:UNTLI)
menge_pri_untli_r	Reaction to underdelivery	char(1)	Reaction to underdelivery empty: Tolerance is not checked X: Error which is created if the tolerance quantity defined as percentage in the above-mentioned field Underdelivery is not reached. This validation check may not be overridden by a mandatory posting. W: Warning if tolerance quantity is exceeded or not reached. This validation check may be overridden by a mandatory posting (PDM field ID: VACODE.OPT:UNTLIR)
mengenpruefung	Quantity check	char(4)	Quantity check [1,1] Activate 100 % quantity check (J/N) If this option is enabled, the entire target quantity of the operation must be declared as yield or (for example) as scrap, i.e. the total quantity must be at least equal to the target quantity. For this reason, an operation may only be logged off if the total target quantity has been confirmed/uploaded, i.e. the total quantity was either posted as yield or scrap. [2,2] Consider additionally in case of inspections: Scrap (J/N) When under/overdelivery or quantity is checked, scrap must also be included. [3,3] Consider additionally in case of inspections: Rework quantity (J/N) When under/overdelivery or quantity is checked, rework quantity must also be included. [4,4] Consider additionally in case of inspections: Open quantity (J/N) When under/overdelivery or quantity is checked, open quantity must also be included. (PDM field ID: VACODE.PLAUS:MENGE)
nacharbeits_ag	Rework OP	char(1)	Rework operation Currently, this field is only used as a comment and cannot be edited. (PDM field ID: VACODE.OPT:NCHANR)
nicht_unterbr	Cannot be interrupted	char(1)	Cannot be interrupted If this option is checked, the detailed planning must plan the operation so that it is not interrupted by a time without shift (e.g. shift breaks). N: Not considered, i.e. in the planning an operation can be "interrupted" by times without shift. W: In the planning, an operation can be "interrupted" by times without shift A warning is issued, however. J: No scheduling for manual/automatic detailed scheduling. The "J" flag is currently not used as there might be the risk for the automatic detailed scheduling that an OP will never be scheduled. (PDM field ID: VACODE.OPT:NAUNPLAN)
opt_erfassung	Miscellaneous flags regarding capturing	char(10)	Miscellaneous flags regarding capturing [1,1] Check status of preceding OP Check whether or when the current OP may be logged on: S: Checking of the predecessor status. In this case, the preceding OP status must have the corresponding flag "successor can be logged on" N/empty: No check ATTENTION: the predecessor does NOT result from afo_lfd_nr, but ONLY from the relations in ADE_AUFTRAGSNETZ
opt_konfig	Miscellaneous flags	char(10)	Obviously currently not used
opt_planung	Miscellaneous flags	char(10)	Obviously currently not used

planen	Planning	char(1)	This setting specifies whether and how operations are relevant for detailed scheduling. The following settings are available N: No scheduling (no transfer to planning component) T: Scheduling only F: Scheduling and detailed planning. The operation is relevant for detailed planning. Therefore, this operation is not only included in the scheduling but also in the automatic and/or interactive planning. Scheduling means J the operation is scheduled , i.e. lead time is determined on the basis of process times and dates are set accordingly. Competitive situations are not taken into account for (lead time) scheduling. N the operation is not scheduled. The scheduled end date of the predecessor OP and the scheduled start date of the subsequent OP are used as start date and end date. Lead time is not taken into account. -> planning only, to avoid differentiation Detailed scheduling means J The operation is dispatched to a workplace when it comes to the automatic dispatching (detailed scheduling). In this context, capacity and reservation situation of the workplace are taken into account, which might lead to that fact that dispatching at the planned date is impossible from lead time scheduling. N With the automatic dispatching (detailed scheduling) the operation is dispatched without checking the capacity of the workplace -> planning only, to avoid differentiation (PDM field ID: VACODE.OPT:PLAN)
pp_caq_ab	Log OP off with still unsettled inspections	char(1)	Log OP off with still unsettled inspections J: If the operation is logged off or interrupted, no plausibility check is performed to find out if an inspection is still pending. N: If the operation is logged off or interrupted, it is checked if an inspection is still pending. If this is the case, the logoff or interruption of the operation is refused and a corresponding note is sent. (PDM field ID: VACODE.OPT:PPCAQAB)
pp_caq_m_ag_ab	Log main OP off with still unsettled inspections	char(1)	Log main OP off with still unsettled inspections This parameter is only available with main operations that include linked operations. J: If the operation is logged off or interrupted, it is checked for all linked operations if an inspection is still pending. If this is the case, the logoff of the main operation is refused and a corresponding note is sent. N: If the main operation is interrupted, no plausibility check is performed to find out if an inspection is still pending for the linked operations. (PDM field ID: VACODE.OPT:PPQMMAGAB)
pp_caq_m_ag_un	Interrupt main OP with still unsettled inspections	char(1)	Interrupt main OP with still unsettled inspections This parameter is only available with main operations that include linked operations. J: If the main operation is interrupted, the system checks for all linked operations whether or not inspections are still pending. If this is the case, the interruption of the main operation is refused and a corresponding note is sent. N: If the main operation is interrupted, no plausibility check is performed to find out if an inspection is still pending for the linked operations. (PDM field ID: VACODE.OPT:PPQMMAGUN)
pruefmerkmal	Inspection characteristic expected	char(1)	Inspection characteristic expected This indicator describes whether or not inspection characteristics are to be recorded for this operation and is respectively displayed for the operation at the shop floor terminal X: Yes, display only N: No, an inspection is not required; no inspection characteristic is expected J: Yes, with processing --> Currently not used (PDM field ID: VACODE.OPT:PMERKM)

seriennr_pflcht	Serial number obligation	char(1)	If this option is checked, postings must be made by serial number as of this operation. J: Yes, irrespective of whether serial numbers were transferred or not. N: No, even if serial numbers were transferred. E: Manual entry of serial number G: Automatic generation of serial number S: Generation of serial numbers using number ranges A: Collection of serial numbers U: Merge serial numbers Please note: This information is redundantly stored in the operation. Only the information stored in the operation is relevant for processing. (PDM field ID: VACODE.OPT:SNR)
sollm_abgl	Target quantity update	char(1)	Use this option to activate a comparison of the target quantity when an operation is logged off (= "FinishOP" posting). J: The Target quantity update is enabled for this operation, i.e. when an operation is logged off, the posted yield is transferred to the subsequent operations as target quantity. This is even valid for a combination of one or several parallel sequences (-> order network) as well as info operations (see configuration ID previously ERFASSBAR) The target quantity continues to be updated, even for partial confirmations/uploads of OPs or OP interruptions, if the target quantity of the current operation is exceeded as a result (is only performed online, not during recalculation!). When updating the target quantity to a split operation, the quantity is equally distributed in integer values, which might lead to a split OP getting a higher or lower target quantity. In this context, please also consider the underdelivery quantity/overdelivery quantity (recalculate). N: Target quantity update is disabled for this operation. If an operation is finished, the target quantity of other operations is not changed. Please note: this flag is transferred to AUFTRAGS_BESTAND.SOLLMENGENFORTS (redundant); but cannot be displayed or changed there. (PDM field ID: VACODE.OPT:SMENGEABGL)
splitten	May be split	char(4)	May be split V: This operation may be split. If the number of splits has already been transferred via the interface, then the split is performed directly in the interface. N: The operation may not be split. (PDM field ID: VACODE.OPT:SPLIT)
synchronisierung	Synchronization with successor OP	char(1)	Synchronization with successor OP J: The start date of the successor OP is synchronized with the finish date of the operation. The period between these two times may not exceed the maximum synchronization time stored in the operation. When planning changes are made, the relationship between the two operations remains the same or must remain the same, which might restrict the planning options. If overlapping is planned it has to be considered respectively. Through the functions it is also possible to define sequences of several operations for synchronization. It has to be taken into account even for order sequences and for order networks N: Synchronization is not planned, i.e. an operation can be planned an entire shift or only one hour after the end of the preceding operation. Of course, also in this case you cannot plan a successor before this operation. (PDM field ID: VACODE.OPT:AGNSYNC)
ueberlappung	Overlapping	char(1)	Overlapping The following types of overlapping are supported N: No overlapping S: Target overlapping. Here, scheduling and planning assumes an overlapping. This does not mean, however, that it must be used. K: Optional overlapping. Here, overlapping can be used during the reduction process. In this case, when there are enough buffers and/or no scheduling bottleneck, there is no overlapping. M: Mandatory overlapping. In this case, overlapping is enforced by planning, i.e. the two predecessor OPs are synchronized as specified. Overlapping may either be specified by a send-ahead quantity or lead time. Both parameters describe the offset of the predecessor to its successor. Lead time may also be negative, i.e. the successor starts with seupt prior to the predecessor. Currently not used (PDM field ID: VACODE.OPT:UEBLAP)
uebli_unfli_menge	Check quantites for under-/overdelivery	char(3)	Please also include the following quantity accounts in addition to yield when overdelivery or underdelivery are checked [1,1] scrap (J/N) [2,2] rework quantity (J/N) [3,3] problem quantity (J/N) (PDM field ID: VACODE.OPT:UEBLIUNFLI)

user_c_07	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data (PDM field ID: VACODE.USRFLD:07)
user_c_08	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data (PDM field ID: VACODE.USRFLD:08)
user_c_09	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_10	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_11	Alphanumeric user field	char(1)	Alphanumeric field reserved for user specific data
user_c_12	Alphanumeric user field	char(10)	Alphanumeric field reserved for user specific data
user_c_13	Alphanumeric user field	char(10)	Alphanumeric field reserved for user specific data
user_c_14	Alphanumeric user field	char(20)	Alphanumeric field reserved for user specific data
user_c_15	Alphanumeric user field	char(20)	Alphanumeric field reserved for user specific data
user_c_16	Alphanumeric user field	char(40)	Alphanumeric field reserved for user specific data
user_code	User field key	char(8)	User field key Reference to the configuration of the user field key or its user fields in the HYD_USERFIELDCFG table
user_f_05	Decimal user field	decimal(18,6)	Decimal field reserved for user specific data
user_f_06	Decimal user field	decimal(18,6)	Decimal field reserved for user specific data
user_n_01	Numeric user field	integer	Numeric field reserved for user specific data
user_n_02	Numeric user field	integer	Numeric field reserved for user specific data
user_n_03	Numeric user field	integer	Numeric field reserved for user specific data
user_n_04	Numeric user field	integer	Numeric field reserved for user specific data
verarb_code	Processing code	char(6)	Processing code identification number SYSTEM" = default processing code that is assigned to the operation if no processing code was explicitly entered (PDM field ID: VACODE.VERARBCODE)
vorgabeliste	Sequencing list	char(1)	If this option is checked, the operations with this processing code are shown in the sequencing list displayed at the terminal. J: Yes, display in the sequencing list. Whether an operation is really displayed in the sequencing list, also depends on the setting with the same name in the order type and in the operation status. N: No; orders of this order type are not displayed in the sequencing list on the terminal. (PDM field ID: VACODE.OPT:VLIST)

2.17. arbplan_bestand

Table name: arbplan_bestand		Product: BDE	
Designation: Work plan/template stock			
Column name	Column designation	Type	Description
a_prio	Priority	char(4)	Analogous to AUFTRAGS_BESTAND
a_stufe	Authorization level	char(3)	Analogous to AUFTRAGS_BESTAND
a_typ		char(4)	Analogous to AUFTRAGS_BESTAND
abmeldopt		char(10)	Analogous to AUFTRAGS_BESTAND
abruest_zeit	Teardown time	integer	Analogous to AUFTRAGS_BESTAND
abruest_zeit_expr	Teardown time formula	char(6)	Analogous to AUFTRAGS_BESTAND
abruest_zeit_mod		char(1)	Analogous to AUFTRAGS_BESTAND
afo_lfd_nr		integer	Analogous to AUFTRAGS_BESTAND
afolg	Sequence	char(10)	Analogous to AUFTRAGS_BESTAND
ag_art		char(5)	Analogous to AUFTRAGS_BESTAND
ag_bez	Operation designation	char(40)	Analogous to AUFTRAGS_BESTAND
ag_verkn_typ		char(1)	
ag_verweis		integer	Analogous to AUFTRAGS_BESTAND
agnr	OP	char(20)	Analogous to AUFTRAGS_BESTAND
als_dsbez	Data identifier	char(20)	Analogous to AUFTRAGS_BESTAND
anlage	Created by	char(10)	Analogous to AUFTRAGS_BESTAND
anlage_date		date	Analogous to AUFTRAGS_BESTAND
anlage_time		integer	Analogous to AUFTRAGS_BESTAND
anmeldopt		char(10)	Analogous to AUFTRAGS_BESTAND
anz_split_masch	Max. no. of splits	smallint	Analogous to AUFTRAGS_BESTAND
arbplan	Work plan	char(40)	Analogous to AUFTRAGS_BESTAND
artikel	Article	char(40)	Analogous to AUFTRAGS_BESTAND
artikel_bez	Article designation	char(40)	Analogous to AUFTRAGS_BESTAND
auftrag_art	Order type	char(5)	Analogous to AUFTRAGS_BESTAND
auftrag_nr	Work plan number	char(40)	Analogous to AUFTRAGS_BESTAND
aunr	Work plan	char(40)	Analogous to AUFTRAGS_BESTAND
bearb	Modified by	char(10)	Last editor
bearb_date		date	Last editing date
bearb_time		integer	Last editing time
bearb_zeit	Processing time	integer	Analogous to AUFTRAGS_BESTAND
bearb_zeit_expr	Processing time formula	char(6)	Analogous to AUFTRAGS_BESTAND
bearb_zeit_mod		char(1)	Analogous to AUFTRAGS_BESTAND
chargen_pflicht	Batch manag. requirement	char(1)	Analogous to AUFTRAGS_BESTAND
einm_menge	Unit quantity	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
einm_menge_einh		char(3)	Analogous to AUFTRAGS_BESTAND
erfass_art	Piecework ID	char(1)	Analogous to AUFTRAGS_BESTAND
erfassbar	Recordable	char(1)	Analogous to AUFTRAGS_BESTAND
erranf_dat		date	Analogous to AUFTRAGS_BESTAND

erranf_zeit		integer	Analogous to AUFTRAGS_BESTAND
errend_dat		date	Analogous to AUFTRAGS_BESTAND
errend_zeit		integer	Analogous to AUFTRAGS_BESTAND
farbe	Color	char(20)	Analogous to AUFTRAGS_BESTAND
fertvar_verweis	Production variant	integer	Analogous to AUFTRAGS_BESTAND
firma		char(4)	Analogous to AUFTRAGS_BESTAND
fremdbearbeitung	External processing OP	char(1)	Analogous to AUFTRAGS_BESTAND
frueh_anf_dat		date	Analogous to AUFTRAGS_BESTAND
frueh_anf_zeit		integer	Analogous to AUFTRAGS_BESTAND
frueh_end_dat		date	Analogous to AUFTRAGS_BESTAND
frueh_end_zeit		integer	Analogous to AUFTRAGS_BESTAND
geaendert_hydra	Modified HYDRA	char(1)	Analogous to AUFTRAGS_BESTAND
geaendert_planung		char(1)	Analogous to AUFTRAGS_BESTAND
geaendert_pps	Modified PPS	char(1)	Analogous to AUFTRAGS_BESTAND
kopf_verweis		integer	Analogous to AUFTRAGS_BESTAND
kostenart	Cost type	char(20)	Analogous to AUFTRAGS_BESTAND
kostenstelle	Cost center	char(10)	Analogous to AUFTRAGS_BESTAND
kunden_bez	Customer designation	char(40)	Analogous to AUFTRAGS_BESTAND
lagerort		char(12)	Analogous to AUFTRAGS_BESTAND
last_afo		char(1)	Analogous to AUFTRAGS_BESTAND
last_term_date		date	Analogous to AUFTRAGS_BESTAND
last_term_time		integer	Analogous to AUFTRAGS_BESTAND
layout	Layout	char(20)	
lieferzeit	Delivery time	integer	Analogous to AUFTRAGS_BESTAND
liege_zeit	Wait time	integer	Analogous to AUFTRAGS_BESTAND
liege_zeit_max	Max. sync. time	integer	Analogous to AUFTRAGS_BESTAND
lohnart	Wage type	char(4)	Analogous to AUFTRAGS_BESTAND
ls_safo_nr		char(40)	Analogous to AUFTRAGS_BESTAND
ls_sammel_kz		char(1)	Analogous to AUFTRAGS_BESTAND
ls_split_anz	Current no. of splits	smallint	Analogous to AUFTRAGS_BESTAND
ls_split_kz		char(1)	Analogous to AUFTRAGS_BESTAND
lst_code		char(6)	Analogous to AUFTRAGS_BESTAND
masch_nr	Planned workplace	char(20)	Analogous to AUFTRAGS_BESTAND
matetyp	Material type	char(20)	Analogous to AUFTRAGS_BESTAND
mb_verh_ruesten	M/O rel. setup	smallfloat	Analogous to AUFTRAGS_BESTAND
mb_verhaeltnis	M/O rel. product.	smallfloat	Analogous to AUFTRAGS_BESTAND
mehrfach_kz	Parallel logon possible	char(1)	Analogous to AUFTRAGS_BESTAND
meinheit_bas	Unit (B)	char(3)	Analogous to AUFTRAGS_BESTAND
meinheit_lief	Unit (P)	char(3)	Analogous to AUFTRAGS_BESTAND
meinheit_pri	Unit (P)	char(3)	Analogous to AUFTRAGS_BESTAND
meinheit_sek	Unit (S)	char(3)	Analogous to AUFTRAGS_BESTAND
meinheit_ter	Unit (T)	char(3)	Analogous to AUFTRAGS_BESTAND
menge_pri_uebli	Overdelivery (%)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
menge_pri_uebli_r	Overdelivery reaction	char(1)	Analogous to AUFTRAGS_BESTAND
menge_pri_untli	Underdelivery (%)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
menge_pri_untli_r	Underdelivery reaction	char(1)	Analogous to AUFTRAGS_BESTAND

mgruppe	Group	char(20)	Analogous to AUFTRAGS_BESTAND
notiz_vorh		char(1)	Analogous to AUFTRAGS_BESTAND
op_code		char(10)	Analogous to AUFTRAGS_BESTAND
pdv_pruefplan_nr		char(20)	Analogous to AUFTRAGS_BESTAND
plan_werk	Company	char(4)	Analogous to AUFTRAGS_BESTAND
prplan_nr		integer	Analogous to AUFTRAGS_BESTAND
pruef_masch_nr		char(20)	Analogous to AUFTRAGS_BESTAND
pruef_zeit	Insp. time	integer	Analogous to AUFTRAGS_BESTAND
pruef_zeit_expr	Insp. time formula	char(6)	Analogous to AUFTRAGS_BESTAND
pruef_zeit_mod		char(1)	Analogous to AUFTRAGS_BESTAND
puffer_zeit	Buffer time	integer	Analogous to AUFTRAGS_BESTAND
qm_ag_typ		char(2)	
qm_m_auftrag_nr		char(40)	
qual_ruesten		integer	
qualifikation		integer	
red_puffer_zeit	Time that can be reduced	integer	Analogous to AUFTRAGS_BESTAND
res_dnc	DNC	char(40)	Analogous to AUFTRAGS_BESTAND
res_emat	Material	char(40)	Analogous to AUFTRAGS_BESTAND
res_wnr	Tool	char(40)	Analogous to AUFTRAGS_BESTAND
rf_a_breite	Output width	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
rf_abzweig	Branch OP	char(1)	Analogous to AUFTRAGS_BESTAND
rf_agtyp	Special indicator	char(1)	Analogous to AUFTRAGS_BESTAND
rf_agvfa	Mass per unit area	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
rf_bsbrs	Seam width	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
rf_e_breite	Input width	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
rf_etr_anz	Daughter rolls/cut	integer	Analogous to AUFTRAGS_BESTAND
rf_gtr_anz	Daugther rolls/cut, total	integer	Analogous to AUFTRAGS_BESTAND
rf_huegewicht	Casing weight	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
rf_m_auftrag_nr	Mother OP	char(40)	Analogous to AUFTRAGS_BESTAND
rf_opcode		char(10)	Analogous to AUFTRAGS_BESTAND
rf_roanz	Number of rolls	integer	Analogous to AUFTRAGS_BESTAND
rf_rosch	Cutting OP	char(1)	Analogous to AUFTRAGS_BESTAND
rf_stflaech	Surface per piece	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
rf_zuzweig		char(1)	Analogous to AUFTRAGS_BESTAND
rf_zuzweigmenge		integer	Analogous to AUFTRAGS_BESTAND
rlz2_expr	Formula RRT2	char(6)	Analogous to AUFTRAGS_BESTAND
rlz_expr	Formula RRT1	char(6)	Analogous to AUFTRAGS_BESTAND
rmnr	Confirmation no.	char(40)	Analogous to AUFTRAGS_BESTAND
ruest_zeit	Setup time	integer	Analogous to AUFTRAGS_BESTAND
ruest_zeit_expr	Setup time formula	char(6)	Analogous to AUFTRAGS_BESTAND
ruest_zeit_mod		char(1)	Analogous to AUFTRAGS_BESTAND
ruest_zeit_zuschl	Additional setup time	integer	Analogous to AUFTRAGS_BESTAND
s_bpc_quan_1		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
s_bpc_uniso_1		char(3)	Analogous to AUFTRAGS_BESTAND
s_bpc_unit_1		char(3)	Analogous to AUFTRAGS_BESTAND
s_co_bpc_1		char(12)	Analogous to AUFTRAGS_BESTAND

s_hdr_denominator		integer	Analogous to AUFTRAGS_BESTAND
s_hdr_nominator		integer	Analogous to AUFTRAGS_BESTAND
s_source_sys		char(10)	Analogous to AUFTRAGS_BESTAND
sap_auftrag_nr		char(12)	Analogous to AUFTRAGS_BESTAND
sap_bezfl		char(6)	Analogous to AUFTRAGS_BESTAND
sap_laufnr		char(12)	Analogous to AUFTRAGS_BESTAND
sap_mapfl		char(6)	Analogous to AUFTRAGS_BESTAND
sap_maufnr		char(12)	Analogous to AUFTRAGS_BESTAND
sap_mrlfg		char(1)	Analogous to AUFTRAGS_BESTAND
sap_mvornr		char(4)	Analogous to AUFTRAGS_BESTAND
sap_split_nr		smallint	Analogous to AUFTRAGS_BESTAND
sap_usr00		char(20)	Analogous to AUFTRAGS_BESTAND
sap_usr01		char(20)	Analogous to AUFTRAGS_BESTAND
sap_usr04		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
sap_usr04_unit		char(3)	Analogous to AUFTRAGS_BESTAND
sap_uvg		char(4)	Analogous to AUFTRAGS_BESTAND
sap_vg_nr		char(4)	Analogous to AUFTRAGS_BESTAND
sap_vgfolge		char(6)	Analogous to AUFTRAGS_BESTAND
sap_vornr1		char(4)	Analogous to AUFTRAGS_BESTAND
sap_vornr2		char(4)	Analogous to AUFTRAGS_BESTAND
serialnr_pflcht	Serial numbers required	char(1)	Analogous to AUFTRAGS_BESTAND
soll_aus_bas	Target scrap quantity (B)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_aus_pri	Target scrap quantity (P)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_aus_sek	Target scrap quantity (S)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_aus_ter	Target scrap quantity (T)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_bedien_ant		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_dauer	Target cycle	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_dauer_expr	Target cycle formula	char(6)	Analogous to AUFTRAGS_BESTAND
soll_dauer_fmt		char(3)	Analogous to AUFTRAGS_BESTAND
soll_dauer_mod		char(1)	Analogous to AUFTRAGS_BESTAND
soll_div	Pulse factor	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_menge_ansatz		decimal(18,6)	
soll_menge_bas	Target quantity (B)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_menge_pri	Target quantity (P)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_menge_sek	Target quantity (S)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_menge_ter	Target quantity (T)	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_te	te	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_te_expr		char(6)	Analogous to AUFTRAGS_BESTAND
soll_te_fmt		char(3)	Analogous to AUFTRAGS_BESTAND
soll_te_mod		char(1)	Analogous to AUFTRAGS_BESTAND
soll_teb	teb	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_teb_expr		char(6)	Analogous to AUFTRAGS_BESTAND
soll_teb_fmt		char(3)	Analogous to AUFTRAGS_BESTAND
soll_teb_mod		char(1)	Analogous to AUFTRAGS_BESTAND
soll_teil	Partitioning	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_tr	tr	decimal(18,6)	Analogous to AUFTRAGS_BESTAND

soll_tr_expr		char(6)	Analogous to AUFTRAGS_BESTAND
soll_tr_mod		char(1)	Analogous to AUFTRAGS_BESTAND
soll_trb	trb	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
soll_trb_expr		char(6)	Analogous to AUFTRAGS_BESTAND
soll_trb_fmt		char(3)	Analogous to AUFTRAGS_BESTAND
soll_trb_mod		char(1)	Analogous to AUFTRAGS_BESTAND
sollmengenforts		char(1)	Analogous to AUFTRAGS_BESTAND
sort_dat		date	Analogous to AUFTRAGS_BESTAND
sort_zeit		integer	Analogous to AUFTRAGS_BESTAND
spael_anf_dat		date	Analogous to AUFTRAGS_BESTAND
spael_anf_zeit		integer	Analogous to AUFTRAGS_BESTAND
spael_end_dat		date	Analogous to AUFTRAGS_BESTAND
spael_end_zeit		integer	Analogous to AUFTRAGS_BESTAND
splitten	Split authorization	char(1)	Analogous to AUFTRAGS_BESTAND
splnr	Split	char(10)	Analogous to AUFTRAGS_BESTAND
szy_abw_proz		decimal(8,3)	
term_anf_dat		date	Analogous to AUFTRAGS_BESTAND
term_anf_zeit		integer	Analogous to AUFTRAGS_BESTAND
term_end_dat		date	Analogous to AUFTRAGS_BESTAND
term_end_zeit		integer	Analogous to AUFTRAGS_BESTAND
terminieren		char(1)	Analogous to AUFTRAGS_BESTAND
text_vorh		char(1)	Analogous to AUFTRAGS_BESTAND
transfer	Transfer by	char(10)	Analogous to AUFTRAGS_BESTAND
transfer_datum	Transfer date	date	Analogous to AUFTRAGS_BESTAND
transfer_zeit	Transfer time	integer	Analogous to AUFTRAGS_BESTAND
transp_zeit	Transport time	integer	Analogous to AUFTRAGS_BESTAND
transp_zeit_kal		integer	Analogous to AUFTRAGS_BESTAND
transp_zeit_min	Minimum transport time	integer	Analogous to AUFTRAGS_BESTAND
transp_zeit_norm		integer	Analogous to AUFTRAGS_BESTAND
uagnr	SOP	char(20)	Analogous to AUFTRAGS_BESTAND
umrech_lief_nen		integer	Analogous to AUFTRAGS_BESTAND
umrech_lief_zae		integer	Analogous to AUFTRAGS_BESTAND
umrech_pri_nen	Primary quantity, denominator	integer	Analogous to AUFTRAGS_BESTAND
umrech_pri_zae	Primary quantity, numerator	integer	Analogous to AUFTRAGS_BESTAND
umrech_sek_nen	Secondary quantity, denominator	integer	Analogous to AUFTRAGS_BESTAND
umrech_sek_zae	Secondary quantity, numerator	integer	Analogous to AUFTRAGS_BESTAND
umrech_ter_nen	Tertiary quantity, denominator	integer	Analogous to AUFTRAGS_BESTAND
umrech_ter_zae	Tertiary quantity, numerator	integer	Analogous to AUFTRAGS_BESTAND
user_c_29		char(1)	User-specific field
user_c_30		char(1)	User-specific field
user_c_31		char(1)	User-specific field
user_c_32		char(1)	User-specific field
user_c_33		char(1)	User-specific field
user_c_34		char(1)	User-specific field
user_c_35		char(1)	User-specific field
user_c_36		char(1)	User-specific field

user_c_37		char(1)	User-specific field
user_c_38		char(1)	User-specific field
user_c_39		char(1)	User-specific field
user_c_40		char(1)	User-specific field
user_c_41		char(1)	User-specific field
user_c_42		char(1)	User-specific field
user_c_43		char(1)	User-specific field
user_c_44		char(1)	User-specific field
user_c_45		char(10)	User-specific field
user_c_46		char(10)	User-specific field
user_c_47		char(10)	User-specific field
user_c_48		char(10)	User-specific field
user_c_49		char(10)	User-specific field
user_c_50		char(10)	User-specific field
user_c_51		char(20)	User-specific field
user_c_52		char(20)	User-specific field
user_c_53		char(20)	User-specific field
user_c_54		char(20)	User-specific field
user_c_55		char(20)	User-specific field
user_c_56		char(20)	User-specific field
user_c_57		char(20)	User-specific field
user_c_58		char(20)	User-specific field
user_c_59		char(20)	User-specific field
user_c_60		char(20)	User-specific field
user_c_61		char(20)	User-specific field
user_c_62		char(20)	User-specific field
user_c_63		char(20)	User-specific field
user_c_64		char(20)	User-specific field
user_c_65		char(40)	User-specific field
user_c_66		char(40)	User-specific field
user_code		char(8)	Analogous to AUFTRAGS_BESTAND
user_d_01		date	User-specific field
user_d_02		date	User-specific field
user_d_03		date	User-specific field
user_d_04		date	User-specific field
user_d_05		date	User-specific field
user_d_06		date	User-specific field
user_f_23		decimal(18,6)	User-specific field
user_f_24		decimal(18,6)	User-specific field
user_f_25		decimal(18,6)	User-specific field
user_f_26		decimal(18,6)	User-specific field
user_f_27		decimal(18,6)	User-specific field
user_f_28		decimal(18,6)	User-specific field
user_n_07		integer	User-specific field
user_n_08		integer	User-specific field
user_n_09		integer	User-specific field

user_n_10		integer	User-specific field
user_n_11		integer	User-specific field
user_n_12		integer	User-specific field
user_n_13		integer	User-specific field
user_n_14		integer	User-specific field
user_n_15		integer	User-specific field
user_n_16		integer	User-specific field
user_n_17		integer	User-specific field
user_n_18		integer	User-specific field
user_n_19		integer	User-specific field
user_n_20		integer	User-specific field
user_n_21		integer	User-specific field
user_n_22		integer	User-specific field
verantw_bereich	Responsibility area	char(15)	Analogous to AUFTRAGS_BESTAND
verarb_code	Processing code	char(6)	Analogous to AUFTRAGS_BESTAND
verarb_code_mod		integer	Analogous to AUFTRAGS_BESTAND
verbrauch_art		char(2)	Analogous to AUFTRAGS_BESTAND
verweis		serial	Analogous to AUFTRAGS_BESTAND
vgw_01	Default value 1	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_02	Default value 2	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_03	Default value 3	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_04	Default value 4	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_05	Default value 5	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_06	Default value 6	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_07	Default value 7	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_08	Default value 8	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_09	Default value 9	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_10	Default value 10	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_code	Default value key	char(5)	Analogous to AUFTRAGS_BESTAND
vorgabeliste		char(1)	Analogous to AUFTRAGS_BESTAND
vorlaufzeit	Lead time	integer	Analogous to AUFTRAGS_BESTAND
warte_zeit	Waiting time	integer	Analogous to AUFTRAGS_BESTAND
warte_zeit_expr	Wait time formula	char(6)	Analogous to AUFTRAGS_BESTAND
warte_zeit_min	Minimum waiting time	integer	Analogous to AUFTRAGS_BESTAND
warte_zeit_mod		char(1)	Analogous to AUFTRAGS_BESTAND
warte_zeit_norm		integer	Analogous to AUFTRAGS_BESTAND
weitergabemenge	Send ahead quantity	decimal(18,6)	Analogous to AUFTRAGS_BESTAND
wpkz	Deletion flag	char(1)	Analogous to AUFTRAGS_BESTAND

2.18. arbplan_hyinfo

Table name: arbplan_hyinfo		Product: BDE	
Designation: (Order-related) additional information			
Column name	Column designation	Type	Description
anzeigen_fehlgrund		char(1)	Analogous to HYINFO
anzeigen_geht		char(1)	Analogous to HYINFO
anzeigen_info		char(1)	Analogous to HYINFO
anzeigen_kommt		char(1)	Analogous to HYINFO
anzeigen_pause		char(1)	Analogous to HYINFO
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
countdown		smallint	Analogous to HYINFO
datum_bis		date	Analogous to HYINFO
datum_von		date	Analogous to HYINFO
gelesen_date		date	Analogous to HYINFO
gelesen_time		integer	Analogous to HYINFO
info1		char(100)	Analogous to HYINFO
info10		char(100)	Analogous to HYINFO
info2		char(100)	Analogous to HYINFO
info3		char(100)	Analogous to HYINFO
info4		char(100)	Analogous to HYINFO
info5		char(100)	Analogous to HYINFO
info6		char(100)	Analogous to HYINFO
info7		char(100)	Analogous to HYINFO
info8		char(100)	Analogous to HYINFO
info9		char(100)	Analogous to HYINFO
infoformat		char(10)	Analogous to HYINFO
key		char(40)	Analogous to HYINFO
kurztext		char(20)	Analogous to HYINFO
subkey1		integer	Analogous to HYINFO
subkey2		integer	Analogous to HYINFO
typ		char(10)	Analogous to HYINFO
verweis		serial	Analogous to HYINFO
verweis_meldung		integer	Analogous to HYINFO
wochentag		integer	Analogous to HYINFO

2.19. arbplan_leistung

Table name: arbplan_leistung		Product: BDE	
Designation: Order activities			
Column name	Column designation	Type	Description
ab_verweis		integer	Analogous to AUFTRAGS_LEISTUNG
auftrag_art		char(5)	Analogous to AUFTRAGS_LEISTUNG
auftrag_nr		char(40)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk01		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk01_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk02		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk02_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk03		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk03_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk04		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk04_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk05		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk05_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk06		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk06_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk07		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk07_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk08		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk08_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk09		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk09_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk10		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk10_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk11		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk11_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk12		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk12_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_dauer		integer	Analogous to AUFTRAGS_LEISTUNG
soll_dauer_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_ist01		decimal(18,6)	Analogous to AUFTRAGS_LEISTUNG
soll_ist01_einh		char(3)	Analogous to AUFTRAGS_LEISTUNG
soll_ist01_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_ist02		decimal(18,6)	Analogous to AUFTRAGS_LEISTUNG
soll_ist02_einh		char(3)	Analogous to AUFTRAGS_LEISTUNG
soll_ist02_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_ist03		decimal(18,6)	Analogous to AUFTRAGS_LEISTUNG
soll_ist03_einh		char(3)	Analogous to AUFTRAGS_LEISTUNG
soll_ist03_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG

soll Ist04		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist04_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist04_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist05		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist05_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist05_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist06		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist06_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist06_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist07		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist07_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist07_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist08		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist08_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist08_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist09		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist09_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist09_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist10		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist10_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist10_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk01		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk01_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk02		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk02_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk03		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk03_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk04		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk04_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk05		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk05_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk06		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk06_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk07		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk07_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk08		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk08_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk09		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk09_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk10		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk10_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk11		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk11_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk12		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk12_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_dauer	Target labor utilization	integer	Analogous to AUFTRAGS LEISTUNG

soll_p_dauer_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
------------------	--	---------	--------------------------------

2.20. arbplan_mlst_hy

Table name: arbplan_mlst_hy		Product: BDE	
Designation: Material list			
Column name	Column designation	Type	Description
anzahl_gesamt		integer	Analogous to MLST_HY
anzahl_von_pps		integer	Analogous to MLST_HY
artikel	Component	char(40)	Analogous to MLST_HY
artikel_bez	Designation	char(40)	Analogous to MLST_HY
auftrag_nr	Work plan number	char(40)	Analogous to MLST_HY
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
bereist_menge_einh	Unit of staging quantity	char(3)	Analogous to MLST_HY
bereistell_menge	Staging quantity	decimal(18,6)	Analogous to MLST_HY
bez_1	Designation 1	char(30)	Analogous to MLST_HY
bez_2	Designation 2	char(30)	Analogous to MLST_HY
ca_wl_pflcht	Requirement to change output batch	char(1)	Analogous to MLST_HY
chargen_nr		char(20)	
datei	File name	char(128)	Analogous to MLST_HY
delete_kz		char(1)	Analogous to MLST_HY
ersetzbar	Replaceable	char(1)	Analogous to MLST_HY
firma	Company	char(4)	Analogous to MLST_HY
hauptressource		char(1)	Analogous to MLST_HY
hz_typ	Material type	char(10)	Analogous to MLST_HY
ist_einh_sek	Unit (S)	char(3)	Analogous to MLST_HY
ist_einh_ter		char(3)	Analogous to MLST_HY
ist_menge	Requirements quantity	decimal(18,6)	Analogous to MLST_HY
ist_menge_einh	QU requirements quantity	char(3)	Analogous to MLST_HY
ist_menge_sek	Secondary yield quantity	decimal(18,6)	Analogous to MLST_HY
ist_menge_ter		decimal(18,6)	Analogous to MLST_HY
kennz	Component type	char(10)	Analogous to MLST_HY
kennz_slos	Superordinate SNo	char(1)	
kz_fmenge		char(1)	Analogous to MLST_HY
manuell		char(1)	Analogous to MLST_HY
menge_von_pps	Required quantity (ERP)	decimal(18,6)	Analogous to MLST_HY
mengen_abweichung		decimal(18,6)	
mengen_tol		decimal(18,6)	
meta_res	Meta resource	char(1)	Analogous to MLST_HY
mlst_param_str01		char(10)	Analogous to MLST_HY
mlst_param_str02		char(30)	Analogous to MLST_HY
mlst_pddouble_01		decimal(18,6)	Analogous to MLST_HY
mlst_pddouble_02		decimal(18,6)	Analogous to MLST_HY

mlst_plong_01		integer	Analogous to MLST_HY
mlst_plong_02		integer	Analogous to MLST_HY
mlst_pshort_01		smallint	Analogous to MLST_HY
mlst_pshort_02		smallint	Analogous to MLST_HY
obere_toleranz	Upper tolerance limit	decimal(18,6)	Analogous to MLST_HY
path	Path	char(8)	Analogous to MLST_HY
plan_artikel	Planned article	char(40)	Analogous to MLST_HY
pos	BOM item	char(10)	Analogous to MLST_HY
pos_m	BOM item	char(10)	Analogous to MLST_HY
res_familie	Resource family	integer	Analogous to MLST_HY
res_typ	Resource type	char(4)	Analogous to MLST_HY
res_version		char(20)	Analogous to MLST_HY
res_verweis		integer	Analogous to MLST_HY
res_verweis_m		integer	Analogous to MLST_HY
rf_sa_mg	Spec. mass per unit area	decimal(18,6)	Analogous to MLST_HY
rf_sa_mg_einh	UOM Spec. mass per unit area	char(3)	Analogous to MLST_HY
rgekz_pps	Backflush	char(1)	Analogous to MLST_HY
sap_vornr		char(4)	Analogous to MLST_HY
soll_einh	QU input quantity	char(3)	Analogous to MLST_HY
soll_einh_sek		char(3)	Analogous to MLST_HY
soll_einh_ter		char(3)	Analogous to MLST_HY
soll_menge	Input quantity	decimal(18,6)	Analogous to MLST_HY
soll_menge_proz	Input quantity in %	decimal(18,6)	Analogous to MLST_HY
soll_menge_sek		decimal(18,6)	Analogous to MLST_HY
soll_menge_ter		decimal(18,6)	Analogous to MLST_HY
sta_erfasst		char(1)	
sta_mengenanp		char(1)	
stueli_stufe	BOM level	integer	Analogous to MLST_HY
stueli_stufe_m	BOM level	integer	Analogous to MLST_HY
tranr		char(40)	
untere_toleranz	Lower tolerance limit	decimal(18,6)	Analogous to MLST_HY
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	

user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	

user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
verb_zaeher	Automatic counter consumption	char(1)	
verbrauch	Consumption quantity	decimal(18,6)	Analogous to MLST_HY
verbrauch_art	Consumption type	char(2)	Analogous to MLST_HY
verbrauch_einh	Unit of consumption quantity	char(3)	Analogous to MLST_HY
verweis		serial	Analogous to MLST_HY
we_menge		decimal(18,6)	Analogous to MLST_HY
we_menge_einh		char(3)	Analogous to MLST_HY

2.21. arbplan_verwalt

Table name: arbplan_verwalt		Product: BDE	
Designation: Work plan/template management			
Column name	Column designation	Type	Description
a_typ	Type	char(4)	Work plan type AU: Order header AG: Operation
aktiv	Active	char(1)	J/N (PDM field ID: APVRW.AKTIV)
arbplan	Work plan	char(40)	APL: corresponds to work plan no. TPL: internal template no., e.g. T... Depending on the defined type (PDM field ID: APVRW.APNR)
arbplan_version	Version number	char(12)	Version number (PDM field ID: APVRW.APVER)
arbplanart	Work plan type	char(4)	Possible values: APL = work plan TPL = Template for OPs (PDM field ID: APVRW.APLART)
artikel	Article	char(40)	Article to be produced (order header) (PDM field ID: APVRW.ATK)
auftrag_art	Order type	char(5)	Order type (PDM field ID: APVRW.AUART)
auftrag_nr	Order	char(40)	----
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
bemerkung	Comment	char(40)	Comment (PDM field ID: APVRW.BEM)
gueltig_bis_dat	valid till	date	if empty, then till infinite (PDM field ID: APVRW.GUELT:BIS)
gueltig_von_dat	valid from	date	if empty, then with immediate effect (PDM field ID: APVRW.GUELT:VON)
loesch_kz	Deletion flag	char(1)	Deletion flag
masch_nr	Machine	char(20)	Machine (PDM field ID: APVRW.MNR)
mattyp	Material type	char(20)	Material type of the article CHAR(20) instead of CHAR(10) due to compatibility reasons of the field of the same name in AUFTRAGS_BESTAND (PDM field ID: APVRW.MATTYP)
meinheit_bas	Base quantity unit	char(3)	Base quantity unit -> is required in order that it can be converted correctly when generating an order with the quantity 10 tons if kg are indicated here. (PDM field ID: APVRW.SGE:B)
mgruppe	Machine group	char(20)	Machine group (PDM field ID: APVRW.MGRP)
soll_menge_bas_max	Batch size to	float	Display at the console: the term "lot size" is used. The values can also remain empty!! Means at MAX: infinite. (PDM field ID: APVRW.SGR:GUTBMAX)

soll_menge_bas_min	Batch size from	float	Display at the console: the term "lot size" is used. The values can also remain empty!! Means at MAX: infinite. (PDM field ID: APVRW.SGR:GUTBMIN)
soll_menge_bas_opt	Optimum batch size	float	Display at the console: the term "lot size" is used. Die values can also remain empty!! Means at MAX: infinite. (PDM field ID: APVRW.SGR:GUTBOPT)
teil_auftr_bilden	Generate partial batches (J/N)	char(1)	Generate partial batches (J/N) "J" means: - at manual generation: value SOLL_MENGE_BAS_OPT is suggested - at transfer from PPS: generate automatically orders in this lot size ""/"N" : take over quantity 1:1. (PDM field ID: APVRW.OPT:TANR)
verweis	Reference	integer	internal reference (PDM field ID: APVRW.VERWEIS)

2.22. arbplan_zusatz

Table name: arbplan_zusatz		Product: BDE	
Designation: (Order-related) additional information			
Column name	Column designation	Type	Description
ab_verweis		integer	Analogous to AUFTRAGS_ZUSATZ
arbplan_version	Work plan version	char(12)	Analogous to AUFTRAGS_ZUSATZ
auftrag_art		char(5)	Analogous to AUFTRAGS_ZUSATZ
auftrag_nr		char(40)	Analogous to AUFTRAGS_ZUSATZ
auftragsgruppe	Order group	char(4)	Analogous to AUFTRAGS_ZUSATZ
auftragsindex	Order index	decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
chargennr	Batch number	char(20)	Analogous to AUFTRAGS_ZUSATZ
disponent	MRP controller	char(10)	Analogous to AUFTRAGS_ZUSATZ
dlz_minimal		integer	Analogous to AUFTRAGS_ZUSATZ
dlz_plan		integer	Analogous to AUFTRAGS_ZUSATZ
fert_version	Production version	char(10)	Analogous to AUFTRAGS_ZUSATZ
kalk_kost_lohn	Labor costs	decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
kalk_kost_masch	Machine costs	decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
kalk_kost_mat	Material costs	decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
kalk_kost_sonst	Other costs	decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
kd_auftrag	Sales order	char(40)	Analogous to AUFTRAGS_ZUSATZ
kd_auftragpos	Sales order item	char(20)	Analogous to AUFTRAGS_ZUSATZ
kostentraeger	Cost object	char(40)	Analogous to AUFTRAGS_ZUSATZ
lbez_id	Closed loop	char(15)	(PDM field ID: ANR.KBN:LBEZID)
mat_wert	Value of raw materials	decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
plan_auftrag	Planned order	char(40)	Analogous to AUFTRAGS_ZUSATZ
proben_typ	Sample category	char(1)	Analogous to AUFTRAGS_ZUSATZ
projekt_nr	Project no.	char(25)	Analogous to AUFTRAGS_ZUSATZ
prueflosnr	Inspection batch number	char(20)	Analogous to AUFTRAGS_ZUSATZ
red_strategie	Reduction strategy	char(2)	Analogous to AUFTRAGS_ZUSATZ
red_stufe	Reduction level	smallint	Analogous to AUFTRAGS_ZUSATZ
schrott_wert	Scrap value	decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
steuerrezept		char(10)	Analogous to AUFTRAGS_ZUSATZ
stueli_version	BOM version	char(12)	Analogous to AUFTRAGS_ZUSATZ
term_art	Scheduling type	char(1)	Analogous to AUFTRAGS_ZUSATZ

2.23. auftrag_status

Table name: auftrag_status		Product: BDE	
Archive table: a_auftrag_status		Reload table: r_auftrag_status	
Designation: Order status		Description: The table contains all data fields based on operations including movement data. All entries apply to the total runtime of the OP, i.e. they are not reset to 0 and thus represent the current condition over the complete runtime.	
Column name	Column designation	Type	Description
a_status	Order status	char(5)	Status of the order (freely configurable!) Is determined via prod_kenn from the status assignment ADE_STATUS_ZUORD Status of OP ("V"/"U"/...) is now contained in prod_kenn (PDM field ID: ANR.AST)
a_status_vorg	Predecessor status	char(5)	Status of the predecessor OP
a_statustext_nr	Status text number	integer	Reference: ADE_STATUSTEXTE
a_typ	OP type (internal)	char(4)	AU -> orders (header information) AG -> operations UAG -> sub operations SPL -> split SAG -> collective operations (PDM field ID: ANR.ATYP)
abbr_grund	Termination reason	integer	Termination reason new Version 7.2: Status text number Machine status (text) number which was active or set at the machine when the OP was interrupted. Is reset when the OP is logged on again or when it is directly logged off
abruest_zyklen	Number of cycles, teardown	integer	Number of cycles, teardown
anmeldbar		char(1)	--- (PDM field ID: ANR.OPT:AAN)
anmelddat	Time of last logon	date	Time of last logon, date (PDM field ID: ADEPRO.DATB)
anmeldzeit	Time of last logon	integer	Time of last logon, time (PDM field ID: ADEPRO.ZEIB)
ap_gedruckt	Work documents printed	char(10)	[1] : work documents printed (J/N) [2..10] : future use (PDM field ID: ANR.OPT:APPRN)
auftrag_nr	BDE - order number	char(40)	BDE-order number new HYDRA 7.2: total key of the object distribution according to SETUP (PDM field ID: ADEPRO.ANR)
aus_bas	Scrap quantity (base quantity unit)	decimal(18,6)	Scrap quantity (base quantity unit) Sum of all reasons in AUFTRAG_MENGEN RW 7.1->7.2: transfer from table auftrag_status from field: prod_aus1 (PDM field ID: ANR.EGR:AUSB)
aus_pri	Scrap quantity (primary)	decimal(18,6)	Scrap quantity (prim.) Sum of all reasons in AUFTRAG_MENGEN RW 7.1->7.2: transfer from table auftrag_status from field: prod_aus1 (PDM field ID: ANR.EGR:AUSP)
aus_sek	Scrap quantity (secondary)	decimal(18,6)	Scrap quantity (sec.) Sum of all reasons in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:AUSS)

aus_ter	Scrap quantity (tertiary)	decimal(18,6)	Scrap quantity (tert.) Sum of all reasons in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:AUST)
bearb		char(10)	Last editor
bearb_date		date	Last editing date
bearb_time		integer	Last editing time
bearb_zyklen	Number of cycles, processing	integer	Number of cycles, processing
bmk_01	Posted activity in RPA 01	integer	Recorded run time with status posted on the respective resource performance accounts Posted activity in RPA 01 (PDM field ID: ANR.EGR:BMK01)
bmk_02	Posted activity in RPA 02	integer	Posted activity in RPA 02 (PDM field ID: ANR.EGR:BMK02)
bmk_03	Posted activity in RPA 03	integer	Posted activity in RPA 03 (PDM field ID: ANR.EGR:BMK03)
bmk_04	Posted activity in RPA 04	integer	Posted activity in RPA 04 (PDM field ID: ANR.EGR:BMK04)
bmk_05	Posted activity in RPA 05	integer	Posted activity in RPA 05 (PDM field ID: ANR.EGR:BMK05)
bmk_06	Posted activity in RPA 06	integer	Posted activity in RPA 06 (PDM field ID: ANR.EGR:BMK06)
bmk_07	Posted activity in RPA 07	integer	Posted activity in RPA 07 (PDM field ID: ANR.EGR:BMK07)
bmk_08	Posted activity in RPA 08	integer	Posted activity in RPA 08 (PDM field ID: ANR.EGR:BMK08)
bmk_09	Posted activity in RPA 09	integer	Posted activity in RPA 09 (PDM field ID: ANR.EGR:BMK09)
bmk_10	Posted activity in RPA 10	integer	Posted activity in RPA 10 (PDM field ID: ANR.EGR:BMK10)
bmk_11	Posted activity in RPA 11	integer	Posted activity in RPA 11 (PDM field ID: ANR.EGR:BMK11)
bmk_12	Posted activity in RPA 12	integer	Posted activity in RPA 12 (PDM field ID: ANR.EGR:BMK12)
calc_bmk_01	SUT	integer	Recorded/calculated activity in RPA 01
calc_bmk_02	DCI	integer	Recorded/calculated activity in RPA 02
calc_bmk_03	LCI	integer	Recorded/calculated activity in RPA 03
calc_bmk_04	SCI	integer	Recorded/calculated activity in RPA 04
calc_bmk_05	IMN	integer	Recorded/calculated activity in RPA 05
calc_bmk_06	IMS	integer	Recorded/calculated activity in RPA 06
calc_bmk_07	SET	integer	Recorded/calculated activity in RPA 07
calc_bmk_08	STA	integer	Recorded/calculated activity in RPA 08
calc_bmk_09	U8	integer	Recorded/calculated activity in RPA 09
calc_bmk_10	U9	integer	Recorded/calculated activity in RPA 10
calc_bmk_11	MUT	integer	Recorded/calculated activity in RPA 11
calc_bmk_12	BKS	integer	Recorded/calculated activity in RPA 12
calc_dauer	Total time	integer	Calculated duration
calc_p_dauer_bmk01	SUT	integer	Calculated labor duration RPA 01
calc_p_dauer_bmk02	DCI	integer	---
calc_p_dauer_bmk03	LCI	integer	---
calc_p_dauer_bmk04	SCI	integer	---
calc_p_dauer_bmk05	IMN	integer	---
calc_p_dauer_bmk06	IMS	integer	---

calc_p_dauer_bmk07	SET	integer	---
calc_p_dauer_bmk08	STA	integer	---
calc_p_dauer_bmk09	U8	integer	---
calc_p_dauer_bmk10	U9	integer	---
calc_p_dauer_bmk11	MUT	integer	---
calc_p_dauer_bmk12	BKS	integer	---
calc_pers_dauer	Labor utilization	integer	Calculated labor duration
caq_erg_prod_kenn		char(2)	CAQ result N = fail O = pass
caq_erg_status		char(5)	Status number of CAQ result Status number according to status configuration of the order for the CAQ result status type
caq_erg_text_nr		integer	Status text number of CAQ result Status text number according to the status configuration of the order for the CAQ result status type
caq_prod_kenn		char(2)	CAQ status F= due G=checked V=missed
caq_status		char(5)	CAQ status number Status number according to status configuration of the order for status type CAQ status
caq_statustext_nr		integer	CAQ status text number Status text number according to status configuration of the order for status type CAQ status
chargen_nr		char(20)	
dauer	Total time	integer	Overall run time of the OP
e_anmeld_dat	First logon - date	date	First logon - date (PDM field ID: ANR.DATB:E)
e_anmeld_zeit	First logon - time	integer	First logon - time (PDM field ID: ANR.ZEIB:E)
ebdf	Decision requirement	char(1)	Decision is required whether a special processing is needed for the OP
eingepplant	Scheduled	char(1)	OP is dispatched ("M") or is still in the pool of groups ("G") (PDM field ID: ANR.OPT:PLAN)
entsperr	Unlocked by	char(10)	User who has cancelled the last block of the order/OP. (PDM field ID: ANR.AKTIV)
entsperr_date		date	Time of canceling the block (PDM field ID: ANR.AKTIVDAT)
entsperr_time		integer	Time of canceling the block (PDM field ID: ANR.AKTIVZEI)
fix	fixed	char(1)	fixed (PDM field ID: ANR.OPT:FIX)
gesperrt	Blocked	char(1)	J/N Blocked orders/OPs CANNOT be logged on (only manual logon), they CANNOT be planned and are neither displayed at the terminal - irrespective of the status configuration ("as if the order/OP was not available"). -> Blocking an order affects all OPs. (PDM field ID: ANR.SPERRKZ)
gesperrt_pflge	J/N Blocking by MLE Interface	char(1)	J/N Blocking by MLE Interface To prevent the operation from being registered before all data has been completely transferred, the operation can be locked while the segments of the MLE transaction are being processed. (PDM field ID: ANR.SPERRKZ:EDIT)
gut_bas	Yield (base quantity unit)	decimal(18,6)	Yield (base quantity unit) RW 7.1->7.2: transfer from table auftrag_status from field: prod_stck (PDM field ID: ANR.EGR:GUTB)

gut_pri	Yield (primary)	decimal(18,6)	Yield (prim.) RW 7.1->7.2: transfer from table auftrag_status from field: prod_stck (PDM field ID: ANR.EGR:GUTP)
gut_sek	Yield (secondary)	decimal(18,6)	Yield (sec.) (PDM field ID: ANR.EGR:GUTS)
gut_ter	Yield (tertiary)	decimal(18,6)	Yield (tert.) (PDM field ID: ANR.EGR:GUTT)
hub_gesamt	Stroke, total	decimal(18,6)	Total amount of strokes. Cycles posted to the OP (total, even during production lock) (PDM field ID: ANR.EGR:HUB)
hub_gut	Stroke, yield	decimal(18,6)	Yield STROKES (PDM field ID: ADEPRO.EGR:HUB)
ist_lst_01	Posted free activity 1	decimal(18,6)	Posted free activity 1
ist_lst_02	Posted free activity 2	decimal(18,6)	Posted free activity 2
ist_lst_03	Posted free activity 3	decimal(18,6)	MPLRF: Yield in unit LFM Posted free activity 3
ist_lst_04	Posted free activity 4	decimal(18,6)	Posted free activity 4
ist_lst_05	Posted free activity 5	decimal(18,6)	Posted free activity 5
ist_lst_06	Posted free activity 6	decimal(18,6)	Posted free activity 6
ist_lst_07	Posted free activity 7	decimal(18,6)	Posted free activity 7
ist_lst_08	Posted free activity 8	decimal(18,6)	Posted free activity 8
ist_lst_09	Posted free activity 9	decimal(18,6)	Posted free activity 9
ist_lst_10	Posted free activity 10	decimal(18,6)	Posted free activity 10
ist_werk	Comp.	char(4)	free
ist_zyklus	Actual cycle	integer	Computed Results from: time produced so far divided by posted cycles. (PDM field ID: ANR.IZY)
l_abmeld_dat	Last logoff - date	date	Last logoff - date (only if OP is finished, otherwise NULL) (PDM field ID: ANR.DATE:L)
l_abmeld_zeit	Last logoff - time	integer	Last logoff - time (only if OP is finished, otherwise NULL) (PDM field ID: ANR.ZEIE:L)
los_idx		integer	
masch_nr		char(20)	Machine on which the OP is scheduled (also see auftrags_bestand) new Version 7.2: OP not yet started: -> planned machine OP already logged on: -> machine on which the OP was active at last or is currently being active (PDM field ID: ANR.MNR)
meinheit_bas	Quantity unit	char(3)	Quantity unit RW 7.1->7.2: transfer from table auftrag_status from field: prod_einh (PDM field ID: ANR.EGE:B)
meinheit_pri	Quantity unit	char(3)	Quantity unit RW 7.1->7.2: Transfer from table auftrag_status from field: prod_einh (PDM field ID: ANR.EGE:P)
meinheit_sek	Quantity unit	char(3)	Quantity unit (PDM field ID: ANR.EGE:S)
meinheit_ter	Quantity unit	char(3)	Quantity unit (PDM field ID: ANR.EGE:T)

nacharb_bas	Rework quantity	decimal(18,6)	Rework quantity (Base quantity unit) Sum of all reasons in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:NCHB)
nacharb_pri	Rework quantity (primary)	decimal(18,6)	Rework quantity (prim.) Sum of all reasons in AUFTRAG_MENGEN RW 7.1->7.2: transfer from table auftrag_status from field: prod_len (PDM field ID: ANR.EGR:NCHP)
nacharb_sek	Rework quantity (secondary)	decimal(18,6)	Rework quantity (sec.) Sum of all reasons in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:NCHS)
nacharb_ter	Rework quantity (tertiary)	decimal(18,6)	Rework quantity (tert.) Sum of all reasons in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:NCHT)
p_dauer_bmk01	Posted PRPA 1 (OP)	integer	Posted personnel activity in RPA 01
p_dauer_bmk02	Posted PRPA 2 (OP)	integer	Posted personnel activity in RPA 02
p_dauer_bmk03	Posted PRPA 3 (OP)	integer	Posted personnel activity in RPA 03
p_dauer_bmk04	Posted PRPA 4 (OP)	integer	Posted personnel activity in RPA 04
p_dauer_bmk05	Posted PRPA 5 (OP)	integer	Posted personnel activity in RPA 05
p_dauer_bmk06	Posted PRPA 6 (OP)	integer	Posted personnel activity in RPA 06
p_dauer_bmk07	Posted PRPA 7 (OP)	integer	Posted personnel activity in RPA 07
p_dauer_bmk08	Posted PRPA 8 (OP)	integer	Posted personnel activity in RPA 08
p_dauer_bmk09	Posted PRPA 9 (OP)	integer	Posted personnel activity in RPA 09
p_dauer_bmk10	Posted PRPA 10 (OP)	integer	Posted personnel activity in RPA 10
p_dauer_bmk11	Posted PRPA 11 (OP)	integer	Posted personnel activity in RPA 11
p_dauer_bmk12	Posted PRPA 12 (OP)	integer	Posted personnel activity in RPA 12
pers_dauer	as hitherto; is virtually the sum	integer	Sum of posted labor time to OP (PDM field ID: ADEPRO.EGR:PDAUER)
person_anz	No. of persons	integer	If the LLE module is active: 0 -> yet no logon of staff or order logon 1 -> there is a logon of staff 2 -> there is an order logon 3 -> there are a logon of staff and an order logon (PDM field ID: ADEPRO.PANZ)
problem_bas	Problem quantity	decimal(18,6)	Problem quantity (Base quantity unit) Sum of all reasons in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:PRBB)
problem_pri	Problem quantity (primary)	decimal(18,6)	Problem quantity (prim.) Sum of all reasons in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:PRBP)
problem_sek	Problem quantity (secondary)	decimal(18,6)	Problem quantity (sec.) Sum of all reasons in AUFTRAG_MENGEN Problemmenge (Sek.) Summe über alle Gründe in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:PRBS)
problem_ter	Problem quantity (tertiary)	decimal(18,6)	Problem quantity (tert.) Sum of all reasons in AUFTRAG_MENGEN (PDM field ID: ANR.EGR:PRBT)

prod_kenn	Production Characteristic	char(2)	"X" - prepared The OP is blocked "V" - prepared "Release indicator" for , BEFORE the OP is processed for the first time "Y" - Inactive The OP is in an alternative sequence and can only be logged on when the sequence is activated and thus the production indicator is set to "V" "L" - OP: running/ AU: in process is automatically set when the OP is logged on "U" - interrupted is automatically set when the OP is interrupted "F" - autom. interrupted is set by the server when the OP is supposed to be interrupted automatically at the change of shifts wir "E" - finished is automatically set when the OP is finished "S" - None other status, i.e. all other statuses: no automatic; means: OP has not yet been processed S "A" - archived The OP has been finished and archived according to a_auftrags_bestand, etc. "D" - deleted The OP has been deleted. (PDM field ID: ANR.OPT:PKENN)
prod_kenn_vorg	Production Char. of the predecessor OP	char(2)	Production characteristic of the predecessor OP
prog_abmeld_dat		date	Anticipated finish date (PDM field ID: PROGN_DATE)
prog_abmeld_zeit		integer	Anticipated end time (PDM field ID: PROGN_ZEIE)
prot_dat		date	Time of last logon (PDM field ID: ANR.* (AST.DAT))
prot_zeit		integer	Time of last logon of the terminal (if a_status = E, then finish date) (PDM field ID: ANR.* (AST.ZEI))
reak	Reactivated by	char(10)	User who has reactivated the order/OP at last; empty if it has never been reactivated Only for documentation purposes, for a better understanding (support) (PDM field ID: ANR.REAK)
reak_date		date	Time of last reactivation (PDM field ID: ANR.REAKDAT)
reak_time		integer	Time of last reactivation (PDM field ID: ANR.REAKZEI)
res1_status	Person OK	char(2)	The determination to which resource type the indicator refers is configured cross-system Is set by the resource check (PDM field ID: ANR.RESSTA:1)
res2_status	Tool OK	char(2)	Status resource 2 (PDM field ID: ANR.RESSTA:2)
res3_status	Material OK	char(2)	Status resource 3 (PDM field ID: ANR.RESSTA:3)
res4_status	Resource status 4	char(2)	Status resource 4 (PDM field ID: ANR.RESSTA:4)
res5_status	Resource status 5	char(2)	Status resource 5 (PDM field ID: ANR.RESSTA:5)
res6_status	Resource status 6	char(2)	Status resource 6 (PDM field ID: ANR.RESSTA:6)

rest_bmk_01	Remain. RPA 1	integer	Current residual activity RPA 1 ATTENTION: it must be possible to reference to the IST and REST fields when it comes to the formula for the RLZ (remaining run time) A residual activity of 0 means that no activity is expected anymore. (PDM field ID: ANR.RGR:BMK01)
rest_bmk_02	Remain. RPA 2	integer	Current residual activity RPA 2
rest_bmk_03	Remain. RPA 3	integer	Current residual activity RPA 3
rest_bmk_04	Remain. RPA 4	integer	Current residual activity RPA 4
rest_bmk_05	Remain. RPA 5	integer	Current residual activity RPA 5
rest_bmk_06	Remain. RPA 6	integer	Current residual activity RPA 6
rest_bmk_07	Remain. RPA 7	integer	Current residual activity RPA 7
rest_bmk_08	Remain. RPA 8	integer	Current residual activity RPA 8
rest_bmk_09	Remain. RPA 9	integer	Current residual activity RPA 9
rest_bmk_10	Remain. RPA 10	integer	Current residual activity RPA 10
rest_bmk_11	Remain. RPA 11	integer	Current residual activity RPA 11
rest_bmk_12	Remain. RPA 12	integer	Current residual activity RPA 12 (PDM field ID: ANR.RGR:BMK12)
rest_dauer	Rem. total time	integer	Remaining run time
rest_lst_01	Remaining activity 1	decimal(18,6)	Current residual activity 1 (PDM field ID: ANR.RGR:LST01)
rest_lst_02	Remaining activity 2	decimal(18,6)	Current residual activity 2
rest_lst_03	Remaining activity 3	decimal(18,6)	Current residual activity 3
rest_lst_04	Remaining activity 4	decimal(18,6)	Current residual activity 4
rest_lst_05	Remaining activity 5	decimal(18,6)	Current residual activity 5
rest_lst_06	Remaining activity 6	decimal(18,6)	Current residual activity 6
rest_lst_07	Remaining activity 7	decimal(18,6)	Current residual activity 7
rest_lst_08	Remaining activity 8	decimal(18,6)	Current residual activity 8
rest_lst_09	Remaining activity 9	decimal(18,6)	Current residual activity 9
rest_lst_10	Remaining activity 1	decimal(18,6)	Current residual activity 10 (PDM field ID: ANR.RGR:LST10)
rest_p_dauer	Rem. labor utilization	integer	Current remaining labor duration (PDM field ID: ADEPRO.RGR:PDAUER)
rest_p_dauer_bmk01	Rem. PRPA 1 (OP)	integer	Current personnel residual activity RPA 1(BMK 1) -> difference between actual and target activity
rest_p_dauer_bmk02	Rem. PRPA 2 (OP)	integer	Current personnel residual activity RPA 2
rest_p_dauer_bmk03	Rem. PRPA 3 (OP)	integer	Current personnel residual activity RPA 3
rest_p_dauer_bmk04	Rem. PRPA 4 (OP)	integer	Current personnel residual activity RPA 4
rest_p_dauer_bmk05	Rem. PRPA 5 (OP)	integer	Current personnel residual activity RPA 5
rest_p_dauer_bmk06	Rem. PRPA 6 (OP)	integer	Current personnel residual activity RPA 6
rest_p_dauer_bmk07	Rem. PRPA 7 (OP)	integer	Current personnel residual activity RPA 7
rest_p_dauer_bmk08	Rem. PRPA 8 (OP)	integer	Current personnel residual activity RPA 8
rest_p_dauer_bmk09	Rem. PRPA 9 (OP)	integer	Current personnel residual activity RPA 9
rest_p_dauer_bmk10	Rem. PRPA 10 (OP)	integer	Current personnel residual activity RPA 10
rest_p_dauer_bmk11	Rem. PRPA 11 (OP)	integer	Current personnel residual activity RPA 11
rest_p_dauer_bmk12	Rem. PRPA 12 (OP)	integer	Current personnel residual activity RPA 12
rest_pers_dauer	Remain. labor utilization	integer	Current residual labor duration (PDM field ID: ADEPRO.RGR:PDAUER)
ruest_zyklen	Setup cycles	integer	Number of cycles setup
s_conf_bpc_1		decimal(18,6)	Internal indicator for SAP
s_conf_rework		decimal(18,6)	Internal indicator for SAP

s_conf_scrap		decimal(18,6)	Internal indicator for SAP
s_conf_yield		decimal(18,6)	Internal indicator for SAP
s_no_remn_bpc_1		char(1)	Internal indicator for SAP
sap_persbezug		char(1)	Internal indicator for SAP
sap_stata		char(1)	internal indicator for SAP
sap_state		char(1)	internal indicator for SAP
sap_statv		char(5)	internal indicator for SAP
sek_status	Secondary status	char(5)	Secondary status (or preparation status) ADE_STATUS_ZUORD (spec. record type)
sek_statustext_nr	Text number of secondary status	integer	Reference: ADE_STATUSTEXTE
sperr	Locked by	char(10)	User who has blocked the order/OP. (PDM field ID: ANR.SPERR)
sperr_date	Time of the block	date	Time of the block (PDM field ID: ANR.SPERRDAT)
sperr_pflge	Blocked for MLE by	char(10)	User who has blocked the op (PDM field ID: ANR.SPERR:EDIT)
sperr_pflge_date	Date of the block by MLE Interface	date	Date of the block by MLE Interface (PDM field ID: ANR.SPERRDAT:EDIT)
sperr_pflge_time	Time of the block by MLE Interface	integer	Time of the block by MLE Interface (PDM field ID: ANR.SPERRZEI:EDIT)
sperr_time	Time of the block	integer	Time of the block (PDM field ID: ANR.SPERRZEI)
sta_mengenap		char(1)	
terminalnr	Terminal no. last posting	smallint	Terminal number of the last logon (PDM field ID: ADEPRO.TNR)
tranr_art		char(10)	
tranr_cnr		char(20)	
tranr_res		char(40)	
tranr_restyp		char(4)	
tranr_smp		char(12)	
tranr_tmp		char(12)	
trigger_anr		char(40)	
u_abmeld_dat	Last interruption - date	date	Last interruption - date (PDM field ID: ANR.DATE:U)
u_abmeld_zeit	Last interruption - time	integer	Last interruption - time (PDM field ID: ANR.ZEIE:U)
user_c_29		char(1)	User-specific field
user_c_30		char(1)	User-specific field
user_c_31		char(1)	User-specific field
user_c_32		char(1)	User-specific field
user_c_33		char(1)	User-specific field
user_c_34		char(1)	User-specific field
user_c_35		char(1)	User-specific field
user_c_36		char(1)	User-specific field
user_c_37		char(1)	User-specific field
user_c_38		char(1)	User-specific field
user_c_39		char(1)	User-specific field
user_c_40		char(1)	User-specific field
user_c_41		char(1)	User-specific field

user_c_42		char(1)	User-specific field
user_c_43		char(1)	User-specific field
user_c_44		char(1)	User-specific field
user_c_45		char(10)	User-specific field
user_c_46		char(10)	User-specific field
user_c_47		char(10)	User-specific field
user_c_48		char(10)	User-specific field
user_c_49		char(10)	User-specific field
user_c_50		char(10)	User-specific field
user_c_51		char(20)	User-specific field
user_c_52		char(20)	User-specific field
user_c_53		char(20)	User-specific field
user_c_54		char(20)	User-specific field
user_c_55		char(20)	User-specific field
user_c_56		char(20)	User-specific field
user_c_57		char(20)	User-specific field
user_c_58		char(20)	User-specific field
user_c_59		char(20)	User-specific field
user_c_60		char(20)	User-specific field
user_c_61		char(20)	User-specific field
user_c_62		char(20)	User-specific field
user_c_63		char(20)	User-specific field
user_c_64		char(20)	User-specific field
user_c_65		char(40)	User-specific field
user_c_66		char(40)	User-specific field
user_code		char(8)	User field key for future use -> Allocation in 1st step "SYSTEM" (PDM field ID: ANR.USRFLD)
user_d_01		date	User-specific field
user_d_02		date	User-specific field
user_d_03		date	User-specific field
user_d_04		date	User-specific field
user_d_05		date	User-specific field
user_d_06		date	User-specific field
user_f_23		decimal(18,6)	User-specific field Current amount of partial quantity print
user_f_24		decimal(18,6)	User-specific field
user_f_25		decimal(18,6)	User-specific field
user_f_26		decimal(18,6)	User-specific field
user_f_27		decimal(18,6)	User-specific field
user_f_28		decimal(18,6)	User-specific field
user_n_07		integer	User-specific field RW 7.1->7.2: transfer from table Tabelle auftrag_status from field: alt_aus1
user_n_08		integer	User-specific field MPLRF: production line number RW 7.1->7.2: transfer from table Tabelle auftrag_status from field: alt_teil

user_n_09		integer	User-specific field MPLRF: Offset when cutting rolls RW 7.1->7.2: transfer from table Tabelle auftrag_status from field: alt_dauer
user_n_10		integer	User-specific field
user_n_11		integer	User-specific field
user_n_12		integer	User-specific field
user_n_13		integer	User-specific field
user_n_14		integer	User-specific field
user_n_15		integer	User-specific field
user_n_16		integer	User-specific field
user_n_17		integer	User-specific field
user_n_18		integer	User-specific field
user_n_19		integer	User-specific field
user_n_20		integer	User-specific field
user_n_21		integer	User-specific field
user_n_22		integer	User-specific field
vl_zyklen	Number of cycles "variable activities"	integer	Number of cycles "variable activities"
vwe_code	Usage decision (RF)	char(10)	Usage decision (MPLRF)
vwe_id	Usage decision (MPLRF)	char(20)	Usage decision (MPLRF)

2.24. auftrags_bestand

Table name: auftrags_bestand		Product: BDE	
Archive table: a_auftrags_bestand		Reload table: r_auftrags_bestand	
Designation: Order backlog		Description: Stock of BDE orders (OPs). All fields, which contain target specifications or no recorded actual data, are summarized in the backlog.	
Column name	Column designation	Type	Description
a_prio	External priority	char(4)	External priority from the PPS system ("0" - "9") Priority Performance according to ADE_AUFTRAGSARTEN.PRIO_STEUERUNG[1,1] please also see priority management (PDM field ID: ANR.EXTPRIO)
a_stufe	Indicator logging on/off	char(3)	Authorization indicator 0...9, if person is authorized to log the OP on/off (qualification indicator) (PDM field ID: ANR.ASTUFE)
a_typ	Order type	char(4)	AU -> orders (header information) AG -> operations UAG -> sub operation SPL -> split SAG -> collective operations Particularities in TPL (PDM field ID: ANR.ATYP)

abmeldopt	Logoff options	char(10)	This field is only kept for internal processing at the OP, the processing code is maintained and is taken over automatically! [1,1]: This option controls which types of logging off are allowed. "U" In case of a manual logoff, the OP is not finished but merely interrupted. "B" OP only logoff when active processing-code != "U" OP logof (STD) [2,2] Automatic transmission of an interruption to the preceding OPs till the next beginning of a milestone ""/"N" No automatic transmission (standard) "J/U" In case of an INTERRUPTION, interrupt the preceding OPs [3,3]: If this indicator is set the target quantity is automatically checked at each quantity posting and the OP is automatically finished if the target quantity is reached. It takes the yield quantity into account and is analyzed in connection with the following indicators. ""/"N" it is not automatically finished when the target quantity is reached (standard) "J" it is automatically finished when the target quantity is reached "U" it is automatically interrupted when the target quantity is reached "F" it is automatically finished when the target quantity is reached und log subsequent OP on with the same article number "K" it is automatically finished when the target quantity is reached und log subsequent OP on with the same campaigning number The OP is not finished but interrupted if the OP, which lies before this OP in the OP sequence, with the indicator target quantity update="J" is not finished [4,4] - see [3,3] or [7,7] + SCRAP = "J" [5,5] - see [3,3] or [7,7] + REWORK= "J" [6,6] - see [3,3] or [7,7] + PROBLEM QUANTITY= "J" [7,7] The preceding OPs are automatically finished till the next beginning of a milestone (see indicator [8,8]) ""/"N" No automatism "J" preceding OPs are finished - only running OPs with the indicator "external processing" "i" preceding OPs are finished - all running OPs, too "M" preceding Ops are finished and filled up to the respective target quantity, in order to determine the remaining quantity "m" is referred to depending on [4,6] yield and also other quantities. preceding OPs are finished with an automatic posting of the residual quantity - all running OPs, too [8,8] Beginning of milestone in connection with [7,7] (PDM field ID: ANR.OPT:xx)
abruest_zeit	Teardown time	integer	Teardown time planned by PPS (teardown time) (PDM field ID: ANR.ABRZ)
abruest_zeit_expr	Formula	char(6)	If RUEST_ZEIT_MOD is set to "F": Reference to formula (PDM field ID: ANR.ABRZ:EXPR)
abruest_zeit_mod	Calculation mode	char(1)	Calculated F = via formula M = manually (by the user) (PDM field ID: ANR.ABRZ:MOD)
afo_lfd_nr	Operation Position	integer	Consecutive numbering of the OPs of an order, 1..X The shop floor scheduling module requires them and they must not be changed. If an OP is deleted or inserted both values have to be redetermined for each OP of the order. ATTENTION: consecutive number according to the sorting of the OP number; does not represent the sequency of the order (PDM field ID: AGPOS)
afolg	Sequence	char(10)	Sequence No. (PDM field ID: ANR.AFOLG)
ag_art		char(5)	Information field for a logical differentiation only - for future use -
ag_bez	Designation of the operation	char(40)	Designation of the operation (article/OP designation) Short designation at <> AU, it is the OP designation (PDM field ID: ANR.AGBEZ)

ag_verkn_typ	Link type	char(1)	Verarbeitung im ANR-Bapi ab HAUB_SWA_DL-030310 / 201003046 (04/2010) (PDM field ID: ANR.VKNTYP)
ag_verweis	Reference	integer	Reference to the superior OP (UAG, SPL)! In case of COPs, the reference of the grouped COPs is written here at the (individual) OPs (PDM field ID: ANR.VERWEIS:ANR)
agnr	OP number	char(20)	OP number ... it can also be a collective OP, this is determined by the record type. (PDM field ID: ANR.AGNR)
als_dsbez	Data identifier for ALS	char(20)	Data set identifier for ALS (Arburg control system) (PDM field ID: ANR.DSBEZ)
anlage	Creation	char(10)	The user who has created the order/OP in the PPS system can also be entered here via the PPS interface. This is the user (BEARB/DAT/ZEI) in case of a manual creation. RW 7.1->7.2: transfer from table a_kopf_best aus Feld: planer_pps (PDM field ID: ANR.ANLAG)
anlage_date	Creation date	date	Creation date RW 7.1->7.2: transfer from table a_kopf_best from field: anlage_date (PDM field ID: ANR.ANLAGDAT)
anlage_time	Creation time	integer	Creation time RW 7.1->7.2: transfer from table a_kopf_best from field: anlage_zeit (PDM field ID: ANR.ANLAGZEI)
anmeldopt	Logon options	char(10)	Manual entry or transfer due to configuration in processing code or template Internal for processing purposes only, not to be displayed
anz_split_masch	Number of split machines	smallint	Max. number of machines on which the OP may be split (number of split machines) Maximum value is 99 (PDM field ID: ANR.MAXANZSPLIT)
arbplan	Number of the work plan	char(40)	Number of the work plan Is assigned to the number of the work plan when creating orders from a work plan Note: Field is not set in the work plan (aplan_best) Can be transferred at the interface; the work plan number is transferred when generating an order from a work plan. The logical differentiation to what this value refers results from the indicator "from PPS". (PDM field ID: ANR.APNR)
artikel	Article	char(40)	Article number (article number) This would be the final article for the order Can also be maintained at the OP RW 7.1->7.2: Transfer from table a_kopf_best aus Feld: teile_nr (PDM field ID: ANR.ATK)
artikel_bez	Article designation	char(40)	AU: Designation of final article <> AU: Article designation (PDM field ID: ANR.ATKBEZ)
artikel_idx	Drawing status of the article	char(50)	Drawing status of the article, also often called index (PDM field ID: ANR.ATKIDX)
auftrag_art	Order type	char(5)	Order type is always the type of the "order header"; it is kept in a redundant way at the process. ADE_AUFTRAGSARTEN (cannot be maintained in the operation!) cannot be changed anymore after INSERT!! RW 7.1->7.2: transfer from table a_kopf_best aus Feld: auftrag_art (PDM field ID: ANR.AUART)

auftrag_nr	Order number	char(40)	BDE order number (= order + operation = OP) Overall key of the object Distribution according to SETUP RW 7.1->7.2: Transfer from table a_kopf_best aus Feld: auftrag_nr BDE order number (= order + operation = OP) Overall key of the object Distribution according to SETUP RW 7.1->7.2: Transfer from table a_kopf_best aus Feld: auftrag_nr (PDM field ID: ANR.ANR)
aunr	Order	char(40)	--- (PDM field ID: ANR.AUNR)
bearb	Last editor	char(10)	Last editor This is the user (BEARB/DAT/ZEI) in case of a manual processing. RW 7.1->7.2: transfer from table a_kopf_best from field: bearb (PDM field ID: ANR.BEARB)
bearb_date	Editing date	date	Editing date RW 7.1->7.2: transfer from table a_kopf_best from field: bearb_date (PDM field ID: ANR.BEARBDAT)
bearb_time		integer	last editing time
bearb_zeit	Processing time	integer	In 7.2 THIS TIME is the target run time of an OP, which is referred to in ALL cases. The formula defines which components flow into the calculation of this time and in what way. In case of an external processing, the delivery time can directly be referred to by means of this. (PDM field ID: ANR.BEARBZ)
bearb_zeit_expr	Formula	char(6)	If BEARB_ZEIT_MOD is set to "F": Reference to formula (PDM field ID: ANR.BEARBZ:EXPR)
bearb_zeit_mod	Calculation mode	char(1)	Calculated F = via formula M = manually (by the user) (PDM field ID: ANR.BEARBZ:MOD)
chargen_pflicht	Subject to management in batches	char(1)	J/N J: This OP is subject to management in batches Please also see processing code (PDM field ID: ANR.OPT:CNR)
einm_menge	Unit quantity	decimal(18,6)	Init quantity (= SAP base quantity) to which the specifications of the operation refer. (The SAP base quantity is taken over here and can be referenced in the formulas for calculating the process times) (PDM field ID: ANR.EINHMENGE)
einm_menge_einh	Unit of the unit quantity	char(3)	Unit of the unit quantity (= SAP base quantity) (PDM field ID: ANR.EINHMENGEEINH)
erfass_art	Piecework indicator/premium	char(1)	Piecework indicator/premium (E/G/S/M/Z..) (PDM field ID: ANR.AKKORD)
erfassbar	OP can be confirmed	char(1)	OP can be confirmed; is also in the processing code (PDM field ID: ANR.OPT:ERF)
erranf_dat	Planned start, date	date	Calculated start date (earliest start dates) Planned start The planned dates are used in BDE displays/reports! (PDM field ID: ANR.DATB)
erranf_zeit	Planned start	integer	Planned start The planned dates are used in BDE displays/reports! (PDM field ID: ANR.ZEIB)
errend_dat	Planned end, date	date	Calculated finish date (lat. finish date) Planned end The planned dates are used in BDE displays/reports! (PDM field ID: ANR.DATE)

errend_zeit	Planned end	integer	Planned end The planned dates are used in BDE displays/reports (PDM field ID: ANR.ZEIE)
farbe	FLS: Color of the OP	char(20)	--- (PDM field ID: ANR.COLOR)
fertvar_verweis	Reference to production variant	integer	Reference to selected production variant ÖRES_FERTIGUNG_VAR Field is renamed! (PDM field ID: ANR.VERWEIS:FERTVAR)
firma	Company of the cost center	char(4)	Company of the cost center (PDM field ID: ANR.FIR)
fremdbearbeitung	Indicator wheter ext. or int. processing	char(1)	Indicator, whether external processing or internal processing; is also kept at the processing code. Please see configuration at the processing code. (PDM field ID: ANR.OPT:FREMDFERT)
frueh_anf_dat	Earliest start	date	Earliest start AU: Basic date Otherwise: scheduling result; whether due date at the console can be positioned before the earliest start date of the AU is defined in the setup (-> plausibility check) (PDM field ID: ANR.DATFB)
frueh_anf_zeit	Earliest start	integer	Earliest start AU: Basic date Otherwise: scheduling result; whether due date at the console can be positioned before the earliest start date of the AU, is defined in the setup (-> plausibility check) (PDM field ID: ANR.ZEIFB)
frueh_end_dat	Earliest end	date	Earliest end (PDM field ID: ANR.DATFE)
frueh_end_zeit	Earliest end	integer	Earliest end (PDM field ID: ANR.ZEIFE)
geaendert_hydra	Modified HYDRA	char(1)	Indicator, whether the order/OP has been changed (PDM field ID: ANR.BEARB:HYDRA)
geaendert_planung		char(1)	Program ppsrueck.c, confirms changes that are relevant for the planning. --> This indicator is prompted here
geaendert_pps	Modified PPS	char(1)	Indicator, whether the order/OP has been changed by the PPS system. (PDM field ID: ANR.BEARB:PPS)
kopf_verweis	Reference to the header	integer	Reference to a_kopf_best (PDM field ID: ANR.VERWEIS:AUNR)
kostenart	Cost type	char(20)	Cost type (PDM field ID: ANR.KART)
kostenstelle	Cost center	char(10)	Cost center ... cost center to be charged (PDM field ID: ANR.KST)
kunden_bez	Customer designation	char(40)	Customer designation can only be maintained in case of AU RW 7.1->7.2: transfer from table a_kopf_best aus Feld: kunden_bez (PDM field ID: ANR.KDBEZ)
lagerort	Storage loc.	char(12)	Storage location of the goods receipt from PPS header only 10-digit in SAP; in System 12-digit due to material buffer
last_afo	Last operation	char(1)	J/N: J = last OP of the order The shop floor scheduling module requires them and they must not be changed. If an OP is deleted or inserted both values have to be redetermined for each OP of the order. ATTENTION: please see afo_lfd_nr
last_term_date		date	Transfer from PPS or in case of internal scheduling -> display in tab "administration" (header and OP) -> HLS-BAPI: has to support this field
last_term_time		integer	Transfer from PPS or in case of internal scheduling -> display in the tab "administration" (header and OP) -> HLS-BAPI: must support this field

layout	Layout	char(20)	(PDM field ID: ANR.LAY)
lieferzeit	Delivery time	integer	Delivery time: Is used as TARGET processing time in case of OPs for which the indicator "external processing" is set in the processing code. This is respectively guaranteed by "switching" the formula. (PDM field ID: ANR.LIZ)
liege_zeit	Wait time	integer	Minimum wait time of the OP prior to the machine (wait time) - no formula - no transfer from template - is preallocated when generating from work plan (PDM field ID: ANR.LIEZ)
liege_zeit_max	Max. wait time	integer	Maximum synchronization time specified, which determines how much time may be between the start of the successor and the end of the predecessor (PDM field ID: ANR.LIEZ:MAX)
lohnart	Wage type	char(4)	(Wage type) (PDM field ID: ANR.LART)
ls_safo_nr	Number of the collective OP	char(40)	Number of the collective OP to which the OP belongs redundant to AG_VERWEIS!! split_auftrag_nr
ls_sammel_kz	Administration: collective OPs	char(1)	Administration: collective OPs N = normal OP M = master of a collective OP S = individual operation of a collective OP (is not selected when displaying); cannot be logged on in BDE system
ls_split_anz	Administration: Splitting	smallint	Administration: Splitting Current number of splits Identification can only be used for reading access! (PDM field ID: ANR.ANZSPLIT)
ls_split_kz	Administration: Splitting	char(1)	Administration: Splitting N = normal OP M = master of a split OP (original); cannot be logged on in the BDE system S = split OP ATTENTION: the information whether a split OP or COP is displayed is controlled via a separate indicator (please see below)
lst_code	activity code	char(6)	Table: Activity code ADE_LST_CODES IN NO WAY THIS MAY BE CHANGED WHEN THE OP HAS BEEN LOGGED ON! (PDM field ID: ANR.LSTCODE)
masch_nr	Planned single machine	char(20)	Planned single machine -> remains unchanged when logging on -> can also be empty -> special case "99999999" (planned for group) is omitted -> current machine is a status information AUFTRAG_STATUS.EINGEPLANT Special case: If "automatic scheduling" is configured at the machine (Ö MASCHINEN.AUTO_EINLASTUNG), the AB.MASCH_NR is changed when logging on! (PDM field ID: ANR.MNR)
matetyp	FLS: Material type	char(20)	Material type Table: HZ_TYPEN Can also be maintained at the OP (please see Feld ARTIKEL) RW 7.1->7.2: transfer from table a_kopf_best aus Feld: matetyp (PDM field ID: ANR.MATTYP)
mb_verh_ruesten	Employee-Setup	smallfloat	Target employee ratio Setup (PDM field ID: ANR.MBVERH:RUE)
mb_verhaeltnis	Employee ratio	smallfloat	Required employees for the production (0.33 = one person can produce 3 orders simultaneously (employee ratio)). (PDM field ID: ANR.MBVERH:NORM)

mehrfach_kz	Parallel production	char(1)	J/N, whether it is allowed to log OP on several times (parallel production) (PDM field ID: ANR.OPT:MULTIMNR)
meinheit_bas	Base quantity unit	char(3)	Base quantity unit -> is set according to the header quantity unit for all OPs in case of the SAP standard interface Reference: HYD_EINHEITEN (PDM field ID: ANR.SGE:B)
meinheit_lief	Delivery quantity unit	char(3)	Delivery quantity unit; only header, is not kept at the status (PDM field ID: ANR.SGE:LI)
meinheit_pri	Primary quantity unit of entry	char(3)	Prim. quantity unit of entry (PDM field ID: ANR.SGE:P)
meinheit_sek	Secondary quantity unit of entry	char(3)	Sec. quantity unit of entry (PDM field ID: ANR.SGE:S)
meinheit_ter	Tertiary quantity unit of entry	char(3)	Tert. quantity unit of entry (PDM field ID: ANR.SGE:T)
menge_pri_uebli	Overdelivery	decimal(18,6)	>100 an overdelivery (of the yield/total quantity) is allowed for this operation. 100(%) = overdelivery is not allowed The entered value is a percentage in relation to the target quantity. Whether overdelivery is allowed results from MENGE_PRI_UEBLI_R and the percentage (PDM field ID: ANR.MENGEPROZ:UEBLI)
menge_pri_uebli_r	Reaction to overdelivery	char(1)	Reaction to overdelivery ATTENTION: new designation Can be transferred via the interface; if the indicator is not transferred via the interface it is taken over by the processing code. (PDM field ID: ANR.OPT:UEBLI)
menge_pri_untli	Underdelivery	decimal(18,6)	< 100 an underdelivery (of the yield/total quantity) is allowed for this operation. 100(%) = underlivery is not allowed The entered value is a percentage in relation to the target quantity. Whether underdelivery is allowed results from MENGE_PRI_UNTLI_R and the percentage (PDM field ID: ANR.MENGEPROZ:UNTLI)
menge_pri_untli_r	Reaction to underdelivery	char(1)	Reaction to underdelivery ATTENTION: new designation Can be transferred via the interface; if the indicator is not transferred via the interface it is taken over by the processing code. (PDM field ID: ANR.OPT:UNTLI)
mgruppe	Machine group	char(20)	Machine group of the MASCH_NR (PDM field ID: ANR.MGRP)
notiz_vorh	Note available	char(1)	Indicator for "commentary available" (notes) at the OP X = notes are present, but don't show them on the terminal T = notes are present, minimum one note is for display on the terminal " " = no note is present This indicator has to be set by HYINFO-BAPI.
op_code	Operation code	char(10)	Operation code, for future use Explanation: see table "HYD_EINHEITEN_UMR"
pdv_pruefplan_nr	PDV inspection plan number	char(20)	for future use (PDM field ID: ANR.PPNR)
plan_werk	ADE: (reserved)	char(4)	Company/plant; is taken over by the order header in case of <> AU. RW 7.1->7.2: transfer from table a_kopf_best aus Feld: sap_werk (PDM field ID: ANR.WERK:S)
prplan_nr	Inspection plan number	integer	If the CAQ module is licensed Inspection plan number for quality management (PDM field ID: ANR.PPLNR)
pruef_masch_nr	Inspection workplace (CAQ)	char(20)	Inspection workplace (CAQ) (PDM field ID: ANR.PMNR)
pruef_zeit	CAQ integration	integer	CAQ integration (PDM field ID: ANR.PZ)
pruef_zeit_expr	Formula	char(6)	If PRUEF_ZEIT_MOD is set to "F": Reference to formula (PDM field ID: ANR.PZ:EXPR)

pruef_zeit_mod	Calculation mode	char(1)	Calculated F = via formula M = manually (by the user) (PDM field ID: ANR.PZ:MOD)
puffer_zeit	Buffer time by scheduling	integer	Buffer time by scheduling OP: OP buffer is determined from the difference between LST and EST. AU: Results from the sum of all OPs Note: if the buffer time is negative the order is probably delayed. (PDM field ID: ANR.PUFZ)
qm_ag_typ		char(2)	QM operation type: 0 or empty = productive operations (without QM share) 1 = pure QM operations (unproductive) 2 = mixed operations (productive operations wiht QM share) (PDM field ID: ANR.QMAGTYP)
qm_m_auftrag_nr		char(40)	Reference to master OP for CAQ OPs: At the moment this function is applied when QM-IDI is in use, to connect one or several QM operations with a productive operation. In this case, it may be configured for processing codes whether the corresponding, connected operations are to be logged on, off or interrupted along with the master. (PDM field ID: ANR.QMMANR)
qual_ruesten	qualification number for setup	integer	PEP: Unique qualification number for the workforce requirements for setup (PDM field ID: QUAL:RUE)
qualifikation	qualification number for production	integer	PEP: Unique qualification number for the workforce requirements for production (PDM field ID: QUAL:NORM)
red_puffer_zeit	Reducible time	integer	OP: reducible time: sum from the differences between normal time and current time for wait and transport times, i.e. this can still be reduced by the reduction strategy. AU: results from the sum of all OPs (PDM field ID: ANR.REDPUFZ)
res_dnc	Component list DNC	char(40)	If the WRM module is used the resource of the type "DNC" that is available at first in the component list is taken over. (PDM field ID: ANR.RES:DNC)
res_emat	Component list input material	char(40)	The resource of the type "material" that is available at first in the component list is taken over here. This is the "most important" input material . RW 7.1->7.2: transfer from table a_kopf_best from field: material (PDM field ID: ANR.RES:EMAT)
res_wnr	Component list tool	char(40)	If the WRM module is used the resource of the type "tool" that is available at first in the component list is taken over. (PDM field ID: ANR.RES:WNR)
rf_a_breite	Output width in MM	decimal(18,6)	If MPLRF-BP is licensed Output width in MM (PDM field ID: ANR.RFBREITEA)
rf_abzweig	Identification branch	char(1)	If MPLRF-BP is licensed Identifies mother and child OP in case of planned branches: "M" mother OP "K" child OP (PDM field ID: ANR.RFABZ)
rf_agtyp	Type of the operation	char(1)	If MPLRF-BP is licensed Identifies the type of the operation: "G": Annealing OP "M": Material staging OP "N": Emergency operaiton "P": Packing OP (central scales or packing location) "H": Parent OP "L": Child OP (PDM field ID: ANR.RFAGTYP)
rf_agvfa	Spec. mass per unit area	decimal(18,6)	If MPLRF-BP is licensed Spec. mass per unit area Unit: G/M2 (PDM field ID: ANR.RFAGVFA)

rf_bsbrs	Sum of the seam width	decimal(18,6)	If MPLRF-BP is licensed Sum of the seam width in mm (PDM field ID: ANR.RFBSBRS)
rf_e_breite	Input width in MM	decimal(18,6)	If MPLRF-BP is licensed Input width in MM (PDM field ID: ANR.RFBREITEE)
rf_etr_anz	Number of daughter rolls per cut	integer	If MPLRF-BP is licensed Cutting operation (mother and child OP) Number of planned daughter rolls per cut. (PDM field ID: ANR.RFTRANZ)
rf_gtr_anz	Number of daughter rolls, sum	integer	If MPLRF-BP is licensed Cutting operation (mother OP) Number of planned daughter rolls per cut - sum beyond all branches/deducted material. (PDM field ID: ANR.RFTRANZSUM)
rf_huegewicht	Casing weight in gramme	decimal(18,6)	If MPLRF-BP is licensed Casing weight in gramme The casing weight of the daughter rolls is indicated here in case of cutting operations Unit: GRAMME (G) (PDM field ID: ANR.RFHUEGEW)
rf_m_auftrag_nr	Mother operation	char(40)	If MPLRF-BP is licensed In case of planned deducted material, this field refers to the respective mother OP. In case of a mother OP, the field refers to itself. (PDM field ID: ANR.RFMANR)
rf_opcode	SAP: Operation code	char(10)	Operation code from SAP. (PDM field ID: ANR.SAP.OPCODE)
rf_roanz	Number of output rolls	integer	If MPLRF-BP is licensed Number of parallel daughter rolls (PDM field ID: ANR.RFRANZ)
rf_rosch	Cutting rolls	char(1)	Indicator cutting rolls: "" no cutting "T" cutting rolls active (numbering of daughter rolls) "M" cutting active (mother rolls are generated again) (PDM field ID: ANR.RFOPT:RS)
rf_stflaech	Surface per piece	decimal(18,6)	If MPLRF-BP is licensed Area of one PIECE of the output material If > 0, the quantity "pieces" is posted. Unit mm2/pieces (PDM field ID: ANR.RFSTKF)
rf_zuzweig	Identification additional quantity	char(1)	If MPLRF-BP is licensed Identifies an operation of a planned additional quantity. The planned additional quantity is then entered in the field RF_ZUZWEIGMENGE. "J" OP with planned additional quantity "N" OP without planned additional quantity If the tracing of rolls is activated planned additionally quantities are additionally transferred as components. (PDM field ID: ANR.RFZUZ)
rf_zuzweigmenge	Quantity of plan.addit. qty. in...	integer	If MPLRF-BP is licensed Quantity of planned additional quantity in the operation quantity unit (PDM field ID: ANR.RFZUZM)
rlz2_expr	Formula RRT2	char(6)	Formula for the remaining run time (PDM field ID: ANR.RLZ2:EXPR)
rlz_expr	Calculation formula	char(6)	Reference to the calculation formula for the determination of the remaining run time. The calculation formula itself is a formula that is defined in the formula administration. The specification itself is defined in the template. Note: In the formula it must be possible to reference to the IST and REST fields in the the table AUFTRAGS_STATUS (PDM field ID: ANR.RLZ:EXPR)
rmnr	Confirmation No.	char(40)	Confirmation number for the identification of the object to be reported The RMNR of the OP has to be indexed in case of splits This is allocated according to the SETUP (PDM field ID: ANR.RMNR)

ruet_zeit	Setup time	integer	Target setup time in seconds (setup time or setup time when changing groups) (PDM field ID: ANR.RUEZ)
ruet_zeit_expr	Formula	char(6)	If RUEST_ZEIT_MOD is set to "F". Reference to formula (PDM field ID: ANR.RUEZ:EXPR)
ruet_zeit_mod	Setup time mode	char(1)	Calculated F = via formula M = manually (by user) (PDM field ID: ANR.RUEZ:MOD)
ruet_zeit_zuschl	Setup time supplement	integer	Is set for setup change matrix (PDM field ID: ANR.RUEZ:ZUSCHL)
s_bpc_quan_1	SAP BPC quantity	decimal(18,6)	SAP BPC Value QUAN 1 (PDM field ID: ANR.SGR:BUP)
s_bpc_uniso_1	SAP BPC ISO unit	char(3)	SAP BPC ISO QUAN 1 (PDM field ID: ANR.SGEISO:BUP)
s_bpc_unit_1	SAP BPC unit	char(3)	SAP BPC Unit QUAN 1 (PDM field ID: ANR.SGE:BUP)
s_co_bpc_1	SAP: Business process	char(12)	SAP: Business process (PDM field ID: ANR.BUPID)
s_hdr_denominator	SAP: Conversion factor denominator	integer	Conversion factor denominator for converting into the base quantity unit (PDM field ID: ANR.EXTUMRFAKT:N)
s_hdr_nominator	SAP: Conversion factor numerator	integer	Conversion factor numerator for converting into the base quantity unit (PDM field ID: ANR.EXTUMRFAKT:Z)
s_source_sys	SAP: Logical system	char(10)	Logical system SAP If the field TRANSFER (see above) is not transferred, but SAPSYS, the value that is written here is also entered there. (PDM field ID: ANR.SAPSYS)
sap_auftrag_nr	SAP: Order number	char(12)	Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAPAUNR)
sap_bezfl	SAP: Reference sequence	char(6)	Reference sequence in case of parallel sequence Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAP:BZGFOLG)
sap_laufnr	SAP: Order header	char(12)	Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAPAUNRK)
sap_maplfl		char(6)	Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAPAFOLGV)
sap_maufnr	SAP: Predecessor in the order network	char(12)	Original data from SAP Are taken over during transfer of SAP data from KK2 (OPERA2) (sapr3avo) SAP standard: Predecessor in the order network IDENTIFICATION: AGNR.SAPAUNRV (PDM field ID: ANR.SAPAUNRV / (diverse))
sap_mrflg		char(1)	Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAP:MRFLG)
sap_mvornr		char(4)	Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAPVGNRV)
sap_split_nr	SAP split number	smallint	Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAP:SPLIT)

sap_usr00	SAP user field 00	char(20)	SAP user field (PDM field ID: ANR.SAP:USR00)
sap_usr01	SAP user field 01	char(20)	SAP user field 01 (PDM field ID: ANR.SAP:USR01)
sap_usr04	SAP user field 04	decimal(18,6)	SAP user field 04 (PDM field ID: ANR.SAP:USR04)
sap_usr04_unit	SAP user field 04 unit	char(3)	SAP user field - unit 4 (PDM field ID: ANR.SAP:USR04EINH)
sap_uvlg	SAP SOP	char(4)	Original data from SAP Are taken over during transfer of SAP data from KK2 file OPERA2 program sapr3avo (PDM field ID: ANR.SAPUVGNR)
sap_vg_nr	PPS operation	char(4)	Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAPVGNR)
sap_vgfolge	SAP sequence	char(6)	Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAPAFOLG)
sap_vornr1	SAP: Branch operation	char(4)	Branch operation in case of parallel sequence Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAP:VGNRA)
sap_vornr2	SAP: Return operation	char(4)	Return operation in case of parallel sequence Original data from SAP Are taken over during the transfer of SAP data from KK2 (OPERA2) (sapr3avo) (PDM field ID: ANR.SAP:VGNRR)
serialnr_pflcht	Serial number requirement	char(1)	Please also see order type or processing code "+" = Positive "-" = Negative " /"N" = No serial number requirement BAPI: When transferring serial numbers the indicator has possibly to be reset if the indicator SERIENNR_PFLICHT is set to "X" at the processing code. (PDM field ID: ANR.OPT:SNR)
soll_aus_bas	Target scrap	decimal(18,6)	Target scrap (base quantity unit) (PDM field ID: ANR.SGR:AUSB)
soll_aus_pri	Target scrap (primary)	decimal(18,6)	Target scrap (prim.) (PDM field ID: ANR.SGR:AUSP)
soll_aus_sek	Target scrap (secondary)	decimal(18,6)	Target scrap (sec.) (PDM field ID: ANR.SGR:AUSS)
soll_aus_ter	Target scrap (tertiary)	decimal(18,6)	Target scrap (tert.) (PDM field ID: ANR.SGR:AUST)
soll_bedien_ant	Proportion of target user	decimal(18,6)	Proportion of the target user
soll_dauer	Target cycle	decimal(18,6)	Duration for 1000 machine cycles in seconds (cycle time) -> CAN ALSO BE 0! (PDM field ID: ANR.SZY)
soll_dauer_expr	Formula	char(6)	Formula for calculating the target cycle (PDM field ID: ANR.SZY:EXPR)
soll_dauer_fmt	Display format	char(3)	Display format for the target cycle time (PDM field ID: ANR.SZY:FMT)
soll_dauer_mod	Target cycle time calculated (F/M)	char(1)	Target cycle time calculated (F/M) F = via formula M = manually (by the user) (PDM field ID: ANR.SZY:MOD)
soll_div	Target pulse factor	decimal(18,6)	Target pulse factor (divisor analogous to partitioning) (PDM field ID: ANR.IMPFAKT)
soll_menge_ansatz		decimal(18,6)	

soll_menge_bas	Target quantity (base quantity unit)	decimal(18,6)	Target quantity (base quantity unit) (PDM field ID: ANR.SGR:GUTB)
soll_menge_pri	Target quantity (primary)	decimal(18,6)	Target quantity (prim.) (PDM field ID: ANR.SGR:GUTP)
soll_menge_sek	Target quantity (secondary)	decimal(18,6)	Target quantity (sec.) (PDM field ID: ANR.SGR:GUTS)
soll_menge_ter	Target quantity (tertiary)	decimal(18,6)	Target quantity (tertiary) (PDM field ID: ANR.SGR:GUTT)
soll_te	Premium specification	decimal(18,6)	Premium specification: te (sec. per 1000 pieces) LLE (person) (PDM field ID: ANR.TE)
soll_te_expr	Formula	char(6)	Formula for calculating the part production time (PDM field ID: ANR.TE:EXPR)
soll_te_fmt	Display format for part production time	char(3)	Display format for the part production time ... part according to TE:... of the object definition is taken over from template and can be changed. (PDM field ID: ANR.TE:FMT)
soll_te_mod	Calculation mode	char(1)	Calculated F = via formula M = manually (by the user) (PDM field ID: ANR.TE:MOD)
soll_teb	teb	decimal(18,6)	Premium specification: te (sec. per 1000 pieces) LLE (ressource) (PDM field ID: ANR.TEB)
soll_teb_expr	Formula for calculating part prod. time	char(6)	Formula for calculating the part production time (PDM field ID: ANR.TEB:EXPR)
soll_teb_fmt	Display format for part production time	char(3)	Display format for the part production time Is taken over from template and can be changed. (PDM field ID: ANR.TEB:FMT)
soll_teb_mod	Calculation mode	char(1)	Calculated F = via formula M = manually (by the user) (PDM field ID: ANR.TEB:MOD)
soll_tell	Partitioning	decimal(18,6)	Target partitioning of the OP (partitioning) can be changed at the terminal (PDM field ID: ANR.TLG)
soll_tr	tr	decimal(18,6)	Premium specification: tr LLE (person) Display via FELDDEFINITION (TR) (PDM field ID: ANR.TR)
soll_tr_expr	Formula	char(6)	Formula for calculating the setup time (PDM field ID: ANR.TR:EXPR)
soll_tr_mod	Calculated	char(1)	Calculated F = via formula M = manually (by the user) (PDM field ID: ANR.TR:MOD)
soll_trb	trb	decimal(18,6)	Premium specification: tr LLE (resources) Display via FELDDEFINITION (TRB) (PDM field ID: ANR.TRB)
soll_trb_expr	Formula for calculating	char(6)	Formula for calculating (PDM field ID: ANR.TRB:EXPR)
soll_trb_fmt	Format trb	char(3)	Format for target TRB

soll_trb_mod	Calculated	char(1)	Calculated F = via formula M = manually (by the user) (PDM field ID: ANR.TRB:MOD)
sollmengenforts	Target quantity update	char(1)	By means of this, it is controlled whether the posted yield of the OP is automatically transferred as target quantity to the following OP (OP numbering) when logging off. Transfer due to configuration in processing code Internal for processing purposes only, not to be displayed
sort_dat		date	Start date for sorting NO DATE in terms of a due date; is merely used in order to sort the sequencing list AVG: Sequencing OTHER: is equated with ERRANF_DAT Should be possible to be displayed at the console!
sort_zeit		integer	Start date for sorting NO DATE in terms of a due date; is merely used in order to sort the sequencing list AVG: Sequencing OTHER: is equated with ERRANF_DAT Should be possible to be displayed at the console! AVG: Reihenfolgeplanung
spaet_anf_dat	Latest start	date	Latest start (PDM field ID: ANR.DATSB)
spaet_anf_zeit	Latest start	integer	Latest start (PDM field ID: ANR.ZEISB)
spaet_end_dat	Latest end	date	Latest finish date (lat. finish date) Latest end AU: Basic date Otherwise: scheduling result; whether due date at the console can be positioned after the latest finish date of the AU, is defined in the setup (-> plausibility check) (PDM field ID: ANR.DATSE)
spaet_end_zeit	Latest end	integer	Latest finish date (lat. finish date) Latest end AU: Basic date Otherwise: scheduling result; whether due date at the console can be positioned after the latest finish date of the AU, is defined in the setup (-> plausibility check) (PDM field ID: ANR.ZEISE)
splitten	Splitting authorization	char(1)	V/M/N (splitting authorization) V = splitting is allowed for the complete number of machines in the group M = splitting is allowed for the max. number of machines, as stated in anz_split_masch N = cannot be split (PDM field ID: ANR.OPT:SPLIT)
splnr	Split number	char(10)	Split number; only filled if A_TYP = 'SPL' (PDM field ID: ANR.SPLNR)
szy_abw_proz	Cycle deviation [%]	decimal(8,3)	
term_anf_dat	Scheduled start time	date	Scheduled start time - from lead time scheduling (PDM field ID: ANR.DATTERMB)
term_anf_zeit	Scheduled start time	integer	Scheduled start time (PDM field ID: ANR.ZEITERMB)
term_end_dat	Scheduled end time	date	Scheduled end time - from lead time scheduling (PDM field ID: ANR.DATTERME)
term_end_zeit	Scheduled end time	integer	Scheduled end time (PDM field ID: ANR.ZEITERME)
terminieren	Indicator scheduling	char(1)	Indicator for scheduling (e.g. is set after the change of target data) (PDM field ID: ANR.OPT:TERM)

text_vorh	Long text available	char(1)	Indicator for "long text available" at the order or OP X = Yes T = long text is available " " = no long text available This indicator has to be set by HYINFO-BAPI.
transfer	Transfer by	char(10)	Transfer user, e.g. - SAP, PPS If the field is transferred (<> blank) TRANSFER_DATUM and TRANSFER_ZEIT have also to be set, otherwise the fields also remain empty. If the field is not transferred, but SAPSYS, the value entered there is also written in here. (PDM field ID: ANR.TRANSFER)
transfer_datum	Transfer date	date	Is assigned to DAT at Insert Date of the transfer (PDM field ID: ANR.TRANSFERDAT)
transfer_zeit	Transfer time	integer	Time of the transfer (PDM field ID: ANR.TRANSFERZEI)
transp_zeit	Current transport time	integer	Current transport time; is initially equal to the TRANSP_ZEIT_NORM and is possibly reduced by the reduction strategy. (PDM field ID: ANR.TPZ)
transp_zeit_kal	Transport time from transport matrix	integer	Derives from the respective value in the transport matrix (ADE_ORTSGRPWECHSEL): 0 = Gregorian calendar -1= Use shift calendar of origin machine (is transferred to planning component) > 0 = Shift model of the origin machine (NOT LEVEL 1) (PDM field ID: ANR.TPZ:KAL)
transp_zeit_min	Transport time minimal	integer	Transport time minimal Is determined from (ADE_ORTSGRPWECHSEL) (PDM field ID: ANR.TPZ:MIN)
transp_zeit_norm	Transport time normal	integer	Transport time normal Is determined from transport matrix (ADE_ORTSGRPWECHSEL) (PDM field ID: ANR.TPZ:NORM)
uagnr	Sub OP number	char(20)	Sub OP number (PDM field ID: ANR.UAGNR)
umrech_lief_nen	Conversion	integer	Conversion of base quantity -> delivery quantities (PDM field ID: ANR.UMRFAKTLI:N)
umrech_lief_zae	Conversion	integer	Conversion of base quantity --> delivery quantity unit (PDM field ID: ANR.UMRFAKTLI:Z)
umrech_pri_nen	Conversion	integer	Conversion prim -> BASIS (denominator) -> is taken over from the field DENOMINATOR in case of SAP standard interface (PDM field ID: ANR.UMRFAKTP:N)
umrech_pri_zae	Conversion	integer	Conversion prim. -> BASIS (numerator) -> is taken over from the field NOMINATOR in case of SAP standard interface (PDM field ID: ANR.UMRFAKTP:Z)
umrech_sek_nen	Conversion	integer	Conversion sec. -> BASIS (denominator) (PDM field ID: ANR.UMRFAKTS:N)
umrech_sek_zae	Conversion	integer	Conversion sec. -> BASIS (numerator) (PDM field ID: ANR.UMRFAKTS:Z)
umrech_ter_nen	Conversion	integer	Conversion tert. -> BASIS (denominator) (PDM field ID: ANR.UMRFAKTT:N)
umrech_ter_zae	Conversion	integer	Conversion tert. -> BASIS (numerator) (PDM field ID: ANR.UMRFAKTT:Z)
user_c_29	User field 29	char(1)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: opt_kz (PDM field ID: ANR.FU:29)
user_c_30	User field 30	char(1)	User-specific field (PDM field ID: ANR.FU:30)
user_c_31	User field 31	char(1)	User-specific field (PDM field ID: ANR.FU:31)

user_c_32	User field 32	char(1)	User-specific field (PDM field ID: ANR.FU:32)
user_c_33	User field 33	char(1)	User-specific field (PDM field ID: ANR.FU:33)
user_c_34	User field 34	char(1)	User-specific field (PDM field ID: ANR.FU:34)
user_c_35	User field 35	char(1)	User-specific field (PDM field ID: ANR.FU:35)
user_c_36	User field 36	char(1)	User-specific field (PDM field ID: ANR.FU:36)
user_c_37	User field 37	char(1)	User-specific field (PDM field ID: ANR.FU:37)
user_c_38	User field 38	char(1)	User-specific field (PDM field ID: ANR.FU:38)
user_c_39	User field 39	char(1)	User-specific field (PDM field ID: ANR.FU:39)
user_c_40	User field 40	char(1)	User-specific field (PDM field ID: ANR.FU:40)
user_c_41	User field 41	char(1)	User-specific field (PDM field ID: ANR.FU:41)
user_c_42	User field 42	char(1)	User-specific field (PDM field ID: ANR.FU:42)
user_c_43	User field 43	char(1)	User-specific field (PDM field ID: ANR.FU:43)
user_c_44	User field 44	char(1)	User-specific field (PDM field ID: ANR.FU:44)
user_c_45	User field 45	char(10)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: baugruppe (PDM field ID: ANR.FU:45)
user_c_46	User field 46	char(10)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: ident_kto1 (PDM field ID: ANR.FU:46)
user_c_47	User field 47	char(10)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: ident_kto2 (PDM field ID: ANR.FU:47)
user_c_48	User field 48	char(10)	User-specific field (PDM field ID: ANR.FU:48)
user_c_49	User field 49	char(10)	User-specific field (PDM field ID: ANR.FU:49)
user_c_50	User field 50	char(10)	User-specific field (PDM field ID: ANR.FU:50)
user_c_51	User field 51	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: neben3 (PDM field ID: ANR.FU:51)
user_c_52	User field 52	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: neben4 (PDM field ID: ANR.FU:52)
user_c_53	User field 53	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: formnr (PDM field ID: ANR.FU:53)

user_c_54	User field 54	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: mbez (PDM field ID: ANR.FU:54)
user_c_55	User field 55	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: txt1 (PDM field ID: ANR.FU:55)
user_c_56	User field 56	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: txt2 (PDM field ID: ANR.FU:56)
user_c_57	User field 57	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: txt3 (PDM field ID: ANR.FU:57)
user_c_58	User field 58	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: txt4 (PDM field ID: ANR.FU:58)
user_c_59	User field 59	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: txt5 (PDM field ID: ANR.FU:59)
user_c_60	User field 60	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand aus Feld: eigensft (PDM field ID: ANR.FU:60)
user_c_61	User field 61	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: opt_kriterium (PDM field ID: ANR.FU:61)
user_c_62	User field 62	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: kd_param5 (PDM field ID: ANR.FU:62)
user_c_63	User field 63	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: kd_param4 (PDM field ID: ANR.FU:63)
user_c_64	User field 64	char(20)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: kd_param3 (PDM field ID: ANR.FU:64)
user_c_65	User field 65	char(40)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: kd_param2 (PDM field ID: ANR.FU:65)
user_c_66	User field 66	char(40)	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: kd_param1 [1,40] (PDM field ID: ANR.FU:66)
user_code	User field key	char(8)	User field key Reference to the configuration of the user field key or its user fields in table HYD_USERFIELDCFG (PDM field ID: ANR.USERFLD)
user_d_01	User field 1	date	User-specific field (PDM field ID: ANR.FU:1)
user_d_02	User field 2	date	User-specific field (PDM field ID: ANR.FU:2)
user_d_03	User field 3	date	User-specific field (PDM field ID: ANR.FU:3)
user_d_04	User field 4	date	User-specific field (PDM field ID: ANR.FU:4)
user_d_05	User field 5	date	User-specific field (PDM field ID: ANR.FU:5)
user_d_06	User field 6	date	User-specific field (PDM field ID: ANR.FU:6)

user_f_23	User field 23	decimal(18,6)	User-specific field Rückmeldeschmittstelle (PDM field ID: ANR.FU:23)
user_f_24	User field 24	decimal(18,6)	User-specific field (PDM field ID: ANR.FU:24)
user_f_25	User field 25	decimal(18,6)	User-specific field (PDM field ID: ANR.FU:25)
user_f_26	User field 26	decimal(18,6)	User-specific field (PDM field ID: ANR.FU:26)
user_f_27	User field 27	decimal(18,6)	User-specific field (PDM field ID: ANR.FU:27)
user_f_28	User field 28	decimal(18,6)	User-specific field (PDM field ID: ANR.FU:28)
user_n_07	User field 7	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: parameter01 (PDM field ID: ANR.FU:7)
user_n_08	User field 8	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: parameter02 (PDM field ID: ANR.FU:8)
user_n_09	User field 9	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: parameter03 (PDM field ID: ANR.FU:9)
user_n_10	User field 10	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: cycle1 (PDM field ID: ANR.FU:10)
user_n_11	User field 11	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: cycle3 (PDM field ID: ANR.FU:11)
user_n_12	User field 12	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: cycle4 (PDM field ID: ANR.FU:12)
user_n_13	User field 13	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: vorgabe (PDM field ID: ANR.FU:13)
user_n_14	User field 14	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: mb_kz (PDM field ID: ANR.FU:14)
user_n_15	User field 15	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: analog1 (PDM field ID: ANR.FU:15)
user_n_16	User field 16	integer	User-specific field RW 7.1->7.2: transfer from table auftrags_bestand from field: sap_param03 (PDM field ID: ANR.FU:16)
user_n_17	User field 17	integer	User-specific field (PDM field ID: ANR.FU:17)
user_n_18	User field 18	integer	User-specific field (PDM field ID: ANR.FU:18)
user_n_19	User field 19	integer	User-specific field (PDM field ID: ANR.FU:19)
user_n_20	User field 20	integer	User-specific field (PDM field ID: ANR.FU:20)
user_n_21	User field 21	integer	User-specific field (PDM field ID: ANR.FU:21)
user_n_22	User field 22	integer	User-specific field (PDM field ID: ANR.FU:22)
verantw_bereich	Responsibility area	char(15)	Is referred to as responsibility area for the authorization; is filled with the value from plan_werk at the interface. (PDM field ID: ANR.VAB)

verarb_code	Processing code	char(6)	Table: ADE_VERARB_CODES Processing code (= SAP control key; 4-digit in SAP) (Does the processing code change when reassigning to another machine (group)?) (PDM field ID: ANR.VERARBCODE)
verarb_code_mod	Processing code mode	integer	It is recorded here which values in the order backlog and that are also in the processing code have been changed manually. 0 - no modification <> 0 - modified The logging is carried out "byte by byte": 1 overdelivery/underdelivery incl. reaction 2 external/internal processing 3 can be recorded 4 can be logged on simultaneously 5 can be split 6 serial number requirement 7 batch management requirement 8 sequencing list The indicator is also set if the respective value is transferred directly at the PPS interface.
verbrauch_art	Consumpt. type	char(2)	for future use
verweis	Reference	serial	--- (PDM field ID: ANR.VERWEIS)
vgw_01	Default value 1	decimal(18,6)	Default value 1 Vorgabewert 1 (PDM field ID: ANR.VGW01)
vgw_02	Default value 2	decimal(18,6)	Default value 2 (PDM field ID: ANR.VGW02)
vgw_03	Default value 3	decimal(18,6)	Default value 3 (PDM field ID: ANR.VGW03)
vgw_04	Default value 4	decimal(18,6)	Default value 4 (PDM field ID: ANR.VGW04)
vgw_05	Default value 5	decimal(18,6)	Default value 5 (PDM field ID: ANR.VGW05)
vgw_06	Default value 6	decimal(18,6)	Default value 6 (PDM field ID: ANR.VGW06)
vgw_07	Default value 7	decimal(18,6)	Default value 7 (PDM field ID: ANR.VGW07)
vgw_08	Default value 8	decimal(18,6)	Default value 8 (PDM field ID: ANR.VGW08)
vgw_09	Default value 9	decimal(18,6)	Default value 9 (PDM field ID: ANR.VGW09)
vgw_10	Default value 10	decimal(18,6)	Default value 10 (PDM field ID: ANR.VGW10)
vgw_code	Default value key	char(5)	Default value key (in SAP CHAR(4)) Table: HYD_USERFIELDCFG, Object VGW1 Note: are virtually like quick user fields (PDM field ID: ANR.VGWCODE)
vorgabeliste	Sequencing list	char(1)	Controls whether the OP is intended for the sequencing list at the terminal (must be seen together with the status) It can be selected at the console which items are supposed to be displayed. (PDM field ID: ANR.OPT:VLIST)
vorlaufzeit	Lead time	integer	An overlap can either be specified by a send-ahead quantity or by a lead time. Both parameters describe the offset of the predecessor to its successor. A lead time can also be negative, which means that the successor starts setting up before the predecessor. Attention: this is also to be taken into account in case of order networks. (PDM field ID: ANR.VLZ)

warte_zeit	Waiting time	integer	Current waiting time; is initially equal to the WARTE_ZEIT_NORM and is possibly reduced by the reduction strategy. (PDM field ID: ANR.WARTZ)
warte_zeit_expr	Formula	char(6)	If a waiting time that is bigger zero is set when transferring operations at the interface from SAP this waiting time is taken over. Otherwise, the default value (-> template) is used. (PDM field ID: ANR.WARTZ:EXPR)
warte_zeit_min	Waiting time minimal	integer	Waiting time minimal (PDM field ID: ANR.WARTZ:MIN)
warte_zeit_mod	Calculation mode	char(1)	Calculated F = via formula M = manually (by user) (PDM field ID: ANR.WARTZ:MOD)
warte_zeit_norm	Waiting time normal	integer	Waiting time normal; is not changed by reduction (PDM field ID: ANR.WARTZ:NORM)
weitgabemenge	Minimum send-ahead quantity	decimal(18,6)	Minimum send-ahead quantity, which has at least to be produced during the operation in order that the following OP is actually able to start. Is kept in the base quantity unit. Synonym: Minimum send-ahead quantity Attention: is also to be taken into account for order networks --> is kept in a redundant way in ADE_AUFTRAGSNETZE. (PDM field ID: ANR.WEIGMENGE)
wpkz	Deletion flag	char(1)	Deletion flag When setting the indicator, the indicator "VORGABELISTE" (see below) and ERFASSBAR are set to "N". -> is handed down to the OPs if set in the order header (AU). If the indicator is reset VORGABELISTE and ERFASSBAR are redetermined in accordance with order type or processing code

2.25. auftrags_leistung

Table name: auftrags_leistung		Product: BDE	
Archive table: a_auftrags_leistun		Reload table: r_auftrags_leistun	
Designation: Order activities			
Column name	Column designation	Type	Description
ab_verweis		integer	Reference to auftrags_bestand.verweis
auftrag_art		char(5)	---
auftrag_nr		char(40)	---
soll_bmk01	Target RPA01	integer	Target activity for RPA01 (PDM field ID: ANR.BMK01)
soll_bmk01_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK01:MOD)
soll_bmk02	Target RPA02	integer	Target activity for RPA02 (PDM field ID: ANR.BMK02)
soll_bmk02_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK02:MOD)
soll_bmk03	Target RPA03	integer	Target activity for RPA03 (PDM field ID: ANR.BMK03)
soll_bmk03_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK03:MOD)
soll_bmk04	Target RPA04	integer	Target activity for RPA04 (PDM field ID: ANR.BMK04)
soll_bmk04_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK04:MOD)
soll_bmk05	Target RPA05	integer	Target activity for RPA05 (PDM field ID: ANR.BMK05)
soll_bmk05_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK05:MOD)
soll_bmk06	Target RPA06	integer	Target activity for RPA06 (PDM field ID: ANR.BMK06)
soll_bmk06_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK06:MOD)
soll_bmk07	Target RPA07	integer	Target activity RPA07 (PDM field ID: ANR.BMK07)
soll_bmk07_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK07:MOD)
soll_bmk08	Target RPA08	integer	Target activity for RPA08 (PDM field ID: ANR.BMK08)

soll_bmk08_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK08:MOD)
soll_bmk09	Target RPA09	integer	Target activity RPA09 (PDM field ID: ANR.BMK09)
soll_bmk09_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK09:MOD)
soll_bmk10	Target RPA10	integer	Target activity for RPA10 (PDM field ID: ANR.BMK10)
soll_bmk10_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK10:MOD)
soll_bmk11	Target RPA11	integer	Target activity for RPA11 (PDM field ID: ANR.BMK11)
soll_bmk11_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK11:MOD)
soll_bmk12	Target RPA12	integer	Target activity for RPA12 (PDM field ID: ANR.BMK12)
soll_bmk12_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.BMK12:MOD)
soll_dauer	Cycle time	integer	Cycle time (PDM field ID: ANR.DAUER)
soll_dauer_mod	Calculated	char(1)	Target cycle time calculated F= formula M= manual (PDM field ID: ANR.DAUER:MOD)
soll_lst01	Target activity 1	decimal(18,6)	Target activity 1 (PDM field ID: ANR.LST01)
soll_lst01_einh		char(3)	Unit of the target activity 1
soll_lst01_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST01:MOD)
soll_lst02	Target activity 2	decimal(18,6)	Target activity 2 (PDM field ID: ANR.LST02)
soll_lst02_einh		char(3)	Unit of the target activity 2
soll_lst02_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST02:MOD)
soll_lst03	Target activity 3	decimal(18,6)	Target activity 3 (PDM field ID: ANR.LST03)
soll_lst03_einh		char(3)	Unit of the target activity 3
soll_lst03_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST03:MOD)
soll_lst04	Target activity 4	decimal(18,6)	Target activity 4 (PDM field ID: ANR.LST04)

soll_lst04_einh		char(3)	Unit of the target activity 4
soll_lst04_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST04:MOD)
soll_lst05	Target activity 5	decimal(18,6)	Target activity 5 (PDM field ID: ANR.LST05)
soll_lst05_einh		char(3)	Unit of the target activity 5
soll_lst05_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST05:MOD)
soll_lst06	Target activity 6	decimal(18,6)	Target activity 6 (PDM field ID: ANR.LST06)
soll_lst06_einh		char(3)	Unit of the target activity 6
soll_lst06_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST06:MOD)
soll_lst07	Target activity 7	decimal(18,6)	Target activity 7 (PDM field ID: ANR.LST07)
soll_lst07_einh		char(3)	Unit of the target activity 7
soll_lst07_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST07:MOD)
soll_lst08	Target activity 8	decimal(18,6)	Target activity 8 (PDM field ID: ANR.LST08)
soll_lst08_einh		char(3)	Unit of the target activity 8
soll_lst08_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST08:MOD)
soll_lst09	Target activity 9	decimal(18,6)	Target activity 9 (PDM field ID: ANR.LST09)
soll_lst09_einh		char(3)	Unit of the target activity 9
soll_lst09_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST09:MOD)
soll_lst10	Target activity 10	decimal(18,6)	Target activity 10 (PDM field ID: ANR.LST10)
soll_lst10_einh		char(3)	Unit of the target activity10
soll_lst10_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.LST10:MOD)
soll_p_bmk01	Target activity for P-BMK01	integer	Target activity for P-BMK01 (PDM field ID: ANR.PBMK01)
soll_p_bmk01_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK01:MOD)
soll_p_bmk02	Target activity for P-BMK02	integer	Target activity for P-BMK02 (PDM field ID: ANR.PBMK02)

soll_p_bmk02_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK02:MOD)
soll_p_bmk03	Target activity for P-BMK03	integer	Target activity for P-BMK03 (PDM field ID: ANR.PBMK03)
soll_p_bmk03_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK03:MOD)
soll_p_bmk04	Target activity for P-BMK04	integer	Target activity for P-BMK04 (PDM field ID: ANR.PBMK04)
soll_p_bmk04_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK04:MOD)
soll_p_bmk05	Target activity for P-BMK05	integer	Target activity for P-BMK05 (PDM field ID: ANR.PBMK05)
soll_p_bmk05_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK05:MOD)
soll_p_bmk06	Target activity for P-BMK06	integer	Target activity for P-BMK06 (PDM field ID: ANR.PBMK06)
soll_p_bmk06_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK06:MOD)
soll_p_bmk07	Target activity P-BMK7	integer	Target activity for P-BMK07 (PDM field ID: ANR.PBMK07)
soll_p_bmk07_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK07:MOD)
soll_p_bmk08	Target activity for P-BMK08	integer	Target activity for P-BMK08 (PDM field ID: ANR.PBMK08)
soll_p_bmk08_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK08:MOD)
soll_p_bmk09	Target activity for P-BMK09	integer	Target activity for P-BMK09 (PDM field ID: ANR.PBMK09)
soll_p_bmk09_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK09:MOD)
soll_p_bmk10	Target activity P-BMK10	integer	Target activity for P-BMK10 (PDM field ID: ANR.PBMK10)
soll_p_bmk10_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK10:MOD)
soll_p_bmk11	Target activity for P-BMK11	integer	Target activity for P-BMK11 (PDM field ID: ANR.PBMK11)
soll_p_bmk11_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK11:MOD)

soll_p_bmk12	Target activity for P-BMK12	integer	Target activity for P-BMK12 (PDM field ID: ANR.PBMK12)
soll_p_bmk12_mod	Calculated	char(1)	Calculated F = via formula: the formula is defined in the activity code M = manually (by the user) (PDM field ID: ANR.PBMK12:MOD)
soll_p_dauer	Target activity for the labor utilizatio	integer	SUM of SOLL_P_BMK01 ... SOLL_P_BMK12 Target activity for the labor utilization (PDM field ID: ANR.PDAUER)
soll_p_dauer_mod	Calculated	char(1)	Target Personnel Duration F = Formula M= Manual (PDM field ID: ANR.PDAUER:MOD)

2.26. auftrags_zusatz

Table name: auftrags_zusatz		Product: BDE	
Archive table: a_auftrags_zusatz		Reload table: r_auftrags_zusatz	
Designation: Order header - additional data			
Column name	Column designation	Type	Description
ab_verweis		integer	Reference to auftrags_bestand.verweis
arbplan_version	Work plan version	char(12)	SAP: change number (PDM field ID: ANR.APVER)
auftrag_art		char(5)	RW 7.1->7.2: transfer from table a_kopf_best from field: auftrag_art
auftrag_nr		char(40)	RW 7.1->7.2: transfer from table a_kopf_best from field: auftrag_nr
auftragsgruppe	Order group	char(4)	ADE_AUFTRAGSGRUPPEN SAP: Production scheduler; CHAR(3) (PDM field ID: ANR.AUGRP)
auftragsindex	Order index	decimal(18,6)	Valid range of values (-999.9 to +999.9) (PDM field ID: ANR.AUIDX)
chargennr	ERP batch	char(20)	Reserved Batch for the order (e.g. from SAP) (PDM field ID: ANR.CNR)
disponent	MRP controller	char(10)	SAP: CHAR(3) (PDM field ID: ANR.DISP)
dlz_minimal	Lead time min.	integer	Minimal lead time (of the order) Is only determined at the first lead time scheduling: always: consideration of the shift calendar minimal: 100% reduced, always due to backward scheduling (as in case of a forward scheduling the material is in stock) RW 7.1->7.2: transfer from table a_kopf_best from field: dlzeit (PDM field ID: ANR.DLZ:MIN)
dlz_plan	Lead time	integer	Planned lead time due to scheduling or planning corresponds to "forecast lead time of the order" RW 7.1->7.2: transfer from table a_kopf_best from field: dlzeit (PDM field ID: ANR.DLZ)
fert_version	Production version	char(10)	Production version from PPS (SAP) -> serial production/planned orders (PDM field ID: ANR.FERTVER)
kalk_kost_lohn	Planned value	decimal(18,6)	Planned value RW 7.1->7.2: tranfer from table a_kopf_best from field: lohn_kosten (PDM field ID: ANR.KLKK:L)
kalk_kost_masch	Planned value	decimal(18,6)	Planned value (PDM field ID: ANR.KLKK:MNR)
kalk_kost_mat	Planned value	decimal(18,6)	Planned value RW 7.1->7.2: tranfer from table a_kopf_best from field: kum_mat_wert (PDM field ID: ANR.KLKK:MAT)
kalk_kost_sonst	Planned value	decimal(18,6)	Planned value (PDM field ID: ANR.KLKK:SONST)
kd_auftrag	Sales order	char(40)	Sales order RW 7.1->7.2: transfer from table a_kopf_best from field: kunden_auftrag_nr (PDM field ID: ANR.KDAUNR)

kd_auftragpos	Sales order item	char(20)	Sales order item SAP: NUMC(6) RW 7.1->7.2: transfer from table a_kopf_best from field: kd_auftrag_pos_c (PDM field ID: ANR.KDAUPOS)
kostentraeger	Cost object	char(40)	RW 7.1->7.2: transfer from table a_kopf_best from field: kostentraeger (PDM field ID: ANR.KTR)
lbez_id	Closed loop	char(15)	 (PDM field ID: ANR.KBN:LBEZID)
mat_wert	Value of materials	decimal(18,6)	"Which value does the produced finished material has" per 1 base quantity unit (PDM field ID: ANR.MATWERT:GUT)
plan_auftrag	Planned order	char(40)	SAP: Planned order (for information) RW 7.1->7.2: transfer from table a_kopf_best from field: projekt_nr (PDM field ID: ANR.PLANAUNR)
proben_typ	Sample category	char(1)	for CBM/ CAQ RW 7.1->7.2: transfer from table a_kopf_best from field: proben_typ (PDM field ID: ANR.PPKTTYP)
projekt_nr	Project number	char(25)	Project number SAP: PSP element RW 7.1->7.2: transfer from table a_kopf_best from field: projekt_nr (PDM field ID: ANR.PRJNR)
prueflosnr	Inspection batch number	char(20)	Inspection batch number RW 7.1->7.2: transfer from table a_kopf_best from field: sap_prueflos (PDM field ID: ANR.PCNR)
red_strategie	Reduction strategy	char(2)	Reduction strategy (PDM field ID: ANR.REDSTRAT)
red_stufe	Reduction level	smallint	Current reduction level, i.e. it has so far been reduced up to this level SAP: NUMC 1 (PDM field ID: ANR.REDSTUFE)
schrott_wert	Scrap value	decimal(18,6)	Scrap value per base quantity unit (PDM field ID: ANR.MATWERT:AUS)
steuerrezept		char(10)	Control recipe number from PPS (SAP: <Tab>.CRID, char 18) There is a so-called control recipe number in the PP-PI. This number can be regarded as a synonym for the order number. To anticipate the future PI projects it is certainly reasonable to provide them also in the order header as far as possible. (PDM field ID: ANR.STRGREZ)
stueli_version	Bill of material version	char(12)	SAP: change number (PDM field ID: ANR.SLVER)
term_art	Scheduling type	char(1)	Scheduling type (forward, backward, new) RW 7.1->7.2: transfer from table a_kopf_best from field: termricht (PDM field ID: ANR.TERMART)

2.27. bedienpos

Table name: bedienpos		Product: BDE	
Designation: Operator positions		Description: The operator positions allowed per machine are defined in this table. When employees are logged on to the terminal it is required to enter the operator position as well (if configured in the dialog).	
Column name	Column designation	Type	Description
anzahl	Number of possible logons of staff to th	integer	Number of possible logons of staff to this operator position (PDM field ID: BPOS.ANZ)
auftrag_art		char(5)	---
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing time	integer	Last editing time
bedienpos		char(3)	Free (PDM field ID: BPOS.BEDIENPOS)
bpoan	Operator position	char(10)	Operator position (PDM field ID: BPOS.BPOS)
funktion		char(8)	Free (PDM field ID: BPOS.FKT)
kurztext	Short description of the operator positi	char(8)	Short description of the operator position (PDM field ID: BPOS.BEZEK)
langtext	Detailed description of the operator pos	char(25)	Detailed description of the operator position (PDM field ID: BPOS.BEZL)
masch_nr	Machine	char(20)	Machine (PDM field ID: BPOS.MNR)

2.28. bm_konten

Table name: bm_konten		Product: BDE	
Designation: Resource performance accounts		Description: Resource performance accounts (RPA) consist of exactly 12 time accounts, which are processed by the system in relation operation, workplace/machine and resource (e.g. tool). They are used for classified time recording, as is customary in REFA, and can be used in various reports and evaluations. Depending on the current status of the workplace/machine, the time is charged to the resource performance account that was defined for this particular status during system configuration. # Special remarks The resource performance accounts are predefined by MPDV and the customer may only change them after having contacted MPDV and before any data acquisition is done. The following restrictions are applicable: - Productive times ("production") are always posted to RPA 11. - Neutral times (e.g. no-shift times like weekends) are always posted to RPA 12. # Key nummer # Connections to other tables Each machine status in database tabel stoer_tabelle - (exept status 20000 and 30000 - must be assigned to a RPA: stoer_tabelle.bmk = bm_konten.kuerzel RPA number are stored in the workplace-related result record: ereignis.bmktonr = bm_konten.nummer	
Column name	Column designation	Type	Description
farbe	Color	integer	Reserved for future use.
kuerzel	Abbreviation	char(3)	Abbreviation for the RPA, e.g. HNZ (MUT). Must be unique. (PDM field ID: BMK.BEZX)
nummer	Number	smallint	Unique, consecutive number (1...12) (PDM field ID: BMK.BMKNR)
txt	Text	char(20)	Plain text of resource performance account (PDM field ID: BMK.BEZX)

2.29. event_adea

Table name: event_adea		Product: BDE	
Archive table: a_event_adea		Reload table: r_event_adea	
Designation: Order-related events			
Column name	Column designation	Type	Description
artikel		char(40)	Internal usage
attribut_1		char(20)	PZE : clocking attribute
attribut_2		char(20)	PZE : time type: W(inter), S(ummer)
attribut_3		char(30)	Bill of material item (CE_AN) or batch status (CE_AB)
attribut_4		char(20)	---
attribut_5		char(20)	Current batch (at event CA_AB or C_AB)
attribut_6		char(10)	LLE: Wage type ID (A_AN)
attribut_7		char(10)	for internal use
attribut_8		char(20)	for internal use
attribut_9		char(30)	for internal use
auftrag_nr		char(40)	Allocated according to event
automatisch		char(1)	J: automatic event, e.g. at the change of shifts
bearb		char(10)	Last editor
bearb_date		date	Last editing date
bearb_time		integer	Last editing time
bpos		char(10)	Operator position at event P_AN
buch_dat		date	Posting time - Currently not assigned
buch_zeit		integer	Posting time - Currently not assigned
buendelnr		char(40)	otherwise free (e.g. COP number)
bzw		char(10)	Booking requirement J/N
chargen_nr		char(20)	Allocated according to event
datum		date	Log date
dialog		char(10)	Dialog identification by which the event was triggered
dlg_data_verweis		integer	Reference to additional data record an event_dlg_data
dlg_id		char(10)	Dialog reference
dllosnr		char(20)	Run-through batch number
editierbar		char(1)	J = Event may be maintained N = Event must not be maintained, e.g. master of a COP or blocked by changing the log record
einheit_1		char(3)	Unit of respective quantity
einheit_10		char(3)	Unit of respective quantity
einheit_11		char(3)	Unit of respective quantity
einheit_12		char(3)	Unit of respective quantity
einheit_13		char(3)	Unit of respective quantity
einheit_14		char(3)	Unit of respective quantity
einheit_15		char(3)	Unit of respective quantity
einheit_16		char(3)	Unit of respective quantity

ein_h_17		char(3)	Unit of respective quantity
ein_h_18		char(3)	Unit of respective quantity
ein_h_19		char(3)	Unit of respective quantity
ein_h_2		char(3)	Unit of respective quantity
ein_h_20		char(3)	Unit of respective quantity
ein_h_3		char(3)	Unit of respective quantity
ein_h_4		char(3)	Unit of respective quantity
ein_h_5		char(3)	Unit of respective quantity
ein_h_6		char(3)	Unit of respective quantity
ein_h_7		char(3)	Unit of respective quantity
ein_h_8		char(3)	Unit of respective quantity
ein_h_9		char(3)	Unit of respective quantity
ereignis		char(10)	Event type
erfass_1		char(1)	free
erfass_10		char(1)	free
erfass_11		char(1)	free
erfass_12		char(1)	free
erfass_13		char(1)	free
erfass_14		char(1)	free
erfass_15		char(1)	free
erfass_16		char(1)	free
erfass_17		char(1)	free
erfass_18		char(1)	free
erfass_19		char(1)	free
erfass_2		char(1)	free
erfass_20		char(1)	free
erfass_3		char(1)	free
erfass_4		char(1)	free
erfass_5		char(1)	free
erfass_6		char(1)	free
erfass_7		char(1)	free
erfass_8		char(1)	free
erfass_9		char(1)	free
erfass_dat		date	Recording time
erfass_zeit		integer	Recording time
erw_status_01		char(1)	for internal use
erw_status_02		char(1)	for internal use
erw_status_03		char(1)	for internal use
erw_status_04		char(1)	for internal use
erw_status_05		char(1)	for internal use
erw_status_06		char(1)	for internal use
firma_1		char(8)	Company/plant number 1
firma_2		char(8)	status of the operation (A..AN)
grund_1		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')

grund_10		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_11		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_12		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_13		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_14		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_15		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_16		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_17		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_18		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_19		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_2		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS'))
grund_20		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_3		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_4		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')

grund_5		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_6		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_7		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_8		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_9		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
herkunft		char(1)	"Blank": original data record from the collection E: manually generated data record L: manually generated data record, for cancellation only O: original data record if maintained X: event is blocked; no posting effected as plausibility error occurred
info_01		integer	The quantity group "n" is determined from the value of the identifier EGR:GUT#n for the dialog A_TR in case of multiple, automatical quantity logons
info_02		integer	free
info_03		integer	HYD-AEV: Error code for rejected dialog logons in the posting
ist_lst_01		decimal(18,6)	Recorded activity 01
ist_lst_02		decimal(18,6)	Recorded activity 02
ist_lst_03		decimal(18,6)	Recorded activity 03
ist_lst_04		decimal(18,6)	Recorded activity 04
ist_lst_05		decimal(18,6)	Recorded activity 05
ist_lst_06		decimal(18,6)	Recorded activity 06
ist_lst_07		decimal(18,6)	Recorded activity 07
ist_lst_08		decimal(18,6)	Recorded activity 08
ist_lst_09		decimal(18,6)	Recorded activity 09
ist_lst_10		decimal(18,6)	Recorded activity 10
ist_lst_11		decimal(18,6)	Recorded activity 11
ist_lst_12		decimal(18,6)	Recorded activity 12
ist_lst_13		decimal(18,6)	Recorded activity 13
ist_lst_14		decimal(18,6)	Recorded activity 14
ist_lst_15		decimal(18,6)	Recorded activity 15
ist_lst_16		decimal(18,6)	Recorded activity 16
ist_lst_17		decimal(18,6)	Recorded activity 17
ist_lst_18		decimal(18,6)	Recorded activity 18
ist_lst_19		decimal(18,6)	Recorded activity 19
ist_lst_20		decimal(18,6)	Recorded activity 20
ist_lst_einh_01		char(3)	Unit of recorded activity 01
ist_lst_einh_02		char(3)	Unit of recorded activity 02
ist_lst_einh_03		char(3)	Unit of recorded activity 03

ist_lst_einh_04		char(3)	Unit of recorded activity 04
ist_lst_einh_05		char(3)	Unit of recorded activity 05
ist_lst_einh_06		char(3)	Unit of recorded activity 06
ist_lst_einh_07		char(3)	Unit of recorded activity 07
ist_lst_einh_08		char(3)	Unit of recorded activity 08
ist_lst_einh_09		char(3)	Unit of recorded activity 09
ist_lst_einh_10		char(3)	Unit of recorded activity 10
ist_lst_einh_11		char(3)	Unit of recorded activity 11
ist_lst_einh_12		char(3)	Unit of recorded activity 12
ist_lst_einh_13		char(3)	Unit of recorded activity 13
ist_lst_einh_14		char(3)	Unit of recorded activity 14
ist_lst_einh_15		char(3)	Unit of recorded activity 15
ist_lst_einh_16		char(3)	Unit of recorded activity 16
ist_lst_einh_17		char(3)	Unit of recorded activity 17
ist_lst_einh_18		char(3)	Unit of recorded activity 18
ist_lst_einh_19		char(3)	Unit of recorded activity 19
ist_lst_einh_20		char(3)	Unit of recorded activity 20
ist_lst_typ_01		char(10)	Type of recorded activity 01
ist_lst_typ_02		char(10)	Type of recorded activity 02
ist_lst_typ_03		char(10)	Type of recorded activity 03
ist_lst_typ_04		char(10)	Type of recorded activity 04
ist_lst_typ_05		char(10)	Type of recorded activity 05
ist_lst_typ_06		char(10)	Type of recorded activity 06
ist_lst_typ_07		char(10)	Type of recorded activity 07
ist_lst_typ_08		char(10)	Type of recorded activity 08
ist_lst_typ_09		char(10)	Type of recorded activity 09
ist_lst_typ_10		char(10)	Type of recorded activity 10
ist_lst_typ_11		char(10)	Type of recorded activity 11
ist_lst_typ_12		char(10)	Type of recorded activity 12
ist_lst_typ_13		char(10)	Type of recorded activity 13
ist_lst_typ_14		char(10)	Type of recorded activity 14
ist_lst_typ_15		char(10)	Type of recorded activity 15
ist_lst_typ_16		char(10)	Type of recorded activity 16
ist_lst_typ_17		char(10)	Type of recorded activity 17
ist_lst_typ_18		char(10)	Type of recorded activity 18
ist_lst_typ_19		char(10)	Type of recorded activity 19
ist_lst_typ_20		char(10)	Type of recorded activity 20
karenz		char(1)	P = waiting period of personnel M = waiting period of machines
klasse		char(1)	A: operation-related message
lohnart		char(4)	LLE wage type
lpkz		char(10)	Wage premium indicator
masch_nr		char(20)	Allocated according to event

menge_1		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_10		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_11		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_12		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_13		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_14		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_15		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_16		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_17		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_18		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap

menge_19		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_2		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_20		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_3		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_4		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_5		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_6		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_7		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_8		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_9		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
offline_kz		char(1)	J: collected offline by the terminal
org_verweis		integer	Reference to a correction data record

p_divisor		decimal(18,6)	Recorded divisor
p_teiligkeit		decimal(18,6)	Recorded partitioning
person_nr		char(10)	Allocated according to event
pggruppe		char(20)	Allocated according to event
pmk		char(1)	Memorize person J/N
prgrp		char(10)	STD-LLE: wage/premium group LPGRP
prioritaet		smallint	Indication of the priority in case of simultaneous events (1 = highest priority)
pze_erzeugt		char(1)	"K" =BDE event was generated by PZE clock-in "G" =BDE event was generated by PZE clock-out
rest_lst_01		decimal(18,6)	Remainder recorded activity 1
rest_lst_02		decimal(18,6)	Remainder of recorded activity 2
rest_lst_03		decimal(18,6)	Remainder recorded activity 3
rest_lst_04		decimal(18,6)	Remainder of recorded activity 4
rest_lst_05		decimal(18,6)	Remainder of recorded activity 5
rest_lst_06		decimal(18,6)	Remainder of recorded activity 6
rest_lst_07		decimal(18,6)	Remainder of recorded activity 7
rest_lst_08		decimal(18,6)	Remainder of recorded activity 8
rest_lst_09		decimal(18,6)	Remainder of recorded activity 9
rest_lst_10		decimal(18,6)	Remainder of recorded activity 10
rest_lst_11		decimal(18,6)	Remainder of recorded activity 11
rest_lst_12		decimal(18,6)	Remainder of recorded activity 12
rest_lst_13		decimal(18,6)	Remainder of recorded activity 13
rest_lst_14		decimal(18,6)	Remainder of recorded activity 14
rest_lst_15		decimal(18,6)	Remainder of recorded activity 15
rest_lst_16		decimal(18,6)	Remainder of recorded activity 16
rest_lst_17		decimal(18,6)	Remainder of recorded activity 17
rest_lst_18		decimal(18,6)	Remainder of recorded activity 18
rest_lst_19		decimal(18,6)	Remainder of recorded activity 19
rest_lst_20		decimal(18,6)	Remainder of recorded activity 20
rest_lst_einh_01		char(3)	Remainder of the unit of recorded activity 1
rest_lst_einh_02		char(3)	Remainder of the unit of recorded activity 2
rest_lst_einh_03		char(3)	Remainder of the unit of recorded activity 3
rest_lst_einh_04		char(3)	Remainder of the unit of recorded activity 4
rest_lst_einh_05		char(3)	Remainder of the unit of recorded activity 5
rest_lst_einh_06		char(3)	Remainder of the unit of recorded activity 6
rest_lst_einh_07		char(3)	Remainder of the unit of recorded activity 7
rest_lst_einh_08		char(3)	Remainder of the unit of recorded activity 8
rest_lst_einh_09		char(3)	Remainder of the unit of recorded activity 9
rest_lst_einh_10		char(3)	Remainder of the unit of recorded activity 10
rest_lst_einh_11		char(3)	Remainder of the unit of recorded activity 11
rest_lst_einh_12		char(3)	Remainder of the unit of recorded activity 12
rest_lst_einh_13		char(3)	Remainder of the unit of recorded activity 13
rest_lst_einh_14		char(3)	Remainder of the unit of recorded activity 14
rest_lst_einh_15		char(3)	Remainder of the unit of recorded activity 15
rest_lst_einh_16		char(3)	Remainder of the unit of recorded activity 16
rest_lst_einh_17		char(3)	Remainder of the unit of recorded activity 17

rest_lst_einh_18		char(3)	Remainder of the unit of recorded activity 18
rest_lst_einh_19		char(3)	Remainder of the unit of recorded activity 19
rest_lst_einh_20		char(3)	Remainder of the unit of recorded activity 20
rest_lst_typ_01		char(10)	Remainder of the type of recorded activity 01
rest_lst_typ_02		char(10)	Remainder of the type of recorded activity 02
rest_lst_typ_03		char(10)	Remainder of the type of recorded activity 03
rest_lst_typ_04		char(10)	Remainder of the type of recorded activity 04
rest_lst_typ_05		char(10)	Remainder of the type of recorded activity 05
rest_lst_typ_06		char(10)	Remainder of the type of recorded activity 06
rest_lst_typ_07		char(10)	Remainder of the type of recorded activity 07
rest_lst_typ_08		char(10)	Remainder of the type of recorded activity 08
rest_lst_typ_09		char(10)	Remainder of the type of recorded activity 09
rest_lst_typ_10		char(10)	Remainder of the type of recorded activity 10
rest_lst_typ_11		char(10)	Remainder of the type of recorded activity 11
rest_lst_typ_12		char(10)	Remainder of the type of recorded activity 12
rest_lst_typ_13		char(10)	Remainder of the type of recorded activity 13
rest_lst_typ_14		char(10)	Remainder of the type of recorded activity 14
rest_lst_typ_15		char(10)	Remainder of the type of recorded activity 15
rest_lst_typ_16		char(10)	Remainder of the type of recorded activity 16
rest_lst_typ_17		char(10)	Remainder of the type of recorded activity 17
rest_lst_typ_18		char(10)	Remainder of the type of recorded activity 18
rest_lst_typ_19		char(10)	Remainder of the type of recorded activity 19
rest_lst_typ_20		char(10)	Remainder of the type of recorded activity 20
sig_knr1		char(10)	
sig_knr2		char(10)	
sig_name1		char(40)	
sig_name2		char(40)	
sig_pnr1		char(10)	
sig_pnr2		char(10)	
sig_type1		char(20)	
sig_type2		char(20)	
soll_te		decimal(18,6)	Premium target TE
soll_teb		decimal(18,6)	Premium target TEB
soll_tr		decimal(18,6)	Premium target TR
stationsnr		integer	free
status_1		integer	Machine status, termination reason, partitioning or target cycle Duration at event deduction or overtime at event overtime
status_2		integer	---
status_3		integer	---
szenario_nr		integer	for future use relevant for event maintenance
terminal_nr		smallint	User who has generated the data record

typ_1		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired ...
typ_10		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_11		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_12		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_13		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_14		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired

typ_15		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_16		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_17		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_18		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_19		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_2		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_20		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired

typ_3		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_4		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_5		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_6		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_7		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_8		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_9		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
umref		decimal(18,6)	Conversion factor for retrograde posting

utc_ts		datetime	
verarb_1		char(1)	Processing PZE
verarb_2		char(1)	OP status at the beginning of the shift (L = running/F = autom. interrupted)
verarb_3		char(1)	Decision requirement J/N
verarb_4		char(1)	HYD-AEV: A = indicator for automatically generated dialogs; e.g. from PZE/ADE comparison
verarb_mde		char(1)	Processing MDE (postprocessing of workplace-related result record messages)
verbuch_kz		char(2)	Update indicator, e.g. "ST" = COP at the terminal "SK"= COP at the console "SB" = Beginning of shift, "SE" = End of shift "W" = wintertime (PZE) "S" = summertime (PZE)
verweis		serial	Distinct reference of the data record
verweis_b1		integer	Reference to the operation-related result record or clocking record
verweis_b2		integer	Reference to a 2nd clocking record
zeit		integer	Log time

2.30. event_ade

Table name: event_ade		Product: BDE	
Archive table: a_event_ade		Reload table: r_event_ade	
Designation: Personal events			
Column name	Column designation	Type	Description
artikel		char(40)	---
attribut_1		char(20)	PZE : clocking attribute (PDM field ID: EREIGADEP.ATTR:1 (ZUSCHL.BEARB:SIGN))
attribut_2		char(20)	STD: wage/premium indicator at event P_AN (LPKZ) PZE : time type: W(inter), S(ummer) LLE bonuses: premium group LEISTGRP (PDM field ID: EREIGADEP.ATTR:2 (ZUSCHL.LEISTGRP))
attribut_3		char(30)	STD : Operator position at event P_AN
attribut_4		char(20)	---
attribut_5		char(20)	free
attribut_6		char(10)	LLE wage type
attribut_7		char(10)	LLE premium group LPGRP
attribut_8		char(20)	free
attribut_9		char(30)	free
auftrag_nr		char(40)	allocated to the order number according to the event (PDM field ID: EREIGADEP.ANR (ZUSCHL.ANR))
automatisch		char(1)	J: Automatic event, e.g. at the change of shifts
bearb		char(10)	Last editor
bearb_date		date	Last editing date
bearb_time		integer	Last editing time
bpos		char(10)	Operator position
buch_dat		date	Posting date
buch_zeit		integer	Posting time
buendelnr		char(40)	otherwise free (e.g. COP number)
bzw		char(10)	Booking requirement
chargen_nr		char(20)	allocated according to the event
datum		date	Log date (PDM field ID: EREIGADEP.DAT (ZUSCHL.DAT))
dialog		char(10)	Dialog identification by means of which the event was triggered Supplements: Not relevant (PDM field ID: EREIGADEP.DLG)
dlg_data_verweis		integer	Reference to the additional dialog data
dlg_id		char(10)	Dialog reference
dilosnr		char(20)	Run-through batch number
editierbar		char(1)	J = Event may be maintained N= Event must not be maintained, e.g. master of a COP or blocked by changing the log record
einheit_1		char(3)	Unit of respective quantity
einheit_10		char(3)	fUnit of respective quantity
einheit_11		char(3)	Unit of respective quantity

ein_h_12		char(3)	Unit of respective quantity
ein_h_13		char(3)	Unit of respective quantity
ein_h_14		char(3)	Unit of respective quantity
ein_h_15		char(3)	Unit of respective quantity
ein_h_16		char(3)	Unit of respective quantity
ein_h_17		char(3)	Unit of respective quantity
ein_h_18		char(3)	freeUnit of respective quantity
ein_h_19		char(3)	Unit of respective quantity
ein_h_2		char(3)	Unit of respective quantity
ein_h_20		char(3)	Unit of respective quantity
ein_h_3		char(3)	Unit of respective quantity
ein_h_4		char(3)	Unit of respective quantity
ein_h_5		char(3)	Unit of respective quantity
ein_h_6		char(3)	Unit of respective quantity
ein_h_7		char(3)	Unit of respective quantity
ein_h_8		char(3)	Unit of respective quantity
ein_h_9		char(3)	freeUnit of respective quantity
ereignis		char(10)	Event type P_AN/P_AB Supplements: P_ZUS (PDM field ID: EREIGADEP.EREIG (ZUSCHL: Fix))
erfass_1		char(1)	free
erfass_10		char(1)	free
erfass_11		char(1)	free
erfass_12		char(1)	free
erfass_13		char(1)	free
erfass_14		char(1)	free
erfass_15		char(1)	free
erfass_16		char(1)	free
erfass_17		char(1)	free
erfass_18		char(1)	free
erfass_19		char(1)	free
erfass_2		char(1)	free
erfass_20		char(1)	free
erfass_3		char(1)	free
erfass_4		char(1)	free
erfass_5		char(1)	free
erfass_6		char(1)	free
erfass_7		char(1)	free
erfass_8		char(1)	free
erfass_9		char(1)	free
erfass_dat		date	Date of collection
erfass_zeit		integer	Time of collection
erw_status_01		char(1)	Bonuses: Subject to permit "J"/other (PDM field ID: ZUSCHL.CERTIFY)

erw_status_02		char(1)	Bonuses: Signed J: approved A: rejected N+other: not yet processed (PDM field ID: ZUSCHL.SIGN)
erw_status_03		char(1)	J = mode for logging all persons off at GWP
erw_status_04		char(1)	Active ADE/PZE comparison: shift type from PZE
erw_status_05		char(1)	for internal use
erw_status_06		char(1)	for internal use
firma_1		char(8)	Company/plant number 1
firma_2		char(8)	Company/plant number 2
grund_1		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_10		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_11		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_12		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_13		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_14		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_15		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_16		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_17		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_18		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_19		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')

grund_2		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_20		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_3		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_4		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_5		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_6		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_7		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_8		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_9		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
herkunft		char(1)	"Blank": original data record from the collection E: manually generated data record L: manually generated data record; for cancellation only O: original data record if maintained
info_01		integer	So far not allocated
info_02		integer	Active ADE/PZE comparison: flextime type from PZE
info_03		integer	HYD-AEV: Error code in case of rejected dialog messages while posting
ist_lst_01		decimal(18,6)	Recorded activity 1
ist_lst_02		decimal(18,6)	Recorded activity 2
ist_lst_03		decimal(18,6)	Recorded activity 3
ist_lst_04		decimal(18,6)	Recorded activity 4
ist_lst_05		decimal(18,6)	Recorded activity 5
ist_lst_06		decimal(18,6)	Recorded activity 6
ist_lst_07		decimal(18,6)	Recorded activity 7
ist_lst_08		decimal(18,6)	Recorded activity 8
ist_lst_09		decimal(18,6)	Recorded activity 9
ist_lst_10		decimal(18,6)	Recorded activity 10
ist_lst_11		decimal(18,6)	Recorded activity 11
ist_lst_12		decimal(18,6)	Recorded activity 12
ist_lst_13		decimal(18,6)	Recorded activity 13

ist_lst_14		decimal(18,6)	Recorded activity 14
ist_lst_15		decimal(18,6)	Recorded activity 15
ist_lst_16		decimal(18,6)	Recorded activity 16
ist_lst_17		decimal(18,6)	Recorded activity 17
ist_lst_18		decimal(18,6)	Recorded activity 18
ist_lst_19		decimal(18,6)	Recorded activity 19
ist_lst_20		decimal(18,6)	Recorded activity 20
ist_lst_einh_01		char(3)	Unit of recorded activity
ist_lst_einh_02		char(3)	Unit of recorded activity
ist_lst_einh_03		char(3)	Unit of recorded activity
ist_lst_einh_04		char(3)	Unit of recorded activity
ist_lst_einh_05		char(3)	Unit of recorded activity
ist_lst_einh_06		char(3)	Unit of recorded activity
ist_lst_einh_07		char(3)	Unit of recorded activity
ist_lst_einh_08		char(3)	Unit of recorded activity
ist_lst_einh_09		char(3)	Unit of recorded activity
ist_lst_einh_10		char(3)	Unit of recorded activity
ist_lst_einh_11		char(3)	Unit of recorded activity
ist_lst_einh_12		char(3)	Unit of recorded activity
ist_lst_einh_13		char(3)	Unit of recorded activity
ist_lst_einh_14		char(3)	Unit of recorded activity
ist_lst_einh_15		char(3)	Unit of recorded activity
ist_lst_einh_16		char(3)	Unit of recorded activity
ist_lst_einh_17		char(3)	Unit of recorded activity
ist_lst_einh_18		char(3)	Unit of recorded activity
ist_lst_einh_19		char(3)	Unit of recorded activity
ist_lst_einh_20		char(3)	Unit of recorded activity
ist_lst_typ_01		char(10)	Type of recorded activity
ist_lst_typ_02		char(10)	Type of recorded activity
ist_lst_typ_03		char(10)	Type of recorded activity
ist_lst_typ_04		char(10)	Type of recorded activity
ist_lst_typ_05		char(10)	Type of recorded activity
ist_lst_typ_06		char(10)	Type of recorded activity
ist_lst_typ_07		char(10)	Type of recorded activity
ist_lst_typ_08		char(10)	Type of recorded activity
ist_lst_typ_09		char(10)	Type of recorded activity
ist_lst_typ_10		char(10)	Type of recorded activity
ist_lst_typ_11		char(10)	Type of recorded activity
ist_lst_typ_12		char(10)	Type of recorded activity
ist_lst_typ_13		char(10)	Type of recorded activity
ist_lst_typ_14		char(10)	Type of recorded activity
ist_lst_typ_15		char(10)	Type of recorded activity
ist_lst_typ_16		char(10)	Type of recorded activity
ist_lst_typ_17		char(10)	Type of recorded activity
ist_lst_typ_18		char(10)	Type of recorded activity
ist_lst_typ_19		char(10)	Type of recorded activity

ist_lst_typ_20		char(10)	Type of recorded activity
karenz		char(1)	Indicator whether processing due to waiting period processing
klasse		char(1)	P: Personal message
lohnart		char(4)	LLE wage type
lpkz		char(10)	Wage premium indicator
masch_nr		char(20)	"
menge_1		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap Supplements: duration of supplement or deduction (PDM field ID: EREIGADEP.MENGE:1 (ZUSCHL.DAUER))
menge_10		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_11		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_12		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_13		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_14		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_15		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_16		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap

menge_17		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_18		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_19		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_2		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap Supplements: number in case of relative supplements (PDM field ID: ZUSCHL:ANZ:ANZ)
menge_20		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_3		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap Supplements: duration per item in case of relative supplements (PDM field ID: ZUSCHL:ANZ:DAUER)
menge_4		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_5		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_6		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_7		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap

menge_8		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_9		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
offline_kz		char(1)	J: Recorded offline by the terminal
org_verweis		integer	Reference to a correction data record
p_divisor		decimal(18,6)	Recorded divisor
p_teiligkeit		decimal(18,6)	Recorded partitioning
person_nr		char(10)	Personnel number (PDM field ID: EREIGADEP.PNR (ZUSCHL.PNR))
pgruppe		char(20)	"
pmk		char(1)	Indicator for memorizing person
prgrp		char(10)	Premium group
prioritaet		smallint	Priority is indicated in case of simultaneous events (1 = highest priority)
pze_erzeugt		char(1)	"K" =BDE event has been generated by PZE clock-in "G" =BDE event has been generated by PZE clock-out
rest_lst_01		decimal(18,6)	Remaining recorded activity
rest_lst_02		decimal(18,6)	Remaining recorded activity
rest_lst_03		decimal(18,6)	Remaining recorded activity
rest_lst_04		decimal(18,6)	Remaining recorded activity
rest_lst_05		decimal(18,6)	Remaining recorded activity
rest_lst_06		decimal(18,6)	Remaining recorded activity
rest_lst_07		decimal(18,6)	Remaining recorded activity
rest_lst_08		decimal(18,6)	Remaining recorded activity
rest_lst_09		decimal(18,6)	Remaining recorded activity
rest_lst_10		decimal(18,6)	Remaining recorded activity
rest_lst_11		decimal(18,6)	Remaining recorded activity
rest_lst_12		decimal(18,6)	Remaining recorded activity
rest_lst_13		decimal(18,6)	Remaining recorded activity
rest_lst_14		decimal(18,6)	Remaining recorded activity
rest_lst_15		decimal(18,6)	Remaining recorded activity
rest_lst_16		decimal(18,6)	Remaining recorded activity
rest_lst_17		decimal(18,6)	Remaining recorded activity
rest_lst_18		decimal(18,6)	Remaining recorded activity
rest_lst_19		decimal(18,6)	Remaining recorded activity
rest_lst_20		decimal(18,6)	Remaining recorded activity
rest_lst_einh_01		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_02		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_03		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_04		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_05		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_06		char(3)	Remainder of unit of the recorded activity

rest_lst_einh_07		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_08		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_09		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_10		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_11		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_12		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_13		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_14		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_15		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_16		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_17		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_18		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_19		char(3)	Remainder of unit of the recorded activity
rest_lst_einh_20		char(3)	Remainder of unit of the recorded activity
rest_lst_typ_01		char(10)	Remainder of type of the recorded activity
rest_lst_typ_02		char(10)	Remainder of type of the recorded activity
rest_lst_typ_03		char(10)	Remainder of type of the recorded activity
rest_lst_typ_04		char(10)	Remainder of type of the recorded activity
rest_lst_typ_05		char(10)	Remainder of type of the recorded activity
rest_lst_typ_06		char(10)	Remainder of type of the recorded activity
rest_lst_typ_07		char(10)	Remainder of type of the recorded activity
rest_lst_typ_08		char(10)	Remainder of type of the recorded activity
rest_lst_typ_09		char(10)	Remainder of type of the recorded activity
rest_lst_typ_10		char(10)	Remainder of type of the recorded activity
rest_lst_typ_11		char(10)	Remainder of type of the recorded activity
rest_lst_typ_12		char(10)	Remainder of type of the recorded activity
rest_lst_typ_13		char(10)	Remainder of type of the recorded activity
rest_lst_typ_14		char(10)	Remainder of type of the recorded activity
rest_lst_typ_15		char(10)	Remainder of type of the recorded activity
rest_lst_typ_16		char(10)	Remainder of type of the recorded activity
rest_lst_typ_17		char(10)	Remainder of type of the recorded activity
rest_lst_typ_18		char(10)	Remainder of type of the recorded activity
rest_lst_typ_19		char(10)	Remainder of type of the recorded activity
rest_lst_typ_20		char(10)	Remainder of type of the recorded activity
sig_knr1		char(10)	
sig_knr2		char(10)	
sig_name1		char(40)	
sig_name2		char(40)	
sig_pnr1		char(10)	
sig_pnr2		char(10)	
sig_type1		char(20)	
sig_type2		char(20)	
soll_te		decimal(18,6)	Premium target TE
soll_teb		decimal(18,6)	Premium target TEB
soll_tr		decimal(18,6)	Premium target TR
stationsnr		integer	otherwise free

status_1		integer	Machine status, termination reason, partitioning or target cycle Supplements: Bonus reason (PDM field ID: EREIGADEP.STA:1 (ZUSCHL.ZUSCHLGR))
status_2		integer	Active ADE/PZE comparison: shift date from PZE
status_3		integer	---
szenario_nr		integer	for future use important for event maintenance
terminal_nr		smallint	User who generated the data record
typ_1		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_10		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_11		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_12		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_13		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_14		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired

typ_15		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_16		char(10)	So far not allocated
typ_17		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_18		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_19		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_2		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_20		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_3		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired

typ_4		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_5		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_6		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_7		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_8		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_9		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
umref		decimal(18,6)	Conversion factor for retrograde posting
utc_ts		datetime	
verarb_1		char(1)	Processing PZE
verarb_2		char(1)	Processing BDE
verarb_3		char(1)	Free
verarb_4		char(1)	HYD-AEV: A = indicator for automatically generated dialogs, e.g. of PZE/ADE comparison
verarb_mde		char(1)	Processing MDE (postprocessing of workplace-related result record messages)

verbuch_kz		char(2)	Posting indicator, e.g. "ST" = COP at the terminal "SK"= COP at the console "SB" = Beginning of shift, "SE" = End of shift "W" = Wintertime (PZE) "S" = Summertime (PZE)
verweis		serial	Distinct reference of the data record (PDM field ID: EREIGADEP.VERWEIS)
verweis_b1		integer	Reference to the operation-related result record or clocking record
verweis_b2		integer	Reference to a 2nd clocking record
zeit		integer	Log time (PDM field ID: EREIGADEP.ZEI (ZUSCHL.ZEI))

2.31. hy_gruppen

Table name: hy_gruppen		Product: BDE	
Designation: Groups			
Column name	Column designation	Type	Description
ausw_gruppe	analyzing group	char(1)	analyzing group: J / N (PDM field ID: GRP.OPT:AUSWGRP)
bearb		char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
benutzer	User	char(10)	User (PDM field ID: GRP.BEARB)
benutzergruppe	User group	char(10)	User group
bezeichnung	Designation	char(40)	MGRP or PGRP are entered here again if automatically from MNR/PNR-BAPI (PDM field ID: GRP.BEZ)
ermittlung_fertvar	Determination of the production variants	char(2)	Determination of the production variants [1,1] Consider production variant by takeover E = search production variant P = only check production variant N= no use [2,2] Consider production variant in planning E = search production variant P = only check production variant N= no use
firma	Company	char(4)	Take over from respective fields if automatically from MNR/PNR-BAPI (PDM field ID: GRP.FIR)
gruppe	Line group	char(20)	Group
kapa_gruppe	Capacity group	char(1)	Capacity group
kostenstelle	Cost center	char(10)	Cost center
leistgrad	Performance rate	smallint	Performance rate
liniengruppe	Indicator "line group"	char(1)	Indicator "line group" Values: J --> line group N / empty / other charaters --> no line group Default: empty
ortsgruppe	Location group	char(1)	Location group
planen	Planning J/N	char(3)	Planning J/N
pps_rueck_bei_a_ab	Upload only when logging OP off	char(1)	Upload to the PPS system only when logging off an OP, not for the single partial confirmations (T, U records) The data are uploaded "en bloc", thus the postings that have so far accrued are not uploaded separately, but the status (PDM field ID: OPT:PPSRCKAAB)
schichtmod	Shift model	smallint	Shift model
simulation		char(3)	--
typenrein	Sing. type	char(1)	Indicator single type All machines of the group are of the same type
user_c_07	User-specific field	char(1)	User-specific field (PDM field ID: GRP.FU:7)

user_c_08	User-specific field	char(1)	User-specific field (PDM field ID: GRP.FU:8)
user_c_09	User-specific field	char(1)	User-specific field (PDM field ID: GRP.FU:9)
user_c_10	User-specific field	char(1)	User-specific field (PDM field ID: GRP.FU:10)
user_c_11	User-specific field	char(1)	User-specific field (PDM field ID: GRP.FU:11)
user_c_12	User-specific field	char(10)	User-specific field (PDM field ID: GRP.FU:12)
user_c_13	User-specific field	char(10)	User-specific field (PDM field ID: GRP.FU:13)
user_c_14	User-specific field	char(20)	User-specific field (PDM field ID: GRP.FU:14)
user_c_15	User-specific field	char(20)	User-specific field (PDM field ID: GRP.FU:15)
user_c_16	User-specific field	char(40)	User-specific field (PDM field ID: GRP.FU:16)
user_code	User field key	char(8)	User field key Reference to the configuration of the user field key or its user fields in table HYD_USERFIELDCFG (PDM field ID: GRP.USRFLD)
user_f_05	User-specific field	decimal(18,6)	User-specific field (PDM field ID: GRP.FU:5)
user_f_06	User-specific field	decimal(18,6)	User-specific field (PDM field ID: GRP.FU:6)
user_n_01	User-specific field	integer	User-specific field (PDM field ID: GRP.FU:1)
user_n_02	User-specific field	integer	User-specific field (PDM field ID: GRP.FU:2)
user_n_03	User-specific field	integer	User-specific field (PDM field ID: GRP.FU:3)
user_n_04	User-specific field	integer	User-specific field (PDM field ID: GRP.FU:4)
vab	Responsibility area	char(15)	Responsibility area

2.32. hy_gruppen_zuord

Table name: hy_gruppen_zuord		Product: BDE	
Designation: Group assignment			
Column name	Column designation	Type	Description
anzeige_pos	Display position	smallint	Display position
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
gruppe	Group	char(20)	Type: GRP (A/N) Note: In the field definitions it is defined how the group fields are formatted (arity, alphanumeric/numeric) - HR master data: PGRUPPE of the type PGRP (A/N), arity can possibly be set (at present 3) for each field definition - Machines: MGRUPPE of the type MGRP (A/N) (PDM field ID: GRPRES.GRP)
res_nr	Number of the resource	char(40)	Number of the resource: - If person from HR master data "PNR" - If machine from machine configuration: "MNR" - If resource from WRM: <RES_TYP> (PDM field ID: GRPRES.RES_NR)
res_typ	Resource type	char(4)	Resource type - If person from HR master data "PNR" - If machine from machine configuration: "MNR" - If resource from WRM: <RES_TYP> (PDM field ID: GRPRES.RESTYP)

2.33. masch_lohngruppen

Table name: masch_lohngruppen		Product: BDE	
Designation: Wage/premium indicator		Description: The wage groups and premium indicators allowed per machine are defined in this table. When employees are logged on to the terminal it is required to enter the wage group or premium indicator (if configured in the dialog).	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bezeichnung	Description of the wage group or of the	char(30)	Description of the wage group or of the premium indicator (PDM field ID: LPKZ.BEZ)
lohngruppe	Wage group or premium indicator	char(10)	Wage group or premium indicator (PDM field ID: LPKZ.LPKZGRP)
masch_nr	Machine	char(20)	Machine (PDM field ID: LPKZ.MNR)

2.34. meister_prot

Table name: meister_prot		Product: BDE	
Designation: System log			
Column name	Column designation	Type	Description
anzahl		smallint	Number of messages of this kind (PDM field ID: MSTPRO.ANZ)
auftrag_nr	Order number	char(40)	OP number (PDM field ID: MSTPRO.ANR)
aw_datum	Evaluation date	date	Evaluation date (PDM field ID: MSTPRO.AWDAT)
bearb		char(10)	
frei_text		char(20)	Customer-specific (PDM field ID: MSTPRO.TXT)
ist_einh		char(3)	Recorded unit (PDM field ID: MSTPRO.ISTMENGE)
ist_stck		integer	Actual number of pieces (PDM field ID: MSTPRO.ISTEINH)
kostenstelle		char(10)	Cost center (PDM field ID: MSTPRO.KST)
masch_nr		char(20)	Machine number (PDM field ID: MSTPRO.MNR)
meld_art	Posting	char(1)	Kind of message It is indicated here which kind of system message is concerned: 1: log records for scrap without reason 2: log records for a target/actual deviation of > +/- 5% 3: Entries in the machine order when the order/OP is not available or running anymore 4: Entries in intrasystem memory table for relogons of people when order/OP is not available or running anymore or when the person is not available anymore 5: Personnel log records that are not approved 6: Overhead cost log records that are not approved 7: Operation-related result record for which there are no orders/OPs 8: the workplace is defined as ADE and MDE machine 10: the last OP of the order has already been finished although at least one preceding OP has not yet been finished K: ANP-000580: automatic logoff by PZE (hy_ups) According to the kind of message, not all data fields are allocated (PDM field ID: MSTPRO.TYP)
person_nr		char(10)	Personnel number (PDM field ID: MSTPRO.PNR)
prod_datum		date	Date (PDM field ID: MSTPRO.DAT)
prod_zeit		integer	Time (PDM field ID: MSTPRO.ZEI)
sign_date		date	
sign_flag		char(1)	
sign_time		integer	
soll_einh		char(3)	Target unit (PDM field ID: MSTPRO.SOLLMENGE)
soll_stck		integer	Target number of pieces (PDM field ID: MSTPRO.SOLLEINH)
verantw_bereich		char(15)	

2.35. pers_merken

Table name: pers_merken		Product: BDE	
Designation: Temporary storage logons of staff		Description: This table is used for intrasystem administration.	
Column name	Column designation	Type	Description
auftrag_nr		char(40)	Order number + OP
bpos		char(10)	Operator position from memorized logon
hyuser		integer	User (terminal)
lohnart		char(4)	---
lpkz		char(10)	Wage group or premium indicator from memorized logon
masch_nr		char(20)	Machine number
melde_art		char(2)	"PV" : logon in advance (is evaluated at the beginning of the shift) "PK" : Waiting period of personnel (last logon memorized at P_GEH) "PM" : Memorized person by OP logoff or interruption
param_01		integer	free
param_str		char(10)	free
person_nr		char(20)	Personnel number
pgruppe		char(10)	Personnel group from memorized logon
prgrp		char(10)	LLE premium group from memorized logon
prot_dat		date	Date of the logon of staff that was memorized
prot_zeit		integer	Time of the logon of staff that was memorized
satz_art		char(2)	Record type (from hybuch): empty: memorized person/person memorized in advance or "P" = comb. logon (A_P_AN) "N" = logon of staff (P_AN) "J" = COP - logon of staff "M" = COP - logon of machine
soll_te		decimal(18,6)	Not allocated (current TE is always taken over from OP when logged on again)
soll_teb		decimal(18,6)	Not allocated (current TEB is always taken over from OP when logged on again)
soll_tr		decimal(18,6)	Not allocated (current TR is always taken over from OP when logged on again)
soll_trb		decimal(18,6)	Not allocated (current TRB is always taken over from OP when logged on again)

2.36. pps_bestand

Table name: pps_bestand		Product: BDE	
Archive table: a_pps_bestand		Reload table: r_pps_bestand	
Designation: Order backlog (PPS)			
Column name	Column designation	Type	Description
a_prio		char(4)	Analogous to AUFTRAGS_BESTAND
a_stufe		char(3)	Analogous to AUFTRAGS_BESTAND
a_typ		char(4)	Analogous to AUFTRAGS_BESTAND
abmeldopt		char(10)	Analogous to AUFTRAGS_BESTAND
abruest_zeit		integer	Analogous to AUFTRAGS_BESTAND
abruest_zeit_expr		char(6)	Analogous to AUFTRAGS_BESTAND
abruest_zeit_mod		char(1)	Analogous to AUFTRAGS_BESTAND
afo_lfd_nr		integer	Analogous to AUFTRAGS_BESTAND
afolg		char(10)	Analogous to AUFTRAGS_BESTAND
ag_art		char(5)	Analogous to AUFTRAGS_BESTAND
ag_bez		char(40)	Analogous to AUFTRAGS_BESTAND
ag_verweis		integer	Analogous to AUFTRAGS_BESTAND
agnr		char(20)	Analogous to AUFTRAGS_BESTAND
als_dsbez		char(20)	Analogous to AUFTRAGS_BESTAND
anlage		char(10)	Analogous to AUFTRAGS_BESTAND
anlage_date		date	Analogous to AUFTRAGS_BESTAND
anlage_time		integer	Analogous to AUFTRAGS_BESTAND
anmeldopt		char(10)	Analogous to AUFTRAGS_BESTAND
anz_split_masch		smallint	Analogous to AUFTRAGS_BESTAND
arbplan		char(40)	Analogous to AUFTRAGS_BESTAND
artikel		char(40)	Analogous to AUFTRAGS_BESTAND
artikel_bez		char(40)	Analogous to AUFTRAGS_BESTAND
auftrag_art		char(5)	Analogous to AUFTRAGS_BESTAND
auftrag_nr		char(40)	Analogous to AUFTRAGS_BESTAND
aunr		char(40)	Analogous to AUFTRAGS_BESTAND
bearb		char(10)	Analogous to AUFTRAGS_BESTAND
bearb_date		date	Analogous to AUFTRAGS_BESTAND
bearb_time		integer	Analogous to AUFTRAGS_BESTAND
bearb_zeit		integer	Analogous to AUFTRAGS_BESTAND
bearb_zeit_expr		char(6)	Analogous to AUFTRAGS_BESTAND
bearb_zeit_mod		char(1)	Analogous to AUFTRAGS_BESTAND
chargen_pflicht		char(1)	Analogous to AUFTRAGS_BESTAND
ein_h_menge		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
ein_h_menge_einh		char(3)	Analogous to AUFTRAGS_BESTAND
erfass_art		char(1)	Analogous to AUFTRAGS_BESTAND
erfassbar		char(1)	Analogous to AUFTRAGS_BESTAND
erranf_dat		date	Analogous to AUFTRAGS_BESTAND

erranf_zeit		integer	Analogous to AUFTRAGS_BESTAND
errend_dat		date	Analogous to AUFTRAGS_BESTAND
errend_zeit		integer	Analogous to AUFTRAGS_BESTAND
farbe		char(20)	Analogous to AUFTRAGS_BESTAND
fertvar_verweis		integer	Analogous to AUFTRAGS_BESTAND
firma		char(4)	Analogous to AUFTRAGS_BESTAND
fremdbearbeitung		char(1)	Analogous to AUFTRAGS_BESTAND
frueh_anf_dat		date	Analogous to AUFTRAGS_BESTAND
frueh_anf_zeit		integer	Analogous to AUFTRAGS_BESTAND
frueh_end_dat		date	Analogous to AUFTRAGS_BESTAND
frueh_end_zeit		integer	Analogous to AUFTRAGS_BESTAND
geaendert_hydra		char(1)	Analogous to AUFTRAGS_BESTAND
geaendert_planung		char(1)	Analogous to AUFTRAGS_BESTAND
geaendert_pps		char(1)	Analogous to AUFTRAGS_BESTAND
kopf_verweis		integer	Analogous to AUFTRAGS_BESTAND
kostenart		char(20)	Analogous to AUFTRAGS_BESTAND
kostenstelle		char(10)	Analogous to AUFTRAGS_BESTAND
kunden_bez		char(40)	Analogous to AUFTRAGS_BESTAND
lagerort		char(12)	Analogous to AUFTRAGS_BESTAND
last_afo		char(1)	Analogous to AUFTRAGS_BESTAND
last_term_date		date	Analogous to AUFTRAGS_BESTAND
last_term_time		integer	Analogous to AUFTRAGS_BESTAND
layout		char(20)	
lieferzeit		integer	Analogous to AUFTRAGS_BESTAND
liege_zeit		integer	Analogous to AUFTRAGS_BESTAND
liege_zeit_max		integer	Analogous to AUFTRAGS_BESTAND
lohnart		char(4)	Analogous to AUFTRAGS_BESTAND
ls_safo_nr		char(40)	Analogous to AUFTRAGS_BESTAND
ls_sammel_kz		char(1)	Analogous to AUFTRAGS_BESTAND
ls_split_anz		smallint	Analogous to AUFTRAGS_BESTAND
ls_split_kz		char(1)	Analogous to AUFTRAGS_BESTAND
lst_code		char(6)	Analogous to AUFTRAGS_BESTAND
masch_nr		char(20)	Analogous to AUFTRAGS_BESTAND
matetyp		char(20)	Analogous to AUFTRAGS_BESTAND
mb_verh_ruesten		smallfloat	Analogous to AUFTRAGS_BESTAND
mb_verhaeltnis		smallfloat	Analogous to AUFTRAGS_BESTAND
mehrfach_kz		char(1)	Analogous to AUFTRAGS_BESTAND
meinheit_bas		char(3)	Analogous to AUFTRAGS_BESTAND
meinheit_lief		char(3)	Analogous to AUFTRAGS_BESTAND
meinheit_pri		char(3)	Analogous to AUFTRAGS_BESTAND
meinheit_sek		char(3)	Analogous to AUFTRAGS_BESTAND
meinheit_ter		char(3)	Analogous to AUFTRAGS_BESTAND
menge_pri_uebli		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
menge_pri_uebli_r		char(1)	Analogous to AUFTRAGS_BESTAND
menge_pri_untli		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
menge_pri_untli_r		char(1)	Analogous to AUFTRAGS_BESTAND

mgruppe		char(20)	Analogous to AUFTRAGS BESTAND
notiz_vorh		char(1)	Analogous to AUFTRAGS BESTAND
op_code		char(10)	Analogous to AUFTRAGS BESTAND
pdv_pruefplan_nr		char(20)	Analogous to AUFTRAGS BESTAND
plan_werk		char(4)	Analogous to AUFTRAGS BESTAND
prplan_nr		integer	Analogous to AUFTRAGS BESTAND
pruef_masch_nr		char(20)	Analogous to AUFTRAGS BESTAND
pruef_zeit		integer	Analogous to AUFTRAGS BESTAND
pruef_zeit_expr		char(6)	Analogous to AUFTRAGS BESTAND
pruef_zeit_mod		char(1)	Analogous to AUFTRAGS BESTAND
puffer_zeit		integer	Analogous to AUFTRAGS BESTAND
qm_ag_typ		char(2)	
qm_m_auftrag_nr		char(40)	
qual_ruesten		integer	
qualifikation		integer	
red_puffer_zeit		integer	Analogous to AUFTRAGS BESTAND
res_dnc		char(40)	Analogous to AUFTRAGS BESTAND
res_emat		char(40)	Analogous to AUFTRAGS BESTAND
res_wnr		char(40)	Analogous to AUFTRAGS BESTAND
rf_a_breite		decimal(18,6)	Analogous to AUFTRAGS BESTAND
rf_abzweig		char(1)	Analogous to AUFTRAGS BESTAND
rf_agtyp		char(1)	Analogous to AUFTRAGS BESTAND
rf_agvfa		decimal(18,6)	Analogous to AUFTRAGS BESTAND
rf_bsbrs		decimal(18,6)	Analogous to AUFTRAGS BESTAND
rf_e_breite		decimal(18,6)	Analogous to AUFTRAGS BESTAND
rf_etr_anz		integer	Analogous to AUFTRAGS BESTAND
rf_gtr_anz		integer	Analogous to AUFTRAGS BESTAND
rf_huegewicht		decimal(18,6)	Analogous to AUFTRAGS BESTAND
rf_m_auftrag_nr		char(40)	Analogous to AUFTRAGS BESTAND
rf_opcode		char(10)	Analogous to AUFTRAGS BESTAND
rf_roanz		integer	Analogous to AUFTRAGS BESTAND
rf_rosch		char(1)	Analogous to AUFTRAGS BESTAND
rf_stflaech		decimal(18,6)	Analogous to AUFTRAGS BESTAND
rf_zuzweig		char(1)	Analogous to AUFTRAGS BESTAND
rf_zuzweigmenge		integer	Analogous to AUFTRAGS BESTAND
rlz2_expr		char(6)	Analogous to AUFTRAGS BESTAND
rlz_expr		char(6)	Analogous to AUFTRAGS BESTAND
rmnr		char(40)	Analogous to AUFTRAGS BESTAND
ruest_zeit		integer	Analogous to AUFTRAGS BESTAND
ruest_zeit_expr		char(6)	Analogous to AUFTRAGS BESTAND
ruest_zeit_mod		char(1)	Analogous to AUFTRAGS BESTAND
ruest_zeit_zuschl		integer	Analogous to AUFTRAGS BESTAND
s_bpc_quan_1		decimal(18,6)	Analogous to AUFTRAGS BESTAND
s_bpc_uniso_1		char(3)	Analogous to AUFTRAGS BESTAND
s_bpc_unit_1		char(3)	Analogous to AUFTRAGS BESTAND
s_co_bpc_1		char(12)	Analogous to AUFTRAGS BESTAND

s_hdr_denominator		integer	Analogous to AUFTRAGS BESTAND
s_hdr_nominator		integer	Analogous to AUFTRAGS BESTAND
s_source_sys		char(10)	Analogous to AUFTRAGS BESTAND
sap_auftrag_nr		char(12)	Analogous to AUFTRAGS BESTAND
sap_bezfl		char(6)	Analogous to AUFTRAGS BESTAND
sap_laufnr		char(12)	Analogous to AUFTRAGS BESTAND
sap_mapfl		char(6)	Analogous to AUFTRAGS BESTAND
sap_maufnr		char(12)	Analogous to AUFTRAGS BESTAND
sap_mrlfg		char(1)	Analogous to AUFTRAGS BESTAND
sap_mvornr		char(4)	Analogous to AUFTRAGS BESTAND
sap_split_nr		smallint	Analogous to AUFTRAGS BESTAND
sap_usr00		char(20)	Analogous to AUFTRAGS BESTAND
sap_usr01		char(20)	Analogous to AUFTRAGS BESTAND
sap_usr04		decimal(18,6)	Analogous to AUFTRAGS BESTAND
sap_usr04_unit		char(3)	Analogous to AUFTRAGS BESTAND
sap_uvg		char(4)	Analogous to AUFTRAGS BESTAND
sap_vg_nr		char(4)	Analogous to AUFTRAGS BESTAND
sap_vgfolge		char(6)	Analogous to AUFTRAGS BESTAND
sap_vornr1		char(4)	Analogous to AUFTRAGS BESTAND
sap_vornr2		char(4)	Analogous to AUFTRAGS BESTAND
serialnr_pflcht		char(1)	Analogous to AUFTRAGS BESTAND
soll_aus_bas		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_aus_pri		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_aus_sek		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_aus_ter		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_bedien_ant		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_dauer		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_dauer_expr		char(6)	Analogous to AUFTRAGS BESTAND
soll_dauer_fmt		char(3)	Analogous to AUFTRAGS BESTAND
soll_dauer_mod		char(1)	Analogous to AUFTRAGS BESTAND
soll_div		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_menge_ansatz		decimal(18,6)	
soll_menge_bas		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_menge_pri		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_menge_sek		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_menge_ter		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_te		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_te_expr		char(6)	Analogous to AUFTRAGS BESTAND
soll_te_fmt		char(3)	Analogous to AUFTRAGS BESTAND
soll_te_mod		char(1)	Analogous to AUFTRAGS BESTAND
soll_teb		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_teb_expr		char(6)	Analogous to AUFTRAGS BESTAND
soll_teb_fmt		char(3)	Analogous to AUFTRAGS BESTAND
soll_teb_mod		char(1)	Analogous to AUFTRAGS BESTAND
soll_teil		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_tr		decimal(18,6)	Analogous to AUFTRAGS BESTAND

soll_tr_expr		char(6)	Analogous to AUFTRAGS BESTAND
soll_tr_mod		char(1)	Analogous to AUFTRAGS BESTAND
soll_trb		decimal(18,6)	Analogous to AUFTRAGS BESTAND
soll_trb_expr		char(6)	Analogous to AUFTRAGS BESTAND
soll_trb_fmt		char(3)	Analogous to AUFTRAGS BESTAND
soll_trb_mod		char(1)	Analogous to AUFTRAGS BESTAND
sollmengenforts		char(1)	Analogous to AUFTRAGS BESTAND
sort_dat		date	Analogous to AUFTRAGS BESTAND
sort_zeit		integer	Analogous to AUFTRAGS BESTAND
spaet_anf_dat		date	Analogous to AUFTRAGS BESTAND
spaet_anf_zeit		integer	Analogous to AUFTRAGS BESTAND
spaet_end_dat		date	Analogous to AUFTRAGS BESTAND
spaet_end_zeit		integer	Analogous to AUFTRAGS BESTAND
splitten		char(1)	Analogous to AUFTRAGS BESTAND
splnr		char(10)	Analogous to AUFTRAGS BESTAND
term_anf_dat		date	Analogous to AUFTRAGS BESTAND
term_anf_zeit		integer	Analogous to AUFTRAGS BESTAND
term_end_dat		date	Analogous to AUFTRAGS BESTAND
term_end_zeit		integer	Analogous to AUFTRAGS BESTAND
terminieren		char(1)	Analogous to AUFTRAGS BESTAND
text_vorh		char(1)	Analogous to AUFTRAGS BESTAND
transfer		char(10)	Analogous to AUFTRAGS BESTAND
transfer_datum		date	Analogous to AUFTRAGS BESTAND
transfer_zeit		integer	Analogous to AUFTRAGS BESTAND
transp_zeit		integer	Analogous to AUFTRAGS BESTAND
transp_zeit_kal		integer	Analogous to AUFTRAGS BESTAND
transp_zeit_min		integer	Analogous to AUFTRAGS BESTAND
transp_zeit_norm		integer	Analogous to AUFTRAGS BESTAND
uagnr		char(20)	Analogous to AUFTRAGS BESTAND
umrech_lief_nen		integer	Analogous to AUFTRAGS BESTAND
umrech_lief_zae		integer	Analogous to AUFTRAGS BESTAND
umrech_pri_nen		integer	Analogous to AUFTRAGS BESTAND
umrech_pri_zae		integer	Analogous to AUFTRAGS BESTAND
umrech_sek_nen		integer	Analogous to AUFTRAGS BESTAND
umrech_sek_zae		integer	Analogous to AUFTRAGS BESTAND
umrech_ter_nen		integer	Analogous to AUFTRAGS BESTAND
umrech_ter_zae		integer	Analogous to AUFTRAGS BESTAND
user_c_29		char(1)	User-specific field
user_c_30		char(1)	User-specific field
user_c_31		char(1)	User-specific field
user_c_32		char(1)	User-specific field
user_c_33		char(1)	User-specific field
user_c_34		char(1)	User-specific field
user_c_35		char(1)	User-specific field
user_c_36		char(1)	User-specific field
user_c_37		char(1)	User-specific field

user_c_38		char(1)	User-specific field
user_c_39		char(1)	User-specific field
user_c_40		char(1)	User-specific field
user_c_41		char(1)	User-specific field
user_c_42		char(1)	User-specific field
user_c_43		char(1)	User-specific field
user_c_44		char(1)	User-specific field
user_c_45		char(10)	User-specific field
user_c_46		char(10)	User-specific field
user_c_47		char(10)	User-specific field
user_c_48		char(10)	User-specific field
user_c_49		char(10)	User-specific field
user_c_50		char(10)	User-specific field
user_c_51		char(20)	User-specific field
user_c_52		char(20)	User-specific field
user_c_53		char(20)	User-specific field
user_c_54		char(20)	User-specific field
user_c_55		char(20)	User-specific field
user_c_56		char(20)	User-specific field
user_c_57		char(20)	User-specific field
user_c_58		char(20)	User-specific field
user_c_59		char(20)	User-specific field
user_c_60		char(20)	User-specific field
user_c_61		char(20)	User-specific field
user_c_62		char(20)	User-specific field
user_c_63		char(20)	User-specific field
user_c_64		char(20)	User-specific field
user_c_65		char(40)	User-specific field
user_c_66		char(40)	User-specific field
user_code		char(8)	Analogous to AUFTRAGS_BESTAND
user_d_01		date	User-specific field
user_d_02		date	User-specific field
user_d_03		date	User-specific field
user_d_04		date	User-specific field
user_d_05		date	User-specific field
user_d_06		date	User-specific field
user_f_23		decimal(18,6)	User-specific field
user_f_24		decimal(18,6)	User-specific field
user_f_25		decimal(18,6)	User-specific field
user_f_26		decimal(18,6)	User-specific field
user_f_27		decimal(18,6)	User-specific field
user_f_28		decimal(18,6)	User-specific field
user_n_07		integer	User-specific field
user_n_08		integer	User-specific field
user_n_09		integer	User-specific field
user_n_10		integer	User-specific field

user_n_11		integer	User-specific field
user_n_12		integer	User-specific field
user_n_13		integer	User-specific field
user_n_14		integer	User-specific field
user_n_15		integer	User-specific field
user_n_16		integer	User-specific field
user_n_17		integer	User-specific field
user_n_18		integer	User-specific field
user_n_19		integer	User-specific field
user_n_20		integer	User-specific field
user_n_21		integer	User-specific field
user_n_22		integer	User-specific field
verantw_bereich		char(15)	Analogous to AUFTRAGS_BESTAND
verarb_code		char(6)	Analogous to AUFTRAGS_BESTAND
verarb_code_mod		integer	Analogous to AUFTRAGS_BESTAND
verbrauch_art		char(2)	Analogous to AUFTRAGS_BESTAND
verweis		serial	Analogous to AUFTRAGS_BESTAND
vgw_01		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_02		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_03		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_04		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_05		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_06		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_07		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_08		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_09		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_10		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
vgw_code		char(5)	Analogous to AUFTRAGS_BESTAND
vorgabeliste		char(1)	Analogous to AUFTRAGS_BESTAND
vorlaufzeit		integer	Analogous to AUFTRAGS_BESTAND
warte_zeit		integer	Analogous to AUFTRAGS_BESTAND
warte_zeit_expr		char(6)	Analogous to AUFTRAGS_BESTAND
warte_zeit_min		integer	Analogous to AUFTRAGS_BESTAND
warte_zeit_mod		char(1)	Analogous to AUFTRAGS_BESTAND
warte_zeit_norm		integer	Analogous to AUFTRAGS_BESTAND
weitergabemenge		decimal(18,6)	Analogous to AUFTRAGS_BESTAND
wpkz		char(1)	Analogous to AUFTRAGS_BESTAND

2.37. pps_leistung

Table name: pps_leistung		Product: BDE	
Archive table: a_pps_leistung		Reload table: r_pps_leistung	
Designation: Order activities (PPS)			
Column name	Column designation	Type	Description
ab_verweis		integer	Analogous to AUFTRAGS_LEISTUNG
auftrag_art		char(5)	Analogous to AUFTRAGS_LEISTUNG
auftrag_nr		char(40)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk01		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk01_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk02		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk02_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk03		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk03_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk04		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk04_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk05		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk05_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk06		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk06_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk07		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk07_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk08		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk08_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk09		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk09_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk10		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk10_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk11		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk11_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_bmk12		integer	Analogous to AUFTRAGS_LEISTUNG
soll_bmk12_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_dauer		integer	Analogous to AUFTRAGS_LEISTUNG
soll_dauer_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_ist01		decimal(18,6)	Analogous to AUFTRAGS_LEISTUNG
soll_ist01_einh		char(3)	Analogous to AUFTRAGS_LEISTUNG
soll_ist01_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_ist02		decimal(18,6)	Analogous to AUFTRAGS_LEISTUNG
soll_ist02_einh		char(3)	Analogous to AUFTRAGS_LEISTUNG
soll_ist02_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG
soll_ist03		decimal(18,6)	Analogous to AUFTRAGS_LEISTUNG
soll_ist03_einh		char(3)	Analogous to AUFTRAGS_LEISTUNG

soll Ist03_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist04		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist04_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist04_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist05		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist05_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist05_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist06		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist06_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist06_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist07		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist07_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist07_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist08		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist08_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist08_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist09		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist09_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist09_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll Ist10		decimal(18,6)	Analogous to AUFTRAGS LEISTUNG
soll Ist10_einh		char(3)	Analogous to AUFTRAGS LEISTUNG
soll Ist10_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk01		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk01_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk02		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk02_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk03		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk03_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk04		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk04_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk05		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk05_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk06		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk06_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk07		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk07_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk08		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk08_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk09		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk09_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk10		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk10_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk11		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk11_mod		char(1)	Analogous to AUFTRAGS LEISTUNG
soll p_bmk12		integer	Analogous to AUFTRAGS LEISTUNG
soll p_bmk12_mod		char(1)	Analogous to AUFTRAGS LEISTUNG

soll_p_dauer		integer	Analogous to AUFTRAGS_LEISTUNG
soll_p_dauer_mod		char(1)	Analogous to AUFTRAGS_LEISTUNG

2.38. pps_zusatz

Table name: pps_zusatz		Product: BDE	
Archive table: a_pps_zusatz		Reload table: r_pps_zusatz	
Designation: Order header - additional data (PPS)			
Column name	Column designation	Type	Description
ab_verweis		integer	Analogous to AUFTRAGS_ZUSATZ
arbplan_version		char(12)	Analogous to AUFTRAGS_ZUSATZ
auftrag_art		char(5)	Analogous to AUFTRAGS_ZUSATZ
auftrag_nr		char(40)	Analogous to AUFTRAGS_ZUSATZ
auftragsgruppe		char(4)	Analogous to AUFTRAGS_ZUSATZ
auftragsindex		decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
chargennr		char(20)	Analogous to AUFTRAGS_ZUSATZ
disponent		char(10)	Analogous to AUFTRAGS_ZUSATZ
dlz_minimal		integer	Analogous to AUFTRAGS_ZUSATZ
dlz_plan		integer	Analogous to AUFTRAGS_ZUSATZ
fert_version		char(10)	Analogous to AUFTRAGS_ZUSATZ
kalk_kost_lohn		decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
kalk_kost_masch		decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
kalk_kost_mat		decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
kalk_kost_sonst		decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
kd_auftrag		char(40)	Analogous to AUFTRAGS_ZUSATZ
kd_auftragpos		char(20)	Analogous to AUFTRAGS_ZUSATZ
kostentraeger		char(40)	Analogous to AUFTRAGS_ZUSATZ
mat_wert		decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
plan_auftrag		char(40)	Analogous to AUFTRAGS_ZUSATZ
proben_typ		char(1)	Analogous to AUFTRAGS_ZUSATZ
projekt_nr		char(25)	Analogous to AUFTRAGS_ZUSATZ
prueflosnr		char(20)	Analogous to AUFTRAGS_ZUSATZ
red_strategie		char(2)	Analogous to AUFTRAGS_ZUSATZ
red_stufe		smallint	Analogous to AUFTRAGS_ZUSATZ
schrott_wert		decimal(18,6)	Analogous to AUFTRAGS_ZUSATZ
steuerrezept		char(10)	Analogous to AUFTRAGS_ZUSATZ
stueli_version		char(12)	Analogous to AUFTRAGS_ZUSATZ
term_art		char(1)	Analogous to AUFTRAGS_ZUSATZ

2.39. sap_pp_conf

Table name: sap_pp_conf		Product: BDE	
Designation: Conf. KK2 check-back interface (CONF21)			
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing date	date	Last editing date
bearb_time	Last editing date	integer	Last editing date
ile01	Unit 1	char(3)	Unit for the activity 1 to be confirmed (possible: H/STD, MIN, SEC) (PDM field ID: SAPRMPP.EINH:1)
ile02	Unit 2	char(3)	Unit for the activity 2 to be confirmed (possible: H/STD, MIN, SEC) (PDM field ID: SAPRMPP.EINH:2)
ile03	Unit 3	char(3)	Unit for the activity 3 to be confirmed (possible: H/STD, MIN, SEC) (PDM field ID: SAPRMPP.EINH:3)
ile04	Unit 4	char(3)	Unit for the activity 4 to be confirmed (possible: H/STD, MIN, SEC) (PDM field ID: SAPRMPP.EINH:4)
ile05	Unit 5	char(3)	Unit for the activity 6 to be confirmed (possible: H/STD, MIN, SEC) (PDM field ID: SAPRMPP.EINH:5)
ile06	Unit 6	char(3)	Unit for the activity 7 to be confirmed (possible: H/STD, MIN, SEC) (PDM field ID: SAPRMPP.EINH:6)
ism01	Activity 1	char(71)	Activity 1 to be confirmed (PDM field ID: SAPRMPP.FORMEL:1)
ism02	Activity 2	char(71)	Activity 2 to be confirmed (PDM field ID: SAPRMPP.FORMEL:2)
ism03	Activity 3	char(71)	Activity 3 to be confirmed (PDM field ID: SAPRMPP.FORMEL:3)
ism04	Activity 4	char(71)	Activity 4 to be confirmed (PDM field ID: SAPRMPP.FORMEL:4)
ism05	Activity 5	char(71)	Activity 5 to be confirmed (PDM field ID: SAPRMPP.FORMEL:5)
ism06	Activity 6	char(71)	Activity 6 to be confirmed (PDM field ID: SAPRMPP.FORMEL:6)
masch_nr	Machine number	char(20)	Machine number If there is no data record for the actual machine (masch_nr) the data record with the machine "SYSTEM" is used. If SYSTEM entry is not available standard processing is carried out. (PDM field ID: SAPRMPP.MNR)

2.40. status_zusatz

Table name: status_zusatz		Product: BDE	
Designation: Status - addition		Description: The additional variables to be recorded for order and batch status are logged over the total runtime of the order/batch in this table. Additional values (e.g. counter) on the machine status can also be recorded here.	
Column name	Column designation	Type	Description
einheit		char(3)	Unit
erfass_art		char(2)	G : Yield quantity A : Scrap quantity H : Strokes ZZ : Additional counters Z : Time account L : Activity
grund		char(10)	Addit. reason, e.g. scrap reason
key_type		char(2)	A : Detail on the order status C : Detail on the batch status M : Detail on the machine status
param_01		integer	free
param_str1		char(20)	free
prot_dat		date	Date of the last update
prot_zeit		integer	Time of the last update
subkey1		char(20)	Machine number
subkey2		char(40)	Order number and OP number
subkey3		char(20)	Batch number
typ		char(10)	Type of the recording size HUB, GUT, AUS, LEN, BMK01...
wert		decimal(18,6)	Recorded value

3. CAQ

3.1. caq_abteilung

Table name: caq_abteilung		Product: CAQ	
Designation: Departments			
Column name	Column designation	Type	Description
abteilung_bez	Designation of the department/group	char(250)	Designation of the department or group (PDM field ID: ABT.ABTBEZ)
abteilung_nr	Identifier department/group	char(50)	Unique number of the department or group (PDM field ID: ABT.ABT)
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - active entry 1 - archived entry (PDM field ID: ABT.ARCHIV)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
email	E-Mail	char(250)	This entry is only relevant for departments and not for groups (GROUP_ITEM = 0). (PDM field ID: ABT.EMAIL)
firma_nr	Company the department/group belongs to	char(50)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). The companies are filed in the CAQ_FIRMA table. (PDM field ID: ABT.FIRID)
firma_typ	Company type the department/group belong	char(50)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). The companies are filed in the CAQ_FIRMA table. The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'FIRMENTYP') table (PDM field ID: ABT.FIRTYP)
group_1	Group indicator hierarchy level 1-5	char(50)	Identifier for departments and groups of hierarchy level 1-5 (PDM field ID: ABT.DSGRP:1)
group_2	Group indicator hierarchy level 1-5	char(50)	Identifier for departments and groups of hierarchy level 1-5 (PDM field ID: ABT.DSGRP:2)
group_3	Group indicator hierarchy level 1-5	char(50)	Identifier for departments and groups of hierarchy level 1-5 (PDM field ID: ABT.DSGRP:3)
group_4	Group indicator hierarchy level 1-5	char(50)	Identifier for departments and groups of hierarchy level 1-5 (PDM field ID: ABT.DSGRP:4)
group_5	Group indicator hierarchy level 1-5	char(50)	Identifier for departments and groups of hierarchy level 1-5 (PDM field ID: ABT.DSGRP:5)
group_item	Department or group ?	smallint	0 - Department 1 - Group (PDM field ID: ABT.DSGRPE)
pager	Pager number	char(250)	This entry is only relevant for departments and not for groups (GROUP_ITEM = 0). (PDM field ID: ABT.PAGER)
tel_mobile	Mobile	char(250)	This entry is only relevant for departments and not for groups (GROUP_ITEM = 0). (PDM field ID: ABT.HANDY)
telefax	Fax	char(250)	This entry is only relevant for departments and not for groups (GROUP_ITEM = 0). (PDM field ID: ABT.FAX)
telefon	Phone	char(250)	This entry is only relevant for departments and not for groups (GROUP_ITEM = 0). (PDM field ID: ABT.TEL)

verantw_flag	Party in charge	smallint	If the value of this field = 1, the corresponding entry is maintained in the caq_verantwortl table at each change. (PDM field ID: ABT.VERANT:COPY)
--------------	-----------------	----------	---

3.2. caq_analaus_eint

Table name: caq_analaus_eint		Product: CAQ	
Designation: Entries of the catalog for failure analysis			
Column name	Column designation	Type	Description
anlage	Created by User	char(50)	Created by User
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
eintrag_nr	Identifier of the entry	char(50)	'MASSKAT' - corresponding catalog entry can be found in the CAQ_MASSKAT table 'MERKMAL' - corresponding catalog entry can be found in the CAQ_MERKMAL (REC_TYPE = "; REC_REF = 'MEK) table 'KOSTENART' - corresponding catalog entry can be found in the CAQ_KOSTENART tale <ANALKR_TYP> - corresponding catalog entry can be found in the CAQ_ANALKAT (ANALKR_TYP = <ANALKR_TYP>) table (PDM field ID: CANAWEINT.EINTNR)
eintrag_typ	Type of the entry	char(50)	'MASSKAT' - entry is a catalog measure 'MERKMAL' - entry is a catalog characteristic 'KOSTENART' - entry is a cost type <ANALKR_TYP> - entry derives from the failure analysis catalog (Type: <ANALKR_TYP>) The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'ANAWEINTTYP') table. (PDM field ID: CANAWEINT.EINTTYP)
filter_typ	Type of the filter criterion	char(50)	INCLUDE - entry is regarded as include filter EXCLUDE - entry is regarded as exclude filter The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'ANAWFLTYP') table (PDM field ID: CANAWEINT.FLTYP)
zuordnung_nr	Number of the selection catalog	char(50)	The corresponding catalog for failure analysis selection can be found in the CAQ_ANALAUSSWAHL table. (PDM field ID: CANAWEINT.ANAUSNR)

3.3. caq_analauswahl

Table name: caq_analauswahl		Product: CAQ	
Designation: Catalog for failure analysis selection			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - current entry 1 - archived entry (PDM field ID: CANAUSW.ARCHIV)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
zuordnung_bez	Designation of selection catalog	char(50)	Designation of the catalog for analysis selection (PDM field ID: CANAUSW.ANAUSBEZ)
zuordnung_nr	Number of selection catalog	char(50)	Number of selection catalog (PDM field ID: CANAUSW.ANAUSNR)

3.4. caq_analkat

Table name: caq_analkat		Product: CAQ	
Designation: Failure analysis catalog			
Column name	Column designation	Type	Description
analkr_bez	Designation of the analysis criterion/gr	char(250)	Designation of the failure analysis criterion or group (PDM field ID: CERRKAT.ERRBEZ)
analkr_nr	Identifier analysis criterion/group	char(50)	Unique number of the failure analysis criterion or the group (unique within the corresponding type) (PDM field ID: CERRKAT.ERRNR)
analkr_typ	Type of analysis criterion/group	char(50)	The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'FHLANTYP') table (PDM field ID: CERRKAT.ERRTYP)
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - current entry 1 - archived entry (PDM field ID: CERRKAT.ARCHIV)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
group_1	Group indicator hierarchy level 1-5	char(50)	Identifier for failure analysis criteria and groups of the hierarchy level 1-5 (PDM field ID: CERRKAT.DSGRP:1)
group_2	Group indicator hierarchy level 1-5	char(50)	Identifier for failure analysis criteria and groups of the hierarchy level 1-5 (PDM field ID: CERRKAT.DSGRP:2)
group_3	Group indicator hierarchy level 1-5	char(50)	Identifier for failure analysis criteria and groups of the hierarchy level 1-5 (PDM field ID: CERRKAT.DSGRP:3)
group_4	Group indicator hierarchy level 1-5	char(50)	Identifier for failure analysis criteria and groups of the hierarchy level 1-5 (PDM field ID: CERRKAT.DSGRP:4)
group_5	Group indicator hierarchy level 1-5	char(50)	Identifier for failure analysis criteria and groups of the hierarchy level 1-5 (PDM field ID: CERRKAT.DSGRP:5)
group_item	Analysis criterion or group?	smallint	0 - Analysis criterion 1 - Group (PDM field ID: CERRKAT.DSGRPE)

3.5. caq_artikel

Table name: caq_artikel		Product: CAQ	
Designation: Article catalog		Description: The table administers articles and their groups	
Column name	Column designation	Type	Description
agvfa	Specific weight	decimal(18,6)	(PDM field ID: ARTIKEL.AGVFA)
anlage	Created by	char(50)	
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - current entry 1 - archived entry (PDM field ID: ARTIKEL.ARCHIV)
artikel_abc	Item A, B or C?	char(250)	This entry is only relevant for articles and not for groups (GROUP_ITEM = 0). (PDM field ID: ARTIKEL.ABC)
artikel_bez	Article or group designation	char(250)	Designation of article or group (PDM field ID: ARTIKEL.ATKBEZ)
artikel_gruppe	Article group	char(50)	This entry is only relevant for articles and not for groups (GROUP_ITEM = 0). (PDM field ID: ARTIKEL.ATKGRP)
artikel_idx	Drawing issue number (article index);	char(50)	Drawing issue number (article index); this entry is only kept for articles not for groups (PDM field ID: ARTIKEL.ATKIDX)
artikel_modell	Model	char(250)	This entry is only relevant for articles and not for groups (GROUP_ITEM = 0). (PDM field ID: ARTIKEL.MOD)
artikel_nr	Number of the article or group	char(50)	Number of the article or group (PDM field ID: ARTIKEL.ATK)
artikel_nr_kunde	Customer article number	char(50)	Customer article number (PDM field ID: ARTIKEL.ATK:KDNR)
ausg_material	End products	char(1)	(PDM field ID: ARTIKEL.OPT:AUSGMAT)
batch_dft_qty_in	Default quantity of input batches	decimal(18,6)	Default quantity of input batches (PDM field ID: ARTIKEL.QTY:DBQI)
batch_dft_qty_out	Default quantity for output batches	decimal(18,6)	Default quantity for output batches (PDM field ID: ARTIKEL.QTY:DBQO)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dokpflicht	Documentation required?	smallint	This entry is only relevant for articles and not for groups (GROUP_ITEM = 0). (PDM field ID: ARTIKEL.DOKPFL)
eing_material	Input material	char(1)	(PDM field ID: ARTIKEL.OPT:EINGMAT)
einheit	Unit	char(50)	This entry is only relevant for articles and not for groups (GROUP_ITEM = 0). The units are filed in the CAQ_EINHEIT table. (PDM field ID: ARTIKEL.CEINH)
fragm_gr	Fragmented size	decimal(18,6)	(PDM field ID: ARTIKEL.FRAGMGR)
group_1	Group indicator hierarchy level 1-5	char(50)	Identifier for articles and groups of the hierarchy level 1-5 (PDM field ID: ARTIKEL.DSGRP:1)
group_2	Group indicator hierarchy level 1-5	char(50)	Identifier for articles and groups of the hierarchy level 1-5 (PDM field ID: ARTIKEL.DSGRP:2)

group_3	Group indicator hierarchy level 1-5	char(50)	Identifier for articles and groups of the hierarchy level 1-5 (PDM field ID: ARTIKEL.DSGRP:3)
group_4	Group indicator hierarchy level 1-5	char(50)	Identifier for articles and groups of the hierarchy level 1-5 (PDM field ID: ARTIKEL.DSGRP:4)
group_5	Group indicator hierarchy level 1-5	char(50)	Identifier for articles and groups of the hierarchy level 1-5 (PDM field ID: ARTIKEL.DSGRP:5)
group_item	article or group?	smallint	0 - article 1- group (PDM field ID: ARTIKEL.DSGRPE)
hz_typ	Material type	char(10)	 (PDM field ID: ARTIKEL.MATTYP)
id	Unique article id	serial	
kbn_artikel	Kanban material	char(1)	Flag Kanban material [Y/N] (PDM field ID: ARTIKEL.OPT:KBNATK)
mat_puf	Stock location	char(21)	 (PDM field ID: ARTIKEL.MATPUF)
material_kfaktor	Correction factor of material	float	By means of this field the inspection quantity is calculated for time wage. (PDM field ID: ARTIKEL.MATKFAK)
msl_comment	Future use	char(50)	
msl_expire_period	Future use	integer	
msl_level	Future use	char(20)	
msl_material	Future use	char(1)	
output_batch_qty_violation	Flag how to deal with default quantity violation	char(1)	Flag how to deal with default quantity violation (PDM field ID: ARTIKEL.QTY:DBQV)
preis	Price	decimal(18,6)	 (PDM field ID: ARTIKEL.KOST)
preis_avg	Average Price	decimal(18,6)	 (PDM field ID: ARTIKEL.KOSTAVG)
schrott_material	Scrap (composition)	char(1)	 (PDM field ID: ARTIKEL.OPT:SCHROTT)
user_c_29	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:29)
user_c_30	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:30)
user_c_31	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:31)
user_c_32	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:32)
user_c_33	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:33)
user_c_34	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:34)
user_c_35	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:35)
user_c_36	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:36)
user_c_37	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:37)
user_c_38	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:38)
user_c_39	userfield	char(1)	 (PDM field ID: ARTIKEL.FU:39)

user_c_40	userfield	char(1)	(PDM field ID: ARTIKEL.FU:40)
user_c_41	userfield	char(1)	(PDM field ID: ARTIKEL.FU:41)
user_c_42	userfield	char(1)	(PDM field ID: ARTIKEL.FU:42)
user_c_43	userfield	char(1)	(PDM field ID: ARTIKEL.FU:43)
user_c_44	userfield	char(1)	(PDM field ID: ARTIKEL.FU:44)
user_c_45	userfield	char(10)	(PDM field ID: ARTIKEL.FU:45)
user_c_46	userfield	char(10)	(PDM field ID: ARTIKEL.FU:46)
user_c_47	userfield	char(10)	(PDM field ID: ARTIKEL.FU:47)
user_c_48	userfield	char(10)	(PDM field ID: ARTIKEL.FU:48)
user_c_49	userfield	char(10)	(PDM field ID: ARTIKEL.FU:49)
user_c_50	userfield	char(10)	(PDM field ID: ARTIKEL.FU:50)
user_c_51	userfield	char(20)	(PDM field ID: ARTIKEL.FU:51)
user_c_52	userfield	char(20)	(PDM field ID: ARTIKEL.FU:52)
user_c_53	userfield	char(20)	(PDM field ID: ARTIKEL.FU:53)
user_c_54	userfield	char(20)	(PDM field ID: ARTIKEL.FU:54)
user_c_55	userfield	char(20)	(PDM field ID: ARTIKEL.FU:55)
user_c_56	userfield	char(20)	(PDM field ID: ARTIKEL.FU:56)
user_c_57	userfield	char(20)	(PDM field ID: ARTIKEL.FU:57)
user_c_58	userfield	char(20)	(PDM field ID: ARTIKEL.FU:58)
user_c_59	userfield	char(20)	(PDM field ID: ARTIKEL.FU:59)
user_c_60	userfield	char(20)	(PDM field ID: ARTIKEL.FU:60)
user_c_61	userfield	char(20)	(PDM field ID: ARTIKEL.FU:61)
user_c_62	userfield	char(20)	(PDM field ID: ARTIKEL.FU:62)
user_c_63	userfield	char(20)	(PDM field ID: ARTIKEL.FU:63)
user_c_64	userfield	char(20)	(PDM field ID: ARTIKEL.FU:64)
user_c_65	userfield	char(40)	(PDM field ID: ARTIKEL.FU:65)
user_c_66	userfield	char(40)	(PDM field ID: ARTIKEL.FU:66)

user_code	userfield code	char(8)	(PDM field ID: ARTIKEL.USRFLD)
user_d_01	userfield	date	(PDM field ID: ARTIKEL.FU:1)
user_d_02	userfield	date	(PDM field ID: ARTIKEL.FU:2)
user_d_03	userfield	date	(PDM field ID: ARTIKEL.FU:3)
user_d_04	userfield	date	(PDM field ID: ARTIKEL.FU:4)
user_d_05	userfield	date	(PDM field ID: ARTIKEL.FU:5)
user_d_06	userfield	date	(PDM field ID: ARTIKEL.FU:6)
user_f_23	userfield	decimal(18,6)	(PDM field ID: ARTIKEL.FU:23)
user_f_24	userfield	decimal(18,6)	(PDM field ID: ARTIKEL.FU:24)
user_f_25	userfield	decimal(18,6)	(PDM field ID: ARTIKEL.FU:25)
user_f_26	userfield	decimal(18,6)	(PDM field ID: ARTIKEL.FU:26)
user_f_27	userfield	decimal(18,6)	(PDM field ID: ARTIKEL.FU:27)
user_f_28	userfield	decimal(18,6)	(PDM field ID: ARTIKEL.FU:28)
user_n_07	userfield	integer	(PDM field ID: ARTIKEL.FU:7)
user_n_08	userfield	integer	(PDM field ID: ARTIKEL.FU:8)
user_n_09	userfield	integer	(PDM field ID: ARTIKEL.FU:9)
user_n_10	userfield	integer	(PDM field ID: ARTIKEL.FU:10)
user_n_11	userfield	integer	(PDM field ID: ARTIKEL.FU:11)
user_n_12	userfield	integer	(PDM field ID: ARTIKEL.FU:12)
user_n_13	userfield	integer	(PDM field ID: ARTIKEL.FU:13)
user_n_14	userfield	integer	(PDM field ID: ARTIKEL.FU:14)
user_n_15	userfield	integer	(PDM field ID: ARTIKEL.FU:15)
user_n_16	userfield	integer	(PDM field ID: ARTIKEL.FU:16)
user_n_17	userfield	integer	(PDM field ID: ARTIKEL.FU:17)
user_n_18	userfield	integer	(PDM field ID: ARTIKEL.FU:18)
user_n_19	userfield	integer	(PDM field ID: ARTIKEL.FU:19)
user_n_20	userfield	integer	(PDM field ID: ARTIKEL.FU:20)

user_n_21	userfield	integer	(PDM field ID: ARTIKEL.FU:21)
user_n_22	userfield	integer	(PDM field ID: ARTIKEL.FU:22)
zeichnung_nr	Drawing number	char(250)	This entry is only relevant for articles and not for groups (GROUP_ITEM = 0). (PDM field ID: ARTIKEL.ZEICHNR)

3.6. caq_ausw_param

Table name: caq_ausw_param		Product: CAQ	
Designation: Analyses parameters			
Column name	Column designation	Type	Description
anlage	created by	char(50)	
anlage_date	Initial data creation - Date	date	
anlage_time	Initial data creation - Time	integer	
auswert_art	Analysis type	char(50)	Auswertungen sind in der Tabelle CAQ_AUSWERTUNG abgelegt. CAQ_GIS - globales Informationssystem CAQ_FSA - Fehlerschwerpunktanalyse CAQ_REK - Reklamationsauswertung CAQ_KST - Kostenauswertung (PDM field ID: CAUSWPAR.AUSWART)
auswert_name	Analysis name	char(100)	Auswertungen sind in der Tabelle CAQ_AUSWERTUNG abgelegt. (PDM field ID: CAUSWPAR.AUSWNAME)
bearb	Last editor	char(50)	
bearb_date	Last change - Date	date	
bearb_time	Last change - Time	integer	
daten_typ	Data type	char(50)	Auswertungen sind in der Tabelle CAQ_AUSWERTUNG abgelegt. FILTER - gespeicherte Daten sind Filter DARSTELLUNG - gespeicherte Daten sind Anzeigoptionen KOMPLETT - gespeicherte Daten sind Filter und Anzeigoptionen (PDM field ID: CAUSWPAR.DATENTYP)
param_name	Parameter identificator	char(50)	 (PDM field ID: CAUSWPAR.PARNAME)
position	Position	integer	 (PDM field ID: CAUSWPAR.POS)
wert_char	Alphanumeric parameter value	char(1464)	 (PDM field ID: CAUSWPAR.WERT:CHAR)

3.7. caq_auswertung

Table name: caq_auswertung		Product: CAQ	
Designation: Saved Analyses			
Column name	Column designation	Type	Description
anlage	created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Date when the entry was created
auswert_art	Analysis type	char(50)	CAQ_GIS - globales Informationssystem CAQ_FSA - Fehlerschwerpunktanalyse CAQ_REK - Reklamationsauswertung CAQ_KST - Kostenauswertung (PDM field ID: CAUSWERT.AUSWART)
auswert_name	Analysis name	char(100)	(PDM field ID: CAUSWERT.AUSWNAME)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
daten_typ	Data type	char(50)	(PDM field ID: CAUSWERT.DATENTYP)
user_list	User list	char(1464)	(PDM field ID: CAUSWERT.USERLIST)
zusatz	Additional analysis filter	char(250)	AUSWERT_ART = 'CAQ_FSA' GLOBAL - globale FSA WEP FEP WAP REK AUSWERT_ART = 'CAQ_KOSTEN' (PDM field ID: CAUSWERT.ZUSATZ)

3.8. caq_bereich

Table name: caq_bereich		Product: CAQ	
Designation: Areas		Description: The table administers the areas of CAQ	
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich_bezk	Short name of area	char(250)	Short name of area (PDM field ID: CBEREICH.BERBEZK)
bereich_bezl	Long name of area	char(250)	Long name of area (PDM field ID: CBEREICH.BERBEZL)
bereich_nr	Identifier of the area	char(50)	Identifier of the area (PDM field ID: CBEREICH.BER)
bereich_typ	Validity of module(s).	char(250)	Validity of module(s). The following entries of modules are possible: [WEP] Goods receipt inspection [FEP] In-production inspection [WAP] Goods issue inspection [PMV] Gage management [REK] Complaint management [LFB] Supplier evaluation [CPL] Production control plan [QMS] QM subsystem [EMU] - Initial sampling testing [COMP] - Composition [EMG] - Energy management (PDM field ID: CBEREICH.BERTYP)
position	Position in lists	smallint	Position in lists (PDM field ID: CBEREICH.POS)
verantw_bereich	Responsibility area	char(15)	
zusatz	MASCHF] - the machine capability is calc	char(250)	[MASCHF] - The machine capability is calculated in this area [AUTOMM_PPL] - Area with only process characteristics [QMS_ART:x] - Assignment to QM-IDI parameter QAILS.HERKUNFT (PDM field ID: CBEREICH.ZUSATZ)

3.9. caq_bew_ausw_grp

Table name: caq_bew_ausw_grp		Product: CAQ	
Designation: Evaluation groups for assessment element			
Column name	Column designation	Type	Description
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
auswgrp_bez	Identifier of evaluation group	char(250)	Identifier of evaluation group (PDM field ID: CBWAUSGR.AUSWGRPBEZ)
auswgrp_id	Identifier of evaluation group	char(50)	Identifier of evaluation group (PDM field ID: CBWAUSGR.AUSWGRP)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time

3.10. caq_bew_auswahl

Table name: caq_bew_auswahl		Product: CAQ	
Designation: Selection for assessment catalogs			
Column name	Column designation	Type	Description
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
auswahl_bez	Designation of the selection	char(250)	Designation of the selection (PDM field ID: CBWAUSW.AUSWBEZ)
auswahl_id	Identifier of the selection	char(50)	Identifier of the selection (PDM field ID: CBWAUSW.AUSWAHL)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bemerkung	Comment	char(250)	Comment (PDM field ID: CBWAUSW.BEM)
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CBWAUSW.BER)
gis_key	GIS - key	char(50)	Key value to reference the GIS entry
key_1	Identifier 1	integer	At REC_REF = 'KAT' --> corresponds to the number of the respective assessment catalog At REC_REF = 'BEW' --> corresponds to the number of the corresponding assessment (PDM field ID: CBWAUSW.KEY:1,BWKATNR,BEWNr)
key_2	Identifier 2	integer	Corresponds to the BAUMNR of the corresponding element. If zero is entered in the field the selection is directly assigned to the catalog or assessment. (PDM field ID: CBWAUSW.KEY:2,ELEMNR)
key_3	Identifier 3	integer	Identifier 3 (PDM field ID: CBWAUSW.KEY:3)
key_4	Identifier 4	integer	Identifier 4 (PDM field ID: CBWAUSW.KEY:4)
key_5	Identifier 5	integer	Identifier 5 (PDM field ID: CBWAUSW.KEY:5)
rec_ref	Data reference	char(20)	'KAT' = Selection of the assessment catalog or an element thereof 'BEW' = Selection of an assessment or an element thereof (PDM field ID: CBWAUSW.RECREF)
rec_type	Type of the entry	char(50)	'LFB' = Supplier evaluation (PDM field ID: CBWAUSW.RECTYP)
wert	Numerical value of the selection	float	Numerical value of the selection (PDM field ID: CBWAUSW.AUSWWERT)

3.11. caq_bew_bewert

Table name: caq_bew_bewert		Product: CAQ	
Designation: Evaluations			
Column name	Column designation	Type	Description
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
artikel_idx	Drawing issue number	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CBWBEW.ATKIDX)
artikel_nr	Article number	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CBWBEW.ATK)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CBWBEW.BER)
beurt_gegenstand	Subject of evaluation	char(50)	 (PDM field ID: CBWBEW.BEURT:GSTAND)
beurteilter_id	Evaluated organization identification	char(50)	 (PDM field ID: CBWBEW.BEURT:ID)
beurteilter_typ	Evaluated organization type	char(50)	 (PDM field ID: CBWBEW.BEURT:TYP)
bewert_art	Evaluation type	char(50)	 (PDM field ID: CBWBEW.BEWART)
bewert_bis	Evaluation period to	date	Evaluation period (PDM field ID: CBWBEW.ZEITRBIS)
bewert_nr	Number of the evaluation	integer	Unique, numeric identifier (PDM field ID: CBWBEW.BEWNR)
bewert_typ	Type of rating	char(50)	The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'BEWTYP') table 'AUTO' = generated automatically 'MAN' = generated manually (PDM field ID: CBWBEW.BEWTYP)
bewert_von	Evaluation period from	date	Evaluation period (PDM field ID: CBWBEW.ZEITRAB)
bewkat_nr	Number of the assessment catalog	integer	The valid entries can be found in the CAQ_BEW_KATALOG table. (PDM field ID: CBWBEW.BWKATNR)
einstuf_date	Date of rating	date	Date of rating (PDM field ID: CBWBEW.EINSTDAT)
einstuf_time	Time of rating	integer	Time of rating (PDM field ID: CBWBEW.EINSTZEI)
einstuf_wert	Degree of fulfillment in percent	float	Degree of fulfillment in percent (PDM field ID: CBWBEW.WERT)
firma_nr	Identifier of the company	char(50)	Valid entry of the CAQ_FIRMA table (PDM field ID: CBWBEW.FIRID)
firma_typ	Type of the company	char(50)	The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'FIRMENTYP') table 'KUNDE' = Customer 'HERSTELLER' = Manufacturer 'LIEFERANT' = Supplier (PDM field ID: CBWBEW.FIRTYP)

gewichtung	Weighting	float	This field determines the weighting in percent (0...100%) which influences article-related assessments of a supplier with respect to the overall evaluation (of the supplier). (PDM field ID: CBWBEW.GEWICHTUNG)
gis_key	GIS key	char(50)	Reference to data from the caq_gis table.
klasse_id	Class assigned to the rating	char(50)	The valid entries can be found in the CAQ_BEW_KLASSE table. (PDM field ID: CBWBEW.KLASSE)
rec_type	Type of the entry	char(50)	'LFB' = Supplier evaluation (PDM field ID: CBWBEW.RECTYP)
status	Status	char(50)	Valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'BEWSTATUS') table (PDM field ID: CBWBEW.STA)

3.12. caq_bew_element

Table name: caq_bew_element		Product: CAQ	
Designation: Assessment elements (groups + criteria)			
Column name	Column designation	Type	Description
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created	integer	Time when the entry was created.
auswahl_elem	Element number that contains the selecti	integer	Element number that contains the selection (PDM field ID: CBWELEM.AUSWAHL:ELEM)
auswahl_id	Selection assigned to the rating	char(50)	Selection assigned to the rating (PDM field ID: CBWELEM.AUSWAHL)
auswgrp_id	Group identifiers for evaluations	char(50)	Group identifiers for evaluations (PDM field ID: CBWELEM.AUSWGRP)
baum_nr	Element number	integer	Unique identifier of the element within an assessment catalog or an evaluation. (PDM field ID: CBWELEM.ELEMNR)
baum_parent	Predecessor within the element tree	integer	Element number of the direct predecessor. (PDM field ID: CBWELEM.PARENT)
baum_pos	Position within the element tree	integer	Unique number within the element tree that includes the absolute index (PDM field ID: CBWELEM.POS)
baum_typ	Type of the element	char(50)	'GRP' = Evaluation group 'KRT' = Assessment criterion (PDM field ID: CBWELEM.ELEMTYP)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CBWELEM.BER)
element_bez	Designation of the element	char(250)	Designation of the element (PDM field ID: CBWELEM.ELEMBEZ)
gewichtung	Weighting of the element	float	Weighting of the criterion or the group within the superordinate group. (PDM field ID: CBWELEM.GEWICHTUNG)
gis_key	GIS key	char(50)	Key value to reference the GIS entry
key_1	Identifier 1	integer	If REC_REF = 'KAT' --> corresponds to the number of the appropriate assessment catalog If REC_REF = 'BEW' --> corresponds to the number of the appropriate evaluation. (PDM field ID: CBWELEM.KEY:1,BWKATNR,BEWNr)
key_2	Identifier 2	integer	Identifier (PDM field ID: CBWELEM.KEY:2)
key_3	Identifier 3	integer	Identifier (PDM field ID: CBWELEM.KEY:3)
key_4	Identifier 4	integer	Identifier (PDM field ID: CBWELEM.KEY:4)
key_5	Identifier 5	integer	Identifier (PDM field ID: CBWELEM.KEY:5)
klasse_elem	Element number that contains the rating	integer	Element number that contains the rating (PDM field ID: CBWELEM.KLASSE:ELEM)
klasse_id	Class assigned to the rating	char(50)	The valid entries can be found in the CAQ_BEW_KLASSE table. (PDM field ID: CBWELEM.KLASSE)
programm	Name of the source program	char(250)	Only interesting if QUELLE = 'PROGRAMM' (PDM field ID: CBWELEM.QPROG)

quelle	Source of the rating value	char(50)	'PROGRAMM' = Program 'AUDITERG' = Audit result 'EINGABE' = Manual input (PDM field ID: CBWELEM.QUELLE)
rec_ref	Data reference	char(20)	'KAT' = Class of the assessment catalog or an element thereof 'BEW' = Class of an assessment or an element thereof (PDM field ID: CBWELEM.RECREF)
rec_type	Type of the entry	char(50)	'LFB' = Supplier evaluation (PDM field ID: CBWELEM.RECTYP)
rueck_code	Return code of the program to be started	char(50)	Only interesting if QUELLE = 'PROGRAMM' (PDM field ID: CBWELEM.PRGRGT:CODE)
rueck_text	Return text of the program to be started	char(250)	Only interesting if QUELLE = 'PROGRAMM' (PDM field ID: CBWELEM.PRGRGT:TEXT)
wert_dec	Decimal value of the rating	float	Decimal value of the rating (PDM field ID: CBWELEM.WERT:DEC)
wert_proz	Percentage value of the rating	float	Percentage value of the rating (PDM field ID: CBWELEM.WERT:PROZ)
zielwert	Target value	float	For programs to be started the target value determines the maximum of the rating value that can be reached. (PDM field ID: CBWELEM.ZIELW)

3.13. caq_bew_kat_fir

Table name: caq_bew_kat_fir		Product: CAQ	
Designation: Assessment catalogs assigned to companie			
Column name	Column designation	Type	Description
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CBWKFIR.BER)
bewkat_id	Identifier of the assessment catalog	char(50)	Valid entries can be found in the CAQ_BEW_KATALOG table. (PDM field ID: CBWKATFIR.BWKATID)
firma_nr	Identifier of the company	char(50)	Valid entry of the CAQ_FIRMA table (PDM field ID: CBWKATFIR.FIRID)
firma_typ	Type of company entry	char(50)	Valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'FIRMENTYP') table 'KUNDE' = Customer 'HERSTELLER' = Manufacturer 'LIEFERANT' = Supplier (PDM field ID: CBWKATFIR.FIRTYP)
rec_type	Type of the entry	char(50)	"LFB" = Supplier evaluation (PDM field ID: CBWKATFIR.RECTYP)

3.14. caq_bew_katalog

Table name: caq_bew_katalog		Product: CAQ	
Designation: Assessment catalogs			
Column name	Column designation	Type	Description
aktiv	Active	smallint	Released (PDM field ID: CBWKAT.AKTIV)
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bemerkung	Comment	char(250)	Comment (PDM field ID: CBWKAT.BEM)
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CBWKAT.BER)
bewkat_bez	Designation of the assessment catalog	char(250)	Designation of the assessment catalog (PDM field ID: CBWKAT.BWKATBEZ)
bewkat_id	Identifier of the evaluation catalog	char(50)	Identifier of the assessment catalog (PDM field ID: CBWKAT.BWKATID)
bewkat_idx	Index of the evaluation catalog	char(50)	Index of the evaluation catalog (PDM field ID: CBWKAT.BWKATIDX)
bewkat_nr	Number of the evaluation catalog	integer	Unique, numeric identifier (PDM field ID: CBWKAT.BWKATNR)
freigabe	Released	smallint	Released (PDM field ID: CBWKAT.FREI)
freigabe_date	Release date	date	Release date (PDM field ID: CBWKAT.FREIDAT)
freigabe_durch	Released by	char(50)	Released by (PDM field ID: CBWKAT.FREIVON)
gis_key	GIS key	char(50)	GIS key
rec_type	Type of the entry	char(50)	'LFB' = Supplier evaluation (PDM field ID: CBWKAT.RECTYP)
verantw_nr	Party in charge - number	char(50)	Party in charge - number (PDM field ID: CBWKAT.VERANT:NR)
verantw_typ	Party in charge - type	char(50)	The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'VERANTWTYP') table (PDM field ID: CBWKAT.VERANT:TYP)

3.15. caq_bew_klasse

Table name: caq_bew_klasse		Product: CAQ	
Designation: Classes for assessment catalogs			
Column name	Column designation	Type	Description
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bemerkung	Comment	char(250)	Comment (PDM field ID: CBWKLASSE.BEM)
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CBWKLASSE.BER)
gis_key	GIS key	char(50)	Key value to reference the GIS entry
key_1	Identifier 1	integer	If REC_REF = 'KAT' --> corresponds to the number of the appropriate assessment catalog If REC_REF = 'BEW' --> corresponds to the number of the appropriate evaluation (PDM field ID: CBWKLASSE.KEY:1,BWKATNR,BEWNr)
key_2	Identifier 2	integer	Corresponds to the BAUMNR of the corresponding element. If zero is entered in the field the class is directly assigned to the catalog or the evaluation. (PDM field ID: CBWKLASSE.KEY:2,ELEMNR)
key_3	Identifier 3	integer	Identifier (PDM field ID: CBWKLASSE.KEY:3)
key_4	Identifier 4	integer	Identifier (PDM field ID: CBWKLASSE.KEY:4)
key_5	Identifier 5	integer	Identifier (PDM field ID: CBWKLASSE.KEY:5)
klasse_bez	Designation of the class	char(250)	Designation of the class (PDM field ID: CBWKLASSE.KLASBEZ)
klasse_id	Identifier of the class	char(50)	Identifier of the class (PDM field ID: CBWKLASSE.KLASSE)
rec_ref	Data reference	char(20)	'KAT' = Class of the assessment catalog or an element thereof 'BEW' = Class of an evaluation or an element thereof (PDM field ID: CBWKLASSE.RECREF)
rec_type	Type of the entry	char(50)	'LFB' = Supplier evaluation (PDM field ID: CBWKLASSE.RECTYP)
wert	Numeric value of the class	float	Value in percent as of which the class is used for the rating (lower limit value). (PDM field ID: CBWKLASSE.KLASWERT)

3.16. caq_ctrl_freig

Table name: caq_ctrl_freig		Product: CAQ	
Designation: Activation of production control plans			
Column name	Column designation	Type	Description
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CCPLFREIG.BER)
ctrlplan_nr	Internal, numeric control plan number	integer	(PDM field ID: CCPLFREIG.CPLNR)
freigabe_date	Release date	date	(PDM field ID: CCPLFREIG.FREIDAT)
freigabe_time	Release time	integer	(PDM field ID: CCPLFREIG.FREIZEI)
rec_type	Type of the entry	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CCPLFREIG.RECTYP)
verantw_nr	Party in charge	char(50)	(PDM field ID: CCPLFREIG.VERANT:NR)
verantw_typ	Party in charge type	char(50)	(PDM field ID: CCPLFREIG.VERANT:TYP)

3.17. caq_ctrl_plan

Table name: caq_ctrl_plan		Product: CAQ	
Designation: Production control plans			
Column name	Column designation	Type	Description
aktiv	Control plan active?	smallint	0: Control plan inactive 1: Control plan active (PDM field ID: CCPL.AKTIV)
anlage	Created by	char(50)	
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
artikel_idx	Drawing issue number (article index)	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CCPL.ATKIDX)
artikel_nr	Number of the article or group	char(50)	Number of the article or group (PDM field ID: CCPL.ATK)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CCPL.BER)
ctrlplan_id	Control plan number	char(50)	Control plan number (PDM field ID: CCPL.CPLID)
ctrlplan_idx	Control plan index	char(50)	Control plan index (PDM field ID: CCPL.CPLIDX)
ctrlplan_nr	Internal, numeric control plan number	integer	- is used for nearly all JOINS (PDM field ID: CCPL.CPLNR)
freigabe	Release control plan?	smallint	0: Control plan not released 1: Control plan released (PDM field ID: CCPL.FREI)
freigabe_date	Release date	date	Release date (PDM field ID: CCPL.FREIDAT)
freigabe_durch	Released by	char(50)	Released by (PDM field ID: CCPL.FREIVON)
gis_key	GIS key	char(50)	GIS key
gueltig_bis	End of validity period	date	Validity period (PDM field ID: CCPL.GUELTBIS)
gueltig_von	Start of validity period	date	validity period (PDM field ID: CCPL.GUELTAB)
hersteller_nr	Manufacturer number	char(50)	Manufacturers are defined in the CAQ_FIRMA table. (PDM field ID: CCPL.HERSTNR)
kunde_nr	Customer number	char(50)	Customers are defined in the CAQ_FIRMA table. (PDM field ID: CCPL.KDNR)
lieferant_nr	Supplier number	char(50)	Suppliers are defined in the CAQ_FIRMA table. (PDM field ID: CCPL.LIEFNR)
rec_type	Type of the entry	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CCPL.RECTYP)

verteiler_nr	Distribution list (team)	char(50)	Distribution list (team) (PDM field ID: CCPL.VERTNR)
zeichnung_nr	Drawing number	char(250)	Drawing number (PDM field ID: CCPL.ZEICHNNR)

3.18. caq_ctrl_pplan

Table name: caq_ctrl_pplan		Product: CAQ	
Designation: Inspection plan references of production			
Column name	Column designation	Type	Description
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
arbgang_bez	Operation designation	char(250)	Operation designation (PDM field ID: CCPLPPL.AGBEZ)
arbgang_nr	Operation number	char(50)	Operation number (PDM field ID: CCPLPPL.AGNR)
artikel_idx	Drawing issue number (article index)	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CCPLPPL.ATKIDX)
artikel_nr	Number of the article or group	char(50)	Number of the article or group (PDM field ID: CCPLPPL.ATK)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CCPLPPL.BER)
ctrlplan_nr	Internal, numeric control plan number	integer	 (PDM field ID: CCPLPPL.CPLNR)
gis_key	GIS key	char(50)	GIS key
hersteller_nr	Manufacturer number	char(50)	Manufacturers are defined in the CAQ_FIRMA table. (PDM field ID: CCPLPPL.HERSTNR)
kunde_nr	Customer number	char(50)	Customers are defined in the CAQ_FIRMA table. (PDM field ID: CCPLPPL.KDNR)
lieferant_nr	Supplier number	char(50)	Suppliers are defined in the CAQ_FIRMA table. (PDM field ID: CCPLPPL.LIEFNR)
maschine_nr	Machine number	char(20)	Machine number
position	Position	integer	Position (PDM field ID: CCPLPPL.POS)
prplan_bereich	Area of the referenced inspection	char(10)	 (PDM field ID: CCPLPPL.PPL:BER)
prplan_nr	Internal, numeric inspection plan number	integer	- is used for nearly all JOINS (PDM field ID: CCPLPPL.PPL:PPLNR)
prplan_rectype	Input type of the referenced inspection	char(50)	 (PDM field ID: CCPLPPL.PPL:RECTYP)
prplan_refnr	Inspection plan reference number	integer	 (PDM field ID: CCPLPPL.PPL:REF)
rec_type	Input type	char(50)	"WEP" ' ' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CCPLPPL.RECTYP)

3.19. caq_dokus

Table name: caq_dokus		Product: CAQ	
Archive table: a_caq_dokus		Reload table: r_caq_dokus	
Designation: Documents		Description: Objective: The spreadsheet manages the document entries. These document entries may include links to files or URLs. Alternatively, multiline texts can be filed here. The doku_typ field decides on the type of the document entry. If texts with more than 250 characters are to be filed they are distributed to the fields text_1 to text_10 in character strings of 250 characters each. Word-wraps are masked via the character string ~"~ (ASCII: 126, 33, 126).	
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CDOKUM.BER,CPPLDOK.BER)
doklist_nr	SERIAL of the entry	serial	
doku_bez	Designation	char(250)	Document designation (PDM field ID: CDOKUM.DOKBEZ,CMMDOK.DOKBEZ,...DOKBEZ)
doku_nr	Consecutive number	integer	Consecutive number which determines the document entry in the list of assigned documents (PDM field ID: CDOKUM.DOKNR,CMMDOK.DOKNR,CPPLDOK.DOKNR)
doku_typ	Type of the entry	char(50)	'TEXT' - Text document (fields text_1 ... text_10 assigned) 'DATEI' - Reference to a file (field doku_url assigned) 'URL' - reference to an URL (field doku_url assigned) (PDM field ID: CDOKUM.DOKTYP,CMMDOK.DOKTYP,...DOKTYP)
doku_url	URL of a document	char(250)	./<Dateiname/-pfad> - Reference to a file within the host computer directory (PDM field ID: CDOKUM.DOKURL,CMMDOK.DOKURL,...DOKURL)
key_1	Identifier 1	integer	If REC_REF = "MEK" to be equated with the characteristics number If REC_REF = "PPL" to be equated with the inspection plan number If REC_REF = "PAN", "PAU" to be equated with the parameter CDOKUM.PANNR (inspection requirement number) If REC_REF = "RKK", "RKD" to be equated with the parameter CDOKUM.REKNR (complaints number) If REC_REF = "PMK" to be equated with the parameter CDOKUM.PMNR (gage number) If REC_REF = "CPL" to be equated with the parameter CDOKUM.CPLNR (control plan number) (PDM field ID: CDOKUM.KEY:1,CMMDOK.LFDNR,CPPLDOK.PPLNR)
key_2	Identifier 2	integer	If REC_REF = "PPL" to be equated with the OP number If REC_REF = "PAU" to be equated with the parameter CDOKUM.PAUNR (inspection order number) If REC_REF = "RKD" to be equated with the parameter CDOKUM.REKDETNR (detail number of complaint) If REC_REF = "PMK" to be equated with the parameter CDOKUM.BAUMNR (failure analysis tree ID) (PDM field ID: CDOKUM.KEY:2,CPPLDOK.AFO)
key_3	Identifier 3	integer	If REC_REF = "PAU" to be equated with the parameter CDOKUM.AFO (OP number) If REC_REF = "RKD" to be equated with the parameter CDOKUM.BAUMNR (failure analysis tree ID) (PDM field ID: CDOKUM.KEY:3)
key_4	Identifier 4	integer	Key field (PDM field ID: CDOKUM.KEY:4)
key_5	Identifier 5	integer	Key field (PDM field ID: CDOKUM.KEY:5)
modify_flag	Modify flag	smallint	Is required for editing tasks of the interface to third-party systems

rec_ref	Data reference	char(20)	'MEK' = Characteristics catalog 'PAN' = Document from inspection requirement 'PAU' = Document from inspection order or subordinate structure (characteristic, measured value) 'PPL' = Document from inspection plan or subordinate structure (characteristic) 'RKK' = Document from complaints header 'RKD' = Document from complaints detail or subordinate structure (failure analysis) 'PMK' = Document from gage header or subordinate structure (failure analysis) 'CPL' = Production control plan (Control Plan) (PDM field ID: CDOKUM.RECREF)
rec_type	Type of the entry	char(50)	Empty = global structures (characteristics catalog) 'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management 'REK' = Complaints management 'CPL' = Production control plan (Control Plan) (PDM field ID: CDOKUM.RECTYP)
text_1	Text, part 1-10	char(250)	The first 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:1,CMMDOK.TEXT:1,...TEXT:1)
text_10	Text, part 1-10	char(250)	The tenth 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:10,CMMDOK.TEXT:10,...TEXT:10)
text_2	Text, part 1-10	char(250)	The second 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:2,CMMDOK.TEXT:2,...TEXT:2)
text_3	Text, part 1-10	char(250)	The third 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:3,CMMDOK.TEXT:3,...TEXT:3)
text_4	Text, part 1-10	char(250)	The fourth 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:4,CMMDOK.TEXT:4,...TEXT:4)
text_5	Text, part 1-10	char(250)	The fifth 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:5,CMMDOK.TEXT:5,...TEXT:5)
text_6	Text, part 1-10	char(250)	The sixth 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:6,CMMDOK.TEXT:6,...TEXT:6)
text_7	Text, part 1-10	char(250)	The seventh 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:7,CMMDOK.TEXT:7,...TEXT:7)
text_8	Text, part 1-10	char(250)	The eighth 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:8,CMMDOK.TEXT:8,...TEXT:8)
text_9	Text, part 1-10	char(250)	The ninth 250 byte of a text. Word-wraps are masked by the character string ~" (PDM field ID: CDOKUM.TEXT:9,CMMDOK.TEXT:9,...TEXT:9)
zus_bol_1	Additional field 1 (Type BOOLEAN)	smallint	If REC_REF = "PPL" to be equated with the parameter CDOKUM.PRAKTIV (display at inspection) If REC_REF = "RKK", "RKD" to be equated with the parameter CDOKUM.EXTERN (display in external documents) (PDM field ID: CDOKUM.ZUSBOL:1,CMMDOK.PRAKTIV,...PRAKTIV)
zus_bol_2	Additional field 2 (Type BOOLEAN)	smallint	Additional field (Type BOOLEAN) (PDM field ID: CDOKUM.ZUSBOL:2)
zus_bol_3	Additional field 3 (Type BOOLEAN)	smallint	Additional field (Type BOOLEAN) (PDM field ID: CDOKUM.ZUSBOL:3)
zus_bol_4	Additional field 4 (Type BOOLEAN)	smallint	Additional field (Type BOOLEAN) (PDM field ID: CDOKUM.ZUSBOL:4)
zus_bol_5	Additional field 5 (Type BOOLEAN)	smallint	Additional field (Type BOOLEAN) (PDM field ID: CDOKUM.ZUSBOL:5)
zus_char_1	Additional field 1 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CDOKUM.ZUSCHR:1)
zus_char_2	Additional field 2 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CDOKUM.ZUSCHR:2)
zus_char_3	Additional field 3 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CDOKUM.ZUSCHR:3)
zus_char_4	Additional field 4 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CDOKUM.ZUSCHR:4)

zus_char_5	Additional field 5 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CDOKUM.ZUSCHR:5)
zus_date_1	Additional field 1 (Type DATE)	date	Additional field (Type DATE) (PDM field ID: CDOKUM.ZUSDAT:1)
zus_date_2	Additional field 2 (Type DATE)	date	Additional field (Type DATE) (PDM field ID: CDOKUM.ZUSDAT:2)
zus_date_3	Additional field 3 (Type DATE)	date	Additional field (Type DATE) (PDM field ID: CDOKUM.ZUSDAT:3)
zus_date_4	Additional field 4 (Type DATE)	date	Additional field (Type DATE) (PDM field ID: CDOKUM.ZUSDAT:4)
zus_date_5	Additional field 5 (Type DATE)	date	Additional field (Type DATE) (PDM field ID: CDOKUM.ZUSDAT:5)
zus_dec_1	Additional field 1-5 (Type DECIMAL)	float	Additional field (Type DECIMAL) (PDM field ID: CDOKUM.ZUSDEC:1)
zus_dec_2	Additional field 1-5 (Type DECIMAL)	float	Additional field (Type DECIMAL) (PDM field ID: CDOKUM.ZUSDEC:2)
zus_dec_3	Additional field 1-5 (Type DECIMAL)	float	Additional field (Type DECIMAL) (PDM field ID: CDOKUM.ZUSDEC:3)
zus_dec_4	Additional field 1-5 (Type DECIMAL)	float	Additional field (Type DECIMAL) (PDM field ID: CDOKUM.ZUSDEC:4)
zus_dec_5	Additional field 1-5 (Type DECIMAL)	float	Additional field (Type DECIMAL) (PDM field ID: CDOKUM.ZUSDEC:5)
zus_int_1	Additional field 1-5 (Type INTEGER)	integer	Additional field (Type INTEGER) (PDM field ID: CDOKUM.ZUSINT:1)
zus_int_2	Additional field 1-5 (Type INTEGER)	integer	Additional field (Type INTEGER) (PDM field ID: CDOKUM.ZUSINT:2)
zus_int_3	Additional field 1-5 (Type INTEGER)	integer	Additional field (Type INTEGER) (PDM field ID: CDOKUM.ZUSINT:3)
zus_int_4	Additional field 1-5 (Type INTEGER)	integer	Additional field (Type INTEGER) (PDM field ID: CDOKUM.ZUSINT:4)
zus_int_5	Additional field 1-5 (Type INTEGER)	integer	Additional field (Type INTEGER) (PDM field ID: CDOKUM.ZUSINT:5)

3.20. caq_dyhis_ppktmm

Table name: caq_dyhis_ppktmm		Product: CAQ	
Archive table: a_caq_dyhis_ppktmm		Reload table: r_caq_dyhis_ppktmm	
Designation: Dyn. history for insp. point character.			
Column name	Column designation	Type	Description
afo	Operation	integer	Corresponding characteristics are defined in the CAQ_MERKMAL table.
anlage	Initial data creation - HYDR user	char(50)	Time when the entry was created
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last change - HYRA user	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table
dyn_pscharf_nr	Inspection severity	char(50)	This field is only relevant when it comes to batch-related inspections (DYN_ART = 'LOS') Normally it is determined by dynamic modification. The DYPSCCHARF:IMPÖRT parameter is only intended for legacy data transfer. The inspection severities of (the inspection severity definition corresponding to the transitional definition CAQ_PRUEFANF.DYN_UEBERG_NR) are filed in the CAQ_DYNPS_EINT table.
dyn_pscharf_usr	Inspection severity corrected by the use	char(50)	This field is only relevant when it comes to batch-related inspections (DYN_ART = 'LOS') The inspection severities of (the inspection severity definition corresponding to the transitional definition CAQ_PRUEFANF.DYN_UEBERG_NR) are filed in the CAQ_DYNPS_EINT table.
eintrag_nr	Number	char(100)	Number
eintrag_typ	Type of number input	char(50)	The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'NUMMERTYP') table
erst_abschl_date	Date of first completion	date	This field serves as sort criterion in the dynamic modification history.
erst_abschl_time	Time of first completion	integer	This field serves as sort criterion in the dynamic modification history.
maschine_nr	Machine	char(20)	Machine
pruefanf_nr	Inspection requirement number	integer	
pruefauf_nr	Inspection order number	integer	Inspection order number
rec_type	Input type	char(50)	

3.21. caq_dynn_aql

Table name: caq_dynn_aql		Product: CAQ	
Designation: AQLs of dynamic modification standards			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
aql_wert	Identifier of AQL value	char(50)	Identifier of AQL value (PDM field ID: CDYNAQL.AQL)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_norm_nr	Dynamic modification	char(50)	The dynamic modification standards are filed in the table CAQ_DYNNORM. (PDM field ID: CDYNAQL.DYNORM)
position	Position	integer	Position (PDM field ID: CDYNAQL.POS)

3.22. caq_dynn_methode

Table name: caq_dynn_methode		Product: CAQ	
Designation: Methods of dynamic modification standard			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_methode	Identifier of dyn. modification method	char(50)	Identifier of dynamic modification method (PDM field ID: CDYNMET.DYNMETH)
dyn_norm_nr	Dynamic modification	char(50)	The dynamic modification standards are filed in the table CAQ_DYNNORM. (PDM field ID: CDYNMET.DYNORM)
position	Position	integer	Position (PDM field ID: CDYNMET.POS)

3.23. caq_dynn_pniveau

Table name: caq_dynn_pniveau		Product: CAQ	
Designation: Inspection level of dynamic modification			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_norm_nr	Dynamic modification	char(50)	The dynamic modification standards are filed in the table CAQ_DYNNORM. (PDM field ID: CDYNPNIV.DYNNORM)
position	Position	integer	Position (PDM field ID: CDYNPNIV.POS)
pruef_pniveau	Identifier of inspection level	char(50)	Identifier of inspection level (PDM field ID: CDYNPNIV.PNIVEAU)

3.24. caq_dynn_stprein

Table name: caq_dynn_stprein		Product: CAQ	
Designation: Sampling schemes of dynamic modification			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
annahme_zahl	Acceptance number	integer	This field is only relevant if CAQ_DYNNORM.STICHPANW_TYP = 'NC' for the corresponding dynamic modification standard. (PDM field ID: CDYNSAEINT.ANMENGE)
aql_wert	AQL	char(50)	The AQL value of the dynamic modification standard are filed in the CAQ_DYNN_AQL table. (PDM field ID: CDYNSAEINT.AQL)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_methode	Dynamic modification method	char(50)	The dynamic modification methods of the dynamic modification standards are filed in the CAQ_DYNN_METHODE table. (PDM field ID: CDYNSAEINT.DYNMETH)
dyn_norm_nr	Dynamic modification	char(50)	The dynamic modification standards are filed in the table CAQ_DYNNORM. (PDM field ID: CDYNSAEINT.DYNORM)
dyn_pscharf_nr	Inspection severity	char(50)	The inspection severities of (the inspection severities definition belonging to the dynamic modification standard) are filed in the CAQ_DYNPS_EINT table (PDM field ID: CDYNSAEINT.DYPSCHARF)
dynam_faktor	Dyn. factor	float	Factor for special kinds of dynamic modification (PDM field ID: CDYNSAEINT.DYNFAKT)
k_wert	K-value	float	This field is only relevant if CAQ_DYNNORM.STICHPANW_TYP = 'K' for the corresponding dynamic modification standard. (PDM field ID: CDYNSAEINT.KWERT)
losumfang	Batch size	integer	This value is the upper limit for which the entry of the sample applies. If this value is empty it applies for all sample sizes of the current class DYN_NORM_NR, PRUEF_NIVEAU, AQL_WERT, DYN_METHODE, DYNPSCHARF_NR) that is greater than the entry with the maximum batch size. (PDM field ID: CDYNSAEINT.LOSUMF)
pruef_niveau	Inspection level	char(50)	The inspection levels of the dynamic modification standard are filed in the CAQ_DYNN_PNIVEAU table. (PDM field ID: CDYNSAEINT.PNIVEAU)
rueckw_zahl	Rejection number	integer	This field is only relevant if CAQ_DYNNORM.STICHPANW_TYP = 'NC' for the corresponding dynamic modification standard. (PDM field ID: CDYNSAEINT.RUMENGE)
skiplot_faktor	Skiplot factor	integer	If the skiplot factor = 1 each sample has to be checked. If the skiplot factor is > 1 each n-th sample has to be checked (n =skiplot factor). If the skiplot factor = 0, all inspections that are dynamically modified are suspended (100% are checked with rejection number 1). (PDM field ID: CDYNSAEINT.SKILOT)
stichpr_anzahl	Number of samples to be inspected	integer	Number of samples to be inspected (PDM field ID: CDYNSAEINT.STPRANZ)
stichpr_umfang	Sample size	integer	Sample size (PDM field ID: CDYNSAEINT.STPRUMF)

3.25. caq_dynnorm

Table name: caq_dynnorm		Product: CAQ	
Designation: Dynamic modification standard			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_norm_bez	Designation of dynamic modification stan	char(250)	Designation of dynamic modification standard (PDM field ID: CDYNORM.DYPSDEF)
dyn_norm_nr	Dynamic modification standards	char(50)	The dynamic modification standards are filed in the table CAQ_DYNNORM. (PDM field ID: CDYNORM.DYNORM)
dyn_pschdef_nr	Corresponding definition of inspection s	char(50)	The definitions of inspection severity are filed in the CAQ_DYNPRFSCHARF table. (PDM field ID: CDYNORM.DYPSDEF)
lst_pruefung_typ	Validity for what inspection types?	char(50)	[A] - applies for attributive characteristics [V] - applies for variable characteristics [A],[V] - applies for attributive and variable characteristics (PDM field ID: CDYNORM.LPRUEFTYP)
stichpanw_typ	Process of results analysis	char(50)	K - determination of the inspection result according to K-value (including dynamic modification of K-value) NC - determination of the inspection result via NC inspection (including dynamic modification of N, C and D). The valid entries can be found in the CAQ_STATUS spreadsheet (STATUS_TYP = 'DYN_STPRANW_TYP') (PDM field ID: CDYNORM.STPANTYP)

3.26. caq_dynprfscharf

Table name: caq_dynprfscharf		Product: CAQ	
Designation: Definitions of inspection severity			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_pschdef_bez	Designation of inspection severity defin	char(250)	Designation of inspection severity definition (PDM field ID: CDYPS.PSDEFBEZ)
dyn_pschdef_nr	Definition of inspection severity	char(50)	The inspection severity definitions are filed in the CAQ_DYNPRFSCHARF table. (PDM field ID: CDYPS.DYPSDEF)

3.27. caq_dynps_eint

Table name: caq_dynps_eint		Product: CAQ	
Designation: Entries of inspect. severity definition			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_pscharf_bez	Designation of inspection severity	char(250)	Designation of inspection severity (PDM field ID: CDYPSEINT.PSCHARFBEZ)
dyn_pscharf_nr	Inspection severity	char(50)	Inspection severity identifier (PDM field ID: CDYPSEINT.DYPSCHARF)
dyn_pschdef_nr	Definition of inspection severity	char(50)	The inspection severity definitions are filed in the CAQ_DYNPRFSCHARF table. (PDM field ID: CDYPSEINT.DYPSDEF)
dynam_faktor	Dyn. factor	float	Factor for special kinds of dynamic modification (PDM field ID: CDYPSEINT.DYNFAKT)
position	Position	integer	Position (PDM field ID: CDYPSEINT.POS)
standard	only for internal use	integer	(PDM field ID: CDYPSEINT.STANDARD)

3.28. caq_dynueb_eint

Table name: caq_dynueb_eint		Product: CAQ	
Designation: Entries of dynamic modif. transitions			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_pscharf_nr	Configuration for inspection severity	char(50)	The inspection severities of (the inspection severity definition belonging to the transitional definition) are filed in the CAQ_DYNPS_EINT table. (PDM field ID: CDYUEBEINT.DYPSCHARF)
dyn_ueberg_nr	Transitional definition	char(50)	The transitional definitions are filed in the CAQ_DYNUEBERGANG table. (PDM field ID: CDYUEBEINT.DYUEBERG)
red_iopf_anz	Ok inspect. in succession for reduction	integer	OK inspections in succession for reduction (PDM field ID: CDYUEBEINT.REDIOFANZ)
red_pscharf_nr	Insp. severity for reducing inspections	char(50)	The inspection severities of (the inspection severity definition belonging to the transitional definition) are filed in the CAQ_DYNPS_EINT table. (PDM field ID: CDYUEBEINT.REDPSCHARF)
vers_niopf_aktiv	NOK inspections in succession active?	smallint	NOK inspections in succession active? (PDM field ID: CDYUEBEINT.VERNIOFAKTIV)
vers_niopf_anz	NOK insp. in succession for tightening	integer	NOK inspections in succession for tightening (PDM field ID: CDYUEBEINT.VERNIOFANZ)
vers_niops_aktiv	Share of NOK inspections active?	smallint	Share of NOK inspections active? (PDM field ID: CDYUEBEINT.VERNIOSAKTIV)
vers_niops_anz	Share of NOK insp. - number for miscell.	integer	Share of NOK inspections - number for miscellaneous (PDM field ID: CDYUEBEINT.VERNIOSANZ)
vers_niops_ges	Share of NOK insp. - total for miscell.	integer	Share of NOK inspections - total for miscellaneous (PDM field ID: CDYUEBEINT.VERNIOSGES)
vers_pscharf_nr	Insp. severity for tightening inspection	char(50)	The inspection severities of the (inspection severity definition belonging to the transitional definition) are filed in the CAQ_DYNPS_EINT table. (PDM field ID: CDYUEBEINT.VERPSCHARF)

3.29. caq_dynuebergang

Table name: caq_dynuebergang		Product: CAQ	
Designation: Dynamic modification transitions			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
dyn_pschdef_nr	Corresponding def. of inspect. severity	char(50)	The definitions of inspection severity are filed in the CAQ_DYNPRFSCHARF table. (PDM field ID: CDYUEB.DYPSDEF)
dyn_ueberg_bez	Designation of transitional definition	char(250)	Designation of transitional definition (PDM field ID: CDYUEB.UEBERGBEZ)
dyn_ueberg_nr	Transitional definition	char(50)	Transitional definition identifier (PDM field ID: CDYUEB.UEBERG)

3.30. caq_einheit

Table name: caq_einheit		Product: CAQ	
Designation: Units		Description: The table administers units and their groups	
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
einheit_bez	Designation of unit or group	char(250)	Designation of unit or group (PDM field ID: EINHEIT.EINHBEZ)
einheit_nr	Number of the unit or group	char(50)	Number of the unit or group (PDM field ID: EINHEIT.CEINH)
group_1	Group indicator hierarchy level 1	char(50)	Identifier for units and groups of the hierarchy level 1-5 (PDM field ID: EINHEIT.DSGRP:1)
group_2	Group indicator hierarchy level 2	char(50)	Identifier for units and groups of the hierarchy level 1-5 (PDM field ID: EINHEIT.DSGRP:2)
group_3	Group indicator hierarchy level 3	char(50)	Identifier for units and groups of the hierarchy level 1-5 (PDM field ID: EINHEIT.DSGRP:3)
group_4	Group indicator hierarchy level 4	char(50)	Identifier for units and groups of the hierarchy level 1-5 (PDM field ID: EINHEIT.DSGRP:4)
group_5	Group indicator hierarchy level 5	char(50)	Identifier for units and groups of the hierarchy level 1-5 (PDM field ID: EINHEIT.DSGRP:5)
group_item	Unit or group?	smallint	0 - Unit 1- Group (PDM field ID: EINHEIT.DSGRPE)

3.31. caq_fhlanal

Table name: caq_fhlanal		Product: CAQ	
Archive table: a_caq_fhlanal		Reload table: r_caq_fhlanal	
Designation: Failure analyses		Description: Spreadsheet administers failure analysis entries. They reference the corresponding failure analysis criteria of the caq_analkat table.	
Column name	Column designation	Type	Description
analkr_code	Defects	char(10)	
analkr_codgr	Code group - defects	char(10)	
analkr_date	Failure analysis criterion date	date	
analkr_katart	Catalog type - defects	char(10)	
analkr_nr	Number of failure analysis criterion	char(50)	Failure analysis criteria are filed in the CAQ_ANALKAT table. . (PDM field ID: CFHLANAL.ERRNR)
analkr_time	Failure analysis criterion time	integer	
analkr_ts	Failure analysis criterion date/time	datetime	
analkr_typ	Type of failure analysis criterion	char(50)	Defect type, defect location, defect cause/... Failure analysis criteria are filed in the CAQ_ANALKAT table. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'FHLANTYP') (PDM field ID: CFHLANAL.ERRTYP,CPAUERR.ERRTYP)
analkr_von	Failure analysis criterion of chart	char(50)	
analkr_vonk	Failure analysis criterion by	char(50)	
analkr_vonp	Failure analysis criterion by person	integer	
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
baugruppe	Assembly	char(50)	
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bemerkung	Comment	char(250)	Comment (PDM field ID: CFHLANAL.BEM,CPAUERR.BEM)
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CFHLANAL.BER,CPAUERR.BER)
einheit	Unit for defect valuation	char(50)	
extern	Additional flag 1	smallint	If REC_REF = "RKD" to be equated with the CFHLANAL.EXTERN parameter (show in external documents) (PDM field ID: CFHLANAL.EXTERN)
fehler_klasse	Defect class	char(20)	
gewichtung	Weighting	integer	Weighting of the failure analysis entry (PDM field ID: CFHLANAL.GEWICHTUNG,CPAUERR.GEWICHTUNG)
gis_key	GIS key	char(50)	Reference to data from the caq_gis table. It has possibly already been determined dynamically by the BAPI from the corresponding structure (inspection order, complaint, etc.). (PDM field ID: CFHLANAL.GIS:MAIN)
key_1	Identifier 1	integer	If REC_REF = "PAU" to be equated with the CFHLANAL.PANNR parameter (inspection requirement number) If REC_REF = "RKD" to be equated with the CFHLANAL.REKNR parameter (complaints number) If REC_REF = "PMK" to be equated with the CFHLANAL.PMNR parameter (gage number) (PDM field ID: CFHLANAL.KEY:1,CPAUERR.PANNR)

key_2	Identifier 2	integer	If REC_REF = "PAU" to be equated with CFHLANAL.PAUNR parameter (inspection order number) If REC_REF = "RKD" to be equated with the CFHLANAL.REKDETNR parameter (complaints detail number) If REC_REF = "PMK" to be equated with the CFHLANAL.BAUMNR parameter (identifier of tree entry) (PDM field ID: CFHLANAL.KEY:2,CPAUERR.PAUNR)
key_3	Identifier 3	integer	If REC_REF = "PAU" to be equated with CFHLANAL.AFO parameter (operation number) If REC_REF = "RKD" to be equated with the CFHLANAL.BAUMNR parameter (identifier of tree entry) (PDM field ID: CFHLANAL.KEY:3,CPAUERR.AFO)
key_4	Identifier 4	integer	If REC_REF = "PAU" to be equated with the CFHLANAL.STPRNR parameter (sample number) (PDM field ID: CFHLANAL.KEY:4,CPAUERR.STPRNR)
key_5	Identifier 5	integer	If REC_REF = "PAU" to be equated with the CFHLANAL.WERTNR parameter (measured value number) (PDM field ID: CFHLANAL.KEY:5,CPAUERR.WERTNR)
menge	Quantitative defect valuation	float	
objekt_code	Object part	char(10)	
objekt_codgr	Code group - object parts	char(10)	
objekt_katart	Catalog type - object parts	char(10)	
pruefning	Single-unit number of unit to be inspect	char(50)	
rasterpos_x	X-axis position	char(50)	
rasterpos_y	Y-axis position	char(50)	
rasterpos_z	Z-axis position	char(50)	
rck_01	Confirmed in system 1?	char(1)	
rck_01_dat	Confirmation date in system 1	date	
rck_01_zeit	Confirmation time in system 1	integer	
rck_02	Confirmed in system 2?	char(1)	
rck_02_dat	Confirmation date in system 2	date	
rck_02_zeit	Confirmation time in system 2	integer	
rck_dat	Confirmation date	date	Confirmation date
rck_zeit	Confirmation time	integer	Confirmation time
rec_ref	Data reference	char(20)	'PAU' = Entry from inspection order or subordinate structure (characteristic, sample, measured value) 'RKD' = Entry from complaints detail or subordinate structure (failure analysis) 'PMK' = Entry from gage header or subordinate structure (failure analysis) (PDM field ID: CFHLANAL.RECREF)
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = in-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'REK' = Complaints management 'PMV' = Gage management 'LFB' = Supplier evaluation 'CPL' = Production control plan (Control Plan) (PDM field ID: CFHLANAL.RECTYP)
rueckgemeldet	Confirmed	char(1)	J/N, indicates whether the log record has been uploaded to the PPS system
subkey	KSBEZ	integer	
systematisch	Indicator: systematic defect	integer	
user_c_01	Alphanumeric user field 1	char(50)	(PDM field ID: CFHLANAL.FU:1)
user_c_02	Alphanumeric user field 2	char(50)	(PDM field ID: CFHLANAL.FU:2)
user_c_03	Alphanumeric user field 3	char(50)	(PDM field ID: CFHLANAL.FU:3)
user_c_04	Alphanumeric user field 4	char(50)	(PDM field ID: CFHLANAL.FU:4)
user_c_05	Alphanumeric user field 5	char(50)	(PDM field ID: CFHLANAL.FU:5)

user_d_01	Date user field 1	date	(PDM field ID: CFHLANAL.FU:13)
user_d_02	Date user field 2	date	(PDM field ID: CFHLANAL.FU:14)
user_f_01	Decimal user field 1	float	(PDM field ID: CFHLANAL.FU:11)
user_f_02	Decimal user field 2	float	(PDM field ID: CFHLANAL.FU:12)
user_n_01	Numeric user field 1	integer	(PDM field ID: CFHLANAL.FU:6)
user_n_02	Numeric user field 2	integer	(PDM field ID: CFHLANAL.FU:7)
user_n_03	Numeric user field 3	integer	(PDM field ID: CFHLANAL.FU:8)
user_n_04	Numeric user field 4	integer	(PDM field ID: CFHLANAL.FU:9)
user_n_05	Numeric user field 5	integer	(PDM field ID: CFHLANAL.FU:10)

3.32. caq_fhlanalbaum

Table name: caq_fhlanalbaum		Product: CAQ	
Designation: Failure analysis tree			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
baum_nr	Identifier within the tree structure	integer	Identifier within the tree structure (PDM field ID: CFHLANAL.BAUMNR,CDOKUM.BAUMNR)
baum_parent	Tree number of the parent element	integer	0: Entry is settled in the root of the tree >0: BAUM_NR of parent element (PDM field ID: CFHLANAL.PARENT,CDOKUM.PARENT)
baum_pos	Position within the failure analysis tre	integer	The content of this field states the line number within the tree. (PDM field ID: CFHLANAL.POS,CDOKUM.POS,CMASSN.POS)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table
gis_key	GIS key	char(50)	Identifier within tree structure
key_1	Identifier 1	integer	If REC_REF = "RKD" to be equated with the complaint number If REC_REF = "PMK" to be equated with the gage number
key_2	Identifier 2	integer	If REC_REF = "RKD" to be equated with the parameter of the complaint detail number
key_3	Identifier 3	integer	Identifier
key_4	Identifier 4	integer	Identifier
key_5	Identifier 5	integer	Identifier
rec_ref	Data reference	char(20)	RKD' = Entry from the failure analysis tree of a complaint detail 'PMK' = Entry from a failure analysis tree of a gage header
rec_type	Input type	char(50)	'REK' = Complaint management 'PMV' = Gage management
tabellen_ref	Table reference	char(50)	caq_fhlanal - corresponding data record can be found in the caq_fhlanal table caq_dokus- corresponding data record can be found in the caq_dokus table caq_massn - corresponding data record can be found in the caq_massn table caq_merkmal - corresponding data record can be found in the caq_merkmal table

3.33. caq_firma

Table name: caq_firma		Product: CAQ	
Designation: Company catalog		Description: The table administers companies and their groups.	
Column name	Column designation	Type	Description
adresse_1	First line of address	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.ADRESSE:1)
adresse_2	Second line of address	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.ADRESSE:2)
adresse_3	Third line of address	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.ADRESSE:3)
anlage	User	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - active entry 1 - archived entry (PDM field ID: FIRMA.ARCHIV)
audit_date	Date of last audit rating	date	This entry is only relevant for companies and suppliers (FIRMA_TYP = 'LIEFERANT') and not for groups (GROUP_ITEM = 0) (PDM field ID: FIRMA.AUDIT:DAT)
audit_einst	Last audit rating	char(50)	This entry is only relevant for companies and suppliers (FIRMA_TYP = 'LIEFERANT') and not for groups (GROUP_ITEM = 0) (PDM field ID: FIRMA.AUDIT:EINST)
audit_wert	Audit rating (value in percent)	smallint	This entry is only relevant for companies and suppliers (FIRMA_TYP = 'LIEFERANT') and not for groups (GROUP_ITEM = 0) (PDM field ID: FIRMA.AUDIT:WERT)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bundesstaat	Federal state	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.STAAT)
email	E-mail address	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.EMAIL)
firma_bez	Company designation	char(250)	Company designation (PDM field ID: FIRMA.FIRBEZ)
firma_nr	Identifier company/group	char(50)	Unique within the current company type (FIRMA_TYP) (PDM field ID: FIRMA.FIRID)
firma_typ	Company type	char(50)	The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'FIRMENTYP') table (PDM field ID: FIRMA.FIRTYP)
group_1	Group indicator hierarchy level 1-5	char(50)	Identifier for companies and groups of the hierarchy level 1-5 (PDM field ID: FIRMA.DSGRP:1)
group_2	Group indicator hierarchy level 1-5	char(50)	Identifier for companies and groups of the hierarchy level 1-5 (PDM field ID: FIRMA.DSGRP:2)
group_3	Group indicator hierarchy level 1-5	char(50)	Identifier for companies and groups of the hierarchy level 1-5 (PDM field ID: FIRMA.DSGRP:3)
group_4	Group indicator hierarchy level 1-5	char(50)	Identifier for companies and groups of the hierarchy level 1-5 (PDM field ID: FIRMA.DSGRP:4)
group_5	Group indicator hierarchy level 1-5	char(50)	Identifier for companies and groups of the hierarchy level 1-5 (PDM field ID: FIRMA.DSGRP:5)
group_item	Company or group?	smallint	0 - Company 1 - Group (PDM field ID: FIRMA.DSGRPE)

land	Country	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.LAND)
ort	Location	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.ORT)
pager	Pager number	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.PAGER)
plz	ZIP code	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.PLZ)
postfach	P. O. Box	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.POSTFACH)
tel_mobile	Mobile number	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.HANDY)
telefax	Fax number	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.FAX)
telefon	Phone number	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.TEL)
verantw_flag	Party in charge	smallint	If the value of this field = 1, the corresponding entry in the caq_verantwortl table is also updated whenever this value is changed. (PDM field ID: FIRMA.VERANT:COPY)
webadresse	Homepage	char(250)	This entry is only relevant for companies and not for groups (GROUP_ITEM = 0). (PDM field ID: FIRMA.WWW)

3.34. caq_formular

Table name: caq_formular		Product: CAQ	
Designation: Form catalog			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
beschreibung	Description	char(250)	(PDM field ID: CFORMUL.FRMBEZL)
dateiname	File name	char(250)	The file name of the Word Report to be designed needs to be entered at first in the "file name" field. Then all macro libraries in use have to be entered, separated by semicolon. Normally, only the HYDRA macro library is used (HydraMacroLibrary.dotm). Moreover, the form number must not start with the terms "TABELLE_", "CAQ_" or "GANT_", as these are reserved prefixes. (PDM field ID: CFORMUL.DATEINAME)
formular_bez	Form designation	char(250)	(PDM field ID: CFORMUL.FRMBEZK)
formular_nr	Form number	char(50)	(PDM field ID: CFORMUL.FRMNR)
formular_typ	Form type	char(50)	(PDM field ID: CFORMUL.FRMTYP)
freigabe	Release	smallint	(PDM field ID: CFORMUL.FREI)
kontext	Context	char(50)	Context in which the form is to be printed. (PDM field ID: CFORMUL.KONTEXT)
optionen	Options	char(250)	(PDM field ID: CFORMUL.OPTION)
position	Position	integer	Numeric specification of which position the form should have in the list of printable forms. The list of the print dialog does not automatically sort by the position number. It is up to the user's decision by which column the content is to be sorted. It is not checked if the position number is unique. (PDM field ID: CFORMUL.POS)
procedur	Export program	char(250)	(PDM field ID: CFORMUL.EXPORTPRG)
sprache	Language	char(50)	(PDM field ID: CFORMUL.LANG)
zusatz	Additional parameter	char(250)	Additional parameters provide further control options for printing forms. Forms provided by HYDRA CAQ can include control parameters. The export program provides information on possible control parameters if new forms are created or existing forms are changed by the user. Further details on the relevant export programs are described in separate documents. (PDM field ID: CFORMUL.ZUSATZ)

3.35. caq_kosten

Table name: caq_kosten		Product: CAQ	
Designation: Cost inputs [general;PAU;REK]			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bemerkung	Comment	char(250)	Comment (PDM field ID: CKOST.BEM)
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CKOST.BER)
betrag	Amount	float	Amount (PDM field ID: CKOST.BETRAG)
dauer	Duration	integer	Duration defined for calculating the amount (PDM field ID: CKOST.DAUER)
gis_key	GIS key	char(50)	GIS key
key_1	Identifier 1	integer	If REC_REF = "RKK", "RKD" to be equated with the CKOST.REKNR parameter (complaint number) (PDM field ID: CKOST.KEY:1)
key_2	Identifier 2	integer	If REC_REF = "RKD" to be equated with the CKOST.REKDETNR parameter (detailed number of complaint) (PDM field ID: CKOST.KEY:2)
key_3	Identifier 3	integer	Key field (PDM field ID: CKOST.KEY:3)
key_4	Identifier 4	integer	Key field (PDM field ID: CKOST.KEY:4)
key_5	Identifier 5	integer	Key field (PDM field ID: CKOST.KEY:5)
kstart_nr	Cost type	char(50)	Cost type of the CAQ_KOSTENART table (PDM field ID: CKOST.KSTART)
rec_ref	Data reference	char(20)	'RKK' = cost rate from complaints header 'RKD' = Cost rate from complaints detail or inferior structure (failure analysis) (PDM field ID: CKOST.RECREF)
rec_type	Type of input	char(50)	'REK' = Complaint management (PDM field ID: CKOST.RECTYP)
waehrung	Currency	char(50)	Currency (PDM field ID: CKOST.WAEHR)

3.36. caq_kostenart

Table name: caq_kostenart		Product: CAQ	
Designation: Catalog of cost types			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - Current measure 1 - Archived measure (PDM field ID: CKSTART.ARCHIV)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereiche	Area(s), which the cost type applies for	char(250)	This entry is only relevant for cost types but not for groups (GROUP_ITEM = 0). The areas are included in squared brackets. If more than one area is stated the areas are separated by a comma. If the field is empty the cost type applies for all areas. The areas are filed in the CAQ_BEREICH table. (PDM field ID: CKSTART.GUELBER)
group_1	Group indicator hierarchy level 1-5	char(50)	Identifier for cost types and groups of the hierarchy levels 1-5 (PDM field ID: CKSTART.DSGRP:1)
group_2	Group indicator hierarchy level 1-5	char(50)	Identifier for cost types and groups of the hierarchy levels 1-5 (PDM field ID: CKSTART.DSGRP:2)
group_3	Group indicator hierarchy level 1-5	char(50)	Identifier for cost types and groups of the hierarchy levels 1-5 (PDM field ID: CKSTART.DSGRP:3)
group_4	Group indicator hierarchy level 1-5	char(50)	Identifier for cost types and groups of the hierarchy levels 1-5 (PDM field ID: CKSTART.DSGRP:4)
group_5	Group indicator hierarchy level 1-5	char(50)	Identifier for cost types and groups of the hierarchy levels 1-5 (PDM field ID: CKSTART.DSGRP:5)
group_item	Cost type or group?	smallint	0 - Cost type 1 - Group (PDM field ID: CKSTART.DSGRPE)
gueltig_flags	Data types, which the cost type applies	char(250)	This entry is only relevant for cost types but not for groups (GROUP_ITEM = 0). The data types are included in squared brackets. If more than one data type is stated the data types are separated by a comma. If the field is empty the cost type applies for all data types. Empty - valid for all modules [REK] - complaints management (PDM field ID: CKSTART.GUELFLAGS)
init_betrag	Initialization amount	float	This entry is only relevant for cost types but not for groups (GROUP_ITEM = 0). This amount is suggested when a cost rate is newly created. (PDM field ID: CKSTART.INIT:BETRAG)
init_dauer	Initialization duration	integer	This entry is only relevant for cost types but not for groups (GROUP_ITEM = 0). This duration is suggested when a cost rate is newly created. (PDM field ID: CKSTART.INIT:DAUER)
init_waehrung	Initialization currency	char(50)	This entry is only relevant for cost types but not for groups (GROUP_ITEM = 0). This currency is suggested when a cost rate is newly created. (PDM field ID: CKSTART.INIT:WAEHR)
kstart_bez	Designation of cost type/group	char(250)	Designation of the cost type or group (PDM field ID: CKSTART.KSTBEZ)
kstart_nr	Identifier of cost type/group	char(50)	Unique number of the cost type or group (PDM field ID: CKSTART.KSTART)

satz_betrag	Cost rate - amount	float	This entry is only relevant for cost types but not for groups (GROUP_ITEM = 0). This amount is regarded as multiplier for processing times, etc. (PDM field ID: CKSTART.SATZ:BETRAG)
satz_waehrung	Cost rate - currency	char(50)	This entry is only relevant for cost types but not for groups (GROUP_ITEM = 0). This currency applies for processing times, etc. (PDM field ID: CKSTART.SATZ:WAEHR)

3.37. caq_masskat

Table name: caq_masskat		Product: CAQ	
Designation: Catalog of measures			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - Current measure 1 - Archived measure (PDM field ID: CMASKAT.ARCHIV)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
group_1	Group indicator hierarchy level 1-5	char(50)	Identifier for measures and groups of hierarchy level 1-5 (PDM field ID: CMASKAT.DSGRP:1)
group_2	Group indicator hierarchy level 1-5	char(50)	Identifier for measures and groups of hierarchy level 1-5 (PDM field ID: CMASKAT.DSGRP:2)
group_3	Group indicator hierarchy level 1-5	char(50)	Identifier for measures and groups of hierarchy level 1-5 (PDM field ID: CMASKAT.DSGRP:3)
group_4	Group indicator hierarchy level 1-5	char(50)	Identifier for measures and groups of hierarchy level 1-5 (PDM field ID: CMASKAT.DSGRP:4)
group_5	Group indicator hierarchy level 1-5	char(50)	Identifier for measures and groups of hierarchy level 1-5 (PDM field ID: CMASKAT.DSGRP:5)
group_item	Cost type or group?	smallint	0 - Measure 1 - Group (PDM field ID: CMASKAT.DSGRPE)
massn_bez	Designation of measure/group	char(250)	Designation of measure/group (PDM field ID: CMASKAT.MASBEZ)
massn_nr	Identifier of cost type/group	char(50)	Unique number of the cost type or group (PDM field ID: CMASKAT.MASNR)

3.38. caq_massn

Table name: caq_massn		Product: CAQ	
Archive table: a_caq_massn		Reload table: r_caq_massn	
Designation: Measures [gen.;PAU]		Description: The table administers the measures. These measures reference the entries of the corresponding measures catalog (caq_massn table).	
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created.
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bemerkung	Comment	char(250)	Comment (PDM field ID: CMASSN.BEM)
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CMASSN.BER)
element_nr	Workflow element	char(50)	This parameter is only relevant if the measure was created due to a workflow process. The elements of the corresponding workflow definitions (WFM_WF_PROCESS.WORKFLOW_NR; WFM_WF_PROCESS.WORKFLOW_IDX) are filed in the CAQ_WF_ELEM table. (PDM field ID: CMASSN.ELEM)
erfuellung	Fulfillment of measure in %	smallint	Fulfillment of measure in % (PDM field ID: CMASSN.ERFUELL)
extern	Is this measure to be printed on ext. re	smallint	Additional flag 1 rec_ref = "RKK"/"RKD" 0: Is not displayed in external reports 1: included in external reports (PDM field ID: CMASSN.EXTERN)
gis_key	GIS key of the measure	char(50)	GIS key of the measure
gis_key_main	GIS key of the corresponding master reco	char(50)	In addition to this parameter the CMASSN.KDNR, CMASSN.LIEFNR, CMASSN.ATK and CMASSN.ATKIDX, CMASSN.AGNR, CMASSN.AGBEZ parameters can be transferred to the BAPI CMASSN. These parameters are entered in the corresponding GIS record of the measure. This is already determined dynamically from the corresponding structure (inspection order, complaint, etc.) by the BAPI.
isttermin_date	Actual date of measure	date	Actual date of measure (PDM field ID: CMASSN.ISTDAT)
isttermin_time	Actual time of measure	integer	Actual time of measure (PDM field ID: CMASSN.ISTZEI)
key_1	Identifier 1	integer	If REC_REF = "PAN", "PAU" to be equated with the CMASSN.PANNR parameter (inspection request number) If REC_REF = "RKK", "RKD" to be equated with CMASSN.REKNR parameter (complaint number) If REC_REF = "PMK" to be equated with CMASSN.PMNR parameter (gage number) (PDM field ID: CMASSN.KEY:1)
key_2	Identifier 2	integer	If REC_REF = "PAU" to be equated with CMASSN.PAUNR parameter (inspection order number) If REC_REF = "RKD" to be equated with the CMASSN.REKDETNR parameter (no.of complaints detail) If REC_REF = "PMK" to be equated with CMASSN.BAUMNR parameter (identifier of tree input) (PDM field ID: CMASSN.KEY:2)
key_3	Identifier 3	integer	If REC_REF = "PAU" to be equated with CMASSN.AFO parameter (operation number) If REC_REF = "RKD" to be equated with CMASSN.BAUMNR parameter (identifier of tree input) (PDM field ID: CMASSN.KEY:3)
key_4	Identifier 4	integer	If REC_REF = "PAU" to be equated with CMASSN.STPRNR parameter (sample number) (PDM field ID: CMASSN.KEY:4)
key_5	Identifier 5	integer	If REC_REF = "PAU" to be equated with CMASSN.WERTNR parameter (measured value number) (PDM field ID: CMASSN.KEY:5)

massn_nr	Unique identifier of the measure	char(50)	Valid identifier of a catalog measure (CAQ_MASSKAT table) (PDM field ID: CMASSN.MASNR)
massn_ser	Unique identifier of the measure	integer	Unique identifier of the measure (PDM field ID: CMASSN.MASSER)
massn_text	Measure text	char(250)	User-defined text of the measure (PDM field ID: CMASSN.MASTEXT)
massn_typ	Measure type	char(50)	Reference to the part of the 8D report. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'MASTYP') (PDM field ID: CMASSN.MASTYP)
process_nr	Workflow process	integer	This parameter is only relevant if the measure was created due to a workflow process. Identifier of the corresponding workflow process (WF_PROCESS table) The workflow processes are filed in the WFM_WF_PROCESS table. (PDM field ID: CMASSN.WFMPROC)
rec_ref	Data reference	char(20)	'PPL' = Entry from inspection plan or inferior structure (characteristic) 'PAU' = Entry from inspection order or inferior structure (characteristic, sample, measured value) 'RKK' = Entry from complaints header 'RKD' = Entry from complaints detail or inferior structure (failure analysis) 'PMK' = Entry from gage header or inferior structure (failure analysis) (PDM field ID: CMASSN.RECREF)
rec_type	Type of the entry	char(50)	Empty = Global structures (characteristics catalog) 'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management 'REK' Complaints management (PDM field ID: CMASSN.RECTYP)
status	Status of measure	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'MASSTATUS') (PDM field ID: CMASSN.STA)
step_nr	Step of workflow process	integer	This parameter is only relevant if the measure was created due to a workflow process. The steps of the corresponding workflow processes are filed in the WFM_WF_STEP table. (PDM field ID: CMASSN.WFMSTEP)
verantw_nr	Party in charge number of measure	char(50)	Parties in charge are defined in the CAQ_VERANTWORTL table. (PDM field ID: CMASSN.VERANT:NR)
verantw_typ	Party in charge type of measure	char(50)	The parties responsible are defined in the CAQ_VERANTWORTL table. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'VERANTWTYP') (PDM field ID: CMASSN.VERANT:TYP)
verteiler_ref	Distributor reference	integer	This field is only filled out if the original measure was created with a distributor as party in charge. In this case all partial measures, which were created for this distributor are summarized in this distributor reference. (PDM field ID: CMASSN.VERTREF)
wirksam	Efficiency of measure in %	smallint	Efficiency of measure in % (PDM field ID: CMASSN.WIRKSAM)
zieltermin_date	Target date of measure	date	Target date of measure (PDM field ID: CMASSN.ZIELDAT)
zieltermin_time	Target time of measure	integer	Target time of measure (PDM field ID: CMASSN.ZIELZEI)

3.39. caq_mdi_channel

Table name: caq_mdi_channel		Product: CAQ	
Designation: MDI Configurations			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
caq_aktiv_typ	CAQ - time of activation	char(50)	Order - Measuring equipment is to be activated when opening the order Characteristic - Measuring equipment is to be activated when choosing the corresponding characteristic (PDM field ID: CMDICFG.CAQ:AKTIVTYP)
caq_anz_direkt	Display CAQ data directly in the field	smallint	0 - Data are displayed 'online' in the corresponding measurement value field 1 - Data are only displayed or accepted by user action (PDM field ID: CMDICFG.CAQ:ANZDIR)
caq_config_str	CAQ - additional configuration param.	char(1464)	The commands included here are sent to the MDI server as configuration change before the measuring equipment is activated. (PDM field ID: CMDICFG.CAQ:CFGPAR)
caq_del_aktiv	Delete CAQ measured value buffer at acti	smallint	0 - Measurement value buffer is not deleted when measuring equipment is activated 1 - Measurement value buffer is deleted when measuring equipment is activated (PDM field ID: CMDICFG.CAQ:DELAktiv)
caq_del_noplausi	CAQ - delete implausible measured values	smallint	0 - Measured values, which are confirmed and saved, are only deleted from the measured value buffer 1 - Confirmed measured values, which have not been saved due to failed plausibility checks, are also deleted from the measurement value buffer (PDM field ID: CMDICFG.CAQ:DELNOPLAUS)
caq_freigabe	Release CAQ configuration?	smallint	0 - MDI configuration not available in CAQ 1 - MDI configuration available in CAQ (PDM field ID: CMDICFG.CAQ:FREI)
group_1	Group indicator hierarchy level 1-5	char(50)	Group indicator hierarchy level 1-5 (PDM field ID: CMDICFG.DSGRP:1)
group_2	Group indicator hierarchy level 1-5	char(50)	Group indicator hierarchy level 1-5 (PDM field ID: CMDICFG.DSGRP:2)
group_3	Group indicator hierarchy level 1-5	char(50)	Group indicator hierarchy level 1-5 (PDM field ID: CMDICFG.DSGRP:3)
group_4	Group indicator hierarchy level 1-5	char(50)	Group indicator hierarchy level 1-5 (PDM field ID: CMDICFG.DSGRP:4)
group_5	Group indicator hierarchy level 1-5	char(50)	Group indicator hierarchy level 1-5 (PDM field ID: CMDICFG.DSGRP:5)
group_item	MDI configuration or group?	smallint	MDI configuration or group? (PDM field ID: CMDICFG.DSGRPE)
ip_adresse	IP address of the corresponding MDI serv	char(20)	IP address of the corresponding MDI server (PDM field ID: CMDICFG.IP)
ip_port	TCP port of the corresponding MDI server	integer	TCP port of the corresponding MDI server (PDM field ID: CMDICFG.PORT)
kanal	Channel number of the corresponding MDI	char(50)	Channel number of the corresponding MDI server (PDM field ID: CMDICFG.CHANNEL)
mdiconf_bez	Designation of MDI configuration	char(250)	Designation of MDI configuration (PDM field ID: CMDICFG.MDIBEZ)

mdiconf_nr	Identifier of MDI configuration	char(50)	Identifier of MDI configuration (PDM field ID: CMDICFG.MDICFG)
------------	---------------------------------	----------	---

3.40. caq_mdi_res_zuord

Table name: caq_mdi_res_zuord		Product: CAQ	
Designation: Mapping of MDI to resource			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
mdiconf_nr	Identifier of MDI configuration	char(50)	Identifier of MDI configuration (PDM field ID: CMDIRESCFG.MDICFG)
res_familie	Identity of resource familyIdentity of r	integer	Identity of resource family (PDM field ID: CMDIRESCFG.RES:RESFAMID)
res_nr	Resource number	char(40)	resource number (PDM field ID: CMDIRESCFG.RES:RES)

3.41. caq_merk_zusatz

Table name: caq_merk_zusatz		Product: CAQ	
Archive table: a_caq_merk_zusatz		Reload table: r_caq_merk_zusatz	
Designation: Additional characteristics information			
Column name	Column designation	Type	Description
aenderung_version	Version counter (external)	integer	
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
ber_formel_extern	Formula for inspection charact. (extern)	char(250)	
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table
capture_func_id	Process data - Capture filter function	integer	(PDM field ID: CMM.KOMPFKT,CPPLMM.KOMPFKT,CMERK.KOMPFKT)
cs_param_1	Process data - Filterintervall	float	(PDM field ID: CMM.KOMPPARAM:1,CPPLMM.KOMPPARAM:1,CMERK)
cs_param_2	Process data - Filteranzahl	float	(PDM field ID: CMM.KOMPPARAM:2,CPPLMM.KOMPPARAM:2,CMERK)
cs_param_3	Process data - Filterprozent	float	(PDM field ID: CMM.KOMPPARAM:3,CPPLMM.KOMPPARAM:3,CMERK)
cs_param_4	Process data - Filterparameter 4	float	(PDM field ID: CMM.KOMPPARAM:4,CPPLMM.KOMPPARAM:4,CMERK)
cs_param_5	Process data - Filterparameter 5	float	(PDM field ID: CMM.KOMPPARAM:5,CPPLMM.KOMPPARAM:5,CMERK)
cv_param_1	Process data - Filterintervall (Visual.)	float	(PDM field ID: CMM.VISPARAM:1,CPPLMM.VISPARAM:1,CMERK.V)
cv_param_2	Process data - Filteranzahl (Visual.)	float	(PDM field ID: CMM.VISPARAM:2,CPPLMM.VISPARAM:2,CMERK.V)
cv_param_3	Process data - Filterprozent (Visual.)	float	(PDM field ID: CMM.VISPARAM:3,CPPLMM.VISPARAM:3,CMERK.V)
cv_param_4	Process data - Filterparam. 4 (Visual.)	float	(PDM field ID: CMM.VISPARAM:4,CPPLMM.VISPARAM:4,CMERK.V)
cv_param_5	Process data - Filterparam. 5 (Visual.)	float	(PDM field ID: CMM.VISPARAM:5,CPPLMM.VISPARAM:5,CMERK.V)
karte_referenz	Control chart - external reference	char(20)	
key_1	Identifier 1	integer	REC_REF = 'MEK' --> Characteristics number REC_REF = 'PPL' --> Inspection plan number REC_REF = 'PAU' --> Inspection requirement number REC_REF = 'RKK','RKD' --> Complaints number
key_2	Identifier 2	integer	REC_REF = 'PPL' --> AFO-Nummer REC_REF = 'PAU' --> Prüfauftragsnummer
key_3	Identifier 3	integer	REC_REF = 'PAU' --> AFO-Nummer
key_4	Identifier 4	integer	
key_5	Identifier 5	integer	
merkmal_gew_text	Text for weighting of inspection char.	char(50)	

merkmal_gewicht	Weighting of insp. characteristic	char(10)	
merkmal_version	Version of master insp. charact.	char(10)	
merkmal_werk	Plant of master inspection charact.	char(4)	
phys_probe	Number of the physical sample	char(20)	
pmethode_nr	Inspection method	char(20)	
pmethode_text	Short text of the inspection method	char(50)	
pmethode_version	Version of the inspection method	char(10)	
pmethode_werk	Plant of the inspection method	char(4)	
pruefer_quali	Inspector qualification	char(10)	
rec_ref	Data reference	char(20)	'MEK' = Catalog characteristic 'PAU' = Inspection order characteristic 'PPL' = Inspection plan characteristic 'RKK' = Characteristic from complaints header 'RKD' = Characteristic from complaints detail or subordinate structure (failure analysis)
rec_type	Type of input	char(50)	Empty = Global structures (characteristics catalog) 'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management 'REK' Complaints management PMV = Gage management 'PMV' = Prüfmittelmanagement
user_grenze_o1	First upper limit value	float	
user_grenze_o2	Second upper limit value	float	
user_grenze_u1	First lower limit value	float	
user_grenze_u2	Second lower limit value	float	
visual_funct_id	Pro.data - Visualization filter function	integer	(PDM field ID: CMM.VISFKT,CPPLMM.VISFKT,CMERK.VISFKT)
visual_pos	Process data - Visualization position	integer	(PDM field ID: CMM.VISPOS,CPPLMM.VISPOS,CMERK.VISPOS)
visual_type	Process data - Visualization type	integer	(PDM field ID: CMM.VISTYP,CPPLMM.VISTYP,CMERK.VISTYP)

3.42. caq_merkmal

Table name: caq_merkmal		Product: CAQ	
Archive table: a_caq_merkmal		Reload table: r_caq_merkmal	
Designation: Characteristics [catalog;PPL;PAU;REK]		Description: This spreadsheet administers the characteristics. It includes catalog characteristics, inspection plan characteristics, inspection order characteristics and failure analysis characteristics. Depending on the type of characteristic entry only some of the fields listed in the following are relevant.	
Column name	Column designation	Type	Description
afolg		char(10)	
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
anz_pruefer	Number of inspectors	integer	
aql_wert	AQL	char(50)	This field is only relevant for dynamically modified characteristics (RECREG = PPL,PAU). The AQL-values of the dynamic modification norm are filed in the CAQ_DYNN_AQL table. (PDM field ID: CPPLMM.AQL)
arbgang_bez	Operation designation	char(250)	Operation designation (PDM field ID: CPPLMM.AGBEZ)
arbgang_nr	Operation number	char(50)	Operation number (PDM field ID: CPPLMM.AGNR)
basis_prueferg	Base for inspection result	char(50)	
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bemerkung	Comment	char(250)	
ber_formel	Computation formula	char(1464)	Computation formula (PDM field ID: CMM.BFORMEL,CPPLMM.BFORMEL)
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table (PDM field ID: CMERK.BER,CPPLMM.BER)
bew_katalog	Assessment catalog for attributive chara	char(50)	The valid entries can be found in the HYD_VWE_STAT table (VWE_ID = "PRUEFTYP_A" AND AUSWMENGE = BEW_KATALOG) (PDM field ID: CMM.BEWKAT,CPPLMM.BEWKAT)
bewertung_art	Valuation type for insp. charact.	char(20)	
bewertung_art_sp	Valuation type for insp. sample	char(20)	
bewertung_rel	Evaluation relevant?	integer	
bewkat_auswmen_1	Evaluation catalog 1-selected set	char(10)	
bewkat_auswmen_2	Evaluation catalog 2- selected set	char(10)	
bewkat_auswmen_3	Evaluation catalog 3- selected set	char(10)	
bewkat_auswmen_4	Evaluation catalog 4- selected set	char(10)	
bewkat_auswmen_5	Evaluation catalog 5- selected set	char(10)	
bewkat_katart_1	Evaluation catalog 1- catalog type	char(10)	
bewkat_katart_2	Evaluation catalog 2- catalog type	char(10)	
bewkat_katart_3	Evaluation catalog 3 - catalog type	char(10)	
bewkat_katart_4	Evaluation catalog 4 - catalog type	char(10)	
bewkat_katart_5	Evaluation catalog 5 - catalog type	char(10)	
bewkat_rel_1	Evaluation catalog 1 - relevant?	integer	

bewkat_rel_2	Evaluation catalog 2 - relevant?	integer	
bewkat_rel_3	Evaluation catalog 3 - relevant?	integer	
bewkat_rel_4	Evaluation catalog 4 - relevant?	integer	
bewkat_rel_5	Evaluation catalog 5 - relevant?	integer	
bewkat_werk_1	Evaluation catalog 1- plant	char(4)	
bewkat_werk_2	Evaluation catalog 2- plant	char(4)	
bewkat_werk_3	Evaluation catalog 3 - plant	char(4)	
bewkat_werk_4	Evaluation catalog 4 - plant	char(4)	
bewkat_werk_5	Evaluation catalog 5 - plant	char(4)	
cpk_aktiv	Process capability index control active?	integer	
dokulist_nr	Document list entry reference	integer	
dokument_pflicht	Documentation required	integer	
dyn_daten_basis	Data base for dyn. modification.	char(50)	
dyn_methode	Dynamic modification method	char(50)	This field is only relevant for dynamically modified characteristics (RECREF = PPL,PAU). The methods of dynamic modification of the dynamic modification norm are filed in the CAQ_DYNN_METHODE table. (PDM field ID: CPPLMM.DYNNMETH)
dyn_norm_nr	Dynamic modification norm	char(50)	This field is only relevant for dynamically modified characteristics (RECREF = PPL,PAU). The dynamic modification norms are filed in the CAQ_DYNORM table. (PDM field ID: CPPLMM.DYNORM)
dyn_pscharf_nr	Current inspection severity	char(50)	This field is only relevant for dynamically modified characteristics (RECREF = PAU). The inspection severities of the (the inspection severity definition belonging to the transitional definition CAQ_MERKMAL.DYN_UEBERG_NR) are filed in the CAQ_DYNPS_EINT table. Using the corresponding BAPI parameter is only intended for the legacy data transfer. (PDM field ID: CMERK.DYPSCHARF)
dyn_pscharf_star	Initial inspection severity	char(50)	This field is only relevant for dynamically modified characteristics (RECREF = PPL,PAU). The inspection severities of the (the inspection severity definition belonging to the transitional definition CAQ_MERKMAL.DYN_UEBERG_NR) are filed in the CAQ_DYNPS_EINT table. (PDM field ID: CPPLMM.DYPSCHARF:STA)
dyn_pscharf_usr	Inspection severity corrected by the use	char(50)	This field is only relevant for a dynamic modification based on characteristics (DYN_ART = 'MERKMAL'; RECREF = 'PAU'). The inspection severities (of the inspection severity definition belonging to the transitional definition CAQ_MERKMAL.DYN_UEBERG_NR) are filed in the CAQ_DYNPS_EINT table. (PDM field ID: CMERK.DYPSCHARF:USR)
dyn_ueberg_nr	Transitional definition	char(50)	This field is only relevant for dynamically modified characteristics (RECREF = PPL,PAU). The transitional definitions are filed in the CAQ_DYNUEBERGANG table. (PDM field ID: CPPLMM.DYUEBERG)
dynamisiert	Characteristic is being dynamically modi	smallint	0 - Characteristic is not modified dynamically 1 - Characteristic is dynamically modified (PDM field ID: CPPLMM.DYNAM)
eingepplant	Planned on machine or group	char(1)	
einheit	Unit of measurement	char(50)	The valid entries can be found in the CAQ_EINHEIT table (PDM field ID: CMM.CEINH,CPPLMM.CEINH)
emu_kopieren	Accept characteristic from ISI?	smallint	- only relevant if REC_TYPE = 'EMU' Is this characteristic also to be copied by the initial sample inspection into GRI/SPC/GII when copying the inspection plan. (PDM field ID: CPPLMM.EMUCOPY)
emu_mmtyp	Type of the corresponding ISI form (init	char(50)	- Only relevant if REC_TYPE = 'EMU' The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EMUMMTYP_' + <PPL/PAN.EMU_FORMULAR>) (PDM field ID: CPPLMM.EMUMMTYP)
entnahme_menge	Issue quantity in per cent	integer	The inspection quantity is calculated for time wage by means of this field. (PDM field ID: CMM.ENTMENGE,CPPLMM.ENTMENGE)
ererbt	Measured values of characteristic inheri	smallint	0 - Measured values of the characteristic are not inherited 1 - Measured values of the characteristic are inherited
erfassung_art	Recording type for insp. charact.	char(30)	
erfassung_detail	Input type	char(50)	

fehlergewicht	Error weighting	char(50)	Major defect, minor defect and critical defect The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'FHLGEW') (PDM field ID: CMM.ERRGEW,CPPLMM.ERRGEW)
format	Input/output format	char(250)	Example: #####0.000 (PDM field ID: CMM.FMT,CPPLMM.FMT)
format_option	Format option for ISI form	char(250)	- only relevant if REC_TYPE = 'EMU' The following parameters are possible for formatting initial sample forms: [FF] - page break after this characteristic (PDM field ID: CPPLMM.FORMOPT)
gis_key	GIS key	char(50)	Key value to reference the GIS input
group_1	Group indicator of hierarchy level 1	char(50)	Group indicator of hierarchy level 1 - 5 (PDM field ID: CMERK.DSGRP:1,CMM.DSGRP:1,CPPLMM.DSGRP:1)
group_2	Group indicator of hierarchy level 2	char(50)	Group indicator of hierarchy level 1 - 5 (PDM field ID: CMERK.DSGRP:2,CMM.DSGRP:2,CPPLMM.DSGRP:2)
group_3	Group indicator of hierarchy level 3	char(50)	Group indicator of hierarchy level 1 - 5 (PDM field ID: CMERK.DSGRP:3,CMM.DSGRP:3,CPPLMM.DSGRP:3)
group_4	Group indicator of hierarchy level 4	char(50)	Group indicator of hierarchy level 1 - 5 (PDM field ID: CMERK.DSGRP:4,CMM.DSGRP:4,CPPLMM.DSGRP:4)
group_5	Group indicator of hierarchy level 5	char(50)	Group indicator of hierarchy level 1 - 5 (PDM field ID: CMERK.DSGRP:5,CMM.DSGRP:5,CPPLMM.DSGRP:5)
group_item	Characteristic or group?	smallint	1 --> it is a group 0 --> it is a characteristic (PDM field ID: CMERK.DSGRPE,CMM.DSGRPE,CPPLMM.DSGRPE)
hinweis_txt	Note	char(250)	Using the corresponding BAPI parameter is only intended for the legacy data transfer. (PDM field ID: CMERK.MSGTXT)
histogramm	Display histogram?	smallint	Display histogram? (PDM field ID: CMM.HISTOGR,CPPLMM.HISTOGR)
intervall_alw	Maturity with output batch change	integer	
intervall_einh	Inspection interval - unit	char(50)	This field is only relevant if INTERVALL_TYP = "ZEIT". The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'INTERVAL') (PDM field ID: CMM.INTEINH,CPPLMM.INTEINH)
intervall_msw	Maturity with machine status change	integer	
intervall_msw_st	Source status for machine status change	char(250)	
intervall_sch_w	Maturity with shifts change	integer	
intervall_typ	Inspection interval - type	char(50)	Time-related/quantity-related The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'ERFINT') (PDM field ID: CMM.INTTYP,CPPLMM.INTTYP)
intervall_wert	Inspection interval - value	integer	This field is only relevant if INTERVALL_TYP = "ZEIT","STUECK". (PDM field ID: CMM.INTERVAL,CPPLMM.INTERVAL)
intstart_einh	First intervall unit	char	
intstart_wert	First intervall value	integer	
k_wert_vorg	K-value specification for dynamic modifi	float	This field is only relevant if characteristics are dynamically modified (RECREP = PAU). Using the corresponding BAPI parameter is only intended for legacy data transfer. (PDM field ID: CMERK.KWERT)
karte1	Control chart 1	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'REGELK' AND ZUSATZ LIKE '%(<PRUEFUNG_TYP>)%') (PDM field ID: CMM.KARTE:1,CPPLMM.KARTE:1)
karte1_ber_art	Method to determine the XQuer value	char(50)	- applies to control chart 1 - is required to recalculate the action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'BERXQART') (PDM field ID: CMM.XQVART:1,CPPLMM.XQVART:1)
karte1_ber_xq	Default value XQuer	float	- applies for control chart 1 - is required to recalculate the action limits This field is only relevant if KARTE1_BER_ART = 'VORGABE'. (PDM field ID: CMM.VORGXQ:1,CPPLMM.VORGXQ:1)

karte1_cpk	cpk default value to calculate limit val	float	- applies to control chart 1 - is required to recalculate the action limits This field is only relevant if KARTE1_VORGABE = 'CPK'. (PDM field ID: CMM.CPK:1,CPPLMM.CPK:1)
karte1_dyn_berech	Dynamic computation of limit values?	smallint	- applies to control chart 1 (PDM field ID: CMM.GWBERDYN:1,CPPLMM.GWBERDYN:1)
karte1_egw_eg	Action probability	char(50)	- applies to control chart 1 - is required to recalculate the action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EGWEINS' or 'EGWZWEI' or 'EGWZWEI_RS') (PDM field ID: CMM.EWEG:1,CPPLMM.EWEG:1)
karte1_egw_wg	Action probability	char(50)	- applies to control chart 1 - is required to recalculate warning limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EGWEINS' or 'EGWZWEI' or 'EGWZWEI_RS') (PDM field ID: CMM.EWWG:1,CPPLMM.EWWG:1)
karte1_eins_zwei	Calculation one-sided or two-sided?	char(50)	- applies to control chart 1 - is required to recalculate the action limits EINS - one-sided calculation (lower or upper limit values only) ZWEI - two-sided calculation (lower and upper limit values) (PDM field ID: CMM.STATVERT:1,CPPLMM.STATVERT:1)
karte1_mw	Mean value	float	- applies to control chart 1 (PDM field ID: CMM.MWAVG:1,CPPLMM.MWAVG:1)
karte1_mw_berech	Calculate mean value at generation of in	smallint	- applies to XQuer charts - Applies to control chart 1 0 - Do not calculate at inspection order generation 1 - Calculate at inspection order generation (PDM field ID: CMM.MWBERECH:1,CPPLMM.MWBERECH:1;...)
karte1_oeg	Upper action limit	float	- applies to control chart 1 (PDM field ID: CMM.OEG:1,CPPLMM.OEG:1)
karte1_oeg_aktiv	Autom. defect type at violation of upper	smallint	- applies to control chart 1 (PDM field ID: CMM.OEGAKTIV:1,CPPLMM.OEGAKTIV:1)
karte1_oeg_berech	Calculate upper action limit at generate	smallint	- Applies to control chart 1 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.OEGBERECH:1;CPPLMM.OEGBERECH:1;...)
karte1_owg	Upper warning limit	float	- applies to control chart 1 (PDM field ID: CMM.OWG:1,CPPLMM.OWG:1)
karte1_owg_aktiv	Autom. defect type at violation of upper	smallint	- applies to control chart 1 (PDM field ID: CMM.OWGAKTIV:1,CPPLMM.OWGAKTIV:1)
karte1_owg_berech	Calculate upper warning limit at generate	smallint	- Applies to control chart 1 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.OWGBERECH:1;CPPLMM.OWGBERECH:1;...)
karte1_quer	Default value Quer to calculate limit va	float	- applies to control chart 1 - is required for recalculation of action limits This field is only relevant if KARTE1_VORGABE = 'QUER'. (PDM field ID: CMM.QUER:1,CPPLMM.QUER:1)
karte1_rel_eg	Action limit specification for relative	float	- applies to XQuer charts only - applies to control chart 1 This field is only relevant if KARTE1_VORGABE = 'ABW_REL' or 'ABW_PROZ'. (PDM field ID: CMM.RELEG:1;CPPLMM.RELEG:1;CMERK.RELEG:1)
karte1_rel_wg	Warning limit specification for relative	float	- applies to XQuer charts only - applies to control chart 1 This field is only relevant if KARTE1_VORGABE = 'ABW_REL' or 'ABW_PROZ'. (PDM field ID: CMM.RELWG:1;CPPLMM.RELWG:1;CMERK.RELWG:1)
karte1_run_aktiv	Run active? (Chart 1)	integer	
karte1_sigma	Default value Sigma to calculate limit v	float	- applies to control chart 1 - is required to recalculate the action limits This field is only relevant if KARTE1_VORGABE = 'SIGMA'. (PDM field ID: CMM.SIGMA:1,CPPLMM.SIGMA:1)

karte1_trend_aktiv	Trend active? (Chart 1)	smallint	
karte1_ueg	Lower action limit	float	- applies to control chart 1 (PDM field ID: CMM.UEG:1,CPPLMM.UEG:1)
karte1_ueg_aktiv	Autom. defect type at violation of lower	smallint	- applies to control chart 1 (PDM field ID: CMM.UEGAKTIV:1,CPPLMM.UEGAKTIV:1)
karte1_ueg_berech	Calculate lower action limit at generate	smallint	- - Applies to control chart 1 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.UEGBERECH:1;CPPLMM.UEGBERECH:1;...)
karte1_uwg	Lower warning limit	float	- applies to control chart 1 (PDM field ID: CMM.UWG:1,CPPLMM.UWG:1)
karte1_uwg_aktiv	Autom. defect type at violation of lower	smallint	- applies to control chart 1 (PDM field ID: CMM.UWGAKTIV:1,CPPLMM.UWGAKTIV:1)
karte1_uwg_berech	Calculate lower warning limit at generate	smallint	- - Applies to control chart 1 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.UWGBERECH:1;CPPLMM.UWGBERECH:1;...)
karte1_vorgabe	Default values to calculate action limit	char(50)	- applies to control chart 1 - is required to recalculate the action limits CPK - cpk specification to calculate SIGMA - Sigma specification to calculate QUER - sQuer/an or RQuer/dn specification for calculation (PDM field ID: CMM.VORG:1,CPPLMM.VORG:1)
karte2	Control chart 2	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'REGELK' AND ZUSATZ LIKE '%(<PRUEFUNG_TYP>)%') (PDM field ID: CMM.KARTE:2,CPPLMM.KARTE:2)
karte2_ber_art	Method to determine the Xquer value	char(50)	- applies to control chart 1 - is required to recalculate action limits The valid entries can be found n the CAQ_STATUS table (STATUS_TYP = 'BERXQART') (PDM field ID: CMM.XQVART:2,CPPLMM.XQVART:2)
karte2_ber_xq	Default value XQuer	float	- applies to control chart 2 - is required to recalculate action limits This field is only relevant if KARTE2_BER_ART = 'VORGABE'. (PDM field ID: CMM.VORGXQ:2,CPPLMM.VORGXQ:2)
karte2_cpk	Cpk default value to calculate limit val	float	- applies to control chart 2 - is required to recalculate limit values This field is only relevant if KARTE2_VORGABE = 'CPK'. (PDM field ID: CMM.CPK:2,CPPLMM.CPK:2)
karte2_dyn_berech	Dynamic computation of limit values	smallint	- applies to control chart 2 (PDM field ID: CMM.GWBERDYN,CPPLMM.GWBERDYN:2)
karte2_egw_eg	Action probability	char(50)	- applies to control chart 2 - is required to recalculate action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EGWEINS' or 'EGWZWEI' or 'EGWZWEI_RS') (PDM field ID: CMM.EWEG:2,CPPLMM.EWEG:2)
karte2_egw_wg	Action probability	char(50)	- applies to control chart 2 - is required to recalculate action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EGWEINS' or 'EGWZWEI' or 'EGWZWEI_RS') (PDM field ID: CMM.EWWG:2,CPPLMM.EWWG:2)
karte2_eins_zwei	Computation one-sided or two-sided?	char(50)	- applies to control chart 2 - is required to recalculate action limits EINS -one-sided calculation (lower or upper limit values only) ZWEI - two-sided calculation (lower and upper limit values) (PDM field ID: CMM.STATVERT:2,CPPLMM.STATVERT:2)
karte2_mw	Mean value	float	- applies to control chart 2 (PDM field ID: CMM.MWAVG:2,CPPLMM.MWAVG:2)
karte2_mw_berech	Calculate mean value at generation of in	smallint	- applies to XQuer charts only - applies to control chart 2 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.MWBERECH:2;CPPLMM.MWBERECH:2;...)

karte2_oeg	Upper action limit	float	- applies to control chart 2 (PDM field ID: CMM.OEG:2,CPPLMM.OEG:2)
karte2_oeg_aktiv	Autom. defect type a violation of upper	smallint	- applies to control chart 2 (PDM field ID: CMM.OEGAKTIV:2,CPPLMM.OEGAKTIV:2)
karte2_oeg_berech	Calculate upper action limit at generati	smallint	- Applies to control chart 2 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.OEGBERECH:2;CPPLMM.OEGBERECH:2;...)
karte2_owg	Upper warning limit	float	- applies to control chart 2 (PDM field ID: CMM.OWG:2,CPPLMM.OWG:2)
karte2_owg_aktiv	Autom. defect type at violation of upper	smallint	- applies to control chart 2 (PDM field ID: CMM.OWGAKTIV:2,CPPLMM.OWGAKTIV:2)
karte2_owg_berech	Calculate upper warning limit at generate	smallint	- Applies to control chart 2 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.OWGBERECH:2;CPPLMM.OWGBERECH:2;...)
karte2_quer	Default value Quer to calculate limit va	float	- applies to control chart 2 - is required to recalculate action limits This field is only relevant if KARTE2_VORGABE = 'QUER'. (PDM field ID: CMM.QUER:2,CPPLMM.QUER:2)
karte2_rel_eg	Action limit specification for relative	float	- applies to XQuer charts only - applies to control chart 2 This field is only relevant if KARTE2_VORGABE = 'ABW_REL' or 'ABW_PROZ'. (PDM field ID: CMM.RELEG:2;CPPLMM.RELEG:2;CMERK.RELEG:2)
karte2_rel_wg	Warning limit specification for relative	float	- applies to XQuer charts only - applies to control chart 2 This field is only relevant if KARTE2_VORGABE = 'ABW_REL' or 'ABW_PROZ'. (PDM field ID: CMM.RELWG:2;CPPLMM.RELWG:2;CMERK.RELWG:2)
karte2_run_aktiv	Run active? (Chart 2)	integer	
karte2_sigma	Default value Sigma to calculate limit v	float	- applies to control chart 2 - is required to recalculate action limits This field is only relevant if KARTE2_VORGABE = 'SIGMA'. (PDM field ID: CMM.SIGMA:2,CPPLMM.SIGMA:2)
karte2_trend_aktiv	Trend active? (Chart 2)	smallint	
karte2_ueg	Lower action limit	float	- applies to control chart 2 (PDM field ID: CMM.UEG:2,CPPLMM.UEG:2)
karte2_ueg_aktiv	Autom. defect type at violation of lower	smallint	- gilt für Regelkarte 2 (PDM field ID: CMM.UEGAKTIV:2,CPPLMM.UEGAKTIV:2)
karte2_ueg_berech	Calculate lower action limit at generate	smallint	- Applies to control chart 2 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.UEGBERECH:2;CPPLMM.UEGBERECH:2;...)
karte2_uwg	Lower warning limit	float	- applies to control chart 2 (PDM field ID: CMM.UWG:2,CPPLMM.UWG:2)
karte2_uwg_aktiv	Autom. defect type at violation of lower	smallint	- applies to control chart 2 (PDM field ID: CMM.UWGAKTIV:2,CPPLMM.UWGAKTIV:2)
karte2_uwg_berech	Calculate lower warning limit at generate	smallint	- Applies to control chart 2 0 - do not calculate at inspection order generation 1 - calculate at inspection order generation (PDM field ID: CMM.UWGBERECH:2;CPPLMM.UWGBERECH:2;...)
karte2_vorgabe	Default value to calculate action limit/	char(50)	- applies to control chart 2 - is required to recalculate action limits CPK - cpk specification for calculation SIGMA - Sigma specification for calculation QUER - sQuer/an or RQuer/dn for calculation (PDM field ID: CMM.VORG:2,CPPLMM.VORG:2)

kein_nest	Characteristic has no cavity relation	smallint	Flag for cavity relation of characteristic 0: characteristic takes settings for the cavity relation over from the inspection plan header data 1: Contrary to inspection plan header data, characteristic has no cavity relation (PDM field ID: CPPLMM.KEINNEST)
key_1	Identifier 1	integer	REC_REF = 'MEK' --> Characteristics number REC_REF = 'PPL' --> Inspection plan number REC_REF = 'PAU' --> Inspection requirement number REC_REF = 'RKK','RKD' --> Complaints number (PDM field ID: CMERK.KEY:1,CMM.LFDNR,CPPLMM.PPLNR)
key_2	Identifier 2	integer	REC_REF = 'PPL' --> OP number REC_REF = 'PAU' --> Inspection order number REC_REF = 'RKD' --> Complaints details number (PDM field ID: CMERK.KEY:2,CPPLMM.AFO)
key_3	Identifier 3	integer	REC_REF = 'PAU' --> OP number REC_REF = 'RKD' --> Identifier in tree structure (PDM field ID: CMERK.KEY:3)
key_4	Identifier 4	integer	Key field (PDM field ID: CMERK.KEY:4)
key_5	Identifier 5	integer	Key field (PDM field ID: CMERK.KEY:5)
maschine_nr	Machine	char(50)	
mass_angabe	Type of indication of design value	char(50)	ABSOLUT - indication of absolute value RELATIV - indication as relative deviation from target value PROZENTUAL - indication as deviation from target value in per cent The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'MASSANGABE') (PDM field ID: CMM.MASSANG,CPPLMM.MASSANG,CMERK.MASSANG)
mehrfach_stichpr	Partial samples for charact.?	integer	
merkmal_bez	Characteristic designation	char(250)	Characteristic designation (PDM field ID: CMERK.MMBEZ,CMM.MMBEZ,CPPLMM.MMBEZ)
merkmal_nr	Characteristic number	char(50)	Via this one the input of the characteristics catalog (CAQ_MERKMAL, REC_REF = 'MEK' table) is referenced. (PDM field ID: CMERK.CMMNR,CMM.CMMNR,CPPLMM.CMMNR)
merkmal_ort	Characteristic location	char(250)	Description of the characteristic location (PDM field ID: CMM.MMORT,CPPLMM.MMORT)
merkmal_pruef	Process data - Check characteristic?	char(1)	 (PDM field ID: CMM.ERFGRPRUEF,CPPLMM.ERFGRPRUEF,CMERK.E)
merkmal_typ	Characteristic type	char(50)	Product/process characteristic The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'MERKTYP') (PDM field ID: CMERK.MMTYP,CMM.MMTYP,CPPLMM.MMTYP)
messwerf_art	Type of measurement recording	char(50)	- automatic/manual The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'ERFART') (PDM field ID: CPPLMM.ERFART)
messwerf_aut_art	Type of measured value recorded automatically	char(50)	Pressure, temperature, etc. (PDM field ID: CPPLMM.ERFAUTART)
mgruppe	Machine group	char(10)	
modify_flag	Modify flag	smallint	Is required for editing tasks by interfaces
muss_pruef	Mandatory inspection?	smallint	Mandatory inspection 0: Inspection order can be finished without having to check the characteristic 1: Inspection order cannot be finished without having to check the characteristic (PDM field ID: CMM.MUSSPRF,CPPLMM.MUSSPRF)
nennmass_normal	Nominal dimension of measurement standard	float	- Only relevant if REC_TYPE = 'PMV' (PDM field ID: CPPLMM.NENNMNORM)
nur_formel	Process data - Only formula based?	char(1)	 (PDM field ID: CMM.NFORMEL,CPPLMM.NFORMEL,CMERK.NFORMEL)
opeg	OPEG	float	 (PDM field ID: CMM.OPEG,CPPLMM.OPEG,CMERK.OPEG)
opeg_aktiv	OPEG aktiv?	smallint	 (PDM field ID: CMM.OPEGAKTIV,CPPLMM.OPEGAKTIV,CMERK.OPE)

opeg_extern	OPEG extern?	smallint	(PDM field ID: CMM.OPEGEXT,CPPLMM.OPEGEXT,CMERK.OPEGEXT)
opeg_extern_feldid	OPEG userfield identifier	integer	(PDM field ID: CMM.OPEGEXT:FELD,CPPLMM.OPEGEXT:FELD,CME)
opeg_extern_zgart	OPEG userfield type	char(1)	(PDM field ID: CMM.OPEGEXT:ZGART,CPPLMM.OPEGEXT:ZGART,C)
opeg_formel	Process data - Formel OPEG	char(1464)	(PDM field ID: CMM.OPEGFORMEL,CPPLMM.OPEGFORMEL,CMERK.O)
opeg_relativ	OPEG relativ?	float	(PDM field ID: CMM.OPEGREL,CPPLMM.OPEGREL,CMERK.OPEGREL)
opg	Upper plausibility limit (absolute)	float	The upper plausibility limit can also be stated relatively in the OPG_RELATIV field. (PDM field ID: CMM.OPG;PPLMM.OPG;CMERK.OPG)
opg_extern	Upper plausibility limit (external)?	smallint	0 - the upper plausibility limit is fixed (in the OPG or OPG_RELATIV field) 1 - the upper plausibility limit is only transferred when the inspection order is generated (PDM field ID: CMM.OPGEXT;CPPLMM.OPGEXT;CMERK.OPGEXT)
opg_extern_feldid	Field ID at transfer (external)	integer	Only relevant if OPG_EXTERN = 1 Corresponding user fields must have the object type CPAN and the user field key = REC_TYPE (or empty for catalog characteristics) (PDM field ID: CMM.OPGEXT:FELD;CPPLMM.OPGEXT:FELD;...)
opg_extern_zgart	Access type at transfer (external)	char(1)	F - Fast user field S - Slow user field (PDM field ID: CMM.OPGEXT:ZGART;CPPLMM.OPGEXT:ZGART;...)
opg_relativ	Upper plausibility limit (relative)	float	Upper plausibility limit (relative) (PDM field ID: CMM.OPGREL;CPPLMM.OPGREL;CMERK.OPGREL)
otg	Upper tolerance limit (absolute)	float	The upper tolerance limit can also be stated relatively in the OTG_RELATIV field. (PDM field ID: CMM.OTG;CPPLMM.OTG;CMERK.OTG)
otg_aktiv	Autom. defect type at violation of upper	smallint	- applies to single values only (PDM field ID: CMM.OTGAKTIV,CPPLMM.OTGAKTIV)
otg_extern	Upper tolerance limit (external)?	smallint	0 - the upper tolerance limit is fixed (in the OTG or OTG_RELATIV field) 1 - the upper tolerance limit is only transferred when the inspection order is generated (PDM field ID: CMM.OTGEXT;CPPLMM.OTGEXT;CMERK.OTGEXT)
otg_extern_feldid	Field ID at transfer (external)	integer	Only relevant if OTG_EXTERN = 1 Corresponding user fields must have the object type CPAN and the user field key = REC_TYPE (or empty for catalog characteristics). (PDM field ID: CMM.OTGEXT:FELD;CPPLMM.OTGEXT:FELD;...)
otg_extern_zgart	Access type at transfer (external)	char(1)	F - Fast user field S - Slow user field (PDM field ID: CMM.OTGEXT:ZGART;CPPLMM.OTGEXT:ZGART;...)
otg_formel	Process data - Formel OTG	char(1464)	(PDM field ID: CMM.OTGFORMEL,CPPLMM.OTGFORME,CMERK.OTGF)
otg_relativ	Upper tolerance limit (relative)	float	Upper tolerance limit (relative) (PDM field ID: CMM.OTGREL;CPPLMM.OTGREL;CMERK.OTGREL)
passung_id	Fit measure	char(50)	The valid entries can be found in the CAQ_PASSUNG table. (PDM field ID: CMM.GWID,CPPLMM.GWID)
passung_norm	Fit norm	char(50)	The valid entries can be found in the CAQ_PASSUNG table. (PDM field ID: CMM.GWNORM,CPPLMM.GWNORM)
pmv_stat_av	Statistical result - appraiser variation	float	
pmv_stat_ev	Statistical result - equipment variation	float	
pmv_stat_pv	Statistical result - part variation	float	
pmv_stat_r_r	Stat. result - repeatability + reproduc.	float	Stat. result - repeatability + reproducibility
pmv_stat_tv	Statistical result - total variation	float	
ppunkt_rast_fakt	Inspection point - insp. grid frequency	integer	
ppunkt_rast_rel	Inspection point with insp. grid?	integer	
prfraster_x	X-axis grid	char(250)	
prfraster_y	Y-axis grid	char(250)	

prfraster_z	Z-axis grid	char(250)	
probe_gruppe	Sample group	char(50)	
probe_zug	Sampling?	integer	
prplatz_nr	Inspection station number	char(50)	The valid entries can be found in the CAQ_PRPLATZ table (PDM field ID: CPPLMM.PPLATZ)
pruef_ergebnis	Inspection result	char(50)	The field is only relevant for inspection order characteristics (RECREF = 'PAU'). The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PRFERG_MM')
pruef_niveau	Inspection level	char(50)	This field is only relevant for dynamically modified characteristics (RECREF = PPL,PAU). The methods of dynamic modification of the dynamic modification norm are filed in the CAQ_DYNN_PNIVEAU table. (PDM field ID: CPPLMM.PNIVEAU)
pruef_umfang	Inspection scope	char(20)	
pruefm_nr	Gage/gage group	char(50)	The valid entries can be found in the CAQ_PMV_PRUEFM table (PDM field ID: CMM.PMID,CPPLMM.PMID)
pruefung_art	Inspector - Piece - Sequence	char(50)	
pruefung_typ	Inspection type	char(50)	A - attributive V - variable The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PRUEFTYP') (PDM field ID: CMM.PRUEFTYP,CPPLMM.PRUEFTYP)
quelle_details	Source of characteristic details	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'QUELLEDET') (PDM field ID: CPPLMM.QDETAIL)
quelle_dokus	Documents origin	char(50)	
quelle_spezif	Source of specifications	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'QUELLESPEZ') (PDM field ID: CPPLMM.QSPEZ)
rck_01	Upload 1	char(1)	
rck_01_dat	Upload 1 date	date	
rck_01_zeit	Upload 1 time	integer	
rck_02	Upload 2	char(1)	
rck_02_dat	Upload 2 date	date	
rck_02_zeit	Upload 2 time	integer	
rck_dat	Upload date	date	
rck_zeit	Upload time	integer	
rec_ref	Data reference	char(20)	'MEK' = Catalog characteristic 'PAU' = Inspection order characteristic 'PPL' = Inspection plan characteristic 'RKK' = Characteristic from complaints header 'RKD' = Characteristic from complaints detail or subordinate structure (failure analysis) (PDM field ID: CMERK.RECREF)
rec_type	Type of input	char(50)	Empty = Global structures (characteristics catalog) 'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management 'REK' Complaints management PMV = Gage management 'PMV' = Prüfmittelmanagement (PDM field ID: CMERK.RECTYP,CPPLMM.RECTYP)
res_familie	Group	char(20)	
rueckgemeldet	Confirmed	char(1)	
rueckmeld_nr	Confirmation number	integer	
rueckw_zahl	Acceptance number	integer	This field is only relevant if STICHPR_PLAN = "NC". The field name is quite contradictory. Yet it is the acceptance number and not the rejection number. (PDM field ID: CMM.RWMENGE,CPPLMM.RWMENGE)

rueckw_zahl_d	Rejection number	integer	This field is only relevant if STICHPR_PLAN = 'NC'. (PDM field ID: CMM.RUMENGE,CPPLMM.RUMENGE,CMERK.RUMENGE)
serienr_pflicht	Serialnumber required	integer	
sigma_prozess	Sigma process	float	- Only relevant if REC_TYPE = 'PMV' (PDM field ID: CPPLMM.SIGMPR)
skiplot	Characteristic in Skiplot?	smallint	0 - characteristic is not in Skiplot 1 - characteristic is in Skiplot
spc_formel	Process data - SPC formula	char(1464)	 (PDM field ID: CMM.SPCFORMEL,CPPLMM.SPCFORMEL,CMERK.SPC)
spezlist_nr	SERIAL relation to CAQ_SPEZLISTE entry	integer	- Only relevant if REC_REF = 'PAU' If the specifications of the inspection order characteristic are based on an entry of the specification list (CAQ_SPEZLISTE table) then the content of the SPEZLIST_NR field of the corresponding data record of the specification list is entered in this field.
splnr	Split number	char(10)	
status	Status of the characteristic	char(50)	The content of this field is only relevant if REC_REF = 'PAU' . "PRF" = testable (a valid measured value has not yet been recorded) "GEP" = checked (at least one valid measured value available) "FHL" = Error--> characteristic cannot be checked due to inspection plan errors "SKL" = Skiplot (till HYDRA-CAQ V7.1.19 only) "ERB" = inherited (characteristic has inherited all of its measured values, till CAQ V7.1.19 only) The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'MERKSTATUS') Die gültigen Einträge finden sich in der Tabelle CAQ_STATUS (STATUS_TYP = 'MERKSTATUS')
stichpr_anzahl	Number of samples to be checked	integer	Number of samples to be checked (PDM field ID: CMM.STPRANZ;CPPLMM.STPRANZ;CMERK:STPRANZ)
stichpr_plan	Sampling scheme	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'STPLPLAN') (PDM field ID: CMM.STPRPLAN,CPPLMM.STPRPLAN)
stichpr_umfang	Sample size	integer	Sample size (PDM field ID: CMM.STPRUMF.CPPLMM.STPRUMF)
stichpru_einheit	Unit of measure for sample	char(10)	
stichpru_fakt	Factor for sample unit of measure	integer	
sw	Target value	float	Target value (PDM field ID: CMM.SW,CPPLMM.SW)
sw_extern	Target value (external)	smallint	0 - the target value is fixed (in the SW field) 1 - the target value is only transferred when the inspection order is generated (PDM field ID: CMM.SWEXT;CPPLMM.SWEXT;CMERK.SWEXT)
sw_extern_feldid	Field ID at transfer (external)	integer	Only relevant if SW_EXTERN = 1 Corresponding user fields must have the object type CPAN and the user field key = REC_TYPE (or empty for catalog characteristics). (PDM field ID: CMM.SWEXT:FELD;CPPLMM.SWEXT:FELD;...)
sw_extern_zgart	Access type at transfer (external)?	char(1)	F - Fast user field S - Slow user field (PDM field ID: CMM.SWEXT:ZGART;CPPLMM.SWEXT:ZGART;...)
toleranz_normal	Tolerance of measurement standard	float	- Only relevant if REC_TYPE = 'PMV' (PDM field ID: CPPLMM.TOLERNORM)
toleranz_pm	Tolerance of gage	float	- Only relevant if REC_TYPE = 'PMV' (PDM field ID: CPPLMM.TOLERPM)
uagnr	Sub operation number	char(20)	
upeg	UPEG	float	 (PDM field ID: CMM.UPEG,CPPLMM.UPEG,CMERK.UPEG)
upeg_aktiv	UPEG aktiv?	smallint	 (PDM field ID: CMM.UPEGAKTIV,CPPLMM.UPEGAKTIV,CMERK.UPE)
upeg_extern	UPEG extern	smallint	 (PDM field ID: CMM.UPEGEXT,CPPLMM.UPEGEXT,CMERK.UPEGEXT)
upeg_extern_feldid	UPEG userfield identifier	integer	 (PDM field ID: CMM.UPEGEXT:FELD,CPPLMM.UPEGEXT:FELD,CME)

upeg_extern_zgart	UPEG userfield type	char(1)	(PDM field ID: CMM.UPEGEXT:ZGART,CPPLMM.UPEGEXT:ZGART,C)
upeg_formel	Process data - Formula UPEG	char(1464)	(PDM field ID: CMM.UPEGFORMEL,CPPLMM.UPEGFORMEL,CMERK.U)
upeg_relativ	UPEG relativ?	float	(PDM field ID: CMM.UPEGREL,CPPLMM.UPEGREL,CMERK.UPEGREL)
upg	Lower plausibility limit (absolute)	float	The lower plausibility limit can also be stated relatively in the UPG_RELATIV field. (PDM field ID: CMM.UPG;CPPLMM.UPG;CMERK.UPG)
upg_extern	Lower plausibility limit (external)?	smallint	0 - the lower plausibility limit is fixed (in the UPG or UPG_RELATIV field) 1 - the lower plausibility limit is only transferred when inspection orders are generated. (PDM field ID: CMM.UPGEXT;CPPLMM.UPGEXT;CMERK.UPGEXT)
upg_extern_feldid	Field ID at transfer (external)	integer	Only relevant if UPG_EXTERN = 1 Corresponding user fields must have the object type CPAN and the user field key = REC_TYPE (or empty for catalog characteristics). (PDM field ID: CMM.UPGEXT:FELD;CPPLMM.UPGEXT:FELD;...)
upg_extern_zgart	Access type at transfer (external)	char(1)	F - Fast user field S - Slow user field (PDM field ID: CMM.UPGEXT:ZGART;CPPLMM.UPGEXT:ZGART;...)
upg_relativ	Lower plausibility limit (relative)	float	Lower plausibility limit (relative) (PDM field ID: CMM.UPGREL;CPPLMM.UPGREL;CMERK.UPGREL)
user_c_01	Alphanumeric user field	char(50)	(PDM field ID: CMM.FU:1;CPPLMM.FU:1;CMERK.FU:1)
user_c_02	Alphanumeric user field	char(50)	(PDM field ID: CMM.FU:2;CPPLMM.FU:2;CMERK.FU:2)
user_c_03	Alphanumeric user field	char(50)	(PDM field ID: CMM.FU:3;CPPLMM.FU:3;CMERK.FU:3)
user_c_04	Alphanumeric user field	char(50)	(PDM field ID: CMM.FU:4;CPPLMM.FU:4;CMERK.FU:4)
user_c_05	Alphanumeric user field	char(50)	(PDM field ID: CMM.FU:5;CPPLMM.FU:5;CMERK.FU:5)
user_d_01	Date - user field	date	Date - user field 1 (PDM field ID: CMM.FU:13;CPPLMM.FU:13;CMERK.FU:13)
user_d_02	Date - user field	date	Date - user field 2 (PDM field ID: CMM.FU:14;CPPLMM.FU:14;CMERK.FU:14)
user_f_01	Decimal user field	float	Decimal user field 1 (PDM field ID: CMM.FU:11;CPPLMM.FU:11;CMERK.FU:11)
user_f_02	Decimal user field	float	Decimal user field 2 (PDM field ID: CMM.FU:12;CPPLMM.FU:12;CMERK.FU:12)
user_n_01	Numeric user field	integer	(PDM field ID: CMM.FU:6;CPPLMM.FU:6;CMERK.FU:6)
user_n_02	Numeric user field	integer	(PDM field ID: CMM.FU:7;CPPLMM.FU:7;CMERK.FU:7)
user_n_03	Numeric user field	integer	(PDM field ID: CMM.FU:8;CPPLMM.FU:8;CMERK.FU:8)
user_n_04	Numeric user field	integer	Numeric user field 1-5 (PDM field ID: CMM.FU:9;CPPLMM.FU:9;CMERK.FU:9)
user_n_05	Numeric user field	integer	Numeric user field 1-5 (PDM field ID: CMM.FU:10;CPPLMM.FU:10;CMERK.FU:10)
utg	Lower tolerance limit (absolute)	float	The lower tolerance limit can also be stated relatively in the UTG_RELATIV field. (PDM field ID: CMM.UTG;CPPLMM.UTG;CMERK.UTG)
utg_aktiv	Autom. defect type at violation of lower	smallint	Autom. defect type at violation of lower tolerance limit? (PDM field ID: CMM.UTGAKTIV,CPPLMM.UTGAKTIV)
utg_extern	Lower tolerance limit (external)?	smallint	0 - the lower tolerance limit is fixed (in the UTG or UTG_RELATIV field) 1 - the lower tolerance limit is only transferred when the inspection order is generated. (PDM field ID: CMM.UTGEXT;CPPLMM.UTGEXT;CMERK.UTGEXT)

utg_extern_feldid	Field ID at transfer (external)	integer	Only relevant if UTG_EXTERN = 1 Corresponding user fields must have the object type CPAN and the user field key = REC_TYPE (or empty for catalog characteristics). (PDM field ID: CMM.UTGEXT:FELD;CPPLMM.UTGEXT:FELD;...)
utg_extern_zgart	Access type at transfer (external)	char(1)	F - Fast user field S - Slow user field (PDM field ID: CMM.UTGEXT:ZGART;CPPLMM.UTGEXT:ZGART;...)
utg_formel	Process data - Formula UTG	char(1464)	(PDM field ID: CMM.UTGFORMEL,CPPLMM.UTGFORME,CMERK.UTGF)
utg_relativ	Lower tolerance limit (relative)	float	Lower tolerance limit (relative) (PDM field ID: CMM.UTGREL;CPPLMM.UTGREL;CMERK.UTGREL)
verteilung	Share calculation procedure	char(20)	
wert_zufall	Random sequence?	smallint	
zertifikat_druck	Print of certificates	char(50)	Never, selection, always The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'ZERTIFDRU') (PDM field ID: CMM.ZERTPRN,CPPLMM.ZERTPRN)
zuordnung_nr	Reference to failure analysis selection	char(50)	The corresponding catalog for failure analysis selection can be found in the CAQ_ANALAUSSWAHL table. (PDM field ID: CMM.ANAUSNR;CPPLMM.ANAUSNR;CMERK.ANAUSNR)
zus_char_1	Additional field 1 (alphanumeric)	char(250)	(PDM field ID: CMM.ZUSCHR:1,CPPLMM.ZUSCHR:1)
zus_char_2	Additional field 2 (alphanumeric)	char(250)	(PDM field ID: CMM.ZUSCHR:2,CPPLMM.ZUSCHR:2)
zus_char_3	Additional field 3 (alphanumeric)	char(250)	Additional field 3 (alphanumeric) (PDM field ID: CMM.ZUSCHR:3,CPPLMM.ZUSCHR:3)
zus_char_4	Additional field 4 (alphanumeric)	char(250)	Additional field 4 (alphanumeric) (PDM field ID: CMM.ZUSCHR:4,CPPLMM.ZUSCHR:4)
zus_char_5	Additional field 5 (alphanumeric)	char(250)	Additional field 5 (alphanumeric) (PDM field ID: CMM.ZUSCHR:5,CPPLMM.ZUSCHR:5)

3.43. caq_msa_statistics

Table name: caq_msa_statistics		Product: CAQ	
Column name	Column designation	Type	Description
amount		integer	
constant_type		char(10)	
norm		char(50)	
value		float	
verweis		serial	

3.44. caq_mst_wechsel

Table name: caq_mst_wechsel		Product: CAQ	
Designation: insp. point creation by machine status			
Column name	Column designation	Type	Description
aktiv	Is active?	integer	
anlage	Created by	char(50)	Time when the entry was created
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
m_status_quelle	Machine status source	integer	
m_status_ziel	Machine status target	integer	
masch_nr	machine number	char(20)	
position	position	integer	
ppunkt_erzeugen	Create inspection point?	integer	
user_c_01	Alphanumeric user field 1-5	char(50)	
user_c_02	Alphanumeric user field 1-5	char(50)	
user_c_03	Alphanumeric user field 1-5	char(50)	
user_c_04	Alphanumeric user field 1-5	char(50)	
user_c_05	Alphanumeric user field 1-5	char(50)	
user_d_01	Date user field 1-2	date	
user_d_02	Date user field 1-2	date	
user_f_01	Decimal user field 1-2	float	
user_f_02	Decimal user field 1-2	float	
user_n_01	Numeric user field 1-5	integer	
user_n_02	Numeric user field 1-5	integer	
user_n_03	Numeric user field 1-5	integer	
user_n_04	Numeric user field 1-5	integer	
user_n_05	Numeric user field 1-5	integer	

3.45. caq_numpool

Table name: caq_numpool		Product: CAQ	
Archive table: a_caq_numpool		Reload table: r_caq_numpool	
Designation: Number pool of inspection requirements			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Created by
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPANUMP.BER)
eintrag_nr	Number	char(100)	Number (PDM field ID: CPANUMP.EINTNR)
eintrag_typ	Type of number	char(50)	The valid entries can be found in the CAQ_STATUS (STATUS_TYP = 'NUMMERTYP') table (PDM field ID: CPANUMP.EINTTYP)
geprueft	Only for internal use	smallint	
losnr	batch number	char(20)	
pps_rueckmeld	KSBEZ	smallint	
ppunkt_abs_date	Insp. point completion date	date	
ppunkt_abs_time	Insp. point completion time	integer	
ppunkt_abs_von	Insp. point completed by	char(50)	
ppunkt_abs_vonk	Insp. point completed by card	char(50)	
ppunkt_abs_vonp	Insp. point completed by person	integer	
ppunkt_anl_date	Insp. point creation date	date	
ppunkt_anl_dauer	Insp. point actual duration by creation	integer	
ppunkt_anl_menge	Insp. point actual quantity by creation	float	
ppunkt_anl_time	Insp. point creation time	integer	
ppunkt_anl_ursach	Insp. point creation cause	char(50)	
ppunkt_anl_von	Insp. point created by	char(50)	
ppunkt_anl_vonk	Insp. point created by card	char(50)	
ppunkt_anl_vonp	Insp. point created by person	integer	
ppunkt_ausschuss	Insp. point scrap	float	
ppunkt_bemerkung	Insp. point comment	char(10)	
ppunkt_charge	Insp. point batch	char(50)	
ppunkt_equipment	Insp. point equipment	char(20)	
ppunkt_maschine	Insp. point target workplace	char(20)	
ppunkt_menge	Insp. point quantity	float	
ppunkt_muss_prf	Insp. point mandatory inspection	integer	
ppunkt_nacharbeit	Insp. point rework	float	
ppunkt_platz	Insp. point techn. place	char(20)	
ppunkt_probe	Insp. point phys. sample	char(20)	

ppunkt_prod_masch	Insp. point producing workplace	char(20)	
ppunkt_pruef_umf	Insp. point inspection scope	char(20)	
ppunkt_ref_dauer	Insp. point reference duration	integer	
ppunkt_ref_menge	Insp. point reference quantity	float	
ppunkt_teillos	Insp. point partial batch	char(50)	
ppunkt_ursach_dat	Insp. point reference event date	date	
ppunkt_ursach_zeit	Insp. point reference event time	integer	
ppunkt_user_c1	Insp. point userfield C1	char(50)	
ppunkt_user_c2	Insp. point userfield C2	char(50)	
ppunkt_user_d1	Insp. point userfield D1	date	
ppunkt_user_n1	Insp. point userfield N1	integer	
ppunkt_user_n2	Insp. point userfield N2	integer	
ppunkt_user_t1	Insp. point userfield T1	integer	
ppunkt_ve_auswm	Insp. point usage decision selected set	char(10)	
ppunkt_ve_code	Insp. point usage decision code	char(10)	
ppunkt_ve_codgr	Insp. point usage decision codegroup	char(10)	
ppunkt_ve_katart	Insp. point usage decision catalog type	char(10)	
ppunkt_ve_werk	Insp. point usage decision plant	char(4)	
probe_date	Phys. sample creation date	date	
probe_gruppe	Phys. sampling group	char(50)	
probe_index	Phys. sample index	integer	
probe_maschine	Phys. sample created from machine	char(50)	
probe_time	Phys. sample creation time	integer	
probe_von	Phys. sample created by	char(50)	
probe_vonk	Phys. sample created by card	char(50)	
probe_vonp	Phys. sample created by person	integer	
pruefanf_nr	Inspection requirement number	integer	Inspection requirements are defined in the CAQ_PRUEFANF table. (PDM field ID: CPANUMP.PANNR)
pruefauf_nr	Inspection order number	integer	Inspection orders are defined in the CAQ_PAUKOP table. (PDM field ID: CPANUMP.PAUNR)
rck_01	Confirmed in system 1?	char(1)	
rck_01_dat	Confirmation date in system 1	date	
rck_01_zeit	Confirmation time in system 1	integer	
rck_02	Confirmed in system 2?	char(1)	
rck_02_dat	Confirmation date in system 2	date	
rck_02_zeit	Confirmation time in system 2	integer	
rck_dat	Confirmation date	date	Confirmation date
rck_zeit	Confirmation time	integer	Confirmation time
rec_type	Input type	char(50)	'WEP ' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPANUMP.RECTYP)
rueckgemeldet	Confirmed	char(1)	J/N, indicates whether the log record has been uploaded to the PPS system
skiplot	skiplot	integer	
status	Status	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'NUMPOOLSTA' AND ZUSATZ LIKE *[NUMMERTYP:<aktueller EINTRAG_TYP>]*) (PDM field ID: CPANUMP.STA)

status_bearb	Modification status	char(50)	
status_info	Posting required informations	char(250)	
stichpr_nr	inspection point sample number	integer	
user_c_01	Alphanumeric user field	char(50)	(PDM field ID: CPANUMP.FU:1)
user_c_02	Alphanumeric user field	char(50)	(PDM field ID: CPANUMP.FU:2)
user_c_03	Alphanumeric user field	char(50)	(PDM field ID: CPANUMP.FU:3)
user_c_04	Alphanumeric user field	char(50)	(PDM field ID: CPANUMP.FU:4)
user_c_05	Alphanumeric user field	char(50)	Alphanumeric user field (PDM field ID: CPANUMP.FU:5)
user_d_01	Date user field	date	(PDM field ID: CPANUMP.FU:13)
user_d_02	Date user field	date	(PDM field ID: CPANUMP.FU:14)
user_f_01	Decimal user field	float	Decimal user field (PDM field ID: CPANUMP.FU:11)
user_f_02	Decimal user field	float	Decimal user field (PDM field ID: CPANUMP.FU:12)
user_n_01	Numeric user field 1-5	integer	(PDM field ID: CPANUMP.FU:6)
user_n_02	Numeric user field 1-5	integer	(PDM field ID: CPANUMP.FU:7)
user_n_03	Numeric user field 1-5	integer	(PDM field ID: CPANUMP.FU:8)
user_n_04	Numeric user field 1-5	integer	Numeric user field 1-5 (PDM field ID: CPANUMP.FU:9)
user_n_05	Numeric user field 1-5	integer	(PDM field ID: CPANUMP.FU:10)

3.46. caq_pan_zusatz

Table name: caq_pan_zusatz		Product: CAQ	
Archive table: a_caq_pan_zusatz		Reload table: r_caq_pan_zusatz	
Designation: Additional insp. requirements infomation			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	
anlage_time	Initial data creation - Time	integer	
artikel_bez	Article designation	char(50)	
artikel_bez_kunde	Customer article designation	char(50)	
artikel_nr_kunde	Customer article number	char(50)	
artikel_nr_lief	Supplier article number	char(50)	
auftrag_nr_kunde	Customer order number	char(20)	
auftrag_pos	Order position	integer	
bearb	Last editor	char(50)	
bearb_date	Last change - Date	date	
bearb_time	Last change - Time	integer	
beleg_nr	Note number	char(20)	
beleg_pos	Note position	integer	
bereich	Area	char(10)	
buchung_date	Document posting date	date	
charge_lager	Batch location	char(20)	
charge_nr_lief	Supplier Batch number	char(20)	
hersteller_bez	Manufacturer designation	char(50)	
kunde_bez	Customer designation	char(50)	
lieferant_bez	Supplier designation	char(50)	
matbeleg_jahr	Material document year	integer	
matbeleg_nr	Material document number	char(20)	
matbeleg_pos	Material document item	integer	
plan_gruppe	Inspection plan group	char(20)	
plan_gruppe_zaehl	Inspection plan group counter	char(20)	
plan_guelt_ab	Inspection plan valid since	date	
plan_ktext	Short text of inspection plan	char(50)	
plan_typ	Plan type	char(20)	
plan_version	Inspection plan version	integer	
plan_verwend	Inspection plan usage	char(20)	
pps_aender	PPS last change - User	char(20)	
pps_aender_date	PPS last change - Date	date	
pps_anlage	PPS initial creation - User	char(20)	
pps_anlage_date	PPS initial creation - Date	date	
pruefanf_nr	Inspection requirement number	integer	
pruefflos_text	Short text of inspection batch	char(50)	

pruefung_ende	Inspection end	date	
pruefung_start	Inspection start	date	
rec_type	Input type	char(50)	(PDM field ID: Bereichstyp)
stichpr_einheit	Sampling unit	char(10)	
stichpr_umfang	Sampling size	integer	

3.47. caq_pauanmeld

Table name: caq_pauanmeld		Product: CAQ	
Archive table: a_caq_pauanmeld		Reload table: r_caq_pauanmeld	
Designation: Inspection orders registered for inspect		Description: The table administers all inspection orders that are registered for inspection	
Column name	Column designation	Type	Description
anlage	Created by	char(50)	Time when the entry was created
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
ausschuss	Scrap confirmed	float	This parameter is only relevant in connection with the BAPIs CPAU.DEVANMELDEN, CPAU.DEVABMELDEN, CPAU.DEVUNTERBR and CPAU.DEVAKTSTUECK. (PDM field ID: CPAU.EGR:AUS)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPAU.BER)
device_id	Device ID	char(50)	 (PDM field ID: CPAU.DEVICE:ID)
device_typ	Device type	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'DEVICETYP') (PDM field ID: CPAU.DEVICE:TYP)
nacharbeit	Rework quantity confirmed	float	This parameter is only relevant in connection with the BAPIs CPAU.DEVANMELDEN, CPAU.DEVABMELDEN, CPAU.DEVUNTERBR and CPAU.DEVAKTSTUECK. (PDM field ID: CPAU.EGR:NACH)
prod_menge	Yield confirmed	float	This parameter is only relevant in connection with the BAPIs CPAU.DEVANMELDEN, CPAU.DEVABMELDEN, CPAU.DEVUNTERBR and CPAU.DEVAKTSTUECK. (PDM field ID: CPAU.EGR:MENGE)
pruefanf_nr	Inspection requirement number	integer	Inspection requirements are defined in the CAQ_PRUEFANF table. (PDM field ID: CPAU.PANNR)
pruefauf_nr	Inspection order number	integer	Inspection orders are defined in the CAQ_PAUKOP table. (PDM field ID: CPAU.PAUNR)
rec_type	Input type	char(50)	"WEP" = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPAU.RECTYP)
status	Logon status of inspection order (PAU) t	char(50)	This parameter is only relevant in connection with the BAPIs CPAU.DEVANMELDEN, CPAU.DEVABMELDEN, CPAU.DEVUNTERBR and CPAU.DEVAKTSTUECK. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PAUANMELD')

3.48. caq_paukonf

Table name: caq_paukonf		Product: CAQ	
Archive table: a_caq_paukonf		Reload table: r_caq_paukonf	
Designation: Inspection order settings			
Column name	Column designation	Type	Description
afo	Operation	integer	(PDM field ID: CPAUCFG.AFO)
anlage	Time when the entry was created	char(50)	Time when the entry was created
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPAUCFG.BER)
maschine_nr	Machine number	char(50)	Machine (PDM field ID: CPAUCFG.MNR)
pruef_zustand	only for internal use	char(50)	(PDM field ID: CPAUCFG.PZUSTAND)
pruefanf_nr	Inspection requirement number	integer	Inspection requirement number (PDM field ID: CPAUCFG.PANNR)
pruefauf_nr	Inspection order number	integer	Inspection order number (PDM field ID: CPAUCFG.PAUNR)
pruefer_nr	Current Inspector	char(50)	(PDM field ID: CPAUCFG.PNR)
pruefmittel_nr	Current gage	char(50)	(PDM field ID: CPAUCFG.PMID)
rec_type	Type of the entry	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPAUCFG.RECTYP)
werkzeug_nr	Current Tool	char(50)	(PDM field ID: CPAUCFG.WNR)

3.49. caq_paukop

Table name: caq_paukop		Product: CAQ	
Archive table: a_caq_paukop		Reload table: r_caq_paukop	
Designation: Inspection orders		Description: The table administers inspection orders. It includes data from all areas (production, goods receipt and goods issue, initial sample inspection, gage management). Depending on the type of inspection requirement only some of the fields listed in the following are relevant.	
Column name	Column designation	Type	Description
abschluss_date	Closing date	date	Closing date (PDM field ID: CPAU.ABSDAT)
abschluss_time	Closing time	integer	Closing time (PDM field ID: CPAU.ABSZEI)
abschluss_von	Personnel number of the finishing person	char(50)	Personnel number of the finishing person (PDM field ID: CPAU.ABSVON)
abschluss_vonk	Badge number of the finishing person	char(50)	Badge number of the finishing person (PDM field ID: CPAU.ABSKNR)
abschluss_vonp	Finished by person	integer	
afolg	order sequence id	char(10)	
anlage	Created by	char(50)	Time when the entry was created
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
arbgang_bez	Operation designation	char(250)	Operation designation (PDM field ID: CPAU.AGBEZ)
arbgang_nr	Operation number	char(50)	Operation number (PDM field ID: CPAU.AGNR)
ausschuss	Scrap quantity	float	Scrap quantity (PDM field ID: CPAU.EGR:AUS)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPAU.BER)
eingepplant	Planned on	char(1)	
ergebnis	Inspection result	char(50)	"": a result is not yet available "OK": Inspection ok "NOK": Inspection not ok The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PAUERG') (PDM field ID: CPAU.ERGEB)
gis_key	GIS key	char(50)	GIS key
kostenstelle	Cost center	char(20)	
lager	Location	char(20)	
maschine_nr	Machine	char(50)	Machine (PDM field ID: CPAU.MNR)
menge_einheit	Quantity unit	char(10)	
mgruppe	Machine group	char(10)	
nacharbeit	Rework quantity	float	Rework quantity (PDM field ID: CPAU.EGR:NACH)

parts_per_million	Parts per Million	float	Parts per Million (PDM field ID: CPAU.EGR:PPM)
pps_rueckmeld	Confirmed	smallint	
ppunkt_auswmen	Insp. point selected set	char(10)	
ppunkt_bewer_rel	Make usage decision in subsystem?	integer	
ppunkt_chargepfl	Insp. point batch obligatory?	integer	
ppunkt_code_a	Insp. point usage decision code accept.	char(10)	
ppunkt_code_r	Insp. point usage decision code rejected	char(10)	
ppunkt_codgr_a	Insp. point usage dec. codegroup accept.	char(10)	
ppunkt_codgr_r	Insp. point usage dec. codegroup reject.	char(10)	
ppunkt_frei	Free inps. point creation?	integer	
ppunkt_int_einh	Insp. point interval unit	char(20)	
ppunkt_int_einho	Insp. point interval unit by interface	char(20)	
ppunkt_int_wert	Insp. point interval value	integer	
ppunkt_katart	Insp. point catalog type	char(10)	
ppunkt_menge	Quantity based inps. point creation?	integer	
ppunkt_menge_rel	Insp. point quantity relevant?	integer	
ppunkt_relevant	Insp. point relevant?	integer	
ppunkt_rmeld_rel	Insp. point confirmation relevant?	integer	
ppunkt_sf_equ_l	Insp. point equipment label	char(20)	
ppunkt_sf_equ_r	Insp. point equipment relevant?	integer	
ppunkt_sf_prb_l	Insp. point phys. sample label	char(20)	
ppunkt_sf_prb_r	Insp. point phys. sample relevant?	integer	
ppunkt_sf_tpl_l	Insp. point techn. place label	char(20)	
ppunkt_sf_tpl_r	Insp. point techn. place relevant?	integer	
ppunkt_sf_uc1_l	Insp. point user field C1 label	char(20)	
ppunkt_sf_uc1_r	Insp. point user field C1 relevant?	integer	
ppunkt_sf_uc2_l	Insp. point user field C2 label	char(20)	
ppunkt_sf_uc2_r	Insp. point user field C2 relevant?	integer	
ppunkt_sf_ud1_l	Insp. point user field D1 label	char(20)	
ppunkt_sf_ud1_r	Insp. point user field D1 relevant?	integer	
ppunkt_sf_un1_l	Insp. point user field N1 label	char(20)	
ppunkt_sf_un1_r	Insp. point user field N1 relevant?	integer	
ppunkt_sf_un2_l	Insp. point user field N2 label	char(20)	
ppunkt_sf_un2_r	Insp. point user field N2 relevant?	integer	
ppunkt_sf_ut1_l	Insp. point user field T1 label	char(20)	
ppunkt_sf_ut1_r	Insp. point user field T1 relevant?	integer	
ppunkt_tlospfl	Insp. point partial batch obligatory?	integer	
ppunkt_typ	Insp. point type	char(10)	
ppunkt_werk	Insp. point plant	char(4)	
ppunkt_zeit	Duration based inps. point creation?	integer	
prod_menge	Quantity produced	float	Quantity produced (PDM field ID: CPAU.EGR:MENGE)
prplatz_bez	Plant of inspection designation	char(50)	
prplatz_nr	Inspection station	char(50)	Inspection stations are defined in the CAQ_PRPLATZ table. (PDM field ID: CPAU.PPLATZ)
prplatz_werk	Plant of inspection station	char(4)	

pruefanf_nr	Inspection requirement number	integer	Inspection requirements are defined in the caq_pruefanf table. (PDM field ID: CPAU.PANNR)
pruefauf_nr	Inspection order number	integer	Inspection order number (PDM field ID: CPAU.PAUNR)
rck_01	Confirmed in system 1?	char(1)	
rck_01_dat	Confirmation date in system 1	date	
rck_01_zeit	Confirmation time in system 1	integer	
rck_02	Confirmed in system 2?	char(1)	
rck_02_dat	Confirmation date in system 2	date	
rck_02_zeit	Confirmation time in system 2	integer	
rck_dat	Confirmation date	date	
rck_zeit	Confirmation time	integer	
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPAU.RECTYP)
rueckgemeldet	Confirmed?	char(1)	
sap_vg_nr	SAP operation number	char(4)	
sap_vgfolge	SAP operation sequence	char(6)	
skiplot	Skiplot?	smallint	
splnr	split number	char(10)	
status	Status	char(50)	"KMM" - Inspection requirement does not include testable characteristics "SKL" - Skip lot (only till CAQ V7.1.19) "ERS" - Created (no valid measured values recorded) "FRE" - Released (no valid measured values recorded) "TER" - Partial result (valid measured values recorded, not all partial inspection orders have been finished yet) "STO" - cancelled "ABG" - finished The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PAUSTATUS') Die gültigen Einträge finden sich in der Tabelle CAQ_STATUS (STATUS_TYP = 'PAUSTATUS') (PDM field ID: CPAU.STA)
status_info	Status information	char(250)	
subsys_nr	subsystem number	char(10)	
uagnr	sub-operation number	char(20)	
user_c_01	Alphanumeric user field	char(50)	
user_c_02	Alphanumeric user field	char(50)	
user_c_03	Alphanumeric user field	char(50)	
user_c_04	Alphanumeric user field	char(50)	
user_c_05	Alphanumeric user field	char(50)	
user_d_01	Date user field	date	
user_d_02	Date user field	date	
user_f_01	Decimal user field	float	
user_f_02	Decimal user field	float	
user_n_01	Numeric user field	integer	
user_n_02	Numeric user field	integer	
user_n_03	Numeric user field	integer	
user_n_04	Numeric user field	integer	
user_n_05	Numeric user field	integer	

werk	plant	char(4)	
------	-------	---------	--

3.50. caq_paumwert

Table name: caq_paumwert		Product: CAQ	
Archive table: a_caq_paumwert		Reload table: r_caq_paumwert	
Designation: Measured values		Description: The spreadsheet administers the single values of the inspection order characteristics. It includes data from all areas (production, goods receipt and goods issue, initial sample inspection, gage management). In case of attributive characteristics only one value is recorded in which the number of nonconforming units is noted. The number of errors results from the entries of the failure analysis catalog (caq_fhlanal table) belonging to the sample.	
Column name	Column designation	Type	Description
afo	Operation	integer	Corresponding characteristics are defined in the CAQ_MERKMAL table. (PDM field ID: CPAUMW.AFO)
anlage	Initial data creation - HYDR user	char(50)	Time when the entry was created
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
anz_f_einheiten	Number of defect units	integer	 (PDM field ID: CPAUMW.ERRMENGE)
anz_fehler	Sample size	integer	The field name is misleading. In this field the sample size can be defined for attributive characteristics. (PDM field ID: CPAUMW.STPRUMF)
anzahl_afehler	Only for internal use	integer	
attribut	attribute	char(20)	
bearb	Last change - HYRA user	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bemerkung	Comment	char(250)	Comment (PDM field ID: CPAUMW.BEM)
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPAUMW.BER)
beweint_grp	Group from attributive assessment catalo	char(50)	The corresponding entries are defined in the HYD_VWE_STAT table (VWE_ID = "PRUEFTYP_A") (PDM field ID: CPAUMW.BEWEINT:GRP)
beweint_nr	Number attributive assessment catalog	char(50)	The corresponding entries are defined in the HYD_VWE_STAT table (VWE_ID = "PRUEFTYP_A") (PDM field ID: CPAUMW.BEWEINT:NR)
bewkat_auswmen_1	Evaluation catalog 1-selected set	char(10)	
bewkat_auswmen_2	Evaluation catalog 2-selected set	char(10)	
bewkat_auswmen_3	Evaluation catalog 3 - selected set	char(10)	
bewkat_auswmen_4	Evaluation catalog 4 - selected set	char(10)	
bewkat_auswmen_5	Evaluation catalog 5 - selected set	char(10)	
bewkat_code_1	Evaluation catalog 1 - code	char(10)	
bewkat_code_2	Evaluation catalog 2 - code	char(10)	
bewkat_code_3	Evaluation catalog 3 - code	char(10)	
bewkat_code_4	Evaluation catalog 4 - code	char(10)	
bewkat_code_5	Evaluation catalog 5 - code	char(10)	
bewkat_codgr_1	Evaluation catalog 1- codegroup	char(10)	
bewkat_codgr_2	Evaluation catalog 2 - codegroup	char(10)	
bewkat_codgr_3	Evaluation catalog 3 - codegroup	char(10)	
bewkat_codgr_4	Evaluation catalog 4 - code group	char(10)	
bewkat_codgr_5	Evaluation catalog 5 - code group	char(10)	

bewkat_katart_1	Evaluation catalog 1- catalog type	char(10)	
bewkat_katart_2	Evaluation catalog 2- catalog type	char(10)	
bewkat_katart_3	Evaluation catalog 3 - catalog type	char(10)	
bewkat_katart_4	Evaluation catalog 4 - catalog type	char(10)	
bewkat_katart_5	Evaluation catalog 5 - catalog type	char(10)	
bewkat_werk_1	Evaluation catalog 1 - plant	char(4)	
bewkat_werk_2	Evaluation catalog 2 - plant	char(4)	
bewkat_werk_3	Evaluation catalog 3 - plant	char(4)	
bewkat_werk_4	Evaluation catalog 4 - plant	char(4)	
bewkat_werk_5	Evaluation catalog 5 - plant	char(4)	
fehler	Only for internal use	char(250)	(PDM field ID: CPAUMW.ERRTYP)
fehler_klasse	Failure class	char(20)	
formel_arg_1	Argument 1	float	
formel_arg_10	Argument 10	float	
formel_arg_2	Argument 2	float	
formel_arg_3	Argument 3	float	
formel_arg_4	Argument 4	float	
formel_arg_5	Argument 5	float	
formel_arg_6	Argument 6	float	
formel_arg_7	Argument 7	float	
formel_arg_8	Argument 8	float	
formel_arg_9	Argument 9	float	
gis_key	GIS key	char(50)	GIS key
messwert	Measured value	float	Relevant for variable characteristics only (PDM field ID: CPAUMW.MW)
messwert_date	Date of the measure value	date	Date of the measure value (PDM field ID: CPAUMW.MWDAT)
messwert_id	Unique identifier of the measured value	char(100)	Unique identifier of the measured value (PDM field ID: CPAUMW.MWID)
messwert_ref	measure reference	char	(PDM field ID: CPAUMW.MW:REF)
messwert_time	Time of measure value	integer	Time of measure value (PDM field ID: CPAUMW.MWZEI)
messwert_von	Measured by	char(50)	The editor's personnel number (PDM field ID: CPAUMW.PNR)
messwert_vonk	The editor's badge number	char(50)	The editor's badge number (PDM field ID: CPAUMW.KNR)
messwert_vonp	Measured by person	integer	
nest_nr	Cavity number	char(50)	Cavity number (PDM field ID: CPAUMW.NEST)
position	position	char(100)	
pps_rueckmeld	Uploaded to PPS?	smallint	0: not yet uploaded 1: uploaded (PDM field ID: CPAUMW.PPS:RMELD)
pruef_ergebnis	Manual inspection result	char(50)	
pruefanf_nr	Inspection requirement number	integer	Inspection requirements are defined in the CAQ_PRUEFANF table. (PDM field ID: CPAUMW.PANNR)
pruefauf_nr	Inspection order number	integer	Inspection orders are defined in the CAQ_PAUKOP table. (PDM field ID: CPAUMW.PAUNR)

rck_01	Confirmed in system 1?	char(1)	
rck_01_dat	Confirmation date in system 1	date	
rck_01_zeit	Confirmation time in system 1	integer	
rck_02	Confirmed in system 2?	char(1)	
rck_02_dat	Confirmation date in system 2	date	
rck_02_zeit	Confirmation time in system 2	integer	
rck_dat	Confirmation date	date	Confirmation date
rck_zeit	Confirmation time	integer	Confirmation time
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPAUMW.RECTYP)
rueckgemeldet	Confirmed?	char(1)	J/N, indicates whether the log record has been uploaded to the PPS system
stichpr_nr	Sample number	integer	Corresponding samples are defined in the CAQ_PAUSTICH table. (PDM field ID: CPAUMW.STPRNR)
ungueltig	Invalid flag	smallint	0: Valid value 1: Invalid value (PDM field ID: CPAUMW.UNGUELTIG)
wert_nr	Consecutive number within the sample	integer	Consecutive number within the sample (PDM field ID: CPAUMW.WERTNR)

3.51. caq_paunumm

Table name: caq_paunumm		Product: CAQ	
Archive table: a_caq_paunumm		Reload table: r_caq_paunumm	
Designation: Number entries		Description: The table administers the numbers recorded for inspection order characteristics, samples or single values. It includes data from all areas (production, goods receipt and goods issue, initial sample inspection, gage management).	
Column name	Column designation	Type	Description
afo	Operation	integer	Corresponding characteristics are defined in the CAQ_MERKMAL table. (PDM field ID: CPAUNR.AFO)
anlage	Created by	char(50)	Time when the entry was created
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPAUNR.BER)
eintrag_nr	Number	char(100)	A list of the numbers that are available can optionally be in the CAQ_NUMPOOL table. (PDM field ID: CPAUNR.EINTNR)
eintrag_typ	Type of number entry	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'NUMMERTYP') (PDM field ID: CPAUNR.EINTTYP)
gis_key	GIS key	char(50)	GIS key
pruefanf_nr	Inspection order number	integer	Inspection orders are defined in the CAQ_PAUKOP. (PDM field ID: CPAUNR.PANNR)
pruefauf_nr	Inspection requirement number	integer	Inspection requirements are defined in the CAQ_PRUEFANF table. (PDM field ID: CPAUNR.PAUNR)
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPAUNR.RECTYP)
stichpr_nr	Sample number	integer	Samples are filed in the CAQ_PAUSTICH table. (PDM field ID: CPAUNR.STPRNR)
wert_nr	Value number within the sample	integer	Measured values are defined in the CAQ_PAUMWERT table. (PDM field ID: CPAUNR.WERTNR)

3.52. caq_paustich

Table name: caq_paustich		Product: CAQ	
Archive table: a_caq_paustich		Reload table: r_caq_paustich	
Designation: Sample statistics		Description: This table contains the sample statistics of inspection step characteristics. It contains data of all subareas (production, goods receipt, etc.). Only valid measured values will be considered for this calculations.	
Column name	Column designation	Type	Description
abgeschl	Sample finished?	smallint	0: Sample has not been finished 1: Sample has been finished
abschl_date	Completion date of sample	date	Completion date of sample (PDM field ID: CPAUSP.ABSDAT)
abschl_time	Completion time of sample	integer	Completion time of sample (PDM field ID: CPAUSP.ABSZEI)
abschl_von	Sample finished by (personnel no.)	char(50)	Sample finished by (personnel no.) (PDM field ID: CPAUSP.ABSVON)
abschl_vonk	Sample finished by (badge no.)	char(50)	Sample finished by (badge no.) (PDM field ID: CPAUSP.ABSKNR)
abschl_vonp	Sample finished by person	integer	
afo	Operation	integer	Corresponding characteristics are defined in the CAQ_MERKMAL table. (PDM field ID: CPAUSP.AFO)
amm	Only for internal use	float	
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
anzahl_afehler	Only for internal use	integer	
anzahl_fehler	Number of errors	integer	In case of variable characteristics the number of single values with violations of limit values are recorded here. The number of nonconforming units are recorded in this field when it comes to attributive characteristics.
anzahl_otgv	No. of violated upper tolerance limits	integer	
anzahl_utgv	No. of violated lower tolerance limits	integer	
attribut	Attribute	char(20)	
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bemerkung	Comment	char(250)	
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPAUSP.BER)
bewkat_auswmen_1	Evaluation catalog 1 - selected set	char(10)	
bewkat_auswmen_2	Evaluation catalog 2 - selected set	char(10)	
bewkat_auswmen_3	Evaluation catalog 3 - selected set	char(10)	
bewkat_auswmen_4	Evaluation catalog 4 - selected set	char(10)	
bewkat_auswmen_5	Evaluation catalog 5 - selected set	char(10)	
bewkat_code_1	Evaluation catalog 1 - code	char(10)	
bewkat_code_2	Evaluation catalog 2 - code	char(10)	
bewkat_code_3	Evaluation catalog 3 - code	char(10)	
bewkat_code_4	Evaluation catalog 4 - code	char(10)	
bewkat_code_5	Evaluation catalog 5 - code	char(10)	

bewkat_codgr_1	Evaluation catalog 1 - ceode group	char(10)	
bewkat_codgr_2	Evaluation catalog 2 - code group	char(10)	
bewkat_codgr_3	Evaluation catalog 3 - code group	char(10)	
bewkat_codgr_4	Evaluation catalog 4 - code group	char(10)	
bewkat_codgr_5	Evaluation catalog 5 - code group	char(10)	
bewkat_katart_1	Evaluation catalog 1- catalog type	char(10)	
bewkat_katart_2	Evaluation catalog 2 - catalog type	char(10)	
bewkat_katart_3	Evaluation catalog 3 - catalog type	char(10)	
bewkat_katart_4	Evaluation catalog 4 - catalog type	char(10)	
bewkat_katart_5	Evaluation catalog 5 - catalog type	char(10)	
bewkat_werk_1	Evaluation catalog 1- plant	char(4)	
bewkat_werk_2	Evaluation catalog 2 - plant	char(4)	
bewkat_werk_3	Evaluation catalog 3 - plant	char(4)	
bewkat_werk_4	Evaluation catalog 4 - plant	char(4)	
bewkat_werk_5	Evaluation catalog 5 - plant	char(4)	
c	Number of defects	integer	
cg_1	Gage capability 1	float	
cg_2	Gage capability 2	float	
cg_3	Gage capability 3	float	
cgk_1	Gage capability Index 1	float	
cgk_2	Gage capability Index 2	float	
cgk_3	Gage capability Index 3	float	
cm	Machine capability	float	
cm_1	Machine capability 1	float	
cm_2	Machine capability 2	float	
cm_3	Machine capability 3	float	
cmk	Machine capability index	float	
cmk_1	Machine capability index 1	float	
cmk_2	Machine capability index 2	float	
cmk_3	Machine capability index 3	float	
cp	Process capability	float	
cp_1	Process capability 1	float	
cp_1_syst	System process capability 1	float	
cp_2	Process capability 2	float	
cp_2_syst	System process capability 2	float	
cp_3	Process capability 3	float	
cp_3_syst	System process capability 3	float	
cp_syst	System process capability	float	
cpk	Process capability index	float	
cpk_1	Process capability index 1	float	
cpk_1_syst	System process capability index 1	float	
cpk_2	Process capability index 2	float	
cpk_2_syst	System process capability index 2	float	
cpk_3	Process capability index 3	float	
cpk_3_syst	System process capability index 3	float	
cpk_syst	System process capability index	float	

cq	Average of defects	float	
device_id	Device ID	char(50)	Device ID (PDM field ID: CPAUSP.DEVICE:ID)
device_stichpr	Sample number specific to devices	integer	Sample number specific to devices (PDM field ID: CPAUSP.DEVICE:STPRNR)
device_typ	Device type	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'DEVICETYP') (PDM field ID: CPAUSP.DEVICE:TYP)
dyn_pscharf_next	Dynamic mod. - Following insp. severity	char(50)	
dyn_pscharf_nr	Dynamic mod. - Current insp. severity	char(50)	
dyn_pscharf_usr	Dynamic mod. - Adjusted insp. severity	char(50)	
einheit	Unit	char(50)	(PDM field ID: CPAUSP.CEINH)
erst_abschl_date	First sample completion - Date	date	
erst_abschl_time	First sample completion - Time	integer	
erst_mw_date	Date of first measured value	date	Date of first measured value
erst_mw_time	Time of first measured value	integer	Time of first measured value
erst_mw_ts	Date/Time of first measured value	datetime	
erst_mw_von	First measured value of (personnel no.)	char(50)	First measured value of (personnel no.)
erst_mw_vonk	First measure value of (badge no.)	char(50)	First measure value of (badge no.)
erst_mw_vonp	First measured value by person	integer	
fehler	Only for internal use	char(250)	
fehler_klasse	Failure class	char(20)	
fhleinh	Number of defect units	integer	
format	Measure format	char(250)	(PDM field ID: CPAUSP.FMT)
gis_key	GIS key	char(50)	GIS key
k_wert_ber	Calculated K value	float	This field is only relevant for variable characteristics.
karte1	Control chart 1	char(50)	Control chart 1 (PDM field ID: CPAUSP.KARTE:1)
karte1_mw	Mean value (Chart 1)	float	- Applies for control chart 1
karte1_oeg	Upper action limit (Chart 1)	float	- Applies for control chart 1
karte1_owg	Upper warning limit (Chart 1)	float	- Applies for control chart 1
karte1_ueg	Lower action limit (Chart 1)	float	- Applies for control chart 1
karte1_uwg	Lower warning limit (Chart 1)	float	- Applies for control chart 1
karte2	Control chart 2	char(50)	Control chart 2 (PDM field ID: CPAUSP.KARTE:2)
karte2_mw	Mean value (Chart 2)	float	- Applies for control chart 2
karte2_oeg	Upper action limit (Chart 2)	float	- Applies for control chart 2
karte2_owg	Upper warning limit (Chart 2)	float	- gilt für Regelkarte 2
karte2_ueg	Lower action limit (Chart 2)	float	- Applies for control chart 2
karte2_uwg	Lower warning limit (Chart 2)	float	- Applies for control chart 2
konstm_paustich	Only for internal use	smallint	
letzt_mw_date	Date of last measured value	date	Date of last measured value
letzt_mw_time	Time of last measured value	integer	Time of last measured value
letzt_mw_ts	Date/Time of last measured value	datetime	
letzt_mw_von	Last measured value of (personnel no.)	char(50)	Last measured value of (personnel no.)
letzt_mw_vonk	Last measured value of (badge no.)	char(50)	Last measured value of (badge no.)
letzt_mw_vonp	Last measured value by person	integer	

m	Number of samples > 0 single value	integer	Number of samples with more than null valid single values
m_r	Number of samples > 1 single value	integer	This field is only relevant for variable characteristics. Samples with multiple measurements
maschine_nr	Machine number	char(50)	Machine for which the sample was recorded (PDM field ID: CPAUMW.MNR)
methode_idx	Underlying calculation method	smallint	Underlying calculation method
n	Number of valid meas.val. in cur. sample	integer	Number of valid measured values in current sample
n_ges	Sum of valid meas.val. in cur. sample	integer	Sum of valid meas.val. in cur. sample
nest_nr	Cavity number	char(50)	Cavity for which the sample was recorded (PDM field ID: CPAUMW.NEST)
npq	Only for internal use	float	
opeg	Upper process action limit	float	(PDM field ID: CPAUSP.OPEG)
opg	Upper plausibility limit	float	(PDM field ID: CPAUSP.OPG)
otg	Upper tolerance limit	float	(PDM field ID: CPAUSP.OTG)
p	This field is only relevant for attribut	float	This field is only relevant for attributive characteristics.
position	Position	char(100)	
ppunkt_bemerk	Inspection point comment	char(250)	
pq	Ratio of defect units	float	
pruef_ergebnis	Inspection result	char(50)	The field is only relevant for inspection order characteristics (RECREP = 'PAU'). The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PRFERG_SP')
pruefanf_nr	Inspection requirement number	integer	Inspection requirements are defined in the CAQ_PRUEFANF table. (PDM field ID: CPAUSP.PANNR)
pruefauf_nr	Inspection order number	integer	Inspection orders are defined in the CAQ_PAUKOP table. (PDM field ID: CPAUSP.PAUNR)
pruefer_id	Inspector identifier	char(50)	
pruefer_nr	Inspector	char(50)	Inspector (PDM field ID: CPAUMW.PRUEFER)
pruefer_stichpr	Inspector specific sample number	integer	Inspector specific sample number
prueferg_eingabe	Manual inspection result	char(50)	
r	Range of current sample	float	This field is only relevant for variable characteristics.
r_ges	Range of all samples	float	
r_move	Moving range	float	
rck_01	Confirmed in system 1?	char(1)	
rck_01_dat	Confirmation date in system 1	date	
rck_01_zeit	Confirmation time in system 1	integer	
rck_02	Confirmed in system 2?	char(1)	
rck_02_dat	Confirmation date in system 2	date	
rck_02_zeit	Confirmation time in system 2	integer	
rck_dat	Confirmation date	date	Confirmation date
rck_zeit	Confirmation time	integer	Confirmation time
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPAUSP.RECTYP)
rq	Average of samples range	float	

rueckgemeldet	Confirmed	char(1)	J/N, indicates whether the log record has been uploaded to the PPS system
s	Standard deviation of current sample	float	This field is only relevant for variable characteristics.
s_hoch2_q	Average of squared standard dev.	float	
s_move	Moving standard deviation	float	
s_rel	Relative standard deviation	float	
sigma_1	Sigma 1	float	
sigma_2	Sigma 2	float	
sigma_3	Sigma 3	float	
sq	Average of standard dev. of all samples	float	
stichpr_nr	Sample number	integer	Sample number (PDM field ID: CPAUSP.STPRNR)
summe_c	Sum of defects	integer	
summe_fhleinh	Sum of defect units	integer	
summe_med_ges	Sum of samples median	float	
summe_mm	Only for internal use	float	
summe_npq	Only for internal use	float	
summe_p	This field is only relevant for attribute	float	This field is only relevant for attributive characteristics.
summe_pq	Sum of defect units ratio	float	
summe_r	Sum of samples range	float	
summe_s_ges	Sum of standard dev. of all samples	float	
summe_s_hoch2	Sum of squared standard dev.	float	
summe_x	Sum of sample single values	float	This field is only relevant for variable characteristics.
summe_x_ges	Sum of all single values	float	This field is only relevant for variable characteristics.
summe_x_hoch2	Sum of squared single values	float	
summe_xq	Sum of averages of all samples	float	
sw	Target value	float	(PDM field ID: CPAUSP.SW)
u	Defects ratio	float	This field is only relevant for attributive characteristics.
ungueltig	Invalid?	integer	
upeg	Lower process action limit	float	(PDM field ID: CPAUSP.UPEG)
upg	Lower plausibility limit	float	(PDM field ID: CPAUSP.UPG)
uq	Average defects ratio	float	
utg	Lower tolerance limit	float	(PDM field ID: CPAUSP.UTG)
v	Only for internal use	float	
v_r	Only for internal use	float	
var	Empirical variance	float	
var_innen	Inner empirical variance	float	
werkzeug_nr	Tool number	char(50)	Tool for which the sample was recorded (PDM field ID: CPAUMW.WNR)
x_med	Median of current sample	float	This field is only relevant for variable characteristics.
x_med_q	Average of samples median	float	
xmax	Maximum value of current sample	float	This field is only relevant for variable characteristics.
xmax_ges	Maximum value of all samples	float	
xmin	Minimum value of current sample	float	This field is only relevant for variable characteristics.
xmin_ges	Minimum value of all samples	float	

xq	Average of current sample	float	This field is only relevant for variable characteristics.
xq_move	Moving average	float	
xqq_arith	Arithm. average for all samples	float	
xqq_proz	Process average for all samples	float	
zkrit_1_otg	Only for internal use	float	
zkrit_1_otg_syst	Only for internal use	float	
zkrit_1_utg	Only for internal use	float	
zkrit_1_utg_syst	Only for internal use	float	
zkrit_2_otg	Only for internal use	float	
zkrit_2_otg_syst	Only for internal use	float	
zkrit_2_utg	Only for internal use	float	
zkrit_2_utg_syst	Only for internal use	float	
zkrit_3_otg	Only for internal use	float	
zkrit_3_otg_syst	Only for internal use	float	
zkrit_3_utg	Only for internal use	float	
zkrit_3_utg_syst	Only for internal use	float	
zkrit_otg	Only for internal use	float	
zkrit_otg_syst	Only for internal use	float	
zkrit_utg	Only for internal use	float	
zkrit_utg_syst	Only for internal use	float	

3.53. caq_person

Table name: caq_person		Product: CAQ	
Designation: Catalog of persons			
Column name	Column designation	Type	Description
abteilung_nr	Department which the person/group belong	char(50)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). The departments are filed in the CAQ_ABTEILUNG table. (PDM field ID: CPERS.ABT)
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - current entry 1 - archived entry (PDM field ID: CPERS.ARCHIV)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
email	E-mail address	char(250)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). (PDM field ID: CPERS.EMAIL)
firma_nr	Company which the person/group belongs to	char(50)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). The companies are filed in the CAQ_FIRMA table. (PDM field ID: CPERS.FIRID)
firma_typ	Company type which the person/group belong	char(50)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). The companies are filed in the CAQ_FIRMA table. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'FIRMENTYP') (PDM field ID: CPERS.FIRTYP)
group_1	Group indicator of hierarchy level	char(50)	Identifier for persons and groups of the hierarchy level 1-5 (PDM field ID: CPERS.DSGRP:1)
group_2	Group indicator of hierarchy level	char(50)	Identifier for persons and groups of the hierarchy level 1-5 (PDM field ID: CPERS.DSGRP:2)
group_3	Group indicator of hierarchy level	char(50)	Identifier for persons and groups of the hierarchy level 1-5 (PDM field ID: CPERS.DSGRP:3)
group_4	Group indicator of hierarchy level	char(50)	Identifier for persons and groups of the hierarchy level 1-5 (PDM field ID: CPERS.DSGRP:4)
group_5	Group indicator of hierarchy level	char(50)	Identifier for persons and groups of the hierarchy level 1-5 (PDM field ID: CPERS.DSGRP:5)
group_item	Person or group?	smallint	0 - Person 1 - Group (PDM field ID: CPERS.DSGRPE)
hydra_usrid	User	char(50)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). The departments are filed in the USER_TAB table. (PDM field ID: CPERS.HYBEARB)
kuerzel	Abbreviation	char(250)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). (PDM field ID: CPERS.KUERZEL)
nachname	Last name (person)/designation (group)	char(250)	The person's last name or group designation (PDM field ID: CPERS.NAME)
pager	Pager number	char(250)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). (PDM field ID: CPERS.PAGER)
person_nr	Identifier of person/group	char(50)	Unique number of the person or group (PDM field ID: CPERS.PERNR)
pim_aufgabe	Measure as PIM task?	char(50)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0).

pim_email	Measure as PIM e-mail?	char(50)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0).
tel_mobile	Mobile number	char(250)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). (PDM field ID: CPERS.HANDY)
telefax	Fax number	char(250)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). (PDM field ID: CPERS.FAX)
telefon	Phone number	char(250)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). (PDM field ID: CPERS.TEL)
verantw_flag	Party in charge	smallint	If the value of this field = 1 the corresponding entry in the caq_verantwortl table is also updated at each change. (PDM field ID: CPERS.VERANT:COPY)
vorname	First name	char(250)	This entry is only relevant for persons and not for groups (GROUP_ITEM = 0). (PDM field ID: CPERS.VORNAME)

3.54. caq_ppktm_info

Table name: caq_ppktm_info		Product: CAQ	
Archive table: a_caq_ppktm_info		Reload table: r_caq_ppktm_info	
Designation: Temp. info. autom. insp. point creation			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
anmelde_dat	Last created Insp. point - Op. log on d	date	Last created Insp. point - Op. log on date
anmelde_zeit	Last created Insp. point - Op. log on t	integer	Last created Insp. point - Op. log on time
bearb	Last change - HYRA user	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table.
lppkt_dauer	Last created Insp. point - Duration	integer	
lppkt_menge	Last created Insp. point - Quantity	float	
maschine_nr	Workplace	char(20)	
offset_dauer	Only for internal use	integer	
offset_menge	Only for internal use	integer	
offset_ref_dat	Only for internal use	date	
offset_ref_zeit	Only for internal use	integer	
pruefanf_nr	Inspection requirement number	integer	Inspection requirements are defined in the CAQ_PRUEFANF table.
pruefauf_nr	Inspection order number	integer	Inspection orders are defined in the CAQ_PAUKOP table.
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management

3.55. caq_ppktm_info_afo

Table name: caq_ppktm_info_afo		Product: CAQ	
Archive table: a_caq_ppktm_info_afo		Reload table: r_caq_ppktm_info_afo	
Designation: Temp. info. autom. insp. point creation			
Column name	Column designation	Type	Description
afo	Operation	integer	
anlage	Initial data creation - HYDR user	char(50)	Time when the entry was created
anlage_date	Initial data creation - Date	date	
anlage_time	Initial data creation - Time	integer	
bearb	Last change - HYRA user	char(50)	Last editor
bearb_date	Last change - Date	date	
bearb_time	Last change - Time	integer	
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table.
lppkt_dauer	Last created Insp. point - Duration	integer	
lppkt_menge	Last created Insp. point - Quantity	float	
maschine_nr	Workplace	char(20)	
pruefanf_nr	Inspection requirement number	integer	Inspection requirements are defined in the CAQ_PRUEFANF table.
pruefauf_nr	Inspection order number	integer	Inspection orders are defined in the CAQ_PAUKOP table.
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management

3.56. caq_ppktm_interv

Table name: caq_ppktm_interv		Product: CAQ	
Archive table: a_caq_ppktm_interv		Reload table: r_caq_ppktm_interv	
Designation: Temp. info. autom. insp. point creation			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	
anlage_time	Initial data creation - Time	integer	
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table.
ppunkt_anl_ursach	Inspection point creation cause	char(50)	
ppunkt_dauer	Inspection point duration	integer	
ppunkt_menge	Inspection point quantity	float	
ppunkt_prod_masch	Insp. point producing workplace	char(20)	
ppunkt_ursach_dat	Inspection point cause - Date	date	
ppunkt_ursach_zeit	Inspection point cause - Time	integer	
pruefanf_nr	Inspection requirement number	integer	Inspection requirements are defined in the CAQ_PRUEFANF table.
pruefauf_nr	Inspection order number	integer	Inspection orders are defined in the CAQ_PAUKOP table.
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management
verweis	Internal serial	serial	

3.57. caq_ppktm_iv_afo

Table name: caq_ppktm_iv_afo		Product: CAQ	
Archive table: a_caq_ppktm_iv_afo		Reload table: r_caq_ppktm_iv_afo	
Designation: Temp. info. autom. insp. point creation			
Column name	Column designation	Type	Description
afo	Operation	integer	
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	
anlage_time	Initial data creation - Time	integer	
bereich	Area	char(10)	
ppunkt_anl_ursach	Inspection point creation cause	char(50)	
ppunkt_dauer	Inspection point duration	integer	
ppunkt_menge	Inspection point quantity	float	
ppunkt_prod_masch	Insp. point producing workplace	char(20)	
ppunkt_ursach_dat	Inspection point cause - Date	date	
ppunkt_ursach_zeit	Inspection point cause - Time	integer	
pruefanf_nr	Inspection requirement number	integer	
pruefauf_nr	Inspection order number	integer	
rec_type	Input type	char(50)	

3.58. caq_pplkop

Table name: caq_pplkop		Product: CAQ	
Designation: Inspection plans		Description: The spreadsheet administers the inspection plans. It includes inspection plans from all areas (production, goods receipt, goods issue, initial sample inspection, gage management). Depending on the type of the inspection plan only some of the fields listed in the following are relevant.	
Column name	Column designation	Type	Description
aktion	Activate inspection orders automatically	char(50)	"PAUERST": Inspection orders are only created but not activated. "PAUFREI": Having been created inspection orders are automatically released. These settings are defined in the CAQ_STATUS table (STATUS_TYP = "PAUAKTION"). (PDM field ID: CPPL.PAUAKTION)
aktiv	Inspection plan active?	smallint	0: Inspection plan inactive 1: Inspection plan active (PDM field ID: CPPL.AKTIV)
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
arbgang_bez	Operation designation	char(250)	Operation designation (PDM field ID: CPPL.AGBEZ)
arbgang_nr	Operation number	char(50)	Operation number (PDM field ID: CPPL.AGNR)
artikel_idx	Drawing issue number (article index)	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CPPL.ATKIDX)
artikel_nr	Article number	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CPPL.ATK)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPPL.BER)
dyn_art	Type of dynamic modification	char(50)	KEINE - No dynamic modification LOS - Batch-related dynamic modification MERKMAL - characteristic-related dynamic modification The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'DYNART') (PDM field ID: CPPL.DYNART)
dyn_pscharf_star	Initial inspection severity	char(50)	This field is only relevant if CAQ_PPLKOP:DYN_ART = 'LOS'. The inspection severities of the (inspection severity definition belonging to the CAQ_PPLKOP.DYN_UEBERG_NR transitional definition) are filed in the CAQ_DYNPS_EINT table. (PDM field ID: CPPL.DYPSCHARF:STA)
dyn_ueberg_nr	Transitional definition for dynamic modi	char(50)	This field is only relevant if CAQ_PPLKOP:DYN_ART = 'LOS'. The transitional definitions are filed in the CAQ_DYNUEBERGANG table. (PDM field ID: CPPL.UEBERG)
emu_formular	Initial sample form	char(50)	Initial sample forms are defined in the CAQ_STATUS table (STATUS_TYP = "EMUFORM"). (PDM field ID: CPPL.EMUFORM)
freigabe	Release inspection plan?	smallint	0: Inspection plan not released 1: Inspection plan released (PDM field ID: CPPL.FREI)
freigabe_date	Release date	date	Release date (PDM field ID: CPPL.FREIDAT)
freigabe_durch	Released by	char(50)	Released by (PDM field ID: CPPL.FREIVON)
gis_key	GIS key	char(50)	GIS key

grenzwert_io	Accept limit	float	(PDM field ID: CPPL.GRENZW:IO)
grenzwert_nio	Reject limit	float	(PDM field ID: CPPL.GRENZW:NIO)
gueltig_bis	End of validity period	date	Validity period (PDM field ID: CPPL.GUELTBIS)
gueltig_von	Start of validity period	date	validity period (PDM field ID: CPPL.GUELTVON)
hersteller_nr	Manufacturer number	char(50)	Manufacturers are defined in the CAQ_FIRMA table. (PDM field ID: CPPL.HERSTNR)
kunde_nr	Customer number	char(50)	Customers are defined in the CAQ_FIRMA table. (PDM field ID: CPPL.KDNR)
lieferant_nr	Supplier number	char(50)	Suppliers are defined in the CAQ_FIRMA table. (PDM field ID: CPPL.LIEFNR)
maschine_nr	Workplace	char(50)	(PDM field ID: CPPL.MNR)
merkmal_aktion	Characteristics creation event	char(50)	
nest_zuordnung	Assignment of cavities to samples/measurement	char(50)	"KEINE": No cavity information is processed. "STICHPROBE": The cavity is assigned on the level of samples. "MESSWERT": The cavity is assigned on the level of measured values. These settings are defined in the CAQ_STATUS table (STATUS_TYP = "NESTZUORD"). (PDM field ID: CPPL.NESTZUORD)
pmv_genauk_bezug	MSA related	char(50)	(PDM field ID: CPPL.GENAUK:BEZUG)
pmv_prueftyp	Method	char(50)	(PDM field ID: CPPL.PMVKALIBTYP)
prauf_prplatz	Splitting of partial inspection orders o	char(50)	"PAU1PP": one inspection order for all inspection stations "PAUxPP": one inspection order for each inspection station These settings are defined in the CAQ_STATUS table (STATUS_TYP = "PAUPPLATZ") (PDM field ID: CPPL.PAUPPLATZ)
prplan_arbgang	Relation of the inspection plan to opera	char(50)	"PPL1AG": one inspection plans for all operations "PPLxAG": one inspection plan for each operations These settings are defined in the CAQ_STATUS table (STATUS_TYP = "PPLAGCFG") (PDM field ID: CPPL.PPLAGCFG)
prplan_id	Inspection plan number	char(50)	Inspection plan number (PDM field ID: CPPL.PPLID)
prplan_idx	Inspection plan index	char(50)	Inspection plan index (PDM field ID: CPPL.PPLIDX)
prplan_nr	Internal, numeric inspection plan number	integer	- is used for nearly all JOINS (PDM field ID: CPPL.PPLNR)
pruefung_art	Inspection type	char(50)	"MERKMAL": Items are inspected with respect to characteristics. "STUECK": Items are inspected with respect to pieces. These settings are defined in the CAQ_STATUS table (STATUS_TYP = "PRUEFART"). (PDM field ID: CPPL.PRUEFART)
qm_ag_erzeugen	Create inspection only operation?	char(50)	
rec_type	Input type	char(50)	"WEP" = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPPL.RECTYP)
user_c_01	Alphanumeric user field 1-5	char(50)	Alphanumeric user field 1-5 (PDM field ID: CPPL.FU:1)
user_c_02	Alphanumeric user field 1-5	char(50)	Alphanumeric user field 1-5 (PDM field ID: CPPL.FU:2)
user_c_03	Alphanumeric user field 1-5	char(50)	Alphanumeric user field 1-5 (PDM field ID: CPPL.FU:3)

user_c_04	Alphanumeric user field 1-5	char(50)	Alphanumeric user field 1-5 (PDM field ID: CPPL.FU:4)
user_c_05	Alphanumeric user field 1-5	char(50)	Alphanumeric user field 1-5 (PDM field ID: CPPL.FU:5)
user_d_01	Date user field 1-2	date	Date user field (PDM field ID: CPPL.FU:13)
user_d_02	Date user field 1-2	date	Datum-Benutzerfeld (PDM field ID: CPPL.FU:14)
user_f_01	Decimal user field 1-2	float	Decimal user field (PDM field ID: CPPL.FU:11)
user_f_02	Decimal user field 1-2	float	Decimal user field (PDM field ID: CPPL.FU:12)
user_n_01	Numeric user field 1-5	integer	Numeric user field (PDM field ID: CPPL.FU:6)
user_n_02	Numeric user field 1-5	integer	Numeric user field (PDM field ID: CPPL.FU:7)
user_n_03	Numeric user field 1-5	integer	Numeric user field (PDM field ID: CPPL.FU:8)
user_n_04	Numeric user field 1-5	integer	Numeric user field (PDM field ID: CPPL.FU:9)
user_n_05	Numeric user field 1-5	integer	Numeric user field (PDM field ID: CPPL.FU:10)
werkz_zuordnung	Tool assignment	char(50)	"KEINE": There are no tool assignments. "PPLMER":The tools have been assigned to the inspection plan characteristics. "PPLKOP":The tools have been assigned to the inspection plan. These settings are defined in the CAQ_STATUS table (STATUS_TYP = "WERKZUORD"). (PDM field ID: CPPL.WERKZUORD)
zeichnung_nr	Drawing number	char(250)	Drawing number (PDM field ID: CPPL.ZEICHNNR)

3.59. caq_prplatz

Table name: caq_prplatz		Product: CAQ	
Designation: Inspection stations			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - Current inspection station 1 - Archived inspection station (PDM field ID: CPPLATZ.ARCHIV)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
group_1	Group indicator of hierarchy level 1-5	char(50)	Identifier for inspection stations and groups of the hierarchy level 1-5 (PDM field ID: CPPLATZ.DSGRP:1)
group_2	Group indicator of hierarchy level 1-5	char(50)	Identifier for inspection stations and groups of the hierarchy level 1-5 (PDM field ID: CPPLATZ.DSGRP:2)
group_3	Group indicator of hierarchy level 1-5	char(50)	Identifier for inspection stations and groups of the hierarchy level 1-5 (PDM field ID: CPPLATZ.DSGRP:3)
group_4	Group indicator of hierarchy level 1-5	char(50)	Identifier for inspection stations and groups of the hierarchy level 1-5 (PDM field ID: CPPLATZ.DSGRP:4)
group_5	Group indicator of hierarchy level 1-5	char(50)	Identifier for inspection stations and groups of the hierarchy level 1-5 (PDM field ID: CPPLATZ.DSGRP:5)
group_item	Inspection station or group?	smallint	0 - Inspection station 1 - Group (PDM field ID: CPPLATZ.DSGRPE)
prplatz_bez	Designation inspection station/group	char(250)	Designation of the inspection station or group (PDM field ID: CPPLATZ.PPLATZBEZ)
prplatz_nr	Identifier inspection station/group	char(50)	Identifier inspection station/group (PDM field ID: CPPLATZ.PPLATZ)

3.60. caq_pruefanf

Table name: caq_pruefanf		Product: CAQ	
Archive table: a_caq_pruefanf		Reload table: r_caq_pruefanf	
Designation: Inspection requirements		Description: The spreadsheet administers inspection requirements. It includes data from all areas (production, goods receipt, goods issue, initial sample inspection, gage management). Depending on the type of inspection requirement only some of the fields listed in the following are relevant	
Column name	Column designation	Type	Description
abschluss_date	Completion date	date	Completion date (PDM field ID: CPAN.ABSDAT)
abschluss_time	Completion time	integer	Completion time (PDM field ID: CPAN.ABSZEI)
abschluss_von	Inspection completion of (personnel no.)	char(50)	Inspection completion of (personnel no.) (PDM field ID: CPAN.ABSVON)
abschluss_vonk	Inspection completion of (badge no.)	char(50)	Inspection completion of (badge no.) (PDM field ID: CPAN.ABSKNR)
abschluss_vonp	Inspection completion by person	integer	
anforderung_date	Request date	date	Request date (PDM field ID: CPAN.PANDAT)
anforderung_time	Request time	integer	Request time (PDM field ID: CPAN.PANZEI)
anforderung_von	Inspection requirement of (personnel no.)	char(50)	Inspection requirement of (personnel no.) (PDM field ID: CPAN.PANVON)
anforderung_vonk	Inspection requirement of (badge no.)	char(50)	Inspection requirement of (badge no.) (PDM field ID: CPAN.PANKNR)
anforderung_vonp	Inspection requirement by person	integer	
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
arbgang_bez	Operation designation	char(250)	Operation designation (PDM field ID: CPAN.AGBEZ)
arbgang_nr	Operation number	char(50)	Operation number (PDM field ID: CPAN.AGNR)
artikel_idx	Drawing issue no. (article index)	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CPAN.ATKIDX)
artikel_nr	Article number	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CPAN.ATK)
auftrag_nr	Order number	char(250)	Order number (PDM field ID: CPAN.ANR)
ausschuss	Ausschussmenge	float	Ausschussmenge (PDM field ID: CPAN.EGR:AUS)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last change - Date
bearb_time	Last change - Time	integer	Last change - Time
bemerkung	Comment	char(250)	
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CPAN.BER)
bestell_nr	Purchase order number	char(250)	Purchase order number (PDM field ID: CPAN.BESTNR)

charge_nr	Batch number	char(250)	Batch number (PDM field ID: CPAN.CNR)
dyn_art	Type of dynamic modification	char(50)	This field derives from inspection planning and cannot be changed anymore after having created the inspection requirement. KEINE - No dynamic modification LOS - Batch-related dynamic modification MERKMAL - characteristic-related dynamic modification The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'DYNART')
dyn_pscharf_nr	Inspection severity	char(50)	This field is only relevant when it comes to batch-related inspections (DYN_ART = 'LOS') Normally it is determined by dynamic modification. The DYPSCHARF:IMPÖRT parameter is only intended for legacy data transfer. The inspection severities of (the inspection severity definition corresponding to the transitional definition CAQ_PRUEFANF.DYN_UEBERG_NR) are filed in the CAQ_DYNPS_EINT table. (PDM field ID: CPAN.DYPSCHARF:IMPORT)
dyn_pscharf_star	Initial inspection severity	char(50)	This field derives from inspection planning and cannot be changed anymore after having created the inspection requirement. The inspection severities of (the inspection severity definition corresponding to the transitional definition CAQ_PRUEFANF.DYN_UEBERG_NR) are filed in the CAQ_DYNPS_EINT table.
dyn_pscharf_usr	Inspection severity corrected by the use	char(50)	This field is only relevant when it comes to batch-related inspections (DYN_ART = 'LOS') The inspection severities of (the inspection severity definition corresponding to the transitional definition CAQ_PRUEFANF.DYN_UEBERG_NR) are filed in the CAQ_DYNPS_EINT table. (PDM field ID: CPAN.DYPSCHARF:USR)
dyn_ueberg_nr	Transitional definition	char(50)	This field derives from inspection planning and cannot be changed anymore after having created the inspection requirement. The transitional definitions are filed in the CAQ_DYNUEBERGANG table.
emu_formular	EMU form (initial sample inspection)	char(50)	This field derives from inspection planning and cannot be changed anymore after having created the inspection requirement. Initial sample forms are defined in the CAQ_STATUS table (STATUS_TYP = "EMUFORM").
ergebnis	Inspection result	char(50)	""; a result is not yet available "OK": Inspection ok. "NOK": Inspection not ok. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PANERG') (PDM field ID: CPAN.ERGEB)
erst_abschl_date	Date of first completion	date	This field serves as sort criterion in the dynamic modification history.
erst_abschl_time	Time of first completion	integer	This field serves as sort criterion in the dynamic modification history.
gis_key	GIS key	char(50)	GIS key
grenzwert_io	Accept limit	float	
grenzwert_nio	Reject limit	float	
herstell_date	Date of manufacture	date	Date of manufacture (PDM field ID: CPAN.HERSTDAT)
hersteller_nr	Manufacturer number	char(50)	Manufacturers are defined in the CAQ_FIRMA table. (PDM field ID: CPAN.HERSTNR)
kalib_befund	Calibration findings	char(50)	
kalib_status	Calibration status	char(50)	
kunde_nr	Customer number	char(50)	Customers are defined in the CAQ_FIRMA table. (PDM field ID: CPAN.KDNR)
liefer_date	Delivery date (actual)	date	Delivery date (actual) (PDM field ID: CPAN.LIEFDAT)
liefer_date_soll	Delivery date (target)	date	Delivery date (target) (PDM field ID: CPAN.LIEFDAT:SOLL)
lieferant_nr	Supplier number	char(50)	Suppliers are defined in the CAQ_FIRMA table. (PDM field ID: CPAN.LIEFNR)
maschine_nr	Machine number	char(50)	Machine number (PDM field ID: CPAN.MNR)
menge	Delivery quantity (actual)	float	Delivery quantity (actual) (PDM field ID: CPAN.CMENGE)
menge_einheit	quantity unit	char(10)	
menge_soll	Delivery quantity (target)	float	Delivery quantity (target) (PDM field ID: CPAN.CMENGE:SOLL)
merkmal_aktion	Characteristics creation event	char(50)	

nacharbeit	Rework quantity	float	Rework quantity (PDM field ID: CPAN.EGR:NACH)
nest_zuordnung	Assignment of cavities to samples/measur	char(50)	"KEINE": No cavity information is processed. "STICHPROBE": The cavity is assigned on the level of samples. "MESSWERT": The cavity is assigned on the level of measured values. These settings are defined in the CAQ_STATUS table (STATUS_TYP = "NESTZUORD").
parts_per_million	Parts per Million	float	Parts per Million (PDM field ID: CPAU.EGR:PPM)
plan_werk	Plant of the inspection lot	char(4)	
pmv_genauk_bezug	MSA related	char(50)	
pmv_prueftyp	Gage - Inspection type	char(50)	A - attributive V - variable The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PRUEFTYP')
pps_referenz_nr	PPS reference number	char(250)	PPS reference number (PDM field ID: CPAN.PPS:REF)
pps_rueckmeld	Uploaded to PPS system?	smallint	0 - Result not yet confirmed 1 - Result confirmed (PDM field ID: CPAN.PPS:RMELD)
pps_zusatz_chr	PPS additional information	char(250)	PPS additional information (PDM field ID: CPAN.PPS:ZCHR1)
prod_menge	Quantity produced	float	Quantity produced (PDM field ID: CPAN.EGR:MENGE)
prplan_id	Inspection plan number (default value)	char(50)	Inspection plans are defined in the CAQ_PPLKOP table. (PDM field ID: CPAN.PPLID)
prplan_idx	Inspection plan index (default value)	char(50)	Inspection plans are defined in the CAQ_PPLKOP table. (PDM field ID: CPAN.PPLIDX)
prplan_nr	Number of the inspection plan in use	integer	Inspection plans are defined in the CAQ_PPLKOP table. (PDM field ID: CPAN.PPLNR)
prplatz_nr	Registering inspection station	char(50)	Inspection stations are defined in the CAQ_PRPLATZ table. (PDM field ID: CPAN.PPLATZ)
pruefanf_nr	Inspection requirement number	integer	Inspection requirement number (PDM field ID: CPAN.PANNR)
pruefung_art	Inspection type	char(50)	"MERKMAL": Parts are inspection with respect to characteristics. "STUECK": Parts are inspection with respect to pieces. These settings are defined in the CAQ_STATUS table (STATUS_TYP = "PRUEFART").
qm_ag_erzeugen	Create inspection only operation?	char(50)	
rck_01	Confirmed in system 1?	char(1)	
rck_01_dat	Confirmation date in system 1	date	
rck_01_zeit	Confirmation time in system 1	integer	
rck_02	Confirmed in system 2?	char(1)	
rck_02_dat	Confirmation date in system 2	date	
rck_02_zeit	Confirmation time in system 2	integer	
rck_dat	Confirmation date	date	Confirmation date
rck_zeit	Confirmation time	integer	Confirmation time
rec_type	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management (PDM field ID: CPAN.RECTYP)
res_nr	Resource identifier	char(40)	
res_typ	Resource type	char(4)	
rueckgemeldet	Confirmed	char(1)	J/N, indicates whether the log record has been uploaded to the PPS system

sammelanf_nr	Collective request number	integer	Collective requests are defined in the CAQ_SAMMELANF table. (PDM field ID: CPAN.SANNR)
sap_art	SAP inspection type	char(8)	
sap_auftrag_nr	SAP order number	char(12)	
sap_herkunft	SAP origin of the inspection lot	char(2)	
skiplot	Skiplot	smallint	0 - Inspection requirement is not included in skiplot 1 - Inspection requirement is included in skiplot
status	Status of inspection requirement	char(50)	"KPP" - No inspection plan found "KMM" - Inspection requirement does not include testable characteristics "SKL" - Skip lot (till CAQ V7.1.19 only) "ERS" - Created (no valid measured values recorded) "TER" - Partial result (valid measured values recorded, not all partial inspection orders have been finished yet) "ERG" - all partial inspection orders finished "STO" - cancelled "ABG" - finished The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PANSTATUS')
status_info	Posting required informations	char(250)	
user_c_01	Alphanumeric user field 1	char(50)	(PDM field ID: CPAN.FU:1)
user_c_02	Alphanumeric user field 2	char(50)	(PDM field ID: CPAN.FU:2)
user_c_03	Alphanumeric user field 3	char(50)	(PDM field ID: CPAN.FU:3)
user_c_04	Alphanumeric user field 4	char(50)	(PDM field ID: CPAN.FU:4)
user_c_05	Alphanumeric user field 5	char(50)	Alphanumeric user field 5 (PDM field ID: CPAN.FU:5)
user_d_01	Date user field 1	date	Date user field 1 (PDM field ID: CPAN.FU:13)
user_d_02	Date user field 2	date	Date user field 2 (PDM field ID: CPAN.FU:14)
user_f_01	Decimal user field 1	float	(PDM field ID: CPAN.FU:11)
user_f_02	Decimal user field 2	float	Decimal user field 2 (PDM field ID: CPAN.FU:12)
user_n_01	Numeric user field 1	integer	(PDM field ID: CPAN.FU:6)
user_n_02	Numeric user field 2	integer	(PDM field ID: CPAN.FU:7)
user_n_03	Numeric user field 3	integer	(PDM field ID: CPAN.FU:8)
user_n_04	Numeric user field 4	integer	(PDM field ID: CPAN.FU:9)
user_n_05	Numeric user field 5	integer	Numeric user field 5 (PDM field ID: CPAN.FU:10)
verantw_nr	Party in charge number	char(50)	Parties in charge are defined in the CAQ_VERANTWORTL table. (PDM field ID: CPAN.VERANTW:NR)
verantw_typ	Type of party in charge	char(50)	Parties in charge are defined in the CAQ_VERANTWORTL table. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'VERANTWTYP') (PDM field ID: CPAN.VERANTW:TYP)
verwend_auswmen	Usage decision selected set	char(10)	
verwend_code	Usage decision code	char(10)	
verwend_codgr	Usage decision code group	char(10)	
verwend_katart	Usage decision catalog type	char(10)	
verwend_relevant	Usage decision relevant	integer	

verwend_werk	Usage decision plant	char(4)	
verwendung	Usage decision	char(50)	""': a usage decision is not yet available "FREIGABE": Release "BEDFREIGABE": Conditional release "RUECKWEISEN": Reject "SORTIEREN": Sort "NACHARBEIT": Rework The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'PANVERWENT') (PDM field ID: CPAN.VERWEND)
verwflt_auswmen	Usage decision selected set - Filter	char(10)	
verwflt_katart	Usage decision catalog type - Filter	char(10)	
verwflt_werk	Usage decision plant - Filter	char(4)	
wart_id	Maintenance identifier	integer	
werkz_zuordnung	Tool assignment	char(50)	"KEINE": There are no tool assignments. "PPLMER": The tools have been assigned to the inspection plan characteristics. "PPLKOP": The tools have been assigned to the inspection plan. These settings are defined in the CAQ_STATUS table (STATUS_TYP = "WERKZUORD").

3.61. caq_pruefmatrix

Table name: caq_pruefmatrix		Product: CAQ	
Archive table: a_caq_pruefmatrix		Reload table: r_caq_pruefmatrix	
Designation: Char. relevanz for number pool entries			
Column name	Column designation	Type	Description
afo	Characteristic sequence	integer	
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	
anlage_time	Initial data creation - Time	integer	
bearb	Last editor	char(50)	
bearb_date	Last change - Date	date	
bearb_time	Last change - Time	integer	
bereich	Area	char(10)	
eintrag_nr	Number	char(100)	
eintrag_typ	Type of number	char(50)	
erstpruef	Only for internal use	smallint	
pruef_umfang	Sampling size	char(20)	
pruefanf_nr	Inspection requirement number	integer	
pruefauf_nr	Inspection order number	integer	
rec_type	Input type	char(50)	
sammelanf_nr	Only for internal use	integer	
stckintv	Only for internal use	smallint	
uhrzeit	Only for internal use	smallint	
zeitintv	Only for internal use	smallint	

3.62. caq_qails_vormerk

Table name: caq_qails_vormerk		Product: CAQ	
Designation: SAP data acquisition configuration			
Column name	Column designation	Type	Description
art	Inspection type	char(8)	
aufnr_bis	Order number to	char(12)	
aufnr_von	Order number from	char(12)	
bearb	Created by	char(10)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
charg	Batch	char(10)	
datum_bis	Date to	char(15)	
datum_von	Date from	char(15)	
herkunft	Origin of the inspection lot	char(2)	
kunnr	Customer number	char(10)	
lifnr	Supplier number	char(10)	
losnr_bis	Inspection lot numbers to	char(12)	
losnr_von	Inspection lot numbers from	char(12)	
matnr	Material number	char(18)	
maxlosanz	Maximum number of inspection lots	char(4)	
mblnr	Number of the material document	char(10)	
plnfl	order sequence id	char(6)	
prplatz	Inspection station	char(8)	
prplatzwrk	Inspection station plant	char(4)	
pruefstat	Inspection status	char(1)	
satzart	Record type	char(3)	
statisch	statical?	char(1)	
status	Status	char(3)	
subsys	Subsystem	char(6)	
ta_id	Transaction identifier	char(30)	
user_c_09	Alphanumeric user field 9	char(20)	
user_c_10	Alphanumeric user field 10	char(40)	
user_d_01	Date user field 1	date	
user_d_02	Date user field 2	date	
user_f_07	Decimal user field 7	decimal(18,6)	
user_f_08	Decimal user field 8	decimal(18,6)	
user_n_03	Numeric user field 3	integer	
user_n_04	Numeric user field 4	integer	
user_n_05	Numeric user field 5	integer	
user_n_06	Numeric user field 6	integer	
verweis	Internal serial	serial	
vorgwerk	Operation plant	char(4)	

vornr_bis	Operation to	char(4)	
vornr_von	Operation from	char(4)	

3.63. caq_qm_mnr

Table name: caq_qm_mnr		Product: CAQ	
Designation: Variable workplaces			
Column name	Column designation	Type	Description
ade_masch_nr	Reference workplace	char(20)	
bearb	Last change - HYRA user	char(10)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
qm_masch_nr	Target workplace	char(20)	
qm_masch_nr_id	Placeholder	char(20)	

3.64. caq_rek_zuord

Table name: caq_rek_zuord		Product: CAQ	
Designation: Complaint assignments			
Column name	Column designation	Type	Description
bereich	Area	char(10)	Valid area of the CAQ_BEREICH table
bereich_zuord	Assigned area	char(10)	
rectype	Input type	char(50)	'WEP' = Goods receipt inspection 'FEP' = in-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'REK' = Complaints management 'PMV' = Gage management 'LFB' = Supplier evaluation 'CPL' = Production control plan (Control Plan)
rectype_zuord	Assigned input type	char(50)	
reklam_nr	Internal, numeric complaint number	integer	- is used for nearly all JOINS
reklam_nr_zuord	Internal, assignnumeric complaint number	integer	

3.65. caq_rekauft

Table name: caq_rekauft		Product: CAQ	
Designation: Complaints			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
ansprechp_nr	Contact person	char(50)	(PDM field ID: CREKAUF.ANSPRP:NR)
ansprechp_typ	Contact type	char(50)	(PDM field ID: CREKAUF.ANSPRP:TYP)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
befund	Findings of the complaint	char(50)	(PDM field ID: CREKAUF.BEF)
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CREKAUF.BER)
eingang_date	Received Date	date	(PDM field ID: CREKAUF.REKDAT)
eingang_time	Received Time	integer	(PDM field ID: CREKAUF.REKZEI)
eingang_von	Received from	char(50)	(PDM field ID: CREKAUF.REKVON)
gis_key	GIS key	char(50)	GIS key
isttermin_date	Actual - Date	date	(PDM field ID: CREKAUF.ISTDAT)
isttermin_time	Actual - Time	integer	(PDM field ID: CREKAUF.ISTZEI)
kostenstelle	Cost center	char(50)	(PDM field ID: CREKAUF.KST)
lagerort	Storage location	char(250)	(PDM field ID: CREKAUF.LAGER)
lieferdatum	Delivery date	date	(PDM field ID: CREKAUF.LIEFDAT)
lieferschein	Delivery note	char(250)	(PDM field ID: CREKAUF.LIEFNR)
pps_referenz_nr	PPS reference number	char(250)	PPS reference number (PDM field ID: CREKAUF.PPS:REF)
pps_rueckmeld	Uploaded to PPS system?	smallint	0 - Result not yet confirmed 1 - Result confirmed (PDM field ID: CREKAUF.PPS:RMELD)
process_nr	Process number	integer	When it comes to the first assignment of the CREK.WFNR parameter a corresponding workflow process is generated whose key field (WFM_WF_PROCESS.PROCESS_NR) is entered here.
rec_type	Input type	char(50)	'REK' = Complaints management (PDM field ID: CREKAUF.RECTYP)
rek_art	Complaint type	char(50)	(PDM field ID: CREKAUF.REKART)

rekauf_nr	Complaint number	char(50)	(PDM field ID: CREKAUF.REKAUFT)
reklam_nr	Internal, numeric complaint number	integer	- is used for nearly all JOINS (PDM field ID: CREKAUF.REKNR)
reklam_nr_ext	External complaint number	char(250)	(PDM field ID: CREKAUF.EXTNR)
reklamier_nr	Complaining party	char(50)	(PDM field ID: CREKAUF.REKLAM:NR)
reklamier_typ	Complaining party type	char(50)	(PDM field ID: CREKAUF.REKLAM:TYP)
status	Status of the complaint	char(50)	(PDM field ID: CREKAUF.STA)
user_c_01	Alphanumeric user field 1	char(50)	
user_c_02	Alphanumeric user field 2	char(50)	
user_c_03	Alphanumeric user field 3	char(50)	
user_c_04	Alphanumeric user field 4	char(50)	
user_c_05	Alphanumeric user field 5	char(50)	
user_d_01	Date user field 1	date	
user_d_02	Date user field 2	date	
user_f_01	Decimal user field 1	float	
user_f_02	Decimal user field 2	float	
user_n_01	Numeric user field 1	integer	
user_n_02	Numeric user field 2	integer	
user_n_03	Numeric user field 3	integer	
user_n_04	Numeric user field 4	integer	
user_n_05	Numeric user field 5	integer	
verantw_nr	Party in charge	char(50)	(PDM field ID: CREKAUF.VERANT:NR)
verantw_typ	Party in charge type	char(50)	(PDM field ID: CREKAUF.VERANT:TYP)
zieltermin_date	Target - Date	date	(PDM field ID: CREKAUF.ZIELDAT)
zieltermin_time	Target - Time	integer	(PDM field ID: CREKAUF.ZIELZEI)
zus_char_1	Additional field 1 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKAUF.ZUSCHR:1)
zus_char_2	Additional field 2 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKAUF.ZUSCHR:2)
zus_char_3	Additional field 3 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKAUF.ZUSCHR:3)
zus_char_4	Additional field 4 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKAUF.ZUSCHR:4)
zus_char_5	Additional field 5 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKAUF.ZUSCHR:4)

3.66. caq_rekdetail

Table name: caq_rekdetail		Product: CAQ	
Designation: Complaint details			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Date when the entry was created	date	Date when the entry was created
anlage_time	Time when the entry was created.	integer	Time when the entry was created.
artikel_idx	Drawing issue no. (article index)	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CREKDET.ATKIDX)
artikel_nr	Number of the article or group	char(50)	Number of the article or group (PDM field ID: CREKDET.ATK)
bearb	Last editor	char(50)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
befund	Findinds of the complaint detail	char(50)	 (PDM field ID: CREKDET.BEF)
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CREKDET.BER)
bestell_nr	purchase order number	char(250)	 (PDM field ID: CREKDET.BESTNR)
charge_nr	Batch	char(250)	 (PDM field ID: CREKDET.CNR)
fehleranteil	Share of defect	float	 (PDM field ID: CREKDET.ERRANTEIL)
gis_key	GIS key	char(50)	GIS key
lieferant_nr	Supplier number	char(250)	Suppliers are defined in the CAQ_FIRMA table. (PDM field ID: CREKDET.LIEFNR)
menge_fehler	Defective quantity	float	 (PDM field ID: CREKDET.CMENGE:ERR)
menge_gepr	Checked quantity	float	 (PDM field ID: CREKDET.CMENGE:PRUEF)
menge_liefer	Delivery quatity	float	 (PDM field ID: CREKDET.CMENGE:LIEF)
menge_reklam	Complaint quantity	float	 (PDM field ID: CREKDET.CMENGE:REKL)
parts_per_million	Parts per million	float	 (PDM field ID: CREKDET.CMENGE:PPM)
process_nr	Workflow process	integer	When it comes to the first assignment of the CREKDET.WFNR parameter a corresponding workflow process is generated whose key field (WFM_WF_PROCESS.PROCESS_NR) is entered here.
prplan_ber	Only for internal use	char(10)	 (PDM field ID: CREKDET.PPL:BER)
prplan_nr	Only for internal use	integer	 (PDM field ID: CREKDET.PPL:PPLNR)
prplan_rect	Only for internal use	char(50)	 (PDM field ID: CREKDET.PPL:RECTYP)
pruefanf_ber	Goods i. insp.req. area	char(10)	 (PDM field ID: CREKDET.PRPAN:BER)

pruefanf_nr	Goods i. insp.req. number	integer	(PDM field ID: CREKDET.PRPAN:PANNR)
pruefanf_rect	Goods i. insp.req. input type	char(50)	(PDM field ID: CREKDET.PRPAN:RECTYP)
rec_type	Input type	char(50)	Input type 'REK' = complaints management (PDM field ID: CREKDET.RECTYP)
rekdetail_nr	Complaint detail number	integer	(PDM field ID: CREKDET.REKDETNR)
reklam_nr	Internal, numeric complaint number	integer	(PDM field ID: CREKDET.REKNR)
reklamanteil	Complaint share	float	(PDM field ID: CREKDET.REKANTEIL)
serien_nr	Serial number	char(250)	(PDM field ID: CREKDET.SERIENR)
status	Status of the complaint detail	char(50)	(PDM field ID: CREKDET.STA)
team	Team identifier	char(50)	(PDM field ID: CREKDET.TEAM)
user_c_01	Alphanumeric user field 1	char(50)	Alphanumeric user field 1 (PDM field ID: CREKDET.FU:1)
user_c_02	Alphanumeric user field 2	char(50)	Alphanumeric user field 2 (PDM field ID: CREKDET.FU:2)
user_c_03	Alphanumeric user field 3	char(50)	Alphanumeric user field 3 (PDM field ID: CREKDET.FU:3)
user_c_04	Alphanumeric user field 4	char(50)	Alphanumeric user field 4 (PDM field ID: CREKDET.FU:4)
user_c_05	Alphanumeric user field 5	char(50)	Alphanumeric user field 5 (PDM field ID: CREKDET.FU:5)
user_d_01	Date user field 1	date	Date user field 1 (PDM field ID: CREKDET.FU:13)
user_d_02	Date user field 2	date	Date user field 2 (PDM field ID: CREKDET.FU:14)
user_f_01	Decimal user field 1	float	Decimal user field 1 (PDM field ID: CREKDET.FU:11)
user_f_02	Decimal user field 2	float	Decimal user field 2 (PDM field ID: CREKDET.FU:12)
user_n_01	Numeric user field 1	integer	Numeric user field 1 (PDM field ID: CREKDET.FU:6)
user_n_02	Numeric user field 2	integer	Numeric user field 2 (PDM field ID: CREKDET.FU:7)
user_n_03	Numeric user field 3	integer	Numeric user field 3 (PDM field ID: CREKDET.FU:8)
user_n_04	Numeric user field 4	integer	Numeric user field 4 (PDM field ID: CREKDET.FU:9)
user_n_05	Numeric user field 5	integer	Numeric user field 5 (PDM field ID: CREKDET.FU:10)
verantw_nr	Party in charge	char(50)	(PDM field ID: CREKDET.VERANT:NR)
verantw_typ	Party in charge type	char(50)	(PDM field ID: CREKDET.VERANT:TYP)
we_pruefanf_ber	Goods r. insp. req. area	char(10)	(PDM field ID: CREKDET.WEPAN:BER)
we_pruefanf_nr	Goods r. insp. req. number	integer	(PDM field ID: CREKDET.WEPAN:PANNR)

we_pruefanf_rect	Goods r. insp. req. input type	char(50)	(PDM field ID: CREKDET.WEPAN:RECTYP)
wert_liefer	Delivery value	float	(PDM field ID: CREKDET.WERT:LIEF)
wert_reklam	Complaint value	float	(PDM field ID: CREKDET.WERT:REKL)
zus_char_1	Additional field 1 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKDET.ZUSCHR:1)
zus_char_2	Additional field 2 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKDET.ZUSCHR:2)
zus_char_3	Additional field 3 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKDET.ZUSCHR:3)
zus_char_4	Additional field 4 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKDET.ZUSCHR:4)
zus_char_5	Additional field 5 (Type CHAR)	char(250)	Additional field (Type CHAR) (PDM field ID: CREKDET.ZUSCHR:5)

3.67. caq_spezliste

Table name: caq_spezliste		Product: CAQ	
Designation: Specification list		Description: The table administers all entries in the specification list. They reference a catalog characteristic	
Column name	Column designation	Type	Description
aktiv	Entry active?	smallint	0 - Entry is inactive 1 - Entry is active (PDM field ID: CSPEZL.AKTIV)
anlage	Created by	char(50)	
anlage_date	Initial creation - Date	date	Date when the entry was created
anlage_time	Initial creation - Time	integer	Time when the entry was created.
arbgang_bez	Operation designation	char(250)	Operation designation (PDM field ID: CSPEZL.AGBEZ)
arbgang_nr	Operation number	char(50)	Operation number (PDM field ID: CSPEZL.AGNR)
artikel_idx	Drawing issue no.	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CSPEZL.ATKIDX)
artikel_nr	article number	char(50)	Articles are defined in the CAQ_ARTIKEL table. (PDM field ID: CSPEZL.ATK)
auslassen	Skip characteristic on insp. ord. gen?	smallint	0: Do not skip characteristic when inspection order is generated 1: Skip characteristic when inspection order is generated (PDM field ID: CSPEZL.IGN)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table. (PDM field ID: CSPEZL.BER)
cpk_aktiv	Is cpk active?	integer	
einheit	Unit	char(50)	Units are defined in the CAQ_EINHEIT table. (PDM field ID: CSPEZL.CEINH)
eintrag_idx	(Revision) index of the entry	integer	(Revision) index of the entry (PDM field ID: CSPEZL.EINTIDX)
entnahme_menge	Issue qty in per cent	integer	Issue quantity (PDM field ID: CSPEZL.ENTMENGE)
format	Input/output format	char(250)	Example: #####0.000 (PDM field ID: CSPEZL.FMT)
hinweis_txt	Note	char(250)	Legend (PDM field ID: CSPEZL.MSGTXT)
histogramm	Display histogram?	smallint	Show histogram? (PDM field ID: CSPEZL.HISTOGR)
intervall_alw	Maturity with output batch change	integer	
intervall_einh	Inspection interval - unit	char(50)	This field is only relevant if INTERVALL_TYP = "ZEIT". The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'INTERVAL') (PDM field ID: CSPEZL.INTEINH)
intervall_msw	Maturity with machine status change	integer	
intervall_msw_st	Source for Maturity with machine status	char(250)	
intervall_sch_w	Maturity with shifts change	integer	

intervall_typ	Inspection interval - type	char(50)	In relation to time/quantity The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'ERFINT') (PDM field ID: CSPEZL.INTTYP)
intervall_wert	Inspection interval - value	integer	This field is only relevant if INTERVALL_TYP = "ZEIT","STUECK". (PDM field ID: CSPEZL.INTERVAL)
karte1	Control chart 1	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'REGELK' AND ZUSATZ LIKE '%<PRUEFUNG_TYP>%') (PDM field ID: CSPEZL.KARTE:1)
karte1_ber_art	Method to determine the XQuer value	char(50)	- Applies for control chart 1 - Is required to recalculate action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'BERXQART') (PDM field ID: CSPEZL.XQVART:1)
karte1_ber_xq	Default value XQuer	float	- Applies for control chart 1 - Is required to recalculate action limits This field is only relevant if KARTE1_BER_ART = 'VORGABE'. (PDM field ID: CSPEZL.VORGXQ:1)
karte1_cpk	cpk default value to calculate limit value	float	- Applies for control chart 1 - Is required to recalculate action limits This field is only relevant if KARTE1_VORGABE = 'CPK'. (PDM field ID: CSPEZL.CPK:1)
karte1_dyn_berech	Dynamic limit value computation	smallint	- Applies for control chart 1 (PDM field ID: CSPEZL.GWBERDYN:1)
karte1_egw_eg	Action probability	char(50)	- Applies to control chart 1 - Is required to recalculate action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EGWEINS' or 'EGWZWEI' or 'EGWZWEI_RS') (PDM field ID: CSPEZL.EWEG:1)
karte1_egw_wg	Action probability	char(50)	- Applies to control chart 1 - Is required to recalculate action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EGWEINS' or 'EGWZWEI' or 'EGWZWEI_RS') (PDM field ID: CSPEZL.EWWG:1)
karte1_eins_zwei	Calculation	char(50)	- Applies for control chart 1 - Is required to recalculate action limits EINS - One-sided calculation (lower or upper limit values only) ZWEI - Two-sided calculation (lower and upper limit values) (PDM field ID: CSPEZL.STATVERT:1)
karte1_mw	Average	float	- Applies for control chart 1 (PDM field ID: CSPEZL.MWAVG:1)
karte1_mw_berech	Average calculation?	smallint	- Applies for control chart 1 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.MWBERECH:1)
karte1_oeg	Upper action limit	float	- Applies for control chart 1 (PDM field ID: CSPEZL.OEG:1)
karte1_oeg_aktiv	autom. Fehlerart bei ob. EG-Verletzung?	smallint	- Applies for control chart 1 (PDM field ID: CSPEZL.OEGAKTIV:1)
karte1_oeg_berech	Calculate upper action limit at generati	smallint	- Applies for control chart 1 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.OEGBERECH:1)
karte1_owg	Upper warning limit	float	- Applies for control chart 1 (PDM field ID: CSPEZL.OWG:1)
karte1_owg_aktiv	autom. Fehlerart bei ob. WG-Verletzung?	smallint	- Applies for control chart 1 (PDM field ID: CSPEZL.OWGAKTIV:1)
karte1_owg_berech	Calculate upper warning limit	smallint	- Applies for control chart 1 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.OWGBERECH:1)

karte1_quer	Vorgabewert Quer für Grenzwertberech.	float	- Applies for control chart 1 - Is required to recalculate action limits This field is only relevant if KARTE1_VORGABE = 'QUER'. (PDM field ID: CSPEZL.QUER:1)
karte1_rel_eg	Action limit default	float	- Applies for XQ charts only - Applies for control chart 1 This field is only relevant if KARTE1_VORGABE = 'ABW_REL' or 'ABW_PROZ'. (PDM field ID: CSPEZL.RELEG:1)
karte1_rel_wg	Warning limit default	float	- Applies for XQ charts only - Applies for control chart 1 This field is only relevant if KARTE1_VORGABE = 'ABW_REL' or 'ABW_PROZ'. (PDM field ID: CSPEZL.RELWG:1)
karte1_run_aktiv	Generate run error	integer	
karte1_sigma	Default for calculating limit values	float	- Applies for control chart 1 - Is required to recalculate action limits This field is only relevant if KARTE1_VORGABE = 'SIGMA'. (PDM field ID: CSPEZL.SIGMA:1)
karte1_trend_aktiv	Generate trend error	smallint	
karte1_ueg	Lower action limit	float	- Applies for control chart 1 (PDM field ID: CSPEZL.UEG:1)
karte1_ueg_aktiv	autom. Fehlerart bei unt. EG-Verletzung?	smallint	- Applies for control chart 1 (PDM field ID: CSPEZL.UEGAKTIV:1)
karte1_ueg_berech	untere EG bei PAU-Erzeugung berechnen?	smallint	- Applies for control chart 1 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.UEGBERECH:1)
karte1_uwg	Lower warning limit	float	- gilt für Regelkarte 1 (PDM field ID: CSPEZL.UWG)
karte1_uwg_aktiv	autom. Fehlerart bei unt. WG-Verletzung?	smallint	- Applies for control chart 1 (PDM field ID: CSPEZL.UWGAKTIV:1)
karte1_uwg_berech	untere WG bei PAU-Erzeugung berechnen?	smallint	- Applies for control chart 1 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.UWGBERECH:1)
karte1_vorgabe	Vorgabe für die Berechnung der EG/WG	char(50)	- Applies for control chart 1 - Is required to recalculate action limits CPK - cpk default for calculation SIGMA - Sigma default for calculation QUER - default of sQuer/an or RQuer/dn for calculation (PDM field ID: CSPEZL.VORG:1)
karte2	Regelkarte 2	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'REGELK' AND ZUSATZ LIKE '%(<PRUEFUNG_TYP>)%') (PDM field ID: CSPEZL.KARTE:2)
karte2_ber_art	Methode zur Ermittlung des XQuer-Werts	char(50)	- Applies for control chart 2 - Is required to recalculate action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'BERXQART') (PDM field ID: CSPEZL.XQVART:2)
karte2_ber_xq	Vorgabewert XQuer	float	- Applies for control chart 2 - Is required to recalculate action limits This field is only relevant if KARTE2_BER_ART = 'VORGABE'. (PDM field ID: CSPEZL.VORGXQ:2)
karte2_cpk	cpk-Vorgabewert für Grenzwertberechnung	float	- Applies for control chart 2 - Is required to recalculate action limits This field is only relevant if KARTE2_VORGABE = 'CPK'. (PDM field ID: CSPEZL.CPK:2)
karte2_dyn_berech	Grenzwerte dynamisch berechnen?	smallint	- Applies for control chart 2 (PDM field ID: CSPEZL.GWBERDYN:2)

karte2_egw_eg	Eingriffswahrscheinlichkeit Eingriffsgr.	char(50)	- Applies for control chart 2 - Is required to recalculate action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EGWEINS' or 'EGWZWEI' or 'EGWZWEI_RS') (PDM field ID: CSPEZL.EWEG:2)
karte2_egw_wg	Eingriffswahrscheinlichkeit Warngrenzen	char(50)	- Applies for control chart 2 - Is required to recalculate action limits The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'EGWEINS' or 'EGWZWEI' or 'EGWZWEI_RS') (PDM field ID: CSPEZL.EWWG:2)
karte2_eins_zwei	einseitige oder zweiseitige Berechnung?	char(50)	- Applies for control chart 2 - Is required to recalculate action limits EINS - one-sided calculation (lower or upper limit values only) ZWEI - two-sided calculation (lower and upper limit values) (PDM field ID: CSPEZL.STATVERT:2)
karte2_mw	Average	float	- Applies for control chart 2 (PDM field ID: CSPEZL.MWAVG:2)
karte2_mw_berech	Calculate mean value	smallint	- Applies for XQ charts only - Applies for control chart 2 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.MWBERECH:2)
karte2_oeg	Upper action limit	float	- Applies for control chart 2 (PDM field ID: CSPEZL.OEG:2)
karte2_oeg_aktiv	autom. Fehlerart bei ob. EG-Verletzung?	smallint	- Applies for control chart 2 (PDM field ID: CSPEZL.OEGAKTIV:2)
karte2_oeg_berech	Calculate upper action limit	smallint	- Applies for control chart 2 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.OEGBERECH:2)
karte2_owg	Upper warning limit	float	- Applies for control chart 2 (PDM field ID: CSPEZL.OWG:2)
karte2_owg_aktiv	autom. Fehlerart bei ob. WG-Verletzung?	smallint	- Applies for control chart 2 (PDM field ID: CSPEZL.OWGAKTIV:2)
karte2_owg_berech	Calculate upper warning limit	smallint	- Applies for control chart 2 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.OWGBERECH:2)
karte2_quer	Vorgabewert Quer für Grenzwertberech.	float	- Applies for control chart 2 - Is required to recalculate action limits This field is only relevant if KARTE2_VORGABE = 'QUER'. (PDM field ID: CSPEZL.QUER:2)
karte2_rel_eg	Action limit default for relative deviat	float	- Applies for XQ charts only - Applies for control chart 2 This field is only relevant if KARTE2_VORGABE = 'ABW_REL' or 'ABW_PROZ'. (PDM field ID: CSPEZL.RELEG:2)
karte2_rel_wg	default for relative deviation of XQ	float	- Applies for XQ charts only - Applies for control chart 2 This field is only relevant if KARTE2_VORGABE = 'ABW_REL' or 'ABW_PROZ'. (PDM field ID: CSPEZL.RELWG:2)
karte2_run_aktiv	Generate run error	integer	
karte2_sigma	Vorgabewert Sigma für Grenzwertberech.	float	- Applies for control chart 2 - Is required to recalculate action limits This field is only relevant if KARTE2_VORGABE = 'SIGMA'. (PDM field ID: CSPEZL.SIGMA:2)
karte2_trend_aktiv	Generate trend error	smallint	
karte2_ueg	Lower action limit	float	- Applies for control chart 2 (PDM field ID: CSPEZL.UEG:2)
karte2_ueg_aktiv	autom. Fehlerart bei unt. EG-Verletzung?	smallint	- Applies for control chart 2 (PDM field ID: CSPEZL.UEGAKTIV:2)
karte2_ueg_berech		smallint	

karte2_uwg	Lower warning limit	float	- Applies for control chart 2 (PDM field ID: CSPEZL.UWG:2)
karte2_uwg_aktiv	autom. Fehlerart bei unt. WG-Verletzung?	smallint	- gilt für Regelkarte 2 (PDM field ID: CSPEZL.UWGAKTIV:2)
karte2_uwg_berech	Calculate lower warning limit	smallint	- Applies for control chart 2 0 - do not calculate when inspection order is generated 1 - calculate when inspection order is generated (PDM field ID: CSPEZL.UWGBERECH:2)
karte2_vorgabe	Vorgabe für die Berechnung der EG/WG	char(50)	- Applies for control chart 2 - Is required to recalculate action limits CPK - cpk default for calculation SIGMA - Sigma default for calculation QUER - Default of sQuer/an or RQuer/dn for calculation (PDM field ID: CSPEZL.VORG:2)
kunde_nr	Customer number	char(50)	Customers are defined in the CAQ_FIRMA table. (PDM field ID: CSPEZL.KDNR)
lieferant_nr	Supplier number	char(50)	Suppliers are defined in the CAQ_FIRMA table. (PDM field ID: CSPEZL.LIEFNR)
maschine_nr	Machine number	char(20)	Machine number (PDM field ID: CSPEZL.MNR)
mass_angabe	Type of indication of design values	char(50)	ABSOLUT - Indication of the absolute value RELATIV - Indication as relative deviation from the target value PROZENTUAL - Indication as deviation in per cent from the target value The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'MASSANGABE') (PDM field ID: CSPEZL.MASSANG)
merkmal_nr	Characteristic No.	char(50)	The corresponding catalog characteristic is defined in the CAQ_MERKMAL table. (PDM field ID: CSPEZL.CMMNR)
opeg	Upper process action limit	float	 (PDM field ID: CSPEZL.OPEG)
opeg_aktiv	Fehlerart bei OPEG-Verletzung anlegen?	smallint	 (PDM field ID: CSPEZL.OPEGAKTIV)
opeg_extern	externe obere Prozesseingriffsgrenze?	smallint	 (PDM field ID: CSPEZL.OPEGEXT)
opeg_extern_feldid	Field ID at external transfer	integer	Only relevant if OPEG_EXTERN = 1 Corresponding user fields must have the CPAN object type, the user field key (REC_TYPE) depends on the fact for which data type the entry is generated later. (PDM field ID: CSPEZL.OPEGEXT:FELD)
opeg_extern_zgart	Access type at external transfer	char(1)	F - Fast user field S - Slow user field (PDM field ID: CSPEZL.OPEGEXT:ZGART)
opeg_relativ	Relativer Wert für OPEG	float	 (PDM field ID: CSPEZL.OPEGREL)
opg	Upper plausibility limit	float	Upper plausibility limit (PDM field ID: CSPEZL.OPG)
opg_extern	External upper plausibility limit?	smallint	0 - The upper plausibility limit is fixed (in the OPG or OPG_RELATIV field) 1 - The upper plausibility limit is only transferred when the inspection order is generated (PDM field ID: CSPEZL.OPGEXT)
opg_extern_feldid	Field ID at external transfer	integer	Only relevant if OPG_EXTERN = 1 Corresponding user fields must have the CPAN object type, the user field key (REC_TYPE) depends on the fact for which data type the entry is generated later. (PDM field ID: CSPEZL.OPGEXT:FELD)
opg_extern_zgart	Access type at external transfer	char(1)	F - Fast user field S - Slow user field (PDM field ID: CSPEZL.OPGEXT:ZGART)
opg_relativ	Upper plausibility limit (relative)	float	Upper plausibility limit (relative) (PDM field ID: CSPEZL.OPGREL)
otg	Upper tolerance limit	float	Upper tolerance limit (PDM field ID: CSPEZL.OTG)

otg_aktiv	autom. Fehlerart bei ob. TG-Verletzung?	smallint	- Applies for single values only (PDM field ID: CSPEZL.OTGAKTIV)
otg_extern	External upper tolerance limit?	smallint	0 - the upper tolerance limit is fixed (in the OTG or OTG_RELATIV field) 1 - The upper tolerance limit is only transferred when the inspection order is generated (PDM field ID: CSPEZL.OTGEXT)
otg_extern_feldid	Field ID at external transfer	integer	Only relevant if OTG_EXTERN = 1 Corresponding user fields must have the CPAN object type, the user field key (REC_TYPE) depends on the fact for which data type the entry is generated later. (PDM field ID: CSPEZL.OTGEXT:FELD)
otg_extern_zgart	Access type at external transfer	char(1)	F - Fast user field S - Slow user field (PDM field ID: CSPEZL.OTGEXT:ZGART)
otg_relativ	Upper tolerance limit (relative)	float	Upper tolerance limit (relative) (PDM field ID: CSPEZL.OTGREL)
passung_id	fit clearance	char(50)	The valid entries can be found in the CAQ_PASSUNG table. (PDM field ID: CSPEZL.GWID)
passung_norm	fit norm	char(50)	The valid entries can be found in the CAQ_PASSUNG table. (PDM field ID: CSPEZL.GWNORM)
red_iopf_anz	Number of OK till special case	integer	How many OK inspections have to be made in a row before the special case can be deleted? (PDM field ID: CSPEZL.REDIOANZF)
res_nr	Ressourcen-Id	char(40)	(PDM field ID: CSPEZL.RES)
res_typ	Resource type	char(4)	(PDM field ID: CSPEZL.RESTYP)
rueckw_zahl	Acceptance qty.	integer	This field is only relevant if STICHPR_PLAN = "NC". The field name is quite contradictory. Yet, it is the acceptance number and not the rejection number. (PDM field ID: CSPEZL.RWMENGE)
rueckw_zahl_d	Rejection number	float	This field is only relevant if STICHPR_PLAN = 'NC'. (PDM field ID: CSPEZL.RUMENGE)
sonderfall	Entry a special or normal case?	smallint	0 - Entry is a normal case 1 - Entry is a special case (PDM field ID: CSPEZL.SONDERF)
spezlist_nr	SERIAL of the entry	serial	SERIAL of the entry (PDM field ID: CSPEZL.SPEZLNR)
stichpr_anzahl	Number of samples to be inspected	integer	Number of samples to be inspected (PDM field ID: CSPEZL.STPRANZ)
stichpr_plan	Sampling scheme	char(50)	The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'STPLPLAN') (PDM field ID: CSPEZL.STPRPLAN)
stichpr_umfang	Sample size	integer	Sample size (PDM field ID: CSPEZL.STPRUMF)
sw	Target value	float	Target value (PDM field ID: CSPEZL.SW)
sw_extern	External target value?	smallint	0 - The target value is fixed (in the SW field) 1 - The target value is only transferred when the inspection order is generated (PDM field ID: CSPEZL.SWEXT)
sw_extern_feldid	Field ID at external transfer	integer	Only relevant if SW_EXTERN = 1 Corresponding user fields must have the CPAN object type, the user field key (REC_TYPE) depends on the fact for which data type the entry is generated later. (PDM field ID: CSPEZL.SWEXT:FELD)
sw_extern_zgart	Access type at external transfer	char(1)	F - Fast user field S - Slow user field (PDM field ID: CSPEZL.SWEXT:ZGART)
upeg	Lower process action limit	float	(PDM field ID: CSPEZL.UPEG)
upeg_aktiv	Fehlerart bei UPEG-Verletzung anlegen?	smallint	(PDM field ID: CSPEZL.UPEGAKTIV)

upeg_extern	External Lower process action limit?	smallint	0 - Lower process action limit (see field OPEG respectively OPEG_RELATIV) 1 - Lower process action limit created after order transfered (PDM field ID: CSPEZL.UPEGEXT)
upeg_extern_feldid	Field ID at external transfer	integer	Only relevant if UPEG_EXTERN = 1 Corresponding user fields must have the CPAN object type, the user field key (REC_TYPE) depends on the fact for which data type the entry is generated later. (PDM field ID: CSPEZL.UPEGEXT:FELD)
upeg_extern_zgart	Access type at external transfer	char(1)	F - Fast user field S - Slow user field (PDM field ID: CSPEZL.UPEGEXT:ZGART)
upeg_relativ	Relative value for UPEG	float	(PDM field ID: CSPEZL.UPEGREL)
upg	Lower plausibility limit	float	Lower plausibility limit (PDM field ID: CSPEZL.UPG)
upg_extern	External lower plausibility limit?	smallint	0 - The lower plausibility limit is fixed (in the UPG or UPG_RELATIV field) 1 - The lower plausibility limit is only transferred when the inspection order is generated (PDM field ID: CSPEZL.UPGEXT)
upg_extern_feldid	Field ID at external transfer	integer	Only relevant if UPG_EXTERN = 1 Corresponding user fields must have the CPAN object type, the user field key (REC_TYPE) depends on the fact for which data type the entry is generated later. (PDM field ID: CSPEZL.UPGEXT:FELD)
upg_extern_zgart	Access type at external transfer	char(1)	F - Fast user field S - Slow user field (PDM field ID: CSPEZL.UPGEXT:ZGART)
upg_relativ	Lower plausibility limit (relative)	float	Lower plausibility limit (relative) (PDM field ID: CSPEZL.UPGREL)
user_c_01	Alphanumeric user field 1	char(50)	Alphanumeric user field (PDM field ID: CSPEZL.FU:1)
user_c_02	Alphanumeric user field 2	char(50)	(PDM field ID: CSPEZL.FU:2)
user_c_03	Alphanumeric user field 3	char(50)	(PDM field ID: CSPEZL.FU:3)
user_c_04	Alphanumeric user field 4	char(50)	Alphanumeric user field (PDM field ID: CSPEZL.FU:4)
user_c_05	Alphanumeric user field 5	char(50)	Alphanumeric user field (PDM field ID: CSPEZL.FU:5)
user_d_01	Date user field 1	date	Date user field (PDM field ID: CSPEZL.FU:13)
user_d_02	Date user field 2	date	Date user field (PDM field ID: CSPEZL.FU:14)
user_f_01	Decimal user field 1	float	(PDM field ID: CSPEZL.FU:11)
user_f_02	Decimal user field 2	float	Decimal user field (PDM field ID: CSPEZL.FU:12)
user_n_01	Numeric user field 1	integer	Numeric user field (PDM field ID: CSPEZL.FU:6)
user_n_02	Numeric user field 2	integer	Numeric user field (PDM field ID: CSPEZL.FU:7)
user_n_03	Numeric user field 3	integer	Numeric user field (PDM field ID: CSPEZL.FU:8)
user_n_04	Numeric user field 4	integer	Numeric user field (PDM field ID: CSPEZL.FU:9)
user_n_05	Numeric user field 5	integer	Numeric user field (PDM field ID: CSPEZL.FU:10)
utg	Lower tolerance limit	float	Lower tolerance limit (PDM field ID: CSPEZL.UTG)

utg_aktiv	??? Automatic. failure mode for ???	smallint	- Applies for single values only (PDM field ID: CSPEZL.UTGAKTIV)
utg_extern	External lower tolerance limit?	smallint	0 - The lower tolerance limit is fixed (in the UTG or UTG_RELATIV field) 1 - The lower tolerance limit is only transferred when the inspection order is generated (PDM field ID: CSPEZL.UTGEXT)
utg_extern_feldid	Field ID at external transfer	integer	Only relevant if UTG_EXTERN = 1 Corresponding user fields must have the CPAN object type, the user field key (REC_TYPE) depends on the fact for which data type the entry is generated later. (PDM field ID: CSPEZL.UTGEXT:FELD)
utg_extern_zgart	Access type at external transfer	char(1)	F - Fast user field S - Slow user field (PDM field ID: CSPEZL.UTGEXT:ZGART)
utg_relativ	Lower tolerance limit (relative)	float	Lower tolerance limit (relative) (PDM field ID: CSPEZL.UTGREL)
zuordnung_nr	Reference to selection of failure analys	char(50)	The corresponding catalog for the failure analysis selection can be found in the CAQ_ANALAUSSWAHL table. (PDM field ID: CSPEZL.ANAUSNR)

3.68. caq_stattyp

Table name: caq_stattyp		Product: CAQ	
Designation: QM system status type			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	
anlage_time	Initial data creation - Time	integer	
bearb	Last editor	char(50)	
bearb_date	Last change - Date	date	
bearb_time	Last change - Time	integer	
bereichs_abh	Subject to area?	smallint	(PDM field ID: CSTATYP.MOD:BER)
editierbar	editable?	smallint	(PDM field ID: CSTATYP.MOD:EDIT)
erweiterbar	expandable?	smallint	(PDM field ID: CSTATYP.MOD:INSDEL)
statustyp	Status type	char(50)	(PDM field ID: CSTATYP.STATYP)
statustyp_bez	Status type designation	char(250)	(PDM field ID: CSTATYP.STATYPBEZ)
zusatz	additional information	char(250)	(PDM field ID: CSTATYP.ZUSATZ)

3.69. caq_status

Table name: caq_status		Product: CAQ	
Designation: QM system status			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	
anlage_time	Initial data creation - Time	integer	
bearb	Last editor	char(50)	
bearb_date	Last change - Date	date	
bearb_time	Last change - Time	integer	
inaktiv	Inactive?	smallint	1 - Status is inactive 0 - Status is active (PDM field ID: CSYSSTAT.INAKTIV)
position	Position	smallint	(PDM field ID: CSYSSTAT.POS)
status_bereiche	Status area(s)	char(250)	(PDM field ID: CSYSSTAT.GUELTBER)
status_bezk	Status short designation	char(250)	(PDM field ID: CSYSSTAT.STABEZK)
status_bezl	Status long designation	char(250)	(PDM field ID: CSYSSTAT.STABEZL)
status_nr	Status identifier	char(50)	(PDM field ID: CSYSSTAT.STA)
status_typ	Status type	char(50)	(PDM field ID: CSYSSTAT.STATYP)
systemstat	Systemstatus?	smallint	1 - Systemstatus (not allowed to delete) 0 - none Systemstatus (PDM field ID: CSYSSTAT.MOD:SYS)
zusatz	Additional parameter	char(250)	(PDM field ID: CSYSSTAT.ZUSATZ)

3.70. caq_verantwortl

Table name: caq_verantwortl		Product: CAQ	
Designation: Parties in charge			
Column name	Column designation	Type	Description
abteilung_nr	Department number	char(50)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). Departments are filed in the CAQ_ABTEILUNG table. (PDM field ID: CVERANT.ABT)
anlage	Created by	char(50)	Time when the entry was created
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
archiv	Archive flag	smallint	0 - Current party in charge 1 - Archived party in charge
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
email	E-mail address	char(250)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). (PDM field ID: CVERANT.EMAIL)
firma_nr	Company number	char(50)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). Companies are filed in the CAQ_FIRMA table. (PDM field ID: CVERANT.FIRID)
firma_typ	Company type	char(50)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). Companies are filed in the CAQ_FIRMA table. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'FIRMENTYP') (PDM field ID: CVERANT.FIRTYP)
group_1	Group indicator of hierarchy level 1	char(50)	Identifier for parties in charge and groups of hierarchy level 1-5 (PDM field ID: CVERANT.DSGRP:1)
group_2	Group indicator of hierarchy level 2	char(50)	Identifier for parties in charge and groups of hierarchy level 1-5 (PDM field ID: CVERANT.DSGRP:2)
group_3	Group indicator of hierarchy level 3	char(50)	Identifier for parties in charge and groups of hierarchy level 1-5 (PDM field ID: CVERANT.DSGRP:3)
group_4	Group indicator of hierarchy level 4	char(50)	Identifier for parties in charge and groups of hierarchy level 1-5 (PDM field ID: CVERANT.DSGRP:4)
group_5	Group indicator of hierarchy level 5	char(50)	Identifier for parties in charge and groups of hierarchy level 1-5 (PDM field ID: CVERANT.DSGRP:5)
group_item	Party in charge or group?	smallint	0 - Party in charge 1 - Group (PDM field ID: CVERANT.DSGRPE)
hydra_usrid	User	char(50)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). The users are filed in the USER_TAB table. (PDM field ID: CVERANT.BEARB)
pager	Pager number	char(250)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). (PDM field ID: CVERANT.PAGER)
person_nr	Personnel number	char(50)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). Persons are filed in the CAQ_PERSON table. (PDM field ID: CVERANT.PERNR)
tabellen_ref	Table reference	char(50)	caq_abteilung - corresponding data record can be found in the caq_abteilung table caq_firma - corresponding data record can be found in the caq_firma table caq_person - corresponding data record can be found in the caq_person table caq_verteiler - corresponding data record can be found in the caq_verteiler table personalstamm - corresponding data record can be found in the personalstamm table (PDM field ID: CVERANT.TABREF)

tel_mobile	Mobile number	char(250)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). (PDM field ID: CVERANT.HANDY)
telefax	Fax number	char(250)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). (PDM field ID: CVERANT.FAX)
telefon	Telephone number	char(250)	This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). (PDM field ID: CVERANT.TEL)
verantw_bez_1	Des. 1 of party in charge/group	char(250)	If verantw_typ = 'PZE_PERSON' --> last name (PDM field ID: CVERANT.VERABEZ:1)
verantw_bez_2	Des. 2 of party in charge	char(250)	If verantw_typ = 'PZE_PERSON' --> first name This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). (PDM field ID: CVERANT.VERABEZ:2)
verantw_bez_3	Des. 3 of party in charge	char(250)	If verantw_typ = 'PZE_PERSON' --> empty This entry is only relevant for parties in charge and not for groups (GROUP_ITEM = 0). (PDM field ID: CVERANT.VERABEZ:3)
verantw_nr	Identifier party in charge/group	char(50)	If verantw_typ = 'PZE_PERSON' --> personnel number (PDM field ID: CVERANT.VERANT:NR)
verantw_typ	Type of party in charge/group	char(50)	'PERSON' - Party in charge is an external person 'ABTEILUNG' - Party in charge is a department 'VERTEILER' - Party in charge is a distributor 'PZE_PERSON' - Party in charge is a person from the PZE HR master <FIRMEN_TYP> - Party in charge is a company (type: <FIRMEN_TYP>) The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'VERANTWTYP') (PDM field ID: CVERANT.VERANT:TYP)

3.71. caq_vert_eint

Table name: caq_vert_eint		Product: CAQ	
Designation: Distributor entries			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
verantw_nr	Party in charge - number	char(50)	The parties in charge are filed in the CAQ_VERANTWORTL table. (PDM field ID: CVEREINT.VERANT:NR)
verantw_typ	Party in charge - type	char(50)	The parties in charge are filed in the CAQ_VERANTWORTL table. The valid entries can be found in the CAQ_STATUS table (STATUS_TYP = 'VERANTWTYP') (PDM field ID: CVEREINT.VERANT:TYP)
verteiler_nr	Distributor	char(50)	The distributors are filed in the CAQ_VERTTEILER table. (PDM field ID: CVEREINT.VERTNR)

3.72. caq_verteiler

Table name: caq_verteiler		Product: CAQ	
Designation: Distributor			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
verantw_flag	Party in charge	smallint	If the value of this field = 1 the corresponding entry in the caq_verantwortl table is also maintained. (PDM field ID: CVERT.VERANT:COPY)
verteiler_bez	designation	char(250)	Distributor designation (PDM field ID: CVERT.VERTBEZ)
verteiler_nr	Distributor	char(50)	Distributor number (PDM field ID: CVERT.VERTNR)

3.73. caq_zusatz_feld

Table name: caq_zusatz_feld		Product: CAQ	
Archive table: a_caq_zusatz_feld		Reload table: r_caq_zusatz_feld	
Designation: Slow user fields			
Column name	Column designation	Type	Description
anlage	Created by	char(50)	
anlage_date	Initial data creation - Date	date	Date when the entry was created
anlage_time	Initial data creation - Time	integer	Time when the entry was created.
attrib	Field content	char(250)	In the dialog of the corresponding BAPI object the field content is referenced wit the parameter SU:x. X represents the field identifier. (PDM field ID: SU:<Inhalt von Feld-Id>)
bearb	Last editor	char(50)	Last editor
bearb_date	Last change - Date	date	Last editing day
bearb_time	Last change - Time	integer	Last editing time
bereich	Area	char(10)	Areas are defined in the CAQ_BEREICH table.
ckey_1	Identifier 1 (alphanumeric)	char(50)	Alphanumeric key field
ckey_2	Identifier 2 (alphanumeric)	char(50)	Alphanumeric key field
feldid	Field identifier	integer	In the dialog of the corresponding BAPI object the field content is referenced wit the parameter SU:x. X represents the field identifier.
key_1	Identifier 1	integer	If REC_REF = "MEK" to be equated with the characteristic number If REC_REF = "PPL" to be equated with the inspection plan number If REC_REF = "PAN", "PAU" to be equated with the inspection requirement number If REC_REF = "RKK", "RKD" to be equated with the complaints number If REC_REF = "PMK" to be equated with the parameter of the gage number If REC_REF = "CPL" to be equated with the parameter of the control plan number
key_2	Identifier 2	integer	If REC_REF = "PPL" to be equated with the OP number If REC_REF = "PAU" to be equated with the inspection order number If REC_REF = "RKD" to be equated with the complaints detail number If REC_REF = "PMK" to be equated with the failure analysis tree ID
key_3	Identifier 3	integer	If REC_REF = "PAU" to be equated with the operation number If REC_REF = "RKD" to be equated with the failure analysis tree ID
key_4	Identifier 4	integer	Numeric key field
key_5	Identifikator 5	integer	Numeric key field
rec_ref	Data reference	char(20)	'MEK' = Characteristics catalog 'PAN' = Document from inspection requirement 'PAU' = Document from inspection order or subordinate structure (characteristic, measured value) 'PPL' = Document from inspection plan or subordinate structure (characteristic) 'RKK' = Document from complaints header 'RKD' = Document from complaints detail or subordinate structure (failure analysis) 'PMK' = Document from gage header or subordinate structure (failure analysis) 'CPL' = Production control plan (Control Plan)
rec_type	Input type	char(50)	Empty = Global structures (characteristics catalog) 'WEP' = Goods receipt inspection 'FEP' = In-production inspection 'WAP' = Goods issue inspection 'EMU' = Initial sample inspection 'PMV' = Gage management 'REK' = Complaints management 'CPL' = Production control plan (Control Plan)

3.74. change_log

Table name: change_log		Product: CAQ	
Designation: Change history of FMEA records		Description: Change history of FMEA records	
Column name	Column designation	Type	Description
commentary		char(250)	Remark
field_name		char(80)	Name of field
field_name_after		char(80)	Value after change
field_value_before		char(80)	Value before change
internal_id		serial	
key1		char(50)	
key2		char(50)	
key3		char(50)	
key4		char(50)	
key5		char(50)	
key6		char(50)	
key7		char(50)	
key8		char(50)	
key9		char(50)	
modified_by		char(10)	MOC-User
modified_ts		datetime	Date of change, set manually
value1		char(50)	
value2		char(50)	
value3		char(50)	
value4		char(50)	
value5		char(50)	
value6		char(50)	
value7		char(50)	
value8		char(50)	
value9		char(50)	
version		char(50)	

3.75. fmea_eval_nbr_catalog

Table name: fmea_eval_nbr_catalog		Product: CAQ	
Designation: FMEA Assessment catalog			
Column name	Column designation	Type	Description
active	Active	char(1)	
cat_comment		char(250)	
created_by	Created by	char(10)	
created_ts	Created on	datetime	
designation		char(250)	
id	Assessment catalog	char(50)	
internal_id		serial	
modified_by	Modified by	char(10)	
modified_ts	Modified on	datetime	
standard_id		char(50)	

3.76. fmea_eval_nbr_entry

Table name: fmea_eval_nbr_entry		Product: CAQ	
Designation: FMEA Assessment catalog entries			
Column name	Column designation	Type	Description
catalog_id	Assessment catalog	char(50)	
created_by	Created by	char(10)	
created_ts	Created on	datetime	
description	Description	char(4000)	
designation		char(250)	
eval_number	Rating	integer	
internal_id		serial	
modified_by	Modified by	char(10)	
modified_ts	Modified on	datetime	
type_id	FMEA type of rating	char(50)	

3.77. fmea_master

Table name: fmea_master		Product: CAQ	
Designation: FMEA Master data			
Column name	Column designation	Type	Description
active	Active	char(1)	
article_id	Id	char(50)	
article_index	Drawing issue number	char(50)	
created_by	Created by	char(10)	
created_ts	Created on	datetime	
end_date	Finish date	date	
evaluationcatalog	Assessment catalog	char(50)	
expense_actual	Actual expenditure in days	decimal(18,6)	
expense_target	Target expenditure in days	decimal(18,6)	
fmea	Number	char(50)	
fmea_id	Id	serial	
fmea_version	Version	char(50)	
manager_partyincharge_id	Project manager	char(50)	
manager_partyincharge_type	Project manager, type	char(50)	
measurestatus	Status of measure	date	
modified_by	Modified by	char(10)	
modified_ts	Modified on	datetime	
objective	Objective	char(4000)	
operation_id		char(50)	
orderer_partyincharge_id	Ordering party	char(50)	
orderer_partyincharge_type	Ordering party, type	char(50)	
originator_partyincharge_id	Created by	char(50)	
originator_partyincharge_type	Created by, type	char(50)	
partyincharge_id	Party in charge	char(50)	
partyincharge_type	Party in charge, type	char(50)	
processingstatus	Processing status in %	integer	
production_release_date	Production release date	date	
project	Project title	char(250)	
qm_area	Area	char(10)	
rec_type	Area type	char(50)	
release_date	Released on	date	
release_partyincharge_id	Release	char(50)	
release_partyincharge_type	Release type	char(50)	
responsibilityarea		char(15)	
start_date	Start date	date	
status_id	Status	char(50)	
team_id	Team No.	char(50)	
type_id	FMEA type	char(50)	

user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	

user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	

3.78. fmea_net

Table name: fmea_net		Product: CAQ	
Designation: FMEA Structure elements net			
Column name	Column designation	Type	Description
fmea_id		integer	
internal_id		serial	
node_source		integer	
node_target		integer	

3.79. fmea_risk_matrix

Table name: fmea_risk_matrix		Product: CAQ	
Column name	Column designation	Type	Description
detection		char(50)	
occurrence		char(50)	
severity		char(50)	
task_priority		char(50)	

3.80. fmea_structure_element

Table name: fmea_structure_element		Product: CAQ	
Designation: FMEA Structure elements			
Column name	Column designation	Type	Description
acceptance_qty	Acceptance qty.	integer	
actual_date	Actual date	date	
article_id	Id	char(50)	
article_index	Drawing issue number	char(50)	
characteristic_id	Characteristic	char(50)	
characteristic_type	Characteristic type	char(50)	
classification	Classification	char(50)	
commentary		char(250)	
completion_grade	Fulfillment in %	integer	
created_by	Created by	char(10)	
created_ts		datetime	
decimal_places	Decimal places	integer	
designation		char(250)	
effectivity_grade	Effectiveness in %	integer	
element_type	Element type	char(50)	
evaluation_a	Evaluation O	char(50)	
evaluation_b	Evaluation S	char(50)	
evaluation_e	Evaluation D	char(50)	
failure_id	Failure	char(50)	
fit	Fit	char(50)	
fmea_id	FMEA	integer	
form	FMEA form	char(1)	
function_type	Function type	char(50)	
gauge_group_id	Gage group	char(40)	
gauge_id	Gage	char(40)	
gauge_type	Gage type	char(50)	
inspection_plan	Inspection plan	char(1)	
inspection_result_base	Inspection result base	char(50)	
internal_id	ID	serial	
lower_tolerance_limit	Lower TL	decimal(18,6)	
lower_tolerance_limit_rel	Lower TL rel. %	decimal(18,6)	
machine	Machine	char(20)	
machine_group	Machine group	char(20)	
measure_date	Status of measure	date	
measure_id	Measure	char(50)	
measure_status	Measure status	char(50)	
measure_text		char(250)	
measure_type	Measure type	char(50)	

modified_by		char(10)	
modified_ts		datetime	
node_id	Identification	char(250)	
operation_designation	Operation designation	char(250)	
operation_id		char(40)	
parent	Tree parent	integer	
partyincharge_id	Party in charge	char(50)	
partyincharge_type	Party in charge, type	char(50)	
position_in_parent		integer	
production_control_plan	Production control plan	char(1)	
risk_priority_nbr	Risk priority number	integer	
sample_size	Sample size	integer	
sampling_scheme	Sampling scheme	char(50)	
show_external	Show externally	char(1)	
size_type	Size	char(50)	
standard	Standard	char(50)	
target_date	Target date	date	
target_value	Target value	decimal(18,6)	
unit	Unit	char(3)	
upper_tolerance_limit	Upper TL	decimal(18,6)	
upper_tolerance_limit_rel	Upper TL rel. %	decimal(18,6)	
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	

user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	

3.81. stg_ir_multiple_assessed

Table name: stg_ir_multiple_assessed		Product: CAQ	
Designation: Staging table for inspection results - multiple assessment		Description: This table contains the staging data of inspection results for multiple assessment	
		* Keys id (technical key)	
Column name	Column designation	Type	Description
acquisition_time	Acquisition time	timestamp(3)	
article_name	Article name	nvarchar2(100)	
batch_number	Batch number	nvarchar2(150)	
card_number	Batch card number of the inspector	nvarchar2(50)	
cavity_name	Cavity name	nvarchar2(50)	
characteristic_name	Characteristic name	nvarchar2(150)	
customer_name	Customer name	nvarchar2(50)	
data_supplier_name	Data supplier name	nvarchar2(100)	
defective_units_quantity	Quantity of defective units	integer	
drawing_revision	Drawing revision of the article	nvarchar2(50)	
id	Technical ID	bigserial	
inspected_units_quantity	Quantity of inspected units	integer	
invalid	Is inspection result invalid?	number(37)	0 = valid 1 = invalid
manufacturer_name	Manufacturer name	nvarchar2(50)	
operation_name	Operation number	nvarchar2(100)	
order_name	Order number	nvarchar2(100)	
personal_number	Personal number of the inspector	nvarchar2(50)	
sample_number	Sample number	integer	
supplier_name	Supplier name	nvarchar2(50)	
test_item_number	Test item number	nvarchar2(150)	
tester_name	Name of the inspector	nvarchar2(150)	
tool_name	Tool name	nvarchar2(50)	
user_name	User name of the inspector	nvarchar2(50)	

3.82. stg_ir_single_measured

Table name: stg_ir_single_measured		Product: CAQ	
Designation: Staging table for inspection results - single measures		Description: This table contains the staging data of inspection results for single measures	
		* Keys id (technical key)	
Column name	Column designation	Type	Description
acquisition_time	Acquisition time	timestamp(3)	
article_name	Article name	nvarchar2(100)	
batch_number	Batch number	nvarchar2(150)	
card_number	Batch card number of the inspector	nvarchar2(50)	
cavity_name	Cavity name	nvarchar2(50)	
characteristic_name	Characteristic name	nvarchar2(150)	
customer_name	Customer name	nvarchar2(50)	
data_supplier_name	Data supplier name	nvarchar2(100)	
drawing_revision	Drawing revision of the article	nvarchar2(50)	
id	Technical ID	bigserial	
invalid	Is inspection result invalid?	number(37)	0 = valid 1 = invalid
lower_plausibility_limit	Lower plausibility limit	float	
lower_tolerance_limit	Lower tolerance limit	float	
manufacturer_name	Manufacturer name	nvarchar2(50)	
measured_value	Measured value	float	
operation_name	Operation number	nvarchar2(100)	
order_name	Order number	nvarchar2(100)	
personal_number	Personal number of the inspector	nvarchar2(50)	
piece_number	Piece number	integer	
sample_number	Sample number	integer	
single_value_number	Single value number in the sample	integer	
supplier_name	Supplier name	nvarchar2(50)	
target_value	Target value	float	
test_item_number	Test item number	nvarchar2(150)	
tester_name	Name of the inspector	nvarchar2(150)	
tool_name	Tool name	nvarchar2(50)	
unit_name	Unit name	nvarchar2(100)	
upper_plausibility_limit	Upper plausibility limit	float	
upper_tolerance_limit	Upper tolerance limit	float	
user_name	User name of the inspector	nvarchar2(50)	

4. HLS

4.1. hls_pers_schichtm

Table name: hls_pers_schichtm		Product: HLS	
Designation: Individual shift/assignment times		Description: Individual shift/assignment times within the graphic shop floor scheduling module	
Column name	Column designation	Type	Description
aktiv	Active	char(1)	
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bedarf	Requirement	integer	
bedarf_abruesten		integer	
bedarf_ruesten		integer	
bemerkung	Commentary	char(40)	
datum_bis	Period until	date	
datum_von	Period from	date	
masch_nr	Workplace	char(20)	
mgruppe	Group	char(20)	
param_str01	Color for period	char(20)	
param_str02		char(20)	
param_str03		char(20)	
schicht_mod	Year model	smallint	
schichtnr	Shift number	smallint	
verw_profil	Reference	integer	
verweis	Reference	serial	
worktime	Working time	char(1)	
zeit_bis	Period to	integer	
zeit_von	Period from	integer	

4.2. hls_rwmatrix

Table name: hls_rwmatrix		Product: HLS	
Designation: Setup change matrix for HLS			
Column name	Column designation	Type	Description
artikel		char(40)	Currently not used
bedikost		integer	Currently not used
field1	Workplace	char(20)	workplace (PDM field ID: RUEW.MNR)
field2		char(20)	Currently not used
field3		char(20)	Currently not used
field4		char(20)	Currently not used
gangno		integer	Currently not used
gruppe	Group	char(20)	Empty if entry applies for all machine groups (for future use) (PDM field ID: RUEW.MGRP)
maschkost		integer	Currently not used
nutzgrad		integer	Currently not used
param1	Ignore static setup time	integer	Option ignore static Setuptime (0/1) (PDM field ID: RUEW.RUEZ_IGN)
param2		integer	Currently not used
param3		integer	Currently not used
param4		integer	Currently not used
ruestzeit	Additional setup time	integer	Additive setup time (PDM field ID: RUEW.RUEZ)
sollzyklus		integer	Currently not used
teil1	ID 1	char(20)	ID for preceding OP, e.g. tool number (PDM field ID: RUEW.VALV)
teil2	ID 2	char(20)	ID for succeeding OP, e.g. tool number (PDM field ID: RUEW.VALN)
teiligkeit		char(20)	Currently not used
typ	HLS_RWMATRIX	smallint	Indicates which type the entry corresponds to 1 Tool 2 Color 3 Material (PDM field ID: RUEW.TYP)
vompps		smallint	Currently not used
zeit1		integer	Currently not used
zeit2		integer	Currently not used

4.3. hls_setup

Table name: hls_setup		Product: HLS	
Designation: Setup für HLS			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
default_term_richt	Default scheduling direction	char(1)	Default scheduling direction (V/R) (PDM field ID: HYDRA.DEFTERMR)
feinplan_horizont	Detailed scheduling horizon	smallint	Detailed scheduling horizon When it comes to the automatic planning it is planned within this horizon. (PDM field ID: HYDRA.PLANHORIZ)
fix_horizont	Planning time fence	smallint	Planning time fence When it comes to the automatic planning the scheduled OPs are fixed within this horizon (PDM field ID: HYDRA.FIXHORIZ)
fixpunkt_term	Checkpoint scheduling	char(1)	If, despite reduction, the earliest end time (EET) of an operation is greater than the finish date of the production order (forward scheduling) or if the latest start time (LST) lies before the start date of the production order (backward scheduling) the finish date of the production order cannot be kept. In this case, this flag decides whether the "S" = Start or "E" = End of the order are adhered to. (PDM field ID: HYDRA.FIXPKTTERM)
hls_kennz		char(10)	[1,1] Scheduling for OPs that are firmly planned (planning component 1.11) V = add OPs to planned OPs -> forward scheduling is of higher priority R = add OPs to planned OPs -> backward scheduling is of higher priority J = add OPs to planned OPs -> backward scheduling in case of forward scheduling, forward scheduling in case of backward scheduling N/empty = no consideration [2,2] Taking queue time into account when scheduling V = shift model of preceding OP is used to calculate the queue time N = shift model of succeeding OP is used to calculate the queue time G = Gregorian calendar is used to calculate the queue time [3,3] Read Resource object list NULL = read Resource object list J = read Resource object list N = not read Resource object list (PDM field ID: HYDRA.HLSKENNZ)
linksverschiebung	Displacement to the left	char(1)	Depending on this flag, operations whose scheduled start lies within the planning horizon are treated differently regarding the dispatching start date when it comes to the automatic planning. If the indicator is set a "shift to the left" is made. The dispatching start date is set to "now" + planning lead time. This means: it is attempted to dispatch the operation before the scheduled start date. If the indicator is not set the scheduled start date is used as dispatching start date. The flag is only evaluated for the first operation of an order that can be planned (PDM field ID: HYDRA.OPT:LV)
plan_vorlauf	Planning lead time	integer	Planning lead time in sec. Automatic planning starts at Now + planning lead time (e.g. 3h) (PDM field ID: HYDRA.PLANVL)
prio_nicht_berueck	priority	char(4)	Orders whose priority is less than the priority defined here are not considered when it comes to the automatic, server-based planning. If this field remains empty all orders (independent of their priority) are taken into account. Attention: This refers to the priority defined in the order header not to the priority of the operations (PDM field ID: HYDRA.PRIONBER)
simul_horizont	Simulation horizon	smallint	Beyond the dispatching horizon operations are simulated taking the actual capacity into account and the single results are written in the respective fields for the dates. This simulation takes place in the defined simulation horizon (PDM field ID: HYDRA.SIMHORIZ)
skyline_horizont		smallint	Currently not used
streubreite		smallint	Currently not used

4.4. res_fertigung_var

Table name: res_fertigung_var		Product: HLS	
Designation: production variants			
Column name	Column designation	Type	Description
abruestzeit	Teardown time	integer	The teardown time is accepted when taking over production variants (PDM field ID: FERTVAR.ABRZ)
anzahl_10		integer	Currently not used
anzahl_11		integer	Currently not used
anzahl_12		integer	Currently not used
anzahl_3		integer	Format N8.2
anzahl_4		integer	Format N8.2
anzahl_5		integer	Currently not used
anzahl_6		integer	Currently not used
anzahl_7		integer	Currently not used
anzahl_8		integer	Currently not used
anzahl_9		integer	Currently not used
artikel	Article	char(40)	Article (PDM field ID: FERTVAR.ATK)
atk_bez	Article designation	char(40)	
aufruestzeit	Setup time	integer	Setup time (PDM field ID: FERTVAR.RUEZ)
bearb	Modified by	char(10)	Is assigned to BEARB during processing.
bearb_datum		date	Is assigned to DAT during processing
bearb_zeit		integer	Is assigned to ZEI during processing.
bemerkung	Comment	char(50)	Comment (PDM field ID: FERTVAR.BEM)
daten_bez	Data record identifier	char(15)	Data record identifier (PDM field ID: FERTVAR.DSBEZ)
field1		char(20)	Currently not used
field2		char(20)	Currently not used
field3		char(20)	Currently not used
field4		char(20)	Currently not used
field5		char(20)	Currently not used
firma	Company for article/material type	char(10)	Company for article/material type (PDM field ID: FERTVAR.FIR:ATK)
firma_10		char(10)	Currently not used
firma_11		char(10)	Currently not used
firma_12		char(10)	Currently not used
firma_3		char(10)	Currently not used
firma_4		char(10)	Currently not used
firma_5		char(10)	Currently not used
firma_6		char(10)	Currently not used
firma_7		char(10)	Currently not used
firma_8		char(10)	Currently not used

firma_9		char(10)	Currently not used
gueltig_bis		date	Valid till (PDM field ID: FERTVAR.DATE)
gueltig_von		date	Valid from (PDM field ID: FERTVAR.DATB)
key	Unique key	serial	Reference (PDM field ID: FERTVAR.VERWEIS)
masch_anzahl		integer	Number of required machines. Always greater than 0 (PDM field ID: FERTVAR.MANZ)
masch_firma	Company machine	char(10)	Company machines (PDM field ID: FERTVAR.FIR:MNR)
masch_gruppe	Machine group	char(20)	Machine group (PDM field ID: FERTVAR.MGRP)
masch_typ		char(4)	Currently not used
masch_version		char(20)	Currently not used
maschine	Machine number	char(20)	Machine (PDM field ID: FERTVAR.MNR)
materialtyp	Materialtyp	char(10)	Currently not used (PDM field ID: FERTVAR.MATTYP)
param1		integer	HLS 7.2 processing time
param2		integer	Currently not used
param3		integer	Currently not used
param4		integer	Currently not used
param5		integer	Currently not used
prioritaet	Priority	integer	Priority (PDM field ID: FERTVAR.PRIO)
ress_familie_10		char(20)	Currently not used
ress_familie_11		char(20)	Currently not used
ress_familie_12		char(20)	Currently not used
ress_familie_3		char(20)	Currently not used
ress_familie_4		char(20)	Currently not used
ress_familie_5		char(20)	Currently not used
ress_familie_6		char(20)	Currently not used
ress_familie_7		char(20)	Currently not used
ress_familie_8		char(20)	Currently not used
ress_familie_9		char(20)	Currently not used
ress_typ_10		char(4)	Currently not used
ress_typ_11		char(4)	Currently not used
ress_typ_12		char(4)	Currently not used
ress_typ_3		char(4)	Currently not used
ress_typ_4		char(4)	Currently not used
ress_typ_5		char(4)	Currently not used
ress_typ_6		char(4)	Currently not used
ress_typ_7		char(4)	Currently not used
ress_typ_8		char(4)	Currently not used
ress_typ_9		char(4)	Currently not used
ress_version_10		char(20)	Currently not used
ress_version_11		char(20)	Currently not used
ress_version_12		char(20)	Currently not used

ress_version_3		char(20)	Currently not used
ress_version_4		char(20)	Currently not used
ress_version_5		char(20)	Currently not used
ress_version_6		char(20)	Currently not used
ress_version_7		char(20)	Currently not used
ress_version_8		char(20)	Currently not used
ress_version_9		char(20)	Currently not used
ressource_10		char(20)	Currently not used
ressource_11		char(20)	Currently not used
ressource_12		char(20)	Currently not used
ressource_3		char(20)	Currently not used
ressource_4		char(20)	Currently not used
ressource_5		char(20)	Currently not used
ressource_6		char(20)	Currently not used
ressource_7		char(20)	Currently not used
ressource_8		char(20)	Currently not used
ressource_9		char(20)	Currently not used
soll_zyklus	Target cycle	integer	Target cycle (PDM field ID: FERTVAR.SZY)
sperr_bem	Lock comment	char(30)	
sperr_grund	Blocking reason	integer	
status	Current status	char(1)	F = released S = blocked L = (logically) deleted (PDM field ID: FERTVAR.STA)
szy_abw	Target cycle deviation	decimal(8,3)	
teiligkeit	Partitioning	integer	Format N8.2 Thus 1.00 = 100 and so on. Can also be 0. If entry is 0 the partitioning of the tool is used (PDM field ID: FERTVAR.TLG)
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	

user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	

user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
verantw_bereich		char(15)	
version	Version within a variant	char(10)	Version (PDM field ID: FERTVAR.VER)
werk_anzahl		integer	Number of required tools. Always greater than 0 (PDM field ID: FERTVAR.WANZ)
werk_familie	Tool family	char(18)	Tool family (PDM field ID: FERTVAR.WFAM)
werk_firma	Company tool	char(10)	Currently not used (PDM field ID: FERTVAR.FIR:WNR)
werk_typ	Resource type	char(4)	Currently not used
werk_version		char(20)	Currently not used
werkzeug	Tool number	char(40)	Tool number (PDM field ID: FERTVAR.WNR)

4.5. user_profil

Table name: user_profil		Product: HLS	
Designation: User profile			
Column name	Column designation	Type	Description
bearb	Editor	char(10)	Last editor (PDM field ID: BEARBPROF.BEARB)
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
profil	Key user profile	char(40)	Key user profile (PDM field ID: BEARBPROF.BEARBPROF)
profil_bezk	Short name of profile	char(6)	Short name of profile (PDM field ID: BEARBPROF.BEZK)
profil_bezl	Long name of profile	char(20)	Long name of profile (PDM field ID: BEARBPROF.BEZ)
usr	User	char(10)	User number (PDM field ID: BEARBPROF.BEARB)
verweis		serial	Unique number of record. (PDM field ID: BEARBPROF.VERWEIS)

4.6. user_profil_zuord

Table name: user_profil_zuord		Product: HLS	
Designation: User profile assignment			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
firma		char(10)	Currently not used
param_01	Sequence	integer	Order for the group
param_02		integer	Order for the workplace
param_str01		char(20)	Currently not used
param_str02		char(20)	Currently not used
param_str03		char(40)	Currently not used
pdate_01		date	Currently not used
pdate_02		date	Currently not used
pdouble_01		decimal(18,6)	Currently not used
pdouble_02		decimal(18,6)	Currently not used
verw_profil		integer	Reference to unique data record in the USER_PROFIL table
zuord_kennung	ID	char(20)	MGRP=machine group, VAB=responsibility area, MNR=machine, KST=cost center (PDM field ID: BEARBPROF.KENN)
zuord_opt	Option	char(40)	1: Display HLS 2: Plan HLS 3: HLS: cross-sectoral planning for machine groups without cost center authorization J - cross-sectoral planning N - non cross-sectoral planning 4: HLS: display machines without cost center authorization J - display N - do not display (PDM field ID: BEARBPROF.HLSOPT)
zuord_wert	Value	char(40)	Machine group (PDM field ID: BEARBPROF.VAL)

5. KERNEL

5.1. esk_event_cfg

Table name: esk_event_cfg		Product: KERNEL	
Designation: Event configuration			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
cfg_active	Event - active	char(1)	J/N=active Event is only checked if it is active. (PDM field ID: ESK.AKTIV)
close_cmd_active	Automatic after having closed escalation	char(1)	--- (PDM field ID: ESK.COMDAKTIVC)
close_cmd_mod	Automatic after having closed escalation	char(1)	--- (PDM field ID: ESK.COMDMODC)
close_cmd_opt	Automatic after having closed escalation	char(10)	--- (PDM field ID: ESK.COMDOPTC:x)
close_cmd_param	Automatic after having closed escalation	char(255)	--- (PDM field ID: ESK.COMDPARAMC)
event_cond	Event - condition	char(255)	A condition is indicated as formula (tab condition in event configuration) (PDM field ID: ESK.EXPR)
event_id	Event - event	char(40)	Reference to registered event --> Registered events (esk_event_reg) (PDM field ID: ESK.ESKID)
event_mod	ESK mode	char(1)	F = Formula (fixed) (PDM field ID: ESK.MOD)
event_name	Event - designation	char(100)	Description of the event In case of initial data creation: take over of the value from esk_event_reg.event_name (default - can be overwritten by the user) (PDM field ID: ESK.ESKBEZ)
farbe	Event - color	smallint	Event - color: 1=Green 2=Light red 3=Pink 4=Purple 5=Black 6=Gray 7=Turquoise 8=Light blue 9=Blue 10=Brown 11=Light green 12=Yellow 13=White 14=Olive 15=Silver 16=Light yellow (PDM field ID: ESK.COLOR)

inform_by_1	Notification - type	char(6)	""; empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console (PDM field ID: ESK.INFO:1)
inform_by_2	Notification - type	char(6)	""; empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console (PDM field ID: ESK.INFO:2)
inform_by_3	Notification - type	char(6)	""; empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console (PDM field ID: ESK.INFO:3)
inform_by_4	Notification - type	char(6)	""; empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console (PDM field ID: ESK.INFO:4)
inform_by_5	Notification type	char(6)	""; empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console (PDM field ID: ESK.INFO:5)
inform_by_6	Notification - type	char(6)	""; empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console (PDM field ID: ESK.INFO:6)
inform_op_1	Notification - Operator	char(6)	""; empty to: "to" and: "and" Only "to" is possible for the first entry. (PDM field ID: ESK.INFOMOD:1)
inform_op_2	Notification - Operator	char(6)	""; empty to: "to" and: "and" Only "to" is possible for the first entry. (PDM field ID: ESK.INFOMOD:2)
inform_op_3	Notification - Operator	char(6)	""; empty to: "to" and: "and" Only "to" is possible for the first entry. (PDM field ID: ESK.INFOMOD:3)
inform_op_4	Notification - Operator	char(6)	""; empty to: "to" and: "and" Only "to" is possible for the first entry. (PDM field ID: ESK.INFOMOD:4)
inform_op_5	Notification - Operator	char(6)	""; empty to: "to" and: "and" Only "to" is possible for the first entry. (PDM field ID: ESK.INFOMOD:5)

inform_op_6	Notification - Operator	char(6)	"": empty to: "to" and: "and" Only "to" is possible for the first entry. (PDM field ID: ESK.INFOMOD:6)
last_chk_date	Last check	date	Date of the last check (only in case of cyclic monitoring)
last_chk_time	Last check	integer	Time of last check (only in case of cyclic monitoring)
msg_body	Message - text	char(320)	Plaintext of the message to be sent. Takeover of the input in the tab escalation of the event configuration. %Identification% is replaced by the value of the identification indicated in the escalation data (dialog string). %% is replaced by % in the text. Plausibility check in BAPI whether variables used in the message text or subject matter are registered (not executed for the time being). (PDM field ID: ESK.MSGTXT)
msg_subject	Message - subject	char(50)	Message - subject (PDM field ID: ESK.MSGSUBJ)
open_cmd_active	Automatic after dispatch of message	char(1)	--- (PDM field ID: ESK.CMDAKTIVO)
open_cmd_mod	Automatic after dispatch of message	char(1)	---- (PDM field ID: ESK.CMDMODO)
open_cmd_opt	Automatic after dispatch of message	char(10)	--- (PDM field ID: ESK.CMDOPTO:n)
open_cmd_param	Automatic after dispatch of message	char(255)	open_cmd_mod=i: "CLOSE" : Closing the event --> the dispatch of a message results in the solution of the event. (PDM field ID: ESK.CMDPARAMO)
prio	Event - priority	smallint	Sorting possibility no other function is connected to the field (PDM field ID: ESK.PRIO)
read_cmd_active	Automatic after having read the message	char(1)	--- (PDM field ID: ESK.CMDAKTIVR)
read_cmd_mod	Automatic after having read the message	char(1)	i: start internal function that is contained in field read_cmd_param --- (PDM field ID: ESK.CMDMODR)
read_cmd_opt	Automatic after having read the message	char(10)	--- (PDM field ID: ESK.CMDOPTR:x)
read_cmd_param	Automatic after having read the message	char(255)	--- (PDM field ID: ESK.CMDPARAMR)
receiver_function	Event - recipient	char(40)	Name of the receiving function group (if receiver_type = "F") --> "reference" to esk_function Plausibility with respect to esk_function: In esk_function a group may only be deleted if there is no configuration. (PDM field ID: ESK.RCV:FKT)
receiver_person	Event - recipient	char(10)	Personnel number of the recipient (if receiver_type = "P") (PDM field ID: ESK.RCV:PNR)
receiver_type	Recipient type	char(1)	Definition whether the recipient is a single person or a function group. (Tab General in event configuration). Recipient type -F=Function Recipient is function group from esk_function - P=Person Recipient is person from HR master data (personalstamm) (PDM field ID: ESK.RCV:ART)
script_name	UserExit	char(80)	---

smtp_cc	Send e-mail by CC to	char(255)	
start_script	Start UserExit	char(1)	---
start_workflow	Start Workflow	char(1)	---
verweis	DB reference	serial	Database reference (PDM field ID: ESK.VERWEIS)
wfaliasname	Workflow	char(50)	
wffunc_group	Function	char(100)	
wffunc_role	Function	char(100)	
wfgroup	Group	char(100)	
wfuser	User	char(100)	
workflow_nr	Workflow	char(50)	---
workflow_rec_ref	Entry type	char(20)	---
workflow_rec_type	Superset	char(50)	---
zyklus_day	Cycle in days	integer	Number of days between 2 cycles Default value from esk_event_reg (default - can be overwritten by the user) (PDM field ID: ESK.ZYKLTG)
zyklus_secs	Cycle in seconds	integer	Number of seconds between 2 cycles Default value from esk_event_reg (default can be overwritten by the user) If there is cyclic monitoring the following applies: (ZYKLUS_DAYS * 86400) + ZYKLUS_SECS > 0 otherwise: ZYKLUS_DAYS = ZYKLUS_SECS = 0 (PDM field ID: ESK.ZYKLDAUER)

5.2. esk_event_msg

Table name: esk_event_msg		Product: KERNEL	
Archive table: a_esk_event_msg			
Designation: Escalations occurred			
Column name	Column designation	Type	Description
close_cmd_ret	Result of the CLOSE_CMD	integer	--- (PDM field ID: ESKMSG.CMDRETC)
end_date	End of the escalation	date	End of the escalation
end_remark	Solution note	char(320)	Solution with comment (PDM field ID: ESKMSG.BEM)
end_res	Solution	char(20)	---
end_time	End of the escalation	integer	End of the escalation
ended_by	User	char(10)	User
esc_state	Status	char(1)	O-Open "open" P-In Process "in process", i.e. the first message has been read C-Closed "closed", i.e. it has been closed (PDM field ID: ESKMSG.STA)
event_id	Event	char(40)	Reference to configured and registered event (esk_event_reg, esk_event_cfg) (PDM field ID: ESKMSG.ESKID)
event_name	Description	char(100)	Transfer from esk_event_cfg (PDM field ID: ESKMSG.ESKBEZ)
event_verweis		integer	Reference to esk_event_cfg Several different escalations can be defined for one event.
first_bearb	First editor	char(10)	First editor
first_bearb_date	Time of first editing	date	Time of first editing, i.e. reading date of the 1st step
first_bearb_time	Time of first editing	integer	Time of first editing, i.e. reading date of 1st step
inform_by_1	Notification type	char(6)	Notification type "": empty "SMS": SMS "EMAIL": e-mail "PAGER": Pager "KONS": Console "TERM": Terminal (PDM field ID: ESKMSG.INFO:1)
inform_by_2	Type	char(6)	see INFORM_BY_1 (PDM field ID: ESKMSG.INFO:2)
inform_by_3	Type	char(6)	see INFORM_BY_1 (PDM field ID: ESKMSG.INFO:3)
inform_by_4	Type	char(6)	see INFORM_BY_1 (PDM field ID: ESKMSG.INFO:4)
inform_by_5	Type	char(6)	see INFORM_BY_1 (PDM field ID: ESKMSG.INFO:5)
inform_by_6	Type	char(6)	see INFORM_BY_1 (PDM field ID: ESKMSG.INFO:6)
key1	Key data of the escalation	char(40)	Key data of the escalation (object name) (PDM field ID: ESKMSG.KEY:1)
key2	Key data of the escalation	char(40)	Key data of the escalation (key value 1) (PDM field ID: ESKMSG.KEY:2)
key3	Key data of the escalation	char(40)	Key data of the escalation (key value 2) (PDM field ID: ESKMSG.KEY:3)

key4	Key data of the escalation	char(40)	Key data of the escalation (key value 3) (PDM field ID: ESKMSG.KEY:4)
key5	Key data of the escalation	char(40)	Key data of the escalation (key value 4) (PDM field ID: ESKMSG.KEY:5)
last_bearb	Last editor	char(10)	Last editor
last_bearb_date	Time of last editing	date	Time of last editing of a processing step
last_bearb_time	Time of last editing	integer	Time of last editing of a processing step
msg_body	Message text	char(350)	Transfer from: esk_event_cfg (with replaced acronyms from esk_event_reg_var) (PDM field ID: ESKMSG.MSGTXT)
msg_subject	Subject of the message	char(50)	Transfer from esk_event_cfg (with replaced acronyms from esk_event_reg_var) (PDM field ID: ESKMSG.MSGSUBJ)
number_of_esc	Number of the escalations occurred	integer	Number of the escalations occurred (e.g. an escalation can be logged on several times)
read_cmd_ret	Result of the READ_CMD	integer	--- (PDM field ID: ESKMSG.CMDRETR)
start_date	Beginning of the escalation	date	Beginning of the escalation (occurrence of the event)
start_time	Beginning of the escalation	integer	Beginning of the escalation (occurrence of the event)
started_by	User	char(10)	User
update_by	User	char(10)	User who entered the escalation logged on the last time
update_date	Time of escalation logged on last time	date	Time of the escalation logged on the last time
update_time	Time of escalation logged on last time	integer	Time of the escalation logged on the last time
verweis	DB reference	serial	Database reference (PDM field ID: ESKMSG.VERWEIS)
workflow_verweis	Reference to open workflow	integer	Reference to open workflow (for future use)

5.3. esk_event_msgdet

Table name: esk_event_msgdet		Product: KERNEL	
Archive table: a_esk_event_msgdet			
Designation: Escalation messages			
Column name	Column designation	Type	Description
det_step	Notification level	integer	1 (highest transmission = current) is increased by 1 with each detail entry (PDM field ID: ESKMSG.STEP)
esc_det_state	Status of the transmission	char(1)	U="unread" R="read" P="unprocessed" The message was not read as another member of the function group forwarded it. F="forwarded" The message has been forwarded (PDM field ID: (ESKMSG.DETSTA))
forward_date	Time of the transmission	date	Date when this step was forwarded (and by whom)
forward_time	Time of the transmission	integer	Time when this step was forwarded (and by whom)
forwarded_by	Forwarded by	char(10)	Forwarded by
inform_by_1	Notification - type 1	char(6)	"": empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console
inform_by_2	Notification - type 2	char(6)	"": empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console
inform_by_3	Notification - type 3	char(6)	"": empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console
inform_by_4	Notification - type 4	char(6)	"": empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console
inform_by_5	Notification - type 5	char(6)	"": empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console
inform_by_6	Notification - type 6	char(6)	"": empty "SMS": SMS "EMAIL:" e-mail "PAGER": Pager "KONS": Console
msg_by	Trigger of the transmission	char(10)	Editor (or SYSTEM) that forwarded the message.
msg_date	Time of forwarding	date	Time of forwarding/escalation
msg_remark	Comment on the transmission	char(320)	Comment on the transmission (PDM field ID: ESKMSG.BEM)

msg_state	Overall status of the notification	char(3)	NEW, new, not yet processed ERR errors arising in the transmission of messages OK successfully sent (completed) IP "in process" NON notification is not required IMP "impossible". Message cannot be sent (e.g. when message is supposed to be sent by e-mail but the person does not have an e-mail account) (PDM field ID: ESKMSG.MSGSTA)
msg_state_1	Status on transmission 1	char(3)	Status on transmission 1
msg_state_2		char(3)	Status on transmission 2
msg_state_3		char(3)	Status on transmission 3
msg_state_4		char(3)	Status on transmission 4
msg_state_5		char(3)	Status on transmission 5
msg_state_6	Status on transmission 6	char(3)	Status on transmission 6
msg_time	Time of forwarding	integer	Time of forwarding/escalation
read_by	Reader of the message	char(10)	Editor who read the message
read_date	Time when message was read	date	Time when message was read.
read_time	Time when message was read	integer	Time when message was read
receiver_bearb		char(10)	Editor from user tab to the personnel number (if available) (PDM field ID: ESKMSG.RCV:BEARB)
receiver_function	Function group	char(40)	If receiver_type = "f" an entry is made for each recipient of the function group with receiver_type = "f", receiver_person = "personnel number" and receiver_function = "function group" (PDM field ID: ESKMSG.RCV:FKT)
receiver_person	Recipient	char(10)	The recipient's personnel number -> personalstamm (HR master) (PDM field ID: ESKMSG.RCV:PNR)
receiver_type	Recipient type	char(1)	Recipient type - F=Function Recipient is function group from esk_function - P=Person Recipient is person from personalstamm (HR master) (PDM field ID: ESKMSG.RCV:ART)
verweis	DB reference	serial	Database reference (PDM field ID: ESKMSG.VERWEIS:DET)
verweis_msg	Reference to esk_event_msg	integer	--- (PDM field ID: ESKMSG.VERWEIS:MSG)

5.4. esk_event_msgext

Table name: esk_event_msgext		Product: KERNEL	
Designation: Zusätze zu Eskalationsnachrichten			
Column name	Column designation	Type	Description
ext_data	Daten	char(1000)	
ext_type	Typ	char(1)	d: ursprüngliche Dialogdaten Die ursprünglichen Dialogdaten werden in esk_event_msgext als Typ "d" gespeichert, wenn ein OPEN_CMD, CLOSE_CMD oder ein READ_CMD im Ereignis definiert ist. Beim Beenden der Eskalation werden die Daten verworfen.
verweis	DB-Verweis	serial	DB-Verweis
verweis_msg	Verknüpfung zu esk_event_msg.verweis	integer	

5.5. esk_event_reg

Table name: esk_event_reg		Product: KERNEL	
Designation: Event registry - escalations			
Column name	Column designation	Type	Description
bearb	Editor	char(10)	Last editor
bearb_date	Date of the entry	date	Last editing day
bearb_time	Time of the entry	integer	Last editing time
close_cmd_active	Automatic after closing the escalation	char(1)	J: Processing is activated N: Processing is inactive
close_cmd_mod	Automatic after closing the escalation	char(1)	b: Start BAPI that is contained in field close_cmd_param for future use: i: internal function s: script u:userexit
close_cmd_opt	Automatic after closing the escalation	char(10)	ESK.CMDOPTC:1 [1,1] J: Value is visible in event configuration (Default N) ESK.CMDOPTC:2 [2,2] J: Value can be activated/deactivated (Default N) ESK.CMDOPTC:3 [3,3] J: Value can be changed (Default N)
close_cmd_param	Automatic after closing the escalation	char(255)	b: BAPI string that is retrieved when the escalation is closed (solved). The BAPI string may contain wildcards such as %AKRONYM% , which are replaced by the memorized values of the original dialog data. The wildcard "%ESKMSG.BEMGR%" contains the value from esk_event_msg.end_res, the wildcard "%ESKMSG.BEM%" contains the corresponding solution text from esk_event_msg.end_remark.
cycl_day	Cycle in days	integer	Number of days between 2 cycles (default value for the configuration)
cycl_secs	Cycle in seconds	integer	Seconds between 2 checking processes (default value for the configuration)
cyclic	Event to be monitored cyclically	char(1)	J / N - cyclic monitoring Yes/No By means of this indicator, events, which have to be monitored, are marked as they cannot actively trigger an escalation. (J/N). If an event is defined as "monitored cyclically" the cyclic monitoring can be defined in the 2 following fields.
event_cat	Category	char(1)	A=application-related (e.g.: ZKS: Entry open) T=technical (e.g. interface SAP: no connection, (e.g. network: client offline, ZKS: sabotage) There is a division in categories in order to simplify the evaluation of the events and configurations und to provide the user a better overview.
event_class	Produkt classification	char(10)	Product classification (e.g. PZE / PDV / S YS) Further division below the category. It can be classified according to the product, for example, in order to enable a selection of PZE events. Thus, there is the classification in e.g. PZE, PDV, TERM, etc...
event_id	Event ID	char(40)	Each event is determined by a unique ID. When starting the escalation manager, the EVENT_ID is absolutely necessary to identify the respective escalation.
event_name	Description of the escalation	char(100)	Description of the escalation
licensekeys	License check	char(80)	If allocated, the event can only be used if one of the licenses is available. Several licenses are separated by a blank character.
open_cmd_active	Automatic after dispatch of the message	char(1)	J: Processing is activated N: Processing is inactive
open_cmd_mod	Automatic after dispatch of the message	char(1)	i: start internal function that is conatined in field open_cmd_param for future use: b: BAPI s: script u:userexit

open_cmd_opt	Automatic after dispatch of the message	char(10)	ESK.CMDOPTO:1 [1,1] J: value is visible in event configuration (Default N) ESK.CMDOPTO:2 [2,2] J: value can be activated/deactivated (Default N) ESK.CMDOPTO:3 [3,3] J: value can be changed (Default N)
open_cmd_param	Automatic after dispatch of the message	char(255)	open_cmd_mod=i: "CLOSE" : Closing the event --> The dispatch of a message results in the solution of the event.
read_cmd_active	Automatic after having read the message	char(1)	J: Processing is activated N: Processing is inactive
read_cmd_mod	Automatic after having read the message	char(1)	i: start internal function that is contained in field read_cmd_param for future use: b: BAPI s: script u:userexit
read_cmd_opt	Automatic after having read the message	char(10)	ESK.CMDOPTR:1 [1,1] J: Value is visible in event configuration (Default N) ESK.CMDOPTR:2 [2,2] J: Value can be activated/deactivated (Default N) ESK.CMDOPTR:3 [3,3] J: Value can be changed (Default N)
read_cmd_param	Automatic after having read the message	char(255)	close_cmd_mod=i: "CLOSE" : Closing the event --> Reading a message results in the solution of an event.
verweis	DB reference	serial	Database reference

5.6. esk_event_reg_res

Table name: esk_event_reg_res		Product: KERNEL	
Designation: Event registry - solutions			
Column name	Column designation	Type	Description
event_id	Field event ID constitutes connection	char(40)	The field event ID constitutes the connection.
var_name	Name of the variable	char(30)	Designation in combobox
var_type	Type of the variable	char(1)	Type of the variable C = Close: Can be used for finishing
var_value	Value of the variable	char(20)	Value that is set as %RET:CLOSE% in the subsequent BAPI call.
verweis	DB reference	serial	When closing an event a "reason for the solution" has to be selected and this reason is saved as END_RES in the message and can be re-used there (if entries with var_type "C" are available for the event in esk-event_reg_res). The designation (VAR_NAME) is only displayed in the DB combo, the internal value (VAR_VALUE) is forwarded as ESKMSG.BEMGR in the BAPI.

5.7. esk_event_reg_var

Table name: esk_event_reg_var		Product: KERNEL	
Designation: Event registry - variables			
Column name	Column designation	Type	Description
event_id	Event ID	char(40)	The field event ID constitutes the connection to the registered event
f_kennung	Acronym	char(20)	Used acronyms, which are also transferred when starting the escalation and which are built in the message text by place holders. e.g.: MNR.MNR
key_nr	Key field	smallint	Key fields are numbered from 1 - 4 and reference to the fields key1, ..., key5 in the table esk_event_msg, "normal" fields have the value 0. Assignment for esk_event_msg: 0 No assignment (default) 1 Identifier in key1 1 Value in key2 2 Value in key3 3 Value in key4 4 Value in key5
ref_kenn	Object type	char(20)	Reference to hyd_userfielddef, the field is defined here (among other things whether the field is numeric, alphanumeric, etc.) e.g. MNR
use_cond	Use in conditions	char(1)	J/N this field indicates whether the acronym can be used as condition for the selection of events (J) or whether it can only be put as wildcard in the message text (N).
var_name	Detailed designation	char(30)	Detailed designation of the content of the acronym e.g.: machine number
verweis	DB reference	serial	DB reference

5.8. esk_function

Table name: esk_function		Product: KERNEL	
Designation: Function groups			
Column name	Column designation	Type	Description
functiondesc	Description of the function	char(40)	Description of the function (e.g. person in charge of the terminal) Designation of the group to which the respective person belongs (PDM field ID: ESKFKT.ESKFKT)
opt	Options	char(10)	ESKFKT.OPT:1 opt[1,1] Check whether logged on to the console in case it should be informed via the console; i.e. if = J the message is only sent if the user is logged on. (Therefore, it is important to state the console, which is normally operated by the user ("regular console"), in the HR master in order that a message can be sent even if the user is not logged on. ESKFKT.OPT:2 opt[2,2] Check if attendant according to PZE ESKFKT.OPT:3 opt[3,3] Check whether person is not on vacation - for future use - (PDM field ID: ESKFKT.OPT:x)
person_nr	Personnel number	char(10)	Reference to the HR master A connection to the employees and their data (e-mail, sms, pager, client number) is established via the personnel number. (PDM field ID: ESKFKT.PNR)
prio	Notification priority of the person	integer	The priority determines the sequence of the notification. Thus, the person(s) with highest priority (1) are informed at first. If these employees are not attendant or logged on the employee(s) with the next highest priority (2) are informed. By means of these priorities it is possible to determine representatives that are informed if the leading person in charge is not attendant. Thus, it is guaranteed that important messages are even processed if the respective person is absent (unscheduled). (PDM field ID: ESKFKT.PRIO)
verweis	DB reference	serial	Database reference

5.9. esk_setup

Table name: esk_setup		Product: KERNEL	
Designation: Basic settings			
Column name	Column designation	Type	Description
pager_path	Reference to path in HY_PATH	char(8)	Reference to path in HY_PATH (PDM field ID: HYDRA.PAGERPATH)
sms_path	Reference to path in HY_PATH	char(8)	Reference to path in HY_PATH (PDM field ID: HYDRA.MOBILTELPATH)
smtp_path	Reference to path in HY_PATH	char(8)	for future use (PDM field ID: HYDRA.SMTPPATH)
smtp_port	Port of the mail server	integer	0 = use default port (25) (PDM field ID: HYDRA.PORT:SMTP)
smtp_sender	Mail address of the System	char(255)	Mail address of the System (PDM field ID: HYDRA.SENDER:SMTP)
smtp_sendername	Mail name of the System	char(255)	Mail name of the System (PDM field ID: HYDRA.SENDERNAME:SMTP)
smtp_server	Host name for SMTP (mail dispatch)	char(255)	Host name or IP address of the SMTP server (mail dispatch) (PDM field ID: HYDRA.HOSTNAME:SMTP)
smtp_timeout	Timeout for mail dispatch	integer	0 = Default (100s) (PDM field ID: HYDRA.TMOUT:SMTP)

5.10. event_dlg_data

Table name: event_dlg_data		Product: KERNEL	
Archive table: a_event_dlg_data		Reload table: r_event_dlg_data	
Designation: Additional data on the event			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
datum		date	BDE comments: entry date HYDDI acronym (DAT) (PDM field ID: HYDDI (DAT))
dlg_data	Additional data	char(1000)	BDE comments: comment text HYDDI acronym (BEM) (PDM field ID: EREIGDATA.DATA; HYDDI(BEM))
ereignis		char(10)	Event (PDM field ID: EREIGDATA.EREIG)
ev_verweis	Reference of the event	integer	Reference of the event (PDM field ID: EREIGDATA.EREIGVERWEIS)
key1		char(40)	BDE comments: order/OP HYDDI acronym (ANR)
key2		char(40)	free
key_type		char(1)	Event class
masch_nr		char(20)	BDE comments: actual machine HYDDI acronym (MNR)
param01		integer	Dialog HY_BEM: shift number
param_d01		decimal(18,6)	Free parameter
param_str01		char(20)	Dialog HY_BEM: shift date
person_nr		char(10)	BDE comments: reporting person HYDDI acronym (PNR/KNR) (PDM field ID: HYDDI (PNR/KNR))
rueckgemeldet		char(1)	Confirmation indicator
status		char(1)	Stauts
verweis		serial	--- (PDM field ID: EREIGDATA.VERWEIS)
zeit		integer	BDE comments: entry date HYDDI acronym (ZEI) (PDM field ID: HYDDI (ZEI))

5.11. fkt_profil

Table name: fkt_profil		Product: KERNEL	
Designation: Function profiles		Description: Function profiles	
		This table is referenced by fkt_tab fkt_tab.art = 'P' fkt_tab.prg = fkt_profil.prg	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	
anlage_date	Date when the entry was created	date	
anlage_time	Time when the entry was created	integer	
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
berechtigung	Authorization level	smallint	(PDM field ID: FKTPROF.BERECHT)
prg	Program abbreviation	char(15)	(PDM field ID: FKTPROF.FKT)
profil	Profiles	char(15)	(PDM field ID: FKTPROF.FKTPROF)

5.12. fkt_tab

Table name: fkt_tab		Product: KERNEL	
Designation: Function authorizations		Description: Single function authorizations can be assigned to the user by means of this table. Thus, each employee has his/her personal authorization profile.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	
anlage_date	Date when the entry was created	date	
anlage_time	Time when the entry was created	integer	
art	Entry type	char(1)	P = Profile F = Function (PDM field ID: BEARBFKT.ART)
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
berechtigung	Authorization level	smallint	Authorization level (only shop floor scheduling module and editing of log data) (PDM field ID: BEARBFKT.BERECHT)
prg	Program abbreviation	char(15)	Program abbreviation (PDM field ID: BEARBFKT.FKT)
usr	User	char(10)	Reference to user_tab.usr (PDM field ID: BEARBFKT.BEARB)

5.13. hy_db_bench

Table name: hy_db_bench		Product: KERNEL	
Designation: Benchmarking (internal use only)		Description: Table for benchmarking	
		Notes: Reserved for setup-department from MPDV	
		The structure of the table depends on the version of the benchmark and is created dynamically.	
Column name	Column designation	Type	Description

5.14. hy_dd_prot

Table name: hy_dd_prot		Product: KERNEL	
Designation: Dialog - error log			
Column name	Column designation	Type	Description
auftrag_nr	Order + operation	char(40)	Order + operation
bearb	Editor	char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
chargen_nr	Batch number	char(20)	Batch number
datum	Logging date	date	Logging date
dd_bearb	Editor	char(10)	Created by (PDM field ID: ERRPRO.BEARB)
dd_datum	Entry date	date	Entry date (PDM field ID: ERRPRO.DAT)
dd_zeit	Entry time	integer	Entry time (PDM field ID: ERRPRO.ZEI)
dialog	Dialog	char(40)	Dialog ID (DLG=...) (PDM field ID: ERRPRO.DLG)
dlg_data	Dialog data string	char(4000)	Dialog data string (DLG=..... ...) (PDM field ID: ERRPRO.DLGDATA)
ereignis	Event	char(40)	Triggered event (PDM field ID: ERRPRO.EREIG)
err_bez	Error description	char(80)	Error description (PDM field ID: ERRPRO.LT)
err_class	Error class	char(10)	Error class: SYS, HYD, ADE, MDE, PZE, ... (PDM field ID: ERRPRO.ERRCLASS)
err_code	Error code	integer	Text must be dissolved by client. RET > 0: error with text from message.msg RET < 0: SQL error (PDM field ID: ERRPRO.ERRCODE)
hyuser	User (e.g. terminal)	smallint	User number: - 1001-1999: console with console numbers 1-999 - 2001-2999: terminal with terminal numbers 0-999 (PDM field ID: ERRPRO.USR)
karten_nr	Badge number	char(10)	Badge number
kommentar	Description of the action	char(80)	Description of the action (PDM field ID: ERRPRO.BEM)
masch_nr	Machine	char(20)	Machine
mgruppe	Machine group	char(20)	Machine group
param_01	(free)	integer	free
person_nr	Personnel number	char(10)	Personnel number
reaktion	Number for solution rule	integer	Reaction key (a code is defined how to solve the problem). A reaction key X is defined in the logon if, for example, a clocking-in is missing in the PZE program. If a reaction key is defined the console shows a plaintext for X in the list (e.g. create clocking-in for person) and activates a button for the editing function. This button executes the function defined for X: e.g. starts a dialog box (e.g. edit PZE clockings), transfers parameters (e.g. personnel number and day).
res_nr	Resource number	char(40)	Resource number

status	Status of the message	char(1)	Status of the message as traffic light: I - Info (blue) W - Warning (yellow) E - Error (red) (PDM field ID: ERRPRO.STA)
verweis	Distinct reference	serial	Distinct reference
zeit	Logging time	integer	Logging time

5.15. hy_path

Table name: hy_path		Product: KERNEL	
Designation: Paths			
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
bem	Comment	char(100)	(PDM field ID: PATH.BEM)
p_host	Host	char(80)	Name of the server or its IP address (PDM field ID: PATH.HOST)
p_password	Password	char(20)	(PDM field ID: PATH.PWD)
p_port	Port	integer	Number of the communication port (PDM field ID: PATH.PORT)
p_scheme	Schema	char(10)	Possible values are: file: Network access to files using UNC file names (= Windows shares) ftp: Access via file transfer log to the FTP server hydra: HYDRA file transfer to the server http: Support of http-Links to view web contents (PDM field ID: PATH.SCHEME)
p_url_path	URL Path	char(255)	Directory of data storage in URL notation without indication of the server (host) (PDM field ID: PATH.URLPATH)
p_user	User name	char(20)	(PDM field ID: PATH.USR)
param_str_01	for future use	char(10)	(PDM field ID: PARAM:1)
param_str_02	for future use	char(20)	(PDM field ID: PARAM:2)
param_str_03	for future use	char(30)	(PDM field ID: PARAM:3)
path	Path	char(8)	Identifies the storage space (PDM field ID: PATH.PATH)

5.16. hy_protokoll

Table name: hy_protokoll		Product: KERNEL	
Designation: System logs			
Column name	Column designation	Type	Description
anwendung	Application	char(10)	Name of the application
anzahl_ds	Number of data records	integer	Total number of data records (PDM field ID: SYSPRO.ANZDAT)
anzahl_fehler	Number of incorrect data records	integer	Number of incorrect data records (PDM field ID: SYSPRO.ANZERR)
bezeichnung	Short description	char(50)	Short description of the application
d_datei_groesse	Size of the data file	integer	Size of the data file in bytes (PDM field ID: SYSPRO.DATSIZE)
d_datei_name	Name of the data file	char(12)	Name of the data file in the directory ./prot (if available) (PDM field ID: SYSPRO.DATFILE)
datum	Entry date	date	Entry date (PDM field ID: SYSPRO.DAT)
f_datei_groesse	Size of the error file	integer	Size of the error file in bytes (PDM field ID: SYSPRO.ERRSIZE)
f_datei_name	Name of the error file	char(12)	Name of the error file in the directory ./prot (if available) (PDM field ID: SYSPRO.ERRFILE)
meldung	Message	char(100)	Message/status text (optional) (PDM field ID: SYSPRO.BEM)
p_datei_groesse	Size of the log file	integer	Size of the log file in bytes (PDM field ID: SYSPRO.PROSIZE)
p_datei_name	Name of the log file	char(12)	Name of the log file in the directory ./prot (if available) (PDM field ID: SYSPRO.PROFILE)
prg	Program name	char(12)	Program name without file extension
prg_datum	Version date	date	Date of the program version
prg_version	Program version	char(10)	Version number
status	Status	char(3)	"-": no status OK: no errors occurred F: one or several errors occurred ->check files (PDM field ID: SYSPRO.STA)
verweis		serial	
x1	reserved	char(20)	reserved
x2	reserved	char(20)	reserved
x3	reserved	integer	reserved
x4	Administration reference with SAP logs	integer	Administration reference with SAP logs
x5	reserved	date	reserved
x6	reserved	date	reserved
x7	reserved	char(1)	reserved
x8	reserved	char(1)	reserved
x9	reserved	char(1)	reserved
zeit	Entry time	integer	Entry time (PDM field ID: SYSPRO.ZEI)

5.17. hy_size_stats

Table name: hy_size_stats		Product: KERNEL	
Designation: Size statistics		Description: Size statistics about tablespaces and hard disks	
Column name	Column designation	Type	Description
belegt	Actual size of the tablespace or hard disk	decimal(18,6)	
datum	Entry date	date	
groesse	Maximum size of the tablespace or hard disk	decimal(18,6)	
name	Tablespace name	char(30)	
typ	Type	char(1)	Supported identifiers T: tablespace D: hard disk
zeit	Entry time	integer	

5.18. hybuch

Table name: hybuch		Product: KERNEL	
Designation: Posting of events		Description: Objective: Basic data for the generation of log records (ADE/MDE) for batches (replaces masch_charge) are kept in this table. Batches: All batches assigned to an order and a machine are filed in this table. In this table the respective entry only exists as long as the batch is logged on. The data fields are allocated as given within the batch status; however, they contain the numbers of pieces and times since the current logon. Description: The table is described in the documentation of ADE and MDE tables.	
Column name	Column designation	Type	Description
a_status		char(5)	
anmeld_dat		date	Logon date
anmeld_zeit		integer	Logon time
artikel		char(40)	Article for the OP or material Only assigned in case of key_type "C" (Batch)
auftrag_art		char(5)	Order type of the OP Only assigned in case of key_type "P" and "A" - but not for entries of waiting periods
aus_bas		decimal(18,6)	Scrap in base quantity unit (PDM field ID: EGR:AUSB)
aus_grund		integer	Scrap reason Corresponds to ade_grund_zuord.grund The indicator of the reason has to be in line with the quantity indicator: for example, if EGR:AUS is recorded the reason has to be recorded with EGG:AUS, analogously EGG:AUSP for EGR:AUSP, etc. (PDM field ID: EGG:AUS(B/P/S/T))
aus_grund_text		integer	Reason text number for scrap reason Corresponds to ade_grund_zuord.grundtext_nr
aus_pri		decimal(18,6)	Scrap in primary quantity unit Corresponds to scrap from 7.1 (PDM field ID: EGR:AUSP oder EGR:AUS)
aus_sek		decimal(18,6)	Scrap in secondary quantity unit (PDM field ID: EGR:AUSS)
aus_ter		decimal(18,6)	Scrap in tertiary quantity unit (PDM field ID: EGR:AUST)
auto_aus_bas		decimal(18,6)	
auto_aus_pri		decimal(18,6)	
auto_aus_sek		decimal(18,6)	
auto_aus_ter		decimal(18,6)	
auto_gut_bas		decimal(18,6)	
auto_gut_pri		decimal(18,6)	
auto_gut_sek		decimal(18,6)	
auto_gut_ter		decimal(18,6)	
auto_hub_gesamt		decimal(18,6)	
auto_hub_gut		decimal(18,6)	
auto_nacharb_bas		decimal(18,6)	
auto_nacharb_pri		decimal(18,6)	

auto_nacharb_sek		decimal(18,6)	
auto_nacharb_ter		decimal(18,6)	
auto_problem_bas		decimal(18,6)	
auto_problem_pri		decimal(18,6)	
auto_problem_sek		decimal(18,6)	
auto_problem_ter		decimal(18,6)	
bedarfmenge		decimal(18,6)	MPL: theoretical requirements for input batches
bmk_01		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK01)
bmk_02		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK02)
bmk_03		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK03)
bmk_04		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK04)
bmk_05		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK05)
bmk_06		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK06)
bmk_07		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK07)
bmk_08		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK08)
bmk_09		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK09)
bmk_10		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK10)
bmk_11		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK11)
bmk_12		integer	Contains the duration of the machine status compared with the shift calendar (PDM field ID: EGR:BMK12)
bmk_nr		smallint	Current RPA (resource performance account)
bpos		char(10)	Operator position
buch_dat		date	Currently not assigned
buch_zeit		integer	Currently not assigned
calc_bmk_01		integer	Calculated account for RPA - this value is taken over in the Operation-related result record Recorded RPA values are transferred from dialog to hybuch -> auftrag_status -> ade_protokoll and event_xxx. The input type at the activity code defines how this is done: · "ZE" is default for times and means that the times are calculated; these entries have not to be available! · "DR"/"DA" discrete collection (as in case of quantities), relative (accumulated) or absolute · "XU"/"XE" calculated according to formula
calc_bmk_02		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_03		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_04		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_05		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_06		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_07		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_08		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_09		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_10		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_bmk_11		integer	Calculated account for RPA - this value is taken over in the Operation-related result record

calc_bmk_12		integer	Calculated account for RPA - this value is taken over in the Operation-related result record
calc_dauer		integer	Calculated account for the duration - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the duration can be defined in the activity code
calc_p_dauer_bmk01		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk02		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk03		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk04		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk05		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk06		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk07		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk08		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk09		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk10		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk11		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_p_dauer_bmk12		integer	Calculated account for the ratio RPA posting for persons - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the ratio RPA posting can be defined in the activity code
calc_pers_dauer		integer	Calculated account for the labor utilization - this value is taken over in the Operation-related result record Analogously to the cal_bmk_..accounts, the determination of the labor utilization can be defined in the activity code
dauer		integer	Sum of the RPAs 1 ... 11 (PDM field ID: EGR:DAUER)
einsatzmenge		decimal(18,6)	Input quantity for input batches
erfass_dat		date	Currently not assigned
erfass_zeit		integer	Currently not assigned
gut_bas		decimal(18,6)	Yield in base quantity unit (PDM field ID: EGR:GUTB)
gut_grund		integer	Reason for yield, e.g. a deviation reason for overdelivery Corresponds to ade_grund_zuord.grund The indicator of the reason has to be in line with the quantity indicator: for example, if EGR:GUT is recorded the reason has to be recorded with EGG:GUT, analogously EGG:GUTP for EGR:GUTP, etc. (PDM field ID: EGG:GUT(B/P/S/T))

gut_grund_text		integer	Reason text number for yield, e.g. a deviation reason for overdelivery Corresponds to ade_grund_zuord.grundtext_nr
gut_pri		decimal(18,6)	Yield in primary quantity unit Corresponds to the yield from 7.1 (PDM field ID: EGR:GUTP oder EGR:GUT)
gut_sek		decimal(18,6)	Yield in secondary quantity unit (PDM field ID: EGR:GUTS)
gut_ter		decimal(18,6)	Yield in tertiary quantity unit (PDM field ID: EGR:GUTT)
hub_gesamt		decimal(18,6)	Total number of strokes (PDM field ID: GGR:HUB oder EGR:HUB)
hub_gut		decimal(18,6)	Reserved for "number of strokes, good parts only" (PDM field ID: EGR:HUBG)
hyuser		integer	Number of the user on which the logon took place.
is_aktiv	active	char(1)	J = active OP at processing center (PDM field ID: AKTIV)
is_vordatiert		char(1)	J = logon has been dated forward (by waiting period)
ist_lst_01		decimal(18,6)	Activities that can be recorded - 10 at most The activity code at the OP (auftrags_bestand.lst_code) defines how an activity is determined or recorded. (PDM field ID: EGR:LST01)
ist_lst_02		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST02)
ist_lst_03		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST03)
ist_lst_04		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST04)
ist_lst_05		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST05)
ist_lst_06		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST06)
ist_lst_07		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST07)
ist_lst_08		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST08)
ist_lst_09		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST09)
ist_lst_10		decimal(18,6)	Activities that can be recorded - 10 at most (PDM field ID: EGR:LST10)
karenz		char(1)	"P" = Waiting period of personnel "M" = Waiting period record of machines otherwise empty
karenz_zeit		integer	Waiting period
key_type		char(2)	Posting table for: M : Machine A : Order - machine C : Batch - order - machine P : Person - order - machine O: Resource Constants from hyincl.h have to be used!
kostenstelle		char(10)	Reserved for cost center (of the machine or the cost center to be charged)
lfd_nr		integer	Reference to an entry that is possibly available in event_dlg_data and that was recorded when creating a book entry.

lpkz		char(10)	Wage/premium indicator
lst_einh_01		char(3)	Unit of the activity (PDM field ID: EGE:LST01)
lst_einh_02		char(3)	Unit of the activity (PDM field ID: EGE:LST02)
lst_einh_03		char(3)	Unit of the activity (PDM field ID: EGE:LST03)
lst_einh_04		char(3)	Unit of the activity (PDM field ID: EGE:LST04)
lst_einh_05		char(3)	Unit of the activity (PDM field ID: EGE:LST05)
lst_einh_06		char(3)	Unit of the activity (PDM field ID: EGE:LST06)
lst_einh_07		char(3)	Unit of the activity (PDM field ID: EGE:LST07)
lst_einh_08		char(3)	Unit of the activity (PDM field ID: EGE:LST08)
lst_einh_09		char(3)	Unit of the activity (PDM field ID: EGE:LST09)
lst_einh_10		char(3)	Unit of the activity (PDM field ID: EGE:LST10)
m_status		smallint	Machine status at the time of the last logon.
meinheit_bas		char(3)	Base quantity unit
meinheit_pri		char(3)	Primary quantity unit
meinheit_sek		char(3)	Secondary quantity unit
meinheit_ter		char(3)	Tertiary quantity unit
nacharb_bas		decimal(18,6)	Rework in base quantity unit (PDM field ID: EGR:NCHB)
nacharb_grund		integer	Rework reason Corresponds to ade_grund_zuord.grund The indicator of the reason has to be in line with the quantity indicator: Analoguous EGG:NCHP for EGR:NCHP, etc. (PDM field ID: EGG:NCH(B/P/S/T))
nacharb_grund_text		integer	Reason text number for rework reason Corresponds to ade_grund_zuord.grundtext_nr
nacharb_pri		decimal(18,6)	Rework in primary quantity unit Corresponds to length of data collection account from 7.1 (PDM field ID: EGR:NCHP oder ERG:LEN)
nacharb_sek		decimal(18,6)	Rework in secondary quantity unit (PDM field ID: EGR:NCHS)
nacharb_ter		decimal(18,6)	Rework in tertiary quantity unit (PDM field ID: EGR:NCHT)
p_bmk_nr		smallint	
p_bmk_prot_dat		date	Point in time of the last calculation of the proportional RPA of personnel
p_bmk_prot_zeit		integer	Date of the last calculation of the proportional RPA of personnel
p_dauer_bmk01		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteil = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK01)

p_dauer_bmk02		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK02)
p_dauer_bmk03		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK03)
p_dauer_bmk04		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK03)
p_dauer_bmk05		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK05)
p_dauer_bmk06		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK05)
p_dauer_bmk07		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK0)
p_dauer_bmk08		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK0)
p_dauer_bmk09		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK0))
p_dauer_bmk10		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteilig = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk.. (PDM field ID: EGR:PBMK!=)

p_dauer_bmk11		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteil = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk_... (PDM field ID: EGR:PBK11)
p_dauer_bmk12		integer	The ratio RPA posting for persons is only active if setup.pdauer_anteil = "J" In this case the proportional duration (compared with the shift calendar of the machine or person) is saved in these accounts - relating to the respective RPA If no RPA posting is active then p_dauer_bmk.. = bmk_... (PDM field ID: EGR:PBK12)
p_divisor		decimal(18,6)	Divisor (from MDE collection)
p_teiligkeit		decimal(18,6)	Partitioning (from MDE collection)
param_01		integer	Remaining duration in seconds in case of ratio BMK posting at the processing center or in case of parallel OPs at the machine Field is set to 0 at the change of shifts
param_02		integer	Reserved/free for customer-specific data
param_03		decimal(18,6)	MPL: Input quantity for input batches Reserved/free for customer-specific data
param_04		integer	Remaining labor time in seconds when posting the labor utilization Field is set to 0 at the change of shifts
param_05		integer	MPLRF: number of individual batches in case of collective batch (output batches when cutting rolls) total number of generated output batches in case of input batch (mother roll)
param_str1		char(40)	Reserved/free for customer-specific data
param_str2	Material	char(40)	MPL: Article number
param_str3	BOM item	char(10)	-MPL: in case of an input batch the bill of material item (BOM item) is concerned
param_str4		char(10)	MPL: [1,1] = the material indicator for input batches (e.g. "T" for carrier material) HYD-AEV: different indicators for logons of staff (key_type = 'P') [1,1] : Enable quantity posting for person J/N [2,2] : Enable continuous posting for person J/N [3,3] : Enable counting as actual person for person J/N
pers_dauer		integer	Labor utilization compared with the shift calendar. This one is proportionate if the employee has logged on several times By default the duration is compared with the shift calendar of the machine - if setup.p_pers_zeiten = "J" is active it is compared with the person's personal shift model (personalstamm.stamm_j_mod) Breaks within the shift calendar are not posted to the labor utilization By default all RPAs are posted to the labor utilization - if setup.pdauer_bmk_verb[1,1] = J is set only statuses with the configured RPAs are posted to the labor utilization By means of this, a break that is logged on (status with RPA 12), for example, can be hidden in the labor utilization. (PDM field ID: EGR:PDAUER)
pers_prot_dat		date	Date of last calculation of labor time
pers_prot_zeit		integer	Time of last calculation of labor time
prgrp		char(10)	LLE premium group for OP and person
problem_bas		decimal(18,6)	Problem quantity in base quantity unit (PDM field ID: EGR:PRBB)
problem_grund		integer	Problem reason Corresponds to ade_grund_zuord.grund The indicator of the reason has to be in line with the quantity indicator: EGG:AUSP for EGR:AUSP, etc. (PDM field ID: EGG:PRB(B/P/S/T))
problem_grund_text		integer	Reason text number for problem reason Corresponds to ade_grund_zuord.grundtext_nr

problem_pri		decimal(18,6)	Problem quantity in primary quantity unit (PDM field ID: EGR:PRBP)
problem_sek		decimal(18,6)	Problem quantity in secondary quantity unit (PDM field ID: EGR:PRBS)
problem_ter		decimal(18,6)	Problem quantity in tertiary quantity unit (PDM field ID: EGR:PRBT)
prot_dat		date	Date of last logging.
prot_zeit		integer	Time of last logging
ref_ag		char(40)	Reserved for reference OP MPLRF: Mother OP
rest_bmk_01		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK01)
rest_bmk_02		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK02)
rest_bmk_03		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK03)
rest_bmk_04		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK04)
rest_bmk_05		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK05)
rest_bmk_06		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK06)
rest_bmk_07		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK07)
rest_bmk_08		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK08)

rest_bmk_09		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK09)
rest_bmk_10		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK10)
rest_bmk_11		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK11)
rest_bmk_12		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0 (PDM field ID: RGR:BMK11)
rest_dauer		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how the remaining duration is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If determined remaining size is < 0 the remaining size is set = 0
rest_lst_01		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining activity is determined By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc. accounts in the Auftrag_Status) is calculated except for the case that the REMAINING size (RGR:...) is stated then the value of the remaining size is logged. If the determined remaining size < 0 then the remaining size is set = 0 (PDM field ID: RGR:LST01)
rest_lst_02		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST02)
rest_lst_03		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST03)
rest_lst_04		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST04)
rest_lst_05		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST05)
rest_lst_06		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST06)
rest_lst_07		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST07)
rest_lst_08		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST08)
rest_lst_09		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST09)
rest_lst_10		decimal(18,6)	Recorded or calculated remaining activity - 10 remaining activities at most (PDM field ID: RGR:LST10)
rest_p_dauer		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how the remaining labor utilization is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged

rest_p_dauer_bmk01		integer	The activity code at the OP (auftrags_bestand.lst_code) defines how a remaining personnel RPA is determined: By default the difference between TARGET (auftrags_leistung) and ACTUAL (calc accounts in the order status) is calculated except for the case that REMAINING size (RGR:...) is stated then the value of the remaining size is logged If the determined remaining size < 0 the remaining size is set = 0 (PDM field ID: RGR:PBMK01)
rest_p_dauer_bmk02		integer	--- (PDM field ID: RGR:PBMK02)
rest_p_dauer_bmk03		integer	--- (PDM field ID: RGR:PBMK03)
rest_p_dauer_bmk04		integer	--- (PDM field ID: RGR:PBMK04)
rest_p_dauer_bmk05		integer	--- (PDM field ID: RGR:PBMK05)
rest_p_dauer_bmk06		integer	--- (PDM field ID: RGR:PBMK06)
rest_p_dauer_bmk07		integer	--- (PDM field ID: RGR:PBMK07)
rest_p_dauer_bmk08		integer	--- (PDM field ID: RGR:PBMK08)
rest_p_dauer_bmk09		integer	--- (PDM field ID: RGR:PBMK09)
rest_p_dauer_bmk10		integer	--- (PDM field ID: RGR:PBMK10)
rest_p_dauer_bmk11		integer	--- (PDM field ID: RGR:PBMK11)
rest_p_dauer_bmk12		integer	--- (PDM field ID: RGR:PBMK12)
satz_art		char(1)	Record type/dialog by which the data record was generated "A" = log OP on (A_AN) "P" = combined logon (A_P_AN) "N" = logon of staff (P_AN) "J" = logon of COP person "M" = logon of COP machine
schichtanf		integer	Beginning of shift
schichtart		char(1)	Shift type from the shift model
schichtend		integer	End of shift
schichtmodell		smallint	Shift model (day type) of the current shift
schichtnr		smallint	Shift number
schichtpause		smallint	Shift break
sortierung		smallint	OP numbering when all OPs have the same logon date/time after the change of shifts (key_type = A)
status1		char(1)	L : running F : interrupted automatically
status2		char(2)	K : generated by PZE clocking-in G : generated by PZE clocking-out
status3		char(1)	Reserved/free for customer-specific data
subkey1		char(20)	Machine number
subkey2		char(40)	Order and OP number
subkey3		char(20)	Batch number
subkey4		char(10)	Personnel number
subkey5		char(10)	- Standard Machine/OP/batch: free Output batch: cut number (coil-base manufacturing) Input batch: bill of material item Person: personnel group

subkey6		integer	Ressource ID for key_type = 'O'
sum_laufzeit		decimal(18,6)	Package logons: sum of the target run time of all OPs contained in the package
sum_perszeit		decimal(18,6)	Reserved for the sum of labor utilization at proportionate calculation
typ		char(1)	For batches (key_type = 'C') : E = Input batch A = Output batch for OPs and persons (key_type = 'A' or 'P') : P = logon in package or en bloc
verbuchung		char(1)	Reserved for order-related RPA posting (ade_status_zuord.verbuchung) : OP-related posting to RPA of OP (person/batch/resource like OP) When changing the status the RPA is only changed for the OPs/persons/batches/resources that have hybuch.verbuchen != "A"
verbuchung_auto_menge		char(1)	
verbuchung_pdauer		char(1)	

5.19. hybuch_zusatz

Table name: hybuch_zusatz		Product: KERNEL	
Designation: Posting of events (additions)		Description: Objective: In this table all entry values (RPA, strokes, yield, scrap) are logged for batches via the time how long the batch is logged on to the machine or the shift time of the machine. Description: The table is described in the documentation of ADE and MDE tables.	
Column name	Column designation	Type	Description
auftrag_art		char(5)	Order type of the OP
einheit		char(3)	Unit
erfass_art		char(2)	In 7.2 only: PR : Premium specifications LLE (TE, TR, TEB, TRB) for persons and OPs (key_type = "A" and "P") P : Data collection accounts since the OP is logged on (GUT, AUS and DAUER) for OP only (key_type = "A") => these data collection accounts are NOT initialized when changing shifts. Z : Time accounts with Type RPBMK = Remaining duration in seconds in case of proportionate RPA posting of RPAs of persons Type RPDauer = Remaining duration in seconds in case of labor time posting depending on RPA for persons only (key_type = 'P') => all of these data collection accounts are initialized when changing shifts All other quantity and time accounts are now directly in hybuch
grund		char(10)	Reason for the collection size
karenz		char(1)	"P" = waiting period record of personnel "M" = waiting period record of machines otherwise empty
key_type		char(2)	Details on the posting table hybuch for: M : Machine A : Order - machine C : Batch - order - machine P : Person - order - machine O: Resource ... Constants from hyincl.h have to be used!
param_01		integer	free
param_str1		char(20)	If TYP = "TE" the wage type is filed here
param_str2		char(40)	- for future use -
subkey1		char(20)	Machine number
subkey2		char(40)	Order and OP number
subkey3		char(20)	Batch number
subkey4		char(10)	Personnel number
subkey5		char(10)	Standard: free
subkey6		integer	Resource ID if key_type = 'O'
typ		char(10)	Type of the collection size TE, TR, ... Type RPBMK = Remaining duration in seconds in case of proportionate RPA posting of RPAs of persons Type RPDauer = Remaining duration in seconds in case of labor time posting depending on RPA for persons only (key_type = 'P')

typ_hybuch		char(1)	1:1 of the content from hybuch.typ : For batches (key_type = 'C') : E = Input size A = Output size For OPs and persons (key_type = 'A' or 'P') : P = Package logon or logon en bloc
wert		decimal(18,6)	Recorded value

5.20. hyd_datamanagement

Table name: hyd_datamanagement		Product: KERNEL	
Designation: Data management			
Column name	Column designation	Type	Description
action	Action	char(1)	It is possible to choose from three variants for one object: D = delete object is deleted M = move (archive) object is transferred to the next area X = export object is unloaded (XUNLOAD format) then deleted (PDM field ID: DATAMGT.AKTION)
add_condition	Condition	char(1464)	Additional conditions (WHERE clause) (PDM field ID: DATAMGT.RESTRIKTION)
aktiv	Active	char(1)	Control indicator saying whether the configuration is active or inactive. Possible values J/N.
arc_mode	Archiving step	char(1)	Specifies whether this archiving executes the archiving function I or II. Archiving function I moves data from the online dataset to archive tables or deletes them: Setting M (medium-term archive). Archiving function II transfers data from archive tables to the file export or deletes them: Setting L (long-term archive)
arc_path	Path	char(8)	Optional path for the generation of the file export (unload)
arc_type	Archiving type	char(1)	Flag for archiving based on time or objects. Supported modes are: O = archiving based on objects (i.e. data are archived separately for each object) Z = archiving based on time (i.e. data are archived together without reference to the object)
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
date_column	Date column	char(30)	
destination	Target object	char(20)	for future use (PDM field ID: DATAMGT.ZOBJTYP)
keepingdate	Last retention date	date	This field is computed and indicates the last day on which data is still available in this object (PDM field ID: DATAMGT.LVERWDAT)
keepingperiod	Retention period	integer	The retention period field define how long data is available until it is archived (PDM field ID: DATAMGT.VERWDAUER)
keepingperiod_unit	Retention period unit	char(1)	The unit for retention periods is indicated in days, months or years (PDM field ID: DATAMGT.VERWDAUEREINH)
key_1	Key 1	char(40)	Unique key column within the master table by way of which the data to be archived can be identified. Up to 5 key columns can be defined with object-based archiving. Time-related archiving only supports one primary key in key 1.
key_2	Key 2	char(40)	Further possible key columns for object-based archiving
key_3	Key 3	char(40)	Further possible key columns for object-based archiving
key_4	Key 4	char(40)	Further possible key columns for object-based archiving
key_5	Key 5	char(40)	Further possible key columns for object-based archiving
kommentar	Commentary	char(255)	
last_run_date	Date of last run	date	
last_run_time	Time of last run	integer	
master_table	Master table	char(30)	Table including archiving data. The enhancements entered in the "condition" field refer to this table

object	Object	char(20)	The object defines which kind of data is to be provided (PDM field ID: DATAMGT.OBJTYP)
priority	Priority	integer	
product	Product	char(10)	The product, for which a rule is to be defined e.g.: BDE, MDE, MPL (PDM field ID: DATAMGT.PROD)
productkey	License	char(80)	
ue_params	for future use	char(40)	
verw_keepingperiod	Administration retention period	integer	Internal use
verw_keepingperiod_unit	Administration retention period unit	char(1)	Internal use
verw_table	Administration table	char(30)	Internal use
verweis	DB reference	serial	

5.21. hyd_einheiten

Table name: hyd_einheiten		Product: KERNEL	
Designation: Table for units			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bezeichnung	Designation	char(20)	E.g. Kilogram (PDM field ID: EINH.EINHBEZ)
einheit	Unit	char(3)	E.g. KG (PDM field ID: EINH.EINH)
einheit_iso	Unit ISO	char(3)	if deviating (PDM field ID: EINH.EINHISO)
si_einheit	SI unit	char(1)	J/; there can be 1 SI unit at most within one type (TYP). But there can also be types without SI unit. (PDM field ID: EINH.OPT:SI)
typ	Classification	char(10)	Classification: Area Weight Length Piece Temperature Volume (PDM field ID: EINH.TYP)

5.22. hyd_einheiten_umr

Table name: hyd_einheiten_umr		Product: KERNEL	
Designation: Unit conversion			
Column name	Column designation	Type	Description
autom_angelegt	Automatically created entry	char(1)	J=Conversion has been created automatically for backwards conversion: e.g. when the conversion from CM into M is created, the conversion from M into CM is automatically created along with it.
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
einheit_expr	Formula	char(6)	Alternative to NENNER,ZAEHLER,EXPONENT,OFFSET: It is the formula within the "quantity conversion" context --> Reference to table of formulas When it comes to unit conversion the value to be converted is defined within variable "X" (e.g. X+30/100). (PDM field ID: EINHUMR.EXPR:EINH)
exponent	Exponent	smallint	Exponent (required for very large or very small figures) (default 0) (PDM field ID: EINHUMR.EXP)
hz_typ	Material type	char(10)	Material type, may also be empty; HZ_TYPEN table is checked (also for COPY). (PDM field ID: EINHUMR.MATTYP)
material	Material	char(40)	Material, may also be empty (PDM field ID: EINHUMR.MAT)
nenner	Denominator	integer	Mandatory! = 0 (default 1) (PDM field ID: EINHUMR.UMRFAKT:N)
offset	Additive constant	float	Additive constant (is required for the conversion of temperatures) (default 0). (PDM field ID: EINHUMR.OFFSET)
op_code	Operation code	char(10)	Operation code, may also be empty for future use: An "operation code" may be defined for the OP. If this code is indicated it can be referenced to this unit conversion table. Example: 2 OPs; both are converted from LFM to KG but they have different density. Within the OP_CODE there is "Varnishing" and "Coating". Now there are two entries in this table referring to different formulas. The formula itself includes the density. Please note: In case the density is written in a user field of the OP, then 1 formula is sufficient, i.e. no OP_CODE is required. However, in this case the formula must be 100% identical and density must always be indicated in the same user field. (PDM field ID: EINHUMR.OPCODE)
rundung	Rounding	char(1)	Options: "N": Do not round "U": Round up "T": Round down "R": Arithmetic rounding (PDM field ID: EINHUMR.RUND:MOD)
stelligkeit	Decimal places	smallint	Rounding to decimal places (how many) (PDM field ID: EINHUMR.RUND:NKS)
von_einheit	Checking of HYD_EINHEITEN	char(3)	Mandatory field; checking of HYD_EINHEITEN (PDM field ID: EINHUMR.EINH:V)
zaehler	Counter	integer	Mandatory ! = 0 (default 1) (PDM field ID: EINHUMR.UMRFAKT:Z)
zu_einheit	Checking of HYD_EINHEITEN	char(3)	Mandatory field; checking of HYD_EINHEITEN (PDM field ID: EINHUMR.EINH:N)

5.23. hyd_expr

Table name: hyd_expr		Product: KERNEL	
Designation: Formula management			
Column name	Column designation	Type	Description
art	Type	smallint	Only for logical differentiation purposes (no processing, no key) --> Definition of the text in REFLISTE.DAT, e.g. 1 "Quantity conversion" 2 "Determination of process time" 7 "Formulas for Composition Restrictions" 8 "Formulas for Composition Scrap portion" 50 "MLE Formulas and Conditions" 999 "user-defined" (PDM field ID: EXPR.ART)
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
bemerkung	Comment	char(255)	Comment for the formula, at least 100 characters (PDM field ID: EXPR.BEM)
editierbar	editable	char(1)	This value is set for the formulas supplied by MPDV; Formulas having EDITABLE = N may only be displayed at the console but not changed or deleted. (PDM field ID: EXPR.OPT:EDIT)
expr	Formula key	char(6)	Formula key; Unique within the context, e.g. 0001 (PDM field ID: EXPR.EXPR)
formel	Formula	char(255)	The actual formula; please also see subdirectory "formula definition". (PDM field ID: EXPR.EXPRTXT)
mod	Mod	char(1)	F=Formula U=Userexit; i.e. the value contained in FORMEL is a file name referring to a userexit. (for further use, actual only "F" is possible) (PDM field ID: EXPR.MOD)
verantw_bereich	Responsibility area	char(15)	Responsibility area (PDM field ID: EXPR.VAB)

5.24. hyd_history

Table name: hyd_history		Product: KERNEL	
Designation: Administration of history archives			
Column name	Column designation	Type	Description
aktiv	Activation	char(1)	Previous, old definition char(1) [1,1] J = history active for this table: Run history for all programs N = history inactive for this table Compatible, new definition char(10) [1,1] J = history active for this table N = history inactive for this table [2,2] Run history for other programs: J = Yes E = Yes + extended (see below) N = No [3,3] Run history for modules "*.cft" via hyaccman (TBK console): J = Yes E = Yes + extended (see below) N = No [4,4] Run history for modules "hybapi": J = Yes E = Yes +extended (se below) N = No [5,5] Run history for modules "hyddi" J = Yes E = Yes + extended (se below) N = No [6,10] free In the extended mode (E) the previous and the changed data record are saved in case of an update. In the normal mode (J) the changed data record is only saved in case of an update - as it has so far been the case.
gueltig	Period of validity	integer	Period of validity
histname	Table name for the history	char(32)	Table name for the history
tabname	Table name	char(32)	Table name

5.25. hyd_ini

Table name: hyd_ini		Product: KERNEL	
Designation: Saving ini configuration settings			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing date
bearb_time		integer	Last editing time
bemerkung	Commentary	char(80)	--- (PDM field ID: INI.BEM)
hydrauser	User	smallint	--- (PDM field ID: INI.USR)
ininame	Name	char(80)	File name of the ini file (PDM field ID: INI.INI)
param_01		integer	---
param_02		integer	---
param_str01	Responsibility area	char(20)	Responsibility area (PDM field ID: INI.VAB)
param_str02		char(20)	---
param_str03		char(40)	---
pdouble_01		decimal(18,6)	---
pdouble_02		decimal(18,6)	---
typ		char(10)	--- (PDM field ID: INI.TYP)
verweis	Reference	serial	Is used for referencing by INIDATA (PDM field ID: INI.VERWEIS)

5.26. hyd_ini_data

Table name: hyd_ini_data		Product: KERNEL	
Designation: Saving ini configuration settings			
Column name	Column designation	Type	Description
aktiv	Active	char(1)	(J/N) (PDM field ID: INIDATA.AKTIV)
bemerkung	Commentary	char(80)	--- (PDM field ID: INIDATA.BEM)
ident	Ident	char(80)	Corresponding to an ini file (PDM field ID: INIDATA.KEY)
ini_verweis	Link to INI.VERWEIS	integer	Reference to table hyd-ini (PDM field ID: INIDATA.INIVERWEIS)
param_01		integer	---
param_02		integer	---
param_str01		char(20)	--- (PDM field ID: INIDATA.PARAM:1)
param_str02		char(20)	--- (PDM field ID: INIDATA.PARAM:2)
param_str03		char(40)	--- (PDM field ID: INIDATA.PARAM:3)
pdouble_01		decimal(18,6)	---
pdouble_02		decimal(18,6)	---
section	Section	char(80)	Corresponding to an ini file (PDM field ID: INIDATA.SECTION)
typ		char(10)	(String/Dword) Standard : String (PDM field ID: INIDATA.TYP)
value	value	char(128)	Corresponding to an ini file (PDM field ID: INIDATA.VAL)
version	Version	integer	--- (PDM field ID: INIDATA.VER)
verweis	Reference	serial	Currently not used (PDM field ID: INI.VERWEIS)

5.27. hyd_license_status

Table name: hyd_license_status		Product: KERNEL	
Designation: License status			
Column name	Column designation	Type	Description
category	category	char(10)	Always "HYDRA"
datum	Date of license assignment	date	
hydrauser	User number	integer	
productkey	Product	char(10)	
zeit	Time of license assignment	integer	

5.28. hyd_lock

Table name: hyd_lock		Product: KERNEL	
Designation: Locked data records		Description: Administration of the internal locking mechanism on used data objects	
Column name	Column designation	Type	Description
bearb	Editor	char(10)	The editor that initiated this entry (PDM field ID: LOCK.BEARB)
datum	Date of the lock	date	 (PDM field ID: LOCK.DAT)
datum_bis	Reserved	date	
datum_von	Reserved	date	
hydrauser	User	smallint	 (PDM field ID: LOCK.USR)
job_id	Job id	integer	for future use
key1	Key 1	char(40)	Subject to the data record/object, the key includes different values. The key uniquely identifies the data record or the object. (PDM field ID: LOCK.KEY:1)
key2	Key 2	char(40)	Subject to the data record/object, the key includes different values. The key uniquely identifies the data record or the object.
key3	Key 3	char(40)	Subject to the data record/object, the key includes different values. The key uniquely identifies the data record or the object.
key4	Key 4	char(40)	Subject to the data record/object, the key includes different values. The key uniquely identifies the data record or the object.
key5	Key 5	char(40)	Subject to the data record/object, the key includes different values. The key uniquely identifies the data record or the object. (PDM field ID: LOCK.KEY:5)
modul	Module	char(40)	Internal ID of the editing module that locks the data record (PDM field ID: LOCK.MODUL)
param1	Session id	char(40)	 (PDM field ID: LOCK.PARAM:1)
param2	Reserved	char(40)	internal use (PDM field ID: LOCK.PARAM:2)
pid	PID - process id	integer	
verweis	DB reference	serial	 (PDM field ID: LOCK.VERWEIS)
zeit	Time of the lock	integer	 (PDM field ID: LOCK.ZEI)
zeit_bis	Reserved	integer	
zeit_von	Reserved	integer	

5.29. hyd_logging

Table name: hyd_logging		Product: KERNEL	
Archive table: a_hyd_logging		Reload table: r_hyd_logging	
Designation: Logging of dialogs			
Column name	Column designation	Type	Description
aktion	Action	char(20)	INSERT, UPDATE, DELETE, SPLIT, (which is behind the BAPI dot)
bearb		char(10)	Who has set the data record - is only set for LOG.INSERT or LOG.UPDATE (PDM field ID: LOG.BEARB)
datum		date	Date - is only set for LOG.INSERT or LOG.UPDATE (PDM field ID: LOG.DAT)
hydrauser	User	smallint	User - is only set for LOG.INSERT or LOG.UPDATE (PDM field ID: LOG.USR)
key1	Key 1	char(40)	Data from order header -> AUNR Data from operation -> AGNR Data from sequences -> AFOLG Data from networks -> ANETZ Data from long text -> HYINFO Data from material -> MAT Data from resources = production resources and tools -> RES (PDM field ID: LOG.KEY:1)
key2	Key 2	char(40)	If KEY1 = AUNR -> order number auftrags_bestand.auftrag_nr If KEY1 = AGNR -> operation = auftrags_bestand.auftrag_nr If KEY1 = AFOLG -> sequences= ade_auftragsfolgen.aunr If KEY1 = ANETZ -> order networks = ade_auftragsnetz. AUFTRAG_NR_V If KEY1 = Long text = HYINFO -> info texts = hyinfo.typ If KEY1 = Material = MAT -> component list = mlst_hy.verweis If KEY1 = Resources/production resources and tools = RES -> component list = mlst_hy.verweis (PDM field ID: LOG.KEY:2)
key3	Key 3	char(40)	If KEY1 = AFOLG -> sequences = ade_auftragsfolgen.afolg If KEY1 = ANETZ -> order networks = ade_auftragsnetz. AUFTRAG_NR_N If KEY1 = Long text = HYINFO -> info texts = hyinfo.key (= AUNR oder AGNR) If KEY1 = Material = MAT -> component list = mlst_hy.auftrag_nr If KEY1 = Resources/production resources and tools = RES -> component list = mlst_hy.auftrag_nr (PDM field ID: LOG.KEY:3)
key4	Key 4	char(40)	If KEY1 = Long text = HYINFO -> info texts = hyinfo.subkey1 (= note index) If KEY1 = Material = MAT -> component list = mlst_hy.res_typ If KEY1 = Resources/production resources and tools = RES -> component list = mlst_hy.res_typ (PDM field ID: LOG.KEY:4)

key5	Key 5	char(40)	If KEY1 = Long text = HYINFO -> info texts = hyinfo.subkey2 (= page number) If KEY1 = Material = MAT -> component list = mlst_hy.artikel If KEY1 = Resources/production resources and tools = RES -> component list = mlst_hy.artikel (= res) (PDM field ID: LOG.KEY:5)
label_text	Labeling	char(40)	Label for grouping / referencing
modul	Modification	char(40)	e.g. ADE (PDM field ID: LOG.MODUL)
operation	Input type	char(10)	Operation new: data inserted change: data modified restore: data restored undo: undo data change
remark_text	Commentary	char(255)	comment/remark
remark_type	Comment type	char(1)	T = see remark_text
rueckgemeldet	Confirmed	char(1)	If INSERT: "N" BAPI/function RUECKGEMELDET (confirmed) is set to "J"
rueckmelde_bearb	Confirm. Editor	char(10)	Who has confirmed. empty if table field RUECKGEMELDET = "N" is set with the value from BEARB in case of BAPI/function RUECKGEMELDET; is not set in case of INSERT, UPDATE.
rueckmelde_datum		date	Date of the confirmation empty if table field RUECKGEMELDET = "N" in case of BAPI/function RUECKGEMELDET it is set with the current date; otherwise empty
rueckmelde_zeit		integer	Time of the confirmation; otherwise empty empty if table field RUECKGEMELDET = "N" is set with the current date in case of BAPI/function RUECKGEMELDET
segnam	Segment name	char(30)	Segment name for MLE
sig_knr1	Sign. 1 - badge no.	char(10)	number of the ID card of person, who signed this entry (HYD-SIG)
sig_knr2	Sign. 2 - badge no.	char(10)	see SIG_KNR1
sig_name1	Sign. 1 - name	char(40)	name of person, who signed this entry (HYD-SIG)
sig_name2	Sign. 2 - name	char(40)	2nd person, see SIG_NAME1
sig_pnr1	Sign. 1 - personnel no.	char(10)	identification of person, who signed this entry (HYD-SIG)
sig_pnr2	Sign. 2 - personnel no.	char(10)	2nd person, see SIG_PNR1
sig_type1	Sign. 1 - type	char(20)	signature type (HYD-SIG)
sig_type2	Sign. 2 - type	char(20)	2nd person, see SIG_TYPE1
version	Version	integer	version of logged entry. Entry is defined by key values key1 to key5
verweis	Reference	serial	--- (PDM field ID: LOG.VERWEIS)
zeit		integer	Time - is only set for LOG.INSERT or LOG.UPDATE (PDM field ID: LOG.ZEI)

5.30. hyd_logging_cfg

Table name: hyd_logging_cfg		Product: KERNEL	
Designation: Logging configuration			
Column name	Column designation	Type	Description
aktion	Action	char(20)	Action (PDM field ID: LOGCFG.AKTION)
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
objekt	Object	char(40)	Object (PDM field ID: LOGCFG.OBJ)
param1	Parameter 1	char(20)	PARAM1[1,1] ID: LOGCFG.OPT:LOGDATA = J/N Default: N PARAM1[2,2] Save changes or complete object: (s)ent dialogdata, (c)omplete objectdata (only in case of BAPI supporting SELECT) ID: LOGCFG.MOD:LOG = s/c Default: s PARAM1[3,3]: compulsory comment: (f)orce, (o)ptional, (n)one ID: LOGCFG.OPT:LOGBEM = f/o/n Default: n PARAM1[4,4]: compulsory label: (f)orce, (o)ptional, (n)one ID: LOGCFG.OPT:LOGLBL = f/o/n Default: n PARAM1[5,5]: Log data with PPS=J (no matter whether compulsory comment/label is required). i.e. - PPS=J deactivates the check whether compulsory comment/label is required. - param1[5,5] = J determines whether these data are logged when they come from PPS ID: LOGCFG.OPT:LOGPPS = J/N Default: N (PDM field ID: LOGCFG.PARAM:1)
param2	Parameter 2	char(20)	Sending the signal to the program indicated The process to be notified is found if the indicated character string is contained in the command bar of the process. (PDM field ID: LOGCFG.PARAM:2)
segnam	Segment name	char(30)	Segment name for MLE (PDM field ID: LOGCFG.SEGNAM)

5.31. hyd_logging_data

Table name: hyd_logging_data		Product: KERNEL	
Archive table: a_hyd_logging_data		Reload table: r_hyd_logging_data	
Designation: Logging of dialog data			
Column name	Column designation	Type	Description
logging_data	Data	char(1000)	Data
logging_pos	Entry number/position	smallint	Entry number/position
verw_logging	Reference to HYD_LOGGING	integer	Reference to hyd_logging.verweis
verweis	DB reference	serial	Database reference

5.32. hyd_logging_keys

Table name: hyd_logging_keys		Product: KERNEL	
Designation: Logging configuration keys			
Column name	Column designation	Type	Description
aktion	Action	char(20)	Value, which will be filled in hyd_logging.aktion for example %ACTION% (PDM field ID: LOGKEY.AKTION)
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
key1	Key 1	char(40)	Value, which will be filled in hyd_logging.key1. for example MNR (PDM field ID: LOGKEY.KEY:1)
key2	Key 2	char(40)	Wert, welche in hyd_logging.key2 eingetragen wird; Bsp. %MNR.MNR% (PDM field ID: LOGKEY.KEY:2)
key3	Key 3	char(40)	 (PDM field ID: LOGKEY.KEY:3)
key4	Key 4	char(40)	 (PDM field ID: LOGKEY.KEY:4)
key5	Key 5	char(40)	 (PDM field ID: LOGKEY.KEY:5)
keyname1	Designation 1	char(255)	Klartext für key1; Bsp.: Maschine (PDM field ID: LOGKEY.KEYNAME:1)
keyname2	Designation 2	char(255)	Klartext für key2; Bsp.: Maschinenummer (PDM field ID: LOGKEY.KEYNAME:2)
keyname3	Designation 3	char(255)	 (PDM field ID: LOGKEY.KEYNAME:3)
keyname4	Designation 4	char(255)	 (PDM field ID: LOGKEY.KEYNAME:4)
keyname5	Designation 5	char(255)	 (PDM field ID: LOGKEY.KEYNAME:5)
objekt	Object	char(40)	reference to BAPI-Call (see table hyd_logging_cfg) (PDM field ID: LOGKEY.OBJ)

5.33. hyd_nummernkreise

Table name: hyd_nummernkreise		Product: KERNEL	
Designation: Number ranges			
Column name	Column designation	Type	Description
aktueller_wert	Current value	char(20)	(PDM field ID: NRKREIS.BER:VAL)
art	Generation type	char(6)	(PDM field ID: NRKREIS.ART:1)
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
bereich_bis	Range to	char(20)	End of the value range (PDM field ID: NRKREIS.BER:BIS)
bereich_von	Range from	char(20)	Start of the value range (PDM field ID: NRKREIS.BER:VON)
objekt_typ	Object	char(20)	Generation object AUNR = Order number AGNR = Operation number APNR = Work plan number IHNR = Main. message number (WRM-IH) RMNR = Upload number ... (PDM field ID: NRKREIS.OBJTYP)
praefix	Prefix	char(5)	Prefix that is placed before the number, e.g. "GK" could be the prefix for GK orders (PDM field ID: NRKREIS.PRAEFIX)
schluessel	Key	char(20)	Qualification within a generation object (for order number, e.g. order type, merged operation) AART = Order type SAG = Merged operation (only for object = "AUNR") MELDART = Posting type (only for object IHNR as a part of WRM-IH) (PDM field ID: NRKREIS.KEY)
schluessel_wert	Key value	char(20)	e.g. PP01 = order type; if "" , then this is not differentiated, or rather all order types for which no explicit number range was defined are given this entry (PDM field ID: NRKREIS.VAR)
vergabecode	Assignment code	char(6)	"NUM" = numeric assignment (PDM field ID: NRKREIS.VERGCODE)
verweis	DB reference	serial	(PDM field ID: NRKREIS.VERWEIS)

5.34. hyd_parklayout

Table name: hyd_parklayout		Product: KERNEL	
Designation: Graphic machinery layouts			
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
bez_lang	Description	char(40)	(PDM field ID: HPARK.BEZL)
bezeichnung	Designation	char(20)	(PDM field ID: HPARK.BEZX)
dateiname	Name of the zip file	char(20)	(PDM field ID: HPARK.DATEI)
firma	Company	char(4)	
id	DB reference	serial	(PDM field ID: HPARK.ID)
kostenstelle	Cost center	char(10)	Deprecated field (PDM field ID: HPARK.KST)
sichtbar	Visible	char(1)	for future use
sort	Sort order	integer	
typ	Layout type	char(1)	W = Cockpit layout M = layout N = layout (MPARK2 - solution)
verantw_bereich	Responsibility area	char(15)	

5.35. hyd_printdesign

Table name: hyd_printdesign		Product: KERNEL	
Designation: Labels			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	"Last editing time
bezeichnung	Designation	char(40)	Designation (PDM field ID: PRINTDESIGN.BEZ)
kommentar	Commentary	char(80)	Comment (PDM field ID: PRINTDESIGN.BEM)
param_01		integer	for future use
param_02		integer	for future use
param_str01	Alias	char(40)	for future use
param_str02	Label type	char(40)	for future use
pdouble_01		decimal(18,6)	for future use
pdouble_02		decimal(18,6)	for future use
report	Label name	char(40)	Label name (PDM field ID: PRINTDESIGN.REPORT)
sart_detail	Type of the detail scheme	char(30)	NO - No assignment HDS - HYDRA Data Scheme HSC - HYDRA Script (PDM field ID: PRINTDESIGN.ART:DETAIL)
sart_master	Type of the master scheme	char(30)	HDS - HYDRA Data Scheme HSC - HYDRA Script (PDM field ID: PRINTDESIGN.ART:MASTER)
schema_detail	Detail scheme	char(40)	Detail scheme (PDM field ID: PRINTDESIGN.SCHEMA:DETAIL)
schema_master	Master scheme	char(40)	Master scheme (PDM field ID: PRINTDESIGN.SCHEMA:MASTER)
suffix	Label suffix	char(10)	Label suffix (PDM field ID: PRINTDESIGN.SUFFIX)
version	Version	integer	Version (PDM field ID: PRINTDESIGN.VERSION)
verweis	Key - Field	serial	Key Field (PDM field ID: PRINTDESIGN.VERWEIS)

5.36. hyd_prn_schema

Table name: hyd_prn_schema		Product: KERNEL	
Designation: Label schema			
Column name	Column designation	Type	Description
bearb		char(10)	"Last editor
bearb_date		date	"Last editing day
bearb_time		integer	"Last editing time
bezeichnung	Designation	char(40)	Designation (PDM field ID: PRINTSCHEMA.BEZ)
hyschema	Schema name	char(40)	Schema name (PDM field ID: PRINTSCHEMA.SCHEMA)
hyschema_art	Schema type	char(1)	M - Master schema D - Detail schema (PDM field ID: PRINTSCHEMA.ART)
kommentar	Commentary	char(80)	Comment (PDM field ID: PRINTSCHEMA.BEM)
param_01		integer	for future use
param_02		integer	for future use
param_str01		char(40)	for future use
param_str02		char(40)	for future use
pdouble_01		decimal(18,6)	for future use
pdouble_02		decimal(18,6)	for future use
version	Version	integer	Version (PDM field ID: PRINTSCHEMA.VERSION)
verweis	Key - Value	serial	Key field (PDM field ID: PRINTSCHEMA.VERWEIS)

5.37. hyd_prn_schema_det

Table name: hyd_prn_schema_det		Product: KERNEL	
Designation: Label schemes (details)			
Column name	Column designation	Type	Description
bearb		char(10)	"Last editor
bearb_date		date	"Last editing day
bearb_time		integer	"Last editing time
hyschema	Schema name	char(40)	Schema name (PDM field ID: PRINTSCHEMADET.SCHEMA)
kennung	Identification	char(40)	Identification (PDM field ID: PRINTSCHEMADET.KENN)
mdkey		char(1)	for future use
param_01		integer	for future use
param_02		integer	for future use
param_str01		char(40)	for future use
param_str02		char(40)	for future use
pdouble_01		decimal(18,6)	for future use
pdouble_02		decimal(18,6)	for future use
protkey	Logging key	char(40)	Logging key (PDM field ID: PRINTSCHEMADET.PROTKEY)
typ	Data type	char(40)	for future use
verweis	Key - Column	serial	Key field (PDM field ID: PRINTSCHEMADET.VERWEIS)
wert	Value	char(100)	Example value for label preview (PDM field ID: PRINTSCHEMADET.VAL)

5.38. hyd_prndesign_cfg

Table name: hyd_prndesign_cfg		Product: KERNEL	
Designation: Label assignment			
Column name	Column designation	Type	Description
aktiv		char(10)	for future use
aktiv_date		date	for future use
aktiv_time		integer	for future use
aktiviert	Active	char(1)	Active (PDM field ID: PRINTDESIGNCFG.AKTIV)
anzahl	Number of prints	integer	Number of prints (PDM field ID: PRINTDESIGNCFG.ANZ)
batch		char(40)	for future use
batchdataconv	Data conversion	char(1)	Data conversion (PDM field ID: PRINTDESIGNCFG.BATCHDATACONV)
batchprint	Batchprint	char(1)	Batchprint (PDM field ID: PRINTDESIGNCFG.BATCHPRINT)
bearb		char(10)	"Last editor
bearb_date		date	"Last editing day
bearb_time		integer	"Last editing time
bezeichnung	Designation	char(40)	Designation (PDM field ID: PRINTDESIGNCFG.BEZ)
dialog	Dialog	char(20)	Dialog (PDM field ID: PRINTDESIGNCFG.DIALOG)
etyp	Label type	char(20)	for future use
inaktiv		char(10)	for future use
inaktiv_date		date	for future use
inaktiv_time		integer	for future use
key1	Reference 1	char(20)	Reference 1 (PDM field ID: PRINTDESIGNCFG.KEY:1)
key2	Reference 2	char(20)	Reference 2 (PDM field ID: PRINTDESIGNCFG.KEY:2)
key3		char(20)	for future use
key4		char(20)	for future use
key5		char(20)	for future use
kommentar	Commentary	char(80)	Comment (PDM field ID: PRINTDESIGNCFG.BEM)
logdrucker	Logical printer	char(40)	Logical printer (PDM field ID: PRINTDESIGNCFG.LOGDRUCKER)
param_01		integer	for future use
param_02		integer	for future use
param_str01	Standard alias	char(40)	for future use
param_str02	Assignment	char(40)	for future use
pdouble_01		decimal(18,6)	for future use
pdouble_02		decimal(18,6)	for future use

printmode	Mode	char(20)	PRINT - print PREVIEW - preview (PDM field ID: PRINTDESIGNCFG.PRINTMODE)
protokoll	Logging	char(1)	J/N: J - Carry out logging (PDM field ID: PRINTDESIGNCFG.PROT)
report	Label name	char(40)	Label name (PDM field ID: PRINTDESIGNCFG.REPORT)
suffix	Label suffix	char(10)	Label suffix (PDM field ID: PRINTDESIGNCFG.SUFFIX)
value1	Value 1	char(80)	Value 1 (PDM field ID: PRINTDESIGNCFG.VAL:1)
value2	Value 2	char(80)	Value 2 (PDM field ID: PRINTDESIGNCFG.VAL:2)
value3		char(80)	for future use
value4		char(80)	for future use
value5		char(80)	for future use
verarbeitung	Processing	char(1)	Processing (PDM field ID: PRINTDESIGNCFG.VERARB)
version	Version	integer	Version (PDM field ID: PRINTDESIGNCFG.VERSION)
verweis	Key - Field	serial	Key - Field (PDM field ID: PRINTDESIGNCFG.VERWEIS)
zuordnung	Name of the assignment	char(40)	Name of the assignment (PDM field ID: PRINTDESIGNCFG.CFG)
zuordnungs_art	Type of assignment	char(40)	K - No assignment D - Dialog assignment (PDM field ID: PRINTDESIGNCFG.CFG:ART)

5.39. hyd_prnlayout

Table name: hyd_prnlayout		Product: KERNEL	
Designation: Drucklayout			
Column name	Column designation	Type	Description
aktiv	Aktiv	char(1)	(PDM field ID: PRNLAYCFG.AKTIV)
anlage		char(10)	
anlage_date		date	
anlage_time		integer	
bearb	Bearbeiter	char(10)	letzter Bearbeiter
bearb_date		date	letzter Bearbeitungstag
bearb_time		integer	letzter Bearbeitungszeitpunkt
bezeichnung	Bezeichnung	char(20)	(PDM field ID: PRNLAYCFG.BEZ)
dateiname	Dateiname	char(40)	(PDM field ID: PRNLAYCFG.DATEI)
id	Konfiguration	integer	(PDM field ID: PRNLAYCFG.ID)
key1	KEY1	char(20)	(PDM field ID: PRNLAYCFG.KEY:1)
key2	KEY2	char(20)	(PDM field ID: PRNLAYCFG.KEY:2)
klassenname		char(40)	
kommentar	Kommentar	char(80)	(PDM field ID: PRNLAYCFG.BEM)
param		char(1000)	
param_01	Parameter 1	integer	Parameter 1 (PDM field ID: PRNLAYCFG.PARAM:1)
param_02	Parameter 2	integer	Parameter 2 (PDM field ID: PRNLAYCFG.PARAM:2)
param_str01	Parameter 5	char(20)	(PDM field ID: PRNLAYCFG.PARAM:5)
param_str02	Parameter 6	char(20)	(PDM field ID: PRNLAYCFG.PARAM:6)
pdouble_01	Parameter 3	decimal(18,6)	(PDM field ID: PRNLAYCFG.PARAM:3)
pdouble_02	Parameter 4	decimal(18,6)	(PDM field ID: PRNLAYCFG.PARAM:4)
suffix		char(10)	
typ	Typ	char(10)	(PDM field ID: PRNLAYCFG.TYP)
value1	VALUE1	char(200)	(PDM field ID: PRNLAYCFG.VAL:1)
value2	VALUE2	char(200)	(PDM field ID: PRNLAYCFG.VAL:2)
verantw_bereich	Verantwortungsbereich	char(15)	(PDM field ID: PRNLAYCFG.VAB)

version	Version	integer	(PDM field ID: PRNLAYCFG.VER)
verweis	Verweis	serial	Primaerschlüssel im Sinne von MPDV (PDM field ID: PRNLAYCFG.VERWEIS)

5.40. hyd_scheduler

Table name: hyd_scheduler		Product: KERNEL	
Designation: Scheduler			
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
begin_date	Start date of last run	date	(PDM field ID: SCHED.LDATB)
begin_time	Start time of last run	integer	(PDM field ID: SCHED.LZEIB)
command	Command	char(255)	Command to execute (PDM field ID: SCHED.CMD)
description	Description	char(255)	(PDM field ID: SCHED.BEZ)
end_date	End date of last run	date	(PDM field ID: SCHED.LDATE)
end_time	End time of last run	integer	(PDM field ID: SCHED.LZEIE)
entry_active	Active	char(1)	J/N (PDM field ID: SCHED.AKTIV)
entry_state	Status	char(3)	NR = not running RUN = running WT = waiting ERR = error NL = not licensed (PDM field ID: SCHED.STA)
entryopt	Entry options	char(10)	[1,1] Type S: Standard (MPDV) C: Customer SCHED.OPT:1 [2,2] Alterable N: Not Customizable C: Customizable SCHED.OPT:2 [3,3] Visible N: Not Visible V: Visible SCHED.OPT:3 (PDM field ID: SCHED.OPT:x)
entrytype	Entry type	char(1)	I = Interval: Means cyclical execution F = Fixed point(s) in time: means the execution at specific points in time O = execution once: stands for the unique execution as soon as the point in time is reached (PDM field ID: SCHED.TYP)
execute_from	I: from	integer	Earliest start time to execute a command (PDM field ID: SCHED.ZYKL:ZEIB)
execute_to	I: to	integer	Latest start time to execute a command (PDM field ID: SCHED.ZYKL:ZEIE)
fix_day	F/O: day	smallint	(PDM field ID: SCHED.FIX:DAY)

fix_hour	F/O: hour	smallint	(PDM field ID: SCHED.FIX:HOURL)
fix_minute	F/O: minute	smallint	(PDM field ID: SCHED.FIX:MIN)
fix_month	F/O: month	smallint	(PDM field ID: SCHED.FIX.MONTH)
fix_weekday	F/O: day of week	smallint	(PDM field ID: SCHED.FIX.WDAY)
fix_year	F/O: year	smallint	(PDM field ID: SCHED.FIX.YEAR)
hydrauser	User	integer	(PDM field ID: SCHED.USR)
interval	I: Interval	integer	(PDM field ID: SCHED.ZYKL:DAUER)
licensekeys	License key	char(80)	If this field is occupied, the scheduler entry will only be active if the licenses specified in the field are available. Several licenses are separated by space characters. For customer entries this field must not be used. (PDM field ID: SCHED.LICKEYS)
pid	PID - process id	integer	(PDM field ID: SCHED.PID)
productkey	Product key	char(10)	Product key (for license verification), this field will not be completed in case of customer entries. (PDM field ID: SCHED.PROKEY)
scheduler_id	Reserved	char(12)	fixed value: "hysched.cfg"
verweis	DB reference	serial	(PDM field ID: SCHED.VERWEIS)

5.41. hyd_userdata

Table name: hyd_userdata		Product: KERNEL	
Archive table: a_hyd_userdata		Reload table: r_hyd_userdata	
Designation: Master-Detail Userfields		Description: # Keys OBJTYP KEY FELDID	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
bezeichnung	Designation	char(80)	(PDM field ID: USRDATA.BEZ)
einheit	Unit	char(3)	(PDM field ID: USRDATA.EINH)
feldid	Field id	integer	(PDM field ID: USRDATA.IDX)
key	Key	char(40)	(PDM field ID: USRDATA.KEY)
objekt_typ	Object type	char(20)	(PDM field ID: USRDATA.OBJTYP)
sort	Sort order	integer	(PDM field ID: USRDATA.SORT)
user_feldid	Reference to Userfield	integer	(PDM field ID: USRDATA.FIDX)
value	Value	char(250)	(PDM field ID: USRDATA.VAL)

5.42. hyd_userexit

Table name: hyd_userexit		Product: KERNEL	
Designation: Registration of hydra script user exits		Description: This table lost its original purpose of Administration/versioning of hydra script user exits. Now it can only be used to see which hydra script user exits have been installed by HYDRA Install / Maintenance Manager.	
Column name	Column designation	Type	Description
aktiv		char(10)	
aktiv_date		date	
aktiv_time		integer	
aktiviert		char(1)	
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
bezeichnung		char(40)	
inaktiv		char(10)	
inaktiv_date		date	
inaktiv_time		integer	
kommentar		char(40)	
param		char(1000)	
released		char(1)	
typ		char(3)	
userexit		char(80)	
version		integer	
verweis		serial	

5.43. hyd_userfieldcfg

Table name: hyd_userfieldcfg		Product: KERNEL	
Designation: Userfields - key configuration		Description: # Keys OBJEKT_TYP USRFLD_KEY	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
bezeichnung	Description	char(80)	(PDM field ID: USRFLDCFG.BEZ)
objekt_typ	Object type	char(20)	(PDM field ID: USRFLDCFG.OBJTYP)
param_str_01	Reserved	char(10)	for future use
param_str_02	Reserved	char(20)	for future use
param_str_03	Reserved	char(30)	for future use
pdouble_01	Reserved	decimal(18,8)	for future use
plong_01	Reserved	integer	for future use
plong_02	Reserved	integer	for future use
pshort_01	Reserved	smallint	for future use
usrfld_key	User field key	char(20)	(PDM field ID: USRFLDCFG.USRFLD)
verantw_bereich	Responsibility area	char(15)	(PDM field ID: USRFLDCFG.VAB)

5.44. hyd_userfielddef

Table name: hyd_userfielddef		Product: KERNEL	
Designation: Userfields - type configuration		Description: # Keys REF_KENN	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
bez_lang	Description	char(80)	(PDM field ID: USRFLDDEF.BEZL)
bezeichnung	Designation	char(40)	(PDM field ID: USRFLDDEF.BEZK)
calc_add	Summand	float	for future use
calc_div	Divisor	float	for future use
calc_mul	Multiplier	float	for future use
calc_sub	Subtrahend	float	for future use
datentyp	Datatype	char(1)	(PDM field ID: USRFLDDEF.TYP)
einheit	Unit	char(15)	(PDM field ID: USRFLDDEF.EINH)
f_bis	Value range up to	decimal(18,6)	(PDM field ID: USRFLDDEF.BIS)
f_expr	Formula	char(6)	for future use
f_laenge	Field length	smallint	(PDM field ID: USRFLDDEF.LEN)
f_opt_aktiv	Reserved	char(10)	for future use
f_opt_inaktiv	Reserved	char(10)	for future use
f_opt_undef	Reserved	char(10)	for future use
f_von	Value range from	decimal(18,6)	(PDM field ID: USRFLDDEF.VON)
f_vorg_eingabe	Default values for entry	char(80)	(PDM field ID: USRFLDDEF.VORG:EDIT)
f_vorg_formel	Default values for formula	char(50)	for future use (PDM field ID: USRFLDDEF.VORG:EXPR)
f_zeichen	Allowed characters	char(100)	(PDM field ID: USRFLDDEF.ZEICH)
fillchar	Fill character	char(3)	
format	Field format	char(20)	(PDM field ID: USRFLDDEF.FMT)
intformat	Input format	char(20)	
nk_stellen	Decimal places	smallint	for future use (PDM field ID: USRFLDDEF.NKS)
param_str_01	Reserved	char(10)	for future use (PDM field ID: USRFLDDEF.PARAM:1)

param_str_02	Reserved	char(20)	for future use (PDM field ID: (reserved for future use))
param_str_03	Syntactic type	char(30)	(PDM field ID: USRFLDDEF.PARAM:3)
pdouble_01	Reserved	decimal(18,8)	for future use
plong_01	Reserved	integer	for future use
plong_02	Reserved	integer	for future use
pshort_01	Reserved	smallint	for future use
ref_kenn	Userfield type	char(20)	(PDM field ID: USRFLDDEF.KENN)
refdat	Reserved	char(20)	for future use

5.45. hyd_userfieldelem

Table name: hyd_userfieldelem		Product: KERNEL	
Designation: Userfields - field configuration		Description: # Keys OBJECT_TYP USRFLD_KEY FELDDID ZUGRIFFSART	
Column name	Column designation	Type	Description
anz_pos	Display position	smallint	Sort order (PDM field ID: USRFLDELEM.POS)
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
bez_lang	Description	char(80)	(PDM field ID: USRFLDELEM.BEZL)
bezeichnung	Designation	char(20)	(PDM field ID: USRFLDELEM.BEZK)
expr	Formula	char(6)	
feldid	Field id	integer	Numeric 1..n (PDM field ID: USRFLDELEM.IDX)
objekt_typ	Object type	char(20)	Object to which the user field key is assigned (e.g. AGNR) (PDM field ID: USRFLDELEM.OBJTYP)
optionen	Options	char(10)	1: [OBJTYP=DNC] Filter field 2: [OBJTYP=DNC] Mandatory field for upload 3: [OBJTYP=DNC] Preassignment at upload 4: [OBJTYP=DNC] Not alterable (read only) 5: [OBJTYP=DNC] Preassignment at download 6: [OBJTYP=ALL] Invisible in MOC (PDM field ID: USRFLDELEM.CFG:1..10)
param_str_01	Reserved	char(20)	for future use
param_str_02	Reserved	char(20)	for future use
param_str_03	Reserved	char(40)	for future use
param_str_04	Reserved	char(40)	for future use
param_str_05	Reserved	char(80)	for future use
plausi	Reserved	char(10)	for future use (PDM field ID: USRFLDELEM.FKT:PLAUS)
ref_kenn	Reference to hyd_userfielddef	char(20)	(PDM field ID: USRFLDELEM.KENN)
usrfld_key	Reference to hyd_userfieldcfg	char(20)	(PDM field ID: USRFLDELEM.USRFLD)
zugriffsart	Access mode	char(1)	Direct or indirect user field: F = direct user field S = indirect user field (PDM field ID: USRFLDELEM.ZGART)

5.46. hydialog

Table name: hydialog		Product: KERNEL	
Designation: Dynamic dialogs			
Column name	Column designation	Type	Description
breite	Height	smallint	(PDM field ID: DLGCFG.X)
cond_dyn_config	Dynamic condition	char(80)	(PDM field ID: DLGCFG.COND:DYNCFG)
cond_lic	Licenses	char(80)	(PDM field ID: DLGCFG.COND:LIC)
cond_stat_config	Static condition	char(80)	(PDM field ID: DLGCFG.COND:STACFG)
dialog	Dialog	char(20)	(PDM field ID: DLGCFG.DLG)
dlgusr	User	char(20)	(PDM field ID: DLGCFG.DLGUSR)
forced_fields	Forced fields	char(80)	(PDM field ID: DLGCFG.FORCEDFLD)
funktion1	Function 1	char(40)	(PDM field ID: DLGCFG.FKT1)
funktion2	Function 2	char(40)	(PDM field ID: DLGCFG.FKT2)
hoehe	Width	smallint	(PDM field ID: DLGCFG.Y)
icon	Resolution	char(12)	optional resloution of the dialog Dialogues at CTWIN are rendered to 640*480 Dialogues at CTAIP are rendered to 800*600 allowed values <empty>, 640*480, 800*600, 1024*768, 1280*1024 (PDM field ID: DLGCFG.ICON)
inaktiv	Activation	char(1)	
kommentar	Comment	char(80)	(PDM field ID: DLGCFG.BEM)
kurztext	Short text	char(40)	(PDM field ID: DLGCFG.TXTK)
langtext	Long text	char(80)	(PDM field ID: DLGCFG.TXTL)
taste	Key	char(10)	(PDM field ID: DLGCFG.TASTE)
taste_nr	Key ID	smallint	(PDM field ID: DLGCFG.TASTENR)
tastentext	Key text	char(50)	(PDM field ID: DLGCFG.TTXT)
typ	Type	char(10)	(PDM field ID: DLGCFG.TYP)
userdef1	User-defined 1	char(80)	(PDM field ID: DLGCFG.USRDEF:1)
userdef2	User-defined 2	char(80)	(PDM field ID: DLGCFG.USRDEF:2)

verweis	Reference	serial	(PDM field ID: DLGCFG.VERWEIS)
---------	-----------	--------	--------------------------------

5.47. hydialogbuttons

Table name: hydialogbuttons		Product: KERNEL	
Designation: Dynamic dialogs - buttons			
Column name	Column designation	Type	Description
b_breite	Width	smallint	(PDM field ID: DLGBTN.Y)
b_funktion	Function	char(40)	(PDM field ID: DLGBTN.FKT)
b_hoehe	Height	smallint	(PDM field ID: DLGBTN.X)
b_icon	Symbol	char(12)	(PDM field ID: DLGBTN.ICON)
b_info	Information	char(80)	(PDM field ID: DLGBTN.INFO)
b_kennung	Acronym	char(10)	(PDM field ID: DLGBTN.KENN)
b_kennung_idx	Acronym index	char(10)	(PDM field ID: DLGBTN.KENNIDX)
b_lizenz	License	char(30)	(PDM field ID: DLGBTN.LIZ)
b_nr	Button no.	smallint	(PDM field ID: DLGBTN.NR)
b_returncode	Return code	smallint	(PDM field ID: DLGBTN.RCODE)
b_taste	Key	char(10)	(PDM field ID: DLGBTN.TASTE)
b_text	Text	char(30)	(PDM field ID: DLGBTN.TXT)
b_wo_aktiv	Activated	char(1)	empty: always K : Console only T : Terminal only (PDM field ID: DLGBTN.AKTIV)
b_xpos	X pos.	smallint	(PDM field ID: DLGBTN.POSX)
b_ypos	Y pos.	smallint	(PDM field ID: DLGBTN.POSY)
dlg_verweis	DB reference to hydialog	integer	(PDM field ID: DLGBTN.VERWEIS)
userdef1	User-def. 1	char(20)	(PDM field ID: DLGBTN.USRDEF:1)
userdef2	Options	char(20)	[1,1] : X = Button is blocked and invisible (PDM field ID: DLGBTN.USRDEF:2)
userdef3	User-def. 2	char(20)	(PDM field ID: DLGBTN.USRDEF:3)

5.48. hydialogfields

Table name: hydialogfields		Product: KERNEL	
Designation: Dynamic dialogs - fields			
Column name	Column designation	Type	Description
db_feld_1	DB field 1	char(30)	(PDM field ID: DLGCFG.COLUMN:1)
db_feld_2	DB field 2	char(30)	(PDM field ID: DLGCFG.COLUMN:2)
db_tabelle_1	DB table 1	char(30)	(PDM field ID: DLGCFG.TABLE:1)
db_tabelle_2	DB table 2	char(30)	(PDM field ID: DLGCFG.TABLE:2)
dlg_verweis	DB reference to hydialog	integer	(PDM field ID: DLGCFG.VERWEIS)
f_attribut1	Field attribute 1	char(20)	Anmerkung: Die Werte für die Attribute 1-8 werden in Listen (für Konsole oder Terminals) in einem Feld "ATTR" durch Kommata getrennt übergeben. (PDM field ID: DLGFLD.ATTR:1)
f_attribut2	Field attribute 2	char(20)	Anmerkung: Die Werte für die Attribute 1-8 werden in Listen (für Konsole oder Terminals) in einem Feld "ATTR" durch Kommata getrennt übergeben. (PDM field ID: DLGFLD.ATTR:2)
f_attribut3	Field attribute 3	char(20)	Anmerkung: Die Werte für die Attribute 1-8 werden in Listen (für Konsole oder Terminals) in einem Feld "ATTR" durch Kommata getrennt übergeben. (PDM field ID: DLGFLD.ATTR:3)
f_attribut4	Field attribute 4	char(20)	Anmerkung: Die Werte für die Attribute 1-8 werden in Listen (für Konsole oder Terminals) in einem Feld "ATTR" durch Kommata getrennt übergeben. (PDM field ID: DLGFLD.ATTR:4)
f_attribut5	Field attribute 5	char(20)	Anmerkung: Die Werte für die Attribute 1-8 werden in Listen (für Konsole oder Terminals) in einem Feld "ATTR" durch Kommata getrennt übergeben. (PDM field ID: DLGFLD.ATTR:5)
f_attribut6	Field attribute 6	char(20)	Anmerkung: Die Werte für die Attribute 1-8 werden in Listen (für Konsole oder Terminals) in einem Feld "ATTR" durch Kommata getrennt übergeben. (PDM field ID: DLGFLD.ATTR:6)
f_attribut7	Field attribute 7	char(20)	Anmerkung: Die Werte für die Attribute 1-8 werden in Listen (für Konsole oder Terminals) in einem Feld "ATTR" durch Kommata getrennt übergeben. (PDM field ID: DLGFLD.ATTR:7)
f_attribut8	Field attribute 8	char(20)	Anmerkung: Die Werte für die Attribute 1-8 werden in Listen (für Konsole oder Terminals) in einem Feld "ATTR" durch Kommata getrennt übergeben. (PDM field ID: DLGFLD.ATTR:8)
f_ausrichtung	Alignment	char(1)	(PDM field ID: DLGFLD.AUSR)
f_bis	To	char(20)	(PDM field ID: DLGFLD.BIS)
f_combo_datei	Select file	char(12)	(PDM field ID: DLGFLD.DATEI)
f_eingabetyp	Input type	char(20)	(PDM field ID: DLGFLD.ETYP)
f_einheit	Unit	char(15)	(PDM field ID: DLGFLD.EINH)
f_fkt_combo	Combobox function	char(20)	(PDM field ID: DLGFLD.COMBO)

f_fkt_liste	Dialog list function	char(20)	(PDM field ID: DLGFLD.LISTE)
f_format	Formatting	char(20)	(PDM field ID: DLGFLD.FMT)
f_funktion1	Function 1	char(40)	(PDM field ID: DLGFLD.FKT1)
f_funktion2	Function 2	char(40)	(PDM field ID: DLGFLD.FKT2)
f_hyeinheit	Unit	char(8)	(PDM field ID: DLGFLD.HYEINH)
f_info	Information	char(80)	(PDM field ID: DLGFLD.INFO)
f_kategorie	Category	char(15)	(PDM field ID: DLGFLD.KAT)
f_kennung	Identification	char(50)	(PDM field ID: DLGFLD.KENN)
f_kennung_idx	ID index	char(10)	(PDM field ID: DLGFLD.KENNIDX)
f_laenge	Length	smallint	(PDM field ID: DLGFLD.LEN)
f_nr	Field no.	smallint	(PDM field ID: DLGFLD.NR)
f_opt_aktiv	Optional field 1	char(5)	Wert, wenn Optionsfeld angeklickt ist (Wert aktiv) (PDM field ID: DLGFLD.OPT:YES)
f_opt_inaktiv	Optional field 2	char(5)	??? (PDM field ID: DLGFLD.OPT:NO)
f_radio_def	Radio button	char(200)	(PDM field ID: DLGFLD.RADIO)
f_text	Text	char(50)	(PDM field ID: DLGFLD.TXT)
f_von	From	char(20)	(PDM field ID: DLGFLD.VON)
f_vorgabe	Default	char(20)	(PDM field ID: DLGFLD.VORG)
f_wo_aktiv	Activated	char(1)	empty: always K : Console only T : Terminal only (PDM field ID: DLGFLD.AKTIV)
f_xpos_einh	X pos. unit	smallint	(PDM field ID: DLGFLD.EPOSX)
f_xpos_feld	X pos. field	smallint	(PDM field ID: DLGFLD.FPOSX)
f_xpos_text	X pos. text	smallint	(PDM field ID: DLGFLD.TPOSX)
f_ypos_einh	Y pos. unit	smallint	(PDM field ID: DLGFLD.EPOSY)
f_ypos_feld	Y pos. field	smallint	(PDM field ID: DLGFLD.FPOSY)
f_ypos_text	Y pos. text	smallint	(PDM field ID: DLGFLD.TPOSY)
f_zeichen	Allowed characters	char(80)	(PDM field ID: DLGFLD.ZEICH)
nsichtbar_wenn	Invisible with dialog control	char(40)	
sichtbar_wenn	Visible with dialog control	char(40)	

userdef1	User-def. 1	char(20)	(PDM field ID: DLGFLD.USRDEF:1)
userdef2	Options	char(20)	[1,1] : X = Field is blocked and invisible [2,2] : J = Field is visible (PDM field ID: DLGFLD.USRDEF:2)
userdef3	User-def. 3	char(20)	(PDM field ID: DLGFLD.USRDEF:3)

5.49. hydialogwf

Table name: hydialogwf		Product: KERNEL	
Designation: Dynamic dialogs - workflows			
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
dlg	Dialog	char(20)	(PDM field ID: DLGWF.DLG)
dlgusr	Dialog user	char(20)	(PDM field ID: DLGWF.DLGUSR)
fwfs	Keep Forced Dialog Sequence	char(1)	(PDM field ID: DLGWF.FWFS)
inaktiv	Reserved	char(1)	for future use
kommentar	Description	char(80)	(PDM field ID: DLGWF.BEM)
step_1	Step 1	char(20)	(PDM field ID: DLGWF.STEP:1)
step_10	Step 10	char(20)	
step_2	Step 2	char(20)	
step_3	Step 3	char(20)	
step_4	Step 4	char(20)	
step_5	Step 5	char(20)	
step_6	Step 6	char(20)	
step_7	Step 7	char(20)	
step_8	Step 8	char(20)	
step_9	Step 9	char(20)	
title	Title	char(100)	(PDM field ID: DLGWF.TITLE)
typ	Type	char(10)	(PDM field ID: DLGWF.TYP)
userdef1	User-defined 1	char(20)	(PDM field ID: DLGWF.USERDEF:1)
userdef2	User-defined 2	char(20)	(PDM field ID: DLGWF.USERDEF:2)
userdef3	User-defined 3	char(20)	(PDM field ID: DLGWF.USERDEF:3)
verweis	DB reference	serial	
wfscr_1	Script for step 1	char(1)	(PDM field ID: DLGWF.WFSCR:1)
wfscr_10	Script for step 10	char(1)	
wfscr_2	Script for step 2	char(1)	
wfscr_3	Script for step 3	char(1)	
wfscr_4	Script for step 4	char(1)	
wfscr_5	Script for step 5	char(1)	
wfscr_6	Script for step 6	char(1)	

wfscr_7	Script for step 7	char(1)	
wfscr_8	Script for step 8	char(1)	
wfscr_9	Script for step 9	char(1)	
workflow	Workflow	char(20)	(PDM field ID: DLGWF.WORKFLOW)

5.50. hyinfo

Table name: hyinfo		Product: KERNEL	
Archive table: a_hyinfo		Reload table: r_hyinfo	
Designation: (Order-related) additional information		Description: Messages, which are displayed on the terminal due to certain activities, are saved here for individual employees.	
Column name	Column designation	Type	Description
anzeigen_fehlgrund		char(1)	Always display when absence reasons are stated (J/N). (PDM field ID: INFO.OPT:FGR)
anzeigen_geht		char(1)	Display always when clocking-out (J/N). (PDM field ID: INFO.OPT:GEH)
anzeigen_info	Display on terminal	char(1)	Always display at INFO (J/N). (PDM field ID: INFO.OPT:INFO)
anzeigen_kommt		char(1)	Display always when clocking-in (J/N). (PDM field ID: INFO.OPT:KOM)
anzeigen_pause		char(1)	Display always at break (J/N). (PDM field ID: INFO.OPT:PAU)
bearb	Modified by	char(10)	
bearb_date	Master - entry created	date	Last editing day
bearb_time		integer	Last editing time
countdown		smallint	How often will a message be displayed? (PDM field ID: INFO.MAXANZ)
datum_bis	Obsolete: INFO.DATB	date	Validity period. (PDM field ID: INFO.DATE)
datum_von	Obsolete: INFO.DATV	date	Validity period. (PDM field ID: INFO.DATB)
gelesen_date		date	----
gelesen_time		integer	----
info1		char(100)	Text line (ten is displayed here) (PDM field ID: INFO.INFO:1)
info10		char(100)	Text line (PDM field ID: INFO.INFO:10)
info2		char(100)	Text line (PDM field ID: INFO.INFO:2)
info3		char(100)	Text line (PDM field ID: INFO.INFO:3)
info4		char(100)	Text line (PDM field ID: INFO.INFO:4)
info5		char(100)	Text line (PDM field ID: INFO.INFO:5)
info6		char(100)	Text line (PDM field ID: INFO.INFO:6)
info7		char(100)	Text line (PDM field ID: INFO.INFO:7)
info8		char(100)	Text line (PDM field ID: INFO.INFO:8)
info9		char(100)	Text line (PDM field ID: INFO.INFO:9)

infoformat		char(10)	Empty/ "FIX80": as hithereto TEXT: Continuous text + "\n" + "\t" Thus, text formatted in RTF or HTML could also be filed in future. (PDM field ID: INFO.FMT)
key	Staff badge no.	char(40)	ADE: order number (complete) PZE : badge number for which the information is supposed to be displayed Complete ident: A*: Order or order/OP number (AUFTRAGS_NR) P*: Personnel number XMNR*: Machine number (PDM field ID: INFO.KEY)
kurztext		char(20)	New field: AN: Short ext of the note (is used as tab caption) Otherwise: can be used freely (PDM field ID: INFO.BEZ)
subkey1	Entry number	integer	ADE: Entry number (e.g. note number) starting with 0 PZE: Relevant for TYP PK (customer-specific info) only; otherwise empty: 2: Annual information from SAP 3: ZGRDINF 4: PERSINF ATTENTION: Type change!!!! Specific assignment ATTENTION: the AGNR (OP No.) is not entered anymore in A* AN: Index of the note; the index of the tab results from this; starting with 0 (PDM field ID: INFO.SUBKEY:1)
subkey2		integer	ADE: Page number 1..n PZE: Internal administration in SAP sub system. Otherwise not relevant for PZE. Otherwise: Page number 1..n ("top down") (PDM field ID: INFO.SUBKEY:2)
typ		char(10)	First character "A" for ADE. "AI" : additional order information "BI" : additional work plan information "AX": additional data on the OP previously (last scheduling of OP on machine/machine group) "AD": additional data on the OP for label printing "AU"/"AG": additional order data or OP data First character "P" for PZE. "PE" : Information entered manually "PI" : Information generated via SAP sub system interface "PM" : Mails generated via SAP sub system interface (IMAIL, ZMAIL) "PN": Message generated via the escalation management "PK" : Customer-specific information, other key in subkey1 First character "L" for Logbook. "L_DETAIL": Detail entry "L_MASTER": Master entry (PDM field ID: INFO.TYP)
verweis		serial	----
verweis_meldung		integer	For the type "PE" this field contains the reference of the message configuration from pze_info_par. For the type "PN" this field contains the reference to the message of the event from the escalation management.
wochentag	Weekday	integer	Day on which the message is displayed (7 = every day, 0 = Sunday, 1 = Monday, ... , 6 = Saturday). (PDM field ID: INFO.WTG)

5.51. persfkt_profil

Table name: persfkt_profil		Product: KERNEL	
Designation: Personal function profiles		Description: Personal function profiles	
		# Keys profil, funktion	
		# logical connection to other tables profile = persfkt_tab.profil	
Column name	Column designation	Type	Description
anlae_time		integer	
anlage	Created by	char(10)	For future use
anlage_date		date	
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
funktion	Description	smallint	
profil	Personal function profile	smallint	
stufe	Level	smallint	
verweis	ID	serial	

5.52. persfkt_tab

Table name: persfkt_tab		Product: KERNEL	
Designation: Personal function authorizations		Description: Personal function authorizations	
		# Keys personalnummer, profil	
		# logical connection to other tables profil = persfkt_profil.profil	
Column name	Column designation	Type	Description
anlae_time		integer	
anlage	Created by	smallint	
anlage_date		date	
bearb		smallint	
bearb_date		date	
bearb_time		integer	
personalnummer		integer	
profil	Profile	smallint	
verweis		serial	

5.53. personen

Table name: personen		Product: KERNEL	
Designation: HR master data		Description: HR master data. # Special remarks The HR master data is versioned by date (gueltig_von to gueltig_bis). To select the current valid HR master data the view personalstamm may be used. # Key personalnummer, gueltig_von	
Column name	Column designation	Type	Description
a_stufe	BDE authorization	char(20)	BDE: [1,1] 0..9 authorization level whether person is allowed to log orders on (comparison with auftrags_bestand.a_stufe) ID:PNR.ASTUFE:1 This is checked additionally: [2,2] J/N: Log OP on (A_AN) ID:PNR.ASTUFE:2 [3,3] J/N: Log OP off (A_AB) ID:PNR.ASTUFE:3 [4,4] J/N: Log all persons off (P_AAB) ID:PNR.ASTUFE:4 (PDM field ID: PNR.ASTUFE)
abmeld_kz	Check whether person is logged on	char(1)	(PDM field ID: PNR.PLAUS:PNRANAG)
abteilung	Department	char(8)	Additional grouping indicator. (PDM field ID: PNR.ABT)
abw_setzen_um	For future use	integer	
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
anrede	Salutation	char(20)	For future use
anrgk	Pers. process of waiting period posting	char(40)	Pers. process of waiting period posting (PDM field ID: PNR.ANRGK)
austritt	Date of leaving	date	Empty if the employee has not left the company. (PDM field ID: PNR.AUSTRITT)
bde_sperrkz	Lock person (BDE)	char(1)	free (PDM field ID: PNR.SPERR:BDE)
bearb	Modified by	char(10)	
bearb_cons	Obsolete	smallint	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich	Area	char(8)	Additional grouping indicator. (PDM field ID: PNR.BER)
bpos	Operator position	char(10)	(PDM field ID: PNR.BPOS)

dienstgangberecht	Authorized to go on short business trip	char(1)	Reserved for future use. (PDM field ID: PNR.DGBERECHT)
eintritt	Date of joining	date	(PDM field ID: PNR.EINTRITT)
email_firma	E-mail address in company	char(80)	
email_privat	Private e-mail address	char(80)	
erste_verrechnung	First compensation date PZE	date	Reserved: day of the first compensation via the work day evaluation (PDM field ID: PNR.ETGAWDAT)
familienstand	Family status	char(1)	
fax_firma	Fax in company	char(20)	
fax_privat	Private fax	char(20)	
fehlgrund_grp	Internal use HR PDC	char(10)	
firmen_nummer	Company	char(4)	Additional grouping indicator. (PDM field ID: PNR.FIR)
geburtsdatum	Date of birth	date	(PDM field ID: PNR.GEBDAT)
geschlecht	Sex	char(1)	M/F (PDM field ID: PNR.GESCHLECHT)
gewerbl_angestellt	Employment relationship	char(1)	A=salaried employee G=non-salaried employee (PDM field ID: PNR.BESCHVERH)
gleitzeitmodell	Working time model	smallint	(PDM field ID: PNR.GLZJMOD)
grafikdatei	Graphic file	char(20)	File name of the graphic file when a picture of the employee is displayed. This column is filled automatically when an image is assigned to the person.. (PDM field ID: PNR.BILD)
gueltig_bis	Valid to	date	(PDM field ID: PNR.DATE)
gueltig_von	Valid from	date	(PDM field ID: PNR.DATB)
info_nr	For future use	smallint	
infodatum_1	Freely configurable information value.	date	(PDM field ID: PNR.INFODAT:1)
infodatum_2	Freely configurable information value.	date	(PDM field ID: PNR.INFODAT:2)
infodatum_3	Freely configurable information value.	date	(PDM field ID: PNR.INFODAT:3)
infodatum_4	Freely configurable information value.	date	(PDM field ID: PNR.INFODAT:4)
infodatum_5	Freely configurable information value.	date	(PDM field ID: PNR.INFODAT:5)
infotext_1	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:1)
infotext_10	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:10)
infotext_11	Freely configurable information value.	char(20)	(PDM field ID: PNR.INFOTXT:11)
infotext_12	Freely configurable information value.	char(20)	(PDM field ID: PNR.INFOTXT:12)
infotext_13	Freely configurable information value.	char(20)	(PDM field ID: PNR.INFOTXT:13)
infotext_14	Freely configurable information value.	char(20)	(PDM field ID: PNR.INFOTXT:14)

infotext_15	Freely configurable information value.	char(20)	(PDM field ID: PNR.INFOTXT:15)
infotext_16	Freely configurable information value.	char(10)	(PDM field ID: PNR.INFOTXT:16)
infotext_18	Freely configurable information value.	char(10)	(PDM field ID: PNR.INFOTXT:18)
infotext_19	Freely configurable information value.	char(10)	(PDM field ID: PNR.INFOTXT:19)
infotext_2	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:2)
infotext_20	Freely configurable information value.	char(10)	(PDM field ID: PNR.INFOTXT:20)
infotext_3	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:3)
infotext_4	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:4)
infotext_5	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:5)
infotext_6	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:6)
infotext_7	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:7)
infotext_8	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:8)
infotext_9	Freely configurable information value.	char(40)	(PDM field ID: PNR.INFOTXT:9)
infowert_1	Freely configurable information value.	integer	(PDM field ID: PNR.INFOWERT:1)
infowert_2	Freely configurable information value.	integer	(PDM field ID: PNR.INFOWERT:2)
infowert_3	Freely configurable information value.	integer	(PDM field ID: PNR.INFOWERT:3)
infowert_4	Freely configurable information value.	integer	(PDM field ID: PNR.INFOWERT:4)
infowert_5	Freely configurable information value.	integer	(PDM field ID: PNR.INFOWERT:5)
karten_nummer	Staff badge no.	char(10)	Unique number of the plant ID card. (PDM field ID: PNR.KNR)
kostenstelle	Cost center	char(10)	(PDM field ID: PNR.KST)
kostenstellen_grp	Internal use HR PDC	char(10)	
kurzzeichen	For future use	char(10)	
leistgrp_grp	For future use	char(10)	
letzte14kw_auswert	Allocate average working time	char(1)	Allocate average working time (J/N). (PDM field ID: PNR.OPT:AVGAZVERB)
letzte14kw_istzeit	Average working time	integer	Average working time as entered in the HR master. (PDM field ID: PNR.AVGAZ)
lle_lohnart	Wage type	char(4)	
lle_lohngruppe	Wage group	char(4)	
lohnstatusmodell	Payment model	smallint	(PDM field ID: PNR.ENTLJMOD)
lpkz	Wage/premium indicator	char(10)	Wage/premium indicator (PDM field ID: PNR.LPKZ)

m_stufe	MDE authorization	char(20)	[1,1] 0..9: person is allowed to change the status ID: PNR.MSTUFE:1 in connection with [1]: [2,2] J/N: modification is only possible if person is logged on ID: PNR.MSTUFE:2 [4,4] J/N: Authorization to change the production lock (as of version MDE 7.2) KENNUNG: PNR.MSTUFE:4 (PDM field ID: PNR.MSTUFE)
maxanmeld	Max. OPs per person	integer	The person's maximum number of OP logons If value = 0 => do not carry out plausibility check (PDM field ID: PNR.ANMELDMAX)
mehr_masch	Log on to several workplaces	char(1)	J/N, whether person is allowed to log on to several machines (PDM field ID: PNR.MEHRMNR)
mobil_firma	Company mobile	char(20)	
mobil_privat	Private mobile	char(20)	
name	Full name of person, populated automatically	char(83)	
nationalitaet	Nationality	char(3)	Free abbreviation. (PDM field ID: PNR.NATION)
nicht_stempler	Person does not clock	char(1)	
pager_firma	Company pager number	char(20)	
pager_privat	Private pager number	char(20)	
param01		char(10)	[3,3]: J/N = staff is automatically logged on to another OP, which is triggered by new P_AN : PNR.OPT:AGWAUTO (PDM field ID: PNR.PARAM:1)
param02		char(10)	[1,1] = 0..9 authorization level whether person is allowed to change the resource status (comparison with res_status_zuord.berecht_stufe) ID: PNR.RSTUFE [2,2] = 0..9 = Authorization to download DNC resources (values >= 1 can be regarded as 'J') ID: PNR.DLSTUFE [4,4] = J = May only be logged off if total quantity = target quantity [5,5] = J/N = Authorization assembly or disassembly resources [6,6] = 0..9 = Authorization level for resetting maintenance ID: PNR.WARTSTUFE:VALUE [7,7] = J/N = Authorization to reset maintenances (as of version WRM 7.2) ID: PNR.WARTSTUFE [8,8] = J/N = Authorization to record measures (as of version WRM 7.2) ID: PNR.MASSSTUFE [9,9] = 0..9 = Authorization to release DNC resources (values >= 1 can be regarded as 'J') ID: PNR.FGSTUFE [10,10] = 0..9 = Authorization to upload DNC resources (values >= 1 can be regarded as 'J') ID: PNR.ULSTUFE (PDM field ID: (Composed of several acronyms))

pers_abmeld	Autom. logoff of person at end of shift	char(1)	Autom. logoff of person at the end of the shift Is only taken into account if an "X" is written in maschinen.pers_abmeld. J: Log persons always off at the end of the shift N: Always memorize persons at the end of the shift, except for a manual logoff - or not relevant if no "X" is written in maschinen.pers_abmeld. (PDM field ID: PNR.OPT:PABSKE)
person_name	Last name	char(40)	(PDM field ID: PNR.PNAME)
person_nr_char	Personnel number alpha-numeric	char(10)	The employee's unique personnel number with fill character that is set according to the basic settings (table setup). This alphanumeric personnel number is mainly used in MF tables. (PDM field ID: PNR.PNR)
person_vorname	First name	char(20)	(PDM field ID: PNR.PVORNAME)
person_vorname_2	Second First name	char(20)	
personalnummer	Personnel number	integer	Unique identification of the person. (PDM field ID: PNR.PNR)
pgruppe		char(20)	--- (PDM field ID: PNR.PGRP)
pgruppe_neu		char(20)	--- (PDM field ID: PNR.PGRPNEU)
pincode	Pin code	char(20)	(PDM field ID: PNR.PIN)
pkreis	Employee subgroup	char(8)	Additional grouping characteristic. If the System is used as SAP sub system this field contains a group of absence reason authorizations, which is composed of several fields of the HR master interface. (PDM field ID: PNR.PKREIS)
postleitzahl	Zip code	char(10)	(PDM field ID: PNR.PLZ)
praemien_grp	Premium group	char(8)	Premium group. Optional field for incentive wage. (PDM field ID: PNR.PRGRP)
praemien_kz	Premium indicator	char(1)	Additional field for LLE Payroll indicator for incentive wage determination (premium indic.) E individual piecework G group piecework N practice B spec. employee group L apprentice/trainee Z or empty or NULL = time wage (PDM field ID: PNR.PRKZ)
pze_ade_abgleich	PZE/ADE comparison	char(1)	PZE/ADE comparison (J, N/""") -> Person is relevant for labor time comparison (time&attendance vs. MF) (PDM field ID: PNR.OPT:PZEADEABGL)
s_stufe		char(20)	[1,1] 0..1, person may change target cycle and target partitioning at the terminal only if 1 is entered ID: PNR.SSTUFE:1 [2,2] J/N: Change target quantity ID: PNR.SSTUFE:2 (PDM field ID: PNR.SSTUFE)
sap_tevtgr	Internal use HR PDC	smallint	
sap_verarb	Internal use HR PDC	smallint	
schchtzeitenmodell	Obsolete	smallint	(PDM field ID: PNR.SCHZJMOD)
schichtrythmus	Shift rhythm model	smallint	(PDM field ID: PNR.SCHZARTJMOD)

smengenpruefung	Target quantity check	char(1)	0/1 : The operation can be logged on at any time 2: A plausibility check is made whether the current actual quantity is within the limits of "underproduction" and "overproduction". The logon is rejected if this is not the case. 3: As described in 2 but a person has additionally to be logged on to the OP (PDM field ID: PLAUS:SMENGE)
sonderurl_anspruch	Special leave	integer	Annual entitlement to special leave (this field is filed in the database after having been multiplied with the factor 10). (PDM field ID: PNR.URLANSPR:SONDER)
sperrkz	Lock person	char(1)	Block indicator (" " / "S") S: Person is blocked for time&attendance (PDM field ID: PNR.SPERR:PZE)
sprache	For future use	smallint	
stamm_cons_nr	not used	integer	Deprecated field
stamm_j_mod	Year model	smallint	Regular year model (PDM field ID: PNR.BDEJMOD)
stamm_masch_nr	Workplace	char(20)	Regular machine (PDM field ID: PNR.SMNR)
strasse	Street	char(30)	 (PDM field ID: PNR.STRASSE)
stundenlohn	Hourly rate, OBSOLETE	decimal(6,2)	For customer specific use (PDM field ID: PNR.PSTD SATZ)
taetigkeit	Job Title	char(20)	 (PDM field ID: PNR.TAETIGKEIT)
teilzeitgrad	Part-time rate	integer	Part-time rate in percent * 1000 (100 percent = 100000). (PDM field ID: PNR.TZGRAD)
telefon_firma	Company phone	char(20)	 (PDM field ID: PNR.TEL:FIR)
telefon_privat	Private phone	char(20)	 (PDM field ID: PNR.TEL:PRIVAT)
temkostnum	Obsolete	char(10)	 (PDM field ID: PNR.KST:TMP)
tempfirma	Obsolete	char(4)	 (PDM field ID: PNR.FIR:TMP)
tempkostbeginn	Obsolete	date	 (PDM field ID: PNR.DATB:TMP)
tempkostende	Obsolete	date	 (PDM field ID: PNR.DATB:TMP)
titel	Title	char(30)	Academic or other title. (PDM field ID: PNR.TITEL)
ueberprod	Maximum target quantity	smallint	Percentage >= 100 % (PDM field ID: PNR.OPG)
unterprod	Minimum target quantity	smallint	Percentage <= 100 % (PDM field ID: PNR.UPG)
url_anspruch	Annual leave	integer	Annual leave entitlement (this field is filed in the database after having been multiplied with the factor 10). (PDM field ID: PNR.URLANSPR:NORM)
url_anspruch_datum	Booking date for the leave entitlement	date	For future use (PDM field ID: PNR.URLANSPR:DAT)
user_c_29	userfield	char(1)	For future use (PDM field ID: PNR.FU:29)
user_c_30	userfield	char(1)	For future use
user_c_31	userfield	char(1)	For future use
user_c_32	userfield	char(1)	For future use
user_c_33	userfield	char(1)	For future use

user_c_34	userfield	char(1)	For future use
user_c_35	userfield	char(1)	For future use
user_c_36	userfield	char(1)	For future use
user_c_37	userfield	char(1)	For future use
user_c_38	userfield	char(1)	For future use
user_c_39	userfield	char(1)	For future use
user_c_40	userfield	char(1)	For future use
user_c_41	userfield	char(1)	For future use
user_c_42	userfield	char(1)	For future use
user_c_43	userfield	char(1)	For future use
user_c_44	userfield	char(1)	For future use
user_c_45	userfield	char(10)	For future use
user_c_46	userfield	char(10)	For future use
user_c_47	userfield	char(10)	For future use
user_c_48	userfield	char(10)	For future use
user_c_49	userfield	char(10)	For future use
user_c_50	userfield	char(10)	For future use
user_c_51	userfield	char(20)	For future use
user_c_52	userfield	char(20)	For future use
user_c_53	userfield	char(20)	For future use
user_c_54	userfield	char(20)	For future use
user_c_55	userfield	char(20)	For future use
user_c_56	userfield	char(20)	For future use
user_c_57	userfield	char(20)	For future use
user_c_58	userfield	char(20)	For future use
user_c_59	userfield	char(20)	For future use
user_c_60	userfield	char(20)	For future use
user_c_61	userfield	char(20)	For future use
user_c_62	userfield	char(20)	For future use
user_c_63	userfield	char(20)	For future use
user_c_64	userfield	char(20)	For future use
user_c_65	userfield	char(40)	For future use
user_c_66	userfield	char(40)	For future use
user_code	User field key	char(8)	For future use
user_d_01	userfield	date	For future use
user_d_02	userfield	date	For future use
user_d_03	userfield	date	For future use
user_d_04	userfield	date	For future use
user_d_05	userfield	date	For future use
user_d_06	userfield	date	For future use
user_f_23	userfield	decimal(18,6)	For future use
user_f_24	userfield	decimal(18,6)	For future use
user_f_25	userfield	decimal(18,6)	For future use
user_f_26	userfield	decimal(18,6)	For future use
user_f_27	userfield	decimal(18,6)	For future use
user_f_28	userfield	decimal(18,6)	For future use

user_n_07	userfield	integer	For future use
user_n_08	userfield	integer	For future use
user_n_09	userfield	integer	For future use
user_n_10	userfield	integer	For future use
user_n_11	userfield	integer	For future use
user_n_12	userfield	integer	For future use
user_n_13	userfield	integer	For future use
user_n_14	userfield	integer	For future use
user_n_15	userfield	integer	For future use
user_n_16	userfield	integer	For future use
user_n_17	userfield	integer	For future use
user_n_18	userfield	integer	For future use
user_n_19	userfield	integer	For future use
user_n_20	userfield	integer	For future use
user_n_21	userfield	integer	For future use
user_n_22	userfield	integer	For future use
verantw_bereich	Responsibility area	char(15)	
verweis	Reference	serial	Internal unique number of the record
vorgesetzter_firma	Company of supervisor	char(4)	
vorgesetzter_pnr	Supervisor	integer	
wochlohnstatustyp	Overtime type	smallint	Number of the overtime type for the person. (PDM field ID: PNR.ENTLTMOD:MEHRARB)
wohntort	Domicile	char(20)	(PDM field ID: PNR.ORT:WOHN)
zaehler1	Ratio factor for A bonus	integer	Ratio factor for activity bonus (PDM field ID: Ratio factor for A bonus)
zaehler2		integer	
zeitnachweisliste	Time sheet	smallint	Number of the time sheet for HYDRA@Web (PDM field ID: PNR.ZNWL)
zusatzurl_anspruch	Additional leave	integer	

5.54. setup

Table name: setup		Product: KERNEL	
Designation: Basic settings		Description: Entries specific to customers are made here. All programs have to evaluate these pieces of information in order that the system can be used as flexibly as possible. MPDV sets the setup during the installation and it should not be changed by the user as otherwise, errors might occur during processing. There is only one data record within the table!	
Column name	Column designation	Type	Description
abbruchgrund	DLG: Collection of termination reason	char(1)	Preassignment for terminal label and ADE-Utility J: Termination reason is supposed to be recorded N: Termination reason is not recorded (PDM field ID: HYDRA.OPT:ABBRNR)
ade_async	BDE: machine number alpha/num	char(1)	N = Numerical machine number (Default) A = Alpha-numerical machine number (PDM field ID: HYDRA.OPT:MNRFTYP)
ade_karenz_bmk	HYD: Resource perform. acc. waiting p.	smallint	Resource performance account for posting the waiting period The resource performance account, to which the waiting periods are supposed to be posted, has to be entered here if ADE waiting period processing is active. (PDM field ID: HYDRA.ADEKAR:BMKNR)
ade_karenz_verarb	HYD:ADE waiting period processing	char(1)	Activates ADE waiting period processing J: ADE waiting period processing active. Is set automatically if "K" or "A" is entered in the data field auto_pze ("PZE (in/out) controls ADE"). N: ADE waiting period processing is not active (PDM field ID: HYDRA.ADEKAR:AKTIV)
ade_karenz_zeit	HYD: Waiting period	smallint	The maximum waiting period is entered here in minutes if ADE waiting period processing is active (PDM field ID: HYDRA.ADEKAR:DAUER)
ade_plaus_kartnr	DLG: Entry of staff badges (ADE)	char(1)	Preassignment for terminal label and ADE-Utility N: badge number is not entered for ADE functions (PDM field ID: HYDRA.OPT:ADEKNRPLAUS)
afolg_nr_len	Length of the sequence	smallint	--- (PDM field ID: LEN:AFOLG)
ag_mengen	DLG:Collect. of quantities based on OPs	char(1)	Preassignment for terminal label and ADE-Utility J: The quantity produced is recorded with respect to the operation N: The quantity produced is not recorded with respect to the operation (PDM field ID: HYDRA.OPT:ERFAMENGE)
ag_nr_len	Length of the operation number	smallint	smallint, Length of the PPS operation number (PDM field ID: LEN:AGNR)
anrgkm	Posting to OP	char(40)	Waiting period processing machine Determination of OP via setup.mnrgk -> if empty overhead cost operation is "GKM<maschinennummer>" like in 6.5 in case of waiting period of machines If the overhead cost operation of the machine is available it is updated with the computed times/duration However, the overhead cost OP is not really logged on, thus there is no entry in hybuch and no status = "L" No activities (neither times nor quantities) are charged on the waiting period OP Like in 7.1 only a waiting period can be active = leading If both waiting periods are activated the waiting period of machines is leading, i.e. the waiting period of personnel does not carry out backing dating processes but only overhead cost records.

anrgkp	Posting to OP	char(40)	Waiting period processing person Determination of OP via personalstamm.anrgk -> if empty -> setup.anrgk If the person's waiting period operation is available it is updated with the computed times/duration However, the waiting period OP is not really logged on, thus there is no entry in hybuch and no status = "L" No activitiets (neither times nor quantities) are charged on the waiting period OP Like in 7.1 only a waiting period can be active = leading If both waiting periods are activated the waiting period of machines is leading, i.e. the waiting period of personnel does not carry out backing dating processes but onyl waiting period records.
auftrag_nr_len	HYD: length of order number	smallint	Length of PPS order number (PDM field ID: HYDRA.LEN:AUNR)
ausschuss	DLG:Manal entry of scrap	char(1)	Preassignment for terminal label and ADE-Utility J: Manual entry of scrap is active N: Manual entry of scrap is not active (PDM field ID: HYDRA.OPT:AUSMANU)
ausschussgrund	DLG: Collection of scrap reason	char(1)	Preassignment for terminal label and ADE utility J: Scrap reason is supposed to be recorded N: Scrap reason is not recorded (PDM field ID: HYDRA.OPT:AUSNR)
ausweis_nr_maske		char(40)	---
auto_monat_aw		char(1)	PZE: automatic evaluation of month/active by default not required in basic settings No processing (!?)
auto_pze	HYD:PZE (in/out) controls ADE	char(1)	A/K/G/N PZE controls ADE K: Person is automatically logged on to the waiting period OP when clocking-in and automatically logged off when clocking-out. The ADE waiting period processing is automatically activated. A: Clocking-out "interrupts" the order logged on but stores the orders and machines. These values are automatically "logged on" again when clocking-in the next time. There is a waiting period posting between ADE logons. The ADE waiting period processing is automatically activated. E G: A person is automatically logged off from the BDE system when clocking-out, if applicable (provided this is the last person) the OP is also interrupted. However, there is no ADE waiting period processing. N: PZE does not affect ADE. (PDM field ID: HYDRA.OPT:PZEAUTO)
barcode_nr_len	HYD: Length AUNR + AGNR + 1	smallint	Length of barcode of BDE order is allocated with HYDRA.LEN:AUNR + HYDRA.LEN:AGNR + 1 (PDM field ID: (Composed of several acronyms))

bde_kz	BDE: div.	char(100)	[1] K = customer-specific sequencing list : HYDRA.OPT:KDVLIST [2] W = Reserved [3] J = Creating unknown batches(ADE-CHV): HYDRA.OPT:UCHGEN [4] -> not assigned anymore (generation of additional partial confirmations) [5] HYDRA.BDEOPT:5 T= Rückmeldung von Teiltrückmeldungen an ein übergeordnetes PPS-System (hy6adrck) (text in setup dialog box: "Confirmation of identified scrap". If active, then [19] = "J") [6] -> not assigned anymore (suppress corerctions - now in order types) [7] -> not assigned anymore (maintenance locked for confirmed data - now in order types) [8] -> not assigned anymore (hiding break times (machine statuses from RPA 12) from labor time) [9] HYDRA.BDEOPT:9 J = Post manual quantities on MDE machine to all OPs and employees [10] HYDRA.BDEOPT:10 J = Post manual quantities on MDE machine proportionately to the employees [11] -> not assigned anymore (automatic termination of all preceding OPs - now in order types) [12] HYDRA.BDEOPT:12 J = Book time of production to MUTduring break [13] J = A log record is generated in the console function finish OP (stard dynam. dialog) N or empty = Update auftrag_status HYDRA.BDEOPT:13 [14] free [15] J = Comparison of the employee's logoff time with the rounded clocking-out time of PZE [16] J = Automatic interruption of overhead cost order OPs at individ. workplaces when a production order is logged on HYDRA.BDEOPT:16 [17] Processing of package logons HYDRA.BDEOPT:17 N = no processing of package logons E = processing of package logons according to the number of individual OPs Z = processing of package logons according to standard time of individual OPs M = processing of package logons according to default quantity of individual OP [18] Group workplace. Deactivation of the new restrictions of the orders displayed with respect to the employees logged on to the terminal Gruppenarbeitsplatz. A J=old procedure, without personnel restrictions N=new procedure, filter of persons [19] J = Editing partial quantity logons (scrap quantity and scrap reason) in the maintenance of bookings HYDRA.BDEOPT:19 [20]=Consideration of production variants when taking over OPsBerücksichtigung Fertigungsvarianten bei AG-Übernahme "E" determination "P" inspection "N"/empty - None HYDRA.BDEOPT:20 [21] J = U records are set to finished in case of erasing procedure N = All records are deleted in case of erasing procedure HYDRA.BDEOPT:21 [22] J = X/V records are set to finished in case of erasing procedure N = All records are deleted in case of erasing procedure HYDRA.BDEOPT:22 [23] HYD-ESM- System label T = ESM test system on which updates are tested and sent to productive systems afterwards P = Productive system on which updates cannot be maintained N = No system label HYDRA.BDEOPT:23 [24] HYD-IH: Prefix for automatic generation of maintenance logon number HYDRA.BDEOPT:24 [25] HYD-IH: Indicator, whether existing maintenance orders are checked in case of time logons HYDRA.BDEOPT:25 [26-27] HYD-IH: Arity for which the material number length is checked when a maintenance logon is inserted If 0 or empty, no check. HYDRA.BDEOPT:26 [28] Indicator if cost centers or responsibility areas are checked K=cons_masch (KST) V=bearb_masch (VAB) [29] Indicator if check on cost center for editing HR Master data is done N=No check on cost center R=Depending on product releases (check is performed, when at least on Product requiring it is licensed)
--------	-----------	-----------	---

			J or anything else=Check on cost center is performed (Default) [30] Indicator if the first logon of order (ADE) should be rounded as the first clock-in (PZE). [31-37]: FREE [38] HYD-IH: Sorting order "A" alphabetical or "S" key (PDM field ID: (Composed of several acronyms))
bde_pers_nr_len		smallint	smallint
bearb	Editor	char(10)	Last editor
bearb_date	Date	date	Last editing day
bearb_time	Time	integer	Last editing time
bmkn_p	BDE: RPA for planned times	smallint	RPA for planned times (PDM field ID: HYDRA.MDEKAR:BMKPLAN)
bmkn_u	BDE: RPA for unplanned times	smallint	Resource performance account to which this time (karenz_p) is supposed to be posted. (PDM field ID: HYDRA.MDEKAR:BMKNPLAN)
ereig_pflge	BDE: Maintenance based on events	char(1)	J / N: Determines whether the event maintenance is active (PDM field ID: HYDRA.OPT:EVENTEDIT)
firnen_nr	HYD:company number/system number	char(5)	When printing the staff badges the company number is set in front of the badge number The company number is checked when reading in the staff badge if this one has been defined in the system (PDM field ID: HYDRA.SYSNR)
fls_kennz	FLS:div.	char(10)	[1] Consider earliest start date (J/N) HYDRA.OPT:ADATF [2] Display of order type in planning board based onDarstellung Auftragsart in Plantafel basierend auf K: order header All operations (bars) are displayed with the order type of the order header. G: Operation: Each operation (bar) is displayed with its individual order type. HYDRA.OPT:AART [3] Resource management N: Without stock check J: With stock check B: Monitor container level HYDRA.OPT:RESMGT [4] Warning falling below M: Minimum stock level W: Warning stock level min. A: Alarm stock level min. HYDRA.OPT:RESUWG [5] Warning exceeding M: Maximum stock level W: Warning stock level max. A: Alarm stock level max. HYDRA.OPT:RESOWG [6]= Consideration of production variants in the planning "E" determination "N"/empty - none HYDRA.FLSOPT:6 (PDM field ID: (Composed of several acronyms))
gutteile	DLG:Manual entry of good parts	char(1)	Preassignment for terminal label and ADE-Utility J: Manual entry of good parts is active N: Manual entry of good parts is not active (PDM field ID: HYDRA.OPT:GUTMANU)
karenz_p	BDE: Upper waiting period	smallint	Waiting period in minutes as of which the waiting period is supposed to be posted to a separate RPA (PDM field ID: HYDRA.MDEKAR:OG)

karenz_u	BDE: Lower waiting period	smallint	Waiting period in minutes as of which waiting period OPs are supposed to be generated for a machine. (PDM field ID: HYDRA.MDEKAR:UG)
kart_nr_len	BDE: Length of staff badge	smallint	Arity of badge number (only relevant in connection with "A") (PDM field ID: HYDRA.LEN:KNR)
kernel_level	HYD: Kernel version	integer	integer (PDM field ID: HYDRA.KERNELVER)
knr_mit_pruefz	HYD: Process check digit	char(1)	Definition whether a check digit is expected or not on barcode ID cards (J/N). (PDM field ID: HYDRA.OPT:PZPLAUS)
kommt_geht_diff	PZE:Interval for clocking rec. supplem.	integer	Max. period of time for the clocking record supplement (PDM field ID: HYDRA.MAXDAUERSTEMP)
kundenummer	HYD: Customer number	decimal(18,6)	MPDV customer number which is used for checking the license (PDM field ID: HYDRA.KDNR)
mde_gen	BDE:Generation MDE logons	char(1)	J/N, whether MDE logons are supposed to be generated from ADE logons (PDM field ID: HYDRA.OPT:MDEGEN)
mde_plaus_kartnr	DLG Entry of staff badges (MDE)	char(1)	Preassignment for terminal label and ADE-Utility N: badge number is not entered for MDE functions (PDM field ID: HYDRA.OPT:MDEKNRPLAUS)
mk_karenz_verarb	BDE:Waiting period processing machine	char(1)	J: Aktiviert die Karenz-Verarbeitung für Maschinen ohne Auftrag By means of Karenz_U the duration is stated in minutes as of which a waiting period data record is supposed to be generated. This time is posted to Bmk_U. By means of Karenz_P the duration is stated in minutes as of which the waiting period is supposed to be booked to a separate resource performance account (Bmk_P). (PDM field ID: HYDRA.MDEKAR:AKTIV)
p_pers_zeiten	Synchronize labor utilization with the person's BDE shift model	char(1)	J/N: Compare labor utilization with the employee's shift model (PDM field ID: HYDRA.OPT:PDAUERSKMOD)
param_01	BDE: miscellaneous	char(10)	[1] J: [2] J: Engel coupling active: controls versatile extension in the user interface of the console EMS machine interface HYDRA.OPT:EMSAKTIV [3] J: Parallel production with different partitioning active at CTWIN terminal Identification HYDRA.OPT:MDETLG [4] J: In case of a parallel production with different partitioning the autom. quantity positing to persons and batches is effected with respect to the respective order (not yet used). [5] J: Display/determination of the point in time of the last machine status change without taking a change of shifts into account [6-7] Offset for lists after the change of shifts. The offset (time offset for lists) of a terminal is calculated from (terminal number - 1) mod 10 * x seconds. Default 0 = no offset. Identification HYDRA.OFSLST [8] J: Advanced order splitting Identification HYDRA.OPT:SPLITTEN [9,10] Internal usage (PDM field ID: (Composed of several acronyms))
param_02	BDE: misc.	char(10)	[1,4] max. waiting period in minutes: --> ID: HYDRA.ADEKAR:DAUERMAX (PDM field ID: (Composed of several acronyms))
param_03		char(10)	Customer-specific (PDM field ID: (Composed of several acronyms))
param_04	BDE:misc.	char(10)	[1] Alternative OPs: Digit in OP No. from for recognition of main OP part [2] Alternative OPs: Digit in OP No. to for recognition in main OP part [3] Alternative OPs: Digit in OP No. for recognition of alternative OP (<>0 is alternative (PDM field ID: (Composed of several acronyms))
param_05		char(10)	Customer-specific
param_06		char(10)	MPLRF: [1,1] = Goods movement mode Customer-specific

param_07	KernelSettings	char(10)	[1]J/N - Partialload at the console (J=active, N=inactive, U=cannot be controlled) [2]J/N - Ignoring the CustomDictionary at the console (J=active, N=inactive, empty=active), [3]J/N - Activate/deactivate skins (default is empty, or J, N=do not activate skins) Customer-specific (PDM field ID: (Composed of several acronyms))
param_08		char(10)	Customer-specific
param_09		char(10)	Customer-specific
param_10		char(10)	Searchstring for legic-badges (PDM field ID: HYDRA.SEARCHSTRING)
pdauer_anteilig	BDE:Ratio RPA posting in staff logon	char(1)	J : activates the ration posting of personnal RPAs in staff logons in case of multiple machine operation akt default = N (PDM field ID: HYDRA.OPT:ANTVERBPM)
pdauer_bmk_verb		char(13)	Which RPAs are posted to the labor utilization If active (pdauer_bmk_verb[1,1] = J) only statuses with the configured RPAs are posted to the labor utilization The following applies: pdauer_bmk_verb[2,2] = J = RPA 1 post to labor utilization pdauer_bmk_verb[3,3] = J = RPA 2 post to labor utilization ... pdauer_bmk_verb[13,13] = J = RPA 12 post to labor utilization
person_mengen	DLG:Collection of personal quantities	char(1)	Preassignment for terminal label and ADE-Utility J: The quantities produced are recorded with respect to persons N: The quantities produced are not recorded with respect to persons (PDM field ID: HYDRA.OPT:ERFPMENGE)
person_nr_fuell	HYD: Fill character for personnel number	char(1)	Fill character ("0" or "") for the conversion of the personnel number (PDM field ID: HYDRA.PNRFUELL)
person_nr_len	HYD: Length of personnel number	smallint	Length of the personnel number if this one is converted from INT (PZE) to CHAR (BDE). 0 = 10 becomes "10", 100 becomes "100" 6 = 10 becomes "000010", 100 becomes "000100" (PDM field ID: HYDRA.LEN:PNR)
projekt	HYD:Project name	char(10)	contains the project name and is intended for controlling particular, customer-specific processings (PDM field ID: HYDRA.PRJ)
pze_async	(free)	char(1)	Not used.
pze_kz	PZE: Some special settings	char(10)	[1] N = Clock change (daylight saving time) is not determined automatically [1] U = Clock change (daylight saving time) for USA is determined automatically [1] A = Clock change (daylight saving time) for Australia is determined automatically [2] S = Manually created and updated pairs of clockings are not automatically regarded as approved. [3] U = Treat breaks without minimal duration and without normal time as unpaid break. [4] Reserved for customer pecific processing: S/N: Workforce requirements plan: Detecting available persons depending on normal working time (N) instead of target time (S). [5] Reserved for customer pecific processing: N = PZE clock in/out controls ADE *not* for clocking of breaks P = PZE clock in/out controls ADE *only* for clocking of breaks
pze_plaus	HYD:plaus. check ADE for PZE-clock-in	char(1)	J/N/M: Plausibility check BDE for PZE clock-IN J: Plausibility check BDE for PZE clocking-in is active, i.e. an OP can only be logged on between PZE clocking-in and clocking-out N: Plausibility check BDE for PZE clocking-in is not active M: Plausibility check is activated when staff logs on and advance logons (PDM field ID: HYDRA.OPT:PZEPLAUS)
rmnr_generieren	Generate upload number using the number range	char(1)	----
rmnr_len	Length of upload number	integer	---
ruestzeit	BDE:confirmation of actual setup time	char(1)	not supported anymore as of 7.2 (PDM field ID: HYDRA.OPT:RMIRUEZ)

safo_homogen	BDE:processing collective operations	char(1)	J: COP at graphical shop floor scheduling/console with homogeneous posting (overflow) N: COP at graphical shop floor scheduling/console with inhomogeneous posting (percentage of target specification) O: COP at graphical shop floor scheduling/console with optimized posting (parts 1:1, time percentage) V: COP at BDE terminal, posting according to standard times M: COP at BDE terminal, posting according to target quantity A: COP at BDE terminal, according to the number of individual OPs (PDM field ID: HYDRA.OPT:SAG)
sap_sub_kk1	PZE:PZE as SAP subsystem	char(1)	J : SAP subsystem KK1 active (PDM field ID: HYDRA.KK1:AKTIV)
sap_sub_kk1_vers	PZE:PZE as SAP subsystem / version	decimal(18,6)	Interface version that is used 3.0: KK1 interface is used 4.5: HR-PDC interface is used (PDM field ID: HYDRA.KK1:VER)
sap_sub_kk2	BDE:BDE as SAP subsystem	char(1)	J: SAP subsystem KK2 is active (PDM field ID: HYDRA.KK2:AKTIV)
sap_sub_kk2_vers	BDE:BDE as SAP subsystem / version	decimal(18,6)	decimal(18,6) (PDM field ID: HYDRA.KK2:VER)
sap_sub_kk_kd1	KK_KD1:AKTIV	char(1)	char(1) (PDM field ID: KK_KD1:AKTIV)
sap_sub_kk_kd2	KK_KD1:AKTIV	char(1)	char(1) (PDM field ID: KK_KD1:AKTIV)
spl_nr_len	Number of splits	smallint	Number of splits (PDM field ID: LEN:SPLNR)
taegl_konto_begr	PZE: Restrict daily account	char(1)	J/N: (PDM field ID: HYDRA.OPT:TGLKTOBEGR)
uag_nr_len	Length of the sub OP number	smallint	Length of the sub OP number (PDM field ID: LEN:UAGNR)
v_list_typ	BDE:Sequencing list when logging on	char(1)	Controls the sequencing list when logging the OP on: M Machine-related sequencing list G Sequencing list based on machine groups (PDM field ID: HYDRA.OPT:VLISTMOD)
version	HYD:HYDRA version	decimal(4,2)	Version number in the format X.YY (e.g. 5.71) (PDM field ID: HYDRA.VER)
vorgabeliste	DLG: Processing with sequencing list	char(1)	Preassignment for terminal label and ADE utility (BDE console) J: Logon processes are made by means of sequencing list at the terminals N: Logon processes are made without sequencing list at the terminals (PDM field ID: HYDRA.OPT:VLIST)
vorgabezeit	BDE: Processing standard time	char(1)	N: display of duration and points in time in normal display I: display of duration and points in time in industrial minutes D: display of duration in industrial minutes (PDM field ID: HYDRA.OPT:VGZ)
waehrung	HYD: Currency unit	char(5)	char(5) (PDM field ID: HYDRA.WAEHRUNG)
wechsel_fehlgrund	PZE: Alternate clocking f. absence reas.	char(1)	char(1) Absence reason clocking automatically contains clocking-out (PDM field ID: HYDRA.OPT:WSTEMPFGR)
wechselstempelung	PZE: Processing alternate clocking	char(1)	char(1) (PDM field ID: HYDRA.OPT:WSTEMP)
zugangs_stati	ZKS: Set access status	char(1)	ZKS: Set access stati (PDM field ID: HYDRA.OPT:ZST)

5.55. software_status

Table name: software_status		Product: KERNEL	
Designation: Software status			
Column name	Column designation	Type	Description
fehler_code	Last error code	integer	Last error code
fehler_dat	last time of error	date	Last time of error
fehler_text	Last error text	char(200)	Last error text
fehler_zei	Last time of error	integer	Last time of error
name	Name of the program	char(80)	Program name without extension An index is added (separated by colon) if several programs run simultaneously
prg_comp_date	Compilation date	date	Compilation date
prg_date	Date of the program version	date	Date of the program version
prg_datei	Program file	char(250)	Program file
prg_funktion	Function description	char(250)	Function description
prg_version	Program version	char(20)	Program version
prot_dat	Logging time	date	Logging time
prot_zei	Logging time	integer	Logging time
typ	Program type	char(10)	PROGRAM: executable program LIBRARY: DLL or Shared Library HYDSCR: Hydra-Script
user_c_09		char(20)	User-specific field
user_c_10		char(40)	User-specific field
user_d_01		date	User-specific field
user_d_02		date	User-specific field
user_f_07		decimal(18,6)	User-specific field
user_f_08		decimal(18,6)	User-specific field
user_n_03		integer	User-specific field
user_n_04		integer	User-specific field
user_n_05		integer	User-specific field
user_n_06		integer	User-specific field
verweis	DB reference	serial	DB reference
zaehler	Counter of starts	integer	Counter of starts

5.56. sys_service

Table name: sys_service		Product: KERNEL	
Designation: System - services		Description: This table contains all service or task. * Notes This table is required for the usage in table sys_service_periodic_log. * Keys id (technical key) service_name (business key)	
Column name	Column designation	Type	Description
id	Technical ID	number(36)	
service_name	Service name	nvarchar2(100)	

5.57. sys_service_periodic_log

Table name: sys_service_periodic_log		Product: KERNEL	
Designation: System - time range of the last processing for a service		Description: This table contains the last processing period of an service or task. * Keys service_id (technical key) *logical connection to other tables sys_services (sys_services.id = sys_service_periodic_log.service_id)	
Column name	Column designation	Type	Description
period_from	Begin time of last processing	timestamp(3)	
period_to	End time of last processing	timestamp(3)	
service_id	Reference to service	integer	

5.58. terminal_status

Table name: terminal_status		Product: KERNEL	
Designation: Terminal status			
Column name	Column designation	Type	Description
aktiv	Active	char(1)	default = "N" (PDM field ID: TNR.AKTIV)
anz_berecht_pers	People with access authorization	smallint	BAPI: reading access only Number of persons that are authorized to access or to clock (normally, the fields BERANZ, BERDAT and BERZEI are always transferred together and in fact directly after loading the authorizations). (PDM field ID: TNR.BERANZ)
anz_daten_lokal	Number of local data records	smallint	BAPI: reading access only Number of local data records (after an offline phase) (PDM field ID: TNR.LOKANZ)
anz_subsysteme	Number of subsystems	smallint	BAPI: reading access only Number of sub systems (DS100 or LEGIC reader) (PDM field ID: TNR.SUBANZ)
anz_subsysteme_ok	Number of active subsystems	smallint	BAPI: reading access only Number of active sub systems (PDM field ID: TNR.SUBOK)
berecht_datum		date	BAPI: read access only Date when the authorizations were read the last time (PDM field ID: TNR.BERDAT)
berecht_zeit		integer	BAPI: read access only Time when the authorizations were read the last time (PDM field ID: TNR.BERZEI)
berechtigung_lesen	Reload authorizations	char(1)	Should the authorizations be reread ? This flag is reset at the next transfer of BERDAT and BERZEI. default = "N" (PDM field ID: TNR.BERLESEN)
date1		date	HYD-ALS (Arburg control system) with terminal type 111: Time stamp of the changes Standard: - free -
date2		date	HYD-ALS (Arburg control system) with terminal type 111: Time stamp of the requirement Standard: - free -
date3	Next restart	date	Next restart (PDM field ID: TNR.NEUDATN)
ip_adresse	IP address	char(20)	BAPI: only reading access (except for MBB terminals) Transfer of the IP address. A character string with 20 characters at most can be transferred (could also be the hardware address) (PDM field ID: TNR.IP)

neustart	Reboot	char(1)	Should the terminal be restarted ('J' yes or 'N' no)? This flag is reset by the terminal at the next transfer of NEUDAT and NEUZEI. default = "N" (PDM field ID: TNR.NEUSTART)
neustart_datum		date	BAPI: read access only Date of the last restart of the terminal (PDM field ID: TNR.NEUDAT)
neustart_zeit		integer	BAPI: read access only Time of the last restart of the terminal (PDM field ID: TNR.NEUZEI)
number1	Network port	integer	HYD-ALS (Arburg control system) with terminal type 111: Time stamp of the changes Standard: Port for event communication at the client -> ID: TNR.PORT:EVCOM -> KENNUNG: TNR.PORT:EVCOM (PDM field ID: TNR.PORT:EVCOM)
number2		integer	HYD-ALS (Arburg control system) with terminal type 111: Time stamp of the requirement Standard: - free -
number3	Next restart	integer	Next restart (PDM field ID: TNR.NEUZEIN)
offline_datum		date	BAPI: read access only Date of the last offline phase (PDM field ID: TNR.OFFDAT)
offline_zeit		integer	BAPI: read access only Time of the last offline phase in seconds since the beginning of the day (PDM field ID: TNR.OFFZEI)
programm_datum		date	BAPI: read access only Date when the terminal program was loaded the last time (PDM field ID: TNR.PROGDAT)
programm_laden	Reload program	char(1)	Should the terminal be reloaded? This flag is reset at the next transfer of PROGDAT and PROGZEI. default = "N" (PDM field ID: TNR.PROGLADEN)
programm_zeit		integer	BAPI: read access only Time when the terminal program was loaded the last time (PDM field ID: TNR.PROGZEI)
programmname	Program	char(20)	Program name of the terminal program or the function list (20 characters at most) In response to the terminal status the name of the program, which was transferred after having loaded the program the last time, is returned to the terminal in this field. If there is no list of the terminal programs available this program name can be used to load the program. (PDM field ID: TNR.PROG)
programmversion	Version	char(20)	BAPI: reading access only Version number of the terminal program (10 characters at most) (PDM field ID: TNR.PROGVER)
protokoll	(reserved for KERNEL)	char(1)	- Value range: 0..9 - Activates the logging of the dialog data strings in the server programs (PDM field ID: TNR.TLVL)

status	Staus	char(1)	BAPI: reading access only O=Online, F=Offline: Terminal answers within the indicated cycle "ZYKL" (see below) and is currently "Online" (no records in queue) or "Offline" (one or several records in queue) o=Online, f=Offline: Terminal does not answer cyclically but only answers when the terminal switches to the status "Online" or "Offline". (PDM field ID: TNR.STA)
status_datum		date	BAPI: read access only (PDM field ID: TNR.STADAT)
status_zeit		integer	BAPI: read access only (PDM field ID: TNR.STAZEI)
string1	(reserved for KERNEL)	char(20)	----

string2		char(20)	[1,1] J/N : J = Terminal is configured with DHCP --> ID: TNR.OPT:DHCP cannot be set by BAPI! [2,2] J/N : J = There is a conflict of terminal numbers is set if a terminal sends the terminals status with the same terminal number but with another IP address --> "Double user number" --> ID: TNR.ERR:TNRIP can only be reset by BAPI (to "N")! [3,3] J/N: HYD-ALS (Arburg control system) J = Update order list (terminal type 110) -> ID: TNR.OPT:VLISTSYN J = Update production combinations (terminal type 111) -> ID: TNR.OPT:ALSSYN [4,4] Remote maintenance empty: "", "none" V: "VNC", "VNC-Viewer" -> ID: TNR.VIEWER:TYP [5,5] Status of the remote maintenance A: activated D: deactivated... -> ID: TNR.VIEWER:STA [6,6] Command to remote maintenance A: activate D: deactivate -> ID: TNR.VIEWER:CMD [7,7] Request diagnosis files (terminal runs upload with current condition) J: execute "", N: do not execute The terminal acknowledges in the terminal status with DIAGUPLOAD=N -> ID: TNR.DIAGUPLOAD [8,8] Update inspection plan J: execute "", N: do not execute -> ID: TNR.PPSYN [9,9] MSGSYN: Escalation management, flag "messages have arrived" J: New messages are available [10,10] Type of terminal connection P: connection PDM or PCC (terminal type 141) F: terminal of other manufacturers otherwise: terminal software [11,11] Upload of INI files requirement J: execute Upload N: there is no requirement -> ID: TNR.INIUL [12,12] Download of INI files requirement J: Execute download N: there is no requirement -> ID: TNR.INIDL [13,13] Activated event communication at the client J/"": activated N: not activated -> do not establish communication to the client (to avoid timeouts) -> ID: TNR.OPT:EVCOM [14,14] Prefer MSI Installation -> reserved for future use
---------	--	----------	---

			default = "NNN DDNN " (PDM field ID: (Composed of several acronyms))
string3	(reserviert für KERNEL)	char(20)	----
terminalnr		smallint	--- (PDM field ID: TNR.TNR)
zykl_status_dauer	Cycle duration of status messages	integer	Time in seconds after that the next status message is supposed to be made default = 900 (PDM field ID: TNR.ZYKL)

5.59. terminals

Table name: terminals		Product: KERNEL	
Designation: Basic configuration of the terminal		Description: Configuration of the terminal	
Column name	Column designation	Type	Description
abteilung	Departm. in which the term. is located	char(4)	Foreman area Commentary, e.g. for evaluations (PDM field ID: TNR.ABT)
ade_plaus_kartnr	Configuration ADE badge number	char(1)	N: No input/check for person in case of ADE logons ade_plaus_kartnr : N : It is not required to enter the badge number at the terminal and it is not checked in the DB interface: (log on, log off, interrupt and partial confirmation; MP becomes MA) default = "J" (PDM field ID: TNR.PLAUS:ADEKNR)
ausweis_nr_maske	Reserved	char(40)	free
bereichsfkt_aktiv	Area function active	char(1)	Area functions active J/N default = "N" (PDM field ID: TNR.OPT:BERFKT)
cfg	Configuration flag 1	smallint	1 = Reserved for terminal 2 = Reserved for terminal 3 = Reserved for terminal 4 = Reserved 5 = Reserved for terminal 6 = Reserved 7 = Reserved 8 = Reserved for terminal default = 1 Contains the terminal class for MBB terminals (PDM field ID: TNR.CFG:1)
dialogsteuerung	Dialog control	char(10)	--- (PDM field ID: DLGSTRG)
firma	Commentary	char(2)	Commentary, e.g. for evaluations (PDM field ID: TNR.FIR)
fkt_tasten	Reserved	char(20)	free
lade_zeit	Cyclic loading time	smallint	Cyclic interval in minutes for reloading the machine label/s Buzzer terminal: buzzer interval in seconds. default = 60 (PDM field ID: TNR.ZYKLLOAD:BDE)
mde_kz	Keyboard layout	char(1)	M: activates MDE keyboard layout A: activates ADE keyboard layout Identification TNR.BART is combined with param1[1,1] (PZE active) IDs TNR.BART:ADE=J/N TNR.BART:MDE=J/N TNR.BART:PZE=J/N (PDM field ID: TNR.BART:(diverse))
mde_plaus_kartnr	Configuration MDE badge number	char(1)	N: No input/check for person in case of MDE logons mde_plaus_kartnr : N : It is not required to enter the badge number at the terminal and it is not checked in the DB interface: (assign disturbance, change target cycle+partitioning) default = "J" (PDM field ID: TNR.PLAUS:MDEKNR)

melde_art	Controlling the logon processes	char(2)	MA/MP: Control of the logon processes at the terminal melde_art: Terminals with logon type PA enable the multiple logon of orders to one machine/workplace. This option is contrary to the application of a shop floor scheduling module. The logon types MA and MP comply with the shop floor scheduling. Differences: MA: order and person are logged on separately MP: order and person are logged on together in one process default = "MA" (PDM field ID: TNR.MELDART)
neustart	Configuration flag 2	char(1)	Configuration flag II : D = Reserved N = Reserved P = Reserved V = Reserved K = Reserved W = Reserved M = Reserved I = CT511 (old version) G = Reserved S = Reserved U = Reserved W = Reserved A = Reserved (PDM field ID: TNR.CFG:2)
param1	Options 1	char(10)	[1]: Activation of the PZE functions at the MDE terminal N: PZE functions are not activated (MDE / ADE) A: PZE functions are activated (MDE / ADE / PZE) S: Only PZE functions are activated (PZE) -> Identification: TNR.BART:(diverse) --> see mde_kz [2]: Activates the SPS communication at the terminal J: SPS (programmable logic controller) as external I/O unit D: Machine interface file interface I: Internal I/O unit (511) N: No I/O unit -> Identification: TNR.MSSTYP [3, 4] Time for advance logon of staff -> Identification: TNR.PVDAUER [5]: J = Activates display in industrial minutes -> Identification: TNR.OPT:IM [6]: J = Activates batch management for ADE -> Identification: TNR.OPT:CHV -> Identification: TNR.OPT:MENGELAN [8]: J = Processing center for COPs [9] : J = ticket printing for TR/UN/AB (15.05.00 KRN) (license: ADE-TDM) -> Identification: TNR.OPT:TICKETPRN [10] : J = Logging all OPS of the order on/off (15.08.00 KRN) default = "NN30NNNNNN" (PDM field ID: (Composed of several acronyms))
param2	Options 2	char(10)	[1]: J = Activation of the sequencing list -> Identification: TNR.OPT:VLIST [2-10] Reserved default = "N" (PDM field ID: (Composed of several acronyms))

param3	Options 3	char(10)	[1] J: Query "Log all persons off" is active when logging off/interrupting the OP -> Identification: TNR.OPT:PAB [4] J: Activates COP functions -> Identification: TNR.OPT:SAG [5] J: activates COPs with quantities (not CT 51x;53x) -> Identification: TNR.OPT:SAGMENGE [6] J: activates ADE-MLB at the CT 56x/CT73x -> Identification: TNR.OPT:MLB [7] J: Activates the symbolic machine display at the CT 76x and CT 8xx N (default): [8] J: Activates ticket printing (MPL) for the collection of goods receipt batches -> Identification: TNR.OPT:CNRPRN [9] Barcode connection (for CT541) empty: no barcode (CT541) or local configuration (all CTxxx except for CT541) 0: no barcode 1: Barcode at COM1 -> Identification: TNR.COM:BAR [10] COP per person or machine (P/M) empty: per person P: per person (default) M: per machine -> Identification: TNR.OPT:SAGART default = "N NNNNN P" (PDM field ID: (Composed of several acronyms))
param4	Options 4	char(10)	[1] J: Stop at the end of the shift till OP is logged off -> Identification: TNR.OPT:AAB [2] J: Overhead cost operations in the sequencing list only -> KENNUNG: TNR.OPT:VLISTGK [3] Coupling M: Master terminal for DS100 coupling E: Engel coupling K: Krauss Maffei coupling N: None -> Identification: TNR.ZUSATZ [10] CAQ active -> Identification: TNR.BART:CAQ=J/N License: (TSW1-SPC oder TSW2-SPC) and terminal type: 8xx default = "NNN" (PDM field ID: (Composed of several acronyms))
param5	Options 5	char(10)	[1] J: Activation of the input of a scrap reason when interrupting/logging an OP off with scrap quantitiy > 0. -> Identification: TNR.OPT:AUSGR [2] J: Activation of the input of an interruption reason when interrupting/logging an OP off. -> Identification: TNR.OPT:ABBRGR [3] J: Activation of the input of quantities when logging a person off (in connection with param5[5] or param5[6]). -> Identification: TNR.OPT:PMENGE [4] J: Activation of the input of quantities when interrupting/logging an OP off (in connection with param5[5] or param5[6]). -> Identification: TNR.OPT:AMENGE [5] J: Activation of the input yield when interrupting/logging OPs and persons off (in connection with param5[3] or param5[4]). -> Identification: TNR.OPT:GUT [6] J: Activation of the input of scrap when interrupting/logging OPs and persons (in connection with param5[3] bzw. param5[4]). -> Identification: TNR.OPT:AUS [7] J: Activation of the input of the premium indicator in the dialog A_P_AN and P_AN at the CTWIN (06.08.01 KRN) -> Identification: TNR.OPT:BPOS [8] J:Activation of the input of the premium indicator in the dialog A_P_AN and P_AN at the CTWIN (06.08.01 KRN) -> Identification: TNR.OPT:LPKZ [9] -free- [10] Reserved for the transfer of the sequencing list type from setup.bde_kz[0] to the terminal default = "JJJJJJJJ " (PDM field ID: (Composed of several acronyms))

param6	Options 6	char(10)	internal
param7	Options 7	char(10)	[1] J: Activates batch management for ADE -> Identification: TNR.OPT:CHV Currently not in console internal (PDM field ID: (Composed of several acronyms))
param8	Hardware address	char(30)	Hardware address for MBB terminals. (PDM field ID: TNR.HWADR)
pdouble_01	Reserved	decimal(18,6)	internal
pdouble_02	Reserved	decimal(18,6)	internal
plaus_auftrag_art	Configuration of opt. input of order typ	char(1)	N: order type has not to be entered in the terminal dialog; terminal always sends 1 default = "N" (PDM field ID: TNR.PLAUS:AART)
plaus_maschnr	Configuration of the machine	char(1)	N: machine number has not to be entered in the terminal dialog; terminal always sends 0 default = "N" (PDM field ID: TNR.PLAUS:MNR)
plaus_stoernr	Configuration of machine status	char(1)	N: machine status has not to be entered in the terminal dialog; terminal always sends 1 default = "N" (PDM field ID: TNR.PLAUS:MST)
plauspruef	Plausibility checks	char(1)	J: Terminal always runs plausibility checks N: No plausibility checks default = "N" (PDM field ID: TNR.PLAUS:OFF)
plong_01	Reserved	integer	internal
plong_02	Reserved	integer	internal
pshort_01	Master terminal	smallint	Number of the masterterminal (PDM field ID: TNR.TNR:HAUPT)
pshort_02	Reader	smallint	Reader number of the terminal when installed as a subterminal (PDM field ID: TNR.LESER)
schichtmod	Shift model for buzzer terminal	smallint	Shift model for buzzer terminal (PDM field ID: TNR.BDEJMOD)
sprache	Language	char(3)	Language (PDM field ID: TNR.LANG)
terminalart	Terminal type	smallint	for the screen presentation and other configuration default = 840 331 = CT331 . 531 = CT531 . 732 = CT732, u.s.w. 140 = data entry server Attention: Valid values are filed in the file ObjektRefListe.dat of the console. . . (PDM field ID: TNR.ART)

terminalnr	Terminal	smallint	Device address (user number) Mandatory field (PDM field ID: TNR.TNR)
werk	Plant number for comments	char(10)	
zeitzone	Time zone	char(40)	relevant for PZE

5.60. user_setup

Table name: user_setup		Product: KERNEL	
Designation: User administration settings			
Column name	Column designation	Type	Description
acc_lo_duration	Period for blocking an account	integer	Time of blocking an account in seconds x = 0: account remains blocked until administrator breaks the blocking x > 0: account remains blocked for x seconds Comment: This can only be indicated if acc_lo_threshold is defined. DEFAULT: 1800 (30 minutes) (PDM field ID: BEARBCFG.KTOSPERRDAUER)
acc_lo_resettime	Reset counter for account block	integer	Reset counter for account block after x seconds Comment: This can only be indicated if acc_lo_threshold is defined. Counter for account block <= Period of blocking an account! DEFAULT: 1800 (30 minutes) (PDM field ID: BEARBCFG.KTOSPERRRST)
acc_lo_threshold	Threshold for blocking an account	smallint	x > 0: the account is blocked at x invalid logon attempts x = 0: account is not blocked Comment: The number of invalid logon attempts is saved in the fields - invalid_login_num (number of invalid attempts) - invalid_login_date (last invalid attempt) - invalid_login_time (last invalid attempt) in user_tab. DEFAULT: 0 (PDM field ID: BEARBCFG.KTOSPERRSCHW)
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
pwd_chars	Valid characters	char(100)	If stated only those characters may be used in a password DEFAULT: '' (PDM field ID: BEARBCFG.PWDZEICH)
pwd_log	Password chronicle	smallint	x > 0: Enforce password chronicle the same password cannot be assigned repeatedly within the last x times x = 0: No pasword chronicle Comment The last passwords are saved in user_tab_history DEFAULT: 0 (PDM field ID: BEARBCFG.PWDLOG)

pwd_max_age	Maximum age of the password	smallint	x > 0: Maximum age of the password in days x = 0: No check Comment: The last change of the password is saved in user_tab.pwd_change_date DEFAULT: 0 (PDM field ID: BEARBCFG.PWDMAXAGE)
pwd_min_len	Minimum length of the password	smallint	Minimum length of the password DEFAULT: 1 (PDM field ID: BEARBCFG.PWDMINLEN)
pwd_min_letter	Min. number of letters in password	smallint	pwd_min_letter > 0 Password must contain at least x letters Comment: pwd_min_letter + pwd_min_number + pwd_min_special <= pwd_min_len DEFAULT: 0 (PDM field ID: BEARBCFG.PWDMIN:L)
pwd_min_number	Min. number of digits in password	smallint	pwd_min_number > 0 Password must contain at least x digits Comment: pwd_min_letter + pwd_min_number + pwd_min_special <= pwd_min_len DEFAULT: 0 (PDM field ID: BEARBCFG.PWDMIN:N)
pwd_min_special	Min. number of special characters in pw	smallint	pwd_min_special > 0 Password must contain at least x special characters Comment: pwd_min_letter + pwd_min_number + pwd_min_special <= pwd_min_len DEFAULT: 0 (PDM field ID: BEARBCFG.PWDMIN:S)
pwd_options	Options	char(10)	[1,1] J=Password must not contain user name ID: BEARBCFG.OPT:1 [2,2] J=Password is case-sensitive N=Password is case-insensitive: it is changed into lower case letters ID: BEARBCFG.OPT:2 [3,3] J=exclusion of terms or character strings (e.g. computer, password...) --> please see entries with entry_type "NEGPWD" in user_tab_history ID: BEARBCFG.OPT:3 [4,4] J=The password assigned by the system administrator has to be changed by the user when logging in for the first time ID: BEARBCFG.OPT:4 (PDM field ID: BEARBCFG.OPT:*)

5.61. user_tab

Table name: user_tab		Product: KERNEL	
Designation: User administration		Description: Assignment of a password to a user. It can be accessed via the login program of the system clients.	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
entsperr	not used	char(10)	Deprecated field
entsperr_date	not used	date	Deprecated field
entsperr_time	not used	integer	Deprecated field
firma	Company	char(4)	
invalid_login_date	Date of last invalid attempt	date	Date of last invalid attempt, also see INVALID_LOGIN_NUM.
invalid_login_num	Number of invalid logon attempts	smallint	The number of invalid logon attempts is saved with the user. The time of the last invalid attempt is also saved in INVALID_LOGIN_DATE/INVALID_LOGIN_TIME so that the "reset time" (see field user_setup.acc_lo_resettime) can become active.
invalid_login_time	Time of last invalid attempt	integer	Time of last invalid attempt, also see INVALID_LOGIN_NUM.
lang	Language	char(10)	Deprecated field
lock_beg_date	Start date of the account block	date	If lock_beg_date and lock_beg_time are set it is not possible anymore to log on as of this point in time. The account is automatically blocked.
lock_beg_time	Start time of the account block	integer	If lock_beg_date and lock_beg_time are set it is not possible anymore to log on as of this point in time. The account is automatically blocked.
lock_end_date	End date of blocking the account	date	If lock_end_date and lock_end_time are set the next login is only possible as of this point in time. (PDM field ID: BEARB.LOCKDATE)
lock_end_time	End time of blocking the account	integer	If lock_end_date and lock_end_time are set the next login is only possible as of this point in time. (PDM field ID: BEARB.LOCKZEIE)
locked	Account block	char(1)	J=Account blocked if LOCK_END_DATE / LOCK_END_TIME is set the blocking will automatically be cancelled N=Account is available (PDM field ID: BEARB.LOCK)
name	Name	char(40)	Name of the user (PDM field ID: BEARB.BEZ)
password	not used	char(10)	Deprecated field
person_nr	Personnel number alpha-numeric	char(10)	
personalnummer	Personnel number	integer	
pwd	The user's password	char(32)	The user's password (crypted) (PDM field ID: BEARB.PWD)
pwd_change	Enforce change of password	char(1)	Enforce change of password J/N (PDM field ID: BEARB.PWDEDITZW)
pwd_change_date	Date of last change of password	date	(PDM field ID: (BEARB.PWDEDITDAT))
pwd_change_time	Time of the last change of password	integer	
sperr	not used	char(10)	Deprecated field
sperr_date	not used	date	Deprecated field
sperr_time	not used	integer	Deprecated field
sso_domainname	Domainname	char(255)	
sso_possible	Login with Single Sign On	char(1)	

sso_username	Username	char(255)	Windows user name
temporary_user	Temporary user	char(1)	
use_idap_roles	Use LDAP roles	char(1)	
usr	User	char(10)	Unique user name (PDM field ID: BEARB.BEARB)

5.62. user_tab_history

Table name: user_tab_history		Product: KERNEL	
Designation: Kennworthistorie			
Column name	Column designation	Type	Description
entry_type	Entry type	char(10)	Entry type "EXPPWD": Expired password "NEGPWD": Negative list (passwords that must not be used) (PDM field ID: BEARBHIST.ART)
expired_date	Password expired on	date	"EXPPWD": Date "NEGPWD": empty
expired_time	Password expired at	integer	"EXPPWD": time "NEGPWD": empty
pwd	Password	char(32)	Entry type ="EXPPWD": expired password (encrypted) Entry type="NEGPWD": terms that must not be used (plain text): %PNR.PVORNAME% %PNR.PNAME% %PNR.PNR% %PNR.KNR% %PNR.GEBDAT% (PDM field ID: BEARBHIST.PWD)
usr	User	char(10)	"EXPPWD": user name "NEGPWD": empty

5.63. vab_berechtigung

Table name: vab_berechtigung		Product: KERNEL	
Designation: Responsibility area authorization			
Column name	Column designation	Type	Description
aendern	Authorization to change	char(1)	In case of type(berechtigung_art) V only (PDM field ID: BEARBVABPROF.UPDATE)
anlage	Created by	char(10)	
anlage_date	Date when the entry was created	date	
anlage_time	Time when the entry was created	integer	
anlegen	Authorization to create	char(1)	In case of type(berechtigung_art) V only (PDM field ID: BEARBVABPROF.INSERT)
anzeigen	Authorization to view	char(1)	In case of type(berechtigung_art) V only (PDM field ID: BEARBVABPROF.SELECT)
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
berechtigung	not used	char(10)	not active
berechtigung_art	Type of authorization	char(1)	V = responsibility area P = responsibility profile (PDM field ID: BEARBVABPROF.ART)
berechtigung_wert	Responsibility profile/area	char(15)	Responsibility area or responsibility profile according to the field berechtigung_art. (PDM field ID: BEARBVABPROF.WERT)
loeschen	Authorization to delete	char(1)	In case of type(berechtigung_art) V only (PDM field ID: BEARBVABPROF.DELETE)
usr	User	char(10)	User who is authorized (PDM field ID: BEARBVABPROF.BEARB:VAB)
verweis	Data record number	serial	Data record number
verwenden	Authorization to use	char(1)	In case of type(berechtigung_art) V only (PDM field ID: BEARBVABPROF.USE)

5.64. vab_profil

Table name: vab_profil		Product: KERNEL	
Designation: Responsibility area profiles			
Column name	Column designation	Type	Description
aendern	Authorization to change	char(1)	(PDM field ID: VABPROF.UPDATE)
anlage	Created by	char(10)	
anlage_date	Date when the entry was created	date	
anlage_time	Time when the entry was created	integer	
anlegen	Authorization to create	char(1)	(PDM field ID: VABPROF.INSERT)
anzeigen	Authorization to view	char(1)	(PDM field ID: VABPROF.SELECT)
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
berechtigung	Reserved	char(10)	for future use
loeschen	Authorization to delete	char(1)	(PDM field ID: VABPROF.DELETE)
verantw_bereich	Responsibility area	char(15)	(PDM field ID: VABPROF.VAB)
verantw_profil	Responsibility profile	char(15)	(PDM field ID: VABPROF.VABPROF)
verweis	Data record number	serial	(PDM field ID: VABPROF.VERWEIS)
verwenden	Authorization to use	char(1)	(PDM field ID: VABPROF.USE)

5.65. vab_tab

Table name: vab_tab		Product: KERNEL	
Designation: Responsibility areas		Description: # Note The contents of the table vab_tab are automatically generated by the system from the responsibility profiles and the individual areas of responsibility. The content comes from the tables vab_authorization and vab_profil. The system automatically resolves the responsibility profiles for the contents of table vab_tab. Furthermore, the default responsibility area "--DEFAULT--" is automatically added for each user. Always change the tables vab_authorization and vab_profile only via the respective API functions. Never change the tables vab_authorization and vab_profil directly at database level, since the contents of table vab_tab are not updated automatically if you access them directly from the database.	
Column name	Column designation	Type	Description
aendern	Authorization to change	char(1)	
anlegen	Authorization to create	char(1)	
anzeigen	Authorization to view	char(1)	
bearb	Last editor	char(10)	
bearb_date	Last editing date	date	
bearb_time	Last editing time	integer	
berechtigung	Reserved	char(10)	for future use
loeschen	Authorization to delete	char(1)	
usr	User	char(10)	
verantw_bereich	Responsibility area	char(15)	
verwenden	Authorization to use	char(1)	

6. LLE

6.1. lle_lart_regel

Table name: lle_lart_regel		Product: LLE	
Designation: LLE Rules for wage type determination		Description: Rule to determine the wage type of time tickets in LLE	
		# Notes -	
		# Keys 1) verweis	
		# logical connection to other tables lohnarten, personen/personalstamm	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	(PDM field ID: LARTBEST.BEARB)
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung	Comment	char(100)	Comment for a rule (PDM field ID: LARTBEST.BEM)
bezug1	Type of reference 1	char(20)	Type of reference 1 (PDM field ID: LARTBEST.BZG:1)
bezug2	Type of reference 2	char(20)	Type of reference 2 (PDM field ID: LARTBEST.BZG:2)
bezug3	Type of reference 3	char(20)	Type of reference 3 (PDM field ID: LARTBEST.BZG:3)
bezug4	Type of reference 4	char(20)	Type of reference 4 (PDM field ID: LARTBEST.BZG:4)
bezug5	Type of reference 5	char(20)	Type of reference 5 (PDM field ID: LARTBEST.BZG:5)
datum_bis	Valid to	date	Valid to (PDM field ID: LARTBEST.DATE)
datum_von	Valid from	date	Valid from (PDM field ID: LARTBEST.DATB)
lart	Wage type to be assigned	char(4)	Wage type to be assigned (PDM field ID: LARTBEST:LART)
lart_quelle	Source of destination wage type	char(1)	Source of destination wage type: F=fix, se column LART M=from the log record P=from employee record A=from ADE operation (PDM field ID: LARTBEST.QUELLE)
reihenfolge	Order	integer	Controls the sequence in which the rules are processed. (PDM field ID: LARTBEST.ORDER)
verweis	Reference	serial	Reference (PDM field ID: LARTBEST.VERWEIS)

wert1	Reference value 1	char(20)	Reference value 1 (PDM field ID: LARTBEST.WERT:1)
wert2	Reference value 2	char(20)	Reference value 2 (PDM field ID: LARTBEST.WERT:2)
wert3	Reference value 3	char(20)	Reference value 3 (PDM field ID: LARTBEST.WERT:3)
wert4	Reference value 4	char(20)	Reference value 4 (PDM field ID: LARTBEST.WERT:4)
wert5	Reference value 4	char(20)	Reference value 4 (PDM field ID: LARTBEST.WERT:5)

6.2. lle_leist_grp

Table name: lle_leist_grp		Product: LLE	
Designation: Definition of premium groups		Description: Master data of premium groups	
		# Notes -	
		# Keys 1) leistgrp,gueltig_von,gueltig_bos 2) verweis	
		# logical connection to other tables lle_leistgrp_tag, lle_leistgrp_zuord, lle_tls_ag via leistgrp and date.	
Column name	Column designation	Type	Description
abrech_periode	Definition of payroll period	char(3)	T=Days W=Weeks M=Calendar months NOT YET PROCESSED
akkord_art	Type of premium group	char(1)	L=Incentive bonus N=Bonus for rate of capacity utilization of machines B=Premium Area I=Inactive (is intended to "eliminate" a remuneration group one day) Else: Alternative Types (PDM field ID: LEISTGRP.PRKZ)
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Long designation	char(20)	--- (PDM field ID: LEISTGRP.BEZL)
gueltig_bis	Valid to	date	)* is set internally by BAPI (PDM field ID: LEISTGRP.DATE*)
gueltig_von	Valid from	date	--- (PDM field ID: LEISTGRP.DATB)
kurzbez	Short designation	char(6)	--- (PDM field ID: LEISTGRP.BEZX)
leistgrp	Premium group	char(8)	--- (PDM field ID: LEISTGRP.LEISTGRP)
leistgrp_entl	reserved	char(8)	---
leistgrp_reserve01	reserved	char(20)	---
leistgrp_reserve02	reserved	char(20)	---
leistgrp_reserve03	reserved	char(20)	---
leistgrp_reserve04	reserved	decimal(18,6)	---
leistgrp_reserve05	reserved	decimal(18,6)	---
leistgrp_reserve06	reserved	decimal(18,6)	---
lohnart	reserved	char(4)	for future use (PDM field ID: LEISTGRP.LART)

pr_modus_01	Control indicator for the calculation of	char(10)	Available as of approx. 04/2003 (PDM field ID: LEISTGRP.PRMOD:01)
pr_modus_02	Control indicator for the calculation of	char(10)	--- (PDM field ID: LEISTGRP.PRMOD:02)
pr_modus_03	Control indicator for the calculation of	char(10)	--- (PDM field ID: LEISTGRP.PRMOD:03)
pr_modus_04	Control indicator for the calculation of	char(10)	--- (PDM field ID: LEISTGRP.PRMOD:04)
pr_modus_05	Control indicator for the calculation of	char(10)	--- (PDM field ID: LEISTGRP.PRMOD:05)
pr_nr	Premium scheme	smallint	Number of the premium scheme in case of incentive wages based on formulas as of approx. 04/2003 (PDM field ID: LEISTGRP.PRNR)
pr_wert_1	Premium parameter 1	decimal(18,6)	Available as of approx. 04/2003 (PDM field ID: LEISTGRP.PRWERT:01)
pr_wert_10		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:10)
pr_wert_11		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:11)
pr_wert_12		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:12)
pr_wert_13		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:13)
pr_wert_14		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:14)
pr_wert_15		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:15)
pr_wert_16		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:16)
pr_wert_17		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:17)
pr_wert_18		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:18)
pr_wert_19		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:19)
pr_wert_2	Premium parameter 2	decimal(18,6)	Available as of approx. 04/2003 (PDM field ID: LEISTGRP.PRWERT:02)
pr_wert_20		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:20)
pr_wert_21		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:21)
pr_wert_22		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:22)
pr_wert_23		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:23)
pr_wert_24		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:24)
pr_wert_25		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:25)
pr_wert_26		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:26)
pr_wert_27		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:27)
pr_wert_28		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:28)

pr_wert_29		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:29)
pr_wert_3	Premium parameter 3	decimal(18,6)	Available as of approx. 04/2003 (PDM field ID: LEISTGRP.PRWERT:03)
pr_wert_30		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:30)
pr_wert_4	Premium parameter 4	decimal(18,6)	Available as of approx. 04/2003 (PDM field ID: LEISTGRP.PRWERT:04)
pr_wert_5	Premium parameter 5	decimal(18,6)	Available as of approx. 04/2003 (PDM field ID: LEISTGRP.PRWERT:05)
pr_wert_6		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:06)
pr_wert_7		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:07)
pr_wert_8		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:08)
pr_wert_9		decimal(18,6)	(PDM field ID: LEISTGRP.PRWERT:09)
prioritaet	reserved	smallint	For future assignments of remuneration groups to machines, people and orders, the priority can control which remuneration group takes priority. Not yet processed. (PDM field ID: LEISTGRP.PRIO)
tr_einmalig	reserved	char(1)	Flag (J/N) whether tr is respectively to be assigned to only the first logon of order or person in case of an order (PDM field ID: LEISTGRP.OPT:TREINMALIG)
verantw_bereich	responsibility area	char(15)	--- (PDM field ID: LEISTGRP.VAB)
verweis	Number of data record	serial	--- (PDM field ID: LEISTGRP.VERWEIS)
vorgabe_1_di	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGDI:01)
vorgabe_1_do	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGDO:01)
vorgabe_1_fr	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGFR:01)
vorgabe_1_mi	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGMI:01)
vorgabe_1_mo	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGMO:01)
vorgabe_1_sa	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGSA:01)
vorgabe_1_so	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGSO:01)
vorgabe_2_di	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGDI:02)
vorgabe_2_do	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGDO:02)
vorgabe_2_fr	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGFR:02)
vorgabe_2_mi	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGMI:02)
vorgabe_2_mo	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGMO:02)
vorgabe_2_sa	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGSA:02)
vorgabe_2_so	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGSO:02)

vorgabe_3_di	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGDI:03)
vorgabe_3_do	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGDO:03)
vorgabe_3_fr	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGFR:03)
vorgabe_3_mi	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGMI:03)
vorgabe_3_mo	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGMO:03)
vorgabe_3_sa	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGSA:03)
vorgabe_3_so	Specifications based on weekdays	decimal(18,6)	--- (PDM field ID: LEISTGRP.VORGSO:03)
vorgabe_4_di	Specifications based on weekdays	char(10)	--- (PDM field ID: LEISTGRP.VORGDI:04)
vorgabe_4_do	Specifications based on weekdays	char(10)	--- (PDM field ID: LEISTGRP.VORGDO:04)
vorgabe_4_fr	Specifications based on weekdays	char(10)	--- (PDM field ID: LEISTGRP.VORGFR:04)
vorgabe_4_mi	Specifications based on weekdays	char(10)	--- (PDM field ID: LEISTGRP.VORGMI:04)
vorgabe_4_mo	Specifications based on weekdays	char(10)	--- (PDM field ID: LEISTGRP.VORGMO:04)
vorgabe_4_sa	Specifications based on weekdays	char(10)	--- (PDM field ID: LEISTGRP.VORGSA:04)
vorgabe_4_so	Specifications based on weekdays	char(10)	--- (PDM field ID: LEISTGRP.VORGSO:04)

6.3. lle_leistberzuord

Table name: lle_leistberzuord		Product: LLE	
Designation: Assignment Premium groups to prem. areas		Description: This table is used to assign premium groups to premium areas. # Keys Primary unique: verweis Secondary unique: leistgrp + leistber +gueltig_von # logical connection to other tables 1) lle_leistberzuord.leistgrp = lle_leist_grp.leistgrp and lle_leistberzuord.gueltig_bis between lle_leist_grp.gueltig_von and lle_leist_grp.gueltig_bis 2) lle_leistberzuord.leistber = lle_leist_grp.leistgrp and lle_leistberzuord.gueltig_bis between lle_leist_grp.gueltig_von and lle_leist_grp.gueltig_bis	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
customer_01	Customer field 1	char(100)	(PDM field ID: LEISTBERZUORD.CUSTOMER:1)
customer_02	Customer field 2	char(100)	(PDM field ID: LEISTBERZUORD.CUSTOMER:2)
customer_03	Customer field 3	char(100)	(PDM field ID: LEISTBERZUORD.CUSTOMER:3)
customer_04	Customer field 4	float	(PDM field ID: LEISTBERZUORD.CUSTOMER:4)
customer_05	Customer field 5	float	(PDM field ID: LEISTBERZUORD.CUSTOMER:5)
customer_06	Customer field 6	float	(PDM field ID: LEISTBERZUORD.CUSTOMER:6)
gueltig_bis	Valid to	date	(PDM field ID: LEISTBERZUORD.DATE)
gueltig_von	Valid from	date	(PDM field ID: LEISTBERZUORD.DATB)
leistber	Premium area	char(8)	A premium aria is a special kind of premium group, where the type of remuneration group is "B" for german "Bereich"="Area". (PDM field ID: LEISTBERZUORD.LEISTBER)
leistgrp	Premium Group.	char(8)	(PDM field ID: LEISTBERZUORD.LEISTGRP)
verweis	Unique record number.	serial	(PDM field ID: LEISTBERZUORD.VERWEIS)

6.4. lle_leistgrp_tag

Table name: lle_leistgrp_tag		Product: LLE	
Archive table: a lle_leistgrp_tag			
Designation: Premium groups of work day results		Description: This table contains the daily results of premium groups. Join into the premium groups via lle_leistgrp_tag lgt lle_leist_grp lg lgt.leistgrp = lg.leistgrp lgt.aw_tag between lg.gueltig_von and lg.gueltig_bis	
Column name	Column designation	Type	Description
archiv		char(1)	
ausfall_zeit	Authorized downtime	integer	Approved inactive period
aw_eforderlich	Recalculation required	char(1)	J: Day has to be recalculated for this remuneration group Otherwise: - Not yet processed
aw_tag	Day of evaluation	date	Day of evaluation
bearb	Modified by	char(10)	
bearb_date	Last editing day	date	Last editing day
bearb_time	Modified time	integer	
dauer	Total processing duration	integer	Total processing duration
erstell_datum	Creation date	date	Date on which the data record was calculated
erstell_zeit	Creation time	integer	Point in time of calculating the data
gk_zeiten	Time on OC orders	integer	---
gutschrift_zeit	Premium result of credited time	integer	in seconds
leistgrp	Premium group	char(8)	Remuneration group
leistungsgrad	Computed performance rate	float	Computed performance rate
prkto_01	Premium account	decimal(18,6)	---
prkto_02	Premium account	decimal(18,6)	---
prkto_03	Premium account	decimal(18,6)	---
prkto_04	Premium account	decimal(18,6)	---
prkto_05	Premium account	decimal(18,6)	---
prkto_06	Premium account	decimal(18,6)	---
prkto_07	Premium account	decimal(18,6)	---
prkto_08	Premium account	decimal(18,6)	---
prkto_09	Premium account	decimal(18,6)	---
prkto_10	Premium account	decimal(18,6)	---
prkto_11	Premium account	decimal(18,6)	---
prkto_12	Premium account	decimal(18,6)	---
prkto_13	Premium account	decimal(18,6)	---
prkto_14	Premium account	decimal(18,6)	---
prkto_15	Premium account	decimal(18,6)	---
prkto_16	Premium account	decimal(18,6)	---
prkto_17	Premium account	decimal(18,6)	---
prkto_18	Premium account	decimal(18,6)	---

prkto_19	Premium account	decimal(18,6)	---
prkto_20	Premium account	decimal(18,6)	---
prkto_21		decimal(18,6)	
prkto_22		decimal(18,6)	
prkto_23		decimal(18,6)	
prkto_24		decimal(18,6)	
prkto_25		decimal(18,6)	
prkto_26		decimal(18,6)	
prkto_27		decimal(18,6)	
prkto_28		decimal(18,6)	
prkto_29		decimal(18,6)	
prkto_30		decimal(18,6)	
prkz_01	Premium result flag 1	char(20)	---
prkz_02	Premium result flag 2	char(20)	---
prkz_03	Premium result flag 3	char(20)	---
prkz_04	Premium result flag 4	char(20)	---
prkz_05	Premium result flag 5	char(20)	---
rueckgemeldet	Uploaded	char(1)	Flag (J/N) whether the data record has been confirmed
rueckmelde_datum	Upload date	date	---
rueckmelde_zeit	Upload time	integer	---
unprod_zeit	Non-productive time	integer	---
verweis		serial	
vorgabe_zeit	Standard time	integer	Standard time
warte_zeit	Premium result of waiting time	integer	in seconds
zuschlaege	Bonus and deduction	integer	Bonus and deduction

6.5. lle_istgrp_zuord

Table name: lle_istgrp_zuord		Product: LLE	
Designation: Assignment of premium group to machine		Description: The table has so far exclusively been used to assign machines to premium groups.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
key	key	char(40)	Machine, person, order, please see key_typ field. Acronym: For type M: LEISTGRPZUORD.MNR (Assignment of a premium group to a machine) (PDM field ID: LEISTGRPZUORD.MNR)
key_typ	Type of the key	char(1)	M=Machine [P=Person] [A=Order] So far only M is processed (PDM field ID: LEISTGRPZUORD.KEY)
lstgrp	Premium group	char(8)	--- (PDM field ID: LEISTGRPZUORD.LEISTGRP)

6.6. lle_pnr_tag

Table name: lle_pnr_tag		Product: LLE	
Archive table: a lle_pnr_tag			
Designation: Daily results of persons for incentive		Description: This table contains the daily results of persons for incentive wages.	
		# Notes Table is available with LLE 7.2.	
		# Keys 1) personalnummer, datum 2) verweis	
		# logical connection to other tables Join to personen via personalnummer and datum between gueltig_von and gueltig_bis	
Column name	Column designation	Type	Description
ade_datb	Date of earliest logon of person in ADE	date	Date of earliest logon of person in ADE
ade_date	Date of latest logoff of person in ADE	date	Date of latest logoff of person in ADE
ade_dauer	Duration of operation-related result record of person	decimal(18,6)	Duration of operation-related result record of person
ade_sowib	reserved	char(1)	reserved
ade_sowie	reserved	char(1)	reserved
ade_zeib	Time of earliest logon of person in ADE	integer	Time of earliest logon of person in ADE
ade_zeie	Time of latest logoff of person in ADE	integer	Time of latest logoff of person in ADE
adepzeab_erf	Match ADE/PZE required	char(1)	Reserved for customer solutions. J: ADE data has to be matched to PZE data (again). N: No matching required D: (tmporarily) person is temporarily deferred, matching will be retried.
archiv	data set is archived	char(1)	J: Data is in archive table
aw_pan_erf	reserved	char(1)	reserved
aw_pln_erf	Recalculation required	char(1)	J: Recalculation of incentive wage of the person of this day is required. else: Nothing to do.
bearb_usr	User number of last recalcualation	integer	User number of last recalcualation
berechn_bearb	User of last recalcualation	char(10)	User of last recalcualation
berechn_date	Date of last recalcualation	date	Date of last recalcualation
berechn_time	Time of last recalcualation	integer	Time of last recalcualation
datum	Date	date	Date
firma	Company	char(4)	Company
ist_dauer	Total processing duration	decimal(18,6)	Total processing duration
leistung	Computed performance rate	decimal(18,6)	Computed performance rate
leistung_max	Max. computed performance rate of day	decimal(18,6)	Max. computed performance rate of day
leistung_min	Min. computed performance rate of day	decimal(18,6)	Min. computed performance rate of day
lle_dauer	Duration of daily time tickets	decimal(18,6)	Duration of daily time tickets
person_nr	Person (alphanumeric version)	char(10)	Person (alphanumeric version)
personalnummer	Personnel number	integer	Person
prkto_01	Premium account	decimal(18,6)	Premium account

prkto_02	Premium account	decimal(18,6)	Premium account
prkto_03	Premium account	decimal(18,6)	Premium account
prkto_04	Premium account	decimal(18,6)	Premium account
prkto_05	Premium account	decimal(18,6)	Premium account
prkto_06	Premium account	decimal(18,6)	Premium account
prkto_07	Premium account	decimal(18,6)	Premium account
prkto_08	Premium account	decimal(18,6)	Premium account
prkto_09	Premium account	decimal(18,6)	Premium account
prkto_10	Premium account	decimal(18,6)	Premium account
prkto_11	Premium account	decimal(18,6)	Premium account
prkto_12	Premium account	decimal(18,6)	Premium account
prkto_13	Premium account	decimal(18,6)	Premium account
prkto_14	Premium account	decimal(18,6)	Premium account
prkto_15	Premium account	decimal(18,6)	Premium account
prkto_16	Premium account	decimal(18,6)	Premium account
prkto_17	Premium account	decimal(18,6)	Premium account
prkto_18	Premium account	decimal(18,6)	Premium account
prkto_19	Premium account	decimal(18,6)	Premium account
prkto_20	Premium account	decimal(18,6)	Premium account
prkto_21	Premium account	decimal(18,6)	Premium account
prkto_22	Premium account	decimal(18,6)	Premium account
prkto_23	Premium account	decimal(18,6)	Premium account
prkto_24	Premium account	decimal(18,6)	Premium account
prkto_25	Premium account	decimal(18,6)	Premium account
prkto_26	Premium account	decimal(18,6)	Premium account
prkto_27	Premium account	decimal(18,6)	Premium account
prkto_28	Premium account	decimal(18,6)	Premium account
prkto_29	Premium account	decimal(18,6)	Premium account
prkto_30	Premium account	decimal(18,6)	Premium account
prkz_01	Premium attribute	char(20)	Premium account
prkz_02	Premium attribute	char(20)	Premium account
prkz_03	Premium attribute	char(20)	Premium account
prkz_04	Premium attribute	char(20)	Premium account
prkz_05	Premium attribute	char(20)	Premium account
pze_dauer	Duration from PZE	decimal(18,6)	Duration from PZE
soll_dauer	Sum of production time target	decimal(18,6)	Sum of production time target
verweis	Data record number	serial	Data record number

6.7. lle_tls

Table name: lle_tls		Product: LLE	
Designation: Daily time tickets without OP reference OBSOLETE		Description: Warning: ----- With LLE 7.2 this table is obsolete. ----- The data is transferred to table lle_tls_ag! -----	
Column name	Column designation	Type	Description
anz_meld	Number of messages	smallint	Number of messages that have been compressed
ap_verweis		integer	---
ausf_kostenstelle		char	---
bearb	Modified by	char	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung		char	---
bm_k_nr		smallint	---
datum	Date	date	Date of time ticket
dauer	Duration	integer	Actual duration (as sum of actual times)
erstell_date		date	---
erstell_time		integer	---
geloescht		char	---
kostenstelle		char	---
leistgrp		char	---
lohnart	Wage type	char	Wage type Time wage Practice Overhead costs Waiting period
lohngruppe		char	---
masch_nr		char	---
person	personnel number	char	Person (receiving the bonus)
prkto_01		decimal(18,6)	---
prkto_02		decimal(18,6)	---
prkto_03		decimal(18,6)	---
prkto_04		decimal(18,6)	---
prkto_05		decimal(18,6)	---
prkto_06		decimal(18,6)	---
prkto_07		decimal(18,6)	---
prkto_08		decimal(18,6)	---
prkto_09		decimal(18,6)	---
prkto_10		decimal(18,6)	---
prkz_01		char	---
prkz_02		char	---

prkz_03		char	---
prkz_04		char	---
prkz_05		char	---
referenz_nr		char	---
reserve1	reserve	char	---
reserve2	reserve	integer	---
reserve3	reserve	date	---
rueckgemeldet	Upload flag	char	J (Yes) /N (No)
rueckmeldedatum		date	---
schicht_dat		date	---
schichtr		smallint	---
verweis	Reference	serial	Unique reference
vorgabe_zeit	Sum of production time target te	integer	$m \cdot te + tr / m \cdot te$
zeitart	Time type	char	ID of time type GK overhead costs ZL time wage EA practice PZE attendance
zuschlaege	Sum of bonuses/deductions	integer	Sum of bonuses and deductions

6.8. lle_tls_ag

Table name: lle_tls_ag		Product: LLE	
Archive table: a lle_tls_ag			
Designation: Daily time tickets with OP reference		Description: This Table is used to store time tickets.	
		# Notes Data is generatet and maintained by wage calculation.	
		# Keys 1) Primary unique: verweis 2) person, datum	
		# logical connection to other tables 1) lle_tls_ag.person = personen.person_nr_char and lle_tls_ag.datum between person.gueltig_von and person.gueltig_bis 2) Outer Join: lle_tls.lohnart = lohnarten.lohnart 3) Outer Join: lle_tls_ag.leistgrp = lle_leist_grp.leistgrp 4) Outer Join: lle_tls_ag.auftrag_nr = auftrags_bestand.auftrag_nr	
Column name	Column designation	Type	Description
anz_meld	Number of messages	smallint	Number of messages that have been compressed
ap_verweis	Reference to original posting	integer	Not always filled out
archiv	archive flag	char(1)	J: data set is archived.
auftrag_nr	Order	char(40)	Order number
ausf_kostenstelle	Operating cost center	char(10)	The person's cost center (master cost center)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung	reserved	char(50)	
bm_k_nr	Number of RPA	smallint	In case of time-related time tickets from piecework processing
datum	Date	date	Date of time ticket
datum_bis	Logoff date	date	
datum_von	Logon date	date	!
dauer	Duration	integer	Actual duration (as sum of actual times)
erstell_date	Time of saving within database	date	---
erstell_time	Time of saving within database	integer	---
geloescht	Reserved for deletion flag	char(1)	---
genehmigender	Approver	char(10)	---
grund	Bonus reason	integer	Bonus/deduction reason
kostenstelle	cost center	char(10)	---
leistgrp	Premium group	char(8)	---
lohnart	Wage type	char(4)	Piecework, bonuses, deductions
lohngruppe	Wage group	char(4)	---

masch_nr	Machine number	char(20)	---
p_ausschuss	Scrap	decimal(18,6)	Scrap produced
p_menge	Quantity for wage calculation	decimal(18,6)	Quantity for wage calculation
p_nacharb	Rework quantity	decimal(18,6)	Rework quantity
p_problem	Problem quantity	decimal(18,6)	Problem quantity
p_stueck	Number of pieces	decimal(18,6)	Yield produced
person	Personnel number	char(10)	Personnel number
prkto_01	Premium account	decimal(18,6)	---
prkto_02	Premium account	decimal(18,6)	---
prkto_03	Premium account	decimal(18,6)	---
prkto_04	Premium account	decimal(18,6)	---
prkto_05	Premium account	decimal(18,6)	---
prkto_06	Premium account	decimal(18,6)	---
prkto_07	Premium account	decimal(18,6)	---
prkto_08	Premium account	decimal(18,6)	---
prkto_09	Premium account	decimal(18,6)	---
prkto_10	Premium account	decimal(18,6)	---
prkto_11	Premium account	decimal(18,6)	
prkto_12	Premium account	decimal(18,6)	
prkto_13	Premium account	decimal(18,6)	
prkto_14	Premium account	decimal(18,6)	
prkto_15	Premium account	decimal(18,6)	
prkto_16	Premium account	decimal(18,6)	
prkto_17	Premium account	decimal(18,6)	
prkto_18	Premium account	decimal(18,6)	
prkto_19	Premium account	decimal(18,6)	
prkto_20	Premium account	decimal(18,6)	
prkto_21	Premium account	decimal(18,6)	
prkto_22	Premium account	decimal(18,6)	
prkto_23	Premium account	decimal(18,6)	
prkto_24	Premium account	decimal(18,6)	
prkto_25	Premium account	decimal(18,6)	
prkto_26	Premium account	decimal(18,6)	
prkto_27	Premium account	decimal(18,6)	
prkto_28	Premium account	decimal(18,6)	
prkto_29	Premium account	decimal(18,6)	
prkto_30	Premium account	decimal(18,6)	
prkz_01	Premium attribute	char(20)	---
prkz_02	Premium attribute	char(20)	---
prkz_03	Premium attribute	char(20)	---
prkz_04	Premium attribute	char(20)	---
prkz_05	Premium attribute	char(20)	---
referenz_nr	reference number	char(20)	Customer-specific use
reserve1	reserve1	char(20)	General reference number -Standard: Machine no. (masch_nr)

reserve2	reserve2	integer	- Standard resource performance account
reserve3	reserve3	date	Date on which the piecework time ticket is generated
rueckgemeldet	Upload flag	char(1)	J/N For special interfaces only
rueckmeldedatum	Date of the upload	date	For special interfaces only
schicht_dat	Shift date from ADE log	date	---
schichtnr	Shift number from ADE log	smallint	---
soll_stck	Reserved for target quantity	decimal(18,6)	---
soll_te	Target production time per piece te	decimal(18,6)	Premium specification: te (sec. per 1000 pieces) LLE (person)
soll_teb	Premium specification: teb	decimal(18,6)	Premium specification: te (sec. per 1000 pieces) LLE (ressource)
soll_tr	Target setup time	decimal(18,6)	Planned specification for setup time (max. for several records) (person)
soll_trb	Premium specification: tr	decimal(18,6)	Premium specification: tr LLE (resources)
verweis	Data record number	serial	---
vorgabe_zeit	Sum of production time target	integer	$m*te + tr / m*te$
zeit_bis	Logoff time	integer	
zeit_von	Logon time	integer	
zeitart	Time type	char(3)	ID of time type AKK: Piecework ZUS: Bonus/deduction
zeitgrad	Result: Labor utilization rate	decimal(18,6)	---
zuschlaege	Sum of bonuses/deductions	integer	Summe der Zu- u. Abschläge

6.9. lle_zuschlaege

Table name: lle_zuschlaege		Product: LLE	
Archive table: a lle_zuschlaege			
Designation: LLE bonuses		Description: The table contains the bonuses and deductions recorded on the console.	
Column name	Column designation	Type	Description
archiv		char(1)	
auftrag_nr	Order number	char(40)	--- (PDM field ID: ZUSCHL.ANR)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung	reserved	char(50)	for future use
certify_flag		char(1)	Subject to authorization "J"/otherwise (PDM field ID: ZUSCHL.CERTIFY)
datum	Time for bonus assignment	date	--- (PDM field ID: ZUSCHL.DAT)
dauer	Value	integer	Bonus time (positive) or deduction time (negative) (PDM field ID: ZUSCHL.DAUER)
ein_h_dauer		char(3)	Reserved: Unit of the "duration". Thus, other factors than times should also be able to be recorded
genehmigender	Approver	char(10)	Approver (user ID) (PDM field ID: ZUSCHL.BEARB:SIGN)
leistgrp		char(8)	Premium group (PDM field ID: ZUSCHL.LEISTGRPG)
masch_nr		char(20)	for future use
menge	Quantity	decimal(18,6)	If the bonus is recorded relatively the quantity used for the calculation is entered here. In spite of that, the dauer field has to contain the total bonus time. (PDM field ID: ZUSCHL.ANZ:ANZ)
person_nr_char		char(10)	This column is automatically assigned to the formatted BDE personnel number during collection. (PDM field ID: [ZUSCHL.PNR])
personalnummer	personnel number	integer	--- (PDM field ID: ZUSCHL.PNR)
sign_flag		char(1)	Approval: J: Authorized A: Refused N+otherwise: not yet processed (PDM field ID: ZUSCHL.SIGN)
user_c_09		char(20)	User-specific field
user_c_10		char(40)	User-specific field
user_d_01		date	User-specific field
user_d_02		date	User-specific field
user_f_07		decimal(18,6)	User-specific field
user_f_08		decimal(18,6)	User-specific field
user_n_03		integer	User-specific field
user_n_04		integer	User-specific field
user_n_05		integer	User-specific field

user_n_06		integer	User-specific field
verweis	No. of data record	serial	--- (PDM field ID: ZUSCHL.VERWEIS)
zeit	Time for bonus assignment	integer	--- (PDM field ID: ZUSCHL.ZEI)
zuschl_te		decimal(18,6)	In case of relative bonuses - time per piece as te. (As seconds per x pieces) (PDM field ID: ZUSCHL.ANZ:DAUER)
zuschlag_nr	Bonus reason	integer	Bonus reason. Reference in zuschlags_kfg.zuschlag_nr table (PDM field ID: ZUSCHL.ZUSCHLGR)

6.10. llesetup

Table name: llesetup		Product: LLE	
Designation: LLE-General settings		Description: General settings for wage calculation.	
Column name	Column designation	Type	Description
abg_rueck	Transfer validated data records only	char(1)	LLE 7.2: Obsolete! Transfer validated data records from ADE logs only. J/N default N. (PDM field ID: LLE.OPT:RMSIGN)
akkord_la	Piecework wage type	char(4)	LLE 7.2: Obsolete! Log records of the order data collection with this wage type become piecework time tickets. (PDM field ID: LLE.LART:AKK)
akkord_la_aus_pze		char(1)	Not used.
akkord_masch	Check whether machines are suitable for	char(1)	LLE 7.2: Obsolete! J/N default N (PDM field ID: LLE.OPT:AKKMNR)
ausschuss	Consider scrap for standard time	char(1)	When it comes to the calculation of standard time the scrap is taken into account (scrap is "paid"). J (YES)/N (No) (PDM field ID: LLE.OPT:AUS)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bmk_01	Include RPA1 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK1)
bmk_01_la	Assignment of RPA1 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK1)
bmk_01_r	Upload RPA1 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK1)
bmk_02	Include RPA2 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK2)
bmk_02_la	Assignment of RPA2 to wage type	char(4)	--- (PDM field ID: LLE.LART:BMK2)
bmk_02_r	Upload RPA2 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK2)
bmk_03	Include RPA3 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK3)
bmk_03_la	Assignment of RPA3 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK3)
bmk_03_r	Upload RPA3 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK3)
bmk_04	Include RPA4 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK4)
bmk_04_la	Assignment of RPA4 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK4)
bmk_04_r	Upload RPA4 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK4)
bmk_05	Include RPA5 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK5)
bmk_05_la	Assignment of RPA5 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK5)

bmk_05_r	Upload RPA5 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK5)
bmk_06	Include RPA6 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK6)
bmk_06_la	Assignment of RPA6 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK6)
bmk_06_r	Upload RPA6 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK6)
bmk_07	Include RPA7 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK7)
bmk_07_la	Assignment of RPA7 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK7)
bmk_07_r	Upload RPA7 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK7)
bmk_08	Include RPA8 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK8)
bmk_08_la	Assignment of RPA8 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK8)
bmk_08_r	Upload RPA8 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK8)
bmk_09	Include RPA9 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK9)
bmk_09_la	Assignment of RPA9 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK9)
bmk_09_r	Upload RPA9 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK9)
bmk_10	Include RPA10 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK10)
bmk_10_la	Assignment of RPA10 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK10)
bmk_10_r	Upload RPA10 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK10)
bmk_11	Include RPA11 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK11)
bmk_11_la	Assignment of RPA11 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK11)
bmk_11_r	Upload RPA11 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK11)
bmk_12	Include RPA12 in actual time	char(1)	J(Yes) / N (No) (PDM field ID: LLE.IZ:BMK12)
bmk_12_la	Assignment of RPA12 to wage type	char(4)	wage type (PDM field ID: LLE.LART:BMK12)
bmk_12_r	Upload RPA12 to wage type	char(1)	J(Yes) / N (No) (PDM field ID: LLE.RM:BMK12)
bmk_rueck	Upload RPAs via wage interface	char(1)	Is occupied automatically, depending on bmk_zu_lohn
bmk_zu_lohn		char(1)	J(Yes) / N (No) (PDM field ID: LLE.OPT:BMKZULART)
certify_aart	Order types subject to authorization	char(100)	List of order types which must be certified, seperated by comma. (PDM field ID: LLE.CERTIFY:AART)
daten_refresh	Number of days for refreshing data	smallint	LLE 7.2: Obsolete! Number of days for refreshing data via wage calculation. (PDM field ID: LLE.DREFRESH)

datenhaltung	Number of days of data retention	smallint	LLE 7.2: Obsolete! --- (PDM field ID: LLE.DELINT)
datenhaltung_lz	reserved	smallint	LLE 7.2: Obsolete! ---
faktor_te	te per x items	integer	--- (PDM field ID: LLE.FAKTTE)
geloescht_bis	reserved	date	LLE 7.2: Obsolete!
geloescht_bis_lz	reserved	date	LLE 7.2: Obsolete!
gut_menge	Consider yield for standard time	char(1)	When it comes to the calculation of standard time the yield is taken into account (yield is "paid"). J (YES)/N (No) (PDM field ID: LLE.OPT:GUT)
istzeit_aus_bmk	Determine actual time from RPAs	char(1)	If activated, the actual time of piecework time tickets are calculated from the personal resource performance accounts of log records of the order data collection. The single RPAs can be controlled via the following fields. If it is not activated, the actual time is determined from the complete labor time. (PDM field ID: LLE.OPT:IZAUSBMK)
lohnart_einarb	Wage type for practice time tickets	char(4)	LLE 7.2: Obsolete! (PDM field ID: LLE.LART:EINARB)
lohnart_karenz	Wage type for waiting period time ticket	char(4)	LLE 7.2: Obsolete! (PDM field ID: LLE.LART:KAR)
lohnart_pze	Wage type for PZE time tickets	char(4)	--- (PDM field ID: LLE.LART:PZE)
ls_zusammenfassen	reserved	char(1)	Reserved: J: Consecutive time tickets with same keys will be merged. N: Consecutive time tickets with same keys are processed separately (PDM field ID: LLE.LS_ZUSAMMENFASS)
m_te_tr	Calculation of labor utilization rate ac	char(1)	J(Yes) / N (No) (PDM field ID: LLE.VGZ:TR)
mehrmasch		char(1)	Not used.
nr	number	smallint	Fixed 1 reserved for future use. (PDM field ID: LLE.NR)
pze_abgleich	Generate PZE comparison of time tickets	char(1)	LLE 7.2: Obsolete! Compares the duration of time tickets from BDE with the PZE attendance time. If the PZE time is greater a waiting period time ticket is generated to compensate this. J/N (PDM field ID: LLE.OPT:PZEABGL)
pze_bezpau_anw	PZE paid break is productive	char(1)	J/"" : PZE unpaid break is production time N : PZE unpaid break is not production time (PDM field ID: LLE.PZEBEZPAUANW)
refresh_erf_bis	reserved	date	LLE 7.2: Obsolete!
reserve1	reserve	smallint	---
reserve10	reserve	date	---
reserve11	reserve	date	---
reserve12	reserve	date	---
reserve13	reserve	decimal(6,3)	---
reserve14	reserve	decimal(6,3)	---
reserve15	reserve	decimal(6,3)	---
reserve2	reserve	smallint	---
reserve3	reserve	smallint	---
reserve4		char(20)	Execute TR posting only once: reserve4[0] = 'J': relating to logon of order reserve4[1] = 'J': relating to logon of person (PDM field ID: LLE.TREINMALIG:AG, LLE.TREINMALIG:PNR)

reserve5	reserve	char(20)	---
reserve6	reserve	char(20)	---
reserve7	reserve	integer	---
reserve8	reserve	integer	---
reserve9	reserve	integer	---
std_rueck	Use standard upload interface	char(1)	Not used
verantw_bereich	reserved	char(15)	---
verarb_akkord	Generate piecework time tickets	char(1)	LLE 7.2: Obsolete! J(Yes) / N (No) (PDM field ID: LLE.OPT:AKK)
verarb_einarb	Generate practice time ticket	char(1)	LLE 7.2: Obsolete! J(Yes) / N (No) (PDM field ID: LLE.OPT:EINARB)
verarb_gk	Generate time tickets from overhead cost	char(1)	LLE 7.2: Obsolete! J(Yes) / N (No) (PDM field ID: LLE.OPT:GK)
verarb_karenz	Generate waiting period time tickets	char(1)	--- (PDM field ID: LLE.OPT:KAR)
verarb_pze	Generate PZE time tickets	char(1)	Generates PZE time tickets of the overall attendance time determined by PZE J/N (PDM field ID: LLE.OPT:PZE)
verarb_zeitlohn	Generate time-related time tickets	char(1)	LLE 7.2: Obsolete! J(Yes) / N (No) (PDM field ID: LLE.OPT:ZL)
verarb_zl_aus_akk	Generate a time-related time ticket from	char(1)	J(Yes) / N (No) (PDM field ID: LLE.OPT:ZLAUSAKK)
zg_akk_ursprung	Piecework calc. of perf. eff. rate	char(10)	"BDE": Performance rate is calculated from ADE related time tickets only "TGERG" : Incentive time is calculated from ADE related time tickets, the actual time is calculated from PZE attendance. (PDM field ID: LLE.ZGRAD:AKK)
zg_automatik	Automatic for labor utilization rate	char(1)	for future use (PDM field ID: LLE.OPT:ZGRDAUTO)
zg_obergrenze	Upper limit of labor utilization rate	decimal(6,3)	LLE 7.2: A warning is generated whe this limit is exceeded (PDM field ID: LLE.ZGRAD:OG)
zg_untergrenze	Lower limit of labor utilization rate	decimal(6,3)	LLE 7.2: A warning is generated whe this limit is exceeded (PDM field ID: LLE.ZGRAD:UG)

6.11. pnr_change

Table name: pnr_change		Product: LLE	
Archive table: a_pnr_change			
Designation: Personel group changes		Description: Change of Groups of Persons	
		# Notes -	
		# Keys 1) Primary unique: verweis 2) personalnummer, datum_von, zeit_von	
		# logical connection to other tables pnr_change.personalnummer = personen.personalnummer and pnr_change.datum_bis between personen.gueltig_von and personen.gueltig_bis	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
archiv		char(1)	
auftrag_nr		char(40)	Reserved / empty (PDM field ID: PNRCHANGE.ANR)
bearb	Modified by	char(10)	(PDM field ID: PNRCHANGE.BEARB)
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung	Commentary	char(100)	Comment (PDM field ID: PNRCHANGE.BEM)
certify_flag		char(1)	Determines whether the record has to be approved. (PDM field ID: PNRCHANGE.CERTIFY)
datum	Date of event	date	(PDM field ID: PNRCHANGE.DAT)
datum_bis		date	Is calculated automatically by BAPI. (PDM field ID: PNRCHANGE.DATE)
datum_von	Start date	date	Is calculated automatically by BAPI. (PDM field ID: PNRCHANGE.DATB)
entl_tmod		smallint	Reserved / empty (PDM field ID: PNRCHANGE.ENTLTMOD)
firma	Company	char(4)	Reserved / empty (PDM field ID: PNRCHANGE.FIR)
glz_tmod		smallint	Reserved / empty (PDM field ID: PNRCHANGE.GLZTMOD)
kost_firma		char(4)	Reserved / empty (PDM field ID: PNRCHANGE.FIR:KST)
kostenstelle		char(10)	Reserved / empty (PDM field ID: PNRCHANGE.KST)
leistgrp	Premium group	char(8)	Premium group to which the person changes. Premium group DEFAULT means, that group assignments are done by "normal" means and not by this table. (PDM field ID: PNRCHANGE.LEISTGRP)

lohnart_lle		char(4)	Reserved / empty (PDM field ID: PNRCHANGE.LART:LLE)
lohnart_pze		char(4)	Reserved / empty (PDM field ID: PNRCHANGE.LART:PZE)
personalnummer	Personnel number	integer	Personnel number (PDM field ID: PNRCHANGE.PNR)
rueckgemeldet		char(1)	Reserved / empty
satzquelle	Type	char(1)	 (PDM field ID: PNRCHANGE.ERFART)
sign_flag		char(1)	Indicator whether this record has been approved. (PDM field ID: PNRCHANGE.SIGN)
sommerwinterzeit	Daylight saving time	char(1)	Daylight saving time (PDM field ID: PNRCHANGE.SOWI)
speicher_dat		date	Reserved / empty (PDM field ID: PNRCHANGE.SPEICHDAT)
speicher_zei		integer	Reserved / empty (PDM field ID: PNRCHANGE.SPEICHZEI)
terminal	Terminal number	smallint	Terminal number where the record was captured (PDM field ID: PNRCHANGE.TNR)
user_c_09		char(20)	Reserved / empty
user_c_10		char(40)	Reserved / empty
user_d_01		date	Reserved / empty
user_d_02		date	Reserved / empty
user_f_07		decimal(18,6)	Reserved / empty
user_f_08		decimal(18,6)	Reserved / empty
user_n_03		integer	Reserved / empty
user_n_04		integer	Reserved / empty
user_n_05		integer	Reserved / empty
user_n_06		integer	Reserved / empty
verweis	Reference	serial	 (PDM field ID: PNRCHANGE.VERWEIS)
verweis_merk		integer	 (PDM field ID: PNRCHANGE.VERWEIS:MK)
zeit_bis		integer	Is calculated automatically by BAPI. (PDM field ID: PNRCHANGE.ZEIE)
zeit_sec	Time of event (seconds)	smallint	 (PDM field ID: PNRCHANGE.SEC)
zeit_std	Time of event (hours)	smallint	 (PDM field ID: PNRCHANGE.ZEI.STD)
zeit_von	Start time	integer	Is calculated automatically by BAPI. (PDM field ID: PNRCHANGE.ZEIB)

6.12. zuschlags_kfg

Table name: zuschlags_kfg		Product: LLE	
Designation: Bonus reasons			
Column name	Column designation	Type	Description
a_stufe	A-Level	char(1)	ADE authorization that has to be allocated at least within the HR master in order that an employee is able to enter this bonus on a terminal. (PDM field ID: ZUSCHLGR.ASTUFE)
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	last editor	char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
certify_flag	Authorization required	char(1)	Flag for approval obligation J/empty: bonus is subject to authorization N: bonus is not subject to authorization (PDM field ID: ZUSCHLGR.CERTIFY)
certify_verb	Allocate if still subject to authorization	char(1)	Allocate bonus if subject to authorization N: bonus is not allocated if it is subject to authorization. (PDM field ID: ZUSCHLGR.VERBCERTIFY)
verantw_bereich		char(15)	Responsibility area (PDM field ID: ZUSCHLGR.VAB)
verbuchung	Posting criterion	char(10)	Posting criterion for individual input. Not yet processed. (PDM field ID: ZUSCHLGR.VERBKRI)
verrechnung	Option target time/actual time	char(1)	This field defines whether a bonus should affect target time or actual time. I: bonus affects actual time S/other: bonus affects target time. (PDM field ID: ZUSCHLGR.VERB)
zuschlag_nr	Bonus reasons	integer	 (PDM field ID: ZUSCHLGR.ZUSCHLGR)
zuschlag_text	Bonus text	char(40)	 (PDM field ID: ZUSCHLGR.BEZ)

7. MDE

7.1. ereignis

Table name: ereignis		Product: MDE	
Archive table: a_ereignis		Reload table: r_ereignis	
Designation: Workplace-related result records		Description: Each machine condition is entered in this table. The entries are made for machines with machine data collection or, provided that it is activated, for the production data collection with activated log record generation for the machine data collection (see setup.mde_gen). Then the log record generator for the machine data collection has to be started cyclically. Events are confirmed in case of changes of the machine condition and at the beginning/end of the shift. Thus, a condition can never take longer than 86400 seconds.	
Column name	Column designation	Type	Description
alt_grund		smallint	internal use
alt_status		smallint	internal use
aus_bas		decimal(18,6)	Scrap in base quantity unit Note: delta quantity (no absolut value)
aus_grund		integer	Number of the scrap reason ('ade_grund_zuord)
aus_grund_text		integer	Number of the text of the scrap reason ('ade_grund_texte)
aus_pri		decimal(18,6)	Scrap in primary quantity unit Note: delta quantity (no absolut value)
aus_sek		decimal(18,6)	Scrap in secondary quantity unit Note: delta quantity (no absolut value)
aus_ter		decimal(18,6)	Scrap in tertiary quantity unit Note: delta quantity (no absolut value)
bearb		char(10)	Abbreviation of the user who changes manually from usr_tab.usr
bearb_date		date	Date of the manual change
bearb_time		integer	Last editing time
begin_dat		date	Start time of the status (PDM field ID: MDEPRO.DATB / MSDATB?)
begin_ts	Message start	datetime	Timestamp for begin_dat, begin_zeit
begin_zeit		integer	Start date of the status (PDM field ID: MDEPRO.ZEIB / MSZEIB?)
bmktionr	RPA (number)	smallint	Resource performance account of the machine condition (PDM field ID: MDEPRO.BMKNR)
dauer		integer	Duration of the status (compared with the shift calendar) (PDM field ID: MDEPRO.MSDAUER)
dlg_data_verweis		integer	Reference to comment
end_ts	End of message	datetime	Timestamp for ende_dat, ende_zeit
ende_dat		date	End date of the status (PDM field ID: MDEPRO.DATE / MSDATE)
ende_zeit		integer	End time of the status (PDM field ID: MDEPRO.ZEIE / MSZEIE)
gut_bas		decimal(18,6)	Yield in base quantity unit Note: delta quantity (no absolut value)
gut_grund		integer	Number of the deviation reason ('ade_grund_zuord)
gut_grund_text		integer	Number of the text of the deviation reason ('ade_grund_texte)
gut_pri		decimal(18,6)	Yield in primary quantity unit Note: delta quantity (no absolut value)

gut_sek		decimal(18,6)	Yield in secondary quantity unit Note: delta quantity (no absolut value)
gut_ter		decimal(18,6)	Yield in tertiary quantity unit Note: delta quantity (no absolut value)
herkunft		char(3)	Origin of the log record - is not yet supported
hub_gesamt	Cycles	decimal(18,6)	Total quantity STROKES Note: delta quantity (no absolut value)
hub_gut	Yield cycles	decimal(18,6)	Yield STROKES
ist_lst_01		decimal(18,6)	Recorded activity 1
ist_lst_02		decimal(18,6)	Recorded activity 2 - is not yet supported
ist_lst_03		decimal(18,6)	Recorded activity 3 - is not yet supported
ist_lst_04		decimal(18,6)	Recorded activity 4 - is not yet supported
ist_lst_05		decimal(18,6)	Recorded activity 5 - is not yet supported
ist_lst_06		decimal(18,6)	Recorded activity 6 - is not yet supported
ist_lst_07		decimal(18,6)	Recorded activity 7 - is not yet supported
ist_lst_08		decimal(18,6)	Recorded activity 8 - is not yet supported
ist_lst_09		decimal(18,6)	Recorded activity 0 - is not yet supported
ist_lst_10		decimal(18,6)	Recorded activity 10 - is not yet supported
kostenstelle	Cost center	char(10)	Cost center of the machine (PDM field ID: MDEPRO.KST)
lst_einh_01		char(3)	Unit of recorded activity 1 - is not yet supported
lst_einh_02		char(3)	Unit of recorded activity 2 - is not yet supported
lst_einh_03		char(3)	Unit of recorded activity 3- is not yet supported
lst_einh_04		char(3)	Unit of recorded activity 4 - is not yet supported
lst_einh_05		char(3)	Unit of recorded activity 5 - is not yet supported
lst_einh_06		char(3)	Unit of recorded activity 6 - is not yet supported
lst_einh_07		char(3)	Unit of recorded activity 7 - is not yet supported
lst_einh_08		char(3)	Unit of recorded activity 8 - is not yet supported
lst_einh_09		char(3)	Unit of recorded activity 9 - is not yet supported
lst_einh_10		char(3)	Unit of recorded activity 10 - is not yet supported
m_status	Status	smallint	Machine status; reference to stoer_tabelle (PDM field ID: MDEPRO.MST)
masch_nr	Resource	char(20)	Machine number (PDM field ID: MDEPRO.MNR)
mauftr		char(9)	Not used so far
meinheit_bas		char(3)	Base quantity unit
meinheit_pri		char(3)	Primary quantity unit
meinheit_sek		char(3)	Secondary quantity unit
meinheit_ter		char(3)	Tertiary quantity unit
mstck		integer	Not used so far
nacharb_bas		decimal(18,6)	Rework quantity in base quantity unit Note: delta quantity (no absolut value)
nacharb_grund		integer	Number of the rework reason (' ade_grund_zuord)
nacharb_grund_text		integer	Number of the text of the rework reason (' ade_grund_texte)
nacharb_pri		decimal(18,6)	Rework quantity in primary quantitiy unit Note: delta quantity (no absolut value)
nacharb_sek		decimal(18,6)	Rework quantity in secondary quantity unit Note: delta quantity (no absolut value)

nacharb_ter		decimal(18,6)	Rework quantity in tertiary quantity unit Note: delta quantity (no absolut value)
neu_grund		smallint	internal use as of HYDRA-Beverage
neu_status		smallint	Not used so far
p_divisor		decimal(18,6)	Current pulse factor
person_nr		char(10)	person who set the status - empty in case of automatic status change or after a change of shifts
problem_bas		decimal(18,6)	Problem quantity in base quantity unit Note: delta quantity (no absolut value)
problem_grund		integer	Number of the problem reason ('ade_grund_zuord)
problem_grund_text		integer	Number of the text of the problem reason ('ade_grund_texte)
problem_pri		decimal(18,6)	Problem quantity in primary quantity unit Note: delta quantity (no absolut value)
problem_sek		decimal(18,6)	Problem quantity in secondary quantity unit Note: delta quantity (no absolut value)
problem_ter		decimal(18,6)	Problem quantity in tertiary quantity unit Note: delta quantity (no absolut value)
reserve1		smallint	Free for customer application
reserve2		smallint	Free for customer application
reserve3		integer	Free for customer application
reserve4		integer	Not used so far
rueckgemeldet	Confirmed	char(1)	J/N, indicates whether the log record has been confirmed/edited (PDM field ID: MDEPRO.RCK)
satzart		char(1)	Record type P: Log record N: Record of the end of shift Original records of changed data 1: Record of the end of shift 2: Log record (PDM field ID: MDEPRO.SART)
schichtanf	Shift start	integer	Beginning of the shift (PDM field ID: MDEPRO.SKZEIB)
schichtart		char(1)	Kind of the shift - is not yet supported
schichtdat		date	Date of the beginning of the shift (PDM field ID: MDEPRO.SKDATB)
schichtend	End of shift	integer	End of the shift (PDM field ID: MDEPRO.SKZEIE)
schichtmodell		smallint	Underlying shift model - not yet supported
schichtnr		smallint	Number of the shift (1..4) (PDM field ID: MDEPRO.SKNR)
schichtpause		smallint	Sum of breaks in this shift (PDM field ID: MDEPRO.SKPAUER)
solltakt	Target cycle	decimal(18,6)	Target cycle at the time of the logging (PDM field ID: MDEPRO.SZY)
stillgrund		smallint	Not used so far
stoertxt_nr	Status text number	smallint	Reference to stoer_texte (PDM field ID: MDEPRO.STNR)
teiligkeit	Partitioning	decimal(18,6)	Partitioning at the time of the logging (PDM field ID: MDEPRO.TLG)
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	

user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	

user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
verweis		serial	Unique internal ID of row. (PDM field ID: MDEPRO.VERWEIS)
zaehler1	Counter 1	integer	Counter 1: good part (yield) ID: MDEPRO.EGR:GUT as of HYDRA-MDE 7.1 ID: MDEPRO.CTR:1 Note: absolut value (accumulated during shift) (PDM field ID: MDEPRO.EGR:GUT / MDEPRO.CTR:1)
zaehler2	Counter 2	integer	Counter 2: machine strokes ID: MDEPRO.EGR:HUB as of HYDRA-MDE 7.1 ID: MDEPRO.CTR:2 Note: absolut value (accumulated during shift) (PDM field ID: MDEPRO.EGR:HUB / MDEPRO.CTR:2)
zaehler3	Counter 3	integer	Counter 3: scrap ID: MDEPRO.EGR:AUS as of HYDRA-MDE 7.1 ID: MDEPRO.CTR:3 Note: absolut value (accumulated during shift) (PDM field ID: MDEPRO.EGR:AUS / MDEPRO.CTR:3)
zaehler4	Counter 4	integer	Counter 4 ID: MDEPRO.CTR:4 Note: absolut value (accumulated during shift) (PDM field ID: MDEPRO.CTR:4)
zaehler5	Counter 5	integer	Counter 5 ID: MDEPRO.CTR:5 Note: absolut value (accumulated during shift) (PDM field ID: MDEPRO.CTR:5)
zaehler6	Counter 6	integer	Counter 6 ID: MDEPRO.CTR:6 Note: absolut value (accumulated during shift) (PDM field ID: MDEPRO.CTR:6)
zflag		smallint	Not used so far

7.2. event_mde

Table name: event_mde		Product: MDE	
Archive table: a_event_mde		Reload table: r_event_mde	
Designation: Machine-related events			
Column name	Column designation	Type	Description
artikel		char(40)	---
attribut_1		char(20)	PZE: clocking attribute ---
attribut_2		char(20)	PZE : Time type : W(inter), S(ummer) Wage group at event P_AN
attribut_3		char(30)	---
attribut_4		char(20)	---
attribut_5		char(20)	Current batch (at event CA_AB or C_AB)
attribut_6		char(10)	free
attribut_7		char(10)	free
attribut_8		char(20)	free
attribut_9		char(30)	---
auftrag_nr	Order number	char(40)	Allocated according to event
automatisch		char(1)	J: automatic event, e.g. at the change of shifts
bearb		char(10)	User's identification
bearb_date		date	Processing date
bearb_time		integer	Processing time
begin_ts		datetime	
bpos		char(10)	Control position at event P_AN
buch_dat		date	Posting date
buch_zeit		integer	Posting time
buendelnr		char(40)	free
bzw		char(10)	Booking requirement J/N
chargen_nr		char(20)	" (PZE: cost center)
datum		date	date
dialog		char(10)	Dialog identifier by which the event was triggered
dlg_data_verweis		integer	Reference to additional data record in event_dlg_data
dlg_id		char(10)	Dialog reference
dllosnr		char(20)	Run-through batch number
editierbar		char(1)	J = Event may be maintained N= Event must not be maintained, e.g. master of a COP or blocked by changing the log record
einheit_1		char(3)	Unit of respective quantity
einheit_10		char(3)	Not yet allocated
einheit_11		char(3)	Not yet allocated
einheit_12		char(3)	Not yet allocated

ein_h_13		char(3)	Not yet allocated
ein_h_14		char(3)	Not yet allocated
ein_h_15		char(3)	Not yet allocated
ein_h_16		char(3)	Not yet allocated
ein_h_17		char(3)	Not yet allocated
ein_h_18		char(3)	Not yet allocated
ein_h_19		char(3)	Not yet allocated
ein_h_2		char(3)	Not yet allocated
ein_h_20		char(3)	Not yet allocated
ein_h_3		char(3)	Not yet allocated
ein_h_4		char(3)	Not yet allocated
ein_h_5		char(3)	Not yet allocated
ein_h_6		char(3)	Not yet allocated
ein_h_7		char(3)	Not yet allocated
ein_h_8		char(3)	Not yet allocated
ein_h_9		char(3)	Not yet allocated
end_ts		datetime	
ereignis		char(10)	Event type
erfass_1		char(1)	free
erfass_10		char(1)	free
erfass_11		char(1)	free
erfass_12		char(1)	free
erfass_13		char(1)	free
erfass_14		char(1)	free
erfass_15		char(1)	free
erfass_16		char(1)	free
erfass_17		char(1)	free
erfass_18		char(1)	free
erfass_19		char(1)	free
erfass_2		char(1)	free
erfass_20		char(1)	free
erfass_3		char(1)	free
erfass_4		char(1)	free
erfass_5		char(1)	free
erfass_6		char(1)	free
erfass_7		char(1)	free
erfass_8		char(1)	free
erfass_9		char(1)	free
erfass_dat		date	Recording date
erfass_zeit		integer	Recording time
erw_status_01		char(1)	Event M_PSPERRE (as of version MDE 7.2): Production lock flag: J - activated/ N - deactivated.
erw_status_02		char(1)	for internal use
erw_status_03		char(1)	for internal use
erw_status_04		char(1)	for internal use
erw_status_05		char(1)	for internal use
erw_status_06		char(1)	for internal use

firma_1		char(8)	Company/plant number 1
firma_2		char(8)	Company/plant number 2
grund_1		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_10		char(10)	Not yet allocated
grund_11		char(10)	Not yet allocated
grund_12		char(10)	Not yet allocated
grund_13		char(10)	Not yet allocated
grund_14		char(10)	Not yet allocated
grund_15		char(10)	Not yet allocated
grund_16		char(10)	Not yet allocated
grund_17		char(10)	Not yet allocated
grund_18		char(10)	Not yet allocated
grund_19		char(10)	Not yet allocated
grund_2		char(10)	Reason of respective quantity e.g. Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_20		char(10)	Not yet allocated
grund_3		char(10)	Not yet allocated
grund_4		char(10)	Not yet allocated
grund_5		char(10)	Not yet allocated
grund_6		char(10)	Not yet allocated
grund_7		char(10)	Not yet allocated
grund_8		char(10)	Not yet allocated
grund_9		char(10)	Not yet allocated
herkunft		char(1)	"Blank" : original data record from recording E: manually generated data record L: manually generated data record, for cancellation only O: original data record if maintained
info_01		integer	Not yet allocated
info_02		integer	M_CTR: The number of the event. If more then 10 counters are inside a second event is generated ...
info_03		integer	HYD-AEV: Error code for rejected dialog messages during posting
ist_lst_01		decimal(18,6)	Recorded activity 01
ist_lst_02		decimal(18,6)	Recorded activity 02
ist_lst_03		decimal(18,6)	Recorded activity 03
ist_lst_04		decimal(18,6)	Recorded activity 04
ist_lst_05		decimal(18,6)	Recorded activity 05
ist_lst_06		decimal(18,6)	Recorded activity 06
ist_lst_07		decimal(18,6)	Recorded activity 07
ist_lst_08		decimal(18,6)	Recorded activity 08
ist_lst_09		decimal(18,6)	Recorded activity 09
ist_lst_10		decimal(18,6)	Recorded activity 10
ist_lst_11		decimal(18,6)	Recorded activity 11
ist_lst_12		decimal(18,6)	Recorded activity 12

ist_lst_13		decimal(18,6)	Recorded activity 13
ist_lst_14		decimal(18,6)	Recorded activity 14
ist_lst_15		decimal(18,6)	Recorded activity 15
ist_lst_16		decimal(18,6)	Recorded activity 16
ist_lst_17		decimal(18,6)	Recorded activity 17
ist_lst_18		decimal(18,6)	Recorded activity 18
ist_lst_19		decimal(18,6)	Recorded activity 19
ist_lst_20		decimal(18,6)	Recorded activity 20
ist_lst_einh_01		char(3)	Unit of recorded activity 1
ist_lst_einh_02		char(3)	Unit of recorded activity 2
ist_lst_einh_03		char(3)	Unit of recorded activity 3
ist_lst_einh_04		char(3)	Unit of recorded activity 4
ist_lst_einh_05		char(3)	Unit of recorded activity 5
ist_lst_einh_06		char(3)	Unit of recorded activity 6
ist_lst_einh_07		char(3)	Unit of recorded activity 7
ist_lst_einh_08		char(3)	Unit of recorded activity 8
ist_lst_einh_09		char(3)	Unit of recorded activity 9
ist_lst_einh_10		char(3)	Unit of recorded activity 10
ist_lst_einh_11		char(3)	Unit of recorded activity 11
ist_lst_einh_12		char(3)	Unit of recorded activity 12
ist_lst_einh_13		char(3)	Unit of recorded activity 13
ist_lst_einh_14		char(3)	Unit of recorded activity 14
ist_lst_einh_15		char(3)	Unit of recorded activity 15
ist_lst_einh_16		char(3)	Unit of recorded activity 16
ist_lst_einh_17		char(3)	Unit of recorded activity 17
ist_lst_einh_18		char(3)	Unit of recorded activity 18
ist_lst_einh_19		char(3)	Unit of recorded activity 19
ist_lst_einh_20		char(3)	Unit of recorded activity 20
ist_lst_typ_01		char(10)	Type of recorded activity 1
ist_lst_typ_02		char(10)	Type of recorded activity 2
ist_lst_typ_03		char(10)	Type of recorded activity 3
ist_lst_typ_04		char(10)	Type of recorded activity 4
ist_lst_typ_05		char(10)	Type of recorded activity 5
ist_lst_typ_06		char(10)	Type of recorded activity 6
ist_lst_typ_07		char(10)	Type of recorded activity 7
ist_lst_typ_08		char(10)	Type of recorded activity 8
ist_lst_typ_09		char(10)	Type of recorded activity 9
ist_lst_typ_10		char(10)	Type of recorded activity 10
ist_lst_typ_11		char(10)	Type of recorded activity 11
ist_lst_typ_12		char(10)	Type of recorded activity 12
ist_lst_typ_13		char(10)	Type of recorded activity 13
ist_lst_typ_14		char(10)	Type of recorded activity 14
ist_lst_typ_15		char(10)	Type of recorded activity 15
ist_lst_typ_16		char(10)	Type of recorded activity 16
ist_lst_typ_17		char(10)	Type of recorded activity 17
ist_lst_typ_18		char(10)	Type of recorded activity 18

ist_lst_typ_19		char(10)	Type of recorded activity 19
ist_lst_typ_20		char(10)	Type of recorded activity 20
karenz		char(1)	P = Waiting period of personnel M = Waiting period of machines
klasse		char(1)	M: Machine-related logon
lohnart		char(4)	LLE wage type
lpkz		char(10)	Wage premium indicator
masch_nr		char(20)	"
menge_1		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_10		decimal(18,6)	Not yet allocated
menge_11		decimal(18,6)	Not yet allocated
menge_12		decimal(18,6)	Not yet allocated
menge_13		decimal(18,6)	Not yet allocated
menge_14		decimal(18,6)	Not yet allocated
menge_15		decimal(18,6)	Not yet allocated
menge_16		decimal(18,6)	Not yet allocated
menge_17		decimal(18,6)	Not yet allocated
menge_18		decimal(18,6)	Not yet allocated
menge_19		decimal(18,6)	Not yet allocated
menge_2		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_20		decimal(18,6)	Not yet allocated
menge_3		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_4		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_5		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_6		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap

menge_7		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_20) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_8		decimal(18,6)	Not yet allocated
menge_9		decimal(18,6)	Not yet allocated
offline_kz		char(1)	J: Recorded offline by the terminal
org_verweis		integer	Reference to a correction data record
p_divisor		decimal(18,6)	Recorded divisor
p_teiligkeit		decimal(18,6)	Recorded partitioning
person_nr		char(10)	"
pgruppe		char(20)	"
pmk		char(1)	Memorize person J/N
pgrgp		char(10)	STD-LLE: Wage/premium group LPGRP
prioritaet		smallint	The priority is indicated in case of simultaneous events (1 = highest priority)
pze_erzeugt		char(1)	"K" =BDE event was generated by PZE clocking-in "G" =BDE event was generated by PZE clocking-out
rest_lst_01		decimal(18,6)	Remaining recorded activity 1
rest_lst_02		decimal(18,6)	Remaining recorded activity 2
rest_lst_03		decimal(18,6)	Remaining recorded activity 3
rest_lst_04		decimal(18,6)	Remaining recorded activity 4
rest_lst_05		decimal(18,6)	Remaining recorded activity 5
rest_lst_06		decimal(18,6)	Remaining recorded activity 6
rest_lst_07		decimal(18,6)	Remaining recorded activity 7
rest_lst_08		decimal(18,6)	Remaining recorded activity 8
rest_lst_09		decimal(18,6)	Remaining recorded activity 9
rest_lst_10		decimal(18,6)	Remaining recorded activity 10
rest_lst_11		decimal(18,6)	Remaining recorded activity 11
rest_lst_12		decimal(18,6)	Remaining recorded activity 12
rest_lst_13		decimal(18,6)	Remaining recorded activity 13
rest_lst_14		decimal(18,6)	Remaining recorded activity 14
rest_lst_15		decimal(18,6)	Remaining recorded activity 15
rest_lst_16		decimal(18,6)	Remaining recorded activity 16
rest_lst_17		decimal(18,6)	Remaining recorded activity 17
rest_lst_18		decimal(18,6)	Remaining recorded activity 18
rest_lst_19		decimal(18,6)	Remaining recorded activity 19
rest_lst_20		decimal(18,6)	Remaining recorded activity 20
rest_lst_einh_01		char(3)	Remainder of the unit of recorded activity 1
rest_lst_einh_02		char(3)	Remainder of the unit of recorded activity 2
rest_lst_einh_03		char(3)	Remainder of the unit of recorded activity 3
rest_lst_einh_04		char(3)	Remainder of the unit of recorded activity 4
rest_lst_einh_05		char(3)	Remainder of the unit of recorded activity 5
rest_lst_einh_06		char(3)	Remainder of the unit of recorded activity 6
rest_lst_einh_07		char(3)	Remainder of the unit of recorded activity 7
rest_lst_einh_08		char(3)	Remainder of the unit of recorded activity 8
rest_lst_einh_09		char(3)	Remainder of the unit of recorded activity 9

rest_lst_einh_10		char(3)	Remainder of the unit of recorded activity 10
rest_lst_einh_11		char(3)	Remainder of the unit of recorded activity 11
rest_lst_einh_12		char(3)	Remainder of the unit of recorded activity 12
rest_lst_einh_13		char(3)	Remainder of the unit of recorded activity 13
rest_lst_einh_14		char(3)	Remainder of the unit of recorded activity 14
rest_lst_einh_15		char(3)	Remainder of the unit of recorded activity 15
rest_lst_einh_16		char(3)	Remainder of the unit of recorded activity 16
rest_lst_einh_17		char(3)	Remainder of the unit of recorded activity 17
rest_lst_einh_18		char(3)	Remainder of the unit of recorded activity 18
rest_lst_einh_19		char(3)	Remainder of the unit of recorded activity 19
rest_lst_einh_20		char(3)	Remainder of the unit of recorded activity 20
rest_lst_typ_01		char(10)	Remainder of the type of recorded activity 1
rest_lst_typ_02		char(10)	Remainder of the type of recorded activity 2
rest_lst_typ_03		char(10)	Remainder of the type of recorded activity 3
rest_lst_typ_04		char(10)	Remainder of the type of recorded activity 4
rest_lst_typ_05		char(10)	Remainder of the type of recorded activity 5
rest_lst_typ_06		char(10)	Remainder of the type of recorded activity 6
rest_lst_typ_07		char(10)	Remainder of the type of recorded activity 7
rest_lst_typ_08		char(10)	Remainder of the type of recorded activity 8
rest_lst_typ_09		char(10)	Remainder of the type of recorded activity 9
rest_lst_typ_10		char(10)	Remainder of the type of recorded activity 10
rest_lst_typ_11		char(10)	Remainder of the type of recorded activity 11
rest_lst_typ_12		char(10)	Remainder of the type of recorded activity 12
rest_lst_typ_13		char(10)	Remainder of the type of recorded activity 13
rest_lst_typ_14		char(10)	Remainder of the type of recorded activity 14
rest_lst_typ_15		char(10)	Remainder of the type of recorded activity 15
rest_lst_typ_16		char(10)	Remainder of the type of recorded activity 16
rest_lst_typ_17		char(10)	Remainder of the type of recorded activity 17
rest_lst_typ_18		char(10)	Remainder of the type of recorded activity 18
rest_lst_typ_19		char(10)	Remainder of the type of recorded activity 19
rest_lst_typ_20		char(10)	Remainder of the type of recorded activity 20
sig_knr1		char(10)	
sig_knr2		char(10)	
sig_name1		char(40)	
sig_name2		char(40)	
sig_pnr1		char(10)	
sig_pnr2		char(10)	
sig_type1		char(20)	
sig_type2		char(20)	
soll_te		decimal(18,6)	Premium target TE
soll_teb		decimal(18,6)	Premium target TEB
soll_tr		decimal(18,6)	Premium target TR
stationsnr		integer	free
status_1		integer	Machine status/termination reason, partitioning or target cycle
status_2		integer	---
status_3		integer	---

szenario_nr		integer	for future use relevant for event maintenance
terminal_nr		smallint	User who generated the data record
typ_1		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_10		char(10)	Not yet allocated
typ_11		char(10)	Not yet allocated
typ_12		char(10)	Not yet allocated
typ_13		char(10)	Not yet allocated
typ_14		char(10)	Not yet allocated
typ_15		char(10)	Not yet allocated
typ_16		char(10)	Not yet allocated
typ_17		char(10)	Not yet allocated
typ_18		char(10)	Not yet allocated
typ_19		char(10)	Not yet allocated
typ_2		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_20		char(10)	Not yet allocated
typ_3		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_4		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_5		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired

typ_6		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_7		char(10)	Type of respective quantity e.g.: GUT - Yield AUS - Scrap HUB - Strokes PRB - Problem quantity NCH - Rework REST - Remaining quantity VERB - Consumption VERF - Quantity expired
typ_8		char(10)	Not yet allocated
typ_9		char(10)	Not yet allocated
umref		decimal(18,6)	Conversion factor for retrograde posting
utc_ts		datetime	
verarb_1		char(1)	Processing PZE
verarb_2		char(1)	Processing BDE
verarb_3		char(1)	Processing MDE
verarb_4		char(1)	MW 7.2 : K= status correction event HYD-AEV: A = indicator for automatically generated dialogs, e.g. from PZE/ADE comparison
verarb_mde		char(1)	Processing MDE (postprocessing of workplace-related result record messages)
verbuch_kz		char(2)	Posting indicator, e.g. "ST" = COP at the terminal "SK"= COP at the console "SB" = Beginning of the shift"SE" = End of the shift "W" = Winter time (PZE) "S" = Summertime (PZE)
verweis		serial	Distinct reference of the data record
verweis_b1		integer	Reference to the operation-related result record or clocking record
verweis_b2		integer	Reference to a 2nd clocking record
zaehler_1		integer	Counter number
zaehler_10		integer	Counter number
zaehler_11		integer	Counter number
zaehler_12		integer	Counter number
zaehler_13		integer	Counter number
zaehler_14		integer	Counter number
zaehler_15		integer	Counter number
zaehler_16		integer	Counter number
zaehler_17		integer	Counter number
zaehler_18		integer	Counter number
zaehler_19		integer	Counter number
zaehler_2		integer	Counter number
zaehler_20		integer	Counter number
zaehler_3		integer	Counter number
zaehler_4		integer	Counter number
zaehler_5		integer	Counter number
zaehler_6		integer	Counter number

zaehler_7		integer	Counter number
zaehler_8		integer	
zaehler_9		integer	
zeit		integer	time

7.3. hy_zykl

Table name: hy_zykl		Product: MDE	
Designation: Actual cycle of a machine		Description: The cycle log data of each machine are filed in this table.	
Column name	Column designation	Type	Description
isttakt		decimal(18,6)	
kz	Indicator	char(1)	State of the machine [S] Standstill [P] Production
masch_nr	Machine number	char(20)	Number of the machine to which the respective cycle time is assigned.
prot_date	Date	date	Date of the cycle determination
prot_time	Time	integer	Time of the cycle determination
solltakt		decimal(18,6)	
zyklus_zeit	Actual cycle	integer	Determined cycle time in milliseconds

7.4. masch_linien_zuord

Table name: masch_linien_zuord		Product: MDE	
Designation: Assignment of the aggregate to the line			
Column name	Column designation	Type	Description
anzeige_pos	Position	smallint	Sequence of the aggregates within the line (PDM field ID: MNRLINIE.POS)
linie	Line	char(20)	Machine number of the line (reference to maschinen.masch_nr of the line) (PDM field ID: MNRLINIE.LINIE)
masch_nr	Aggregate	char(20)	Machine number of the aggregate (reference to maschinen.masch_nr of the aggregate). (PDM field ID: MNRLINIE.MNR)
param_str01		char(10)	Reserved (PDM field ID: MNRLINIE.POS)
param_str02		char(10)	Reserved
param_str03		char(30)	Reserved
plong_01		integer	Reserved
plong_02		integer	Reserved
pshort_01		smallint	Reserved
pshort_02		smallint	Reserved
referenz_aggregat		char(1)	Is set to "J" if this aggregate is transferred with MNR.REFMNR when creating the line. (PDM field ID: MNRLINIE.OPT:REF)

7.5. masch_term_zuord

Table name: masch_term_zuord		Product: MDE	
Designation: Assignment of workplaces/machines to the terminal		Description: Configuration of assigning workplaces/machines to terminals. # Special remarks A workplace must be assigned to a terminal in order to be able to use the MDE specific functions such as automatic shift change, cyclical status update or data entry via interface. However, these functions are only available if the terminal is configured as the so-called "MDE terminal". These functions are not active for terminals that are configured as ADE terminals, not even if the workplaces are assigned to the terminal. Assignment of a workplace to multiple terminals using SQL insert is not recommended and will not be supported by MPDV. # Key terminal_nr, masch_nr terminal_nr, anzeige_pos # Connections to other tables terminals.terminalnr = masch_term_zuord.terminal_nr maschinen.masch_nr = masch_term_zuord.masch_nr	
Column name	Column designation	Type	Description
anzeige_pos	Display position	smallint	Display position of the workplace/machine at the terminal Please consider the maximum number of workplaces that should be assigned to a terminal. (PDM field ID: MNRTNR.POS)
betriebsart	Processing	char(1)	The following options are available: A - ADE processing M - MDE processing (blank) - Processing according to operation mode defined in the terminal configuration (field terminals.mde_kz) For a group workplace (maschinen.art=G), the flag must be set to "A" if this is to be assigned to an MDE terminal.
masch_nr	Workplace/machine number	char(20)	Workplace/machine number that the terminal is assigned to (PDM field ID: MNRTNR.MNR)
terminal_nr	Terminal number	smallint	Terminal number that a workplace should be assigned to. (PDM field ID: MNRTNR.TNR)

7.6. maschinen

Table name: maschinen		Product: MDE	
Designation: Machines		Description: Definition of machines. If it is an MDE terminal the definition of the processing is added.	
Column name	Column designation	Type	Description
a_an_sk_beginn	Log OP on automatically when shift ends	char(1)	OP re-login at the beginning of the shift : This setting is only evaluated if ade_auftragsarten.a_an_sk_beginn = "X" = "Check machine" is active: a_an_sk_beginn = "J" : Log OP on again at the beginning of the shift a_an_sk_beginn = "N" : Do not log OP on again at the beginning of the shift (PDM field ID: MNR.OPT:AANSKBAUTO)
ag01		char(4)	Not allocated
ag02		char(4)	Not allocated
ag03		char(4)	Not allocated
ag04		char(4)	Not allocated
akkord	Piecework indicator/bonus	char(1)	Piecework indicator/bonus (E/G/S/M/Z) default = Z (PDM field ID: MNR.AKKORD)
auftr_ersch	Several orders in parallel	char(1)	J: several orders can simultaneously be logged on to the machine N: only one order can be logged on to the machine (default) default = "N" (PDM field ID: MNR.OPT:MULTIAG)
aus	Scrap processing	char(1)	J/N/G : Processing of scrap J = the automatic and manual scrap is deducted from the automatic yield (default) N = the automatic and manual scrap is not deducted from the automatic yield G = the automatic and manual scrap is not deducted from the automatic yield and manual scrap is additionally posted as strokes (Hub=stroke+scrap/partitioning) GUT-/AUS_XXXX: The pulses recorded via counters are collected as follows: The counter of good parts provides a machine pulse, no numbers of pieces. Therefore, it has to be multiplied by partitioning. Postings Good parts += yield counter * partitioning (from order) Scrap += Scrap counter Good parts -= Scrap counter In theory, the collection via the counter and manual input can be activated at the same time. However, practically, this is not reasonable. In contrast to this, it is useful to record good parts via the counter and scrap manually. Customers use this method. default = "J" (PDM field ID: MNR.OPT:AUS)
aus_dim	Unit of scrap	char(3)	Dimension of the collected scrap; ST (default) MT, KG optional default = "ST" (PDM field ID: MNR.EGE:AUS)
aus_impuls	Scrap, automatic	char(1)	J/N, whether scrap pulses are recorded via counter (N = default) default = "N" (PDM field ID: MNR.OPT:AUSAUTO)
aus_manu	Scrap, manual	char(1)	J/N, whether scrap can be entered manually or not (N = default) default = "N" (PDM field ID: MNR.OPT:AUSMANU)

aus_manu_takte	Posting of scrap as cycles	char(1)	J/N: J = Allocation of manual scrap as cycles (thus additionally as AGR:HUB) (Default N) (PDM field ID: MNR.OPT:AUSMANUTAKT)
aus_nr_impuls	Scrap reason, automatic	smallint	Scrap reason for automatically recorded scrap. (PDM field ID: AUSNR:AUTO)
aus_nr_pspere	Scrap reason, P lock	smallint	Scrap reason for scrap during P lock (PDM field ID: AUSNR:PSPERRE)
aus_prot		smallint	Reserved for V24 interface (log) default = 0
aus_rs232		char(1)	Reserved for V24 interface (J/N)
aus_zaeht	Scrap counter	smallint	If aus_impuls = J, the counter number is indicated, otherwise 0 (0 = default) default = 0 (PDM field ID: MNR.DIGIN:AUS)
ausw_j_mod		smallint	Evaluation year model Currently, customer-specific only
auswmod		smallint	Reference to default evaluation models for MDE evaluations about alternative shifts Is not yet supported by console configuration (BAPI only), i.e., the option is invisible at the client (PDM field ID: MNR.AUSWMOD)
auto_einlastung	Automatic planning	char(1)	At the moment only assigned to option "M" (empty is interpreted as "M"): When the OP is logged on -> the machine and group are updated in the order backlog -> ast.eingeplant = is set to M (PDM field ID: MNR.OPT:AUTOPLAN)
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bez_lang	Detailed machine designation	char(40)	Detailed machine designation (PDM field ID: MNR.BEZL)
bezeichnung	Plaintext designation	char(8)	Plaintext designation (PDM field ID: MNR.BEZK)
dialogsteuerung	Dialog control	char(10)	Dialog control A dialog control deviating from the standard performance can be defined at the workplace and it can respectively be referred to it in the dialog in order to represent different requirements of the dialogs of the Windows terminal CTWIN.
digout1	Relay number for machine lock	smallint	>0:Relay number for machine lock, otherwise 0 (0 = default) default = 0 (PDM field ID: MNR.DIGOUT:MSPERRE)
digout2	Rel. no. f. target no. of pieces reached	smallint	>0: Relay number for target number of pieces reached, otherwise 0 (0 = default) default = 0 (PDM field ID: MNR.DIGOUT:SMENGE)
digout3	No. of targ. cycles till switch. to prod	smallint	Number of target cycles till switching to production: Available as of May 2000 under DOS and WIN Value range: 0 - 9999 (0 = default) default = 0 (PDM field ID: MNR.ANZSTAKT)
digout4	External device: device address/class	smallint	- ID for master terminal = number of MT3/DS100 (0 = default) - Machine class in case of Arburg interface (according to the external device in maschinen.kfg_kz02) default = 0 (PDM field ID: MNR.EXTID)

drucker		char(100)	Reserved (customer-specific)
firma	Comp.	char(4)	--- (PDM field ID: MNR.FIR)
fremd_apz	External workplace	char(1)	MDE 7.2 "external workplace" (PDM field ID: OPT:FREMDAPZ)
gut	Batch option	char(1)	J: Batch management active L: Batch processing active D: Run-through batch processing active N: no option of the batch management is active (default) default = "N" (PDM field ID: MNR.OPT:CHV)
gut_dim	Unit of yield	char(3)	Dimension of the recorded good parts ST (default) , MT, KG optional default = "ST" (PDM field ID: MNR.EGE:GUT)
gut_impuls	Yield, automatic	char(1)	J/N: wheter good parts pulses are recorded via the counter (N = default) (PDM field ID: MNR.OPT:GUTAUTO)
gut_manu	Yield, manual	char(1)	J/N, whether good parts (yield) can be entered manually or not (N = default) default = "N" (PDM field ID: MNR.OPT:GUTMANU)
gut_manu_takte	Posting of yield as cycles	char(1)	J/N: J = allocation of manual yield as cycles (thus additionally as AGR:HUB) (Default N) ab MDE 7.2 (PDM field ID: MNR.OPT:GUTMANUTAKT)
gut_prot	Customer-specific	smallint	Year model of the machine (only until 5.7.5E) Released (as of 6.5) (0 = default) (PDM field ID: MNR.PARAM:12)
gut_rs232		char(1)	Reserved for V24 interface (J/N)
gut_zaeht	Yield counter	smallint	If gut_impuls = J, the counter number is stated, otherwise 0 (0 = default) (PDM field ID: MNR.DIGIN:GUT)
hls_opt		char(5)	
hls_pep_opt		char(5)	
kap_j_mod	Availability	integer	Year shift model for capacities

kfg_kz01		char(5)	[1-2] : Batch change signal -> Indicator: MNR.DIGIN:CAWL [3]: Order change when logging on an order MNR.OPT:AWLGAP [4]: Machine type -> Indicator: MNR.TYP : N/empty: Machine J: Processing center L: Line (MDE-LIN) A: Aggregate (MDE-LIN) P: Workplace K = Construction H = Manual workplace Q=CAQ inspection station [5]: J = Post the quantity of A_UN/A_AB to the person that is logged on for the longest time default = N Indicator: MNR.OPT:MAABP default = "1 NNN" (PDM field ID: (Composed of several acronyms))
kfg_kz02		char(5)	[1]: Posting during P-lock G = Yield A = Scrap X = No quantity posting, strokes are counted -> Indicator: MNR.BUCHSPERRE [2]: External device K: No ext. device J: DS100 N: MT3 E: Engel interface A: Arburg interface P: PDE machine ID (MNRID) (PDE = MWP) -> Indicator: MNR.EXTTYP [3]: J = It is allowed to log off OPs with status "V"/"U" J = Actual-OP logon is allowed in the standard -> Indicator: MNR.OPT:AGIST [4]: J = Reserved [5]: J = Quantity conversion active -> Indicator: MNR.OPT:MENGUMR default = "AKN N" (PDM field ID: (Composed of several acronyms))
kfg_kz03	Parameter	char(5)	-> Indicator: MNR.PARAM:13E default = "0010" (PDM field ID: MNR.PARAM:13)
kfg_kz04	Parameter	char(5)	[1]: J = active according to package processing (J/N) [2]: Reserved [3]: Reserved -> Identifier: MNR.PARAM:14C [4]: Reserved -> Identifier: MNR.PARAM:14D [5]: Reserved -> Identifier: MNR.PARAM:14E default = "N-NNN" (PDM field ID: MNR.PARAM:14)

kfg_kz05	Parameter	char(5)	default = "NNEJJ" (DUNLOP) default = "" (PDM field ID: MNR.PARAM:11)
konf_maske	Free input/output	smallint	default = 0 (PDM field ID: MNR.DIGIO)
kostenstelle	Number of the cost center	char(10)	Number of the cost center (is compared to kstst_tab.kostenstelle in case of evaluations/reports) Mandatory field (PDM field ID: MNR.KST)
leistgrad	Leistungsgrad in %	smallint	Performance rate in % default = 100 (PDM field ID: MNR.LEIGRAD)
linie	Machine category	char(10)	Machine category (PDM field ID: MNR.CAT)
masch_art	Machine type	char(1)	Machine type E : Single-user workplace default) G : Group workplace K: Capacity default = "E" (PDM field ID: MNR.ART)
masch_nr	Machine number	char(20)	Machine number Mandatory field (PDM field ID: MNR.MNR)
maxpersonen		integer	Internal
meinheit_bas	Quantity unit (B)	char(3)	Base quantity unit (PDM field ID: MNR.EGE:GUTB)
meinheit_pri	Quantity unit (P)	char(3)	Primary quantity unit (PDM field ID: MNR.EGE:GUTP)
meinheit_sek	Quantity unit (S)	char(3)	Secondary quantity unit (PDM field ID: MNR.EGE:GUTS)
meinheit_ter	Quantity unit (T)	char(3)	Tertiary quantity unit (PDM field ID: MNR.EGE:GUTT)
mgruppe	Machine/place groups	char(20)	Machine/place group Mandatory field (PDM field ID: MNR.MGRP)
mss	Hourly rate of machines	smallfloat	Hourly rate of machines default = 0 (PDM field ID: MNR.MSTDSATZ)
nch_manu	Manual entry of rework quantity	char(1)	J/N, whether rework quantities may be entered manually (N= default) (PDM field ID: MNR.OPT:NCHMANU)
nch_manu_takte	Posting of rework as cycles	char(1)	J/N: J = allocation of manual rework quantity as cycles (thus additionally as AGR:HUB) (Default N) (PDM field ID: MNR.OPT:NCHMANUTAKT)

opt_mdetlg		char(1)	"Partitioning specific to orders" option ab MDE 7.2 (PDM field ID: MNR.OPT:MDETLG)
opt_tranr_in	Generate transport order for input material	char(1)	
opt_tranr_out	Generate transport order for output material	char(1)	
ortgr		char(4)	Location group
pal_anz_bearb		smallint	Reserved Number of processing stations/palletizing machines In case of processing centers the number of available stations, which is to be taken into account for the assignment/planning, is defined here.
pal_umspannzeit		integer	Reserved Transformation time (palletizing machines) The average transformation time is defined here for processing centers
param_str01		char(10)	[1,1] J/N : J = automatic disturbance reason request after waiting period from pshort_03 --> Identifier: MNR.OPT:MSTAUAF [2,2] J/N : Weekend automatic: J = set the machine status before the weekend starts, N = Show dialog "enter machine status" at the terminal. --> Identifier: MNR.OPT:WENDAUTO [4,4] Ratio posting of the working time of machines N: No ratio posting of the working time of machines J : Ratio posting of the machine time to OP and person according to the number of OPs in case of parallel OPs V : Ratio posting of the machine time to OP and person according to the specified quantity of the OP in case of parallel OPs Z : Ratio posting of the machine time to OP and person according to the specified standard time of the OP in case of parallel OPs --> Identifier: MNR.OPT:ANTDAUER [5,5] J/N/W :J : Compulsory sequence in sequencing list has mandatorily to be observed W: Compulsory sequence can be skipped by means of booking requirement --> Identifier: MNR.OPT:VLISTZW [6,6] G/M/S :G :Sequencing list group-related (in 7.2 field has been changed into separate field sequencing list !!!) M :Sequencing list machine-related S: Sequencing list according to setup setting (default) --> Identifiter: MNR.OPT:VLISTMOD [9,9] J/N : "J", "" : Automatic generation of batch numbers for production batches (MPL) "N": Manual entry of the batch number when logging on batches "E": Manual entry of the batch number when logging off batches --> Identifier: MNR.OPT:CNRAUTOGEN [10,10] "N", "" : OP is not logged on at C_GEN/C_UMB. " J" : OP is automatically logged on to the machine at C_GEN/C_UMB. "U" : Like "J" but current logons of the OP to other machines are automatically interrupted. --> Identifier: MNR.OPT:CNRAGAN default = "NN NNSNNNN" (PDM field ID: (Composed of several acronyms))

param_str02		char(10)	[5,5] = MPL/RF-CAQ : Plausibility concerning characteristics inspection whether all characteristics may be checked or only those that are planned for this workplace {J/N} default N -> All, J -> Planned ones only --> Identifier: MNR.PARAM:2F ----- (PDM field ID: (Composed of several acronyms))
-------------	--	----------	--

param_str03		char(30)	[1,12] = Still free !!!! --> Identifier: MNR.PARAM:3 [13,13] = Planning function for the machine --> Identifier: MNR.PLANFKT {N/H/A} default=H N: No planning H: HLS planning (HLS = shop floor scheduling module) A: AVG planning (AVG = order sequencing) MPL71: [14,14] J: Activates label printing (MPL) batch change MPL71: Identifier: MNR.OPT:TICKETDRUCK MPL72: [14,14] J: Quantity balance after log off order (A_UN/A_AB) MPL72: Identifier: MNR.VISVERBRBLZ [15,15] J: Logging off OPs of the order at all machines of the same machine group -> Identifier: MNR.OPT:MGRPAGAB (License: ANP-000055) default=N [16,16] = Should the machine be shown in the PEP? --> Identifier: MNR.OPT:PEP J: Maschine is visible [18,18] Block indicator of the machine " J" : Machine is blocked --> Identifier: MNR.SPERR MPL71: [21,21] J: Ticket printing in case of scrap (MPL) -> Identifier: MNR.OPT:CNRPRNAUS ->default=N (processing everything <> 'N' is evaluated as 'J') MPL72: free [22,22] J: Back posting of cycles at the terminal -> Identifier: MNR.OPT:ZYKLRB default=N (processing everything <> 'J' is evaluated as 'N') [23,23] P : activates the ration posting of RPAs and duration in staff logons in case of multiple machine operation akt. That means use personal shift-model. M : deactivates the setup-option. That means, use mashine shift-modell Normally the setup-switch setup.pdauer_anteilig for all mashines. This switch acitvates/deactivates this function of this mashine. It is an additive switch to setup. If setup-switch is off, this switch is also not used. default = " " = ("P") [24,24]: base for MDE quantity conversion M ... conversion factor of the working place / machine (default) A ... conversion factor of the operation if an operation is running; otherwise conversion factor of the working place / machine -> Identifier: MNR.OPT:UMRMENGE [25,25]: Logoff operation when reaching target quantity empty/A=processing according to operation (Processing Code) N=No J=log off operation automatically U=interrupt operation automatically F=log off operation automatically and start next order in machines default list if it produces same article K=it is automatically finished when the target quantity is reached und log subsequent OP on with the same campaigning number -> Identifier: MNR.OPT:AUTOAABMENGE [26,26] Book time of production to MUTduring break (J/N) -> Identifier: MNR.OPT:PAUVERBHNZ [28,28]: J = Suppressing of posting in case of ADE and MDE (e.g. CAQ machines (TYPE=Q)) [29,29]: J = Retroactive postings possible
-------------	--	----------	---

			-> Identifier: MNR.OPT:NERF [30,30]: Machining center: J = Book malfunction periods along the lines of production time (i.e. only book to current OP and do not distribute times to all OPs that are logged on) ----- (PDM field ID: (Composed of several acronyms))
pdouble_01	Machine-related partitioning	decimal(18,6)	Machine-related partitioning Machine-related partitioning default = 1 (PDM field ID: MNR.TLG)
pdouble_02	short-term disturbance	decimal(18,6)	short-term disturbance: time in seconds (as of version MDE 7.2) (PDM field ID: MNR.STKZG)
pdouble_03	Screw diameter	decimal(18,6)	free (PDM field ID: MNR.PARAM:15)
pdouble_04		decimal(18,6)	Conversion factor for actual cycle in case of external interfaces Internally, the system computes in milliseconds The external measured value can be converted into the internal system format via this conversion factor Example: Internal system value = conversion factor * external value 4000 [ms]= 1000 * 4 [s]
pers_abmeld	Log person off automatically when shift ends	char(1)	Re-logout of persons (only if OP re-logout is active) at the beginning of the shift: This setting is only evaluated if ade_auftragsarten.pers_abmeld = "X" = "check machine" is active: pers_abmeld = "J" -> Do not log person on again pers_abmeld = "N" -> Log person on again pers_abmeld = "X" -> Check person -> personalstamm.pers_abmeld (PDM field ID: OPT:PABSKE)
pers_erfass	Activation of process data processing	char(1)	J: Machine with process data processing (PDV active) default = "N" (PDM field ID: MNR.OPT:PDV)
plan_j_mod	Planned year model	smallint	Planning year model; a planning shift model deviating from the BDE data collection model (system_j_mod), which is used in shop floor scheduling, can be defined here.
planungsfunktion	Planning function	char(1)	This indicator determines whether or in which planning function a workplace or a machine is displayed. P Planning in the graphical planning board of the shop floor scheduling module, i.e. the workplace is planned via the HLS and thus it is visible there but not in the AVG (order sequencing). Note: Whether a workplace is displayed in HLS also depends on other settings: - assignment to a group that is marked as "capacity group" - responsibility area authorization for this workplace - user profile in the HLS H = analogous to P. Furthermore, the workplace is also considered when it comes to the automatic (server-based) planning. The automatic (server-based) planning is activated within the scope of the system customizing. T = the workplace is only considered in case of the automatic, server-based planning. The workplace is not displayed in the graphical planning board. A = planning in the AVG module (order sequencing), i.e. the workplace is planned by means of AVG and thus it is visible there but not in the HLS module. N = No planning; the workplace is neither displayed in the AVG nor HLS module.
plong_01	External devices: Serial number	integer	Serial number Engel machine Serial number Arburg machine (depending on the external device in maschinen.kfg_kz02) default = 0 (PDM field ID: MNR.EXTSNR)
plong_02	Time of unlimited standstill w/o MSPERR	integer	free (PDM field ID: MNR.PARAM:9)
plong_03	Malfunction	integer	Output is set if machine has any malfunction (PDM field ID: MNR.DIGOUT:STOER)

plong_04	Synchronization range	integer	MW 2.0 / AEV Synchronization range in seconds = allowed logon time in the past (PDM field ID: MNR.PARAM:10)
prb_manu	Manual entry of open quantity	char(1)	J/N, whether problem quantities may be entered manually (N = default) (PDM field ID: MNR.OPT:PRBMANU)
prb_manu_takte	Posting of open quantity as cycles	char(1)	J/N: J = allocation of manual problem quantity as cycles (thus additionally as AGR:HUB) (Default N) ab MDE 7.2 (PDM field ID: MNR.OPT:PRBMANUTAKT)
pshort_01	Customer-specific counter	smallint	Standard: 3rd customer-specific counter default = 0 (PDM field ID: MNR.DIGIN:KD)
pshort_02	Pulse factor	smallint	Standard: Pulse factor (how many pulses are one stroke) default = 0 (PDM field ID: MNR.IMPFAKT)
pshort_03	Wait. period f. autom. dist. reason req.	smallint	Standard: Waiting period for the automatic disturbance reason request default = 0 (PDM field ID: MNR.OPT:MSTAUDAUER)
pshort_04	No. of max. OPs that c.b.logged on sim.	smallint	default = 1 (PDM field ID: MNR.PARAM:7)
pss	Hourly rate of persons	smallfloat	Hourly rate of persons default = 0 (PDM field ID: MNR.PSTDSATZ)
puffer	Input buffer	char(12)	Input material buffer (MPL) (PDM field ID: MNR.MATPUF:IN)
s_acti1_uniso		char(3)	internal
s_acti1_unit		char(3)	internal
s_acti2_uniso		char(3)	internal
s_acti2_unit		char(3)	internal
s_acti3_uniso		char(3)	internal
s_acti3_unit		char(3)	internal
s_acti4_uniso		char(3)	internal
s_acti4_unit		char(3)	internal
s_acti5_uniso		char(3)	internal
s_acti5_unit		char(3)	internal
s_acti6_uniso		char(3)	internal
s_acti6_unit		char(3)	internal
s_co_area		char(4)	internal
s_co_busproc		char(12)	internal
s_co_busproc_name		char(20)	internal
s_cost_driver		char(3)	internal
s_cost_driver_iso		char(3)	internal
s_div		decimal(18,6)	internal
s_noacti1		char(1)	internal
s_noacti2		char(1)	internal
s_noacti3		char(1)	internal
s_noacti4		char(1)	internal

s_noacti5		char(1)	internal
s_noacti6		char(1)	internal
s_subgroup		char(3)	internal
s_teil		decimal(18,6)	internal
s_valid_end		date	internal
s_valid_start		date	internal
schichtmod	Reference to year model	smallint	Reference to year model in case of ADE machines, otherwise 0 default = 0 (PDM field ID: MNR.BDEJMOD)
soll_effektivitaet		decimal(18,6)	For future use
soll_nutzgrad		decimal(18,6)	For future use
soll_oeo		decimal(18,6)	For future use
soll_produkktivitaet		decimal(18,6)	For future use
soll_qualitaet		decimal(18,6)	For future use
soll_technutzgrad		decimal(18,6)	For future use
symbol	File name	char(12)	File name for a graphic that is displayed in the machine/workplace configuration and in the machine/workplace information.
umrech_pri_nen	Denominator, primary quantity	integer	Conversion factor primary quantity (PDM field ID: MNR.UMRFAKTP:N)
umrech_pri_zae	Numerator, primary quantity	integer	Conversion factor primary quantity (PDM field ID: MNR.UMRFAKTP:Z)
umrech_sek_nen	Denominator, secondary quantity	integer	Conversion factor secondary quantity (PDM field ID: MNR.UMRFAKTS:N)
umrech_sek_zae	Numerator, secondary quantity	integer	Conversion factor secondary quantity (PDM field ID: MNR.UMRFAKTS:Z)
umrech_ter_nen	Denominator, tertiary quantity	integer	Conversion factor tertiary quantity (PDM field ID: MNR.UMRFAKTT:N)
umrech_ter_zae	Numerator, tertiary quantity	integer	Conversion factor tertiary quantity (PDM field ID: MNR.UMRFAKTT:Z)
user_c_29		char(1)	User-specific field (PDM field ID: MNR.FU:29)
user_c_30		char(1)	User-specific field (PDM field ID: MNR.FU:30)
user_c_31		char(1)	User-specific field (PDM field ID: MNR.FU:31)
user_c_32		char(1)	User-specific field (PDM field ID: MNR.FU:32)
user_c_33		char(1)	User-specific field (PDM field ID: MNR.FU:33)
user_c_34		char(1)	User-specific field (PDM field ID: MNR.FU:34)
user_c_35		char(1)	User-specific field (PDM field ID: MNR.FU:35)
user_c_36		char(1)	User-specific field (PDM field ID: MNR.FU:36)
user_c_37		char(1)	User-specific field Prüfung (PDM field ID: MNR.FU:37)
user_c_38		char(1)	User-specific field (PDM field ID: MNR.FU:38)
user_c_39		char(1)	User-specific field (PDM field ID: MNR.FU:39)

user_c_40		char(1)	User-specific field (PDM field ID: MNR.FU:40)
user_c_41		char(1)	User-specific field (PDM field ID: MNR.FU:41)
user_c_42		char(1)	User-specific field (PDM field ID: MNR.FU:42)
user_c_43		char(1)	User-specific field (PDM field ID: MNR.FU:43)
user_c_44		char(1)	User-specific field (PDM field ID: MNR.FU:44)
user_c_45		char(10)	User-specific field (PDM field ID: MNR.FU:45)
user_c_46		char(10)	User-specific field (PDM field ID: MNR.FU:46)
user_c_47		char(10)	(PDM field ID: MNR.FU:47)
user_c_48		char(10)	Konfigurationsdokumentation. User-specific field (PDM field ID: MNR.FU:48)
user_c_49		char(10)	User-specific field
user_c_50		char(10)	User-specific field (PDM field ID: MNR.FU:50)
user_c_51		char(20)	User-specific field User-specific field (PDM field ID: MNR.FU:51)
user_c_52		char(20)	User-specific field (PDM field ID: MNR.FU:52)
user_c_53		char(20)	User-specific field
user_c_54		char(20)	User-specific field
user_c_55		char(20)	User-specific field
user_c_56		char(20)	User-specific field
user_c_57		char(20)	User-specific field
user_c_58		char(20)	User-specific field
user_c_59		char(20)	User-specific field
user_c_60		char(20)	User-specific field
user_c_61		char(20)	User-specific field
user_c_62		char(20)	User-specific field
user_c_63		char(20)	User-specific field
user_c_64		char(20)	User-specific field (PDM field ID: MNR.FU:64)
user_c_65		char(40)	User-specific field
user_c_66		char(40)	User-specific field
user_code		char(8)	User field key
user_d_01		date	User-specific field (PDM field ID: MNR.FU:01)
user_d_02		date	User-specific field
user_d_03		date	User-specific field

user_d_04		date	User-specific field
user_d_05		date	User-specific field
user_d_06		date	FU:22) User-specific field (PDM field ID: MNR.FU:6)
user_f_23		decimal(18,6)	User-specific field (PDM field ID: MNR.FU:23)
user_f_24		decimal(18,6)	User-specific field (PDM field ID: MNR.FU:24)
user_f_25		decimal(18,6)	User-specific field (PDM field ID: MNR.FU:25)
user_f_26		decimal(18,6)	User-specific field (PDM field ID: MNR.FU:26)
user_f_27		decimal(18,6)	User-specific field
user_f_28		decimal(18,6)	User-specific field
user_n_07		integer	User-specific field (PDM field ID: MNR.FU:7)
user_n_08		integer	User-specific field Änderung möglich (Dialogkonfiguration) (PDM field ID: MNR.FU:8)
user_n_09		integer	User-specific field (PDM field ID: MNR.FU:9)
user_n_10		integer	User-specific field (PDM field ID: MNR.FU:10)
user_n_11		integer	User-specific field (PDM field ID: MNR.FU:11)
user_n_12		integer	User-specific field
user_n_13		integer	User-specific field
user_n_14		integer	User-specific field
user_n_15		integer	User-specific field
user_n_16		integer	User-specific field
user_n_17		integer	User-specific field
user_n_18		integer	User-specific field
user_n_19		integer	User-specific field
user_n_20		integer	User-specific field (PDM field ID: MNR.FU:20)
user_n_21		integer	User-specific field (PDM field ID: MNR.FU:21)
user_n_22		integer	User-specific field (PDM field ID: MNR.FU:22)
verantw_bereich	Responsibility area	char(15)	Responsibility area
verrech_aus	Allocation of scrap	char(10)	Allocation of manual scrap quantity with GUT/NCH/PRB empty=no allocation (default) ab MDE 7.2 (PDM field ID: MNR.VERB:AUS)
verrech_gut	Allocation of yield	char(10)	Allocation of manual yield with AUS/NCH/PRB empty=no allocation (default) (PDM field ID: MNR.VERB:GUT)

verrech_nch	Allocation of rework	char(10)	Allocation of manual rework quantity with GUT/AUS/PRB empty=no allocation (default) ab MDE 7.2 (PDM field ID: MNR.VERB:NCH)
verrech_prb	Allocating open quantity	char(10)	Allocation of manual problem quantity with GUT/AUS/NCH empty=no allocation (default) ab MDE 7.2 (PDM field ID: MNR.VERB:PRB)
vgs01		integer	Internal
vgs02		integer	Internal
vgs03		integer	Internal
vgs04		integer	Internal
vgs05		integer	Internal
vgs06		integer	internal
vgw01		char(20)	Internal
vgw02		char(20)	Internal
vgw03		char(20)	Internal
vgw04		char(20)	Internal
vgw05		char(20)	Internal
vgw06	Preliminary machine number	char(20)	Preliminary machine number (PDM field ID: MNR.MNRV)
vis_fhm_tnr_a_an	Show mat./PRT list when logging OP on	char(1)	"Display material/PRT list when logging OP on" option J/N (N = default) (PDM field ID: MNR.VISFHMTNRAAN)
vis_list3	Display 3rd list	char(10)	Display of third list (material, resources or people) at the terminal This field contains none, one ore more of these options, which are separated by semikolon: - M: material - R: resources - P: people - A: output material for example "M;R;P;A", if all options are set. (PDM field ID: MNR:VISLIST3)
vl_anzahl	Number of OPs in sequencing list	smallint	Maximum number of OPs that are displayed in the sequencing list
voranmeldezeit		integer	Internal

vorgabeliste		char(1)	By means of this option, it is defined which operations are displayed in the sequencing list at the terminal. The following settings are possible: S = Basic setting. The value is taken over from the option of the same name. M = Pool of workplaces. The operations, which are planned for the workplace, are only displayed in the sequencing list at the terminal. G = Pool of workplaces and groups. Those OPs, which are either scheduled for the current workplace or for another workplace of the group or which are still in the pool of groups, are displayed in the sequencing list at the terminal. K = Pool of workplaces and categories. The operations, which are planned for workplaces of the category, are only displayed in the sequencing list at the terminal. H = Group control. Those OPs, which are either scheduled for the current workplace or for another workplace of the group, are displayed in the sequencing list at the terminal.
wache_sign	Number of single values for MDE-ZYK	char(1)	Number of single values for MDE-ZYK default = "0" (PDM field ID: MNR.MWANZ)
wache_takt	Monitoring, cycle	char(1)	Z/B/K: Z = Cycle monitoring B = Operating signal K = No monitoring wache_takt: Determines the kind of monitoring: Z cycle time monitored = cycle time of the order * wache_zykl / 100 If this time is over without a counter pulse the terminal automatically switches to "STOEREINGABE" ("malfunction input"). It is not possible to assign the status "production" manually. B If the operating signal is not set longer than (länger als) WACHEDAUER (monitoring time) the terminal switches automatically to "STOEREINGABE" ("malfunction input"). It is not possible to assign the status "production" manually. K The status production can be assigned manually (default). default = "K" default = "K" (PDM field ID: MNR.UEBART)
wache_zykl	% rate to determine actual cycle time	smallint	Percentage to determine the actual cycle time Value < 100: cycle is reduced Value > 100: cycle is extended default = 100 (PDM field ID: MNR.IZYABW)
wachedauer	Min. disturbance time f. operat. signal	smallint	Minimum disturbance time for operating signal (seconds) Minimum cycle time at cycle time monitoring (seconds) default = 0 (PDM field ID: MNR.UEBDAUER)
wartezeit	Wait time before machine in seconds	integer	Wait time before machine in seconds default = 0 (PDM field ID: MNR.WARTZ)
werk	Designation for plant	char(10)	Designation for plant (PDM field ID: MNR.WERK)
zielort	Output buffer	char(12)	Output material buffer (MPL) (PDM field ID: MNR.MATPUF:OUT)

7.7. maschinen_detail

Table name: maschinen_detail		Product: MDE	
Designation: Addition machine characteristics			
Column name	Column designation	Type	Description
masch_nr		char(20)	Machine number
max_wert1		decimal(18,6)	Overdelivery, absolute 1 (PDM field ID: MNR.UEBLIMENGE:1)
max_wert2		decimal(18,6)	Overdelivery, absolute 2 (PDM field ID: MNR.UEBLIMENGE:2)
min_wert1		decimal(18,6)	Underdelivery, absolute 1 (PDM field ID: MNR.UNTLIMENGE:1)
min_wert2		decimal(18,6)	Underdelivery, absolute 2 (PDM field ID: MNR.UNTLIMENGE:2)
pruefe_wert1		char(5)	[1,1] = J : Check min_wert1 identifier -> MNR.OPTUNTLI:1 [2,2] = J : Check max_wert1 identifier -> MNR.OPTUEBLI:1 default = "NN" (PDM field ID: (Composed of several acronyms))
pruefe_wert2		char(5)	[1,1] = J : Check min_wert2 identifier -> MNR.OPTUNTLI:2 [2,2] = J : Check max_wert2 identifier -> MNR.OPTUEBLI:2 default = "NN" (PDM field ID: (Composed of several acronyms))
ueberlieferung		integer	Overdelivery, in percent (PDM field ID: MNR.UEBLIP)
unterlieferung		integer	Underdelivery, in percent (PDM field ID: MNR.UNTLIP)

7.8. maschinen_status

Table name: maschinen_status		Product: MDE	
Designation: Machine condition		Description: The current statuses of the machine terminals are entered in this table. If a machine terminal is restarted the machine status is read and taken as basis. Approximately every two to three minutes these conditions are transferred from the terminals for each configured machine to the host computer. If the menu item "machine overview" is selected in the production data collection client only thos machines, which have an entry in this table, are displayed (provided that you have the cost center authorization fir these machines). Objective: This table is intended for the collection of machine-related variable data. The contents are set to 0 at each end of the shift. If the log record generator for the machine data collection is available the table is edited via this program. masch_nr	
		masch_nr	
Column name	Column designation	Type	Description
ade_begin_dat		date	Machine status has been active since ... Is even not reset when changing shifts
ade_begin_zeit		integer	Machine status has been active since ... Is even not reset when changing shifts
ade_status	Machine status	smallint	Current machine status for ADE machines
alt_grund		smallint	For internal use only
alt_status		smallint	Last/previous machine condition
anzauftr		smallint	Not allocated - number of OPs must be determined via hybuch
anzpers		smallint	Not allocated - number of persons must be determined via hybuch
auftrag_01		char(40)	Current order; OBSOLETE
auftrag_02		char(40)	So far not used
aus_bas		decimal(18,6)	Scrap in base quantity unit
aus_grund		integer	Number of the scrap reason (' ade_grund_zuord)
aus_grund_text		integer	Number of the text of the scrap reason (' ade_grund_texte)
aus_pri		decimal(18,6)	Scrap in primary quantity unit
aus_sek		decimal(18,6)	Scrap in secondary quantity unit
aus_ter		decimal(18,6)	Scrap in tertiary quantity unit
begin_dat		date	Start of current machine condition (PDM field ID: MSDATB)
begin_zeit		integer	Point in time when current machine condition started (PDM field ID: MSZEIB)
bmk_01	SUT	integer	Posted status time to single resource performance accounts in sec.
bmk_02	DCI	integer	Posted status time to single resource performance accounts in sec.
bmk_03	LCI	integer	Posted status time to single resource performance accounts in sec.
bmk_04	SCI	integer	Posted status time to single resource performance accounts in sec.
bmk_05	IMN	integer	Posted status time to single resource performance accounts in sec.
bmk_06	IMS	integer	Posted status time to single resource performance accounts in sec.
bmk_07	SET	integer	Posted status time to single resource performance accounts in sec.
bmk_08	STA	integer	Posted status time to single resource performance accounts in sec.
bmk_09	U8	integer	Posted status time to single resource performance accounts in sec.

bmk_10	U9	integer	Posted status time to single resource performance accounts in sec.
bmk_11	MUT	integer	Posted status time to single resource performance accounts in sec.
bmk_12	BKS	integer	Posted status time to single resource performance accounts in sec.
bmktonr		smallint	Current machine status = referene to bm_konten (PDM field ID: BMKNR)
datum		date	Beginning of the shift, date (PDM field ID: SKDAT)
dauer		integer	Duration of current machine condition in seconds (PDM field ID: MSDAUER)
gut_bas		decimal(18,6)	Yield in base quantity unit
gut_grund		integer	Number of the deviation reason ('ade_grund_zuord)
gut_grund_text		integer	Number of the text of the deviation reason ('ade_grund_texte)
gut_pri		decimal(18,6)	Yield in primary quantity unit
gut_sek		decimal(18,6)	Yield in secondary quantity unit
gut_ter		decimal(18,6)	Yield in tertiary quantity unit
hub_gesamt		decimal(18,6)	Total quantity STROKES
hub_gut		decimal(18,6)	Yield STROKES
ist_lst_01		decimal(18,6)	Recorded activity 1
ist_lst_02		decimal(18,6)	MPLRF: Activity 2
ist_lst_03		decimal(18,6)	MPLRF: Activity 3
ist_lst_04		decimal(18,6)	MPLRF: Activity 4
ist_lst_05		decimal(18,6)	MPLRF: Activity 5
ist_lst_06		decimal(18,6)	MPLRF: Activity 6
ist_lst_07		decimal(18,6)	MPLRF: Activity 7
ist_lst_08		decimal(18,6)	MPLRF: Activity 8
ist_lst_09		decimal(18,6)	MPLRF: Activity 9
ist_lst_10		decimal(18,6)	MPLRF: Activity 10
m_status	Status	smallint	Current machine status = reference to stoer_tabelle if 30000 is assigned by default "not assigned" is allocated. (PDM field ID: MNR.MST)
masch_nr		char(20)	Machine number (PDM field ID: MNR.MNR)
mauftr		char(16)	So far not used
meinheit_bas		char(3)	Base quantity unit
meinheit_pri		char(3)	Primary quantity unit
meinheit_sek		char(3)	Secondary quantity unit
meinheit_ter		char(3)	Tertiary quantity unit
mstck	Actual cycle	integer	Actual cycle - Medium cycle time in seconds * 1000 (MDE-ZYKL)
nacharb_bas		decimal(18,6)	Rework quantity in base quantity unit
nacharb_grund		integer	Number of the rework reason ('ade_grund_zuord)
nacharb_grund_text		integer	Number of the text of the rework reason ('ade_grund_texte)
nacharb_pri		decimal(18,6)	Rework quantity in primary quantity unit
nacharb_sek		decimal(18,6)	Rework quantity in secondary quantity unit
nacharb_ter		decimal(18,6)	Rework quantity in tertiary quantity unit
p_div		decimal(18,6)	Current pulse factor
pause		smallint	Free breaks of the shift in minutes
personnr		char(10)	person who set the status - empty in case of automatic status change or after a change of shifts
pgruppe		char(20)	So far not used

problem_bas		decimal(18,6)	Problem quantity in base quantity unit
problem_grund		integer	Number of the problem reason ('ade_grund_zuord)
problem_grund_text		integer	Number of the text of the problem reason ('ade_grund_texte)
problem_pri		decimal(18,6)	Problem quantity in primary quantity unit
problem_sek		decimal(18,6)	Problem quantity in secondary quantity unit
problem_ter		decimal(18,6)	Problem quantity in tertiary quantity unit
prog_begin_dat		date	Time of entering predicted downtime (PDM field ID: PROGN_DATB)
prog_begin_zeit		integer	Time of entering predicted downtime (PDM field ID: PROGN_ZEIB)
prog_dauer		integer	Estimated (predicted) downtime (in seconds) (PDM field ID: PROGNDAUER)
prot_dat		date	Time of last status record
prot_zeit		integer	integer
reserve1	PDV: Prozessqualität der Maschine	smallint	Saving the current process quality in maschinen_status.reserve1 0 = gray -> no collection 1 = green -> OK 2 = yellow -> beyond the action limits 3 = red -> beyond the tolerance limits
reserve2	CAQ: CAQ-Status der Maschine	smallint	Saving the CAQ status in maschinen_status.reserve2 0 = gray -> no status 1 = green 2 = yellow 3 = red
reserve3		integer	HYD-AEV:RECALC flag for the machine
reserve4		integer	Free for customer application
schichtanf		integer	Beginning of the shift, sec. as of midnight (PDM field ID: SKZEIB)
schichtend		integer	End of the shift, sec. as of midnight (PDM field ID: SKZEIE)
schichtnr		smallint	No. of the current shift (1...4) (PDM field ID: SKNR)
solltakt		decimal(18,6)	Target cycle
stillgrund		smallint	For internal use only
stoertextnr		smallint	Current machine status = reference to stoertexte (malfunction texts)
teiligkeit		decimal(18,6)	Current partitioning
wart1		integer	Maintenance counter 1
wart2		integer	Maintenance counter 2 :
wart3		integer	Maintenance counter 3 (scrap on the basis of OPs)
zaehler1		integer	Counter 1: good parts ID: MNR.AGR:GUT ID: MNR.CTR:1 (PDM field ID: MNR.AGR:GUT / MNR.CTR:1)
zaehler2		integer	Counter 2: machine strokes ID: MNR.AGR:HUB ID: MNR.CTR:2 (PDM field ID: MNR.AGR:HUB / MNR.CTR:2)
zaehler3		integer	Counter 3: scrap ID: MNR.AGR:AUS ID: MNR.CTR:3 (PDM field ID: MNR.AGR:AUS / MNR.CTR:3)

zaehler4		integer	Counter 4: length ID: MNR.AGR:LEN ID: MNR.CTR:4 (PDM field ID: MNR.AGR:LEN / MNR.CTR:4)
zaehler5		integer	Not allocated (PDM field ID: MNR.CTR:5)
zaehler6		integer	Not allocated (PDM field ID: MNR.CTR:6)
zflag		smallint	For internal use only

7.9. maschinen_zaeher

Table name: maschinen_zaeher		Product: MDE	
Designation: machine counters			
Column name	Column designation	Type	Description
aktiv		char(1)	- for future use -
bearb		char(10)	(PDM field ID: BEARB)
bearb_dat		date	(PDM field ID: BEARB_DAT)
bearb_zeit		integer	(PDM field ID: BEARB_ZEI)
bemerkung	Comment	char(100)	(PDM field ID: MNRCTR.BEM)
bezeichnung		char(40)	Designation (free text) (PDM field ID: MNRCTR.BEZ)
einh		char(3)	Unit (PDM field ID: MNRCTR.EINH)
ext_referenz		char(20)	- for future use -
grund	Reason	char(10)	Reason (PDM field ID: MNRCTR.GR)
kanal		char(20)	- for future use -
masch_nr	Resource	char(20)	Machine number Mandatory field (PDM field ID: MNRCTR.MNR)
og_absmenge		decimal(18,6)	- for future use -
taktzaehler	Posting as cycles	char(1)	"Posting as cycles" flag ("stroke counter") T: counter identifies cycle counter (PDM field ID: MNRCTR.OPT:TAKT)
typ	as	char(10)	Assessment: Determination what kind of quality is recorded at counter quantity Possible values: GUT/AUS/NCH/PRB/VERBRAUCH empty = no posting (PDM field ID: MNRCTR.TYP)
ug_absmenge		decimal(18,6)	- for future use -
umrech_nen		integer	- for future use -
umrech_zae		integer	- for future use -
verrech	Allocation with	char(10)	Allocation with GUT/AUS/NCH/PRB empty = no allocation (PDM field ID: MNRCTR.VERB)
verrech_hz_typ	Material type	char(10)	Materialtyp des Material, auf das der Verbrauchszähler verbucht werden soll (PDM field ID: MNRCTR.MATTYP)
verrech_imp		char(1)	J/N = allocation with pulse factor (PDM field ID: MNRCTR.VERB:DIV)
verrech_mat	Compensation with material	char(1)	N/leer - keine Verrechnung J: Verrechnung mit Material (PDM field ID: MNRCTR.VERB:MAT)
verrech_psperr		char(10)	- for future use -
verrech_res	Compensation with resource	char(1)	N/leer - keine Verrechnung J: Verrechnung mit Ressource (PDM field ID: MNRCTR.VERB:RES)

verrech_res_familie	Resource family	integer	Ressourcenfamilie, dem die Ressource zugeordnet sein muss, auf die verbucht wird (PDM field ID: MNRCTR.RESFAMID)
verrech_res_nr	Resource	char(40)	Ressource, auf die verbucht wird (PDM field ID: MNRCTR.RES)
verrech_res_typ	Resource type	char(4)	Ressourcentyp, dem die Ressource zugeordnet sein muss, auf die verbucht wird (PDM field ID: MNRCTR.RESTYP)
verrech_slp	BOM item	char(10)	
verrech_tlg	Allocation with partitioning	char(1)	J/N = allocation with partitioning (PDM field ID: MNRCTR.VERB:TLG)
zaehler	Counter input	integer	Counter: consecutive number, starting with 1 Unique identification of the counter within resource (PDM field ID: MNRCTR.CTR)
zyklussignal	Cycles monitoring	char(1)	"For monitoring" flag Z: For channels where this flag is set, incoming counter pulses are taken into account when it comes to cycle time monitoring. (PDM field ID: MNRCTR.OPT:UEB)

7.10. mde_feiertage

Table name: mde_feiertage		Product: MDE	
Designation: Days off		Description: In this table the public holidays are created for editing the year models	
Column name	Column designation	Type	Description
art		char(1)	
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bereich		char(8)	
bezeichnung		char(20)	Plaintext of the holiday (PDM field ID: MDEFEITG.BEZ)
datum		date	Date of the holiday (PDM field ID: MDEFEITG.DAT)
firma		char(4)	
geloescht		char(1)	
kostenstelle		char(10)	
paramstr_01		char(20)	free
plong_01		integer	free
plong_02		integer	free
user_c_07		char(1)	
user_c_08		char(1)	
user_c_09		char(1)	
user_c_10		char(1)	
user_c_11		char(1)	
user_c_12		char(10)	
user_c_13		char(10)	
user_c_14		char(20)	
user_c_15		char(20)	
user_c_16		char(40)	
user_code		char(8)	
user_f_05		decimal(18,6)	
user_f_06		decimal(18,6)	
user_n_01		integer	
user_n_02		integer	
user_n_03		integer	
user_n_04		integer	
verantw_bereich		char(15)	
verweis		serial	Reference to data record

7.11. mz_stklasse

Table name: mz_stklasse		Product: MDE	
Designation: Status classes		Description: Status classes can be defined to group and evaluate workplace/machine statuses into user-related classes independently from the Resource Performance Accounts (RPA). # Special remarks Each workplace/machine status can be assigned to a status class. # Key nummer # Connections to other tables stoer_tabelle.klasse = mz_stklasse.kuerzel	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Reserved for future use.
bearb_date	Last editing day	date	Reserved for future use.
bearb_time	Last editing time	integer	Reserved for future use.
farbe	Color	integer	Reserved for future use.
kuerzel	Abbreviation	char(3)	Abbreviation for the status classes, e.g. TEC. Must be unique. (PDM field ID: STKL.STKL)
nummer	Status class	smallint	Unique number of the status class, should be consecutive. (PDM field ID: STKL.STKLNR)
text1	Designation	char(18)	Plain text of status class (PDM field ID: STKL.BEZ)

7.12. prozess_param

Table name: prozess_param		Product: MDE	
Designation: Process parameters		Description: An entry has to be made in the process parameter table if cycle monitoring is to be activated for a machine. This information is displayed in the cycle overview of machines on the production data collection client.	
Column name	Column designation	Type	Description
anz_minmax		smallint	Not allocated (PDM field ID: ZYP.MMANZ)
anz_mittelwert		smallint	free (PDM field ID: ZYP.MWANZ)
bde_stoer_neg		char(1)	Not allocated
bde_stoer_epos		char(1)	Not allocated
bde_stoer_tneg		char(1)	Not allocated
bde_stoer_tpos		char(1)	Not allocated
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
datum		date	Not allocated
eingriff_neg	Action limit negative	integer	The limit values are indicated in % of the target value. (PDM field ID: ZYP.UEG)
eingriff_pos	Action limit positive	integer	Action limit positive, negative: Percentage rates can be indicated here for which a warning is triggered when these rates are reached. Therefore, the action limits should be defined within a narrower range than the tolerance limits. The limit values are indicated in % of the target value. (PDM field ID: ZYP.OEG)
einheit		char(6)	Not allocated
masch_nr	Resource	char(20)	Number of the machine to be collected (PDM field ID: ZYP.MNR)
mess_beginn		char(1)	Not allocated
mess_speichern		char(1)	Not allocated
mess_start		smallint	Not allocated
messkanal		smallint	Always enter 0 as the measuring channel 0 is only evaluated
messtellen		char(15)	Not allocated
messwert_kenn1		char(3)	Not allocated
messwert_kenn2		char(3)	Not allocated
messwert_kenn3		char(3)	Not allocated
messwert_kenn4		char(3)	Not allocated
messwert_kenn5		char(3)	Not allocated
messwert_wahl		smallint	free
pdv_stoer_neg		char(1)	free
pdv_stoer_epos		char(1)	Not allocated
pdv_stoer_tneg		char(1)	Not allocated
pdv_stoer_tpos		char(1)	Not allocated
signal_neg		char(1)	Action limits should be defined tighter than tolerance limits. Violation of action limits is a warning that the tolerance limit will be reached soon.
signal_epos		char(1)	Tolerance +/- :

signal_tneg		char(1)	Admissible tolerance limits must not be exceeded
signal_tpos		char(1)	Tolerance +/- :
sollwert_gr		integer	Not allocated
toleranz_neg	Tolerance limit negative	integer	The limit values are indicated in % of the target value. (PDM field ID: ZYP.UTG)
toleranz_pos	Tolerance limit positive	integer	Tolerance limit positive, negative: the percentage rates indicated here must not be exceeded or fallen short of. The cycle time of the operation logged on is always referenced as target value for the cycle time monitoring. The limit values are indicated in % of the target value. (PDM field ID: ZYP.OTG)
uhrzeit		integer	Not allocated
umrechn_faktor		integer	Not allocated
verweis		serial	Distinct number
wertart_neg		char(1)	Not allocated
wertart_epos		char(1)	Not allocated
wertart_tneg		char(1)	Not allocated
wertart_tpos		char(1)	Not allocated

7.13. stoer_tab_hierarc

Table name: stoer_tab_hierarc		Product: MDE	
Designation: Machine/workplace conditions			
Column name	Column designation	Type	Description
m_status		smallint	Machine status Mandatory field (PDM field ID: MST.MST:UEB)
m_substatus		smallint	Machine sub status Mandatory field (PDM field ID: MST.MST)
masch_nr		char(20)	Machine number, which the disturbance is assigned to Mandatory field (PDM field ID: MST.MNR)
stufe		smallint	0..9: may only be assigned by persons whose personal_bestand.m_stufe > than level (Stufe) default = "0" (PDM field ID: MST.MSTUFE)

7.14. stoer_tabelle

Table name: stoer_tabelle		Product: MDE	
Designation: Machine/workplace conditions		Description: Defintion of the different machine/workplace statuses that can occur. # Special remarks With creating a new workplace/maschine using the appropriate service two statuses 20000 ("NO SHIFT") and 30000 ("NOT ASSIGNED") are automatically created. They must not be deleted. # Key masch_nr, stoernr # Connections to other tables maschinen.masch_nr = stoer_tabelle.masch_nr stoertexte.stoertxt_nr = stoer_tabelle.stoertxt_nr bm_konten.bmk = stoer_tabelle.bmk (outer join) mz_stklasse.kuerzel = stoer_tabelle.klasse (outer join) ade_grund_zuord.grund (art=A) = stoer_tabelle.aus_grund (outer join) ade_grund_zuord.grund (art=A) = stoer_tabelle.aus_grund_psperr (outer join) auftrags_bestand.auftrag_nr = stoer_tabelle.folge_auftrag_nr (outer join)	
Column name	Column designation	Type	Description
abbruchgrund		char(1)	Reserved for future use. (PDM field ID: MST.OPT:ABBGRD)
auftragsmeldung	Operation posting	char(5)	[1,1] : operation posting when the status is assigned manually K/blank: No processing U: Automatic interruption of all running OPs at the workplace and logoff all persons logged on the the workplace A: Automatic interruption of all running OPs at the workplace and logoff all persons logged on the the workplace. Then logon of the operation defined in field folge_auftrag_nr [2,2] : not supported, leave blank [3,3] : Take over active persons J: Take over (log on) active persons to the following operation defined in field folge_auftrag_nr N: No processing (PDM field ID: MST.MELDOPT:1..5)
aus_grund	Scrap reason	integer	Automatic scrap reason that is assigned to automatically recorded scrap during the actual status (production lock is not active) (PDM field ID: MST.GR:AUSNRAUTO)
aus_grund_psperr	Scrap reason during production lock	integer	Automatic scrap reason during production lock is active. (PDM field ID: MST.GR:AUSNRPSPERRE)
automatic	Automatically via digital input	char(1)	This option must be activated if a status assignment is made automatically via machine interface (CT-MSS, CT-UMPS, PCC). J: Processing is activated. The number of the digital input through which a status occurrence is detected must be entered in the field zuord_nr N: No processing (PDM field ID: MST.OPT:AUTO)
bearb		char(10)	Reserved for future use.
bearb_date		date	Reserved for future use.
bearb_time		integer	Reserved for future use.
blinkzeit		integer	Reserved for future use.
bmk	Resource performance account	char(3)	Resource performance account (RPA/BMK) to which the status is assigned. Reference to bm_konten.kuerzel This value must exist in database table bm_konten (PDM field ID: MST.BMKNR)
farbe		integer	Not supported. The color of a status is defined in the database table stoertexte.
folge_auftrag_nr	Order number of follow-up operation	char(40)	This operation (Order number) is automatically logged on if auftragsmeldungen[1,1] = 'A' (PDM field ID: MST.ANRN)

klasse	Status class	char(3)	Status class to which the status is assigned. Reference to mz_stklasse.kuerzel This value must exist in database table mz_stklasse (PDM field ID: MST.STKL)
kosten_art		integer	Used for bonus calculations default = 0
last_kst01	(multiple use)	char(10)	[1]-[3] : Reserved [4] : Use of unplanned material J - Use of unplanned material is allowed, i.e. batches that are not specified in the input material list at the operation can be logged on as input material N - Use of unplanned material is not allowed [5]-[10] : Reserved (PDM field ID: (Composed of several acronyms))
last_kst02	(multiple use)	char(10)	[1] : Machine-related and/or order-related standstill reason M - machine-related -> status is only allowed if no OP is active A - order-related -> status only allowed if at least one OP is active X/empty - not machine-related and not order-related (no check) [2]-[10] : Reserved (PDM field ID: (Composed of several acronyms))
last_kst03	(multiple use)	char(10)	Reserved (PDM field ID: (Composed of several acronyms))
last_kst04	(multiple use)	char(10)	Reserved (PDM field ID: MST.SAPSTKL)
last_kst05	(multiple use)	char(10)	[1] : Activate production lock J - Activate production lock when status is set by the terminal or PCC N - Deactivate production lock when status is set by the terminal or PCC [2-8] : Reserved [9] : Transfer of the status of the line to the aggregates J - Transfer of the status of the line to the aggregates (MDE-SFL only) N - Do not transfer of the status of the line to the aggregates (MDE-SFL only) [10] : Reserved (PDM field ID: (Composed of several acronyms))
manuell	Manually at terminal	char(1)	Plausibility check, if operator can assign this status manually J : Operator can enter this status manually at the terminal. N: Operator can enter this status manually at the terminal. Status will no longer be displayed in the status selection list at the terminal. (PDM field ID: MST.OPT:MANU)
masch_nr	Workplace	char(20)	Workplace/Machine number to which the status is assigned (mandatory). (PDM field ID: MST.MNR)
p_abmeld	Log staff off	char(1)	Automatism to log of persons when status is set J : all persons currently logged on are logged off when this status is set. N : persons stay logged on. (PDM field ID: MST.OPT:PAB)
prod_kenn	Control characteristic	char(1)	The following identifiers are available to control machine monitoring. Except for the "production" control indicator, all following control indicators are only allowed for machines/workplaces of the type "individual workplace". P: designates "production", to be defined exactly once per workplace S: designates "all other status", a maximum of 9999 entries per workplace (type "individual workplace") A: designates the "general disturbance", to be defined exactly once per machine (type "individual workplace") Z: designates "short-term disturbance", to be defined max. once per machine (type "individual workplace") H: designates the status as "hierarchy level" (type "individual workplace") N: is used internally for "not assigned" at the terminal O: no order: the terminal automatically sets this status when the last operation is interrupted/logged off, to be defined max. once per machine (type "individual workplace") (PDM field ID: MST.OPT:PKENN)
prog_stillstd_zeit	Estimated downtime	integer	Once a status is set, an estimated downtime can be entered during manual status assignment. In the process, the downtime defined in the master data is shown as a suggestion. During automatic status change, the downtime defined in the master data is automatically set. (PDM field ID: MST.PROGNDAUER)
psperre		char(1)	Reserved

sperre	Set machine lock output	char(1)	This option must be set if machine lock should be activated during status assignment. If it is, you must also ensure that machine lock output is configured accordingly in the machine configuration. J: activate machine lock for this status N: deactivate/do not set machine lock (PDM field ID: MST.OPT:MSPERRE)
stoernr	Status	smallint	Number of the machine status (mandatory) Numbers > 9999 are reserved for internal processing purposes - e.g.: 20000 : NO SHIFT 30000 : NOT ASSIGNED (PDM field ID: MST.MST)
stoernr_uebord	Superior status	smallint	If no status is defined in the superior status field, then this relates to a status of the uppermost level. Otherwise, the number entered here is the one for the status directly above it. This status must already exist and be provided with a "hierarchy level" control characteristic (PDM field ID: MST.MST:UEB)
stoertxt_nr	Status text	smallint	Reference to status text in table stoertexte (mandatory) (PDM field ID: MST.STNR)
stufe	Authorization	char(1)	Access authorization for entering a status at the terminal (a value from 0 to 9). An authorization level for machine status modification is defined for every person in the HR master data. If the authorization level in the master data is lower than the authorization defined here, the operator cannot assign this status at the terminal. Default: 0 (PDM field ID: MST.MSTUFE)
ueblinie		char(1)	Reserved
user_c_07	User-specific field	char(1)	(PDM field ID: MST.FU:07)
user_c_08	User-specific field	char(1)	
user_c_09	User-specific field	char(1)	
user_c_10	User-specific field	char(1)	
user_c_11	User-specific field	char(1)	
user_c_12	User-specific field	char(10)	
user_c_13	User-specific field	char(10)	
user_c_14	User-specific field	char(20)	
user_c_15	User-specific field	char(20)	
user_c_16	User-specific field	char(40)	
user_code	User field key	char(8)	User field key for object typ "MST". Only "DEFAULT" is supported.
user_f_05	User-specific field	decimal(18,6)	
user_f_06	User-specific field	decimal(18,6)	
user_n_01	User-specific field	integer	(PDM field ID: MST.FU:01)
user_n_02	User-specific field	integer	
user_n_03	User-specific field	integer	
user_n_04	User-specific field	integer	
zuord_nr	Digital input	smallint	Number of the digital input, if automatic > 0 default = 0 (PDM field ID: MST.DIGIN:AUTO)
zuordnung		char(1)	Reserved

7.15. stoertexte

Table name: stoertexte		Product: MDE	
Designation: Workplace/machine status texts		Description: Definition of all possible workplace/machine states (statuses). These status texts are then used in the status assignment. The goal is to use standard status texts for all workplaces and machines. # Special remarks Important states that have always to be available: 20000 NO SHIFT 30000 NOT ASSIGNED # Key stoertxt_nr # Connections to other tables Each machine status must be assigned to a status text: stoer_tabelle.stoertxt_nr = stoertexte.stoertxt_nr Status text number are stored in the workplace-related result record: ereignis.stoertxt_nr = stoertexte.stoertxt_nr	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
farbe	Color	integer	obsolete (PDM field ID: MSTTXT.COLOR)
rgbcolor	Color	integer	Color code in RGB format (RGB - red/green/blue)
stoer_text	Designation	char(20)	Informative description of the status. This text is displayed at the terminal, among other places. Recommendation: Use uppercase letters (PDM field ID: MSTTXT.MSTTXT)
stoertxt_nr	Status text	smallint	Unique number of the text of the status Important status text that have always to be available: 20000 NO SHIFT 30000 NOT ASSIGNED (PDM field ID: MSTTXT.STNR)

7.16. system_j_mod

Table name: system_j_mod		Product: MDE	
Designation: BDE (PDC) year model		Description: Definition of the year model for the production data collection. Each work day is assigned exactly to a day type in the year model. Each machine can be assigned to exactly one year model. # Special remarks A year model has to be assigned to each workplace/machine as otherwise there will be no time recording. A different year model can optionally be assigned to a workplace/machine for considering in the shopfloor planning (HLS). Only one year model may be defined as a factory calendar. # Key jahr, schicht_mod # Connections to other tables A year model is assigned to a machine: maschinen.schichtmod = system_j_mod.schicht_mod personen.stamm_j_mod = system_j_mod.schicht_mod (optional) For scheduling purposes (HLS) the following connections are possible: maschinen.plan_j_mod = system_j_mod.schicht_mod hy_gruppen.schichtmod = system_j_mod.schicht_mod	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	
bearb_date	Last editing day	date	
bearb_time	Last editing time	integer	
jahr	Year	smallint	Year in 4 digits, e.g. 2018 (PDM field ID: BDEJMOD.JAHR)
kommentar	Designation	char(20)	Designation of the year model (PDM field ID: BDEJMOD.BEZ)
modell	Day model structure	char(1464)	For each day in the year (max, 366 days) 4 characters are provided for a day model: 4 * 366 = 1464 characters When considering days off (no shifts) during configuration then blanks are stored at the corresponding day position. (PDM field ID: BDEJMOD.MODELL)
schicht_mod	Year model	smallint	Number of the year model (PDM field ID: BDEJMOD.BDEJMOD)
werkskalender	Factory calendar	char(1)	A comprehensive factory calendar is used in the shopfloor scheduling (HLS). The factory calendar is used, for example, to determine the horizons (e.g. dispatching horizon). J = factory calendar N or blank = not a factory calendar

7.17. system_t_mod

Table name: system_t_mod		Product: MDE	
Designation: BDE (PDC) day model		Description: The planned working times and break times for up to four shifts for each day are defined in a day model. # Special remarks Day types must first be defined before the shift plan can be created for each work day. For technical reasons, a shift may not start or end at 12:00 am (midnight). Only the last shift of a day model may include a day change (e.g. 10.00 pm - 6.00 am)! # Key tag_nr # Connections to other tables You assign BDE day models to BDE year models. Due to the way of saving the day model in a year model a SQL join is not possible. Day model determination of the n-th day of a year (pseudocode): position = (n-1) * 4 system_t_mod.tag_nr = substring(system_j_mod.modell, position, 4)	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
gueltig	Number of shifts	smallint	Indicates how many shifts of the max. 4 shifts are actually used.
kommentar	Designation	char(20)	Designation of the shift model (PDM field ID: BDETMOD.BEZ)
s1_anfang	Beginning of shift 1	integer	Beginning of shift 1 seconds as of midnight (PDM field ID: BDETMOD.SKZEIB:1)
s1_ende	End of shift 1	integer	End of shift 1 in seconds as of midnight. (PDM field ID: BDETMOD.SKZEIE:1)
s1_frei	Automatic status change to status 999 in shift 1	smallint	Automatic status change to status 999 (only relevant for MDE configuration - see documentation) 0 : automatic status change is not active 60 : activate status 999 after the end of the shift 120 : deactivate status 999 at the beginning of the shift (PDM field ID: BDETMOD.SKAMST:1)
s1_p1_anf	Beginning of break 1 in shift 1	integer	Beginning of break 1 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP1ZEIB:1)
s1_p1_end	End of break 1 in shift 1	integer	End of break 1 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP1ZEIE:1)
s1_p2_anf	Beginning of break 2 in shift 1	integer	Beginning of break 2 in shift 1 seconds as of midnight (PDM field ID: BDETMOD.SKP2ZEIB:1)
s1_p2_end	End of break 2 in shift 1	integer	End of break 2 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP2ZEIE:1)
s1_p3_anf	Beginning of break 3 in shift 1	integer	Beginning of break 3 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP3ZEIB:1)
s1_p3_end	End of break 3 in shift 1	integer	End of break 3 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP3ZEIE:1)
s1_p4_anf	Beginning of break 4 in shift 1	integer	Beginning of break 4 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP4ZEIB:1)
s1_p4_end	End of break 4 in shift 1	integer	End of break 4 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP4ZEIE:1)

s1_p5_anf	Beginning of break 5 in shift 1	integer	Beginning of break 5 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP5ZEIB:1)
s1_p5_end	End of break 5 in shift 1	integer	End of break 5 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP5ZEIE:1)
s1_p6_anf	Beginning of break 6 in shift 1	integer	Beginning of break 6 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP6ZEIB:1)
s1_p6_end	End of break 6 in shift 1	integer	End of break 6 in shift 1 in seconds as of midnight (PDM field ID: BDETMOD.SKP6ZEIE:1)
s1_pers_anz_prod	Number of personnel capacity for production in shift 1	decimal(18,6)	There group utilization in the graphic planning board (HLS) is calculated based on the defined shift calendar and the planned production capacities. If no personnel capacity is defined, the system implicitly assumes capacity 1.
s1_pers_anz_ruest		decimal(18,6)	Reserved for future use.
s1_schichtart	Shift indicator shift 1	char(1)	Shift indicator that is independent of the shift number (e.g. E=early shift, L=late shift, N=night shift) (PDM field ID: BDETMOD.SKART:1)
s1_stat999_beginn		char(1)	Reserved for future use.
s2_anfang	Beginning of shift 2	integer	Beginning of shift 2 in sec. as of midnight (PDM field ID: BDETMOD.SKZEIB:2)
s2_ende	End of shift 2	integer	End of shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKZEIE:2)
s2_frei	Automatic status change to status 999 in shift 2	smallint	Automatic status change to status 999 (only relevant for MDE configuration - see documentation) 0 : automatic status change is not active 60 : activate status 999 after the end of the shift 120 : deactivate status 999 at the beginning of the shift (PDM field ID: BDETMOD.SKAMST:2)
s2_p1_anf	Beginning of break 1 in shift 2	integer	Beginning of break 1 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP1ZEIB:2)
s2_p1_end	End of break 1 in shift 2	integer	End of break 1 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP1ZEIE:2)
s2_p2_anf	Beginning of break 2 in shift 2	integer	Beginning of break 2 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP2ZEIB:2)
s2_p2_end	End of break 2 in shift 2	integer	End of break 2 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP2ZEIE:2)
s2_p3_anf	Beginning of break 3 in shift 2	integer	Beginning of break 3 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP3ZEIB:2)
s2_p3_end	End of break 3 in shift 2	integer	End of break 3 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP3ZEIE:2)
s2_p4_anf	Beginning of break 4 in shift 2	integer	Beginning of break 4 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP4ZEIB:2)
s2_p4_end	End of break 4 in shift 2	integer	End of break 4 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP4ZEIE:2)
s2_p5_anf	Beginning of break 5 in shift 2	integer	Beginning of break 5 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP5ZEIB:2)
s2_p5_end	End of break 5 in shift 2	integer	End of break 5 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP5ZEIE:2)
s2_p6_anf	Beginning of break 6 in shift 2	integer	Beginning of break 6 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP6ZEIB:2)
s2_p6_end	End of break 6 in shift 2	integer	End of break 6 in shift 2 in seconds as of midnight (PDM field ID: BDETMOD.SKP6ZEIE:2)
s2_pers_anz_prod	Number of personnel capacity for production in shift 2	decimal(18,6)	Please see s1_pers_anz_prod
s2_pers_anz_ruest		decimal(18,6)	Reserved for future use.

s2_schichtart	Shift indicator shift 2	char(1)	Shift indicator Determination of a shift indicator that is independent of the previous shift number (CHAR, similar to PZE: early, late, night) à In all reports/analyses (ADE and MDE) it is no longer evaluated according to the shift number but to the shift type. The previous shift number (1,2,3,4) is only used for internal purposes and does not influence the reports/analyses, i.e. the analyses/reports have to be made in accordance with this indicator. à Additional field everywhere where the (current, previous) shift number is saved as well (ade_protokoll, etc.) à Level 1: allow only numerical values; thus the effort when converting the reports/analyses (e.g. MDE) is reduced at first. à OPEN: possibly, the numerical shift indicator is additionally assigned to a text, e.g. "early shift" via an entry in the reflat (PDM field ID: BDETMOD.SKART:2)
s2_stat999_beginn		char(1)	Reserved for future use.
s3_anfang	Beginning of shift 3	integer	Beginning of shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKZEIB:3)
s3_ende	End of shift 3	integer	End of shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKZEIE:3)
s3_frei	Automatic status change to status 999 in shift 3	smallint	Automatic status change to status 999 (only relevant for MDE configuration - see documentation) 0 : automatic status change is not active 60 : activate status 999 after the end of the shift 120 : deactivate status 999 at the beginning of the shift (PDM field ID: BDETMOD.SKAMST:3)
s3_p1_anf	Beginning of break 1 in shift 3	integer	Beginning of break 1 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP1ZEIB:3)
s3_p1_end	End of break 1 in shift 3	integer	End of break 1 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP1ZEIE:3)
s3_p2_anf	Beginning of break 2 in shift 3	integer	Beginning of break 2 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP2ZEIB:3)
s3_p2_end	End of break 2 in shift 3	integer	End of break 2 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP2ZEIE:3)
s3_p3_anf	Beginning of break 3 in shift 3	integer	Beginning of break 3 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP3ZEIB:3)
s3_p3_end	End of break 3 in shift 3	integer	End of break 3 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP3ZEIE:3)
s3_p4_anf	Beginning of break 4 in shift 3	integer	Beginning of break 4 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP4ZEIB:3)
s3_p4_end	End of break 4 in shift 3	integer	End of break 4 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP4ZEIE:3)
s3_p5_anf	Beginning of break 5 in shift 3	integer	Beginning of break 5 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP5ZEIB:3)
s3_p5_end	End of break 5 in shift 3	integer	End of break 5 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP5ZEIE:3)
s3_p6_anf	Beginning of break 6 in shift 3	integer	Beginning of break 6 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP6ZEIB:3)
s3_p6_end	End of break 6 in shift 3	integer	End of break 6 in shift 3 in seconds as of midnight (PDM field ID: BDETMOD.SKP6ZEIE:3)
s3_pers_anz_prod	Number of personnel capacity for production in shift 3	decimal(18,6)	Please see s1_pers_anz_prod
s3_pers_anz_ruest		decimal(18,6)	Reserved for future use.
s3_schichtart	Shift indicator shift 3	char(1)	Shift indicator Determination of a shift indicator that is independent of the previous shift number (CHAR, similar to PZE: early, late, night) à In all reports/analyses (ADE and MDE) it is no longer evaluated according to the shift number but to the shift type. The previous shift number (1,2,3,4) is only used for internal purposes and does not influence the reports/analyses, i.e. the analyses/reports have to be made in accordance with this indicator. à Additional field everywhere where the (current, previous) shift number is saved as well (ade_protokoll, etc.) à Level 1: allow only numerical values; thus the effort when converting the reports/analyses (e.g. MDE) is reduced at first. à OPEN: possibly, the numerical shift indicator is additionally assigned to a text, e.g. "early shift" via an entry in the reflat (PDM field ID: BDETMOD.SKART:3)
s3_stat999_beginn		char(1)	Reserved for future use.
s4_anfang	Beginning of shift 4	integer	Beginning of shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKZEIB:4)

s4_ende	End of shift 4	integer	End of shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKZEIE:4)
s4_frei	Automatic status change to status 999 in shift 4	smallint	Automatic status change to status 999 (only relevant for MDE configuration - see documentation) 0 : automatic status change is not active 60 : activate status 999 after the end of the shift 120 : deactivate status 999 at the beginning of the shift (PDM field ID: BDETMOD.SKAMST:4)
s4_p1_anf	Beginning of break 1 in shift 4	integer	Beginning of break 1 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP1ZEIB:4)
s4_p1_end	End of break 1 in shift 4	integer	End of break 1 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP1ZEIE:4)
s4_p2_anf	Beginning of break 2 in shift 4	integer	Beginning of break 2 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP2ZEIB:4)
s4_p2_end	End of break 2 in shift 4	integer	End of break 2 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP2ZEIE:4)
s4_p3_anf	Beginning of break 3 in shift 4	integer	Beginning of break 3 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP3ZEIB:4)
s4_p3_end	End of break 3 in shift 4	integer	End of break 3 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP3ZEIE:4)
s4_p4_anf	Beginning of break 4 in shift 4	integer	Beginning of break 4 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP4ZEIB:4)
s4_p4_end	End of break 4 in shift 4	integer	End of break 4 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP4ZEIE:4)
s4_p5_anf	Beginning of break 5 in shift 4	integer	Beginning of break 5 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP5ZEIB:4)
s4_p5_end	End of break 5 in shift 4	integer	End of break 5 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP5ZEIE:4)
s4_p6_anf	Beginning of break 6 in shift 4	integer	Beginning of break 6 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP6ZEIB:4)
s4_p6_end	End of break 6 in shift 4	integer	End of break 6 in shift 4 in seconds as of midnight (PDM field ID: BDETMOD.SKP6ZEIE:4)
s4_pers_anz_prod	Number of personnel capacity for production in shift 4	decimal(18,6)	Please see s1_pers_anz_prod
s4_pers_anz_ruest		decimal(18,6)	Reserved for future use.
s4_schichtart	Shift indicator shift 4	char(1)	Shift indicator Determination of a shift indicator that is independent of the previous shift number (CHAR, similar to PZE: early, late, night) à In all reports/analyses (ADE and MDE) it is no longer evaluated according to the shift number but to the shift type. The previous shift number (1,2,3,4) is only used for internal purposes and does not influence the reports/analyses, i.e. the analyses/reports have to be made in accordance with this indicator. à Additional field everywhere where the (current, previous) shift number is saved as well (ade_protokoll, etc.) à Level 1: allow only numerical values; thus the effort when converting the reports/analyses (e.g. MDE) is reduced at first. à OPEN: possibly, the numerical shift indicator is additionally assigned to a text, e.g. "early shift" via an entry in the reflist (PDM field ID: BDETMOD.SKART:4)
s4_stat999_beginn		char(1)	Reserved for future use.
tag_nr	Day model	smallint	Identifier of the model: 1..9999 (PDM field ID: BDETMOD.SKMODNR)

8. MLE

8.1. hysap_dist_mod

Table name: hysap_dist_mod		Product: MLE	
Designation: MLE distribution model			
Column name	Column designation	Type	Description
bearb		char(10)	last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
dm_cmd	Processing program	char(50)	Program or script to be started as INBOUND processing process. If a script (.scr) is indicated here the start of a Shell is preceded under Windows. (PDM field ID: HSVERTMOD.PROG)
dm_cmdparam	Command parameters	char(50)	Parameter of the program to be started (PDM field ID: HSVERTMOD.PROGPARAM)
dm_desc	Description	char(40)	Description of the model (PDM field ID: HSVERTMOD.BEZ)
dm_dest	Logical target system for output process	char(10)	Logical target system for output processing (PDM field ID: HSVERTMOD.HSSYS)
dm_direct	Input/output	char(1)	I: INBOUND O: OUTBOUND (PDM field ID: HSVERTMOD.OPT:IO)
dm_keepdays	Delete interval	integer	Number of days after which data records of the type described here are archived and thus can be deleted from the active dataset. (PDM field ID: HSVERTMOD.DELINT)
dm_param1		char(40)	Possible parameters for transfer
dm_param2		char(40)	Possible parameters for transfer
dm_prio	Priority	integer	0 - no priority (normal) 1 - high priority (e.g. for upload request) (PDM field ID: HSVERTMOD.PRIO)
dm_sap_cimtyp	Extension of IDOC type	char(30)	Subsegment (PDM field ID: HSVERTMOD.IDOCEXT)
dm_sap_idoctyp	IDOC Typ	char(30)	IDoc type used (PDM field ID: HSVERTMOD.IDOC)
dm_sap_mescod	Message code	char(3)	Message code (PDM field ID: HSVERTMOD.MSGVAR)
dm_sap_mesfct	Message function	char(3)	Example: UPD, APP, DEL (not used for SAP-BAPIs) (PDM field ID: HSVERTMOD.MSGFKT)
dm_sap_mestyp	Identification for program selection	char(30)	Identification for program selection (PDM field ID: HSVERTMOD.MSGTYP)
dm_sap_segnam01	Segment name for upload	char(30)	Segment name for upload (1) -> PRIMARY output control (PDM field ID: HSVERTMOD.SEG:1)
dm_sap_segnam02	Segment name 2	char(30)	Segment name An alternative file name can be entered here at the fileport (otherwise sag_segnam01 = file name applies) (PDM field ID: HSVERTMOD.SEG:2)
dm_sap_segnam03	Segment name 3	char(30)	Segment name (PDM field ID: HSVERTMOD.SEG:3)
dm_sap_segnam04	Segment name 4	char(30)	Segment name (PDM field ID: HSVERTMOD.SEG:4)

dm_sap_segnam05	Segment name 5	char(30)	Segment name (PDM field ID: HSVERTMOD.SEG:5)
dm_sap_segnam06	Segment name 6	char(30)	Segment name (PDM field ID: HSVERTMOD.SEG:6)
dm_sap_segnam07	Segment name 7	char(30)	Segment name (PDM field ID: HSVERTMOD.SEG:7)
dm_sap_segnam08	Segment name 8	char(30)	Segment name (PDM field ID: HSVERTMOD.SEG:8)
dm_sap_segnam09	Segment name 9	char(30)	Segment name (PDM field ID: HSVERTMOD.SEG:9)
dm_sap_segnam10	Segment name 10	char(30)	Segment name (PDM field ID: HSVERTMOD.SEG:10)
dm_sap_test	Test flag	char(1)	Test flag (PDM field ID: HSVERTMOD.OPT:TEST)
dm_sourcesys	SAP target system	char(10)	Intended to differentiate between different target systems with respect to a segment type (PDM field ID: HSVERMOD.SAPSYS)

8.2. hysap_inbound_ctrl

Table name: hysap_inbound_ctrl		Product: MLE	
Archive table: hysap_in_ctrl_a			
Designation: MLE INBOUND control records			
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
param1	Possible parameters	char(40)	Possible, additional parameters
param2	Possible parameters	char(40)	Possible, additional parameters
sap_arckey		char(70)	Key of the external message archive
sap_cimtyp		char(30)	Subsegment (e.g. for customer-specific enhancements, future-proof)
sap_creat		date	Creation date (in SAP)
sap_cretim	Number of attempts	integer	Creation time (in SAP)
sap_direct		char(1)	Transfer direction (viewed from R/3)
sap_docnum	IDOC Number	char(16)	IDOC Number
sap_docrel	IDOC-Release	char(4)	IDOC-Release
sap_exprss		char(1)	Overriding in input
sap_idoctyp	IDoc type	char(30)	IDOC type
sap_mandt	Client	char(3)	Client
sap_mescod		char(3)	Message variant
sap_mesfct	Message function	char(3)	Message function
sap_mestyp	Message type	char(30)	Message type
sap_outmod		char(1)	Output mode of IDocs in R/3
sap_rcvld		char(70)	The recipient's log. address
sap_rcvpfc		char(2)	Partner function during IDoc communication with SAP
sap_rcvpor	Receiver port	char(10)	Recipient port
sap_rcvprn	Receiver partner no.	char(10)	The recipient's partner number (log. system)
sap_rcvppt	Receiver partner type	char(2)	Partner type
sap_rcvsad		char(21)	Recipient's address
sap_refgrp		char(14)	Message group (EDI)
sap_refint	Duration	char(14)	Transfer file (EDI)
sap_refmes		char(14)	Message (EDI)
sap_serial		char(20)	Serialization
sap_sndld		char(70)	The sender's logical address
sap_sndpfc		char(2)	The recipient's partner role
sap_sndpor	SAP sending port	char(10)	Sender port
sap_sndprn	SAP sending partner no.	char(10)	The sender's partner number (log. system)
sap_sndprt	SAP sending partner type	char(2)	Partner type
sap_sndsad		char(21)	Return address
sap_status		char(2)	Status of IDoc processing
sap_std		char(1)	EDI standard ID

sap_stdmes		char(6)	EDI message type
sap_stdvrs		char(6)	EDI standard, version, release
sap_tabnam		char(10)	Name of table structure
sap_test		char(1)	Test indicator
ta_id	Transaction ID	char(30)	Transaction ID
ta_idone	No. of edited DR	integer	Number of processed data records in transaction
ta_lerror	No. of erroneous DR	integer	Number of faulty data records in transaction
ta_lines	No. of data records	integer	Number of data records in transaction
ta_logsys		char(10)	Logical system from which the data were transferred
ta_lunknown	No. of unknown DR	integer	Number of unknown data records in transaction
ta_savdate		date	Date of receipt
ta_savtime		integer	Time of receipt
ta_status	Status of processing	char(3)	Status of processing HYSAP_STAT_NEW "000" HYSAP_STAT_TODO "001" HYSAP_STAT_REACTIVATED "002" HYSAP_STAT_INPROCESS "100" HYSAP_STAT_UNKNOWN "089" HYSAP_STAT_DONE_ERR "097" HYSAP_STAT_DONE_UNK "098" HYSAP_STAT_DONE_ALL "099"
ta_type	Description of the structure type	char(5)	Description of the structure type
ta_workdate		date	Date of processing
ta_worktime		integer	Time of processing
verweis	Reference	serial	Consecutive number (allocated by database)

8.3. hysap_inbound_data

Table name: hysap_inbound_data		Product: MLE	
Archive table: hysap_in_data_a			
Designation: MLE INBOUND data records			
Column name	Column designation	Type	Description
bearb		char(10)	last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
ds_savdate	Date of receipt in HYSAP	date	Date of receipt in HYSAP
ds_savtime		integer	Time of receipt in HYSAP
ds_status	Status of the segment	char(3)	Status of the segment HYSAP_DSSTAT_NEW "000" HYSAP_DSSTAT_TODO "001" HYSAP_DSSTAT_INPROCESS "100" HYSAP_DSSTAT_SUBINPROCESS "101" HYSAP_DSSTAT_CREATION "200" /* der Datensatz- / bzw. dessen Untersegment wird gerade erzeugt */ HYSAP_DSSTAT_CHILD "007" /* Kindsegment mit Zusatzdaten */ HYSAP_DSSTAT_ERROR "079" HYSAP_DSSTAT_UNKNOWN "089" HYSAP_DSSTAT_DONE "099"
ds_workdate	Date of last processing	date	Date of last processing
ds_worktime	Time of last processing	integer	Time of last processing
param1	Possible parameters to be transferred	char(40)	Possible parameters to be transferred
param2		char(40)	param2[40,40] : EOL flag;
sap_docnum	Number of the IDoc	char(16)	Number of the IDoc
sap_hlevel	Hierarchy level	char(2)	Hierarchy level
sap_mandt	Client	char(3)	Client
sap_psgnum	Number of the parent segment (if availab	char(6)	Number of the parent segment (if available)
sap_sdata	IDoc data	char(4000)	IDoc data
sap_segnam	Segment	char(30)	Segment
sap_segnum	Segment no.	char(6)	Segment number
ta_id	Transaction ID	char(30)	Transaction ID
verweis	Consecutive number	serial	Consecutive number

8.4. hysap_logsys

Table name: hysap_logsys		Product: MLE	
Designation: MLE Partner system			
Column name	Column designation	Type	Description
act_role	Active role	char(1)	Description if test or productive system (PDM field ID: HSSYS.ROLE)
bearb		char(10)	last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
logsys	Logical system	char(10)	--- (PDM field ID: HSSYS.HSSYS)
ls_desc	Description	char(40)	Description of target system (PDM field ID: HSSYS.BEZ)
param1	Communication mode	char(40)	CONNMODE [1,1] Connectionmode R / leer = HYSAP_CONNMODE_RFC F = HYSAP_CONNMODE_FILE P = HYSAP_CONNMODE_PDM W = HYSAP_CONNMODE_WEBSERVICE (only MW4pe)
param2		char(40)	Possible parameters for transfer

8.5. hysap_logsys_cfg

Table name: hysap_logsys_cfg		Product: MLE	
Designation: MLE System configuration			
Column name	Column designation	Type	Description
bearb		char(10)	last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
logsys		char(10)	Description for target system (PDM field ID: HSSYSCFG.HSSYS)
param1		char(40)	Possible parameters for transfer
param2		char(40)	Possible parameters for transfer
param_name01	Parameter name 1	char(30)	Parameter name from RFC-ini (PDM field ID: HSSYSCFG.KEY:1)
param_name02	Parameter name 2	char(30)	Parameter name from RFC-ini (PDM field ID: HSSYSCFG.KEY:2)
param_name03	Parameter name 3	char(30)	Parameter name from RFC-ini (PDM field ID: HSSYSCFG.KEY:3)
param_name04	Parameter name 4	char(30)	Parameter name from RFC-ini (PDM field ID: HSSYSCFG.KEY:4)
param_name05	Parameter name 5	char(30)	Parameter name from RFC-ini (PDM field ID: HSSYSCFG.KEY:5)
param_name06	Parameter name 6	char(30)	Parameter name from RFC-ini (PDM field ID: HSSYSCFG.KEY:6)
param_name07	Parameter name 7	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:7)
param_name08	Parameter name 8	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:8)
param_name09	Parameter name 9	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:9)
param_name10	Parameter name 10	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:10)
param_name11	Parameter name 11	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:11)
param_name12	Parameter name 12	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:12)
param_name13	Parameter name 13	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:13)
param_name14	Parameter name 14	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:14)
param_name15	Parameter name 15	char(30)	Parameter name (PDM field ID: HSSYSCFG.KEY:15)
param_val01	Parameter value 1	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:1)
param_val02	Parameter value 2	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:2)
param_val03	Parameter value 3	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:3)
param_val04	Parameter value 4	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:4)

param_val05	Parameter value 5	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:5)
param_val06	Parameter value 6	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:6)
param_val07	Parameter value 7	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:7)
param_val08	Parameter value 8	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:8)
param_val09	Parameter value 9	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:9)
param_val10	Parameter value 10	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:10)
param_val11	Parameter value 11	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:11)
param_val12	Parameter value 12	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:12)
param_val13	Parameter value 13	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:13)
param_val14	Parameter value 14	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:14)
param_val15	Parameter value 15	char(80)	Parameter value from RFC-ini (PDM field ID: HSSYSCFG.VAL:15)
prog_typ	Program type	char(2)	Entry whether client or server (PDM field ID: HSSYSCFG.PROGTYP)
role	Role	char(1)	Fixture for spec. config. for C/S (PDM field ID: HSSYSCFG.ROLE)
sap_rcvpor	RCV port	char(10)	Receiver port (PDM field ID: HSSYSCFG.PORT:RCV)
sap_rcvprn	RCV partner number	char(10)	Partner number of receiver (PDM field ID: HSSYSCFG.PARTNR:RCV)
sap_rcvppt	RCV partner	char(2)	Partner type of receiver (PDM field ID: HSSYSCFG.PART:RCV)
sap_sndpor	SND port	char(10)	Sending system port (PDM field ID: HSSYSCFG.PORT:SND)
sap_sndprn	SND partner number	char(10)	Partner number of sender (PDM field ID: HSSYSCFG.PARTNR:SND)
sap_sndppt	SND partner	char(2)	Partner type of sending system (PDM field ID: HSSYSCFG.PART:SND)

8.6. hysap_out_ctrl

Table name: hysap_out_ctrl		Product: MLE	
Archive table: hysap_out_ctrl_a			
Designation: MLE OUTBOUND control records			
Column name	Column designation	Type	Description
bearb		char(10)	last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
param1		char(40)	Possible, additional parameters
param2		char(40)	Possible, additional parameters
sap_arkkey		char(70)	Key of external message archive
sap_cimtyp		char(30)	Subsegment (e.g. for customer-specific extensions, future-proof)
sap_credat		date	Creation date (in SAP)
sap_cretim		integer	Creation time (in SAP)
sap_direct		char(1)	Transfer direction (viewed from R/3)
sap_docnum	IDoc number	char(16)	IDOC number
sap_docrel		char(4)	IDOC-Release
sap_exprss		char(1)	Overriding in input
sap_idoctyp	IDoc type	char(30)	IDOC type
sap_mandt		char(3)	Client
sap_mescod		char(3)	Message variant
sap_mesfct		char(3)	Message function
sap_mestyp	Message type	char(30)	Message type
sap_outmod		char(1)	Output mode of IDocs in R/3
sap_rcvlad		char(70)	Recipient's logical address
sap_rcvpfc		char(2)	The recipient's partner role
sap_rcvpor	Receiver port	char(10)	Receive port
sap_rcvprn	Receiver partner no.	char(10)	Receive partner (log. system)
sap_rcvppt	Receiver partner type	char(2)	Partner type
sap_rcvsad		char(21)	Recipient's address
sap_refgrp		char(14)	Message group (EDI)
sap_refint	Duration	char(14)	Transfer file (EDI)
sap_refmes		char(14)	Message (EDI)
sap_serial		char(20)	Serialization
sap_sndlad		char(70)	The sender's logical address
sap_sndpfc		char(2)	The recipient's partner role
sap_sndpor	SAP sending port	char(10)	Send port
sap_sndprn	SAP sending partner no.	char(10)	Send partner (log. system)
sap_sndprt	SAP sending partner type	char(2)	Partner type
sap_sndsad		char(21)	Return address
sap_status		char(2)	Status of IDoc processing
sap_std		char(1)	EDI standard indicator

sap_stdmes		char(6)	EDI message type
sap_stdvrs		char(6)	EDI standard, version, release
sap_tabnam		char(10)	Name of the table structure
sap_test		char(1)	Test indicator
ta_id	Transaction no.	char(30)	Transaction ID
ta_idone	No. of edited DR	integer	Number of processed segments of the IDoc
ta_lines	No. of data records	integer	Number of segments of the data record of the IDoc
ta_savdate		date	Date of receipt
ta_savtime		integer	Time of receipt
ta_status	Status	char(3)	Status of processing
ta_type		char(5)	Description of structure type
ta_workdate		date	Transfer date
ta_worktime		integer	Transfer time
verweis	Reference	serial	Consecutive number

8.7. hysap_out_data

Table name: hysap_out_data		Product: MLE	
Archive table: hysap_out_data_a			
Designation: MLE OUTBOUND data records			
Column name	Column designation	Type	Description
bearb	last editor	char(10)	last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
ds_savdate		date	Date of saving the data
ds_savtime		integer	Time of saving the data
ds_sourcysys		char(10)	SAP target system
ds_status	Status of the segment	char(3)	Status of the segment
ds_workdate		date	Date of processing
ds_worktime		integer	Time of processing
kopf_verweis		integer	Reference to the header segment's reference in case of hierarchical IDoc structure (PDM field ID: HSODATA.VERWEIS:HEADER)
param1		char(40)	Process ID of the confirming hysapupl process (first 8 digits) + start time of the process
param2		char(40)	param2[40,40] : EOL flag; param2[1,2] : Redo-Count counter. It is evaluated in case of online cancellations. param2[3,6]: Length of data string when issuing the file
sap_docnum	Number of the IDoc	char(16)	Number of the IDoc
sap_hlevel	Hierarchy level	char(2)	Hierarchy level
sap_mandt	Client	char(3)	Client
sap_psgnum		char(6)	Number of parent segment (if available)
sap_sdata	IDoc data	char(1000)	IDoc data (PDM field ID: HSODATA.SDATA)
sap_segnam		char(30)	Segment (PDM field ID: HSODATA.SEGNAM)
sap_segnum	Segment number	char(6)	Segment number
ta_id	Transaction ID	char(30)	Transaction ID (PDM field ID: HSODATA.ID)
verweis	Consecutive number	serial	Consecutive number (PDM field ID: HSODATA.VERWEIS)

8.8. hysap_protokoll

Table name: hysap_protokoll		Product: MLE	
Archive table: hysap_protokoll_a			
Designation: MLE logging			
Column name	Column designation	Type	Description
anwendung	Application	char(10)	Program name
anzahl_done	No. of edited DR	integer	Number of data records, which were transferred successfully, within the transaction processed at last
anzahl_ds	No. of data records	integer	Number of data records within the transaction processed at last
anzahl_fehler	No. of erroneous DR	integer	Number of data records, which were transferred with errors, within the transaction processed at last
anzahl_unknown	No. of unknown DR	integer	Number of data records, whose segment name was unknown, within the transaction processed at last
bezeichnung	Designation	char(50)	Program name
d_datei_groesse	Data file size	integer	Size of the data file
d_datei_name	Data file name	char(30)	Name of the data file
datum		date	Date of the entry
f_datei_groesse	Size of error file	integer	Size of the error file
f_datei_name	Name of error file	char(30)	Name of the error file
log_sys	Log. system	char(10)	Logical system
meldung	Posting	char(100)	Entry of the program after the last run (e.g. processed transaction number)
p_datei_groesse	Size of log file	integer	Size of the log file
p_datei_name	Log file name	char(30)	Name of the log file
prg	Program	char(12)	Program name
prg_datum	Program date	date	Program date
prg_version	Program version	char(10)	Program version
role	Roll	char(1)	Active role of the logical system
status	Status	char(3)	Status of the transaction
ta_id	Transaction no.	char(30)	Transaction number
ta_status	Status	char(3)	Transaction status
text_no	Text no.	integer	Not used
verweis	Reference	serial	Consecutive number (allocated by the database)
x1		char(20)	INTERNAL USE
x2		char(20)	INTERNAL USE
x3		integer	INTERNAL USE
x4		integer	INTERNAL USE
x5		date	INTERNAL USE
x6		date	INTERNAL USE
x7		char(20)	INTERNAL USE
x8		char(1)	INTERNAL USE
x9		char(1)	INTERNAL USE
zeit		integer	Time of the entry

8.9. hysap_status

Table name: hysap_status		Product: MLE	
Designation: MLE interface status			
Column name	Column designation	Type	Description
anwendung	Application	char(10)	Name of executive routine
anzahl_done	No. of edited DR	integer	Number of data records, which were transferred successfully, within the transaction processed at last
anzahl_ds	No. of data records	integer	Number of data records within the transaction processed at last
anzahl_fehler	No. of erroneous DR	integer	Number of data records, which were transferred with errors, within the transaction processed at last
anzahl_unknown	No. of unknown DR	integer	Number of data records, whose segment name was unknown, within the transaction processed at last
bezeichnung	Designation	char(50)	Program designation
d_datei_groesse	Data file size	integer	Size of data file
d_datei_name	Data file name	char(30)	Name of data file
f_datei_groesse	Size of error file	integer	Size of error file
f_datei_name	Name of error file	char(30)	Name of error file
last_date		date	Date of last execution
last_time		integer	Time of last execution
log_sys	Log. system	char(10)	Logical system for which the activity was carried out
meldung	Posting	char(100)	Entry of the program after the last run (e.g. processed transaction number)
p_datei_groesse	Size of log file	integer	Size of log file
p_datei_name	Log file name	char(30)	Name of log file
prg	Program	char(12)	Name of executive routine
prg_datum	Program date	date	Date of program version
prg_version	Program version	char(10)	Program version
role	Roll	char(1)	Currently active role of the logical system via which the program was run
sap_segnam	Segment	char(30)	Segment name that was processed (at last)
status	Status	char(3)	Status of the program
text_no		integer	No use
x1		char(20)	INTERNAL USE
x2		char(20)	INTERNAL USE
x3		integer	INTERNAL USE
x4		integer	INTERNAL USE
x5		date	INTERNAL USE
x6		date	INTERNAL USE
x7		char(20)	INTERNAL USE
x8		char(1)	INTERNAL USE
x9		char(1)	INTERNAL USE

8.10. hysap_tidmgt

Table name: hysap_tidmgt		Product: MLE	
Archive table: hysap_tidmgt_a			
Designation: MLE TID management			
Column name	Column designation	Type	Description
param1		char(40)	INTERNAL USE
param2		char(40)	INTERNAL USE
prog		char(12)	Program name
prog_typ		char(2)	Program type "RS" RFC server "RC" RFC client "FS" File server "FC" File client "PC" PDM client
state		char(20)	Status of transaction
tid		char(30)	Transaction number
updatedate		date	Date of last entry
updatetime		integer	Time of last entry
verweis		serial	Consecutive number (allocated by the database)

8.11. sap_setup

Table name: sap_setup		Product: MLE	
Designation: MLE for SAP subsystem			
Column name	Column designation	Type	Description
auftragnr_bis	Order number to	smallint	Digit of SAP order number as of which this one is transferred to the system order number (PDM field ID: HYDRA.SAP:AUNRBIS)
auftragnr_von	Order number from	smallint	Digit of SAP order number as of which this one is transferred to the system order number (PDM field ID: HYDRA.SAP:AUNRVON)
ausweis_bis	Badge number to	smallint	Not used (PDM field ID: HYDRA.SAP:KNRBIS)
ausweis_von	Badge number from	smallint	Not used (PDM field ID: HYDRA.SAP:KNRVON)
bearb		char(10)	last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
kapsplit_bis	Capacity category to	smallint	Not used (PDM field ID: HYDRA.SAP:KAPARTBIS)
kapsplit_von	Capacity category from	smallint	Not used (PDM field ID: HYDRA.SAP:KAPARTVON)
kostenstelle_bis	Cost center to	smallint	Not used (PDM field ID: HYDRA.SAP:KSTBIS)
kostenstelle_von	Cost center from	smallint	Not used (PDM field ID: HYDRA.SAP:KSTVON)
param_1_bis		smallint	parameter field (INTERNAL USE)
param_1_von		smallint	parameter field (INTERNAL USE)
param_2_bis		smallint	parameter field (INTERNAL USE)
param_2_von		smallint	parameter field (INTERNAL USE)
param_str1	Control options for BDE as SUB-KK2	char(10)	[1,1] = J : SAP specification planned workplace is interpreted as system machine group Default as machine number ID: HYDRA.OPT.PLNAPZMGRP [2,2] = J : Upload system machine group as actual workplace ID: HYDRA.SAPOPT:2 [3,3] = J : Suppressing the personnel number within BDE uploads to SAP ID: HYDRA.SAPOPT:3 [4,4] = J : Suppressing of scrap within BDE uploads to SAP ID: HYDRA.SAPOPT:4 [5,5] = J : SAP split number is added to the order number, not to the OP ID: HYDRA.SAPOPT:5 IDs HYDRA.SAPOPT:6 .. HYDRA.SAPOPT:10 free (PDM field ID: (Composed of several acronyms))
param_str2		char(10)	=> IDs HYDRA.SAPOPT:11 .. HYDRA.SAPOPT:20 free
param_val1		integer	parameter field (INTERNAL USE)
param_val2		integer	parameter field (INTERNAL USE)
person_bis	Person to	smallint	Not used (PDM field ID: HYDRA.SAP:PNRBIS)
person_von	Person from	smallint	Not used (PDM field ID: HYDRA.SAP:PNRVON)
pze_berechtigung		char(1)	INTERNAL USE (PDM field ID: HYDRA.OPT:PZEBERECHT)

pze_info_form		char(1)	INTERNAL USE (PDM field ID: HYDRA.OPT:PZEINFOFORM)
splitnr_bis	Split number to	smallint	Not used (PDM field ID: HYDRA.SAP:SPLITNRBIS)
splitnr_von	Split number from	smallint	Not used (PDM field ID: HYDRA.SAP:SPLITNRVON)
untervgnr_bis	Suboperation number to	smallint	Digit of SAP suboperation number as of which this one is transferred to the system suboperation number (PDM field ID: HYDRA.SAP:UVGNRBIS)
untervgnr_von	Suboperation number from	smallint	Digit of SAP suboperation number as of which this one is transferred to the system suboperation number (PDM field ID: HYDRA.SAP:UVGNRVON)
vorgangsfolge_bis	Operation sequence to	smallint	Digit of SAP sequence number as of which this one is transferred to the system sequence number (PDM field ID: HYDRA.SAP:VGFOLGBIS)
vorgangsfolge_von	Operation sequence from	smallint	Digit of SAP sequence number as of which this one is transferred to the system sequence number (PDM field ID: HYDRA.SAP:VGFOLGVON)
vorgangsnr_bis	Operation number to	smallint	Digit of SAP operation number as of which this one is transferred to the system operation number (PDM field ID: HYDRA.SAP:VGNRBIS)
vorgangsnr_von	Operation number from	smallint	Digit of SAP operation number as of which this one is transferred to the system operation number (PDM field ID: HYDRA.SAP:VGNRVON)
werk	Plant	char(4)	SAP plant (for uploads to R/3) (PDM field ID: HYDRA.SAP:WERK)
ziel_bereich		char(50)	INTERNAL USE (PDM field ID: HYDRA.SAP:ZBER)
ziel_firma		char(50)	INTERNAL USE (PDM field ID: HYDRA.SAP:ZFIR)
zks_berechtigung		char(1)	INTERNAL USE (PDM field ID: HYDRA.OPT:ZKSBERECHT)

9. MPL

9.1. event_los

Table name: event_los		Product: MPL	
Archive table: a_event_los		Reload table: r_event_los	
Designation: Events based on batches		Description: The single batch events are recorded in this table.	
Column name	Column designation	Type	Description
adll_nr	Unique output batch	char(20)	
al_nr	Output batch	char(20)	
artikel	Loshistorie / batch history	char(40)	Material number of input or output batch
attribut_1	Material buffer	char(20)	Destination = material buffer at C_GEN, C_UMB, CE_AN, CE_AB, CA_AN, CA_AB, CNR.INSERT, CNR.UPDATE
attribut_2	Comment	char(20)	CE_AB, C_GEN , CNR.INSERT/UPDATE: batch information CA_AB: client batch number (KDCNR) at BELC
attribut_3		char(30)	Transport unit (CA_AB, C_GEN, CNR.INSERT/UPDATE) or bill of material item (CE_AN) or
attribut_4		char(20)	
attribut_5		char(20)	Current batch (at Event CA_AB or C_BE)
attribut_6	Material type	char(10)	Material type = semi-finished type at C_GEN, CNR.INSERT/UPDATE
attribut_7		char(10)	CE_AB/CE_AN: bill of material item CA_AN/*_RS: cutting plan
attribut_8	Batch status	char(20)	Batch status (CE_AB,CA_AB,C_GEN): A(processed), F(free), S(blocked)
attribut_9		char(30)	CE_AN: master batch number for rolls in container (package)
auftrag_nr	Order number	char(40)	Order+operation
automatisch		char(1)	J : automatic event, e.g. at change of shifts
bearb	Modified by	char(10)	Editor ID
bearb_date	Modify date	date	Editing date
bearb_time	Modify time	integer	Editing time
bpos	Operator position	char(10)	Operator position
buch_dat	Date of posting	date	Date of posting
buch_zeit	Time of posting	integer	Time of posting
buendelnr		char(40)	---
bzw	Booking obligation	char(10)	Booking obligation
chargen_nr	Batch ID	char(20)	Batch ID
datum	Log date	date	Log date
dialog	Dialog	char(20)	Dialog ID by which the event was triggered, e.g. CA_WL : output batch change, ..
dlg_data_verweis	Reference	integer	Reference to additional dialog data
dlg_id	Reference	char(10)	Dialog reference
dllosnr	Run-through batch number	char(20)	Run-through batch number
editierbar		char(1)	J = event may be maintained N= event must not be maintained, e.g. master of a COP or blocked by changing the log record
einheit_1	Unit	char(3)	Unit of respective quantity
einheit_10		char(3)	for future use

ein_h_11		char(3)	for future use
ein_h_12		char(3)	for future use
ein_h_13		char(3)	for future use
ein_h_14		char(3)	for future use
ein_h_15		char(3)	for future use
ein_h_16		char(3)	for future use
ein_h_17		char(3)	for future use
ein_h_18		char(3)	for future use
ein_h_19		char(3)	for future use
ein_h_2		char(3)	for future use
ein_h_20		char(3)	for future use
ein_h_3		char(3)	for future use
ein_h_4		char(3)	for future use
ein_h_5		char(3)	for future use
ein_h_6		char(3)	for future use
ein_h_7		char(3)	for future use
ein_h_8		char(3)	for future use
ein_h_9		char(3)	for future use
ereignis	Event type	char(10)	Event types : C_GEN : generating batches (goods receipt) C_UMB : transfer posting batches CE_AN : logging input batches on CE_AB : logging input batches off CA_AN : logging output batches on CA_AB : logging output batches off CNR.INSERT : creating batches (console) CNR.UPDATE : changing batch (console) CNR.DELETE : deleting batch (console) CNR.STATUS : material status change (console/ process monitoring /parameter)
erfass_1		char(1)	for future use
erfass_10		char(1)	for future use
erfass_11		char(1)	for future use
erfass_12		char(1)	for future use
erfass_13		char(1)	for future use
erfass_14		char(1)	for future use
erfass_15		char(1)	for future use
erfass_16		char(1)	for future use
erfass_17		char(1)	for future use
erfass_18		char(1)	for future use
erfass_19		char(1)	for future use
erfass_2		char(1)	for future use
erfass_20		char(1)	for future use
erfass_3		char(1)	for future use
erfass_4		char(1)	for future use
erfass_5		char(1)	for future use
erfass_6		char(1)	for future use
erfass_7		char(1)	for future use
erfass_8		char(1)	for future use
erfass_9		char(1)	for future use

erfass_dat	Date recording	date	Time of collection
erfass_zeit	Time recording	integer	Time of collection
erw_status_01	Batch class	char(1)	Batch class G(yield) or A(scrap) at C_GEN, CA_AB, CNR.INSERT/UPDATE
erw_status_02	Batch status	char(1)	Batch status at CNR.INSERT, CNR.UPDATE, CNR.STATUS, C_GEN, CE_AB
erw_status_03	Transport status	char(1)	Transport status at CNR.INSERT, CNR.UPDATE Event A_VERB: consumption type of the component (R, L,)
erw_status_04	Event	char(1)	Event "C_VWE" (MPLRF): "J" uploaded to SAP "N"/"" not yet uploaded
erw_status_05	Material status	char(1)	Material status as of 7.2
erw_status_06	Quality status	char(1)	Quality status as of 7.2
firma_1	Company/plant no. 1	char(8)	Company/plant no. 1
firma_2	Company/plant no. 2	char(8)	Company/plant no. 2
grund_1	Deviation/ scrap reason	char(10)	Deviation reason (at typ_1 = 'GUT') or scrap reason (at typ_1 = 'AUS')
grund_10		char(10)	for future use
grund_11		char(10)	for future use
grund_12		char(10)	for future use
grund_13		char(10)	for future use
grund_14		char(10)	for future use
grund_15		char(10)	for future use
grund_16		char(10)	for future use
grund_17		char(10)	for future use
grund_18		char(10)	for future use
grund_19		char(10)	for future use
grund_2	Scrap reason	char(10)	Scrap reason
grund_20		char(10)	for future use
grund_3		char(10)	for future use
grund_4		char(10)	for future use
grund_5		char(10)	for future use
grund_6		char(10)	for future use
grund_7		char(10)	for future use
grund_8		char(10)	for future use
grund_9		char(10)	for future use
herkunft		char(1)	"Blank" : original data record from collection E: manually generated data record L: manually generated data record for cancellation only O: original data record if maintained
info_01		integer	---
info_02		integer	---
info_03	Error code	integer	HYD-AEV: error code for rejected dialog messages during posting
ist_lst_01		decimal(18,6)	Recorded activity
ist_lst_02		decimal(18,6)	Recorded activity
ist_lst_03		decimal(18,6)	Recorded activity
ist_lst_04		decimal(18,6)	Recorded activity
ist_lst_05		decimal(18,6)	Recorded activity
ist_lst_06		decimal(18,6)	Recorded activity

ist_lst_07		decimal(18,6)	Recorded activity
ist_lst_08		decimal(18,6)	Recorded activity
ist_lst_09		decimal(18,6)	Recorded activity
ist_lst_10		decimal(18,6)	Recorded activity
ist_lst_11		decimal(18,6)	Recorded activity
ist_lst_12		decimal(18,6)	Recorded activity
ist_lst_13		decimal(18,6)	Recorded activity
ist_lst_14		decimal(18,6)	Recorded activity
ist_lst_15		decimal(18,6)	Recorded activity
ist_lst_16		decimal(18,6)	Recorded activity
ist_lst_17		decimal(18,6)	Recorded activity
ist_lst_18		decimal(18,6)	Recorded activity
ist_lst_19		decimal(18,6)	Recorded activity
ist_lst_20		decimal(18,6)	Recorded activity
ist_lst_einh_01		char(3)	Unit of recorded activity
ist_lst_einh_02		char(3)	Unit of recorded activity
ist_lst_einh_03		char(3)	Unit of recorded activity
ist_lst_einh_04		char(3)	Unit of recorded activity
ist_lst_einh_05		char(3)	Unit of recorded activity
ist_lst_einh_06		char(3)	Unit of recorded activity
ist_lst_einh_07		char(3)	Unit of recorded activity
ist_lst_einh_08		char(3)	Unit of recorded activity
ist_lst_einh_09		char(3)	Unit of recorded activity
ist_lst_einh_10		char(3)	Unit of recorded activity
ist_lst_einh_11		char(3)	Unit of recorded activity
ist_lst_einh_12		char(3)	Unit of recorded activity
ist_lst_einh_13		char(3)	Unit of recorded activity
ist_lst_einh_14		char(3)	Unit of recorded activity
ist_lst_einh_15		char(3)	Unit of recorded activity
ist_lst_einh_16		char(3)	Unit of recorded activity
ist_lst_einh_17		char(3)	Unit of recorded activity
ist_lst_einh_18		char(3)	Unit of recorded activity
ist_lst_einh_19		char(3)	Unit of recorded activity
ist_lst_einh_20		char(3)	Unit of recorded activity
ist_lst_typ_01		char(10)	Activity type
ist_lst_typ_02		char(10)	Activity type
ist_lst_typ_03		char(10)	Activity type
ist_lst_typ_04		char(10)	Activity type
ist_lst_typ_05		char(10)	Activity type
ist_lst_typ_06		char(10)	Activity type
ist_lst_typ_07		char(10)	Activity type
ist_lst_typ_08		char(10)	Activity type
ist_lst_typ_09		char(10)	Activity type
ist_lst_typ_10		char(10)	Activity type
ist_lst_typ_11		char(10)	Activity type
ist_lst_typ_12		char(10)	Activity type

ist_lst_typ_13		char(10)	Activity type
ist_lst_typ_14		char(10)	Activity type
ist_lst_typ_15		char(10)	Activity type
ist_lst_typ_16		char(10)	Activity type
ist_lst_typ_17		char(10)	Activity type
ist_lst_typ_18		char(10)	Activity type
ist_lst_typ_19		char(10)	Activity type
ist_lst_typ_20		char(10)	Activity type
karenz	Indicator	char(1)	Indicator whether processing due to waiting period processing
klasse	C : batch-related message	char(1)	C : batch-related message
lohnart	LLE wage type	char(4)	LLE wage type
lpkz	Wage premium indicator	char(10)	Wage premium indicator
masch_nr	Machine number	char(20)	Machine number
menge_1		decimal(18,6)	All quantity fields can be assigned freely. The assignment is only made via the type (data fields typ_1, .. typ_10) e.g. menge_1 = 10; typ_1 = 'GUT' = 10 Yield or menge_1 = 10; typ_1 = 'AUS' = 10 Scrap
menge_10		decimal(18,6)	see menge_1
menge_11		decimal(18,6)	for future use
menge_12		decimal(18,6)	for future use
menge_13		decimal(18,6)	for future use
menge_14		decimal(18,6)	for future use
menge_15		decimal(18,6)	for future use
menge_16		decimal(18,6)	for future use
menge_17		decimal(18,6)	for future use
menge_18		decimal(18,6)	for future use
menge_19		decimal(18,6)	for future use
menge_2		decimal(18,6)	see menge_1
menge_20		decimal(18,6)	for future use
menge_3		decimal(18,6)	see menge_1
menge_4		decimal(18,6)	see menge_1
menge_5		decimal(18,6)	see menge_1
menge_6		decimal(18,6)	see menge_1
menge_7		decimal(18,6)	see menge_1
menge_8		decimal(18,6)	see menge_1
menge_9		decimal(18,6)	see menge_1
offline_kz		char(1)	J : recorded offline by terminal
org_verweis	Reference	integer	Reference to a correction data record
p_divisor	Recorded divisor	decimal(18,6)	Recorded divisor
p_teiligkeit	Recorded partitioning	decimal(18,6)	Recorded partitioning
person_nr	Person	char(10)	Personnel number
pgruppe	Personnel group	char(20)	Personnel group
pmk	Memorize ID for person	char(1)	Memorize ID for person
prgrp	Premium group	char(10)	Premium group
prioritaet	Indication of priority	smallint	Indication of priority at simultaneous events (1 = highest priority)

pze_erzeugt	BDE event	char(1)	"K" =BDE event generated by PZE clocking-in "G" =BDE event generated by PZE clocking-out
rest_lst_01		decimal(18,6)	Remaining recorded activity
rest_lst_02		decimal(18,6)	Remaining recorded activity
rest_lst_03		decimal(18,6)	Remaining recorded activity
rest_lst_04		decimal(18,6)	Remaining recorded activity
rest_lst_05		decimal(18,6)	Remaining recorded activity
rest_lst_06		decimal(18,6)	Remaining recorded activity
rest_lst_07		decimal(18,6)	Remaining recorded activity
rest_lst_08		decimal(18,6)	Remaining recorded activity
rest_lst_09		decimal(18,6)	Remaining recorded activity
rest_lst_10		decimal(18,6)	Remaining recorded activity
rest_lst_11		decimal(18,6)	Remaining recorded activity
rest_lst_12		decimal(18,6)	Remaining recorded activity
rest_lst_13		decimal(18,6)	Remaining recorded activity
rest_lst_14		decimal(18,6)	Remaining recorded activity
rest_lst_15		decimal(18,6)	Remaining recorded activity
rest_lst_16		decimal(18,6)	Remaining recorded activity
rest_lst_17		decimal(18,6)	Remaining recorded activity
rest_lst_18		decimal(18,6)	Remaining recorded activity
rest_lst_19		decimal(18,6)	Remaining recorded activity
rest_lst_20		decimal(18,6)	Remaining recorded activity
rest_lst_einh_01		char(3)	Remaining unit of recorded activity
rest_lst_einh_02		char(3)	Remaining unit of recorded activity
rest_lst_einh_03		char(3)	Remaining unit of recorded activity
rest_lst_einh_04		char(3)	Remaining unit of recorded activity
rest_lst_einh_05		char(3)	Remaining unit of recorded activity
rest_lst_einh_06		char(3)	Remaining unit of recorded activity
rest_lst_einh_07		char(3)	Remaining unit of recorded activity
rest_lst_einh_08		char(3)	Remaining unit of recorded activity
rest_lst_einh_09		char(3)	Remaining unit of recorded activity
rest_lst_einh_10		char(3)	Remaining unit of recorded activity
rest_lst_einh_11		char(3)	Remaining unit of recorded activity
rest_lst_einh_12		char(3)	Remaining unit of recorded activity
rest_lst_einh_13		char(3)	Remaining unit of recorded activity
rest_lst_einh_14		char(3)	Remaining unit of recorded activity
rest_lst_einh_15		char(3)	Remaining unit of recorded activity
rest_lst_einh_16		char(3)	Remaining unit of recorded activity
rest_lst_einh_17		char(3)	Remaining unit of recorded activity
rest_lst_einh_18		char(3)	Remaining unit of recorded activity
rest_lst_einh_19		char(3)	Remaining unit of recorded activity
rest_lst_einh_20		char(3)	Remaining unit of recorded activity
rest_lst_typ_01		char(10)	Remainder of type of recorded activity
rest_lst_typ_02		char(10)	Remainder of type of recorded activity
rest_lst_typ_03		char(10)	Remainder of type of recorded activity
rest_lst_typ_04		char(10)	Remainder of type of recorded activity

rest_lst_typ_05		char(10)	Remainder of type of recorded activity
rest_lst_typ_06		char(10)	Remainder of type of recorded activity
rest_lst_typ_07		char(10)	Remainder of type of recorded activity
rest_lst_typ_08		char(10)	Remainder of type of recorded activity
rest_lst_typ_09		char(10)	Remainder of type of recorded activity
rest_lst_typ_10		char(10)	Remainder of type of recorded activity
rest_lst_typ_11		char(10)	Remainder of type of recorded activity
rest_lst_typ_12		char(10)	Remainder of type of recorded activity
rest_lst_typ_13		char(10)	Remainder of type of recorded activity
rest_lst_typ_14		char(10)	Remainder of type of recorded activity
rest_lst_typ_15		char(10)	Remainder of type of recorded activity
rest_lst_typ_16		char(10)	Remainder of type of recorded activity
rest_lst_typ_17		char(10)	Remainder of type of recorded activity
rest_lst_typ_18		char(10)	Remainder of type of recorded activity
rest_lst_typ_19		char(10)	Remainder of type of recorded activity
rest_lst_typ_20		char(10)	Remainder of type of recorded activity
sig_knr1		char(10)	
sig_knr2		char(10)	
sig_name1		char(40)	
sig_name2		char(40)	
sig_pnr1		char(10)	
sig_pnr2		char(10)	
sig_type1		char(20)	
sig_type2		char(20)	
soll_te		decimal(18,6)	for future use
soll_teb		decimal(18,6)	for future use
soll_tr		decimal(18,6)	for future use
stationsnr		integer	As of MPL7.2: web number in cutting plan when cutting rolls otherwise free
status_1	Machine status	integer	Machine status
status_2		integer	CA AN : number of parallel batches
status_3		integer	MPL7.2: Target length
szenario_nr		integer	for future use
terminal_nr	User	smallint	User who created the data record
typ_1		char(10)	GUT - yield AUS - scrap HUB - number of strokes LEN REST- remaining quantity VERB VERF - expired quantity
typ_10		char(10)	for future use
typ_11		char(10)	for future use
typ_12		char(10)	for future use
typ_13		char(10)	for future use
typ_14		char(10)	for future use
typ_15		char(10)	for future use
typ_16		char(10)	for future use
typ_17		char(10)	for future use

typ_18		char(10)	for future use
typ_19		char(10)	for future use
typ_2		char(10)	see typ_1
typ_20		char(10)	for future use
typ_3		char(10)	see typ_1
typ_4		char(10)	see typ_1
typ_5		char(10)	see typ_1
typ_6		char(10)	see typ_1
typ_7		char(10)	see typ_1
typ_8		char(10)	for future use
typ_9		char(10)	for future use
umref	Conversion factor	decimal(18,6)	Conversion factor for retrograde posting
utc_ts		datetime	
verarb_1	PZE processing	char(1)	PZE processing
verarb_2	Batch status	char(1)	Batch status at beginning of shift (L=running/F=autom. interrupted)
verarb_3		char(1)	For future use
verarb_4		char(1)	HYD-AEV: A = flag for automatically generated dialogs; e.g. by PZE/ADE comparison
verarb_mde	MDE processing	char(1)	MDE processing (postprocessing of MDE log messages)
verbuch_kz	Update indicator	char(2)	Update indicator, e.g. "ST" = COP at terminal, "SK"= COP at console "SB" = beginning of shift, "SE" = end of shift "W" = standard time (PZE) "S" = daylight saving time (PZE)
verweis	Reference	serial	Unique reference of data record
verweis_b1	Reference to ADE	integer	Reference to the operation-related result record or clocking record
verweis_b2	Reference to 2nd ADE	integer	Reference to a 2nd operation-related result record or clocking record
zeit	Log time	integer	Log time

9.2. event_mlb

Table name: event_mlb		Product: MPL	
Archive table: a_event_mlb		Reload table: r_event_mlb	
Designation: Material-related events			
Column name	Column designation	Type	Description
abruf	Material movements	smallint	free (PDM field ID: MBEW)
artikel		char(40)	Article number (PDM field ID: MBEW.ATK)
artikel_bez	Description	char(40)	Article designation (PDM field ID: MBEW.ATKBEZ)
attribut_1		char(20)	
attribut_2		char(20)	free
attribut_3		char(30)	free
attribut_4		char(20)	free
attribut_5		char(20)	free
attribut_6	Material type	char(10)	Material type (PDM field ID: MBEW.ATTR:6)
attribut_7		char(10)	free
attribut_8		char(20)	free
attribut_9		char(30)	MPL-PAL: Package number at packing location (CA_WL_PA)
auftrag_nr	Order number	char(40)	Operation number - allocated according to the event (PDM field ID: MBEW.ANR)
automatisch		char(1)	Only for internal use
bearb		char(10)	Last editor (PDM field ID: BEARB)
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
blatt		char(10)	free
bwtyp	Typ/Bezug der Bewegung	char(1)	Only for internal use
chargen_nr		char(20)	allocated according to the event (PDM field ID: MBEW.CNR)
datum		date	Log date (PDM field ID: DAT)
dialog		char(10)	Identification of the dialog by which the event was triggered (PDM field ID: MBEW.DLG)
dlg_id		char(10)	Dialog reference (Only for internal use)
dlosnr	Batch number	char(20)	Run-through batch number (PDM field ID: MBEW.DLL)
editierbar		char(1)	Only for internal use
ein_h_1		char(3)	Quantity unit goods receipt and goods issue (PDM field ID: MBEW.EINH:1)
ein_h_10		char(3)	free (PDM field ID: MBEW.EINH:10)
ein_h_2		char(3)	So far not allocated

ein_h_3	Unit	char(3)	So far not allocated
ein_h_4	Unit	char(3)	So far not allocated
ein_h_5	Unit	char(3)	So far not allocated
ein_h_6	Unit	char(3)	So far not allocated
ein_h_7	Unit	char(3)	So far not allocated
ein_h_8	Unit	char(3)	So far not allocated
ein_h_9		char(3)	So far not allocated
end_lief	Delivery completed	char(1)	Final delivery J/N
ereignis	Movement	char(10)	Type of movement: CMM_A, CMM_E, CMM_R, CMM_VWE (PDM field ID: MBEW.EVENT)
erw_status_01		char(1)	Reserved/free for customer-specific data (PDM field ID: MBEW.ERWSTA:1)
erw_status_02		char(1)	Reserved/free for customer-specific data (PDM field ID: MBEW.ERWSTA:2)
erw_status_03		char(1)	(PDM field ID: MBEW.ERWSTA:3)
erw_status_04		char(1)	Goods receipt: memorized status to be confirmed for KDCNR (PDM field ID: MBEW.ERWSTA:4)
erw_status_05		char(1)	J - > status package weighed (CA_WL_PA) (PDM field ID: MBEW.ERWSTA:5)
erw_status_06		char(1)	CMM_A: material indicator from component (e.g. M,T,Z) (PDM field ID: MBEW.ERWSTA:6)
firma_1		char(8)	Company/plant number 1 (PDM field ID: MBEW.FIR:1)
firma_2		char(8)	Company/plant number 2 (PDM field ID: MBEW.FIR:2)
grund_1	Reason	char(10)	Deviation reason / Scrap reason (PDM field ID: MBEW.GR:1)
grund_10		char(10)	So far not allocated (PDM field ID: MBEW.GR:10)
grund_2	Scrap reason	char(10)	So far not allocated (PDM field ID: MBEW.GR:2)
grund_3	Reason	char(10)	So far not allocated (PDM field ID: MBEW.GR:3)
grund_4	Reason	char(10)	So far not allocated (PDM field ID: MBEW.GR:4)
grund_5	Reason	char(10)	So far not allocated (PDM field ID: MBEW.GR:5)
grund_6	Reason	char(10)	So far not allocated (PDM field ID: MBEW.GR:6)
grund_7	Reason	char(10)	So far not allocated (PDM field ID: MBEW.GR:7)
grund_8	Reason	char(10)	So far not allocated (PDM field ID: MBEW.GR:8)
grund_9		char(10)	So far not allocated (PDM field ID: MBEW.GR:9)
herkunft		char(1)	"Blank": original data record from collecting E : manually generated data record (or original record edited in the event maintenance) L : manually generated data record, for cancellation only O : original data record if maintained (PDM field ID: MBEW.OPT:HERKUNFT)
hzart	Material type	char(10)	Material type (PDM field ID: MBEW.HZART)

info_01		integer	
info_02		integer	free
info_03		integer	free
klasse		char(1)	Only for internal use
kompartikel		char(40)	Only for internal use
kopf_verweis		integer	free
kostenstelle	Cost center	char(10)	Cost center (PDM field ID: MBEW.KST)
kzeaus	Finally issued	char(1)	Indicator finally issued/completed J/N (PDM field ID: MBEW.OPT:EAUS)
kzsobest	Special inventory	char(1)	free
lag		char(3)	Storage location (PDM field ID: MBEW.LAG)
lagerort	Storage location: source	char(20)	Storage location (PDM field ID: MBEW.LAGORT)
lagerort_z	Storage location: target	char(20)	Destination storage location (PDM field ID: MBEW.LAGORT:Z)
lagerplatz	Storage bin: source	char(20)	Storage place
lagerplatz_z	Storage bin: target	char(20)	Destination storage place
lagz		char(3)	Output material buffer
lieferant		char(20)	free
los_klasse	Batch class	char(1)	batch class (PDM field ID: MBEW.CKL)
los_status	Batch status	char(1)	batch status (PDM field ID: MBEW.CST)
masch_nr		char(20)	machine number (PDM field ID: MBEW.MNR)
mat_status	Material status	char(1)	Material status (PDM field ID: MBEW.MATST)
meinheit_bas		char(3)	free
meinheit_pri		char(3)	free
meinheit_sek		char(3)	free
meinheit_ter		char(3)	free
menge_1		decimal(18,6)	Quantity of movement in batch unit --- (PDM field ID: MBEW.EGR:1)
menge_10		decimal(18,6)	CMM A: mass per unit area from batch stock (PDM field ID: MBEW.EGR:10)
menge_2		decimal(18,6)	Scrap (PDM field ID: MBEW.EGR:2)
menge_3	Activity 1	decimal(18,6)	Activity 1 from batch stock (PDM field ID: MBEW.EGR:3)
menge_4	Activity 2	decimal(18,6)	Activity 2 from batch stock (PDM field ID: MBEW.EGR:4)
menge_5	Activity 3	decimal(18,6)	Activity 3 from batch stock (PDM field ID: MBEW.EGR:5)
menge_6	Activity 4	decimal(18,6)	Activity 4 from batch stock (PDM field ID: MBEW.EGR:6)
menge_7	Activity 5	decimal(18,6)	Activity 5 from batch stock (PDM field ID: MBEW.EGR:7)

menge_8	Activity 6	decimal(18,6)	Activity 6 from batch stock (PDM field ID: MBEW.EGR:8)
menge_9		decimal(18,6)	CMM_A: Width from batch stock (PDM field ID: MBEW.EGR:9)
menge_bas		decimal(18,6)	free
menge_pri		decimal(18,6)	free
menge_sek		decimal(18,6)	free
menge_ter		decimal(18,6)	free
mlst_pos	Bill of material item	char(10)	Bill of material item (PDM field ID: MBEW.SLP)
offline_kz		char(1)	Only for internal use
org_verweis		integer	Only for internal use
person_nr		char(10)	personal number (PDM field ID: MBEW.PNR)
prioritaet		smallint	Only for internal use
q_status	Quality status	char(1)	Quality status (PDM field ID: MBEW.QST)
referenz		char(10)	free
rf_abzweig	Deducted material	char(1)	Branching indicator
rueckgemeldet	Uploaded	char(1)	J -> goods movement reported to SAP (PDM field ID: MBEW.STA:RCK)
rueckmelden	To be uploaded	char(1)	J -> Report goods movement to SAP (PDM field ID: MBEW.OPT:RCK)
sap_aufnr	PPS order	char(12)	Order number for PPS (PDM field ID: MBEW.SAPANR)
sap_bwart	Movement type	char(3)	Movement type for PPS e.g. 101 - incoming movement 261 - outgoing movment (PDM field ID: MBEW.SAPBWART)
sap_charge	ERP batch	char(20)	Batch number for PPS (PDM field ID: MBEW.SAPCNr)
satzart		char(2)	Only for internal use
sig_knr1		char(10)	
sig_knr2		char(10)	
sig_name1		char(40)	
sig_name2		char(40)	
sig_pnr1		char(10)	
sig_pnr2		char(10)	
sig_type1		char(20)	
sig_type2		char(20)	
status_1		integer	free
status_2		integer	free
status_3		integer	free
stueckl_pos		smallint	Not used as of 7.2
terminal_nr		smallint	User who generated the data record (PDM field ID: MBEW.TNR)
typ_1	Material type	char(10)	Yield (PDM field ID: MBEW.TYP:1)
typ_10		char(10)	So far not allocated (PDM field ID: MBEW.TYP:10)

typ_2		char(10)	Scrap (PDM field ID: MBEW.TYP:2)
typ_3		char(10)	Stroke
typ_4		char(10)	LEN
typ_5		char(10)	Z1
typ_6		char(10)	Z2
typ_7		char(10)	Z3
typ_8		char(10)	So far not allocated
typ_9		char(10)	So far not allocated
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	

user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
utc_ts		datetime	
verarb_1		char(1)	(PDM field ID: MBEW.VERARB:1)
verarb_2		char(1)	(PDM field ID: MBEW.VERARB:2)
verarb_3		char(1)	(PDM field ID: MBEW.VERARB:3)
verarb_4		char(1)	free (PDM field ID: MBEW.VERARB:4)
verweis		serial	Distinct reference of the data record (PDM field ID: EREIGMLB.VERWEIS)
verweis_b1		integer	Only for internal use
verweis_b2		integer	Only for internal use
wiederbelegung		char(1)	free
zeile		char(10)	free
zeit		integer	Log time (PDM field ID: ZEI)

zlo	Source buffer	char(12)	Destination (PDM field ID: MBEW.ZLO)
zloz	Target buffer	char(12)	Output material buffer (PDM field ID: MBEW.ZLO:Z)

9.3. event_pp

Table name: event_pp		Product: MPL	
Designation: Events of production parameters			
Column name	Column designation	Type	Description
artikel		char(40)	Article
attribut_1		char(20)	PZE : clocking attribute
attribut_2		char(20)	PZE : Zeitarbeit ((W)inter, (S)ommer)
attribut_3		char(30)	Operator position at event P_AN
attribut_4		char(20)	Internal use
attribut_5		char(20)	Current batch (at event CA_AB or C_AB)
attribut_6		char(10)	For future use
attribut_7		char(10)	For future use
attribut_8		char(20)	For future use
attribut_9		char(30)	For future use
auftrag_nr		char(40)	According to event assigned to order number
automatisch		char(1)	J : automatic event, e.g. at change of shifts
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bpos		char(10)	Operator position
buch_dat		date	Time of posting
buch_zeit		integer	Time of posting
buendelnr		char(40)	Otherwise free (e.g. COP number)
bzw		char(10)	Booking obligation
chargen_nr		char(20)	Assigned according to event
datum		date	Log date
dialog		char(10)	Dialog ID by which the event was triggered Supplements: not relevant
dlg_data_verweis		integer	Reference to additional dialog data
dlg_id		char(10)	Dialog reference
dllosnr		char(20)	Run-through batch number
editierbar		char(1)	J = event may be maintained N = event must not be maintained, e.g. master of a COP or blocked by changing the log record
einheit_1		char(3)	For future use
einheit_10		char(3)	For future use
einheit_11		char(3)	For future use
einheit_12		char(3)	For future use
einheit_13		char(3)	For future use
einheit_14		char(3)	For future use
einheit_15		char(3)	For future use
einheit_16		char(3)	For future use
einheit_17		char(3)	For future use
einheit_18		char(3)	For future use

ein_h_19		char(3)	For future use
ein_h_2		char(3)	For future use
ein_h_20		char(3)	For future use
ein_h_3		char(3)	For future use
ein_h_4		char(3)	For future use
ein_h_5		char(3)	For future use
ein_h_6		char(3)	For future use
ein_h_7		char(3)	For future use
ein_h_8		char(3)	For future use
ein_h_9		char(3)	For future use
ereignis		char(10)	Event type P_AN/P_AB Supplements: P_ZUS
erfass_1		char(1)	For future use
erfass_10		char(1)	For future use
erfass_11		char(1)	For future use
erfass_12		char(1)	For future use
erfass_13		char(1)	For future use
erfass_14		char(1)	For future use
erfass_15		char(1)	For future use
erfass_16		char(1)	For future use
erfass_17		char(1)	For future use
erfass_18		char(1)	For future use
erfass_19		char(1)	For future use
erfass_2		char(1)	For future use
erfass_20		char(1)	For future use
erfass_3		char(1)	For future use
erfass_4		char(1)	For future use
erfass_5		char(1)	For future use
erfass_6		char(1)	For future use
erfass_7		char(1)	For future use
erfass_8		char(1)	For future use
erfass_9		char(1)	For future use
erfass_dat		date	Time of collection
erfass_zeit		integer	Time of collection
erw_status_01		char(1)	For future use
erw_status_02		char(1)	For future use
erw_status_03		char(1)	For future use
erw_status_04		char(1)	For future use
erw_status_05		char(1)	For future use
erw_status_06		char(1)	For future use
firma_1		char(8)	Company/plant number 1
firma_2		char(8)	Company/plant number 2
grund_1		char(10)	Deviation reason
grund_10		char(10)	Deviation reason
grund_11		char(10)	For future use
grund_12		char(10)	For future use

grund_13		char(10)	For future use
grund_14		char(10)	For future use
grund_15		char(10)	For future use
grund_16		char(10)	For future use
grund_17		char(10)	For future use
grund_18		char(10)	For future use
grund_19		char(10)	For future use
grund_2		char(10)	Scrap reason
grund_20		char(10)	For future use
grund_3		char(10)	For future use
grund_4		char(10)	For future use
grund_5		char(10)	For future use
grund_6		char(10)	For future use
grund_7		char(10)	For future use
grund_8		char(10)	For future use
grund_9		char(10)	For future use
herkunft		char(1)	"Blank" : original data record from the collection E: manually generated data record L: manually generated data record for cancellation only O: original data record, if maintained
info_01		integer	Reference to additional data record in event_dlg_data
info_02		integer	Active ADE/PZE comparison: flextime type from PZE
info_03		integer	For future use
ist_lst_01		decimal(18,6)	Recorded activity
ist_lst_02		decimal(18,6)	Recorded activity
ist_lst_03		decimal(18,6)	Recorded activity
ist_lst_04		decimal(18,6)	Recorded activity
ist_lst_05		decimal(18,6)	Recorded activity
ist_lst_06		decimal(18,6)	Recorded activity
ist_lst_07		decimal(18,6)	Recorded activity
ist_lst_08		decimal(18,6)	Recorded activity
ist_lst_09		decimal(18,6)	Recorded activity
ist_lst_10		decimal(18,6)	Recorded activity
ist_lst_11		decimal(18,6)	Recorded activity
ist_lst_12		decimal(18,6)	Recorded activity
ist_lst_13		decimal(18,6)	Recorded activity
ist_lst_14		decimal(18,6)	Recorded activity
ist_lst_15		decimal(18,6)	Recorded activity
ist_lst_16		decimal(18,6)	Recorded activity
ist_lst_17		decimal(18,6)	Recorded activity
ist_lst_18		decimal(18,6)	Recorded activity
ist_lst_19		decimal(18,6)	Recorded activity
ist_lst_20		decimal(18,6)	Recorded activity
ist_lst_einh_01		char(3)	Unit of recorded activity
ist_lst_einh_02		char(3)	Unit of recorded activity
ist_lst_einh_03		char(3)	Unit of recorded activity
ist_lst_einh_04		char(3)	Unit of recorded activity

ist_lst_einh_05		char(3)	Unit of recorded activity
ist_lst_einh_06		char(3)	Unit of recorded activity
ist_lst_einh_07		char(3)	Unit of recorded activity
ist_lst_einh_08		char(3)	Unit of recorded activity
ist_lst_einh_09		char(3)	Unit of recorded activity
ist_lst_einh_10		char(3)	Unit of recorded activity
ist_lst_einh_11		char(3)	Unit of recorded activity
ist_lst_einh_12		char(3)	Unit of recorded activity
ist_lst_einh_13		char(3)	Unit of recorded activity
ist_lst_einh_14		char(3)	Unit of recorded activity
ist_lst_einh_15		char(3)	Unit of recorded activity
ist_lst_einh_16		char(3)	Unit of recorded activity
ist_lst_einh_17		char(3)	Unit of recorded activity
ist_lst_einh_18		char(3)	Unit of recorded activity
ist_lst_einh_19		char(3)	Unit of recorded activity
ist_lst_einh_20		char(3)	Unit of recorded activity
ist_lst_typ_01		char(10)	Type of recorded activity
ist_lst_typ_02		char(10)	Type of recorded activity
ist_lst_typ_03		char(10)	Type of recorded activity
ist_lst_typ_04		char(10)	Type of recorded activity
ist_lst_typ_05		char(10)	Type of recorded activity
ist_lst_typ_06		char(10)	Type of recorded activity
ist_lst_typ_07		char(10)	Type of recorded activity
ist_lst_typ_08		char(10)	Type of recorded activity
ist_lst_typ_09		char(10)	Type of recorded activity
ist_lst_typ_10		char(10)	Type of recorded activity
ist_lst_typ_11		char(10)	Type of recorded activity
ist_lst_typ_12		char(10)	Type of recorded activity
ist_lst_typ_13		char(10)	Type of recorded activity
ist_lst_typ_14		char(10)	Type of recorded activity
ist_lst_typ_15		char(10)	Type of recorded activity
ist_lst_typ_16		char(10)	Type of recorded activity
ist_lst_typ_17		char(10)	Type of recorded activity
ist_lst_typ_18		char(10)	Type of recorded activity
ist_lst_typ_19		char(10)	Type of recorded activity
ist_lst_typ_20		char(10)	Type of recorded activity
karenz		char(1)	Indicator whether processing due to waiting period processing
klasse		char(1)	P : personnel-related message
lohnart		char(4)	LLE wage type
lpkz		char(10)	Lohnprämienkennzeichen
masch_nr		char(20)	Machine number
menge_1		decimal(18,6)	Yield
menge_10		decimal(18,6)	For future use
menge_11		decimal(18,6)	For future use
menge_12		decimal(18,6)	For future use
menge_13		decimal(18,6)	For future use

menge_14		decimal(18,6)	For future use
menge_15		decimal(18,6)	For future use
menge_16		decimal(18,6)	For future use
menge_17		decimal(18,6)	For future use
menge_18		decimal(18,6)	For future use
menge_19		decimal(18,6)	For future use
menge_2		decimal(18,6)	Scrap
menge_20		decimal(18,6)	For future use
menge_3		decimal(18,6)	Stroke
menge_4		decimal(18,6)	Length
menge_5		decimal(18,6)	Counter1
menge_6		decimal(18,6)	Counter 2
menge_7		decimal(18,6)	Counter 3
menge_8		decimal(18,6)	For future use
menge_9		decimal(18,6)	For future use
offline_kz		char(1)	J : recorded offline by terminal
org_verweis		integer	Reference to a correction data record
p_divisor		decimal(18,6)	Recorded divisor
p_teiligkeit		decimal(18,6)	Recorded partitioning
person_nr		char(10)	Personnel number
pgruppe		char(20)	Personnel group
pmk		char(1)	Flag for memorizing person
prgrp		char(10)	Premium group
prioritaet		smallint	Indication of priority in case of simultaneous events (1=highest priority)
pze_erzeugt		char(1)	"K" =BDE event generated by PZE-clocking-in "G" =BDE event generated by PZE clocking-out
rest_lst_01		decimal(18,6)	Remaining recorded activity
rest_lst_02		decimal(18,6)	Remaining recorded activity
rest_lst_03		decimal(18,6)	Remaining recorded activity
rest_lst_04		decimal(18,6)	Remaining recorded activity
rest_lst_05		decimal(18,6)	Remaining recorded activity
rest_lst_06		decimal(18,6)	Remaining recorded activity
rest_lst_07		decimal(18,6)	Remaining recorded activity
rest_lst_08		decimal(18,6)	Remaining recorded activity
rest_lst_09		decimal(18,6)	Remaining recorded activity
rest_lst_10		decimal(18,6)	Remaining recorded activity
rest_lst_11		decimal(18,6)	Remaining recorded activity
rest_lst_12		decimal(18,6)	Remaining recorded activity
rest_lst_13		decimal(18,6)	Remaining recorded activity
rest_lst_14		decimal(18,6)	Remaining recorded activity
rest_lst_15		decimal(18,6)	Remaining recorded activity
rest_lst_16		decimal(18,6)	Remaining recorded activity
rest_lst_17		decimal(18,6)	Remaining recorded activity
rest_lst_18		decimal(18,6)	Remaining recorded activity
rest_lst_19		decimal(18,6)	Remaining recorded activity
rest_lst_20		decimal(18,6)	Remaining recorded activity

rest_lst_einh_01		char(3)	Remaining unit of recorded activity
rest_lst_einh_02		char(3)	Remaining unit of recorded activity
rest_lst_einh_03		char(3)	Remaining unit of recorded activity
rest_lst_einh_04		char(3)	Remaining unit of recorded activity
rest_lst_einh_05		char(3)	Remaining unit of recorded activity
rest_lst_einh_06		char(3)	Remaining unit of recorded activity
rest_lst_einh_07		char(3)	Remaining unit of recorded activity
rest_lst_einh_08		char(3)	Remaining unit of recorded activity
rest_lst_einh_09		char(3)	Remaining unit of recorded activity
rest_lst_einh_10		char(3)	Remaining unit of recorded activity
rest_lst_einh_11		char(3)	Remaining unit of recorded activity
rest_lst_einh_12		char(3)	Remaining unit of recorded activity
rest_lst_einh_13		char(3)	Remaining unit of recorded activity
rest_lst_einh_14		char(3)	Remaining unit of recorded activity
rest_lst_einh_15		char(3)	Remaining unit of recorded activity
rest_lst_einh_16		char(3)	Remaining unit of recorded activity
rest_lst_einh_17		char(3)	Remaining unit of recorded activity
rest_lst_einh_18		char(3)	Remaining unit of recorded activity
rest_lst_einh_19		char(3)	Remaining unit of recorded activity
rest_lst_einh_20		char(3)	Remaining unit of recorded activity
rest_lst_typ_01		char(10)	Remainder of type of recorded activity
rest_lst_typ_02		char(10)	Remainder of type of recorded activity
rest_lst_typ_03		char(10)	Remainder of type of recorded activity
rest_lst_typ_04		char(10)	Remainder of type of recorded activity
rest_lst_typ_05		char(10)	Remainder of type of recorded activity
rest_lst_typ_06		char(10)	Remainder of type of recorded activity
rest_lst_typ_07		char(10)	Remainder of type of recorded activity
rest_lst_typ_08		char(10)	Remainder of type of recorded activity
rest_lst_typ_09		char(10)	Remainder of type of recorded activity
rest_lst_typ_10		char(10)	Remainder of type of recorded activity
rest_lst_typ_11		char(10)	Remainder of type of recorded activity
rest_lst_typ_12		char(10)	Remainder of type of recorded activity
rest_lst_typ_13		char(10)	Remainder of type of recorded activity
rest_lst_typ_14		char(10)	Remainder of type of recorded activity
rest_lst_typ_15		char(10)	Remainder of type of recorded activity
rest_lst_typ_16		char(10)	Remainder of type of recorded activity
rest_lst_typ_17		char(10)	Remainder of type of recorded activity
rest_lst_typ_18		char(10)	Remainder of type of recorded activity
rest_lst_typ_19		char(10)	Remainder of type of recorded activity
rest_lst_typ_20		char(10)	Remainder of type of recorded activity
sig_knr1		char(10)	
sig_knr2		char(10)	
sig_name1		char(40)	
sig_name2		char(40)	
sig_pnr1		char(10)	
sig_pnr2		char(10)	

sig_type1		char(20)	
sig_type2		char(20)	
soll_te		decimal(18,6)	Premium target TE
soll_teb		decimal(18,6)	Premium target TEB
soll_tr		decimal(18,6)	Premium target TR
stationsnr		integer	Otherwise free
status_1		integer	Machine status, termination reason, partitioning or target cycle Supplements: bonus reason
status_2		integer	Active ADE/PZE comparison: shift date from PZE
status_3		integer	---
szenario_nr		integer	for future use relevant for event maintenance
terminal_nr		smallint	User who generated the data record
typ_1		char(10)	GUT (Yield)
typ_10		char(10)	For future use
typ_11		char(10)	For future use
typ_12		char(10)	For future use
typ_13		char(10)	For future use
typ_14		char(10)	For future use
typ_15		char(10)	For future use
typ_16		char(10)	For future use
typ_17		char(10)	For future use
typ_18		char(10)	For future use
typ_19		char(10)	For future use
typ_2		char(10)	AUS (Scrap)
typ_20		char(10)	For future use
typ_3		char(10)	HUB (Stroke)
typ_4		char(10)	LEN (Length)
typ_5		char(10)	Z1
typ_6		char(10)	Z2
typ_7		char(10)	Z3
typ_8		char(10)	For future use
typ_9		char(10)	For future use
umref		decimal(18,6)	Conversion factor for retrograde posting
utc_ts		datetime	
verarb_1		char(1)	PZE processing
verarb_2		char(1)	BDEprocessing
verarb_3		char(1)	For future use
verarb_4		char(1)	For future use
verarb_mde		char(1)	MDE processing (postprocessing of MDE log messages)
verbuch_kz		char(2)	Update indicator e.g. "ST" = COP at terminal, "SK"= COP at console "SB" = beginning of shift, "SE" = end of shift "B" = block message "W" = standard time (PZE) "S" = daylight saving time (PZE)
verweis		serial	Unique reference of data record
verweis_b1		integer	Reference to operation-related result record or clocking record

verweis_b2		integer	Reference to 2nd clocking record
zeit		integer	Log time

9.4. hyd_vwe_stat

Table name: hyd_vwe_stat		Product: MPL	
Designation: Usage decision / object status			
Column name	Column designation	Type	Description
auswmen_bez	Selected set designation	char(40)	(PDM field ID: VWE.HARCSTUFEBEZ:1)
auswmenge	SAP selected set	char(8)	(PDM field ID: VWE.HARCSTUFE:1)
bearb	Created by	char(10)	
bearb_date	Initial data creation - Date	date	
bearb_time	Initial data creation - Time	integer	
code	SAP single code	char(10)	(PDM field ID: VWE.VWE)
code_bez	Single code designation	char(40)	(PDM field ID: VWE.VWEBEZ)
codegrp	SAP code group	char(10)	(PDM field ID: VWE.HARCSTUFE:2)
codegrp_bez	Code group designation	char(40)	(PDM field ID: VWE.HARCSTUFEBEZ:2)
ext_bewert	External evaluation	char(1)	If VWG="PRUEFTYP_A": "A" Acceptance (well) "R" Rejection (not well) "" none assessment (PDM field ID: VWE.STA:EXT)
firma	Company / Site identification	char(4)	(PDM field ID: VWE.FIR)
geloescht	deleted	char(1)	
hyd_status	Object status	char(1)	internal status (PDM field ID: VWE.STA:HYD)
katab	SAP KATAB	char(1)	(PDM field ID: VWE.SAP:KATAB)
katalgart	SAP-Catalog type	char(1)	(PDM field ID: VWE.KATART)
kennung_1	identification 1	char(20)	(PDM field ID: VWE.KENN:1)
kennung_2	identification 2	char(20)	(PDM field ID: VWE.KENN:2)
kennung_3	identification 3	char(20)	(PDM field ID: VWE.KENN:3)
kennung_4	identification 4	char(20)	(PDM field ID: VWE.KENN:4)
kennung_5	identification 5	char(20)	(PDM field ID: VWE.KENN:5)
param_c01	free	char(40)	
param_c02	free	char(40)	
param_d01	free	decimal(18,6)	
param_d02	free	decimal(18,6)	
param_n01	free	integer	

param_n02	free	integer	
sap_bwart	Movement type	char(3)	(PDM field ID: VWE.SAP:BWART)
val_1	Value 1	char(20)	(PDM field ID: VWE.VAL:1)
val_2	Value 2	char(20)	(PDM field ID: VWE.VAL:2)
val_3	Value 3	char(20)	(PDM field ID: VWE.VAL:3)
val_4	Value 4	char(20)	(PDM field ID: VWE.VAL:4)
val_5	Value 5	char(20)	(PDM field ID: VWE.VAL:5)
verweis	Reference	serial	(PDM field ID: VWE.VERWEIS)
vwe_bez	Assessment group designation	char(40)	(PDM field ID: VWE.VWGBEZ)
vwe_id	Assessment group	char(20)	Assessment group: "PRUEFTYP_A" = Assessment attributive characteristics "VWECNR" = Charge usage decision (PDM field ID: VWE.VWG)

9.5. hz_atgen

Table name: hz_atgen		Product: MPL	
Designation: Definition of the attributes for materia		Description: Definition of attributes for material types	
Column name	Column designation	Type	Description
a_ref_dbcol	Name of database field from order header	char(20)	Name of database field from order header or OP, which is used as default (if configured) (PDM field ID: CNRATTRCFG.COLUMN)
a_ref_kenn	Acronym of database	char(40)	Acronym of database field in case of default from OP or order header (PDM field ID: CNRATTRCFG.KENN)
anz_pos	Position within display sequence	integer	Position within display sequence (PDM field ID: CNRATTRCFG.POS:SIB)
anzeigen	Display on console	char(1)	Visible at console: J/N - indicator whether the attribute is to be displayed (applies for all views of the console) (PDM field ID: CNRATTRCFG.OPT:SIB)
attrib01	Attribute 1	char(50)	
attrib02	Attribute 2	char(50)	
attrib03	Attribute 3	char(50)	
attrib04	Attribute 4	char(50)	
attrib05	Attribute 5	char(50)	
attrib06	Attribute 6	char(50)	
attrib07	Attribute 7	char(50)	
attrib08	Attribute 8	char(50)	
attrib09	Attribute 9	char(50)	
attrib10	Attribute 10	char(50)	
attrib11	Attribute 11	char(50)	
attrib12	Attribute 12	char(50)	
attrib13	Attribute 13	char(50)	
attrib14	Attribute 14	char(50)	
attrib15	Attribute 15	char(50)	
attrib16	Attribute 16	char(50)	
attrib17	Attribute 17	char(50)	
attrib18	Attribute 18	char(50)	
attrib19	Attribute 19	char(50)	
attrib20	Attribute 20	char(50)	
attrib21	Attribute 21	char(50)	
attrib22	Attribute 22	char(50)	
attrib23	Attribute 23	char(50)	
attrib24	Attribute 24	char(50)	
attrib25	Attribute 25	char(50)	
attrib26	Attribute 26	char(50)	
attrib27	Attribute 27	char(50)	
attrib28	Attribute 28	char(50)	
attrib29	Attribute 29	char(50)	
attrib30	Attribute 30	char(50)	
bearb	Last editor	char(10)	Last editor

bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
druck_pos	Position when printing	integer	Position within the sequence at ticket printing (PDM field ID: CNRATTRCFG.POS:PRN)
drucken	Print J/N	char(1)	Flag whether the attribute is to be printed on the batch ticket (J/N) (PDM field ID: CNRATTRCFG.OPT:PRN)
erfass_idx	Index of the material attribute	integer	Index of the material attribute to be recorded. Corresponds to the number of the batch attribute (important for recording = "J") (PDM field ID: CNRATTRCFG.IDX:ERF)
erfass_len	Length of the field	integer	Length of the field: the maximum length is determined by the attribute DB field in which the value is supposed to be saved, if necessary (PDM field ID: CNRATTRCFG.LEN:ERF)
erfass_nachkomma	Number of decimal places	integer	Number of decimal places to be recorded for decimal attributes (PDM field ID: CNRATTRCFG.NKS:ERF)
erfass_pos	Position during collection	integer	Position within the sequence while recording (PDM field ID: CNRATTRCFG.POS:ERF)
erfass_typ	Type of entry field	char(1)	Type of entry field: N = Numerical C = Text field F = Decimal value (This type can cause, if necessary, that a numerical value is saved in a text DB field if intended) (PDM field ID: CNRATTRCFG.TYP:ERF)
erfassen	recorded (J/N)	char(1)	Indicator how the attribute is recorded (J/N) (PDM field ID: CNRATTRCFG.OPT:ERF)
header	Description of the attribute	char(40)	Description of the attribute. Is displayed before the content (PDM field ID: CNRATTRCFG.TXT)
hz_typ	Assigned material type	char(10)	Assigned material type (hz_typen.hz_typ) (PDM field ID: CNRATTRCFG.MATTYP)
idx	Index	integer	Completes the unique key (with HZ_TYP) --> Position of the info text of the info interface --> important if recording = 'N' if recording = J this is erfass_pos + 100 (PDM field ID: CNRATTRCFG.IDX)
terminpu		char(1)	
trailer	Unit of attribute	char(10)	"Unit" of the attribute. Is displayed after the content. (PDM field ID: CNRATTRCFG.EINH)
u_ref_feldidx	SAP field ID	char(6)	SAP field ID in case of default from OP or order header (PDM field ID: CNRATTRCFG.IDX:USRFLD)
vorgabe_art	Default type	char(2)	Default for field assignment at the collection (if necessary, it can be overwritten at the terminal - if configured) Type of default: "NN" - no specification "UA" - by field ID from OP "UK" - by field ID from order header "HA" - by acronym from OP "HK" - by acronym from order header (PDM field ID: CNRATTRCFG.VORGART)

9.6. hz_tpe

Table name: hz_tpe		Product: MPL	
Designation: Definition of material types		Description: Definition of material types	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
default_tpe	Flag for default transport unit	char(1)	J = default transport unit N = alternative transport unit (PDM field ID: MATTYPTPE.OPT:VORG)
einheit	Unit	char(3)	Unit of quantity that can be transported in transport unit. Default: ST (pieces) (PDM field ID: MATTYPTPE.EINH)
hz_typ	Material type	char(10)	Material type (PDM field ID: MATTYPTPE.MATTYP)
menge	Quantity	integer	Quantity that can be transported in transport unit Default:0 (PDM field ID: MATTYPTPE.ANZ)
param_01		integer	For future use
param_02		integer	For future use
param_str01		char(20)	For future use
param_str02		char(20)	For future use
pdouble_01		decimal(18,6)	For future use
pdouble_02		decimal(18,6)	For future use
trans_einh	Transport unit	char(10)	Transport unit (PDM field ID: MATTYPTPE.TPE)

9.7. hz_typen

Table name: hz_typen		Product: MPL	
Designation: material types		Description: Definition of material types	
Column name	Column designation	Type	Description
abezug_um_kz	OP reference indicator UM	char(1)	Flag whether OP reference is required for batch transfer posting (PDM field ID: MATTYP.OPT:ABZGVERB)
abezug_we_kz	OP reference indicator WE	char(1)	Flag whether OP reference is required for batch generation (e.g.: GR-goods receipt) (PDM field ID: MATTYP.OPT:ABZGGEN)
agan_plaus_kz	Indicator for AG-AN	char(1)	J = flag whether all input batches have to be logged on for logging a batch on. (PDM field ID: MATTYP.PLAUS:MATOK)
art_kz	Type	char(10)	E - Finished product H - Material type V - Packing (ALCAN only) New as of MPL 7.2: B - Bale M - Mix (= Portion?) D - Dispersion T - Carrier material R - Roll L - Batch (as general term) G - Container O - Bulk container P - Pallet (package) (PDM field ID: MATTYP.ART)
auto_ceab	Log off input batches	char(1)	 (PDM field ID: MATTYP.OPT:AUTOCEAB)
batch_dft_qty_in	Default quantity of input batches	decimal(18,6)	Default quantity of input batches (PDM field ID: MATTYP.QTY:DBQI)
batch_dft_qty_out	Default quantity for output batches	decimal(18,6)	Default quantity for output batches (PDM field ID: MATTYP.QTY:DBQO)
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bestand_kz	Stock indicator	char(1)	'N' -> No 'R' -> Yes, retrograde posting 'E' -> Yes, when logging input batch off 'G' -> Yes, retrograde posting only at yield 'A' -> Anonymous (Composition) 'W' -> retrograde posting only material movement 'S' -> retrograde posting without reducing batch quantity 'H' -> retrograde posting (only at yield) without reducing batch quantity (PDM field ID: MATTYP.OPT:INBESTVERB)
ea_los_kz	Input batch only valid for exactly 1 output batch	char(1)	Flag whether input batch is only valid for exactly 1 output batch (PDM field ID: MATTYP.OPT:CNREA)
einheit	Unit	char(3)	Unit for batch (PDM field ID: MATTYP.EINH)
hz_bez	Designation	char(30)	Designation (PDM field ID: MATTYP.BEZ)

hz_param_str01		char(4)	[1,1] : J = Input batch of this material type may be logged on several times. ID: MATTYP.OPT:MULTIMNR [2,2] : J = Input batches of this material type have always to be assigned when OPs are logged on ID: MATTYP.PLAUS:EMATOK [3,3] : J = Recording/filing of unknown input batches is allowed ID: MATTYP.OPT: UCHGEN [4,4]: J = Output batch change and logon of OP only possible if all required input materials have a value that is greater than 0 in the "restmenge" field ID: MATTYP.OPT:EMATRGR (PDM field ID: (Composed of several acronyms))
hz_param_str02		char(20)	[1,1] N/J = Generate transfer order automatically when loading via PPS interface ID: MATTYP.OPT:AUTOTRPA ANP-000434 (ALCAN) [2,2] N/J = Plausibility check of underdelivery/overdelivery tolerance (flag in HR master data) ID: MATTYP.OPT:UOTOL MPL 7.1: [3,3]: J = Material type is defined as WIP material (N default) ID: MATTYP.OPT:WIP (PDM field ID: (Composed of several acronyms))
hz_param_str03		char(20)	for future use
hz_pddouble_01		decimal(18,6)	for future use
hz_pddouble_02		decimal(18,6)	for future use
hz_plong_01		integer	for future use
hz_plong_02		integer	for future use
hz_typ	Material type	char(10)	Material type (PDM field ID: MATTYP.MATTYP)
layout	Layout	char(10)	Layout used for the ticket print (PDM field ID: MATTYP.LAY)
los_groesse	Batch size	integer	Standard lot size that is suggested as default for new creations (PDM field ID: MATTYP.ANZ)
matrix		char(25)	----
max_wert	Absolute value for tolerance limit	integer	Absolute value for tolerance limit (PDM field ID: MATTYP.UTGAGAB)
mehrfach_kz	Multiple indicator	char(1)	Indicator whether the same material types can be logged on several times (PDM field ID: MATTYP.OPT:MULTICNR)
min_lagerzeit	Minimum storage time	integer	Minimum storage time (PDM field ID: MATTYP.LAGZMIN)
opt_attr_ver	Pass batch attributes on	char(1)	
opt_config		char(20)	free
opt_del_lcnr	Log off/interrupt OP without the last batch	char(1)	
opt_del_zuord	Delete batch assignment	char(1)	
opt_dok_ver	Pass document links on	char(1)	
opt_ewe_ent	Decision on changing the input batch	char(1)	
opt_gen_hu	Generation of HU	char(1)	 (PDM field ID: MATTYP.OPT:GENHU)
opt_snr_verh	Automatic assignment of serial numbers	char(1)	
opt_tranr_in	Generate transport order for input material	char(1)	
opt_tranr_out	Generate transport order for output material	char(1)	
output_batch_qty_violation	Flag how to deal with default quantity violation	char(1)	Flag how to deal with default quantity violation (PDM field ID: MATTYP.QTY:DBQV)
res_art	Reserved when batch is generated	char(4)	--- (PDM field ID: MATTYP.RESART)

rf_vbr_losbez	MPL-RF: Material usage	char(1)	MPL-RF: J: Material usage is recorded on the basis of output batches N/": Material usage is recorded on the basis of operations (PDM field ID: MATTYP.OPT:VGRCNR)
seriennr_pflcht	Serial number requirement	char(1)	(PDM field ID: MATTYP.OPT:SNR)
ticket_anz	Number of tickets that is printed.	integer	Number of tickets that is printed. License: MPL-TDR (PDM field ID: MATTYP.TICKETANZ)
toleranz_ab	Tolerance limit	integer	Tolerance limit when logging OP off AG-AB (%) (PDM field ID: MATTYP.PROZAGAB)
user_c_29	User field 29	char(1)	User specific field (PDM field ID: MATTYP.FU:29)
user_c_30		char(1)	User specific field
user_c_31		char(1)	User specific field
user_c_32		char(1)	User specific field (PDM field ID: MATTYP.FU:32)
user_c_33		char(1)	User specific field (PDM field ID: MATTYP.FU:33)
user_c_34		char(1)	User specific field
user_c_35		char(1)	User specific field (PDM field ID: MATTYP.FU:35)
user_c_36		char(1)	User specific field (PDM field ID: MATTYP.FU:36)
user_c_37		char(1)	User specific field (PDM field ID: MATTYP.FU:37)
user_c_38		char(1)	User specific field
user_c_39		char(1)	User specific field
user_c_40		char(1)	User specific field
user_c_41		char(1)	User specific field
user_c_42		char(1)	User specific field
user_c_43		char(1)	User specific field
user_c_44		char(1)	User specific field
user_c_45		char(10)	User specific field
user_c_46		char(10)	User specific field
user_c_47		char(10)	User specific field
user_c_48		char(10)	User specific field
user_c_49		char(10)	User specific field
user_c_50		char(10)	User specific field
user_c_51		char(20)	User specific field (PDM field ID: MATTYP.FU:51)
user_c_52		char(20)	User specific field
user_c_53		char(20)	User specific field
user_c_54		char(20)	User specific field
user_c_55		char(20)	User specific field
user_c_56		char(20)	User specific field
user_c_57		char(20)	User specific field
user_c_58		char(20)	User specific field
user_c_59		char(20)	User specific field
user_c_60		char(20)	User specific field

user_c_61		char(20)	User specific field
user_c_62		char(20)	User specific field
user_c_63		char(20)	User specific field
user_c_64		char(20)	User specific field
user_c_65		char(40)	User specific field
user_c_66		char(40)	User specific field
user_code	User field key	char(8)	User field key Reference to the configuration of the user field key or its user fields in the HYD_USERFIELDCFG table (PDM field ID: MATTYP.USRFLD)
user_code_out	User field key for output batch	char(8)	(PDM field ID: MATTYP.USRFLDOUT)
user_d_01	User field 1	date	User specific field (PDM field ID: MATTYP.FU:1)
user_d_02		date	User specific field
user_d_03		date	User specific field
user_d_04		date	User specific field
user_d_05		date	User specific field
user_d_06		date	User specific field
user_f_23		decimal(18,6)	User specific field
user_f_24		decimal(18,6)	User specific field
user_f_25		decimal(18,6)	User specific field
user_f_26		decimal(18,6)	User specific field
user_f_27		decimal(18,6)	User specific field
user_f_28		decimal(18,6)	User specific field
user_n_07		integer	User specific field (PDM field ID: MATTYP.FU:7)
user_n_08		integer	User specific field (PDM field ID: MATTYP.FU:8)
user_n_09		integer	User specific field
user_n_10		integer	User specific field
user_n_11		integer	User specific field
user_n_12		integer	User specific field
user_n_13		integer	User specific field
user_n_14		integer	User specific field
user_n_15		integer	User specific field
user_n_16		integer	User specific field
user_n_17		integer	User specific field
user_n_18		integer	User specific field
user_n_19		integer	User specific field
user_n_20		integer	User specific field
user_n_21		integer	User specific field
user_n_22		integer	User specific field
vererben_kz	Inheritance indicator	char(1)	Indicator for inheriting the batch number (PDM field ID: MATTYP.OPT:VERE)

verf_dat_aus_elos	Determination of expiry date	char(1)	Indicator whether the least expiry date of the appropriate batches is to be used to calculate the own expiry date (see VERF_DAT_IN_ALOS). If no appropriate input batch is available the expiry date is calculated according to the individual settings. New option "S" = "expiry date from shift date" (KRN 11.10.04) Thus, this field has the following characteristics: N = from current point in time J = from input batch >= 7.2.1 or DUNL S = from shift date >= 7.2.1. (PDM field ID: MATTYP.OPT:VFCNRE)
verf_dat_in_alos	Use data for output material	char(1)	Indicator whether the own expiry date can be used to calculate the expiry date of the output batch (see VERF_DAT_AUS_ELOS). (PDM field ID: MATTYP.OPT:VFCNRA)
verfallgrenze	Expiry limit	integer	Expiry limit (PDM field ID: MATTYP.VFG)
vis_vblz	Verbrauchsbilanz J/N	char(1)	 (PDM field ID: MATTYP.VISVERBRBLZ)
warngrenze	Warning limit	integer	Warning limit (PDM field ID: MATTYP.WG)
we_ext_kz	Transfer to interface	char(1)	'J' -> Upload to PPS
we_ext_vwe	Hold goods receipt back until usage decision is made	char(1)	---

9.8. lbz_term_zuord

Table name: lbz_term_zuord		Product: MPL	
Designation: Control circuit terminal assignment			
Column name	Column designation	Type	Description
anzeige_pos	Position	smallint	(PDM field ID: LBZTNR.POS)
lbez_id	Closed loop	char(15)	(PDM field ID: LBZTNR.LBZ)
terminal_nr	Terminal	smallint	(PDM field ID: LBZTNR.TNR)

9.9. los_attribute

Table name: los_attribute		Product: MPL	
Archive table: a_los_attribute		Reload table: r_los_attribute	
Designation: batch attributes		Description: Batch attributes for a batch	
Column name	Column designation	Type	Description
attrib_101	Batch attribute	char(50)	User specific field (PDM field ID: ATTR:101)
attrib_102	Attribute 2	char(50)	User specific field
attrib_103	Attribute 3	char(50)	User specific field
attrib_104	Attribute 4	char(50)	User specific field
attrib_105	Attribute 5	char(50)	User specific field
attrib_106	Attribute 6	char(50)	User specific field
attrib_107	Attribute 7	char(50)	User specific field
attrib_108	Attribute 8	char(50)	User specific field
attrib_109	Attribute 9	char(50)	User specific field
attrib_110	Attribute 10	char(50)	User specific field
attrib_111	Attribute 11	char(50)	User specific field
attrib_112	Attribute 12	char(50)	User specific field
attrib_113	Attribute 13	char(50)	User specific field
attrib_114	Attribute 14	char(50)	User specific field
attrib_115	Attribute 15	char(50)	User specific field
attrib_116	Attribute 16	char(50)	User specific field
attrib_117	Attribute 17	char(50)	User specific field
attrib_118	Attribute 18	char(50)	User specific field
attrib_119	Attribute 19	char(50)	User specific field
attrib_120	Attribute 20	char(50)	User specific field
attrib_121	Attribute 21	char(50)	User specific field
attrib_122	Attribute 22	char(50)	User specific field
attrib_123	Attribute 23	char(50)	User specific field
attrib_124	Attribute 24	char(50)	User specific field
attrib_125	Attribute 25	char(50)	User specific field
attrib_126	Attribute 26	char(50)	User specific field
attrib_127	Attribute 27	char(50)	User specific field
attrib_128	Attribute 28	char(50)	User specific field
attrib_129	Attribute 29	char(50)	User specific field
attrib_130	Attribute 30	char(50)	User specific field
attrib_131	Attribute 31	char(50)	User specific field
attrib_132	Attribute 32	char(50)	User specific field
attrib_133	Attribute 33	char(50)	User specific field
attrib_134	Attribute 34	char(50)	User specific field
attrib_135	Attribute 35	char(50)	User specific field
attrib_136	Attribute 36	char(50)	User specific field

attrib_137	Attribute 37	char(50)	User specific field
attrib_138	Attribute 38	char(50)	User specific field
attrib_139	Batch attribute	char(50)	User specific field (PDM field ID: ATTR:139)
attrib_140	Batch attribute	char(50)	User specific field (PDM field ID: ATTR:140)
attrib_201	Attribute 41	integer	User specific field (PDM field ID: ATTR:201)
attrib_202	Batch attribute	integer	User specific field (PDM field ID: ATTR:202)
attrib_203	Attribute 43	integer	User specific field
attrib_204	Attribute 44	integer	User specific field
attrib_205	Attribute 45	integer	User specific field
attrib_206	Attribute 46	integer	User specific field
attrib_207	Attribute 47	integer	User specific field
attrib_208	Attribute 48	integer	User specific field
attrib_209	Attribute 49	integer	User specific field
attrib_210	Attribute 50	integer	User specific field
attrib_211	Attribute 51	integer	User specific field
attrib_212	Attribute 52	integer	User specific field
attrib_213	Attribute 53	integer	User specific field
attrib_214	Attribute 54	integer	User specific field
attrib_215	Attribute 55	integer	User specific field
attrib_216	Attribute 56	integer	User specific field
attrib_217	Attribute 57	integer	User specific field
attrib_218	Attribute 58	integer	User specific field
attrib_219	Attribute 59	integer	User specific field
attrib_220	Batch attribute	integer	User specific field (PDM field ID: ATTR:220)
attrib_301	Attribute 61	decimal(18,6)	User specific field (PDM field ID: ATTR:301)
attrib_302	Attribute 62	decimal(18,6)	User specific field
attrib_303	Attribute 63	decimal(18,6)	User specific field
attrib_304	Attribute 64	decimal(18,6)	User specific field
attrib_305	Attribute 65	decimal(18,6)	User specific field
attrib_306	Attribute 66	decimal(18,6)	User specific field
attrib_307	Attribute 67	decimal(18,6)	User specific field
attrib_308	Attribute 68	decimal(18,6)	User specific field
attrib_309	Attribute 69	decimal(18,6)	User specific field
attrib_310	Attribute 70	decimal(18,6)	User specific field
attrib_311	Attribute 71	decimal(18,6)	User specific field
attrib_312	Attribute 72	decimal(18,6)	User specific field
attrib_313	Attribute 73	decimal(18,6)	User specific field
attrib_314	Attribute 74	decimal(18,6)	User specific field
attrib_315	Attribute 75	decimal(18,6)	User specific field
attrib_316	Attribute 76	decimal(18,6)	User specific field
attrib_317	Attribute 77	decimal(18,6)	User specific field
attrib_318	Attribute 78	decimal(18,6)	User specific field

attrib_319	Attribute 79	decimal(18,6)	User specific field
attrib_320	Attribute 80	decimal(18,6)	User specific field
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
losnr	batch number	char(20)	batch number (PDM field ID: CNR)

9.10. los_bestand

Table name: los_bestand		Product: MPL	
Archive table: a_los_bestand		Reload table: r_los_bestand	
Designation: Batch stock		Description: All batches defined for an order/OP and all batches (input and output material) that are available in the system are defined here.	
Column name	Column designation	Type	Description
alt_einheit	Alternative unit	char(3)	Not used (PDM field ID: CNR.ALTEINH)
alt_menge	Alternative quantity	decimal(18,6)	Not used (PDM field ID: CNR.ALTMENGE)
altern_losnr1	Alternative batch number	char(20)	Alternative batch number 1 (PDM field ID: CNR.CNR:ALT1)
altern_losnr10	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT10)
altern_losnr11	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT11)
altern_losnr12	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT12)
altern_losnr13	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT13)
altern_losnr14	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT14)
altern_losnr15	Alternative batch number	char(100)	(PDM field ID: CNR.CNR:ALT15)
altern_losnr16	Alternative batch number	char(100)	(PDM field ID: CNR.CNR:ALT16)
altern_losnr17	Alternative batch number	char(100)	(PDM field ID: CNR.CNR:ALT17)
altern_losnr18	Alternative batch number	char(100)	(PDM field ID: CNR.CNR:ALT18)
altern_losnr19	Alternative batch number	char(512)	(PDM field ID: CNR.CNR:ALT19)
altern_losnr2	Alternative batch number	char(20)	Alternative batch number 2 (PDM field ID: CNR.CNR:ALT2)
altern_losnr20	Alternative batch number	char(512)	(PDM field ID: CNR.CNR:ALT20)
altern_losnr3	Alternative batch number	char(20)	Alternative batch number 3 (PDM field ID: CNR.CNR:ALT3)
altern_losnr4	Alternative batch number	char(20)	Alternative batch number 4 (PDM field ID: CNR.CNR:ALT4)
altern_losnr5	Alternative batch number	char(40)	Alternative batch number 5 (PDM field ID: CNR.CNR:ALT5)
altern_losnr6	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT6)
altern_losnr7	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT7)
altern_losnr8	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT8)
altern_losnr9	Alternative batch number	char(40)	(PDM field ID: CNR.CNR:ALT9)

anz_einzellose	No. of ind. batches	integer	For collective batches: number of individual batches for which the collective batch applies (PDM field ID: CNR.ANZ:SLOS (hyddi: LOSANZ))
archiv_status		char(1)	
archiv_status_date		date	
archiv_status_time		integer	
art	Reason type	char(1)	Reason type (e.g. A = scrap) (PDM field ID: CNR.GRART)
artikel	Article	char(40)	Article (PDM field ID: CNR.ATK)
artikel_bez	Article designation	char(40)	Article designation (PDM field ID: CNR.ATKBEZ)
artikel_idx	Article index	char(50)	CAQ article reference (not yet assigned) (PDM field ID: CNR.ATKIDX)
attrib01	Attribut 1	integer	Attribute 1 (PDM field ID: CNR.ATTR:1)
attrib02	Attribut 2	integer	Attribute 2 (PDM field ID: CNR.ATTR:2)
attrib03	Attribut 3	integer	Attribute 3 (PDM field ID: CNR.ATTR:3)
attrib04	Attribut 4	decimal(18,6)	Attribute 4 (PDM field ID: CNR.ATTR:4)
attrib05	Attribut 5	decimal(18,6)	Attribute 5 (PDM field ID: CNR.ATTR:5)
attrib06	Attribut 6	decimal(18,6)	Attribute 6 (PDM field ID: CNR.ATTR:6)
attrib_str01	Attribut 7	char(4)	--- (PDM field ID: CNR.ATTR:7)
attrib_str02	Attribut 8	char(10)	--- (PDM field ID: CNR.ATTR:8)
attrib_str03	Attribut 9	char(10)	--- (PDM field ID: CNR.ATTR:9)
attrib_str04	Attribut 10	char(20)	--- (PDM field ID: CNR.ATTR:10)
attrib_str05	Attribut 11	char(40)	Order producing the batch (PDM field ID: CNR.ATTR:11)
auftrag_art	Order type	char(5)	Order type of OP (PDM field ID: CNR.AUART)
ausschussgrund	Scrap reason	char(10)	Not used (PDM field ID: CNR.EGG:AUS)
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bestand_kz	Inventory management	char(1)	Inventory management J / N
bestart	Status "stock type"	char(1)	--- (PDM field ID: CNR.BESTART)
dlg_data_verweis	Reference to table of comments	integer	Reference to table of comments
dll_kennz	Throughput batch indicator	char(1)	N = no run-through batch G = valid batch for run-through batch A = invalid (already processed) batch for run-through batch E = running (input) batch for run-through batch (PDM field ID: CNR.DLL:KZ)

dilosnr	Run-through batch number	char(20)	Run-through batch number (PDM field ID: CNR.DLL)
einheit	Batch unit	char(3)	Batch unit (PDM field ID: CNR.EINH -> CNR.EGE:GUT (!))
firma	Company	char(4)	Company (PDM field ID: CNR.FIR)
grund	reason	integer	Scrap reason (PDM field ID: CNR.GR)
grundtext	Reason text no.	integer	Reason text no. (PDM field ID: CNR.GRTXT)
hinweis	Batch info	char(20)	Batch info (PDM field ID: CNR.BEM)
hu_level	HU level	integer	MPL-SNR: Handling Unit Level (PDM field ID: CNR.HULEVEL)
hyuser	User	integer	User (PDM field ID: CNR.USR)
hz_typ	Material type	char(10)	Material type (PDM field ID: CNR.MATTYP)
hzart	Material type	char(10)	Material type: please see in table material_arten (PDM field ID: CNR.MATTYPART)
klasse	Batch class	char(1)	G - Yield R - Return run A - Scrap O - Problem or onhold quantity N - Rework (PDM field ID: CNR.CKL)
l_los_status	Last status	char(1)	MPL-PAL: Last batch status
lb_aus_grund		smallint	Not used
lb_param_str01		char(4)	[1,1]: 'V' - Batch has been logged on in advance [2,2]: J/N - Batch has been reused
lb_param_str02		char(20)	---
lb_param_str03	Operation	char(20)	MPL: OP for which the batch had been logged on in advance
lb_pdouble_01	Remaining qty. of input batch	decimal(18,6)	MPL: Latest rest value of input batch ---
lb_pdouble_02		decimal(18,6)	---
lb_plong_01		integer	---
lb_plong_02	Commentary	integer	MPL: Reference to last commentary concerning batch status in event_dlg_data
losnr	Batch number	char(20)	Batch number (PDM field ID: CNR.CNR)
lot_nr	Lot number	char(20)	Lot number (PDM field ID: CNR.EXTCNR)
lst_01	Activity 1	decimal(18,6)	Activity 1 (PDM field ID: CNR.EGR:1)
lst_01_einh	Activity type 1	char(3)	Activity type 1 (PDM field ID: CNR.EGE:1)
lst_01_rest	Remaining activity 1	decimal(18,6)	Remaining activity 1 (PDM field ID: CNR.RGR:1)
lst_01_zuord	Activity assignment 1	char(1)	(PDM field ID: CNR.ZUORD:1)
lst_02	Activity 2	decimal(18,6)	Activity 2 (PDM field ID: CNR.EGR:2)
lst_02_einh	Activity type 2	char(3)	Activity type 2 (PDM field ID: CNR.EGE:2)

lst_02_rest	Remaining activity 2	decimal(18,6)	Remaining activity 2 (PDM field ID: CNR.RGR:2)
lst_02_zuord	Activity assignment 2	char(1)	(PDM field ID: CNR.ZUORD:2)
lst_03	MPL7.2: Activity 3	decimal(18,6)	MPLRF: Length of batch in running meters (PDM field ID: CNR.EGR:3)
lst_03_einh	Unit for activity 3	char(3)	MPLRF: "LFM"/ "M" (PDM field ID: CNR.EGE:3)
lst_03_rest	Remainder for activity 3	decimal(18,6)	MPLRF: remaining length of batch (PDM field ID: CNR.RGR:3)
lst_03_zuord	Activity assignment 3	char(1)	(PDM field ID: CNR.ZUORD:3)
lst_04	MPL7.2: Activity 4	decimal(18,6)	MPLRF: weight of batch (PDM field ID: CNR.EGR:4)
lst_04_einh	Unit for activity 4	char(3)	MPLRF: "KG" (PDM field ID: CNR.EGE:4)
lst_04_rest	Rest zur Leistung 4	decimal(18,6)	MPLRF: remaining weight of the batch (PDM field ID: CNR.RGR:4)
lst_04_zuord	Activity assignment 4	char(1)	(PDM field ID: CNR.ZUORD:4)
lst_05	MPL7.2: Activity 5	decimal(18,6)	MPLRF: area of batch (PDM field ID: CNR.EGR:5)
lst_05_einh	Unit for activity 5	char(3)	MPLRF: "M2" (PDM field ID: CNR.EGE:5)
lst_05_rest	Remainder for activity 5	decimal(18,6)	MPLRF: remaining area of batch (PDM field ID: CNR.RGR:5)
lst_05_zuord	Activity assignment 5	char(1)	(PDM field ID: CNR.ZUORD:5)
lst_06	MPL7.2: Activity 6	decimal(18,6)	MPLRF: pieces of the batch (PDM field ID: CNR.EGR:6)
lst_06_einh	Unit for activity 6	char(3)	e.g."ST" (pieces) (PDM field ID: CNR.EGE:6)
lst_06_rest	Remainder for activity 6	decimal(18,6)	MPLRF: remaining number of pieces of batch (PDM field ID: CNR.RGR:6)
lst_06_zuord	Activity assignment 6	char(1)	(PDM field ID: CNR.ZUORD:6)
m_auftrag_nr	Master OP	char(40)	Master OP (PDM field ID: CNR.MANR)
masch_nr	Machine number	char(20)	Machine number (PDM field ID: CNR.MNR)
mat_puf	Material buffer	char(12)	Material buffer (PDM field ID: CNR.MATPUF)
mat_status	Material status	char(1)	Material status: 'U': Unchecked 'V': Packed 'P': Under test 'K': checked 'R': Repair (PDM field ID: CNR.MATST)
meinheit_bas	Base quantity unit	char(3)	Not used
meinheit_pri	Unit (P)	char(3)	Not used
meinheit_sek	Secondary quantity unit	char(3)	Not used
meinheit_ter	Tertiary quantity unit	char(3)	Not used
menge	Quantity	decimal(18,6)	Quantity (PDM field ID: CNR.SGR:GUT -> CNR.EGR:GUT (!))

menge_bas	Basic quantity	decimal(18,6)	Not used
menge_pri	Quantity (P)	decimal(18,6)	Not used
menge_sek	Secondary quantity	decimal(18,6)	Not used
menge_ter	Tertiary quantity	decimal(18,6)	Not used
msl_expire_date		date	
msl_expire_period		integer	
msl_expire_time		integer	
mutter_losnr	Master batch number for package/containe	char(20)	Master batch number for package/containers/handling units and collective batches (PDM field ID: CNR.MCNR)
person_nr	Personal number	char(10)	MPL - machine operator at output batch change (PDM field ID: CNR.PNR)
prod_dat	Date of manufacture	date	Date of manufacture (PDM field ID: CNR.HSDAT)
prod_zeit	Time of manufacture	integer	Time of manufacture (PDM field ID: CNR.HSZEI)
pruefauftr_nr	Inspection step	integer	Reference to inspection requirement/order (PDM field ID: CNR.PAUNR)
q_status	Quality status	char(1)	Quality status of the batch 'F': Free 'S': Blocked 'O': Open (PDM field ID: CNR.QST)
q_status_manu	Quality status	char(1)	Manually set quality status of the batch 'F': Free 'S': Blocked 'I', '': Not set Overrules the automatic Q status QST (PDM field ID: CNR.QSTMANU)
res_art	reservation type	char(4)	MPL7.2 : reservation type "" - not reserved "AG" - reservation for OP "AK" - reservation for an order (all OPs) "CC" - Reservation with commentary (without system reference) (PDM field ID: CNR.RESART)
res_auftrag_nr	Reserved for	char(40)	MPL7.2: order at reservation type AG or AK - order without OP at reservation type AK - order/OP at reservation type AG (PDM field ID: CNR.RESVAL)
res_kommentar	Reservation commentary	char(100)	MPL7.2 :reservation commentary at reservation type CC - reservation commentary, reason, editor, customer, etc. (PDM field ID: CNR.RESBEM)
res_masch_nr	Resource	char(20)	
res_slp		char(10)	
rest_kz	Remaining quantity indicator	char(1)	Remaining quantity indicator J/N (PDM field ID: CNR.OPT:REST)
rest_menge_bas	Remaining quantity (base)	decimal(18,6)	Not used
rest_menge_pri	Target quantity (P)	decimal(18,6)	Not used
rest_menge_sek	Remaining quantity (secondary)	decimal(18,6)	Not used
rest_menge_ter	Remaining quantity (tertiary)	decimal(18,6)	Not used
restmenge	Remaining quantity	decimal(18,6)	Remaining quantity (PDM field ID: CNR.SGR:REST -> CNR.RGR:GUT (!))
rf_agvfa	MPL/RF: Mass per unit area	decimal(18,6)	MPL/RF: mass per unit area of material batch (e.g. in G/M2) (PDM field ID: CNR.RFAGVFA)
rf_breite	MPL/RF: Roll width	decimal(18,6)	MPL/RF: roll width (e.g. in MM) (PDM field ID: CNR.BREITE)

rf_stflaech	MPL/RF: area per piece	decimal(18,6)	MPL/RF: area per piece in MM2/PCE (PDM field ID: CNR.RFSTKF)
sammellos	Collective batch	char(1)	'J' - Collective batch (PDM field ID: CNR.OPT:SLOS)
sammellos_kz	Collective batch type	char(1)	Collective batch type (PDM field ID: CNR.OPT:SLOSTYP)
sap_charge	SAP batch number	char(20)	PPS batch number (PDM field ID: CNR.SAPCNR)
sap_lagerort	SAP storage location	char(20)	PPS storage location (is transferred at the interface and is intended to be returned in the withdrawal message) (PDM field ID: CNR.LAGORT)
sap_lagerplatz	PPS storage bin	char(20)	for future use (PDM field ID: CNR.LAGPZ)
serien_nr	Serial number	char(20)	MPL-SNR: Serial number (PDM field ID: CNR.SNR)
stat_upd_dat	Date of last status change	date	Date of last status change
stat_upd_zeit	Time of last status change	integer	Time of last status change
status	Status	char(1)	Batch status: F - Free S - Blocked M - Minimum storage time P - Inspection V - Expired T - Transport L - Running A - Processed D - Deleted (PDM field ID: CNR.STA)
status1		char(1)	free
status2		char(1)	free
status3		char(1)	free
status4		char(1)	free
status5		char(1)	free
tech_info	Technical information	char(20)	Technical information (PDM field ID: CNR.TECHINFO)
tr_anz	MPLRF: Number of daughter rolls within c	integer	MPLRF: if set (>0) number of rolls within cut (PDM field ID: CNR.TR:ANZ)
tr_anz_gesamt	MPLRF: Number of all daughter rolls (of	integer	MPLRF: only if set (> 0) cutting process at mother roll or respective batch. Number of all output batches of all cuts (PDM field ID: CNR.TR:ANZSUM (hyddi: TR:ANZ_GES))
tr_index	MPLRF: Production line number	integer	Index of produced output batches within the OP or pallet number (PDM field ID: CNR.PBANDNR)
tr_pos	MPLRF: Position of daughter roll within	integer	--- (PDM field ID: CNR.TR:POS)
tr_schnr	MPLRF: Record/cut number	integer	MPLRF: If set (>0) record/cut number (PDM field ID: CNR.SCHNEIDNR)
trans_einh	Transport unit	char(10)	Transport unit (PDM field ID: CNR.TPE)
transport_status	Transport status	char(1)	F - "Normal" batch B - Ready for booking out L - Booked out in storage O - Booked out for external I - Sent to external T - Transport carried out (PDM field ID: CNR.TST)
umrech_pri_nen	Numerator of primary quantity	integer	(PDM field ID: CNR.UMRFAKTP:N)

umrech_pri_zae	Denominator of primary quantity	integer	(PDM field ID: CNR.UMRFAKTP:Z)
umrech_sek_nen	Numerator of secondary quantity	integer	(PDM field ID: CNR.UMRFAKTS:N)
umrech_sek_zae	Denominator of secondary quantity	integer	(PDM field ID: CNR.UMRFAKTS:Z)
umrech_ter_nen	Numerator of tertiary quantity	integer	(PDM field ID: CNR.UMRFAKTT:N)
umrech_ter_zae	Denominator of tertiary quantity	integer	(PDM field ID: CNR.UMRFAKTT:Z)
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	

user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
van_auftrag_nr	Advance logon for ANR (order number)	char(40)	Advance logon for ANR (order number) (PDM field ID: CNR.VANR)
van_masch_nr		char(10)	
van_slp	Advance logon for SLP (BOM)	char(10)	Advance logon for SLP (BOM) (PDM field ID: CNR.VSLP)
van_status	Advance logon of status:	char(1)	Advance logon of status: 'V' - Batch has been logged on in advance (PDM field ID: CNR.VST)
verfall_dat	Expiry date	date	Expiry date (PDM field ID: CNR.VFDAT)
verfall_zeit	Expiry time	integer	Expiry time (PDM field ID: CNR.VFZEI)
verfueg_dat	Availability date	date	Availability date (PDM field ID: CNR.VVDAT)
verfueg_zeit	Availability time	integer	Availability time (PDM field ID: CNR.VVZEI)
verw_dauer	Retention period	integer	Retention period

vwe_code	Usage decision - group	char(10)	Possible values: GSB -> blocked GFB -> free AUS -> scrap (PDM field ID: CNR.VWG)
vwe_id	Usage decision - single code	char(20)	Usage decision - single code (PDM field ID: CNR.VWE)
warn_dat	Warning date	date	Warning date (PDM field ID: CNR.WDAT)
warn_zeit	Warning time	integer	Warning time (PDM field ID: CNR.WZEI)
working_status		char(10)	

9.11. los_status

Table name: los_status		Product: MPL	
Designation: Batch status		Description: The table is not used instead of that the current status is saved in the los_bestand table. For the description please see los_bestand inventory tables.	
Column name	Column designation	Type	Description
anmeld_dat		date	Please see los_bestand inventory tables
anmeld_zeit		integer	Please see los_bestand inventory tables
auftrag_nr		char(40)	Please see los_bestand inventory tables
bmk_01		integer	Please see los_bestand inventory tables
bmk_02		integer	Please see los_bestand inventory tables
bmk_03		integer	Please see los_bestand inventory tables
bmk_04		integer	Please see los_bestand inventory tables
bmk_05		integer	Please see los_bestand inventory tables
bmk_06		integer	Please see los_bestand inventory tables
bmk_07		integer	Please see los_bestand inventory tables
bmk_08		integer	Please see los_bestand inventory tables
bmk_09		integer	Please see los_bestand inventory tables
bmk_10		integer	Please see los_bestand inventory tables
bmk_11		integer	Please see los_bestand inventory tables
bmk_12		integer	Please see los_bestand inventory tables
dauer		integer	Please see los_bestand inventory tables
ein_h_1		char(3)	Please see los_bestand inventory tables
ein_h_2		char(3)	Please see los_bestand inventory tables
ein_h_3		char(3)	Please see los_bestand inventory tables
ein_h_4		char(3)	Please see los_bestand inventory tables
ein_h_5		char(3)	Please see los_bestand inventory tables
losnr	siehe Bestandstabellen los_bestand	char(20)	Please see los_bestand inventory tables (PDM field ID: Siehe Bestandstabellen los_bestand)
masch_nr		char(20)	Please see los_bestand inventory tables
menge_1		decimal(18,6)	Please see los_bestand inventory tables
menge_2		decimal(18,6)	Please see los_bestand inventory tables
menge_3		decimal(18,6)	Please see los_bestand inventory tables
menge_4		decimal(18,6)	Please see los_bestand inventory tables
menge_5		decimal(18,6)	Please see los_bestand inventory tables
param_01		integer	Please see los_bestand inventory tables
param_02		decimal(18,6)	Please see los_bestand inventory tables
param_str01		char(10)	Please see los_bestand inventory tables
param_str02		char(30)	Please see los_bestand inventory tables
pers_dauer		integer	Please see los_bestand inventory tables
prot_dat		date	Please see los_bestand inventory tables
prot_zeit		integer	Please see los_bestand inventory tables
status		char(1)	Please see los_bestand inventory tables

9.12. los_zuordnung

Table name: los_zuordnung		Product: MPL	
Archive table: a_los_zuordnung		Reload table: r_los_zuordnung	
Designation: Loszuordnung		Description: Batch relations between input and output batches for batch tracing	
Column name	Column designation	Type	Description
a_atkbez	Output batch	char(40)	Material designation of output batch
adll_nr		char(20)	external output batch number
al_ab_dat		date	Date of log off output batch
al_ab_zeit		integer	Time of log off output batch
al_an_dat		date	Date of log on output batch
al_an_zeit		integer	Time of log on output batch
al_charge		char(20)	ERP charge number of output batch
al_hztyp		char(10)	Material type of output batch
al_matnr		char(40)	Material number of output batch
al_nr		char(20)	Output batch (PDM field ID: CNRBAUM.CNR:A)
auftrag_nr	Order number	char(40)	Operation number
buendelnr		char(40)	
deleted	Flag for marking a record as logically deleted.	integer	Flag for marking a record as logically deleted.
dialog		char(80)	
e_atkbez	Input batch	char(40)	Material designation of input batch
edll_nr		char(20)	external input batch number
einr		char(3)	Unit of input quantity
einsatz_menge		decimal(18,6)	Input quantity based on the production of 1 article in the primary quantity unit at the operation
el_ab_dat		date	Date of log off input batch
el_ab_zeit		integer	Time of log off input batch
el_an_dat		date	Date of log on input batch
el_an_zeit		integer	Time of log on input batch
el_charge		char(20)	ERP charge number of input batch
el_hztyp		char(10)	Material type of input batch
el_matnr		char(40)	Material number of input batch
el_nr		char(20)	Input batch (PDM field ID: CNRBAUM.CNR:E)
masch_nr		char(20)	Machine number (PDM field ID: CNRBAUM.MNR)
mlst_kennz		char(1)	Material type of material list (e.g. M, Z, T)
mutter_al_nr		char(20)	
mutter_el_nr		char(20)	
param01		integer	not used
param02		integer	not used
param_d01		decimal(18,6)	not used
param_d02		decimal(18,6)	not used

param_str01		char(20)	not used
param_str02		char(20)	not used
rf_sa_einh		char(3)	not used
rf_sa_menge		decimal(18,6)	not used
rf_sflg		char(10)	Position in input material list
stationsnr		integer	customer specific usage
zuordtyp		char(1)	

9.13. mat_matpuf

Table name: mat_matpuf		Product: MPL	
Designation: Inventory limits		Description: Assignment of material to material buffer	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bemerkung	Comment	char(40)	Comment (PDM field ID: MATMATPUF.BEM)
best_high	Upper warning limit	integer	Upper warning limit (PDM field ID: MATMATPUF.BEST:OEG)
best_highhigh	Upper alarm limit	integer	Upper alarm limit (PDM field ID: MATMATPUF.BEST:OTG)
best_low	Lower warning limit	integer	Lower warning limit (PDM field ID: MATMATPUF.BEST:UEG)
best_lowlow	Lower alarm limit	integer	Lower alarm limit (PDM field ID: MATMATPUF.BEST:UTG)
best_max	Maximum stock level	integer	Maximum stock level (PDM field ID: MATMATPUF.BEST:MAX)
best_min	Minimum stock level	integer	Minimum stock level (PDM field ID: MATMATPUF.BEST:MIN)
einheit	Unit	char(3)	Unit (PDM field ID: MATMATPUF.EINH)
mat_puf	Material buffer	char(12)	Material buffer (PDM field ID: MATMATPUF.MATPUF)
material	Material	char(40)	Material (PDM field ID: MATMATPUF.MAT)
param_01		integer	For future use
param_02		integer	For future use
param_str01		char(20)	For future use
param_str02		char(20)	For future use
pdouble_01		decimal(18,6)	For future use
pdouble_02		decimal(18,6)	For future use

9.14. mat_mattyp

Table name: mat_mattyp		Product: MPL	
Designation: Assignment material to material type		Description: Definition of the assignment of material to material types. On the basis of this assignment the respective material type is determined from the article	
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bemerkung	Comment	char(40)	Comment (PDM field ID: MATMATTYP.BEM)
hz_typ	Material type	char(10)	Material type (PDM field ID: MATMATTYP.MATTYP)
material	Article number	char(40)	Article number (PDM field ID: MATMATTYP.MAT)
min_lagerzeit	Minimum storage time	integer	Minimum storage time (PDM field ID: MATMATTYP.LAGZMIN)
param_01		integer	For future use
param_02		integer	For future use
param_str01		char(20)	[1,1] J/N Material is reusable "/N": Material is not reusable "J": Material is reusable ID: MATMATTYP.OPT:WDVW (PDM field ID: (Composed of several acronyms))
param_str02		char(20)	For future use
pdouble_01		decimal(18,6)	For future use
pdouble_02		decimal(18,6)	For future use
verfallgrenze	Expiry limit	integer	Expiry limit in seconds (PDM field ID: MATMATTYP.VFG)
warngrenze	Warning limit	integer	Warning limit in seconds (PDM field ID: MATMATTYP.WG)

9.15. mat_puffer

Table name: mat_puffer		Product: MPL	
Designation: Material buffers		Description: Material buffers and destinations	
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bez	Designation	char(30)	Designation (PDM field ID: MATPUF.BEZ)
h_mat_puf	Superior material buffer	char(12)	Superior material buffer (PDM field ID: MATPUF.HARCMATPUF)
hierarchie_id	Hierarchy level	smallint	Hierarchy level (PDM field ID: MATPUF.HARCID)
kfg_kz01		char(10)	[1,1] J = Trash ID: MATPUF.OPT:PKORB [2,2] J = Include in stock ID: MATPUF.OPT:INBESTVERB [3,3] Buffer type E = Input buffer A = Output buffer ID: MATPUF.ART [4,4] L = Storage posting buffer ID: MATPUF.OPT:LAGVERB [5,5] J = Virtual storage buffer ID: MATPUF.OPT:VIRTLAG [8,8] Storage location is located "E"=external, "I"=internal for slitter winder ID: MATPUF.OPT:LAGORT (PDM field ID: (Composed of several acronyms))
kfg_kz02	Corr. system	char(10)	Correspondent system to which data of the buffer are transferred (for output buffers and storage posting buffers) reference to los_zielorte.ziel (PDM field ID: MATPUF.ZLO)
kfg_kz03		char(10)	For future use
lgort	Storage location	char(20)	Storage location (PDM field ID: MATPUF.LAGORT)
mat_puf	Material buffer	char(12)	Material buffer (PDM field ID: MATPUF.MATPUF)
msl_buffer_type		char(1)	
param01	Comment	char(20)	For future use (PDM field ID: MATPUF.BEM)
param_01		integer	For future use
param_02		integer	For future use
param_str01		char(20)	For future use
param_str02		char(20)	For future use
pdouble_01		decimal(18,6)	For future use
pdouble_02		decimal(18,6)	For future use
puffer_typ	buffer type	char(1)	F = Production buffer H = Hierarchical buffer W = Goods receipt buffer C = Casting house buffer (PDM field ID: MATPUF.TYP)

verw_dauer	Retention period	smallint	Retention period (PDM field ID: MATPUF.DAUER)
werk		char(4)	Plant (PDM field ID: MATPUF.FIR)
zu_abteilung		char(10)	Department (PDM field ID: MATPUF.ABT)
zu_bereich	Area	char(10)	Area (PDM field ID: MATPUF.BER)
zu_kst		char(10)	Cost center (PDM field ID: MATPUF.KST)

9.16. mat_verw_einschr

Table name: mat_verw_einschr		Product: MPL	
Designation: material usage restriction			
Column name	Column designation	Type	Description
art	restriction type	char(1)	
bearb	last editor	char(10)	
bearb_date	last edit date	date	
bearb_time	last edit time	integer	
einschr_expr	restriction formula	char(6)	
kurztext	designation	char(20)	
langtext	description	char(80)	
material	material	char(40)	

9.17. mat_zul_ein_material

Table name: mat_zul_ein_material		Product: MPL	
Designation: permitted input materials			
Column name	Column designation	Type	Description
bearb	last editor	char(10)	
bearb_date	last edit date	date	
bearb_time	last edit time	integer	
eing_material	input material	char(40)	
kurztext	designation	char(20)	
langtext	description	char(80)	
material	material	char(40)	
user_c_29	userfield	char(1)	
user_c_30	userfield	char(1)	
user_c_31	userfield	char(1)	
user_c_32	userfield	char(1)	
user_c_33	userfield	char(1)	
user_c_34	userfield	char(1)	
user_c_35	userfield	char(1)	
user_c_36	userfield	char(1)	
user_c_37	userfield	char(1)	
user_c_38	userfield	char(1)	
user_c_39	userfield	char(1)	
user_c_40	userfield	char(1)	
user_c_41	userfield	char(1)	
user_c_42	userfield	char(1)	
user_c_43	userfield	char(1)	
user_c_44	userfield	char(1)	
user_c_45	userfield	char(10)	
user_c_46	userfield	char(10)	
user_c_47	userfield	char(10)	
user_c_48	userfield	char(10)	
user_c_49	userfield	char(10)	
user_c_50	userfield	char(10)	
user_c_51	userfield	char(20)	
user_c_52	userfield	char(20)	
user_c_53	userfield	char(20)	
user_c_54	userfield	char(20)	
user_c_55	userfield	char(20)	
user_c_56	userfield	char(20)	
user_c_57	userfield	char(20)	
user_c_58	userfield	char(20)	
user_c_59	userfield	char(20)	

user_c_60	userfield	char(20)	
user_c_61	userfield	char(20)	
user_c_62	userfield	char(20)	
user_c_63	userfield	char(20)	
user_c_64	userfield	char(20)	
user_c_65	userfield	char(40)	
user_c_66	userfield	char(40)	
user_code	userfield code	char(8)	
user_d_01	userfield	date	
user_d_02	userfield	date	
user_d_03	userfield	date	
user_d_04	userfield	date	
user_d_05	userfield	date	
user_d_06	userfield	date	
user_f_23	userfield	decimal(18,6)	
user_f_24	userfield	decimal(18,6)	
user_f_25	userfield	decimal(18,6)	
user_f_26	userfield	decimal(18,6)	
user_f_27	userfield	decimal(18,6)	
user_f_28	userfield	decimal(18,6)	
user_n_07	userfield	integer	
user_n_08	userfield	integer	
user_n_09	userfield	integer	
user_n_10	userfield	integer	
user_n_11	userfield	integer	
user_n_12	userfield	integer	
user_n_13	userfield	integer	
user_n_14	userfield	integer	
user_n_15	userfield	integer	
user_n_16	userfield	integer	
user_n_17	userfield	integer	
user_n_18	userfield	integer	
user_n_19	userfield	integer	
user_n_20	userfield	integer	
user_n_21	userfield	integer	
user_n_22	userfield	integer	
zusatz	Additional material	char(1)	

9.18. material_arten

Table name: material_arten		Product: MPL	
Designation: Material classification			
Column name	Column designation	Type	Description
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing time	integer	Last editing time
bezeichnung		char(40)	---- (PDM field ID: HZART.BEZ)
hzart	Material type of material category	char(10)	E - Finished product H - Material type New as of MPL 7.2: B - Bale M - Mixture (= portion?) D - Dispersion T - Carrier material R - Coil L - Batch (as general term) G - Container O - Big container P - Pallet (package) (PDM field ID: HZART.ART)
opt_delete		char(1)	--- (PDM field ID: HZART.OPT:DEL)
verweis		integer	---

9.19. mlst_hy

Table name: mlst_hy		Product: MPL	
Archive table: a_mlst_hy		Reload table: r_mlst_hy	
Designation: Material list		Description: If required, component lists/bill of materials of the operation are filed in this table. All input materials intended for an order/OP are defined here.	
Column name	Column designation	Type	Description
anzahl_gesamt	Total entries.	integer	Total entries. The anzahl_gesamt field must not be mistaken for the IST_MENGE. In ist_menge the total quantity required for the order is entered and in anzahl_gesamt the frequency of the transferred bill of material items is allocated internally. Which means if there is an entry of a resource with the required quantity = 4 then in anzahl_gesamt = 1 and in ist_menge = 4 (ST). -> Number of added items from bill of material = anzahl_gesamt - anzahl_von_pps 1 : Default value
anzahl_von_pps		integer	Entries coming from the PPS system. The anzahl_von_pps field is the frequency of positions directly coming from PPS. O: not transferred by PPS system
artikel	material number	char(40)	For materials: material number For documents: optional, but should be filled so that something is displayed in the list at the console or terminal (can be the name or file name) (PDM field ID: MATLIST.ATK)
artikel_bez	Material designation	char(40)	Optional: designation of the component (material, document, etc.) (PDM field ID: MATLIST.ATKBEZ)
auftrag_nr	Reference to order/OP	char(40)	Reference to auftrags_bestand.auftrag_nr Reference to order/OP (PDM field ID: MATLIST.ANR)
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bereist_menge_einh	Unit of staging quantity	char(3)	Unit of staging quantity (PDM field ID: MATLIST.EINH:PPS)
bereitstell_menge	Quantity provided by SAP	decimal(18,6)	Staging quantity of the PPS system (PDM field ID: MATLIST.MENGE:PPS)
bez_1	Designation 1	char(30)	Customer-specific (PDM field ID: MATLIST.BEZ)
bez_2	Designation 2	char(30)	Standard: ID: MATLIST.BEZ:2 (PDM field ID: MATLIST.BEZ:2)
ca_wl_pflicht	Obligation to change output batch	char(1)	If the input batch of this component is changed it is required to change the output batch as well. MPL: if the input batch of this component is changed it is required to change the output batch as well. (PDM field ID: MATLIST.OPT:WZW)
chargen_nr		char(20)	 (PDM field ID: MATLIST.CNR)
datei	File name	char(128)	For documents: file name (PDM field ID: MATLIST.DATEI)
delete_kz		char(1)	MPL/RF interface: Identifies components to be deleted deletion flag
ersetzbar	Component is worth being "replaced"	char(1)	Identifies the component as being replaceable. MPL-RF: identifies the component as being replaceable. (PDM field ID: MATLIST.OPT:ERSB)
firma	Comp.	char(4)	Company of component (PDM field ID: MATLIST.FIR)

hauptressource	Main resource	char(1)	Indicator: main resource (WRM) --> first resource taken over into order. (PDM field ID: MATLIST.HAUPTRES)
hz_typ	Material type	char(10)	Material type (PDM field ID: MATLIST.MATTYP)
ist_einh_sek	Unit of secondary quantity	char(3)	Unit of secondary quantity (PDM field ID: MATLIST.EGE:S)
ist_einh_ter	Unit of secondary quantity	char(3)	Unit of secondary quantity (PDM field ID: MATLIST.EGE:T)
ist_menge	Requirements quantity	decimal(18,6)	Theoretical consumption quantity during current logon of OP. For resources this field is empty. The required amount of resources is deposited in the field soll_menge. (PDM field ID: MATLIST.EGR:GUT)
ist_menge_einh	Unit of requirement quantity	char(3)	Unit of requirement quantity (PDM field ID: MATLIST.EGE:GUT)
ist_menge_sek	Absolute component consumption	decimal(18,6)	Absolute component consumption (PDM field ID: MATLIST.EGR:GUTS)
ist_menge_ter		decimal(18,6)	for future use (PDM field ID: MATLIST.EGR:GUTS)
kennz	Identifies the component	char(10)	B = Operating resources M = Material V = Devices W = Tools Q = Meas. equipment D = Documents C = NC programs Then there are the following IDs only: "M" (Consumable) material "I" Info component "T" Carrier material "A" Scrap component "Z" Added material (PDM field ID: MATLIST.ART)
kennz_slos	Superordinate SNo	char(1)	
kz_fmenge		char(1)	Quantity is fixed: quantity of an item is constant (PDM field ID: MATLIST.MENGE:FIX)
manuell	Data record created manually (J)	char(1)	Data record created manually (J/N) (PDM field ID: MATLIST.OPT:MANU)
menge_von_pps	Required quantity (ERP)	decimal(18,6)	Quantity transferred by the PPS in the interface. Is required for hy7PPs processing.
mengen_abweichung	Deviation [%]	decimal(18,6)	 (PDM field ID: MATLIST.MENGEABW)
mengen_tol	Tolerance [%]	decimal(18,6)	 (PDM field ID: MATLIST.MENGETOL)
meta_res	Meta resource	char(1)	In this case, it is a package which is assigned to further components via the bill of materials
mlst_param_str01	unit of weight	char(10)	So far: unit of weight is transferred to SOLL_EINH_SEK (PDM field ID: MATLIST.EINH:GEW)
mlst_param_str02	div.	char(30)	[1,1] composition type (MATLIST.COMPART) P-planned sump A-actual sump R-reserved material [2,2] = 'C': confirmation executed (COMP.CHRGCONFIRM) (PDM field ID: div.)
mlst_pddouble_01	weight	decimal(18,6)	So far: weight is transferred to SOLL_MENGE_SEK (PDM field ID: MATLIST.GEW)
mlst_pddouble_02		decimal(18,6)	For future use
mlst_plong_01		integer	For future use
mlst_plong_02		integer	For future use
mlst_pshort_01		smallint	For future use

mlst_pshort_02		smallint	For future use
obere_toleranz	Upper tolerance limit	decimal(18,6)	Input quantity - upper tolerance (PDM field ID: MATLIST.OTG)
path	Path	char(8)	For documents: reference to HY_PATH Is preassigned to "HYDRA" if not transferred by external. (PDM field ID: MATLIST.PATH)
plan_artikel	MPL-RF: Planned article	char(40)	MPL-RF: planned article
pos	Position	char(10)	Bill of materials item (PDM field ID: MATLIST.SLP)
pos_m	BOM item	char(10)	Bill of material item master material (PDM field ID: MATLIST.SLP:M)
res_familie	Resource family	integer	Family to which the resource belongs (PDM field ID: MATLIST.RESFAM)
res_typ	Resource type	char(4)	WNR, DOC, etc = Resource type MAT = Materials--> At insert the material type is determined unless this one is not indicated! (PDM field ID: MATLIST.RESTYP)
res_version	Version	char(20)	Resource version
res_verweis		integer	Reference to the data record of this resource in res_bestand
res_verweis_m		integer	Reference to the data record of the package in res_bestand; in case of a package (meta_res = "J"), this value is identical to RES_VERWEIS This is, for example, important to be able to determine whether a document is assigned to a DNC package or directly to the OP.
rf_sa_mg	Spec. mass per unit area	decimal(18,6)	MPL-RF: specific mass per unit area/layer thickness of layer to be applied (PDM field ID: MATLIST.SAMG)
rf_sa_mg_einh	UOM Spec. mass per unit area	char(3)	Unit of RF_SA_MG (PDM field ID: MATLIST.EINH:SAMG)
rgekz_pps	Backflush	char(1)	J = indicator for backflush (PDM field ID: MATLIST.PPS:RETRO)
sap_vornr	SAP operation number	char(4)	SAP operation number to which this component belongs. MPL-RF: SAP operation number to which this component belongs. (PDM field ID: MATLIST.SAPVGNR)
soll_einh	Unit of input quantity	char(3)	Unit of input quantity (PDM field ID: MATLIST.SGE:GUT)
soll_einh_sek	Unit of secondary quantity	char(3)	Unit of secondary quantity
soll_einh_ter	Unit of secondary quantity	char(3)	Unit of secondary quantity
soll_menge	Input quantity	decimal(18,6)	Input quantity based on the production of 1 article in the primary quantity unit at the operation (PDM field ID: MATLIST.SGR:GUT)
soll_menge_proz	Input quantity in %	decimal(18,6)	Percentage requirement quantity (PDM field ID: MATLIST.MENGEPROZ)
soll_menge_sek	Secondary quantity, e.g. weight	decimal(18,6)	Secondary quantity, e.g. weight (PDM field ID: MATLIST.GEW)
soll_menge_ter	Secondary quantity , e.g. weight	decimal(18,6)	Secondary quantity , e.g. weight
sta_erfasst		char(1)	(PDM field ID: MATLIST.STA:ERF)
sta_mengenanp		char(1)	(PDM field ID: MATLIST.STA:MENGENANP)
stueli_stufe	Bill of material level	integer	Bill of material level (PDM field ID: MATLIST.SLS)
stueli_stufe_m	BOM level	integer	Bill of material level master material (PDM field ID: MATLIST.SLS:M)
tranr		char(40)	
untere_toleranz	Lower tolerance limit	decimal(18,6)	Input quantity - lower tolerance (PDM field ID: MATLIST.UTG)
user_c_29		char(1)	

user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	(PDM field ID: MATLIST.FU:45)
user_c_46		char(10)	(PDM field ID: MATLIST.FU:46)
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	(PDM field ID: MATLIST.FU:53)
user_c_54		char(20)	(PDM field ID: MATLIST.FU:54)
user_c_55		char(20)	(PDM field ID: MATLIST.FU:55)
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	

user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	(PDM field ID: MATLIST.FU:23)
user_f_24		decimal(18,6)	(PDM field ID: MATLIST.FU:24)
user_f_25		decimal(18,6)	(PDM field ID: MATLIST.FU:25)
user_f_26		decimal(18,6)	(PDM field ID: MATLIST.FU:26)
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	(PDM field ID: MATLIST.FU:7)
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
verb_zaehtler	Automatic counter consumption	char(1)	
verbrauch	Consumption quantity	decimal(18,6)	Previously posted consumption of this component (only batch related). (PDM field ID: MATLIST.MENGE:VBR -> MATLIST.VGR:GUT)
verbrauch_art	Consumpt. type	char(2)	Type of consumption calculation: 'N': none 'D': discrete (without batch reference) 'L': retrograde with batch reference 'A': anonymous (ANP-000098) 'U': customer specific 'W': retrograde/goods movement only (optional with batch reference) (PDM field ID: MATLIST.VERBR)
verbrauch_einh	MPL-RF: Unit of consumption quantity	char(3)	MPL-RF: Unit of consumption quantity (PDM field ID: VGE:GUT)
verweis	Reference	serial	Reference (PDM field ID: MATLIST.VERWEIS)
we_menge	Quantity posted by goods receipt batches	decimal(18,6)	default = 0 Goods receipt quantity: quantity posted by goods receipt batches (PDM field ID: MATLIST.MENGE:WE)
we_menge_einh	Unit of goods receipt quantity	char(3)	Unit of goods receipt quantity (PDM field ID: MATLIST.EINH:WE)

9.20. mpl_beziehungen

Table name: mpl_beziehungen		Product: MPL	
Archive table: a_mpl_beziehungen		Reload table: r_mpl_beziehungen	
Designation: Batch relations			
Column name	Column designation	Type	Description
art	Losbeziehungen	char(10)	Type
auftrag_nr		char(40)	
datum		date	
losnr1		char(20)	
losnr2		char(20)	
masch_nr		char(10)	
mattyp1		char(10)	
mattyp2		char(10)	
nummer1		char(40)	
nummer2		char(40)	
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	

user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
verweis		serial	
zeit		integer	

9.21. mpl_setup

Table name: mpl_setup		Product: MPL	
Designation: MPL-Setup		Description: Definition der MPL-Grundeinstellungen	
Column name	Column designation	Type	Description
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
c_fix	Fixer Teil bei Prod.-Losen	char(10)	Fixe Stellen, die der Losnummer für Fertigungslose vorangestellt wird (z.B. bei CA_WL). (PDM field ID: HYDRA.CNRFIX:PR)
c_gen_fix	Fixer Teil bei Generierung	char(10)	Fixe Stellen, die der Losnummer für WE-Lose vorangestellt wird. Die Stellenanzahl muß gleich mit der von C_FIX sein (PDM field ID: HYDRA.CNRFIX:WE)
c_gen_manu	Kennzeichen Automatische Losnummerngen.	char(1)	Kennzeichen, mit dem festgelegt wird, ob HYDRA die Losnummer automatisch generieren soll. "J" / "" Automatische Generierung der Losnummer bei Los anlegen (z.B. WE Los anlegen) "N" Bei manueller Generierung von Losen wird die Eingabe der Losnummer erwartet. (PDM field ID: HYDRA.OPT:CNRAUTOGEN)
cnr_len	Losnummernlänge	smallint	Losnummerlänge Mindestlänge: 8 (bei 0 fixen Stellen) Die Länge muß mindestens 8 + Stellenanzahl (C_FIX bzw. C_GEN_FIX) sein, darf jedoch max. 20-stellig sein. (PDM field ID: HYDRA.LEN:CNR)
elos_auto_ab	Aumatische ELos-Abmeldung	char(1)	Kennzeichen, ob alle Eingangslose beim Abmelden des letzten AGs ebenfalls abgemeldet werden (PDM field ID: HYDRA.OPT:CNRAUTOAB)
param_01		integer	free
param_02		integer	free
param_str01	MPL Parameter 1	char(20)	free (PDM field ID: HYDRA.MPL:PARAM1)
param_str02	MPL Parameter 2	char(20)	free (PDM field ID: HYDRA.MPL:PARAM2)
pdouble_01		decimal(18,6)	free
pdouble_02		decimal(18,6)	free

9.22. r_los_zuordnung

Table name: r_los_zuordnung		Product: MPL	
Designation: Loszuordnung			
Column name	Column designation	Type	Description
a_atkbez		char(40)	
adll_nr		char(20)	
al_ab_dat		date	
al_ab_zeit		integer	
al_an_dat		date	
al_an_zeit		integer	
al_charge		char(20)	
al_hztyp		char(10)	
al_matnr		char(40)	
al_nr		char(20)	
auftrag_nr		char(40)	
buendelnr		char(40)	
deleted	Flag for marking a record as logically deleted.	integer	Flag for marking a record as logically deleted.
dialog		char(80)	
e_atkbez		char(40)	
edll_nr		char(20)	
einb		char(3)	
einsatz_menge		decimal(18,6)	
el_ab_dat		date	
el_ab_zeit		integer	
el_an_dat		date	
el_an_zeit		integer	
el_charge		char(20)	
el_hztyp		char(10)	
el_matnr		char(40)	
el_nr		char(20)	
masch_nr		char(20)	
mlst_kennz		char(1)	
mutter_al_nr		char(20)	
mutter_el_nr		char(20)	
param01		integer	
param02		integer	
param_d01		decimal(18,6)	
param_d02		decimal(18,6)	
param_str01		char(20)	
param_str02		char(20)	
rf_sa_einh		char(3)	

rf_sa_menge		decimal(18,6)	
rf_sflg		char(10)	
stationsnr		integer	
zuordtyp		char(1)	

10. PDV

10.1. ana_pdatref_pparam

Table name: ana_pdatref_pparam		Product: PDV	
Designation: Process data reference - process parameters - combinations		Description: This table contains combinations of process data references and process parameters of the analysis data pool. * Keys id (technical key) pdatref_id, pparam_id (business key) *logical connection to other tables ana_pdatref (ana_pdatref.id = ana_pdatref_pparam.pdatref_id) ana_pparam (ana_pparam.id = ana_pdatref_pparam.pparam_id)	
Column name	Column designation	Type	Description
id	Technical ID	bigserial	
pdatref_id	Reference to process data reference	integer	
pparam_id	Reference to process parameter (analysis data)	integer	

10.2. ana_pdatref_pparam_datasup

Table name: ana_pdatref_pparam_datasup		Product: PDV	
Designation: Process data reference - process parameter - data suppliers - combinations		Description: This table contains combinations of process data references, process parameters and data suppliers of the analysis data pool. * Keys id (technical key) pdatref_pparam_id, data_supplier_id (business key) *logical connection to other tables ana_pdatref_pparam (ana_pdatref_pparam.id = ana_pdatref_pparam_datasup.pdatref_pparam_id) ana_datasup (ana_datasup.id = ana_pdatref_pparam_datasup.data_supplier_id)	
Column name	Column designation	Type	Description
data_supplier_id	Reference to data supplier	integer	
id	Technical ID	bigserial	
pdatref_pparam_id	Reference to process data reference - process parameter - data supplier	bigint	

10.3. ana_pdatref_pparam_last_spec

Table name: ana_pdatref_pparam_last_spec		Product: PDV	
Designation: Most recent external process data specifications		Description: This table contains the latest external process specifications of the analysis data pool. * Keys id (technical key) workplace_name, process_param_name, specification_type (business key)	
Column name	Column designation	Type	Description
change_time	Specification change time	datetime	
id	Technical ID	datetime	
process_param_name	Process parameter name	char(100)	
specification_type	Type of specification	char(10)	
specification_value	Value	float	
workplace_name	Workplace name	char(50)	

10.4. ana_pdatref_pparam_spec

Table name: ana_pdatref_pparam_spec		Product: PDV	
Designation: Process data specifications		Description: This table contains process specifications of the analysis data pool.	
		* Note The process specifications in this the table is a compressed result of all process specification changes of the table ana_pdatref_pparam_spec_change.	
		* Keys change_time, pdatref_pparam_id (business key)	
		*logical connection to other tables ana_pdatref_pparam (ana_pdatref_pparam.id = ana_pdatref_pparam_spec.pdatref_pparam_id)	
Column name	Column designation	Type	Description
change_time	Specification change time	datetime	
lower_plausibility_limit	Lower plausibility limit	float	
lower_process_action_limit	Lower plausibility limit	float	
lower_tolerance_limit	Lower tolerance limit	float	
pdatref_pparam_id	Reference to process data reference - process parameter - data supplier	bigint	
target_value	Target value	float	
upper_plausibility_limit	Upper plausibility limit	float	
upper_process_action_limit	Upper process action limit	float	
upper_tolerance_limit	Upper tolerance limit	float	

10.5. ana_pdatref_pparam_spec_change

Table name: ana_pdatref_pparam_spec_change		Product: PDV	
Designation: Process data specification changes		Description: This table contains process specification changes of the analysis data pool.	
		* Keys change_time, pdatref_pparam_datasup_id (business key)	
		*logical connection to other tables ana_pdatref_pparam_datasup (ana_pdatref_pparam_datasup.id = ana_pdatref_pparam_spec_change.pdatref_pparam_datasup_id)	
Column name	Column designation	Type	Description
change_time	Specification change time	datetime	
lower_plausibility_change	Change lower plausibility limit?	smallint	0 = dont change 1 = change
lower_plausibility_limit	Lower plausibility limit	float	
lower_process_action_change	Change lower process action limit?	smallint	0 = dont change 1 = change
lower_process_action_limit	Lower plausibility limit	float	
lower_tolerance_change	Change lower tolerance limit?	smallint	0 = dont change 1 = change
lower_tolerance_limit	Lower tolerance limit	float	
pdatref_pparam_datasup_id	Reference to process data reference - process parameter - data supplier	bigint	
target_change	Change target value?	smallint	0 = dont change 1 = change
target_value	Target value	float	
upper_plausibility_change	Change upper plausibility limit?	smallint	0 = dont change 1 = change
upper_plausibility_limit	Upper plausibility limit	float	
upper_process_action_change	Change upper process action limit?	smallint	0 = dont change 1 = change
upper_process_action_limit	Upper process action limit	float	
upper_tolerance_change	Change upper tolerance limit?	smallint	0 = dont change 1 = change
upper_tolerance_limit	Upper tolerance limit	float	

10.6. ana_pdatref_sequence_spec

Table name: ana_pdatref_sequence_spec		Product: PDV	
Designation: Specification of reference curve		Description: This table contains the specification of the reference curve (for sequence analysis)	
		* Keys reference_time, pdatref_pparam_id (business key)	
Column name	Column designation	Type	Description
lower_plausibility_limit	Lower plausibility limit	float	
lower_process_action_limit	Lower plausibility limit	float	
lower_tolerance_limit	Lower tolerance limit	float	
pdatref_pparam_id	Reference to process data reference - process parameter - data supplier	bigint	
reference_time	Specification change time	datetime	
target_value	Target value	float	
upper_plausibility_limit	Upper plausibility limit	float	
upper_process_action_limit	Upper process action limit	float	
upper_tolerance_limit	Upper tolerance limit	float	

10.7. ana_pparam

Table name: ana_pparam		Product: PDV	
Designation: Process parameters		Description: This table contains process parameters of the analysis data pool. * Keys id (technical key) process_param_name (business key) *logical connection to other tables caq_merkmal (caq_merkmal.id = ana_pparam.process_param_id)	
Column name	Column designation	Type	Description
id	Technical ID	serial	
process_param_id	Reference to process parameter (master data)	bigint	
process_param_name	Process parameter name	char(100)	
unit_id	Reference to unit (analysis data)	integer	

10.8. ana_process_data_char

Table name: ana_process_data_char		Product: PDV	
Designation: Process values (alphanumeric)		Description: This table contains alphanumeric process values of the analysis data pool. * Keys acquisition_time, pdatref_pparam_datasup_id (business key) *logical connection to other tables ana_pdatref_pparam_datasup (ana_pdatref_pparam_datasup.id = ana_process_data_char.pdatref_pparam_datasup_id)	
Column name	Column designation	Type	Description
acquisition_time	Acquisition time	datetime	
char_value	Alphanumeric process value	char(250)	
pdatref_pparam_datasup_id	Reference to process data reference - process parameter - data supplier	bigint	

10.9. ana_process_data_decimal

Table name: ana_process_data_decimal		Product: PDV	
Designation: Process values (numeric)		Description: This table contains numeric process values of the analysis data pool. * Keys acquisition_time, pdatref_pparam_datasup_id (business key) *logical connection to other tables ana_pdatref_pparam_datasup (ana_pdatref_pparam_datasup.id = ana_process_data_decimal.pdatref_pparam_datasup_id)	
Column name	Column designation	Type	Description
acquisition_time	Acquisition time	datetime	
decimal_value	Numeric process value	float	
pdatref_pparam_datasup_id	Reference to process data reference - process parameter - data supplier	bigint	

10.10. ana_serial

Table name: ana_serial		Product: PDV	
Designation: Serial numbers (for test results)		Description: This table contains values of the serail numbers. *Note This table builds basis data for test results. * Keys id (technical key)	
Column name	Column designation	Type	Description
id	Technical ID	bigserial	
serial_number	Serial number	char(250)	

10.11. ana_serial_test

Table name: ana_serial_test		Product: PDV	
Designation: Test results of serial numbers (FPY)		Description: This table contains test results of the serial numbers. * Keys test_time, serial_id (business key) *logical connection to other tables ana_serial (ana_serial.id = ana_serial_test.serial_id)	
Column name	Column designation	Type	Description
serial_id	Reference to serial number (FPY)	bigint	
test_result	Test result	smallint	0 not passed
test_time	Test timestamp	datetime	
wplace_id	Reference to workplace (Analysis Data)	integer	

10.12. ana_tag

Table name: ana_tag		Product: PDV	
Designation: Tags		Description: This table contains tags of the analysis data pool.	
		* Note Tags in this table represents the "type of tag" (example: SNR = serial number). Each tag(-value), that is generates in the production process, is stored in table ana_tag_value.	
		* Keys id (technical key) tag name (business key)	
Column name	Column designation	Type	Description
id	Technical ID	serial	
tag_name	Tag name	char(50)	

10.13. ana_tag_process_data_char

Table name: ana_tag_process_data_char		Product: PDV	
Designation: Tags of process parameter values (alphanumeric)		Description: This table contains the tags for alphanumeric process values of the analysis data pool. * Keys process_data_acquisition_time, process_data_pdatref_ppa_ds_id, tag_value_id (business key) *logical connection to other tables ana_process_data_char (ana_process_data_char.acquisition_time = ana_tag_process_data_char.process_data_acquisition_time and ana_process_data_char.pdatref_pparam_datasup_id =ana_tag_process_data_char.process_data_pdatref_ppa_ds_id) ana_tag_value (ana_tag_value.id = ana_tag_process_data_char.tag_value_id)	
Column name	Column designation	Type	Description
process_data_acquisition_time	Reference to acquisition time of process data	datetime	
process_data_pdatref_ppa_ds_id	Reference to process data reference - process parameter - data supplier of process data	bigint	
tag_value_id	Reference to tag value	bigint	

10.14. ana_tag_process_data_decimal

Table name: ana_tag_process_data_decimal		Product: PDV	
Designation: Tags of process parameter values (numeric)		Description: This table contains the tags for numeric process values of the analysis data pool. * Keys process_data_acquisition_time, process_data_pdatref_ppa_ds_id, tag_value_id (business key) *logical connection to other tables ana_process_data_decimal (ana_process_data_decimal.acquisition_time = ana_tag_process_data_decimal.process_data_acquisition_time and ana_process_data_decimal.pdatref_pparam_datasup_id =ana_tag_process_data_decimal.process_data_pdatref_ppa_ds_id) ana_tag_value (ana_tag_value.id = ana_tag_process_data_char.tag_value_id)	
Column name	Column designation	Type	Description
process_data_acquisition_time	Reference to acquisition time of process data	datetime	
process_data_pdatref_ppa_ds_id	Reference to process data reference - process parameter - data supplier of process data	bigint	
tag_value_id	Reference to tag value	bigint	

10.15. ana_tag_value

Table name: ana_tag_value		Product: PDV	
Designation: Tag values		Description: This table contains tag values of the analysis data pool. * Keys id (technical key) tag_value, tag_id (business key) *logical connection to other tables ana_tag (ana_tag.id = ana_tag_value.tag_id)	
Column name	Column designation	Type	Description
id	Technical ID	bigserial	
tag_id	Tag name	integer	
tag_value	Tag value	char(250)	

10.16. caq_paumm_ausp

Table name: caq_paumm_ausp		Product: PDV	
Archive table: a_caq_paumm_ausp		Reload table: r_caq_paumm_ausp	
Designation: Specification history for characteristic			
Column name	Column designation	Type	Description
afo	Seq.	integer	
aktiv		smallint	
anlage		char(50)	
anlage_date		date	
anlage_time		integer	
arbgang_bez	Operation designation	char(250)	
arbgang_nr	Order number	char(50)	
artikel_idx	Drawing issue number	char(50)	
artikel_nr	Id	char(50)	
auslassen	Ignore	smallint	
bearb	Changed by	char(50)	
bearb_date	Last change - Date	date	
bearb_time	Last change - Time	integer	
bereich	Area	char(10)	
cpk_aktiv	Generate CPK error	smallint	
einheit	Unit	char(50)	
entnahme_menge	Issue quantity	integer	
format	Decimal places	char(250)	
hinweis_txt	Note	char(250)	
histogramm	Histogram	smallint	
intervall_alw	With output batch change	integer	
intervall_einh	Interval unit	char(50)	
intervall_msw	With machine status change	integer	
intervall_msw_st	Source status	char(250)	
intervall_sch_w	With change of shifts	integer	
intervall_typ	Interval type	char(50)	
intervall_wert	Interval value	integer	
karte1	Chart 1	char(50)	
karte1_ber_art	calculation type	char(50)	
karte1_ber_xq	Default XQ	float	
karte1_cpk	cpk	float	
karte1_dyn_berech	calculate dynamically	smallint	
karte1_egw_eg	action limits	char(50)	
karte1_egw_wg	warning limit	char(50)	
karte1_eins_zwei	one-sided/two-sided	char(50)	
karte1_mw	MV	float	
karte1_oeg	Upper AL	float	

karte1_oeg_aktiv	Generate failure (UAL)	smallint	
karte1_owg	Upper WL	float	
karte1_owg_aktiv	Generate failure (UWL)	smallint	
karte1_quer	Transverse	float	
karte1_rel_eg	rel. AL	float	
karte1_rel_wg	rel. WL	float	
karte1_run_aktiv	Generate run error	smallint	
karte1_sigma	Sigma	float	
karte1_trend_aktiv	Generate trend error	smallint	
karte1_ueg	Generate failure (LAL)	float	
karte1_ueg_aktiv	Lower AL	smallint	
karte1_uwg	Lower WL	float	
karte1_uwg_aktiv	Generate failure (LWL)	smallint	
karte1_vorgabe	specifications	char(50)	
karte2	Chart 2	char(50)	
karte2_ber_art	Calculation type	char(50)	
karte2_ber_xq	default XQ	float	
karte2_cpk	cpk	float	
karte2_dyn_berech	calculate dynamically	smallint	
karte2_egw_eg	Action limit	char(50)	
karte2_egw_wg	Warning limit	char(50)	
karte2_eins_zwei	one-sided/two-sided	char(50)	
karte2_mw	MV	float	
karte2_oeg	Upper AL	float	
karte2_oeg_aktiv	Generate failure (UAL)	smallint	
karte2_owg	Upper WL	float	
karte2_owg_aktiv	Generate failure (UWL)	smallint	
karte2_quer	Transverse	float	
karte2_rel_eg	rel. AL	float	
karte2_rel_wg	rel. WL	float	
karte2_run_aktiv	Generate run error	smallint	
karte2_sigma	Sigma	float	
karte2_trend_aktiv	Generate trend error	smallint	
karte2_ueg	Generate failure (LAL)	float	
karte2_ueg_aktiv	Lower AL	smallint	
karte2_uwg	Lower WL	float	
karte2_uwg_aktiv	Generate failure (LWL)	smallint	
karte2_vorgabe	specifications	char(50)	
kunde_nr	Customer-No.	char(50)	
lieferant_nr	Supplier No.	char(50)	
maschine_nr	Machine	char(20)	
merkmal_nr	Characteristic no.	char(50)	
opeg	Upper PAL	float	
opeg_aktiv	Generate failure (UPAL)	smallint	
opg	Upper PL	float	
otg	Upper TL	float	

otg_aktiv	Generate failure (UTL)	smallint	
passung_id	Fit	char(50)	
passung_norm	Standard	char(50)	
pruefanf_nr	Control chart type	integer	
pruefauf_nr	Inspection step no.	integer	
rec_type	Area type	char(50)	
res_nr	Resource	char(40)	
res_typ	Resource type	char(4)	
rueckw_zahl	Acceptance qty.	integer	
rueckw_zahl_d	Rejection quantity	integer	
spezlist_nr	Specification no.	integer	
stichpr_anzahl	Number of samples	integer	
stichpr_plan	Sampling scheme	char(50)	
stichpr_umfang	Sample size	integer	
sw	Target value	float	
upeg	Lower PAL	float	
upeg_aktiv	Generate failure (LPAL)	smallint	
upg	Lower PL	float	
user_c_01	User fields	char(50)	
user_c_02	User fields	char(50)	
user_c_03	User fields	char(50)	
user_c_04	User fields	char(50)	
user_c_05	User fields	char(50)	
user_d_01	User fields	date	
user_d_02	User fields	date	
user_f_01	User fields	float	
user_f_02	User fields	float	
user_n_01	User fields	integer	
user_n_02	User fields	integer	
user_n_03	User fields	integer	
user_n_04	User fields	integer	
user_n_05	User fields	integer	
utg	Lower TL	float	
utg_aktiv	Generate failure (LTL)	smallint	
valid_from_ts	Valid from	datetime	
valid_to_ts	Valid till	datetime	
zuordnung_nr	Analysis selection catalog	char(50)	

10.17. pdv_event_cfg

Table name: pdv_event_cfg		Product: PDV	
Designation: PDV Event Configuration		Description: This table can be used to configure any possible PDV relevant events that a maschine can communicate (for example a line break down).	
		* Notes Configured PDV Events can be assigned by using a logical channel to get captured from a machine. Appeared events also can set a digital output for use of a alert notification.	
		* Keys (event)	
		* logical connection to other tables pdv_event_prot stores appeared/captured PDV Events (pepr.event = pec.event where pepr.type = 'E') pdv_logic_chan can be used to assign a physical channel number (pec.event = plc.fkey, where plc.type = 'E')	
Column name	Column designation	Type	Description
alert	Alert Mark	char(1)	Mark if specified PDV Event should cause an alert. Possible values are: 'Y' or 'N' (N is default) Y will cause alert N (or everything else) will not cause an alert (PDM field ID: PDVEVENTCFG.OPT:ALERT)
alert_duration	Alert Duration	integer	Alert duration when configured PDV Event occures. Value in seconds. Only necessary if OPT:ALERT is set to Y (PDM field ID: PDVEVENTCFG.ALERT:DURATION)
bearb	Modified by	char(10)	Last editor
bearb_date		date	Last editing date
bearb_time		integer	Last editing time
caption	Caption	char(100)	(PDM field ID: PDVEVENTCFG.CAPTION)
category	Event category	char(20)	
event	Event Id	char(50)	Unique event id, must be filled (PDM field ID: PDVEVENTCFG.EVENT)
type	Event type	char(1)	
valid_from		datetime	for future use
valid_to		datetime	for future use

10.18. pdv_event_prot

Table name: pdv_event_prot		Product: PDV	
Archive table: a_pdv_event_prot		Reload table: r_pdv_event_prot	
Designation: PDV Event Protocol		Description: This table stores appered PDV Events as well as any Setpoint or Limit excesses. * Notes PDV Events must be configured by using table pdv_event_cfg to appear in the protocol table. Setpoint or Limit excesses will be stored automatically. No BAPI available for stored data. Only selection through Masks are supported. * Keys (capture_ts, event, event_type, setpoint_type, masch_nr) * logical connection to other tables pdv_event_cfg holds configured PDV Events maschinen holds masterdata of protocolled machine (maschinen.masch_nr = pdv_event_cfg.masch_nr)	
Column name	Column designation	Type	Description
capture_toff	Capture timestamp	integer	Appearance time of current stored event
capture_ts		datetime	- for future use - (PDM field ID: PDVEVENT.CAPTURETIME)
event	Event-Id	char(50)	Event-Id If even_type = 'S' affected processparameter id will be stored If event_type = 'E' affected PDV Event id will be stored (PDM field ID: PDVEVENT.EVENT)
event_type	Event Type	char(1)	Defines which type of event current record stored. Supported values are: - 'S' processparameter - 'E' PDV Event (PDM field ID: PDVEVENT.EVENT)
masch_nr	Machine number	char(20)	Machine number (PDM field ID: PDVEVENT.MNR)
setpoint_type	Border Area	char(4)	Stores current border area state of captured value Supported values: - OTG (upper tolerance limit area) - OPEG (upper process intervention limit area) - OK (ok area) - UPEG (lower process intervention limit area) - UTG (lower tolerance limit area) Field will only be filled if event_type = 'S' (PDM field ID: PDVEVENT.SPTYPE)
user_c_07		char(1)	(PDM field ID: PDVEVENT.FU:7)
user_c_08		char(1)	(PDM field ID: PDVEVENT.FU:8)
user_c_09		char(1)	(PDM field ID: PDVEVENT.FU:9)
user_c_10		char(1)	(PDM field ID: PDVEVENT.FU:10)

user_c_11		char(1)	(PDM field ID: PDVEVENT.FU:11)
user_c_12		char(10)	(PDM field ID: PDVEVENT.FU:12)
user_c_13		char(10)	(PDM field ID: PDVEVENT.FU:13)
user_c_14		char(20)	(PDM field ID: PDVEVENT.FU:14)
user_c_15		char(20)	(PDM field ID: PDVEVENT.FU:15)
user_c_16		char(40)	(PDM field ID: PDVEVENT.FU:16)
user_code		char(8)	(PDM field ID: PDVEVENT.USRFLD)
user_f_05		decimal(18,6)	(PDM field ID: PDVEVENT.FU:5)
user_f_06		decimal(18,6)	(PDM field ID: PDVEVENT.FU:6)
user_n_01		integer	(PDM field ID: PDVEVENT.FU:1)
user_n_02		integer	(PDM field ID: PDVEVENT.FU:2)
user_n_03		integer	(PDM field ID: PDVEVENT.FU:3)
user_n_04		integer	(PDM field ID: PDVEVENT.FU:4)
value		decimal(18,6)	(PDM field ID: PDVEVENT.VALUE)
verweis		serial	

Table name: pdv_logic_chan		Product: PDV	
Designation: Logical Channels		Description: PDV Logical Channels are the central configuration to assign physical channels (connectors) of workplaces and terminals to a specific PDV element as processparameters or PDV Events. Can be used to configure output and input data. The way to capture data can be specified as the type of data, too. * Notes With this configuration you can configure channles of different workplace/temrinal combination and the current activ workplce <> terminal assignment will be used. These are versioned master data tables with acuracy of seconds. * Keys (masch_nr, capture_id, chan_nr, fkey, type, chan_data, orientation, valid_from) * logical connection to other tables masch_nr can be joined with table maschinen.masch_nr capture_id can be joined with terminals.terminalnr fkey can be joined with pdv_event_cfg.event if type = 'E' or with caq_merkmal.messwerf_aut_art if type = 'PP'	
Column name	Column designation	Type	Description
active	Active channel	char(1)	Defines whether current channel configuration is active and should be considered or not. Possible values: Y: Channel is active N: Channel is not active (PDM field ID: LOGCHAN.AKTIV)
alert	Alert	char(1)	Defines whether the application should set an output signal if the specified channel data type (field: chan_data) is violated or not. Supported alues are: Y: Yes, alert signal should be set on channel defined by field alert_chan_nr N: No, no alert signal should be set (PDM field ID: LOGCHAN.OPT:ALERT)
alert_chan_nr	Alert Channel	integer	Defines on which physical channel an output signal should be set, if captured value violates channel data (field: chan_data). Only neccessary if field alert is set to 'Y' (PDM field ID: LOGCHAN.ALERTK)
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
capture_id	Terminal	smallint	Terminal, reference to master data table terminals (PDM field ID: LOGCHAN.TNR)
chan_cap	Channel Caption	char(20)	Channel Caption (PDM field ID: LOGCHAN.KCAP)

chan_data	Data Type	char(4)	This field specifies which type of data the captured values will belong to. These can be the upper tolerance limit, upper process intervention limit, setpoint/target value, lower process intervention limit, lower tolerance limit or measured value The following values are available: Limits: OTG - upper tolerance limit OPEG - upper process intervention limit UPEG - lower process intervention limit UTG - lower tolerance limit setpoint/target value SW - setpoint/target value Measure MW - measured value SW and MW can't be assigned if you are configuring a Channel with alert flag. If the reference id points to an anonym processparameter, only MW is allowed, because anonym processparameters don't contain any specifications. (PDM field ID: LOGCHAN.KDATA)
chan_nr	Channel Number	integer	Number of the physical channel to capture data of. Must be unique for every terminal - independent of assigned workplaces (PDM field ID: LOGCHAN.LOGK)
chan_trigger	Trigger number	integer	Channel number of physical channel, which initiates capturing current value of chan_nr. Only necessary if chan_type = 'T' (PDM field ID: LOGCHAN.TRIGGERK)
chan_type	Physical Channel Type	char(1)	Defines which method for capturing values of the physical channel should be used. There are 3 supported types of tapping values: T: (Trigger-driven) You can specify another physical channel number in field chan_trigger which will cause the PLC-Interface to capture current value of channel defined in chan_nr C: (Cyclic-driven) You can specify a time interval in seconds in field cycle_time which will cause the PLC-Interface to capture current value of channel defined in chan_nr every n seconds A: (Automatic-driven) Your machine connection allows you to transmit current data completely by itself - no trigger channel or timer is needed to receive values from the PLC-Interface (PDM field ID: LOGCHAN.KTYP)
cycle_time	Time Interval	integer	Interval in seconds which defines the cycle time after which data of chan_nr will be stored. Only necessary if chan_type = 'C' (PDM field ID: LOGCHAN.TIMER)
data_type	Data type	char(1)	
fkey	Reference Id	char(50)	Reference which data that will be captured by the physical channel belongs to. This can be any PDV Events or any configured Processparameters. (PDM field ID: LOGCHAN.ID)
masch_nr	Workplace	char(20)	Workplace reference to masterdata table maschinen (PDM field ID: LOGCHAN.MNR)
orientation	Data Direction	char(1)	Defines data exchange direction between application and machine using PLC-Interface. Supported values are: I: (Input) Data from machine to application O: (Output) Data from application to machine (PDM field ID: LOGCHAN.ARTK)
type	Reference Type	char(2)	Specifies whether the configured data id belongs to a PDV Event ('E') or to a Processparameter ('PP') Possible Values are: E - PDV Event PP - Processparameter (PDM field ID: LOGCHAN.TYP)

unit		char(3)	for future use
valid_from	Valid from	datetime	(PDM field ID: LOGCHAN.VALIDFROM)
valid_to		datetime	(PDM field ID: LOGCHAN.VALIDTO)

Table name: pdv_spc		Product: PDV	
Archive table: a_pdv_spc		Reload table: r_pdv_spc	
Designation: Setpoint changes		Description: Logs occurred setpoint or limit changes either initiated by machine or manually initiated.	
		* Notes No BAPI available for database table. Data can only be accessed using associated form of the System Client	
		* Keys (capture_ts, process_param, setpoint_type, source)	
		* logical connection to other tables Affected processparameter can be linked with inspectionorder pdv_spc.process_param = caq_merkmal.messwerf_aut_art	
Column name	Column designation	Type	Description
capture_toff		integer	- for future use -
capture_ts	Capture timestamp	datetime	Appearance time of current stored event (PDM field ID: SPC.CAPTURETIME)
masch_nr	Machine number	char(20)	Machine number (maschinen.masch_nr) (PDM field ID: SPC.MNR)
process_param	Processparameter	char(50)	Processparameter (caq_merkmal.messwerf_aut_art) (PDM field ID: SPC.PRP)
pruefauf_nr	Inspectionorder	integer	Number of associated inspectionorder (caq_paukop.pruefauf_nr) (PDM field ID: SPC.PAUNR)
setpoint_type	Setpoint / Limit type	char(4)	Setpoint / Limit type: Defines which setpoint or limit received a value change. Supported values are: - OTG (upper tolerance limit) - OPEG (upper process intervention limit) - SW (setpoint / target value) - UPEG (lower process intervention limit) - UTG (lower tolerance limit) (PDM field ID: SPC.VGT)
source	Input Source	char(1)	Defines whether setpoint/limit change was caused by machine or manually. Supported values are: - 'M' : Machine - 'C' : Client (manually) (PDM field ID: SPC.SOURCE)
user_c_07		char(1)	(PDM field ID: SPC.FU:7)
user_c_08		char(1)	(PDM field ID: SPC.FU:8)
user_c_09		char(1)	(PDM field ID: SPC.FU:9)
user_c_10		char(1)	(PDM field ID: SPC.FU:10)
user_c_11		char(1)	(PDM field ID: SPC.FU:11)
user_c_12		char(10)	(PDM field ID: SPC.FU:12)

user_c_13		char(10)	(PDM field ID: SPC.FU:13)
user_c_14		char(10)	(PDM field ID: SPC.FU:14)
user_c_15		char(10)	(PDM field ID: SPC.FU:15)
user_c_16		char(10)	(PDM field ID: SPC.FU:16)
user_code		char(8)	(PDM field ID: SPC.USRFLD)
user_f_05		decimal(18,6)	(PDM field ID: SPC.FU:5)
user_f_06		decimal(18,6)	(PDM field ID: SPC.FU:6)
user_n_01		integer	(PDM field ID: SPC.FU:1)
user_n_02		integer	(PDM field ID: SPC.FU:2)
user_n_03		integer	(PDM field ID: SPC.FU:3)
user_n_04		integer	(PDM field ID: SPC.FU:4)
value	Value	decimal(18,6)	Contains the new value for setpoint / limit defined in field setpoint_type of procesparameter defined by field process_param (PDM field ID: SPC.VGW)
verweis		serial	

10.21. stg_process_data_block_id

Table name: stg_process_data_block_id		Product: PDV	
Designation: Staging table for process values (processing mode: BLOCK)		Description: This table contains the staging data of process values. * Note This table is contains data of the staging mode "BLOCK". This mode is used, when process values are transfered via webservice without direct distribution. * Keys id (technical key) acquisition_time, workplace_name, process_param_name, data_supplier_name (business key)	
Column name	Column designation	Type	Description
acquisition_time	Acquisition time	timestamp(3)	
char_value	Alphanumeric process value	nvarchar2(250)	
data_supplier_name	Data supplier name	nvarchar2(50)	
data_type	Process value data type	number(37)	1 = Numeric 2 = Alphanumeric
decimal_value	Numeric process value	float	
id	Technical ID	bigserial	
process_param_name	Process parameter name	nvarchar2(100)	
unit_name	Unit name	nvarchar2(50)	
workplace_name	Workplace name	nvarchar2(50)	

10.22. stg_process_data_block_id_ps

Table name: stg_process_data_block_id_ps		Product: PDV	
Designation: Logtable for incorrect distribution of process values (processing mode: BLOCK)		Description: This table contains the logs for incorret distribution porcessings of table stg_process_data_block_id. * Note This table is is used for the staging mode "BLOCK". This mode is used, when process values are transfered via webservice without direct distribution. * Keys stg_data_id_to, stg_data_id_from (techical key)	
Column name	Column designation	Type	Description
processing_status	Processing status of distribution	number(37)	
stg_data_id_from	Processing range - from ID	bigint	
stg_data_id_to	Processing range - to ID	bigint	

10.23. stg_process_data_single_id

Table name: stg_process_data_single_id		Product: PDV	
Designation: Staging table for process values (processing mode: SINGLE)		Description: This table contains the staging data of process values. * Note This table is contains data of the staging mode "SINGLE". This mode is used, when process values are transfered via webservice with direct distribution. * Keys id (technical key) acquisition_time, workplace_name, process_param_name, data_supplier_name (business key)	
Column name	Column designation	Type	Description
acquisition_time	Acquisition time	timestamp(3)	
char_value	Alphanumeric process value	nvarchar2(250)	
data_supplier_name	Data supplier name	nvarchar2(50)	
data_type	Process value data type	number(37)	1 = Numeric 2 = Alphanumeric
decimal_value	Numeric process value	float	
id	Technical ID	bigserial	
process_param_name	Process parameter name	nvarchar2(100)	
processing_status	Processing status of distribution	number(37)	
unit_name	Unit name	nvarchar2(50)	
workplace_name	Workplace name	nvarchar2(50)	

10.24. stg_process_data_tag_block_id

Table name: stg_process_data_tag_block_id		Product: PDV	
Designation: Staging table for tags of process values (processing mode: BLOCK)		Description: This table contains the staging data of process values tags.	
		* Note This table is contains data of the staging mode "BLOCK". This mode is used, when process values are transfered via webservice without direct distribution.	
		* Keys id, tag_name (technical key)	
		*logical connection to other tables stg_process_data_block_id (stg_process_data_block_id.id = stg_process_data_tag_block_id.id)	
Column name	Column designation	Type	Description
id	Technical ID	bigint	
tag_name	Tag name	nvarchar2(50)	
tag_value	Tag value	nvarchar2(250)	

10.25. stg_process_data_tag_single_id

Table name: stg_process_data_tag_single_id		Product: PDV	
Designation: Staging table for tags of process values (processing mode: SINGLE)		Description: This table contains the staging data of process values tags. * Note This table is contains data of the staging mode "SINGLE". This mode is used, when process values are transfered via webservice with direct distribution. * Keys id, tag_name (technical key) *logical connection to other tables stg_process_data_single_id (stg_process_data_single_id.id = stg_process_data_tag_block_id.id)	
Column name	Column designation	Type	Description
id	Technical ID	bigint	
tag_name	Tag name	nvarchar2(50)	
tag_value	Tag value	nvarchar2(250)	

10.26. stg_process_spec_block_id

Table name: stg_process_spec_block_id		Product: PDV	
Designation: Staging table for process specification changes (processing mode: BLOCK)		Description: This table contains the staging data of process specification changes.	
		* Note This table is contains data of the staging mode "BLOCK". This mode is used, when process specification changes are transfered via webservice without direct distribution.	
		* Keys id (technical key) change_time, workplace_name, process_param_name, data_supplier_name (business key)	
Column name	Column designation	Type	Description
change_time	Specification change time	timestamp(3)	
data_supplier_name	Data supplier name	nvarchar2(50)	
id	Technical ID	bigserial	
lower_plausibility_change	Change lower plausibility limit?	number(37)	0 = dont change 1 = change
lower_plausibility_limit	Lower plausibility limit	float	
lower_process_action_change	Change lower process action limit?	number(37)	0 = dont change 1 = change
lower_process_action_limit	Lower plausibility limit	float	
lower_tolerance_change	Change lower tolerance limit?	number(37)	0 = dont change 1 = change
lower_tolerance_limit	Lower tolerance limit	float	
process_param_name	Process parameter name	nvarchar2(100)	
target_change	Change target value?	number(37)	0 = dont change 1 = change
target_value	Target value	float	
unit_name	Unit name	nvarchar2(50)	
upper_plausibility_change	Change upper plausibility limit?	number(37)	0 = dont change 1 = change
upper_plausibility_limit	Upper plausibility limit	float	
upper_process_action_change	Change upper process action limit?	number(37)	0 = dont change 1 = change
upper_process_action_limit	Upper process action limit	float	
upper_tolerance_change	Change upper tolerance limit?	number(37)	0 = dont change 1 = change
upper_tolerance_limit	Upper tolerance limit	float	
workplace_name	Workplace name	nvarchar2(50)	

10.27. stg_process_spec_block_id_ps

Table name: stg_process_spec_block_id_ps		Product: PDV	
Designation: Logtable for incorrect distribution of process specification changes (processing mode: BLOCK)		Description: This table contains the logs for incorret distribution porcessings of table stg_process_spec_block_id. * Note This table is is used for the staging mode "BLOCK". This mode is used, when process specifiaction changes are transfered via webservice without direct distribution. * Keys stg_data_id_to, stg_data_id_from (techical key)	
Column name	Column designation	Type	Description
processing_status	Processing status of distribution	number(37)	
stg_data_id_from	Processing range - from ID	bigint	
stg_data_id_to	Processing range - to ID	bigint	

10.28. stg_process_spec_single_id

Table name: stg_process_spec_single_id		Product: PDV	
Designation: Staging table for process specification changes (processing mode: SINGLE)		Description: This table contains the staging data of process specifiaction changes.	
		* Note This table is contains data of the staging mode "SINGLE". This mode is used, when process specification changes are transfered via webservice with direct distribution.	
		* Keys id (technical key) change_time, workplace_name, process_param_name, data_supplier_name (business key)	
Column name	Column designation	Type	Description
change_time	Specification change time	timestamp(3)	
data_supplier_name	Data supplier name	nvarchar2(50)	
id	Technical ID	bigserial	
lower_plausibility_change	Change lower plausibility limit?	number(37)	0 = dont change 1 = change
lower_plausibility_limit	Lower plausibility limit	float	
lower_process_action_change	Change lower process action limit?	number(37)	0 = dont change 1 = change
lower_process_action_limit	Lower plausibility limit	float	
lower_tolerance_change	Change lower tolerance limit?	number(37)	0 = dont change 1 = change
lower_tolerance_limit	Lower tolerance limit	float	
process_param_name	Process parameter name	nvarchar2(100)	
processing_status	Processing status of distribution	number(37)	
target_change	Change target value?	number(37)	0 = dont change 1 = change
target_value	Target value	float	
unit_name	Unit name	nvarchar2(50)	
upper_plausibility_change	Change upper plausibility limit?	number(37)	0 = dont change 1 = change
upper_plausibility_limit	Upper plausibility limit	float	
upper_process_action_change	Change upper process action limit?	number(37)	0 = dont change 1 = change
upper_process_action_limit	Upper process action limit	float	
upper_tolerance_change	Change upper tolerance limit?	number(37)	0 = dont change 1 = change
upper_tolerance_limit	Upper tolerance limit	float	
workplace_name	Workplace name	nvarchar2(50)	

10.29. tnt_columns

Table name: tnt_columns		Product: PDV	
Designation: Column configuration of TNT-Framework		Description: Necessary table to configure all columns of a tnt table used to stored id or timebased data	
		* Notes Entrys can not be changed after system installation. No User-Interface or BAPI-Interface available for table. Table will only be chaneged during system installation!	
		* logical connection to other tables Contains column information of tnt table which header is definied in tnt_headers tht_columns.table_id = tnt_headers.table_id	
Column name	Column designation	Type	Description
anonym_object	Anonym Object	char(1)	Defines whether this column contains a anonym object or not. Anonym object can be used by consumer application to capture values without the need of configure corresponding objects in the consumer application. Supported Values are: Y: Yes N: No (default) For example the PDV consumer uses this field to capture PDV values without the need of configure a inspection plan (PDM field ID: Anonym Object)
col_caption	Column Caption	char(50)	Column Caption (PDM field ID: Column Caption)
col_content	Column Content	char(20)	Only necessary if col_type = D (default columns) Contains information which data is stored in the column (e.g. workplace, capture_ts, ...) This field values are depending on each application whcih is using TNT Framework. (PDM field ID: Column Content)
col_datatype	Column data type	char(10)	Defines which data type the coulmn should store. Supported values are: DECIMAL: floating point values INTEGER: integer values DATETIME: datetime values CHAR: text values (PDM field ID: Column data type)
col_field_type	Column field type	char(10)	Optionally parameter for defining Field-Type of values that are stored in the column (PDM field ID: Column field type)
col_format	Column Format	char(10)	Optionally defines the display representation of the stored values of this column. Supported values are: TEXT: text representation DATE: date representation TIME: time representation DATETIME: date and time representation DECIMAL: floating point representation HEX: hexadecimal representation OKT: octal representation BIN: binary representation (PDM field ID: Column Format)
col_length	Column Data Length	integer	Defines maximum data length of column data. Only necessary if col_datatype = CHAR (PDM field ID: Column Data Length)

col_name	Column name	char(18)	Name of the column. Will be used in any SQL Command. So must be unique for each table id. In use of time based tables the following name convention must be used: value_[datatype] So there are 4 possible values / entries: value_decimal, value_char, value_integer, value_datetime (PDM field ID: Column name)
col_pos	Column Position	integer	Position number of the column in the TNT Table. Must be unique for every table id and must be greater or equal value 0. IMPORTANT: The values must be numbered consecutively. (PDM field ID: Column Position)
col_type	Column Type	char(1)	Defines whether the column stores normal data (captured values) or stroes default data (e.g. workplace id). Supported Values are: N: normal column (default value) D: default column (PDM field ID: Column Type)
index_pos	Index Pos	integer	Optionally the position at which the configured column should be appear when defining an index for the table. If the entry is empty, the column will not appear in the index. IMPORTANT: If any value will be set in this field, all the values must be numbered consecutively. (PDM field ID: Index Pos)
is_capture_ts	Capture Timestamp	char(1)	Only for default columns necessary (col_typ = D) Defines whether this column stores the capture timestamp of the values Supported values are: Y: Yes N: No (default) (PDM field ID: Capture Timestamp)
is_object_id	Is Object Id	char(1)	Only for default columns necessary (col_typ = D) Defines whether this column stores the object id of the values Supported values are: Y: Yes N: No (default) (PDM field ID: Is Object Id)
is_reference_id	Is Reference Id	char(1)	Only for default columns necessary (col_typ = D) Defines whether this column stores the reference id of the values Supported values are: Y: Yes N: No (default) (PDM field ID: Is Reference Id)
key_field	Key Field	char(1)	Defines whether this column should be handled as key column or not. Consumer applications of the TNT Framework can use this configuration for filtering data in any analytic programmms. Supported values are: Y: key field N: no key filed (default value) (PDM field ID: Key Field)
object_id	Object Id	char(50)	Defines which object id will be stored in this column. For example this can be a processparameter when using PDV as consumer application. The type of the object id is stored in the <code>tnt_headers.object_type</code> column (PDM field ID: Object Id)
passes_id	Passes Id	char(1)	Configuration whether this column contains the passes number or not. Supported values are: Y: Yes N: No (default) (PDM field ID: Passes Id)

reference_id	Reference Id	char(50)	Reference id which informs the consumers which data is stored in this column. For example this can be a machine number when using PDV as consumer application. The type of the reference id is stored in the <code>tnt_headers.reference_type</code> column (PDM field ID: Reference Id)
relation	Relation	char(50)	Optionally relations to the system Objects can be defined in this field. This field can only be filled for normal columns (<code>col_type = N</code>). For example you can assign values like CNR or AGNR. The responsibility for processing this value is up to the consumer application. (PDM field ID: HYDRA Relation)
table_id	Table-Id	char(6)	System unique Table-Id (PDM field ID: Table-Id)
tag_id	Tag Id	char(1)	Defines whether this column contains the TNT Tag id. Only one column of any table id can be set as tag id. Supported values are: Y: Yes, column contains tag id N: No (default value) (PDM field ID: Tag Id)
user_c_29		char(1)	User-specific field
user_c_30		char(1)	User-specific field
user_c_31		char(1)	User-specific field
user_c_32		char(1)	User-specific field
user_c_33		char(1)	User-specific field
user_c_34		char(1)	User-specific field
user_c_35		char(1)	User-specific field
user_c_36		char(1)	User-specific field
user_c_37		char(1)	User-specific field
user_c_38		char(1)	User-specific field
user_c_39		char(1)	User-specific field
user_c_40		char(1)	User-specific field
user_c_41		char(1)	User-specific field
user_c_42		char(1)	User-specific field
user_c_43		char(1)	User-specific field
user_c_44		char(1)	User-specific field
user_c_45		char(10)	User-specific field
user_c_46		char(10)	User-specific field
user_c_47		char(10)	User-specific field
user_c_48		char(10)	User-specific field
user_c_49		char(10)	User-specific field
user_c_50		char(10)	User-specific field
user_c_51		char(20)	User-specific field
user_c_52		char(20)	User-specific field
user_c_53		char(20)	User-specific field
user_c_54		char(20)	User-specific field
user_c_55		char(20)	User-specific field
user_c_56		char(20)	User-specific field
user_c_57		char(20)	User-specific field
user_c_58		char(20)	User-specific field
user_c_59		char(20)	User-specific field
user_c_60		char(20)	User-specific field

user_c_61		char(20)	User-specific field
user_c_62		char(20)	User-specific field
user_c_63		char(20)	User-specific field
user_c_64		char(20)	User-specific field
user_c_65		char(40)	User-specific field
user_c_66		char(40)	User-specific field
user_code		char(8)	---
user_d_01		date	User-specific field
user_d_02		date	User-specific field
user_d_03		date	User-specific field
user_d_04		date	User-specific field
user_d_05		date	User-specific field
user_d_06		date	User-specific field
user_f_23		decimal(18,6)	User-specific field
user_f_24		decimal(18,6)	User-specific field
user_f_25		decimal(18,6)	User-specific field
user_f_26		decimal(18,6)	User-specific field
user_f_27		decimal(18,6)	User-specific field
user_f_28		decimal(18,6)	User-specific field
user_n_07		integer	User-specific field
user_n_08		integer	User-specific field
user_n_09		integer	User-specific field
user_n_10		integer	User-specific field
user_n_11		integer	User-specific field
user_n_12		integer	User-specific field
user_n_13		integer	User-specific field
user_n_14		integer	User-specific field
user_n_15		integer	User-specific field
user_n_16		integer	User-specific field
user_n_17		integer	User-specific field
user_n_18		integer	User-specific field
user_n_19		integer	User-specific field
user_n_20		integer	User-specific field
user_n_21		integer	User-specific field
user_n_22		integer	User-specific field

10.30. tnt_headers

Table name: tnt_headers		Product: PDV	
Designation: Table configuration of TNT-Framework		Description: Provides functionality to configure table wide data, containing global informations like table type, or which object types will be stored in this table. * Keys Table Id must be unique: unique index ixu_table_id on tnt_headers (table_id) * logical connection to other tables tnt_headers.table_id = tnt_columns.table_id (Reference to containing columns) tnt_headers.table_id = tnt_table_repo.table_id (Reference to physical table management)	
Column name	Column designation	Type	Description
capture_type	Capture Type	char(4)	Defines for which type to store data the current table should be configured. The supported values are: ID: id based data organisation, relational storing in horizontal direction TIME: time based data organisation, relational storing in vertical direction (default) (PDM field ID: Capture Type)
dbgroupname	DB Groupname	char(20)	Provides possibility for consumer applications to define to which database groupname the table should belong to, if they should be generated dynamically (PDM field ID: DB Groupname)
def_idx_template	Default Index Template	char(1000)	Provides template functionality for consumer applications. Consumer application can insert a SQL Template written in SQL dialect for a second index statement the current table should use. There are the following place marker that can be used to replace for example tablename or index name: %TABLENAME%: replace actual tablename %INDEXNAME%: replace actual indexname (PDM field ID: Default Index Template)
file_struc_time	File structure time	char(1)	This field offers configuration possibilities for time structured table storage. If consumer application stores data in time structured tables, they can also assign a time unit, by which the data should be exported. Supported values are: N: No time structured table storage needed (default) H: Hour - Exported files will be structured hourly D: Day - Exported files will be structured daily W: Week - Exported files will be structured weekly M: Month - Exported files will be structured monthly Y: Year - Exported files will be structured yearly Note: file_structure_time can't contain a time unit with higher time range than the field tab_struc_time. Otherwise the values will automatically be set as the same value than tab_struc_time (PDM field ID: File structure time)
idx_template	Index Template	char(1000)	Provides template functionality for consumer applications. Consumer application can insert a SQL Template written in SQL dialect for the index statement the current table should use. There are the following place marker that can be used to replace for example tablename or index name: %TABLENAME%: replace actual tablename %INDEXNAME%: replace actual indexname (PDM field ID: Index Template)
indexspace	Index Tablespace	char(40)	Provides possibility for consumer applications to define which table space should be used for indices when tables should be created dynamically (PDM field ID: Index Tablespace)
object_type	Object Type	char(20)	Object type defines which type of objectes current configured table will store. It defines which object type the column tnt_columns.object_id will store. (PDM field ID: Object Type)

reference_type	Reference Type	char(20)	Object type defines which type of references the objects of the current configured table will store. It defines which reference type the column tnt_columns.reference_id will store. (PDM field ID: Reference Type)
released	Released	char(1)	Defines whether the current table configuration is completed and valid, so current system can use the configuration to store and select data. Note: After releasing a table configuration, no more changes of the table configuration are allowed. Supported values are: Y: Table configuration released and ready to be used N: Table configuration not released yet (default) (PDM field ID: Released)
tab_group	Table group	char(10)	Text field to group structural identical table configurations. This field can be used by TNT-Frameworks kernel function to optimize data selection algorithm (PDM field ID: Table group)
tab_struc_time	Table structure time	char(1)	This field offers configuration possibilities for time structured table storage. If consumer application stores data in time structured tables, they can also assign a time unit, by which the data should be exported. Supported values are: N: No time structured table storage needed (default) H: Hour - Tables will be structured hourly D: Day - Tables will be structured daily W: Week - Tables will be structured weekly M: Month - Tables will be structured monthly Y: Year - Tables will be structured yearly (PDM field ID: Table structure time)
table_id	Table Ident	char(6)	Unique identification for tnt based stored data. (PDM field ID: Table Ident)
table_template	Table Template	char(4000)	Provides template functionality for consumer applications. Consumer application can insert a SQL Template written in SQL dialect for the table structures the current table consists of. There are the following place marker that can be used to replace for example tablename or index name: %TABLENAME%: replace actual tablename %INDEXNAME%: replace actual indexname Note: Stores up to 4000 characters. If template length is higher then 4000 the add-on fields (table_template_x) can be used when splitting the template statement (PDM field ID: Table Template)
table_template_1	Table Template (1)	char(4000)	Template add-on column for column table_template if text-length of statement template exceeds 4000 characters (PDM field ID: Table Template (1))
table_template_2	Table Template (2)	char(4000)	Template add-on column for column table_template_1 if text-length of statement template exceeds 4000 characters (PDM field ID: Table Template (2))
table_template_3	Table Template (3)	char(4000)	Template add-on column for column table_template_2 if text-length of statement template exceeds 4000 characters (PDM field ID: Table Template (3))
table_template_4	Table Template (4)	char(4000)	Template add-on column for column table_template_3 if text-length of statement template exceeds 4000 characters (PDM field ID: Table Template (4))
table_template_5	Table Template (5)	char(4000)	Template add-on column for column table_template_4 if text-length of statement template exceeds 4000 characters (PDM field ID: Table Template (5))
table_template_6	Table Template (6)	char(4000)	Template add-on column for column table_template_5 if text-length of statement template exceeds 4000 characters (PDM field ID: Table Template (6))
table_template_7	Table Template (7)	char(4000)	Template add-on column for column table_template_6 if text-length of statement template exceeds 4000 characters (PDM field ID: Table Template (7))
tablespace	Tablespace	char(40)	Provides possibility for consumer applications to define which table space should be used, when tables should be created dynamically (PDM field ID: Tablespace)
user_c_29		char(1)	User-specific field
user_c_30		char(1)	User-specific field
user_c_31		char(1)	User-specific field
user_c_32		char(1)	User-specific field

user_c_33		char(1)	User-specific field
user_c_34		char(1)	User-specific field
user_c_35		char(1)	User-specific field
user_c_36		char(1)	User-specific field
user_c_37		char(1)	User-specific field
user_c_38		char(1)	User-specific field
user_c_39		char(1)	User-specific field
user_c_40		char(1)	User-specific field
user_c_41		char(1)	User-specific field
user_c_42		char(1)	User-specific field
user_c_43		char(1)	User-specific field
user_c_44		char(1)	User-specific field
user_c_45		char(10)	User-specific field
user_c_46		char(10)	User-specific field
user_c_47		char(10)	User-specific field
user_c_48		char(10)	User-specific field
user_c_49		char(10)	User-specific field
user_c_50		char(10)	User-specific field
user_c_51		char(20)	User-specific field
user_c_52		char(20)	User-specific field
user_c_53		char(20)	User-specific field
user_c_54		char(20)	User-specific field
user_c_55		char(20)	User-specific field
user_c_56		char(20)	User-specific field
user_c_57		char(20)	User-specific field
user_c_58		char(20)	User-specific field
user_c_59		char(20)	User-specific field
user_c_60		char(20)	User-specific field
user_c_61		char(20)	User-specific field
user_c_62		char(20)	User-specific field
user_c_63		char(20)	User-specific field
user_c_64		char(20)	User-specific field
user_c_65		char(40)	User-specific field
user_c_66		char(40)	User-specific field
user_code		char(8)	---
user_d_01		date	User-specific field
user_d_02		date	User-specific field
user_d_03		date	User-specific field
user_d_04		date	User-specific field
user_d_05		date	User-specific field
user_d_06		date	User-specific field
user_f_23		decimal(18,6)	User-specific field
user_f_24		decimal(18,6)	User-specific field
user_f_25		decimal(18,6)	User-specific field
user_f_26		decimal(18,6)	User-specific field
user_f_27		decimal(18,6)	User-specific field

user_f_28		decimal(18,6)	User-specific field
user_n_07		integer	User-specific field
user_n_08		integer	User-specific field
user_n_09		integer	User-specific field
user_n_10		integer	User-specific field
user_n_11		integer	User-specific field
user_n_12		integer	User-specific field
user_n_13		integer	User-specific field
user_n_14		integer	User-specific field
user_n_15		integer	User-specific field
user_n_16		integer	User-specific field
user_n_17		integer	User-specific field
user_n_18		integer	User-specific field
user_n_19		integer	User-specific field
user_n_20		integer	User-specific field
user_n_21		integer	User-specific field
user_n_22		integer	User-specific field
valid_from	- for future use -	datetime	- for future use - (PDM field ID: - for future use -)
valid_to	- for future use -	datetime	- for future use - (PDM field ID: - for future use -)
version	- for future use -	integer	- for future use - (PDM field ID: - for future use -)

Table name: tnt_table_repo		Product: PDV	
Designation: TNT Table Repository		Description: TNT Table Repository stores any tables managed by TNT Framework. It offers the ability to select the physical table name to a specific TNT table id for a defined time range. It also contains table status information like how many records currently stored or if table data is already exported into data file. Which this repository table the TNT Framework receives the ability to determine the table names for a time range. * Notes Some information are necessary for TNT Framework and some information are necessary for TNT's consumer application * Keys unique keys: capture_ts_start, capture_ts_end, table_id * logical connection to other tables The table_id field is linked to tnt_headers.table_id, where the master data is configured. Field arc_path is linked to hy_path.path	
Column name	Column designation	Type	Description
arc_path	Export Path	char(8)	Reference to Path configuration (tnt_table_repo.arc_path = hy_path.path), containing information about the directory to the exported data file. TNT Importer uses this information together with the field exportfile to find necessary export data file if a data import was requested. (PDM field ID: Export Path)
capture_ts_end	Capture Timestamp End	datetime	Contains timestamp of first possibly last record of the stored table (tnt_table_repo.tablename) Note: This date mustn't be the date of the last record, its only the first possibly timestamp value Note: If there isn't any time splitted table holding used by TNT consumer application, the value '12/31/9999 23:59:59' should be insert here (PDM field ID: Capture Timestamp End)
capture_ts_start	Capture Timestamp Start	datetime	Contains timestamp of first possibly occurred record of the stored table (tnt_table_repo.tablename) Note: This date mustn't be the date of the first record, its only the first possibly timestamp value Note: If there isn't any time splitted table holding used by TNT consumer application, the value of installation date should be insert here (PDM field ID: Capture Timestamp Start)
count_rec	Record Count	integer	Current record count of the stored table. Consumer Application is responsible for updating this value and TNT Framework will just read the information. (PDM field ID: Record Count)
exportfile	Export File	char(256)	Contains name of the exportfile if table data is exported. (no path information, only filename is stored in this field) (PDM field ID: Export File)
is_online	Online Status	char(1)	Information if current table data is online or if the data is already exported. Suppoerted values: Y: table data is online N: data of table currently not in database / not online (PDM field ID: Online Status)
reload_duration	Reload Duration	integer	Expected reload duration of the stored table. Consumer Application is responsible for updating this value and TNT Framework will just read the information. (PDM field ID: Reload Duration)
schemafile	- for future use -	char(256)	- for future use - (PDM field ID: - for future use -)

table_id	Table Id	char(6)	TNT Table Id. Linked to tnt_headers.table_id (PDM field ID: Table Id)
tablename	Tablename	char(256)	Physical tablename of the current stored entry to the defines table_id. Consumer Application is responsible for updating this value and TNT Framework will just read the information. (PDM field ID: Tablename)
version	- for future use -	integer	- for future use - (PDM field ID: - for future use -)

11. PEP

11.1. pep_masch_belegung

Table name: pep_masch_belegung		Product: PEP	
Designation: Machine scheduling		Description: Machine scheduling	
Column name	Column designation	Type	Description
anlage		char(10)	
anlage_date		date	
anlage_time		integer	
auftrag_nr		char(40)	
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
belegung	Assignment	integer	Assignment of personnel capacity in percent (PDM field ID: PNRMNR.BEL:IST)
endedatum	to	date	End date of machine scheduling (PDM field ID: PNRMNR.DATE)
endezeit	To	integer	End time of machine scheduling (PDM field ID: PNRMNR..ZEIE)
firma		char(4)	Company to personnel number (PDM field ID: PNRMNR.FIR)
fixiert	Fixed	char(1)	Determines whether machine scheduling is fixed (PDM field ID: PNRMNR.FIX)
maschine		char(20)	Workplace/machine (PDM field ID: PNRMNR.MNR)
person		integer	Personnel number (PDM field ID: PNRMNR.PNR)
qual_id		integer	
sim_nr		smallint	Number of simulation (PDM field ID: PNRMNR.SIMNR)
sim_usr		integer	Console number for simulation (PDM field ID: PNRMNR.SIMKONS)
startdatum	Date from	date	Start date of machine scheduling (PDM field ID: PNRMNR.DATB)
startzeit	Time	integer	Start time of machine scheduling (PDM field ID: PNRMNR.ZEIB)
verweis	Reference	serial	

11.2. pep_qual_maschine

Table name: pep_qual_maschine		Product: PEP	
Designation: Machine qualifications		Description: Assignment of qualities to machines	
Column name	Column designation	Type	Description
abruesten		char(1)	
anlage		char(10)	
anlage_date		date	
anlage_time		integer	
autom	Assign automatically	char(1)	Not used (PDM field ID: QUALMNR.OPT:AUTO)
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
bedarf		integer	PEP: Workforce requirements of machines for the module PEP. (PDM field ID: QUALMNR.BEL:SOLL)
bedarf_abruesten		integer	
bedarf_ruesten		integer	
datum_bis	Valid until	date	Valdidity period for the assignment (end date) (PDM field ID: QUALMNR.DATE)
datum_von	Valid from	date	Validity period for the assignment (start date) (PDM field ID: QUALMNR.DATB)
fertigen		char(1)	
maschine	Workplace	char(20)	Workplace/machine (PDM field ID: QUALMNR.MNR)
qual_id	Qualification	integer	Qualification (PDM field ID: QUALMNR.QUAL)
ruesten		char(1)	
schichtnr	Shift	smallint	
verweis	Reference	serial	

11.3. pep_qual_person

Table name: pep_qual_person		Product: PEP	
Designation: Persons' qualifications		Description: Assignment of qualities to persons	
Column name	Column designation	Type	Description
anlage		char(10)	
anlage_date		date	
anlage_time		integer	
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
bemerkung_1	Comment	char(40)	(PDM field ID: QUALPNR.BEM:1)
bemerkung_2	Comment	char(40)	(PDM field ID: QUALPNR.BEM:2)
bemerkung_3	Comment	char(40)	(PDM field ID: QUALPNR.BEM:3)
bewertung	Evaluation	char(20)	The qualification can be assessed in this field. The field is only available if the user has a special authorization. (PDM field ID: QUALPNR.BEWERTUNG)
dateiname	File	char(256)	A file can be stored for each entry. This field shows the unique file name under which the file has been stored on the server. (PDM field ID: QUALPNR.DATEI)
datum_bis	Valid until	date	Validity period for the assignment (end date) (PDM field ID: QUALPNR.DATE)
datum_von	Valid from	date	Validity period for the assignment (start date) (PDM field ID: QUALPNR.DATB)
firma		char(4)	Company to personnel number
masch_nr		char(20)	
mgruppe		char(20)	
person	Person	integer	Personnel number (PDM field ID: QUALPNR.PNR)
qual_id	Qualification	integer	Qualification (PDM field ID: QUALPNR.QUAL)
rangfolge	Ranking order	integer	Ranking of qualification for the automatic assignment (PDM field ID: QUALPNR.POS)
verweis	Reference	serial	
weiterbildung_erfolgt	Advanced training done	char(1)	This field documents whether or not the advanced training has been carried out. (PDM field ID: QUALPNR.WEITERB:ERFOLGT)
weiterbildung_geplant_am	Advanced training planned	date	Date on which an advanced training is planned for this qualification (PDM field ID: QUALPNR.WEITERB:DAT)
weiterbildung_geplant_um	Advanced training planned	integer	Start time on which an advanced training is planned for this qualification (PDM field ID: QUALPNR.WEITERB:ZEI)

11.4. pep_qualifikation

Table name: pep_qualifikation		Product: PEP	
Designation: PEP qualifications		Description: Qualification master	
Column name	Column designation	Type	Description
anlage		char(10)	
anlage_date		date	
anlage_time		integer	
auto_zuord	Assign automatically	char(1)	This option determines if the qualification is considered in the automatic planning.
bearb		char(10)	last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bezeichnung	Designation	char(40)	Designation of qualification (PDM field ID: QUAL.BEZ)
farbe		smallint	Outdated. Now field rgbcolor is used!
gueltigkeit	Validity period	integer	Indicates how long the qualification will be valid (in days). If a value is entered in this field, the validity period will be assigned automatically starting from the current day until the end of the specified validity period, when an assignment is created for this qualification. (PDM field ID: QUAL.GUELTIGKEIT)
gueltigkeit_max	Max. validity period	integer	Maximum validity of the qualification in days that is checked, when an assignment is created or edited. If the validity start date is not indicated it will automatically be set to "Today". If the validity end date is not entered, it will automatically be set to the validity start date + maximum validity period. If both fields are assigned values and the maximum validity period is exceeded, editing of a qualification will be cancelled by issuing the error message "maximum validity period exceeded". (PDM field ID: QUAL.GUELTIGKEIT:MAX)
kategorie	Category	char(8)	Category which this qualification belongs to. The category controls the authorizations for viewing and editing qualifications within the application staff qualifications. (PDM field ID: QUAL.KAT)
pep_relevant	Relevant to workforce requirements plann	char(1)	This field specifies whether or not the qualification is to be displayed and processed in workforce requirements planning. (PDM field ID: QUAL.OPT:PEP)
qual_id	Qualification	integer	Qualification (PDM field ID: QUAL.QUAL)
rgbcolor	Color	integer	Color with which the qualification is to be displayed in personnel assignment. This field can only be accessed if the additional function Advanced selection and visualization is present. (PDM field ID: QUAL.RGBCOLOR)
sortierung	Order	smallint	The order in which several qualifications for a workplace are displayed in the workplace assignment can be set. (PDM field ID: QUAL.SORT)
verantw_bereich	Responsibility Area	char(15)	Responsibility area (PDM field ID: QUAL.VAB)

12. PZE

12.1. antritt

Table name: antritt		Product: PZE	
Designation: Presence premium regulation		Description: When it comes to processing of the presence premium an additional wage type (presence wage type) can be posted. Having processed the presence premium regulation all postings of the source wage type are deleted on the day of evaluation and are not available any longer.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausrichtung	Alignment	char(1)	In this field it is determined whether the presence wage type is generated before or after the selected point in time. (PDM field ID: ANTRITT.AUSR)
bearb		char(10)	Last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezug	Personnel selection key	char(20)	
bezug_dauer	Reference	char(1)	
bezug_prozent	Percentage	smallint	
certify_flag	Authorization required	char(1)	Determines whether the presence premium posting has to be approved. (PDM field ID: ANTRITT.CERTIFY)
datum_bis	Valid until	date	Date as of which the rule applies. (PDM field ID: ANTRITT.DATE)
datum_von	Valid from	date	Date as of which the rule applies. (PDM field ID: ANTRITT.DATB)
firma		char(4)	Possible restriction of presence premium regulation to a company (for future use). (PDM field ID: ANTRITT.FIR)
loeschen	Delete	char(1)	Definition whether initial wage type (source wage type) is to be deleted after posting the presene wage type. (PDM field ID: ANTRITT.DEL)
lohnart	Wage type	char(4)	Posted wage type from wage type booking (source wage type). (PDM field ID: ANTRITT.LART)
personalnummer	Personnel number	integer	
prioritaet		smallint	
summe	Duration	integer	For future use (5.7.5). (PDM field ID: ANTRITT.DAUER)
verweis		serial	---
wert	Personnel selection value	char(20)	
zeitpunkt	Point in time	char(1)	The following points in time are processed: - M: midnight - A: first occurrence of initial wage type - E: last end time of initial wage type (PDM field ID: ANTRITT.OPT:ZEI)
zuschlag	Duration	integer	Time in seconds that is posted to presence wage type. (PDM field ID: ANTRITT.ZUSCHL)
zuschlag_la	Wage type	char(4)	Bonus or presence wage type (target wage type). (PDM field ID: ANTRITT.LART:ZUSCHL)

12.2. arbeitsmittel

Table name: arbeitsmittel		Product: PZE	
Designation: Work equipment management		Description: Work equipment management	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausgabe_bearb	Handed out by	char(10)	The user name of the person handing out the equipment
ausgabe_date	Handed out on	date	
ausgabe_time	Handed out on	integer	
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung_1	Comment	char(40)	
bemerkung_2	Comment	char(40)	
bemerkung_3	Comment	char(40)	
bezeichnung	Designation	char(40)	Description of the work equipment
datei	File	char(256)	A file can be stored for each entry. This field shows the unique file name under which the file has been stored on the server.
groesse	Size	char(10)	Size, e.g. size or shoe size
hersteller	Manufacturer	char(40)	Manufacturer of the work equipment
inventar_nr	Inventory number	char(40)	Inventory number of the work equipment
kategorie	Category	char(8)	Assigns the entry to a category. Authorizations for accessing work equipment can be controlled by categories
lagerort	Storage location	char(40)	Storage location of the work equipment, provided it is not lent out at the moment
lieferant	Supplier	char(40)	Supplier of the work equipment
modell	Model	char(40)	Model of the work equipment
personalnummer	Personnel number	integer	The person's personnel number
rueckgabe_bearb	Received by	char(10)	User name of the person receiving/accepting the equipment.
rueckgabe_date	Returned on	date	
rueckgabe_time	Returned on	integer	
serien_nr	Serial number	char(40)	Serial number of the work equipment
verweis		serial	Unique ID

12.3. fehlgr_berecht

Table name: fehlgr_berecht		Product: PZE	
Designation: Authorization for absence reason		Description: The authorizations of persons or person groups for posting absence reasons on PZE terminals can be configured by means of this table.	
		Warning: This table is not processed any more since PZW/PZE version 8.1. Maybe it will be reused in a future version.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich		char(8)	Validity period of absence reason authorization. (PDM field ID: FGRBERECHT.BER)
datum_bis		date	Validity period (PDM field ID: FGRBERECHT.DATE)
datum_von		date	Validity period (PDM field ID: FGRBERECHT.DATB)
ereignis		char(4)	Absence reason for which the authorization applies. (PDM field ID: FGRBERECHT.FGR)
firma	Company	char(4)	Validity period of absence reason authorization. (PDM field ID: FGRBERECHT.FIR)
konfig		char(10)	In case of SAP subsystem only used for internal administration.
kostenstelle		char(10)	Validity period of absence reason authorization. (PDM field ID: FGRBERECHT.KST)
personalnummer	Personnel number	integer	Validity period of absence reason authorization. (PDM field ID: FGRBERECHT.PNR)
verweis		serial	Unique number to access the data record. (PDM field ID: FGRBERECHT.VERWEIS)

12.4. fehlgruende

Table name: fehlgruende		Product: PZE	
Designation: Advance clockings / Subsequent clockings		Description: Advance and subsequent clockings reported on the terminal. # Special remarks - # Key Logical: personalnummer, stempeldatum, stempelzeit_std, stempelzeit_sec, ereignis Technical: verweis # Connections to other tables 1) personalnummer = personen.personalnummer and stempeldatum between person.gueltig_von and person.gueltig_bis 2) ereignis = st_attribut.ereignis + consider company of person	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausgewertet	Evaluated	char(1)	Already evaluated by work day evaluation (Yes=J/No=N).
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bedeutung	Clocking status	char(1)	Indication whether it is an advance or subsequent clocking (advance=V/subsequent=N).
ereignis	Absence reason	char(4)	
firma	Company	char(4)	Company of the person
personalnummer	Personnel number	integer	
rueckgemeldet	Confirmed	char(1)	Reserved for future use: If PZE is used as subsystem (e.g. for SAP) it is entered in this field whether the absence reason clocking has already been confirmed. Currently advance/subsequent clockings in SAP subsystems are processed via table stempelsaetze.
sommerwinterzeit	DST	char(1)	Indication whether clocking was made during daylight saving (S) or standard (W) time.
stempeldatum	Date	date	Day of posting.
stempelzeit_sec	Time (seconds)	smallint	Time of clocking. Seconds only are saved. Minutes result from (stempelzeit_sec_1 / 60)
stempelzeit_std	Time (hours)	smallint	Time of clocking (clock hours).
terminal	Terminal number	smallint	Number of the terminal on which the absence reason was entered.
verweis	Reference	serial	Internal unique number of the record.
verweis_stempel	Reference to clocking	integer	Reference to the generated clocking record.
weiterbuch	Post on	char(1)	See configuration of absence reasons.

12.5. fehlgrund_gruppe

Table name: fehlgrund_gruppe		Product: PZE	
Designation: HR-PDC time event type groups, absence r		Description: Table is used to store time event type groups and attendance/abbsence reasons of HR-PDC.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung		char(30)	
datum_bis		date	
datum_von		date	
ereignis		char(4)	
ereignis_bez		char(30)	
fehlgrund_gruppe		char(8)	
sap_source_sys		char(10)	

12.6. fehlzeiten

Table name: fehlzeiten		Product: PZE	
Designation: Absence planning		Description: Scheduling absences of individual employees. # Special remarks Absence planings can be planned for 1) Single persons by personalnummer and bezug=PNR and wert (personalnummer is redundant. It can be used to join numerical) 2) Companies by firma and bezug=<null> 3) Several other combinations of bezug/wert # Key verweis # Connections to other tables 1) To table personen by personalnummer and bezug/wert 2) To lohnarten_zuord by lohnstatustyp = lohnarten_zuord.typnummer 3) To pze_entlohnung by lohnstatustyp = pze_entlohnung.typnummer	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
antrag_date	Date	date	Date and time of filing the request.
antrag_time	Time	integer	Date and time of filing the request.
antrag_verweis	n.a.	integer	not used
antragbearb	Signing/rejecting user	char(10)	
antragbearb_date	Signing/rejecting date	date	
antragbearb_time	Signing/rejecting time	integer	
beantragt	Absence requested	char(1)	This field defines whether this absence planning is an applied absence planning request. J: Applied G: Signed/Confirmed A: Rejected N: Normal absence planning (no request)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich	Area	char(8)	Area for that the absence is planned. (PDM field ID: FZ.BER)
bezeichnung	Commentary	char(40)	Comment on the absence planning. This comment is visible to the person, e.g. in the absence planning in SMA. (PDM field ID: FZ.BEZL)
bezeichnung_intern	Internal comment	char(40)	The internal comment is not visible to the person
bezug	Personnel selection key	char(20)	
certify_flag	Authorization required	char(1)	Flag whether this absence time is subject to authorization. (PDM field ID: FZ.CERTIFY)
datum_bis	Valid until	date	End date of absence. (PDM field ID: FZ.DATE)
datum_von	Valid from	date	Start date of absence. (PDM field ID: FZ.DATB)

fehlzeit	Absence	integer	Indication of absence time in seconds. (PDM field ID: FZ.DAUER)
firma	Company	char(4)	Company that the absence is planned for. (PDM field ID: FZ.FIR)
geloescht	Deleted	char(1)	J: Data set ist deleted, N: Data set is active
kommentar	n.a.	char(3)	Not used any more (PDM field ID: FZ.BEZK)
kostenstelle	Cost center	char(10)	Cost center that the absence is planned for. (PDM field ID: FZ.KST)
lfd_nr	Obsolete: Weekday	smallint	Now see column "wochentage". Formerly: Weekday which the absence planning applies to: 7 =Every day, 0 =Sunday,1 = Monday, ... , 6 =Saturday. (PDM field ID: FZ.WTG)
lfz_erster_tag	Start date	date	In case of continued pay: This field contains the date when the illness occurred for the first time. (PDM field ID: FZ.LFZ:DATB)
lfz_vorige_dauer	Duration	smallint	In case of continued pay: Duration of the previous subsequent illnesses in days. (PDM field ID: FZ.LFZ:DAUER)
lfz_vorige_verweis	lfz_vorige_verweis	integer	In case of continued pay: Reference to subsequent absence plannings (verweis field in fehlzeiten table). (PDM field ID: FZ.LFZ:VERWEIS)
lohnstatustyp	Payment	smallint	Reference to the typnummer field in the lohnarten_zuord table. The entry determines the payment of the absence time. (PDM field ID: FZ.ENTLTMOD)
personalnummer	Personnel number	integer	Person for that absence is planned. (PDM field ID: FZ.PNR)
rueckgemeldet	Uploaded	char(1)	Indicator whether the absence has been uploaded. (Yes=J/No=N)
sim_geloescht	n.a.	char(10)	For future use
sim_nr	n.a.	smallint	For future use
sim_usr	n.a.	integer	For future use
teil_krank	Fill up target time to	smallint	Percentage up to which the target time is to be filled up with absence time. (PDM field ID: FZ.TLWABW)
verarbeitung	Duration	char(1)	'S': Allocate planned target working time. 'N': Allocate planned normal time. 'D': Allocate average working time from HR master. 'F': Allocate absence time from absence planning. (PDM field ID: FZ.VERB)
verweis	Reference	serial	Internal unique number of the record. (PDM field ID: FZ.VERWEIS)
wert	Personnel selection value	char(20)	
wochentage	Weekdays	char(7)	Weekdays for which the absence planning applies: (First character: Sunday J/N, , second character: Monday J/N, ... Saturday J/N).
zeit_bis	Time to	integer	
zeit_von	Time from	integer	

12.7. fehlzeiten_prio

Table name: fehlzeiten_prio		Product: PZE	
Designation: Control of absences		Description: Different settings for processing absences can be defined by means of this table. A public holiday planned on company level, for example, should take priority over a leave day planned for an employee.	
Column name	Column designation	Type	Description
aend_moeglich	Modification enabled	char(1)	Indication whether the specifications made here (except for the priority) can be overwritten in the absence time planning ('J' = Yes, 'N' = No). (PDM field ID: FZV.OPT:AEND)
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
autogenehmigt	Request needs to be approved	char(1)	Defines if this absence time is subject to authorization. J: absence is NOT subject to authorization N: absence is subject to authorization (PDM field ID: FZV.OPT:AUTOSIGN)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
certify_flag	Authorization required	char(1)	Approval required for absence with this payment (J/N).
datum_bis		date	Validity period for the configuration (not yet processed) (PDM field ID: FZV.DATE)
datum_von		date	Validity period for the configuration (not yet processed). (PDM field ID: FZV.DATB)
entlohnungstyp	Payment day type	smallint	Payment day type for which this configuration applies. (PDM field ID: FZV.ENTLTMOD)
farbe		smallint	Determines with what color the absence time is to be displayed (PDM field ID: FZV.COLOR)
fehlzeit	Absence	integer	Indication of absence time in seconds. (PDM field ID: FZV.DAUER)
fehlzeit_max	Maximum duration	integer	Not yet processed
fehlzeit_min	Minimum duration	integer	Not yet processed
geplant_abwesend	Display as planned absent	char(1)	
halber_urlaubstag	Allocate half a leave day	char(1)	
istzeit_verrechnen	Compensation	char(1)	
kategorie	Category	char(3)	Category of absences. At some entries this one affects the allocation.
kommentar	Full-day absence	char(3)	Commentary taken over into the absence planning and thus also into the absence overview. (PDM field ID: FZV.BEZK)
kommentar_teilabw	Partly absent	char(3)	
konfig		char(20)	The characters 5 to 9 contain a maximum absence time for partial absences (in seconds). (PDM field ID: FZV.LFZ:FRIST)
kontextmenue		char(1)	Position in the context menu where the absence is to be displayed (not yet processed). (PDM field ID: FZV.KTXTMENU)
lfz_entlohnungstyp	Subseq. payment of continued pay	smallint	Subsequent payment of continued pay
lfz_frist	Period of continued pay	smallint	Has not been processed yet in 7.1. As of the next version: period of continued pay.
lobu_fehlgrund	Absence reason	char(10)	
lobu_kennzeichen	Control indicator	char(10)	

nummer		integer	This field is currently not used. (PDM field ID: FZV.ENTLTMOD:LFZ)
prioritaet	Priority	smallint	Priority from 0 to 99. The higher the value the higher the priority. (PDM field ID: FZV.PRIO)
prozent	Percentage	smallint	The absence time is multiplied by this percentage. Thus, 80% continued pay can be achieved in the case of illness. (PDM field ID: FZV.PROZ)
rgbcolor	Color	integer	
rueckmelden	Upload to payroll accounting	char(1)	
sollzeit_fehlzeit	Set target time as absence time	char(1)	This button determines whether the target time is equated with the planned absence time (J/N). Consequently, neither overtime nor undertime are posted on days of this absence time (PDM field ID: FZV.OPT:SZFZ)
teil_krank		smallint	Indication of the percentage to fill up in case of partial absence. The entries 0 or empty represent absences taking the whole day. (PDM field ID: FZV.TLWABW)
trotz_anwesend	Generate complete absence despite attendance	char(1)	Determination whether the absence record is to be generated on the respective day although a clocking is available. (PDM field ID: FZV.OPT:TRANW)
typ_half_feiertag		smallint	
urlaubstag	Allocate leave day	char(1)	
verarbeitung	Duration	char(1)	Determination whether the planned target time, the planned normal time, the average working time from the HR master or the entered absence are to be posted. (PDM field ID: FZV.VERB)
weiterbuch	Post on	char(1)	
workflowanzeige	Absence may be requested	char(1)	Defines whether this absence payment day type is contained in the selection list for the absence planning within the web. (PDM field ID: FZV.OPT:WFDISPLAY)

12.8. gltzeitjhresmodell

Table name: gltzeitjhresmodell		Product: PZE	
Designation: Working time models		Description: Determination which working time day type is to be used on which day of the year.	
		# Key Technical: verweis	
		# Connections to other tables From tagestypen to gltzeittagestyp.typnummer, see column description column tagestypen	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
art	Type	char(1)	Type of the model: 'W': Week model 'Z': Period model 'J' or empty: year model (PDM field ID: GLZJMOD.ART)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bez_ausf	Designation	char(40)	Designation (PDM field ID: GLZJMOD.BEZL)
bez_kurz	Short designation	char(6)	Short designation (PDM field ID: GLZJMOD.BEZX)
gueltig_bis	Valid to	date	Validity period of the model. The end date is set automatically within the system. The start date can only be entered in the user interface.
gueltig_von	Valid from	date	Validity period of the model. (PDM field ID: GLZJMOD.DATB)
jahr	Year	smallint	The year in case of year models or 0 for models of weeks or periods (PDM field ID: GLZJMOD.JAHR)
modellnummer	Model	smallint	Number of year model of the working time (PDM field ID: GLZJMOD.GLZJMOD)
referenz_datum	Reference date	date	Reference date for period models. The defined period starts on the reference date and is repeated as frequently as required. (PDM field ID: DAT:REF)
tagestypen	Day types	char(1999)	Character string with 1464 characters. Year Models: Year models have 365 or 366 blocks of four characters. Each 4 characters represent one day in the year/week/period. The character string starts with a separator () for year models. For day type numbers from 1000 on the pipe is replaced by the first digit of the type number. Week models have 28 blocks of 5 characters (7 for normal days, 7 for public holidays, 7 for important public holidays and 7 for other days off). Each day type has four characters. The 5. character is a separator (). Period models have 1 to n blocks of five pipe seperated strings with dynamic width. The 5 pipe seperated values correspond to the definon of period models: 1) Number of days of the period element 2) Day type for normal days 3) Day type for public holidays 4) Day type for important public holidays 5) Day type for other days off (PDM field ID: GLZJMOD.MODELL)
verantw_bereich	Responsibility area	char(15)	 (PDM field ID: GLZJMOD.VAB)
verweis	Reference	serial	Internal unique number of the record

12.9. gltzeittagestyp

Table name: gltzeittagestyp		Product: PZE	
Designation: Working time day types / personal working time		Description: Definition of the planned working time on the basis of days. This table is also used to save personal working times. # Key Logical: 1) Working time day types: typnummer,datum_von,schicht_art. personalnummer=0 2) Personal working time: personalnummer,datum_von,schicht_art. typnummer=0, schichtart=<null> Technical: verweis # Connections to other tables personen	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
art	Type	char(1)	Type of working time day type: G: day type of flextime F: day type of flexible shift P: Personal working time
az_hoechst	Default maximum working time for this day.	integer	(PDM field ID: GLZTMOD.AZMAX)
az_kern_bis	End of core time.	integer	(PDM field ID: GLZTMOD.KERNE)
az_kern_von	Start of core time.	integer	(PDM field ID: GLZTMOD.KERNB)
az_mindest	Default target working time for this day.	integer	(PDM field ID: GLZTMOD.SZ)
az_normal_bis	End of normal time.	integer	(PDM field ID: GLZTMOD.NORME)
az_normal_von	Start of normal time.	integer	(PDM field ID: GLZTMOD.NORMB)
az_rahmen_bis	End of skeleton time.	integer	(PDM field ID: GLZTMOD.RAHME)
az_rahmen_von	Start of skeleton time.	integer	(PDM field ID: GLZTMOD.RAHMB)
basis_schicht_art	Shift type	char(1)	For personal working times: Shift type from which the current personal working time is derived.
basis_typnummer	Day type	smallint	For personal working times: Day type number from which the current personal working time is derived.
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereitschaft_1_bis	On-call duty 1: End	integer	
bereitschaft_1_von	On-call duty 1: Beginning	integer	
bereitschaft_2_bis	On-call duty 2: End	integer	
bereitschaft_2_von	On-call duty 2: Beginning	integer	

bez_ausf	Designation	char(40)	(PDM field ID: GLZTMOD.BEZL)
bez_kurz	Short designation	char(6)	(PDM field ID: GLZTMOD.BEZK)
datum_bis	Valid until	date	(PDM field ID: GLZTMOD.DATE)
datum_von	Valid from	date	(PDM field ID: GLZTMOD.DATB)
entlohnungstyp	n.a.	smallint	For future use (PDM field ID: GLZTMOD.ENTLTMOD)
freipause	Duration of an arbitrary break.	integer	(PDM field ID: GLZTMOD.PAUFREI)
lobu_kennzeichen	For future use	char(10)	
lobu_rueckmelden	For future use	char(1)	
lobu_typnummer	For future use	char(10)	
mehrarbeit_anfang	For future use	char(1)	For future use
p1_art	Type of break 1	char(1)	B: Paid break U or empty: Unpaid break (PDM field ID: GLZTMOD.PAUART:1)
p1_mindest	Minimum time of first break.	integer	(PDM field ID: GLZTMOD.PAUMIN:1)
p1_normal_bis	End of normal time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAUNORME:1)
p1_normal_von	Start of normal time of first break.	integer	(PDM field ID: GLZTMOD.PAUNORMB:1)
p1_rahmen_bis	End of skeleton time of first break.	integer	(PDM field ID: GLZTMOD.PAURAHME:1)
p1_rahmen_von	Start of skeleton time of first break.	integer	(PDM field ID: GLZTMOD.PAURAHMB:1)
p2_art	Type of break 2	char(1)	B: Paid break U or empty: Unpaid break (PDM field ID: GLZTMOD.PAUART:2)
p2_mindest	Minimum time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAUMIN:2)
p2_normal_bis	Ende der Normalzeit der ersten Pause.	integer	(PDM field ID: GLZTMOD.PAUNORME:2)
p2_normal_von	Start of normal time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAUNORMB:2)
p2_rahmen_bis	End of skeleton time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAURAHME:2)
p2_rahmen_von	Start of skeleton time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAURAHMB:2)
p3_art	Type of break 3	char(1)	B: Paid break U or empty: Unpaid break (PDM field ID: GLZTMOD.PAUART:3)
p3_mindest	Minimum time of the breaks1 to 3.	integer	(PDM field ID: GLZTMOD.PAUMIN:3)
p3_normal_bis	End of normal time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAUNORME:3)
p3_normal_von	Start of normal time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAUNORMB:3)

p3_rahmen_bis	End of skeleton time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAURAHME:3)
p3_rahmen_von	Start of skeleton time of the breaks 1 to 3.	integer	(PDM field ID: GLZTMOD.PAURAHMB:3)
p4_art	n.a.	char(1)	Not processed
personalnummer	Personnel number	integer	Only used for personal working times. Else 0.
ruhezeit	Rest period	integer	
schicht_art	Shift type for flexible shift models.	char(1)	(PDM field ID: GLZTMOD.SCHZART)
schicht_entlohnung	Payment day type	smallint	Payment day type that is to be allocated when this shift of the working time day type is in use. (PDM field ID: GLZTMOD.ENTLTMOD:SCHZART)
schicht_zuord_ab	For future use	integer	
sollzeit_anfang	Compensation of target time	char(1)	Reference point for starting the allocation of target times: A=Beginning of working time R=Start of skeleton time K=Start of core time N=Start of normal time (PDM field ID: GLZTMOD.OPT:SZB)
typnummer	Day type	smallint	Unique key of the day type. 0 for personal working time. (PDM field ID: GLZTMOD.GLZTMOD)
verantw_bereich	Responsibility area	char(15)	
verweis	Reference	serial	
vorholzeit	For future use	integer	For future use

12.10. hymeld

Table name: hymeld		Product: PZE	
Designation: Message listings		Description: The messages of PZE evaluations are filed with message texts in this table.	
		# Key Logical: personalnummer,datum,melde_nr Technical: verweis	
		# Connections to other tables melde_nr = meldungen.melde_nr	
Column name	Column designation	Type	Description
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
d1	Date value	date	Date that is possibly contained in the message.
datum	Date	date	Date
firma	Company	char(4)	
geloescht	Deleted	char(1)	For future use
lohnart	Wage type	char(4)	For future use (for wage types requiring authorization)
melde_nr	Number of message text	integer	Number of the message text. Reference to meldungen.melde_nr. Numbers 900-949 are reserved for incentive wage.
melde_stufe	Confirmation level	char(1)	*': PZE system error 'c': Message for required approval. else: "Normal" message
melde_txt	Text of message	char(66)	This text is only for debugging reasons. The text shown in clients comes form table meldungen and is translatetd by client translation tools.
meldekennung	Not used	char(1)	
n1	Numeric value 1	integer	Numerical values that are possibly contained in the confirmation (for multilingual processing)
n2	Numeric value 2	integer	Numerical values that are possibly contained in the confirmation (for multilingual processing)
n3	Numeric value 3	integer	Numerical values that are possibly contained in the confirmation (for multilingual processing)
personalnummer	Personnel number	integer	
prg_kuerzel	Application	char(3)	Application that created the message. PWA: Labor time calculation / wage type booking PMA: Monthly evaluation PTG: Labor time calculation / evaluation of clockings PTg: Labor time calculation / evaluation of clockings LLB: Incentive wage calcualtion
t1	Text vaue 1	char(40)	Character string that is possibly contained in the message.
t2	Text vaue 2	char(20)	For future use
verweis	Reference	serial	Unique number.

Table name: jahranwes		Product: PZE	
Designation: An employee's annual presence		Description: Statistics about an employee's allocated presence times throughout the whole year.	
		# Key personalnummer, jahr	
		# Connections to other tables personen.personalnummer = personalnummer and <today> between personen.gueltig_von and personen.gueltig_bis	
Column name	Column designation	Type	Description
anwesbez	Presence times and shift types	char(1464)	String with 1464 characters. Each day has four characters. The first three characters contain the presence time in minutes in Hexadecimal notation. The fourth character contains the shift type or the separator ().
firma	Company	char(4)	Optional.
jahr	Year	smallint	
personalnummer	Personnel number	integer	
verweis	Reference	serial	Internal unique number of the record

Table name: jahrfehl		Product: PZE	
Designation: An employee's annual absence		Description: Statistics about an employee's allocated absence times throughout the whole year.	
		# Key personalnummer, jahr	
		# Connections to other tables personen.personalnummer = personalnummer and <today> between personen.gueltig_von and personen.gueltig_bis	
Column name	Column designation	Type	Description
fehlbez	Absence indicators	char(1464)	Character string with 1464 characters. Each day is considered with four characters. The first three characters refer to the bezeich1 field in the lohnarten_zuord table. They contain the first three characters of the designation of the first allocated payment day type. The fourth character is a separator (). The complete character string starts and ends with a separator.
firma	Company	char(4)	Optional
jahr	Year	smallint	
personalnummer	Personnel number	integer	Personnel number.
verweis	Reference	serial	Internal unique number of the record

12.13. kategorien

Table name: kategorien		Product: PZE	
Designation: Categories		Description: The "categories" application has been designed to manage categories for different applications. The categories advanced training, instructions, driver's license, inspection, etc., for example, may be defined for the qualifications. The categories are also used in the digital personnel file (e.g. application, appraisal, etc.) and the work equipment management. # Keys verweis (unique) kategorie (unique) # logical connection to other tables By column kategorie into tables arbeitsmittel, pep_qualifikation and personalakte.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
anwendung	Application	char(10)	Transaction code for the application in which the category is to be used.
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Designation	char(40)	Category name
kategorie	Category	char(8)	Alpha-numeric key for the category
verantw_bereich	Responsibility area ("category" group)	char(15)	The responsibility area which the category is assigned to. This responsibility area is checked when the category is edited but it does not affect using the category in other applications.
verantw_bereich_anw	Responsibility area ("Authorization chec	char(15)	The responsibility area entered here is checked if you want to show, create, change or delete a data record assigned to this category in another application. This authorization controls, for example, if a user in the digital personnel file is allowed to view, create, change or delete entries assigned to the "appraisal" category.
verweis		serial	Unique number of the record.

12.14. kontoaenderung

Table name: kontoaenderung		Product: PZE	
Designation: Manual account changes		Description: Manual account changes are saved in this table. Thus, it can be recognized when and who edited account balances on the console.	
Column name	Column designation	Type	Description
aenderungsdatum		date	Date of the account change (editing).
aenderungsursache		char(3)	Identification via which module the account was changed ("PAK" = manual account change).
aenderungszeit		integer	Time of the account change in seconds since the beginning of the day.
aw_datum		date	Date on which the account change was allocated.
bearbeiter		char(10)	User that changed the account.
bemerkung		char(40)	
firma	Company	char(4)	Company of the person editing
kontoaenderung		integer	Duration of the account change in seconds.
kontoart		smallint	Internal number to identify the account (please see pze_konten table).
kontostand		integer	Status of the account after the change.
lfd_kontoaenderung		integer	Currently not processed.
personalnummer	Personnel number	integer	Person edited
verr_datum		date	Currently not processed.
verweis		serial	

12.15. kontogrenze

Table name: kontogrenze		Product: PZE	
Designation: Limiting the flextime account		Description: Limiting the accounts of person and person groups at the end of the month. This is processed during the evaluation of months. Depending on which employee subgroup is to be affected by the limitation, one of the fields firma (company), bereich (area), kostenstelle (cost center) or personalnummer (personnel number) has to be filled out. The firma field can be assigned in all cases for a unique specification.	
Column name	Column designation	Type	Description
abteilung		char(8)	free
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung		char(40)	
bereich		char(8)	Area (field within the HR master) for which the entry applies. (PDM field ID: PZEKTOG.BER)
bezug	Personnel selection key	char(20)	
firma	Company	char(4)	Company (field within the HR master) for which the entry applies. (PDM field ID: PZEKTOG.FIR)
grenze_max	Limit value	integer	Upper limit value in seconds. (PDM field ID: PZEKTOG.KTOG:MAX)
grenze_min	Limit value	integer	Lower limit value in seconds. (PDM field ID: PZEKTOG.KTOG:MIN)
gueltig_bis	Valid until	date	
gueltig_von	Valid from	date	
jahr		smallint	Indication of the year for which the limitation should apply. (PDM field ID: PZEKTOG.JAHR)
kontoart		smallint	Internal number of the account. Please see "pze_konten" table. (PDM field ID: PZEKTOG.KTO)
kostenstelle		char(10)	Cost center (field within the HR master) for which the entry applies. (PDM field ID: PZEKTOG.KST)
lohnart_max		char(4)	Wage type onto which the time cut off above is posted (PDM field ID: PZEKTOG.LART:MAX)
lohnart_max_2		char(4)	For future use
lohnart_max_3		char(4)	For future use
lohnart_min		char(4)	Wage type onto which the time cut off below is posted. (PDM field ID: PZEKTOG.LART:MIN)
lohnart_min_2		char(4)	For future use
lohnart_min_3		char(4)	For future use
periode	Settlement period	smallint	Indication of the period which the limitation should apply for. (PDM field ID: PZEKTOG.PER)
personalnummer	Personnel number	integer	Personnel number to be limited. (PDM field ID: PZEKTOG.PNR)
prioritaet	Priority	smallint	
reihenfolge	Sorting	integer	Reserved.

summe_grenze_max		integer	In case of limited sums the upper limit of the sum. (PDM field ID: PZEKTOG.SUMG:MAX)
summe_grenze_min		integer	In case of limited sums the lower limit of the sum. (PDM field ID: PZEKTOG.SUMG.MIN)
summe_kontoart		smallint	In case of limited sums, the account that is to be referred to when it comes to totals formation (PDM field ID: PZEKTOG.KTO:SUM)
summe_lohnart_max		char(4)	Wage type onto which the time cut off above is posted. (PDM field ID: PZEKTOG.SUMLART:MAX)
summe_lohnart_min		char(4)	Wage type which the limited time is posted onto due to the lower limit of the sum. (PDM field ID: PZEKTOG.SUMLART:MIN)
summe_umr_faktor		integer	Conversion factor of daily accounts in hours in order to post them on to wage types. (PDM field ID: PZEKTOG.SUMUMRFAKT)
umrechnungs_faktor		integer	Conversion factor of daily accounts in hours in order to post them on wage types. (PDM field ID: PZEKTOG.UMRFAKT)
verarbeitung		char(1)	'B' or empty: It is an account limit 'K': It is a constant value that is to be allocated with the account. (PDM field ID: PZEKTOG.VERB)
verweis	Reference	serial	Unique record number. (PDM field ID: PZEKTOG.VERWEIS)
wert	Personnel selection value	char(20)	

12.16. kostenstellen

Table name: kostenstellen		Product: PZE	
Designation: Cost centers		Description: Contains the definition of cost centers (for PZE-KST only).	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
anzeigen		char(1)	- Determination whether the cost center is to be displayed within ,PZE' or ,BDE'. (Currently not used). (PDM field ID: KST.SPERR)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Designation	char(40)	Designation of the cost center. (PDM field ID: KST.BEZ)
firma	Company	char(4)	Designation of the company. (PDM field ID: KST.FIR)
gueltig_bis		date	It is possible to use the "KST.GUELTDATBIS" alias. (PDM field ID: KST.DATE (alias: KST.GUELTDATBIS))
gueltig_von		date	It is possible to use the "KST.GUELTDATVON" alias. (PDM field ID: KST.DATB (alias: KST.GUELTDATVON))
kostenstelle		char(10)	Key of the cost center. (PDM field ID: KST.KST)
kostenstellen_grp		char(15)	Field for transferring cost centers from SAP (HR-PDC).
lobu_kennzeichen	Control indicator	char(10)	
lobu_kostenstelle	Cost center	char(10)	
sap_logical_system		char(10)	Field for transferring cost centers from SAP (HR-PDC).
verantw_bereich		char(15)	
verweis		serial	

12.17. la_beziehung

Table name: la_beziehung		Product: PZE	
Designation: Wage type competition and additions		Description: In this table wage types can be defined competitively and in addition to each other. In case of competitive wage types only one of the two wage types can be posted at a time. If both wage types are posted at the same time the "weak" wage type is hidden by the "strong" one. In case of complementary wage types, the time that is posted with the two source wage types is, instead of that, posted with the target wage type.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Commentary	char(40)	Free designation of the configuration or commentary. (PDM field ID: LARTBEZI.BEZ)
bezug	Personnel selection key	char(20)	The relation of wage types is restricted to another sort criterion.
datum_bis	Valid until	date	Validity period for the relation of wage types.
datum_von	Valid from	date	Validity period for the relation of wage types.
dauer_bis	Duration until	integer	Minimum duration and maximum duration to delete wage types.
dauer_von	Duration from	integer	Minimum duration and maximum duration to delete wage types.
firma	Company	char(4)	The relation of wage types is restricted to one company.
kz_char		char(10)	kkz_char[1]: "N"= rule is not to be carried out daily but for the whole overtime period (in case of record type "U" only). kz_char[2]: "N"= rule is not be carried out prior to the allocation of accounts but thereafter.
kz_long		integer	Duration as of which transfer postings are to be performed (in case of record type "U" only).
la_quelle1	Initial wage type	char(4)	"Strong" wage type in case of competitions, one of the source wage types in case of additions. In case of deletions it is the wage type to be deleted. (PDM field ID: LARTBEZI.LART)
la_quelle2	Initial wage type 2	char(4)	"Weak" wage type for competitions, second source wage type for additions. (PDM field ID: LARTBEZI.LART:2)
la_ziel	Target wage type	char(4)	Target wage type in case of additions. In case of competitions this field has to be assigned to the same value as la_quelle1, in order that that the sequence is right. (PDM field ID: LARTBEZI.LART:Z)
reihenfolge	Order	integer	Order in that the rules are processed. (PDM field ID: LARTBEZI.SORT)
satzart	Processing	char(1)	'K': competition, 'E': addition, 'U': transfer posting, 'L': deletion, 'D' duplicating (PDM field ID: LARTBEZI.ART)
taeglich		char(1)	
verarbeiten_ab	Process from	integer	
verweis	Reference	serial	Unique key to access the data record.
wert	Personnel selection value	char(20)	Value of the sort criterion set in the bezug field.
zeitpunkt		char(1)	

12.18. lhnstatusjhrmod

Table name: lhnstatusjhrmod		Product: PZE	
Designation: Payment model		Description: Determination which payment day type is to be used on which day of the year.	
		# Key Technical: verweis	
		# Connections to other tables From tagestypen to lohnarten_zuord.typnummer, see column description column tagestypen	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
art	Type	char(1)	Definition whether it is a ‚J‘ year model, a ‚W‘ week model or a ‚Z‘ period model.
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bez_ausf	Designation	char(40)	Designation (PDM field ID: ENTLJMOD.BEZL)
bez_kurz	Short designation	char(6)	Designation (PDM field ID: ENTLJMOD.BEZK)
gueltig_bis	Valid to	date	Validity period of the model. The end date is set automatically within the system. The start date can only be entered in the user interface.
gueltig_von	Valid from	date	Validity period of the model.
jahr		smallint	The year in case of year models or 0 for models of weeks or periods (PDM field ID: ENTLJMOD.JAHR)
modellnummer	Model	smallint	Unique number of the entry within the year stated (PDM field ID: ENTLJMOD.ENTLJMOD)
referenz_datum	Reference date	date	Reference date for period models. The defined period starts on the reference date and is repeated as frequently as needed. (PDM field ID: ENTLJMOD.DAT:REF)
tagestypen	Day types	char(1999)	Character string with 1464 characters. Year Models: Year models have 365 or 366 blocks of four characters. Each 4 characters represent one day in the year/week/period. The character string starts with a separator () for year models. For day type numbers from 1000 on the pipe is replaced by the first digit of the type number. Week models have 28 blocks of 5 characters (7 for normal days, 7 for public holidays, 7 for important public holidays and 7 for other days off). Each day type has four characters. The 5. character is a separator (). Period models have 1 to n blocks of five pipe seperated strings with dynamic width. The 5 pipe seperated values correspond to the definon of period models: 1) Number of days of the period element 2) Day type for normal days 3) Day type for public holidays 4) Day type for important public holidays 5) Day type for other days off (PDM field ID: ENTLJMOD.MODELL)
verantw_bereich	Responsibility area	char(15)	
verweis	Reference	serial	Internal unique number of the record

12.19. Lohnarten

Table name: lohnarten		Product: PZE	
Designation: Wage types		Description: Definition of wage types	
		# Key lohnart	
Column name	Column designation	Type	Description
ade_abgleich	Use wage type for comparing with BDE	char(1)	(PDM field ID: LART.OPT:ADEABGL)
ade_loeschen	Delete wage type after comparing with BDE	char(1)	(PDM field ID: LART.OPT:ADEDEL)
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
anzeigen	For future use	char(1)	Currently not used.
auswahl_kz	Selection indicator	char(1)	Reserved field for customer-specific processing. (PDM field ID: LART.OPT:KST)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Designation	char(40)	Designation of the wage type (PDM field ID: LART.BEZL)
certify_flag	Authorization required	char(1)	Indication whether this wage type is subject to authorization. (PDM field ID: LART.CERTIFY)
durchschn_art	Average type	char(1)	T: wage type is uploaded in the "Days" field of some payroll interfaces. (PDM field ID: LART.AVGART)
grundlohn	Type	char(1)	Basic wage type or bonus wage type (G/Z/) (PDM field ID: LART.ART)
kurzbez	Short designation	char(6)	Short designation of the wage type. (PDM field ID: LART.BEZK)
lle_grp_zeit	Is personel time for premium groups	char(1)	Attendance time of this wage type is used as personel time for premium group calculations J: yes N: no (PDM field ID: LART.OPT:PZEITGRPR)
lle_kz	Incentive wage indicator	char(1)	Reserved for customer specific prosscung (PDM field ID: LART.OPT:LLE)
lle_menge	Controls determination of quantity	char(1)	Controls determination of quantity for wage calculation: S or empty: According to LLE-General settings L: According to the further settings "lle_menge_..." in this wage type (PDM field ID: LART.OPT:LLEMENGE)
lle_menge_a_b	Basic quantity	char(1)	Scrap (base quantity unit) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_A_B)
lle_menge_a_p	Primary quantity	char(1)	Scrap (primary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_A_P)
lle_menge_a_s	Secondary quantity	char(1)	Scrap (secondary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_A_S)
lle_menge_a_t	Tertiary quantity	char(1)	Scrap (tertiary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_A_T)

lle_menge_g_b	Basic quantity	char(1)	Yield (base quantity unit) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_G_B)
lle_menge_g_p	Primary quantity	char(1)	Yield (primary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_G_P)
lle_menge_g_s	Secondary quantity	char(1)	Yield (secondary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_G_S)
lle_menge_g_t	Tertiary quantity	char(1)	Yield (tertiary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_G_T)
lle_menge_n_b	Basic quantity	char(1)	Rework quantity (base quantity unit) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_N_B)
lle_menge_n_p	Primary quantity	char(1)	Rework quantity (primary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_N_P)
lle_menge_n_s	Secondary quantity	char(1)	Rework quantity (secondary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_N_S)
lle_menge_n_t	Tertiary quantity	char(1)	Rework quantity (tertiary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_N_T)
lle_menge_p_b	Basic quantity	char(1)	Problem quantity (base quantity unit) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_P_B)
lle_menge_p_p	Primary quantity	char(1)	Problem quantity (primary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_P_P)
lle_menge_p_s	Secondary quantity	char(1)	Problem quantity (secondary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_P_S)
lle_menge_p_t	Tertiary quantity	char(1)	Problem quantity (tertiary) is considered for wage calculation J/N (PDM field ID: LART.OPT:LLEMENGE_P_T)
lle_perszeit	Is personel time for LLE	char(1)	Attendance time of this wage type is used as personel time in incentive wages J: yes n: no (PDM field ID: LART.OPT:PZEITLLE)
lobu_kennzeichen	Control indicator	char(10)	Upload to LOBU (PDM field ID: LART.LOBU:MOD)
lobu_lohnart	Wage type	char(10)	Wage type used for the interface to the payroll. (PDM field ID: LART.LOBU:LART)
lohnart	Wage type	char(4)	Wage type ID (PDM field ID: LART.LART)
prozent	Percentage	smallint	Allocation record of the wage type in %. This percentage is actually only allocated when it comes to the overtime compensation. Wage types with 0% are not allocated. (PDM field ID: LART.PROZ)
rueckmelden	Upload wage type to payroll system	char(1)	Defines whether the wage type is to be uploaded to the payroll system (PDM field ID: LART.LOBU:RM)
soll_mehr_az	Usage	char(1)	Definition of whether the wage type will be used to compensate the target working time (S), overtime (M) or undertime (I). It is also possible to make no definition here (<null>/empty). The wage types marked by overtime will be listed in the time sheet in the Overtime column. This applies analogously to the use of undertime but where the times will be presented with a negative sign. (PDM field ID: LART.OPT:SZMA)
std_unterteilung	Rounding interval	integer	 (PDM field ID: LART.RINT)
stufe	For future use	smallint	For future use
stufung	Rounding limit	integer	 (PDM field ID: LART.RG)
stundensatz	Hourly rate	integer	Reserved for customer specific processing. Contains the hourly rate multiplied by the factor 100 e.g. EUR 86,50 -> 8650. (PDM field ID: LART.LSS)
verantw_bereich	Responsibility area	char(15)	Responsibility area that this wage type is assigned to. (PDM field ID: LART.VAB)
verarb_kz	For future use	char(1)	For future use
verarbeitung	Processing	char(1)	Currently not used. (PDM field ID: LART.VERB)

zeitart	Time type	char(3)	ID of time type for LLE AKK accord GK overhead costs ZL time wage EA practice PZE attendance (PDM field ID: LART.ZEIART)
zusatzkz	For future use	char(1)	For future use
zusatztext	For future use	char(10)	For future use

12.20. lohnarten_aw

Table name: lohnarten_aw		Product: PZE	
Designation: Wage type bookings per overtime period		Description: Aggregation of wage type bookings over the overtime period.	
		# Key verweis_ausw, lohnart, kostenstelle (unique)	
		# Connections to other tables verweis_ausw refers to zeitspanne_aw.satznummer	
Column name	Column designation	Type	Description
kennzeichen	For future use	char(1)	
kost_firma	Company of cost center	char(4)	
kostenstelle	Cost center used for this wage type	char(10)	
lohnart	Wage type	char(4)	
user_c_09	Reserved for customer specific processing	char(20)	
user_c_10	Reserved for customer specific processing	char(40)	
user_d_01	Reserved for customer specific processing	date	
user_d_02	Reserved for customer specific processing	date	
user_f_07	Reserved for customer specific processing	decimal(18,6)	
user_f_08	Reserved for customer specific processing	decimal(18,6)	
user_n_03	Reserved for customer specific processing	integer	
user_n_04	Reserved for customer specific processing	integer	
user_n_05	Reserved for customer specific processing	integer	
user_n_06	Reserved for customer specific processing	integer	
verweis_ausw	Reference to result of overtime period	integer	Refers to the field satznummer in the zeitspanne_aw table.
zeit_anw	Attendance time	integer	
zeit_fehl	Absence time	integer	

12.21. lohnarten_zuord

Table name: lohnarten_zuord		Product: PZE	
Designation: Payment day types header record		Description: Definition how the working time rendered is posted onto wage types.	
		# Key typnummer, gueltig_von (unique)	
		# Connections to other tables typnummer = pze_entlohnung,typnummer	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
arbeitszeit_1	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_10	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_11	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_12	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_13	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_14	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_15	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_16	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_17	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_18	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_2	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_3	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_4	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_5	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_6	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_7	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_8	Not used anymore	integer	See table pze_entlohnung
arbeitszeit_9	Not used anymore	integer	See table pze_entlohnung
art_1	Not used anymore	char(1)	See table pze_entlohnung
art_10	Not used anymore	char(1)	See table pze_entlohnung
art_11	Not used anymore	char(1)	See table pze_entlohnung
art_12	Not used anymore	char(1)	See table pze_entlohnung
art_13	Not used anymore	char(1)	See table pze_entlohnung
art_14	Not used anymore	char(1)	See table pze_entlohnung
art_15	Not used anymore	char(1)	See table pze_entlohnung
art_16	Not used anymore	char(1)	See table pze_entlohnung
art_17	Not used anymore	char(1)	See table pze_entlohnung
art_18	Not used anymore	char(1)	See table pze_entlohnung
art_2	Not used anymore	char(1)	See table pze_entlohnung
art_3	Not used anymore	char(1)	See table pze_entlohnung
art_4	Not used anymore	char(1)	See table pze_entlohnung

art_5	Not used anymore	char(1)	See table pze_entlohnung
art_6	Not used anymore	char(1)	See table pze_entlohnung
art_7	Not used anymore	char(1)	See table pze_entlohnung
art_8	Not used anymore	char(1)	See table pze_entlohnung
art_9	Not used anymore	char(1)	See table pze_entlohnung
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bez_ausf	Designation	char(40)	Designation of the payment day type. (PDM field ID: ENLTMOD.BEZL)
bezeich1	Short designation	char(6)	Short designation of the payment day type. The first three letters of this designation are entered in the annual absence overview in case of absences. (PDM field ID: ENLTMOD.BEZK)
bezeich2	Usage	char(6)	Definition whether it is about an ,E' Payment day type, an ,F' Absence payment or an ,M' Overtime type. (PDM field ID: ENLTMOD.ART)
certify_flag_1	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_10	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_11	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_12	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_13	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_14	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_15	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_16	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_17	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_18	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_2	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_3	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_4	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_5	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_6	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_7	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_8	Not used anymore	char(1)	See table pze_entlohnung
certify_flag_9	Not used anymore	char(1)	See table pze_entlohnung
gueltig_bis	Not used anymore	date	Validity period for the paymment day type.
gueltig_von	Valid from	date	Validity period for the payment day type.
istzeit_verrechnen	Not used anymore	char(1)	
kons_pflege	Not used anymore	char(1)	See table pze_entlohnung
lohnart_1	Not used anymore	char(4)	See table pze_entlohnung
lohnart_10	Not used anymore	char(4)	See table pze_entlohnung
lohnart_11	Not used anymore	char(4)	See table pze_entlohnung
lohnart_12	Not used anymore	char(4)	See table pze_entlohnung
lohnart_13	Not used anymore	char(4)	See table pze_entlohnung
lohnart_14	Not used anymore	char(4)	See table pze_entlohnung
lohnart_15	Not used anymore	char(4)	See table pze_entlohnung
lohnart_16	Not used anymore	char(4)	See table pze_entlohnung

[illegible]

typnummer	Day type	smallint	Unique key of the day type. Value: 1..900 (PDM field ID: ENLTMOD.ENTLTMOD)
verantw_bereich	Responsibility area	char(15)	
zeit_bis_1	Not used anymore	integer	See table pze_entlohnung
zeit_bis_10	Not used anymore	integer	See table pze_entlohnung
zeit_bis_11	Not used anymore	integer	See table pze_entlohnung
zeit_bis_12	Not used anymore	integer	See table pze_entlohnung
zeit_bis_13	Not used anymore	integer	See table pze_entlohnung
zeit_bis_14	Not used anymore	integer	See table pze_entlohnung
zeit_bis_15	Not used anymore	integer	See table pze_entlohnung
zeit_bis_16	Not used anymore	integer	See table pze_entlohnung
zeit_bis_17	Not used anymore	integer	See table pze_entlohnung
zeit_bis_18	Not used anymore	integer	See table pze_entlohnung
zeit_bis_2	Not used anymore	integer	See table pze_entlohnung
zeit_bis_3	Not used anymore	integer	See table pze_entlohnung
zeit_bis_4	Not used anymore	integer	See table pze_entlohnung
zeit_bis_5	Not used anymore	integer	See table pze_entlohnung
zeit_bis_6	Not used anymore	integer	See table pze_entlohnung
zeit_bis_7	Not used anymore	integer	See table pze_entlohnung
zeit_bis_8	Not used anymore	integer	See table pze_entlohnung
zeit_bis_9	Not used anymore	integer	See table pze_entlohnung
zeit_nach_1	Not used anymore	integer	See table pze_entlohnung
zeit_nach_10	Not used anymore	integer	See table pze_entlohnung
zeit_nach_11	Not used anymore	integer	See table pze_entlohnung
zeit_nach_12	Not used anymore	integer	See table pze_entlohnung
zeit_nach_13	Not used anymore	integer	See table pze_entlohnung
zeit_nach_14	Not used anymore	integer	See table pze_entlohnung
zeit_nach_15	Not used anymore	integer	See table pze_entlohnung
zeit_nach_16	Not used anymore	integer	See table pze_entlohnung
zeit_nach_17	Not used anymore	integer	See table pze_entlohnung
zeit_nach_18	Not used anymore	integer	See table pze_entlohnung
zeit_nach_2	Not used anymore	integer	See table pze_entlohnung
zeit_nach_3	Not used anymore	integer	See table pze_entlohnung
zeit_nach_4	Not used anymore	integer	See table pze_entlohnung
zeit_nach_5	Not used anymore	integer	See table pze_entlohnung
zeit_nach_6	Not used anymore	integer	See table pze_entlohnung
zeit_nach_7	Not used anymore	integer	See table pze_entlohnung
zeit_nach_8	Not used anymore	integer	See table pze_entlohnung
zeit_nach_9	Not used anymore	integer	See table pze_entlohnung
zeit_nachbis_1	Not used anymore	integer	See table pze_entlohnung
zeit_nachbis_10	Not used anymore	integer	See table pze_entlohnung
zeit_nachbis_11	Not used anymore	integer	See table pze_entlohnung
zeit_nachbis_12	Not used anymore	integer	See table pze_entlohnung
zeit_nachbis_13	Not used anymore	integer	See table pze_entlohnung
zeit_nachbis_14	Not used anymore	integer	See table pze_entlohnung
zeit_nachbis_15	Not used anymore	integer	See table pze_entlohnung

[illegible]

zeitfenster_bis_9	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_1	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_10	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_11	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_12	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_13	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_14	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_15	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_16	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_17	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_18	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_2	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_3	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_4	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_5	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_6	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_7	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_8	Not used anymore	integer	See table pze_entlohnung
zeitfenster_kz_9	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_1	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_10	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_11	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_12	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_13	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_14	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_15	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_16	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_17	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_18	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_2	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_3	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_4	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_5	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_6	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_7	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_8	Not used anymore	integer	See table pze_entlohnung
zeitfenster_von_9	Not used anymore	integer	See table pze_entlohnung

12.22. lohnartengruppe

Table name: lohnartengruppe		Product: PZE	
Designation: Wage type groups		Description: In this table wage types can be summarized to groups for certain evaluations (e.g. configurable wage type list).	
Column name	Column designation	Type	Description
abgelehnte	Rejected postings	char(1)	Determination whether refused postings are to be displayed ("X"/"-") (PDM field ID: LARTGRP.OPT:REJECT)
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Designation	char(40)	The designation of the wage type group has to be entered in each data record of the group. (PDM field ID: LARTGRP.BEZ)
genehmigte	Approved postings	char(1)	("X"/"-") approved postings are considered in the group. (PDM field ID: LARTGRP.OPT:SIGN)
gr_lohnart	Wage type group	char(4)	Indicator for the wage type group (group wage type). (PDM field ID: LARTGRP.LARTGRP)
herkunft	Origin	char(1)	Origin of data (,T'=daily wage type postings, ,M'=monthly wage types) (PDM field ID: LARTGRP.OPT:TYP)
kz		char(1)	For future use
lohnart		char(4)	Indicator of a wage type contained in the group. (PDM field ID: LARTGRP.LART)
lohnart_text		smallint	Not used at the moment
normale	Postings that do not require approval	char(1)	("X"/"-") postings that are not subject to authorization are considered in the group. (PDM field ID: LARTGRP.OPT:NORM)
prozent	Factor	smallint	Factor in percent by means of which the wage type has to be assessed in the group. (PDM field ID: LARTGRP.PROZ)
ungenehmigte	Unapproved postings	char(1)	("X"/"-") unapproved postings are considered in the group. (PDM field ID: LARTGRP.OPT:CERTIFY)
verantw_bereich		char(15)	Responsibility area the wage type group is assigned to.

12.23. lohnartenliste

Table name: lohnartenliste		Product: PZE	
Designation: Wage type list		Description: The configurable wage type lists can be defined in this table. The wage types of single groups can be displayed and accumulated in these lists (please see lohnartengruppe table).	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Designation	char(40)	List designation. It has to be entered in each data record of the list configuration. (PDM field ID: LARTLST.BEZ)
gr_lohnart		char(4)	Indicator of the wage type group. (PDM field ID: LARTLST.LARTGRP)
liste_nr	Wage type statistics	smallint	Unique number of the wage type list. (PDM field ID: LARTLST.LARTLST)
verantw_bereich		char(15)	Responsibility area that the wage type list is assigned to.

12.24. lohnstat_familie

Table name: lohnstat_familie		Product: PZE	
Designation: Payment depending on shift type		Description: In this table payment day types can be planned for shift workers depending on the shift type determined automatically (when payment day type X and shift type Y are originally planned use payment day type Z instead).	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
datum_bis		date	Validity period for this configuration (currently not used). (PDM field ID: ENTLSCHZART.DATB)
datum_von		date	Validity period for this configuration (currently not used). (PDM field ID: ENTLSCHZART.DATE)
familie		smallint	Payment day type planned originally. (PDM field ID: ENTLSCHZART.ENTLTMOD)
lohnstatus		smallint	Payment day type that is to be used instead of the type planned originally. (PDM field ID: ENTLSCHZART.ENTLTMOD:Z)
schichtart		char(1)	Shift type at which the payment day type is to be changed. (PDM field ID: ENTLSCHZART.SCHZART)
verweis	Reference	serial	Unique key to access the data record.

12.25. meldeliste

Table name: meldeliste		Product: PZE	
Designation: Configuration of message listings		Description: The configurable message listings can be defined in this table. Then selected messages are only displayed in these lists.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Designation	char(40)	Designation of the list. It has to be entered in each data record of the list configuration. (PDM field ID: MELDLST.BEZ)
liste_nr		smallint	Unique number of the list. (PDM field ID: MELDLST.MELDLST)
melde_nr	Number	integer	Message number that is to be mentioned in the list. (PDM field ID: MELDLST.MELDNR)
verantw_bereich		char(15)	Responsibility area that the message listing is assigned to.

12.26. meldungen

Table name: meldungen		Product: PZE	
Designation: Messages for message listings			
Column name	Column designation	Type	Description
checkliste		char(1)	Not used at the moment
melde_nr		integer	900-949 reserved for LLE
melde_stufe		char(1)	Type of message: '*' = error message 'c' = message concerning required approval ' ' = note
melde_txt		char(66)	Text of message
meldeliste		char(1)	Not used at the moment
suchen		char(1)	Not used at the moment

12.27. moaw_per_par

Table name: moaw_per_par		Product: PZE	
Designation: Evaluation parameters (month)		Description: Determination of evaluation periods for monthly evaluations.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausw_beginn		date	Start date of the 1st period (for periods only) (PDM field ID: MONATPER.DATB)
ausw_opt	Type	char(1)	Type of evaluation period for the evaluation of months: - 'M': periodes of months (calendar months) - 'Z': free periods (PDM field ID: MONATPER.ART)
bearb	Modified by	char(10)	
bearb_date		date	Last editing date
bearb_time	Modified time	integer	
dauer_1	1	smallint	Duration of the 1st period (for periods only) (PDM field ID: MONATPER.DAUER:1)
dauer_10	10	smallint	Duration of the single periods in days. (PDM field ID: MONATPER.DAUER:10)
dauer_11	11	smallint	Duration of the single periods in days.
dauer_12	12	smallint	Duration of the single periods in days.
dauer_13	13	smallint	Duration of the single periods in days.
dauer_14	14	smallint	Duration of the single periods in days.
dauer_15	15	smallint	Duration of the single periods in days.
dauer_16	16	smallint	Duration of the single periods in days.
dauer_17	17	smallint	Duration of the single periods in days.
dauer_18	18	smallint	Duration of the single periods in days.
dauer_19	19	smallint	Duration of the single periods in days.
dauer_2	2	smallint	Duration of the single periods in days.
dauer_20	20	smallint	Duration of the single periods in days. (PDM field ID: MONATPER.DAUER:20)
dauer_21	21	smallint	Duration of the single periods in days.
dauer_22	22	smallint	Dauer der einzelnen Zeiträume in Tagen.
dauer_23	23	smallint	Duration of the single periods in days.
dauer_24	24	smallint	Duration of the single periods in days.
dauer_25	25	smallint	Duration of the single periods in days.
dauer_26	26	smallint	Duration of the single periods in days.
dauer_27	27	smallint	Duration of the single periods in days.
dauer_28	28	smallint	Duration of the single periods in days.
dauer_29	29	smallint	Duration of the single periods in days.
dauer_3	3	smallint	Duration of the single periods in days.
dauer_30	30	smallint	Duration of the single periods in days. (PDM field ID: MONATPER.DAUER:30)
dauer_4	4	smallint	Duration of the single periods in days.

dauer_5	5	smallint	Duration of the single periods in days.
dauer_6	6	smallint	Duration of the single periods in days.
dauer_7	7	smallint	Duration of the single periods in days.
dauer_8	8	smallint	Duration of the single periods in days.
dauer_9	9	smallint	Duration of the single periods in days.
firmen_nummer		char(4)	The evaluation periods for the evaluation of months are defined per company (PDM field ID: MONATPER.FIR)
jahr		smallint	Indication of the year for which the definition is to apply (PDM field ID: MONATPER.JAHR)
verweis		serial	

12.28. moaw_periode

Table name: moaw_periode		Product: PZE	
Designation: Evaluation periods (month)		Description: The evaluation of months can have different evaluation periods for different companies. The period for a month evaluation is gathered from this table to start this one.	
Column name	Column designation	Type	Description
aw_begin	From	date	Start of evaluating the period.
aw_ende	To	date	End of evaluating the period.
firma	Company	char(4)	Company (field within the HR master) that this period applies for.
jahr		smallint	Year in which this configuration applies.
periode	Settlement period	smallint	Number of the period.
verweis		serial	
zusatz_kz		char(1)	For future use

Table name: monat_aw		Product: PZE	
Designation: Monthly results		Description: Result record of the monthly evaluation.	
		# Key personalnummer, aw_datum, firma (unique)	
		# Connections to other tables monat_aw.satznummer = monatllohnarten_aw.verweis_ausw personen.personalnummer = personalnummer and aw_datum_ende between personen.gueltig_von and personen.gueltig_bis	
Column name	Column designation	Type	Description
ae_anzahl	Days absent	smallint	Number of days with absence time
ausgewertet	Date of last evaluation	date	Date of last evaluation
ausgewertet_bearb	User of last evaluation	char(10)	
ausgewertet_zeit	Time of last evaluation	integer	
auto_ktoaend_1	Account change by processing account limits	integer	
auto_ktoaend_10	Account change by processing account limits	integer	
auto_ktoaend_11	Account change by processing account limits	integer	
auto_ktoaend_12	Account change by processing account limits	integer	
auto_ktoaend_13	Account change by processing account limits	integer	
auto_ktoaend_14	Account change by processing account limits	integer	
auto_ktoaend_15	Account change by processing account limits	integer	
auto_ktoaend_16	Account change by processing account limits	integer	
auto_ktoaend_17	Account change by processing account limits	integer	
auto_ktoaend_18	Account change by processing account limits	integer	
auto_ktoaend_19	Account change by processing account limits	integer	
auto_ktoaend_2	Account change by processing account limits	integer	
auto_ktoaend_20	Account change by processing account limits	integer	
auto_ktoaend_3	Account change by processing account limits	integer	
auto_ktoaend_4	Account change by processing account limits	integer	
auto_ktoaend_5	Account change by processing account limits	integer	
auto_ktoaend_6	Account change by processing account limits	integer	
auto_ktoaend_7	Account change by processing account limits	integer	
auto_ktoaend_8	Account change by processing account limits	integer	
auto_ktoaend_9	Account change by processing account limits	integer	
aw_datum	Start of period	date	First day of evaluation period. The reporting is always carried out for a whole evaluation period.
aw_datum_ende	End of period	date	Last day of evaluation period.
az_anw	Attendance time	integer	Attendance time within month.
az_fehl	Absence	integer	Absence time within month.
az_soll	Target time	integer	Target working time in the indicated month.
az_unbez	Other unpaid	integer	Unpaid time within month.
firma	Company	char(4)	Evaluated person's company.

flexktoaend	Change of account number 3 (Flexible time) within period.	integer	
gleitzeitend	Change of account number 1 (Gliding time) within period	integer	
jahr	Year	smallint	
kg_anzahl	Days present	smallint	Number of days of attendance
ktoaend_10	Change of account within period	integer	
ktoaend_11	Change of account within period	integer	
ktoaend_12	Change of account within period	integer	
ktoaend_13	Change of account within period	integer	
ktoaend_14	Change of account within period	integer	
ktoaend_15	Change of account within period	integer	
ktoaend_16	Change of account within period	integer	
ktoaend_17	Change of account within period	integer	
ktoaend_18	Change of account within period	integer	
ktoaend_19	Change of account within period	integer	
ktoaend_20	Change of account within period	integer	
ktoaend_5	Change of account within period	integer	
ktoaend_6	Change of account within period	integer	
ktoaend_7	Change of account within period	integer	
ktoaend_8	Change of account within period	integer	
ktoaend_9	Change of account within period	integer	
ktostand_1	Account balance at end of period after processing account limits.	integer	
ktostand_10	Account balance at end of period after processing account limits.	integer	
ktostand_11	Account balance at end of period after processing account limits.	integer	
ktostand_12	Account balance at end of period after processing account limits.	integer	
ktostand_13	Account balance at end of period after processing account limits.	integer	
ktostand_14	Account balance at end of period after processing account limits.	integer	
ktostand_15	Account balance at end of period after processing account limits.	integer	
ktostand_16	Account balance at end of period after processing account limits.	integer	
ktostand_17	Account balance at end of period after processing account limits.	integer	
ktostand_18	Account balance at end of period after processing account limits.	integer	
ktostand_19	Account balance at end of period after processing account limits.	integer	
ktostand_2	Account balance at end of period after processing account limits.	integer	
ktostand_20	Account balance at end of period after processing account limits.	integer	
ktostand_3	Account balance at end of period after processing account limits.	integer	

ktostand_4	Account balance at end of period after processing account limits.	integer	
ktostand_5	Account balance at end of period after processing account limits.	integer	
ktostand_6	Account balance at end of period after processing account limits.	integer	
ktostand_7	Account balance at end of period after processing account limits.	integer	
ktostand_8	Account balance at end of period after processing account limits.	integer	
ktostand_9	Account balance at end of period after processing account limits.	integer	
man_ktoaend_1	Manually recorded account change within period	integer	
man_ktoaend_10	Manually recorded account change within period	integer	
man_ktoaend_11	Manually recorded account change within period	integer	
man_ktoaend_12	Manually recorded account change within period	integer	
man_ktoaend_13	Manually recorded account change within period	integer	
man_ktoaend_14	Manually recorded account change within period	integer	
man_ktoaend_15	Manually recorded account change within period	integer	
man_ktoaend_16	Manually recorded account change within period	integer	
man_ktoaend_17	Manually recorded account change within period	integer	
man_ktoaend_18	Manually recorded account change within period	integer	
man_ktoaend_19	Manually recorded account change within period	integer	
man_ktoaend_2	Manually recorded account change within period	integer	
man_ktoaend_20	Manually recorded account change within period	integer	
man_ktoaend_3	Manually recorded account change within period	integer	
man_ktoaend_4	Manually recorded account change within period	integer	
man_ktoaend_5	Manually recorded account change within period	integer	
man_ktoaend_6	Manually recorded account change within period	integer	
man_ktoaend_7	Manually recorded account change within period	integer	
man_ktoaend_8	Manually recorded account change within period	integer	
man_ktoaend_9	Manually recorded account change within period	integer	
moaw_erforderlich	Monthly evaluation has to be performed	char(1)	Flag whether new month evaluation is required (J/N).
periode	Period	smallint	

personalnummer	Personnel number	integer	
rueckgemeldet	Confirmed	char(1)	When starting the interface it is recorded that the interface has already been active by putting "J" in this field.
satznummer	Reference	serial	Each data record of this table receives a unique key.
solltage	Days with target time	smallint	Number of days with target time.
ueberstdaend	Change of account number 2 (Overtime) within period.	integer	
url_anspruch	Leave entitlement granted within this period	integer	
urlaubaeend	Change of account number 4 (Leave) within period	integer	
user_c_09	Reserved for customer specific use	char(20)	
user_c_10	Reserved for customer specific use	char(40)	
user_d_01	Reserved for customer specific use	date	
user_d_02	Reserved for customer specific use	date	
user_f_07	Reserved for customer specific use	decimal(18,6)	
user_f_08	Reserved for customer specific use	decimal(18,6)	
user_n_03	Reserved for customer specific use	integer	
user_n_04	Reserved for customer specific use	integer	
user_n_05	Reserved for customer specific use	integer	
user_n_06	Reserved for customer specific use	integer	
wo_lostzeit	Reserved	integer	Additional evaluation field (currently not used).

12.30. monatlohnarten_aw

Table name: monatlohnarten_aw		Product: PZE	
Designation: Monthly wage types		Description: Aggregation of wage types accumulated during the month evaluation period.	
		# Key verweis_ausw, lohnart, kostenstelle (unique)	
		# Connections to other tables monatlohnarten_aw.verweis_ausw = monat_aw.satznummer	
Column name	Column designation	Type	Description
aw_datum	Start of period	date	
aw_datum_ende	End of period	date	
ganze_tage_fehl	Full-day absence	smallint	Number of days with complete absence.
kennzeichen	For future use	char(1)	For future use
kost_firma	Company of cost center	char(4)	
kostenstelle	Cost center	char(10)	Cost center used for this wage type.
lohnart	Wage type	char(4)	The allocated wage type.
personalnummer	Personnel number	integer	
teil_tage_fehl	Part-time absent	smallint	Number of days with partial absence.
user_c_09	Reserved for customer specific processing	char(20)	
user_c_10	Reserved for customer specific processing	char(40)	
user_d_01	Reserved for customer specific processing	date	
user_d_02	Reserved for customer specific processing	date	
user_f_07	Reserved for customer specific processing	decimal(18,6)	
user_f_08	Reserved for customer specific processing	decimal(18,6)	
user_n_03	Reserved for customer specific processing	integer	
user_n_04	Reserved for customer specific processing	integer	
user_n_05	Reserved for customer specific processing	integer	
user_n_06	Reserved for customer specific processing	integer	
verweis	Reference	serial	Internal unique number of the record
verweis_ausw	Reference	integer	Refers to the satznummer field in the monat_aw table.
zeit_anw	Attendance time	integer	Attendance time posted to this wage type.
zeit_fehl	Absence	integer	Absence time posted to this wage type.

12.31. persauswertparm

Table name: persauswertparm		Product: PZE	
Designation: Control of labor time calculation		Description: Control of labor time calculation	
		# Special remarks This table contains both general settings and personal settings. General settings have bezug='GLOBAL' and persoanlich=N. Personal settings have persoanlich=J and key/value pairs in bezug/wert. Personnel selection can be: 1) Global: bezug='GLOBAL', persoanlich=N 2) Single persons: personalnummer=<personnel no>, bezug=<null>, wert=<personnel no>, persoanlich=J 2) Several other personnel selections: [firmen_nummer=<company>] (optional), bezug=<personnel selection key>, wert=<personnel selection value>, persoanlich=J	
		# Key <Key fields for unique access>	
		# Connections to other tables If the personnel number is assigned an outer-join to the HR master can be made.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung	Comment	char(40)	
bereich	Obsolete	char(8)	See bezug/wert
bezug	Personnel selection key	char(20)	
bezug_block_anf	Start time Blocking/Waiting period - Reference	char(1)	Reference time of blocking at the beginning (K/N/R). K=Start of core time N=Start of normal time R=Start of skeleton time
bezug_block_ende	End time Blocking/Waiting period - Reference	char(1)	Reference time of blocking at the end (K/N/R).
bezug_block_soll	Target time Blocking/Waiting period - Reference	char(1)	Reference time for blocking the target time (S/N): S=Planned target time N=Planned normal time
bezug_karenz_anf	Start time Blocking/Waiting period - Reference	char(1)	Reference time for the waiting period at the beginning (K/N/R): K=Start of core time N=Start of normal time R=Start of skeleton time
bezug_karenz_ende	End time Blocking/Waiting period - Reference	char(1)	Reference time for the waiting period at the end (K/N/R): K=End of core time N=End of normal time R=End of skeleton time

bezug_karenz_soll	Target time Blocking/Waiting period - Reference	char(1)	Reference time for the waiting period of target time (S/N): S=Planned target time N=Planned normal time
blockierunganfang	Blocking start time - Blocking	integer	Blocking time at the beginning of working time. For shift workers this point in time refers to the beginning of the shift and for employees working flexible hours it refers to the reference time set.
blockierungende	Blocking end time - Blocking	integer	Blocking time at the end of working time. For shift workers this point in time refers to the end of the shift and for employees working flexible hours it refers to the reference time set.
blockierungsollend	Target time - Blocking	integer	Blocking time after reaching the target working time or normal time depending on the reference time set.
datum_bis	Valid until	date	
datum_von	Valid from	date	
ergaenzung_geht	For future use	char(1)	
ergaenzung_kommt	For future use	char(1)	
feiertag_abr	Reserved	char(1)	Activation of customer-specific allocation of public holidays
festloart_mask	Obsolete	char(1)	
firmer_nummer	Company	char(4)	Company which the following configuration applies for.
flex_lohnart_1	For future use	smallint	
flex_lohnart_2	For future use	smallint	
flex_lohnart_3	For future use	smallint	
flex_lohnart_4	For future use	smallint	
flex_lohnart_5	For future use	smallint	
grenz_gleichzeit	Minimum duration of break	integer	Time in seconds. If a clocking-in follows a clocking-out within the time entered here the clocking-in is rounded down to the clocking-out time.
hoechst_az_ausbl	For future use	char(1)	
inaz_nutzen	Rounding: Within working time: Active	char(1)	B = Yes (both flextime and fixed shft time) G = Flextime day type S = Shift day type N = No, inactive. Time is masked.
istaz_nutzen	Actual working time - Active	char(1)	Indication whether the working time is rounded after reaching the target working time. B = Yes (both flextime and fixed shft time) G = Flextime day type S = Shift day type N = No, inactive. Time is masked.
karenzanfang	Waiting period	integer	Information on this field can be found with rounding according to waiting period.
karenzende	Waiting period	integer	Information on this field can be found with rounding according to waiting period.
karenzsollende	Target time - Waiting period	integer	Waiting period before reaching the target working time.
kostenstelle	Obsolete	char(10)	See bezug/wert
letztes_ende_zeit	Hours after end of skeleton time	integer	Period how long after the planned end time clocking-ins are still assigned to the current day of evaluation. For employees working flexible time the time refers to the end of skeleton time and for shift workers to the end of shift. 20000 (approx. 6 hours) is the default entry for this field.
nachaz_nutzen	Working time after end of skeleton time - Active	char(1)	Indication whether the clocking time is processed and rounded after the target end time. If rounding after the target end time is not active the respective time is hidden. The skeleton end time constitutes the target end time for flexible time models. B = Yes (both flextime and fixed shft time) G = Flextime day type S = Shift day type N = No, inactive. Time is masked.
pause_nutzen	Rounding within working time - Active	char(1)	Use rounding for the break (B/G/N/S). B = Yes (both flextime and fixed shft time) G = Flextime day type S = Shift day type N = No, inactive. Time is masked.
persoenlich	Validity - Type	char(1)	J: Personal setting Else: General setting
personalnummer	Personnel number	integer	Personnel number which the following configuration applies for.
prioritaet	Priority	smallint	

rahmen_ausbl	Obsolete	char(1)	Indication whether working time that lies beyond the skeleton time will be hidden. This field is replaced by the nachaz_nutzen field in version 7.1. The 'H' entry causes that the working time accumulated after reaching the maximum working time will be hidden.
rund_art	Rounding type	char(1)	Indication whether clocking-ins or clocking-outs are rounded by waiting periods or by what is known as gradation. ('V'=gradation, 'K'=waiting period, 'B'=both, 'S'=both, but cut seconds off at first (recommended!))
schichtart_such	Automatic shift identification	char(1)	Definition whether the shift type is to be determined automatically on the basis of the first clocking-in.
schichtart_teil	Limit between shifts	smallint	Percentage to determine the correct shift in case of "search shift type".
schichtart_vortag	Adopt shift type of previous day	char(1)	Determines whether the shift type of the last working day is used or if the shift type planned within the shift rhythm model is to be used for absences that are generated automatically.
sollaz_nutzen	Overtime - Active	char(1)	Indication whether the calculated actual working time is to be rounded with respect to the target working time. (Only if target working time is exceeded). B = Yes (both flextime and fixed shft time) G = Flextime day type S = Shift day type N = No, inactive. Time is masked.
std_teil	Interval	integer	Information on this field can be found with rounding according to gradation mechanism. This field applies for clocking-ins for fixed shift models.
std_teil_gl	Interval	integer	Information on this field can be found with rounding according to gradation mechanism. This field applies for employees with flextime or flexible shift models.
std_teil_inaz	Rounding: Within working time: Interval	integer	
std_teil_istaz	Interval	integer	Details on this field can be found when rounding the actual working time.
std_teil_nachaz	Working time after end of skeleton time - Interval	integer	
std_teil_pause	Rounding within working time - Interval	integer	Rounding interval within break frames (for employees working flexible hours or flexible shift workers only).
std_teil_sollaz	Overtime - Interval	integer	Rounding rule for target working time.
std_teil_voraz	Interval	integer	Information on this field can be found with rounding of clockings before the target start time.
stempel_zum_tag	Assign clocking record to current day until - Time	integer	Flag for the evaluation of days showing by what time a clocking still belongs to the current day, even if a target working time is not planned for this day. 82800 (= 11 pm) is the default setting for this field.
stuf_teil	Waiting period clock-in	integer	Information on this field can be found with rounding according to gradation mechanism. This field applies for clocking-ins for fixed shift models.
stuf_teil_geht	Shift day type - Waiting period clock-out	integer	Details on this field can be found when rounding according to gradation mechanism. This field applies to clocking-outs for fixed shift models.
stuf_teil_gl	Waiting period clock-in	integer	Information on this field can be found with rounding according to gradation mechanism. This field applies for clocking-ins for flextime or flexible shift models.
stuf_teil_gl_geht	Flextime day type - Waiting period clock-out	integer	Details on this field can be found when rounding according to gradation mechanism. This field applies to clocking-outs of flexible time or flexible shift models.
stuf_teil_inaz	Rounding: Within working time: Waiting period	integer	
stuf_teil_istaz	Waiting period	integer	Details on this field can be found when rounding the actual working time.
stuf_teil_nachaz	Working time after end of skeleton time - Waiting period	integer	Details on these fields can be found when rounding clockings after the target end time.
stuf_teil_pause	Rounding within working time - Waiting period	integer	Waiting period within the rounding interval of the break frame.
stuf_teil_sollaz	Overtime - Waiting period	integer	Gradation rules for target working time.
stuf_teil_voraz	Waiting period	integer	Information on this field can be found with rounding of clockings before the target start time.
ungeplant_fehlzeit	Generate unplanned absences	char(1)	Indication whether an absence time record is to be generated for unplanned absences: J = record is generated. N = record is not generated. C = record is generated the postings are subject to authorization. A = record is generated as attendance time
ungeplant_lohntyp	Absence payment	smallint	Payment day type used to allocate unplanned absences.
url_anspruch_datum	For future use	date	
verweis	Reference	serial	

voraz_nutzen	Working time before beginning of skeleton time - Active	char(1)	Indication whether the clocking time is processed and rounded before the target start time. If rounding before the target start time is not used it is hidden. The target start time is the start of the skeleton time for flexible time models. B = Yes (both flextime and fixed shft time) G = Flextime day type S = Shift day type N = No, inactive. Time is masked.
wert	Personnel selection value	char(20)	

12.32. personalakte

Table name: personalakte		Product: PZE	
Designation: Digital personnel file		Description: The application "digital personnel file" allows for staff information to be stored in the system in the form of a digital personnel file. Several categories with different access rights can be managed within the personnel file. A file may be stored for each entry in the digital personnel file.	
Column name	Column designation	Type	Description
anlage_bearb	Created by	char(10)	
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung_1	Comment	char(40)	
bemerkung_2	Comment	char(40)	
bemerkung_3	Comment	char(40)	
bezeichnung	Designation	char(40)	Description of the entry
datei	File	char(256)	A file may be stored for each entry in the digital personnel file. This field shows the unique file name under which the file has been stored on the server.
datum	Date	date	The date to which this entry belongs
geloescht	Deleted	char(1)	Entry is deleted J=Yes, N=No
kategorie	Category	char(8)	Assigns the entry to a category. If categories are used, the authorizations for accessing entries can be controlled by responsibility areas.
personalnummer	Personnel number	integer	The person's personnel number
verweis		serial	
zeit	Time	integer	

12.33. pze_az_intervalle

Table name: pze_az_intervalle		Product: PZE	
Designation: Working time intervals		Description: Working time intervals	
		# Key Logical: personalnummer,aw_tag (not unique) Technical: verweis (unique) # Connections to other tables personen.personalnummer = personalnummer and aw_datum between personen.gueltig_von and personen.gueltig_bis outer join: verweis_stempel = stempelsaetze.verweis	
Column name	Column designation	Type	Description
arbeitsdat_anf	Beginning of interval	date	Date, rounded
arbeitsdat_end	End of interval	date	Date, rounded
arbeitszei_anf	Beginning of interval	integer	Time, rounded
arbeitszei_end	End of interval	integer	Time, rounded
auftrag_nr	For future use	char(40)	
aw_tag	Settlement date	date	
bearb	Modified by (from clocking)	char(10)	
bearb_date	Modified date (from clocking)	date	
bearb_time	Modified time (from clocking)	integer	
bedeutung	Type	char(1)	K = Attendance time D = Business trip F = Absence Time - = Working time dependant break so that no core time violation is reported whilst this interval) B = Payed break Y = Stand-by duty Q = Working time before beginning of skeleton time R = Working time after end of skeleton time
certify_flag	Authorization required	char(1)	Authorization required (J=Yes, N=No).
dauer	Duration	integer	
entlohnungstyp	Payment day type	smallint	
firma	Company	char(4)	
gleitzeittyp	Working time day type	smallint	
kost_firma	Company of the cost center	char(4)	
kostenstelle	Cost center	char(10)	
leistgrp	Premium group	char(8)	For future use
lle_kz	For future use	char(1)	
personalnummer	Personnel number	integer	
schichtart	Shift type	char(1)	
sign_flag	Authorized	char(1)	Flag whether this record was authorized: "J": The record has been approved. "A": The record has been rejected. "N": The record has so far neither been approved nor rejected.
sowizeit_anf	Beginning of interval	char(1)	DST S: DST W: No DST

sowizeit_end	End of interval	char(1)	DST S: DST W: No DST
stempeldat_anf	Beginning of interval	date	Date, not rounded
stempeldat_end	End of interval	date	Date, not rounded
stempelzei_anf	Beginning of interval	integer	Time, not roundet
stempelzei_end	End of interval	integer	Time, not roundet
user_c_01	Customer specific field	char(10)	For future use
user_c_02	Customer specific field	char(40)	For future use
user_c_03	Customer specific field	char(40)	For future use
user_c_04	Customer specific field	char(100)	For future use
user_d_05	Customer specific field	date	For future use
user_d_06	Customer specific field	date	For future use
user_f_07	Customer specific field	decimal(18,6)	For future use
user_f_08	Customer specific field	decimal(18,6)	For future use
user_n_09	Customer specific field	integer	For future use
user_n_10	Customer specific field	integer	For future use
user_n_11	Customer specific field	integer	For future use
user_n_12	Customer specific field	integer	For future use
verweis	Reference	serial	Internal unique number of the record
verweis_stempel	Reference to clocking	integer	

12.34. pze_bez_pause

Table name: pze_bez_pause		Product: PZE	
Designation: Paid breaks		Description: Paid breaks of a day type. An additional clocking record is generated while days are evaluated in order to log and allocate paid breaks. Warning: This table is obsolete and is not processed since version 8.1.	
Column name	Column designation	Type	Description
abt		smallint	Out of date: Number of the shift day type
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
az		integer	Time posted in seconds that has to be passed in order to allocate paid breaks. (PDM field ID: PAUBEZ.IZ)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
benutzen		char(1)	Indication which paid breaks are used for the calculation of actual time: K: attendance times only F: absence times only B: both (PDM field ID: PAUBEZ.ZEIART)
bereich		char(8)	Area for which the configuration is supposed to apply (PDM field ID: PAUBEZ.BER)
datum_bis		date	Validity period (end date)
datum_von		date	Validity period (start date) (PDM field ID: PAUBEZ.DATB)
firma	Company	char(4)	Company for which the configuration is supposed to apply. (PDM field ID: PAUBEZ.FIR)
gleit		smallint	Out of date: Number of the flextime day type
kom		char(3)	Commentary within the generated clocking record (PDM field ID: PAUBEZ.BEZK)
kst		char(10)	Cost center within the generated clocking record (PDM field ID: PAUBEZ.KST)
lost		smallint	Number of the payment day type with which the generated clocking is to be allocated. (PDM field ID: PAUBEZ.ENTLTMOD)
sart		char(1)	Out of date: Shift type in the shift day type
status		char(1)	Meaning of the generated clocking record (PDM field ID: PAUBEZ.STMPART)
typkz		char(1)	Out of date: G: flextime day type S: shift day type
typnr		smallint	Number of the working time model to which the entry belongs (PDM field ID: PAUBEZ.GLZTMOD)
verweis		serial	Unique record number (PDM field ID: PAUBEZ.VERWEIS)
zuschlag		integer	Duration of paid breaks in seconds (PDM field ID: PAUBEZ.PAU)

12.35. pze_entlohnung

Table name: pze_entlohnung		Product: PZE	
Designation: Payment rules		Description: A payment day type contains payment rules.	
		# Key typnummer, gueltig_von (not unique)	
		# Connections to other tables typnummer = lohnarten_zuord.typnummer and gueltig_von = lohnarten_zuord.gueltig_von	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
arbeitszeit_bis	For future use	integer	Currently not processed. (PDM field ID: ENTLREGEL.AZE)
arbeitszeit_von	from (processing = working time)	integer	Payment rule applies for the working time as of the time entered. (PDM field ID: ENTLREGEL.AZB)
art	Processing	char(1)	Type ID S: Till reaching the target working time (or undertime for the overtime type) M: Overtime from T: Working time from V: Compensation time to F: Fixed time from - to K: Core time violation Q: Working time prior to start of skeleton time R: Working time after the end of skeleton time D: Otherwise (use old type ID "art_alt") N: After reaching normal working time H: After reaching maximum working time B: Paid break U: On-call duty Y: Stand-by duty (PDM field ID: ENTLREGEL.ART)
art_alt	Internal use, obsolete	char(1)	Downward compatible processing flag. (PDM field ID: ENTLREGEL.ARTALT)
ausblenden	Hide	char(1)	Hides the subjacent basic wage types when posting fixed times (J/N). (PDM field ID: ENTLREGEL.OPT:AUSBL)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Commentary	char(40)	
certify_flag	Authorization required	char(1)	Determines whether the wage type postings resulting from this payment rule are subject to authorization (J/N). (PDM field ID: ENTLREGEL.CERTIFY)
gueltig_folgetag	Process payment rule also on the next day	char(1)	
gueltig_von	Valid from	date	The payment day type and the payment rules are connected via the fields typnummer and gueltig_von.
gueltig_vortag	Process payment rule also on the previous day	char(1)	
lohnart	Wage type	char(4)	Wage type which is to be allocated. (PDM field ID: ENTLREGEL.LART)
mehrarbeit_bis	For future use	integer	Currently not processed. (PDM field ID: ENTLREGEL.MEHRARBE)

mehrarbeit_von	from (processing=overtime)	integer	Payment rule applies for overtime as of the entered time. (PDM field ID: ENTLREGEL.MEHRARBB)
mehrarbeitstyp	Allocate via overtime type	char(1)	Time is to be posted via the overtime type (J/N). (PDM field ID: ENTLREGEL.OPT:MEHRARB)
nicht_verbuchen	Do not post	char(1)	By payment rules with 'J' in this field the posting of overtime can be restricted as of a certain duration. (PDM field ID: ENTLREGEL.OPT:NVERB)
prozent	Obsolete	smallint	Not used anymore. (PDM field ID: ENTLREGEL.PROZ)
schichtart	Shift type	char(1)	
sortierung	Sorting	smallint	Internal control of the sorting when payment rules are displayed. (PDM field ID: ENTLREGEL.SORT)
typnummer	Payment day type	smallint	Number of the Paymentday type which this payment rule is assigned to. (PDM field ID: ENTLREGEL.ENTLTMOD)
uhrzeit_bis	to (processing = fixed times)	integer	Start and end time for processing fixed times. (PDM field ID: ENTLREGEL.ZEIE)
uhrzeit_von	from (processing = fixed times)	integer	Start and end time for processing fixed times. (PDM field ID: ENTLREGEL.ZEIB)
verweis	Reference	serial	Unique key to access the data record. (PDM field ID: ENTLREGEL.VERWEIS)
vorholzeit	to (processing = compensation time)	integer	Definition of compensation time. (PDM field ID: ENTLREGEL.VHZ)
wochentage	Day of validity	char(10)	Weekdays for which the absence planning applies: (First character: Sunday J/N, , second character: Monday J/N, ... Saturday J/N).
zeitart	Time type	char(1)	Time type for posting fixed times ('S' target time, 'M' overtime, 'B'oth). (PDM field ID: ENTLREGEL.OPT:SZMA)

12.36. pze_feiertage

Table name: pze_feiertage		Product: PZE	
Designation: Public holidays HR		Description: Public holiday calendar for HR	
		# Special remarks Public holidays can be planned for 1) Companies by firma and bezug=<null> 2) Several other combinations of bezug/wert	
		# Key datum,firma,bezug,wert,geloesch verweis (unique)	
		# Connections to other tables	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
art	Type	char(1)	Type of public holiday 1 = Public holiday 2 = Important public holiday 3 = Other day off 0 = No public holiday (used to overwrite public holidays defined with more common personnel selections)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich	Area	char(8)	Reserved (currently not processed).
bezahlt	For future use	smallint	Currently not processed.
bezeichnung	Designation	char(40)	Designation of public holiday (PDM field ID: PZEFEITG.BEZ)
bezug	Personnel selection key	char(20)	
datum	Date	date	Date of public holiday. (PDM field ID: PZEFEITG.DAT)
entlohnungstyp	Payment day type	smallint	Payment day type with which absences are allocated on public holidays. (PDM field ID: PZEFEITG.ENTLTMOD:FZ)
fehlzeit	For future use	integer	Currently not processed.
firma	Company	char(4)	Company for which the following configuration should apply.
geloesch	Deleted	char(1)	J: Definition of public holidays is deleted. Otherwise: Definition of public holidays is valid.
kostenstelle	Cost center	char(10)	Reserved (currently not processed)
personalnummer	Personnel number	integer	Reserved (currently not processed).
verantw_bereich	Responsibility area	char(15)	
verarbeitung	For future use	char(1)	Currently not processed.
verweis	Reference	serial	Unique data record number
wert	Personnel selection value	char(20)	
zuschlagstyp	Payment day type for bonuses	smallint	For future use: Payment day type for the definition of bonuses for public holidays.

12.37. pze_info_par

Table name: pze_info_par		Product: PZE	
Designation: Messages displayed on the terminal		Description: Messages, which are displayed on the terminal at specific times, can be defined for individual employees in this table.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
anzeigen_fehlgrund	Absence reason	char(1)	Always display when absence reasons are entered (J/N). (PDM field ID: INFOCFG.OPT:FGR)
anzeigen_geht	Out	char(1)	Always display at clocking-out (J/N). (PDM field ID: INFOCFG.OPT:GEH)
anzeigen_info	Information	char(1)	Always display at info (J/N). (PDM field ID: INFOCFG.OPT:INFO)
anzeigen_kommt	In	char(1)	Always display at clocking-in (J/N). (PDM field ID: INFOCFG.OPT:KOM)
anzeigen_pause	Break	char(1)	Always display at break (J/N). (PDM field ID: INFOCFG.OPT:PAU)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich		char(8)	Persons which the information is to be displayed for. (PDM field ID: INFOCFG.BER)
bezug	Personnel selection key	char(20)	
countdown	Quantity	smallint	How many times will the message still be displayed? (PDM field ID: INFOCFG.MAXANZ)
datum_bis	Valid until	date	Validity period. (PDM field ID: INFOCFG.DATE)
datum_von	Valid from	date	Validity period. (PDM field ID: INFOCFG.DATB)
ereignis	Event	char(10)	Reserved. (PDM field ID: INFOCFG.EREIG)
firma	Company	char(4)	Persons which the information is to be displayed for. (PDM field ID: INFOCFG.FIR)
info1	Message	char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:1)
info10		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:10)
info2		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:2)
info3		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:3)
info4		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:4)
info5		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:5)
info6		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:6)

info7		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:7)
info8		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:8)
info9		char(80)	Ten text lines that are displayed. (PDM field ID: INFOCFG.INFO:9)
konfig		char(10)	Internal configuration flag; not yet used.
kostenstelle		char(10)	Persons which the information is to be displayed for. (PDM field ID: INFOCFG.KST)
personalnummer	Personnel number	integer	Persons which the information is to be displayed for. (PDM field ID: INFOCFG.PNR)
verarb_intern		char(1)	Internal configuration flag; not yet used.
verweis	Reference	serial	Unique data record number. (PDM field ID: INFOCFG.VERWEIS)
wert	Personnel selection value	char(20)	
wochentag	Weekday	integer	Day on which the message is displayed (7 = everyday, 0 = Sunday, 1 = Monday, ..., 6 = Saturday). (PDM field ID: INFOCFG.WTG)

12.38. pze_konten

Table name: pze_konten		Product: PZE	
Designation: Configuration of accounts		Description: Includes the definition of accounts. Eight data records with the account numbers 1 to 8 have to be created in this table.	
Column name	Column designation	Type	Description
aktiv	Active	char(1)	Is the account active (J/N)? (PDM field ID: PZEKTO.AKTIV)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bewertung	For future use	integer	Currently not used.
bez_ausf	Detailed designation of the account.	char(40)	 (PDM field ID: PZEKTO.BEZL)
bez_kurz	Short designation of the account.	char(6)	 (PDM field ID: PZEKTO.BEZK)
faktor	Decimal places	integer	Factor with which the value is to be interpreted for day accounts (e.g.=35, Factor=10, -> 3.5 leave days). (PDM field ID: PZEKTO.FAKT)
gelb_bis	Yellow to	integer	
gelb_von	Yellow from	integer	
gruen_bis	Green to	integer	
gruen_von	Green from	integer	
konto_nr	Account	smallint	Account number (1 to 8). (PDM field ID: PZEKTO.KTO)
kontoart	Account type	char(1)	"T": day account "Z": Time account. (PDM field ID: PZEKTO.ART)
lobu_kennzeichen	For future use	char(10)	
lobu_lohnart_diff	For future use	char(10)	
lobu_lohnart_s_neg	Upload negative account balance - wage type	char(10)	
lobu_lohnart_saldo	Upload positive account balance - wage type	char(10)	
sort_kontolisten	Account lists	smallint	Indication at which position the account is to be placed when displaying account lists. Empty: Account is not displayed. (PDM field ID: PZEKTO.SORT:KTOLST)
sort_sonst	Account limits	smallint	This field determines the order when limiting accounts. (PDM field ID: PZEKTO.SORT:KTOGR)
sort_terminalinfo	Terminal information	smallint	Indication at which position the account is to be placed when displaying the inof on the terminal. Empty: Account is not displayed (PDM field ID: PZEKTO.SORT:INFO)
sort_zeitnachweis	Time sheet	smallint	Indication at which position the account is to be placed on the time sheet. Empty: Account is not displayed. (PDM field ID: PZEKTO.SORT:ZNW)
verantw_bereich	Responsibility area	char(15)	
verarbeitung	For future use	char(1)	Not yet processed (5.7.5).
vorzeichen_s_neg	Upload positive account balance - Sign	char(1)	

12.39. pze_pers_daten

Table name: pze_pers_daten		Product: PZE	
Designation: Persons time&attendance data		Description: Current account balances of persons and other status data HR. # Special remarks The content ist set automatically by HR applications. MPDV advises against changing the data, otherwise inconsistencies may arise. # Key personalnummer (unique) # Connections to other tables personen.personalnummer = personalnummer and <today> between personen.gueltig_von and personen.gueltig_bis	
Column name	Column designation	Type	Description
auswertungsstand	Date of latest labor time calculation	date	Date of the day which has successfully been evaluated via the labor time calculation the last time. (PDM field ID: PNR.ABREDAT (nur Anzeige!))
flexzeitkonto	Account balance (account 3)	integer	(PDM field ID: PNR.KTO:3)
gleitzeitkonto	Account balance (account 1)	integer	(PDM field ID: PNR.KTO:1)
konto_10	Account balance	integer	For future use
konto_11	Account balance	integer	For future use
konto_12	Account balance	integer	For future use
konto_13	Account balance	integer	For future use
konto_14	Account balance	integer	For future use
konto_15	Account balance	integer	For future use
konto_16	Account balance	integer	For future use
konto_17	Account balance	integer	For future use
konto_18	Account balance	integer	For future use
konto_19	Account balance	integer	For future use
konto_20	Account balance	integer	For future use
konto_5	Account balance	integer	(PDM field ID: PNR.KTO:5)
konto_6	Account balance	integer	(PDM field ID: PNR.KTO:9)
konto_7	Account balance	integer	(PDM field ID: PNR.KTO:7)
konto_8	Account balance	integer	(PDM field ID: PNR.KTO:8)
konto_9	Account balance	integer	For future use
personalnummer	Personnel number	integer	Personnel number (PDM field ID: PNR.PNR)
plan_anwesend	Internal processing	date	Used for buffering the planning status of person
plan_az_typ	Internal processing	smallint	Used for buffering the planning status of person
plan_datum	Internal processing	date	Used for buffering the planning status of person
plan_fehlzeit	Internal processing	integer	Used for buffering the planning status of person
plan_schichtart	Internal processing	char(1)	Used for buffering the planning status of person

resturlaub	Account balance (account 4)	integer	Remaining leave account: the account balance is multiplied by the factor defined during the configuration of accounts when it is processed as day account. (PDM field ID: PNR.KTO:4)
satznum	Reference to last clocking	integer	This field refers to the field verweis (reference) in the table stempelsaetze (clocking records). It contains the record number of the employee's last clocking.
satznum_zks	Reference to last access	integer	This field refers to the field verweis (reference) in the table zks_ereignis. It contains the record number of the employee's last access log.
status	Status	char(1)	Person is currently "K" present "G" absent "P" in break "D" on short business trip "E" after entry, prior to clocking-in (in case of access control) "A" before exit, after clocking-out (in case of access control) "d" on short business trip but still in the office (in case of access control) "k" present (has clocked-in) but out of the office (in case of access control) "p" in break, but out of the office (in case of access control) (PDM field ID: PNR.STA)
statusgrund	For future use	char(4)	Reserved for the absence reason on which an employee logs off via an advance clocking
ueberstundenkonto	Account balance (account 2)	integer	(PDM field ID: PNR.KTO:2)
urlaub_geplant	For future use	integer	
zeitzone	Time zone	char(40)	For future use

12.40. pze_perstagtyp

Table name: pze_perstagtyp		Product: PZE	
Designation: Personal day types / personal models		Description: Personal day types / personal models	
		# Special remarks This table is used for both personal day types and personal models, see column geloescht.	
		Personal day types and personal models can be planned for 1) Single persons by personalnummer and bezug=PNR and wert (personalnummer is redundant. It can be used to join numerical) 2) Companies by firma and bezug=<null> 3) Several other combinations of bezug/wert The fields firma, bereicht and kistenstelle are filled in additionally when bezug/wert refer to these attributes.	
		# Key verweis	
		# Connections to other tables 1) To table personen by personalnummer and bezug/wert 2) To lohnarten_zuord by lohnstatustyp = lohnarten_zuord.typnummer 3) To pze_entlohnung by lohnstatustyp = pze_entlohnung.typnummer	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich	Area	char(8)	(PDM field ID: PMOD.BER)
bezeichnung	Comment	char(40)	
bezug	Personnel selection key	char(20)	
datum_bis	Valid until	date	Validity period of the planning. The datum_bis field may remain empty for personal models. (PDM field ID: PMOD.DATE)
datum_von	Valid from	date	Validity period of the planning. The datum_bis field may remain empty for personal models. (PDM field ID: PMOD.DATB)
entlohnungstyp	Payment day type / payment model	smallint	Payment day type or payment model. Empty, if it does not deviate from the normal model. (PDM field ID: PTMOD.ENTLTMOD bzw. PJMOD.ENTLJMOD)
firma	Company	char(4)	(PDM field ID: PMOD.FIR)
geloescht	Type / deleted	char(1)	"j": Deleted personal model "m": Active personal model "J": Deleted personal day type "N": Active personal day type
gleitzeittyp	Working time day type / working time model	smallint	Working time day type or working time model. Empty, if there is no deviation from the planned models (PDM field ID: PJMOD.GLZJMOD bzw. PTMOD.GLZTMOD)
kostenstelle	Cost center	char(10)	(PDM field ID: PMOD.KST)
maxzeit_mehrarb	Overtime type	integer	In case of personal models a deviating overtime type can be defined in this field. (PDM field ID: PJMOD.ENTLTMOD:MEHRARB)

maxzeit_vorsollanf	Shift rhythm model	integer	Personal models: The shift rhythm year model can be overwritten for personal models in this field. (PDM field ID: PJMOD.SCHZRH)
mehrarb_genehmigt	Approved overtime	integer	For future use
nach_rahmenende	Working time after end of frame time	char(1)	For future use
p1_nicht_genommen	Break 1 not taken	char(1)	For future use
p2_nicht_genommen	Break 2 not taken	char(1)	For future use
p3_nicht_genommen	Break 3 not taken	char(1)	For future use
personalnummer	Personnel number	integer	(PDM field ID: PMOD.PNR)
rgbcolor	Color	integer	For future use
schichtart	Shift type	char(1)	Shift type for personal day types. Empty, if it does not deviate from the planned shift type. (PDM field ID: PTMOD.SCHZART)
schichttyp	Obsolete	smallint	
sim_geloescht	For future use	char(10)	
sim_nr	For future use	smallint	
sim_usr	For future use	integer	
verweis	Reference	serial	Unique number to access the data record. (PDM field ID: PMOD.VERWEIS)
vor_rahmenanfang	Working time before beginning of frame time	char(1)	For future use
wert	Personnel selection value	char(20)	
wochentag	Weekday	smallint	Weekday which the configuration applies for. 7 = Every day, 0 = Sunday, 1 = Monday, ..., 6 = Saturday (PDM field ID: PTMOD.WTG)
wochentage	For future use	char(7)	Weekday which the configuration applies for. 7 = Every day, 0 = Sunday, 1 = Monday, ..., 6 = Saturday (cannot yet be maintained).

12.41. pze_pst_var_kfg

Table name: pze_pst_var_kfg		Product: PZE	
Designation: Configuration of HR master info fields		Description: Configuration of additional fields within the HR master	
Column name	Column designation	Type	Description
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
feld_aktiv_1		char(1)	
feld_aktiv_10		char(1)	
feld_aktiv_11		char(1)	
feld_aktiv_12		char(1)	
feld_aktiv_13		char(1)	
feld_aktiv_14		char(1)	
feld_aktiv_15		char(1)	
feld_aktiv_16		char(1)	
feld_aktiv_17		char(1)	
feld_aktiv_18		char(1)	
feld_aktiv_19		char(1)	
feld_aktiv_2		char(1)	
feld_aktiv_20		char(1)	
feld_aktiv_21		char(1)	
feld_aktiv_22		char(1)	
feld_aktiv_23		char(1)	
feld_aktiv_24		char(1)	
feld_aktiv_25		char(1)	
feld_aktiv_26		char(1)	
feld_aktiv_27		char(1)	
feld_aktiv_28		char(1)	
feld_aktiv_29		char(1)	
feld_aktiv_3		char(1)	
feld_aktiv_30		char(1)	
feld_aktiv_4		char(1)	
feld_aktiv_5		char(1)	
feld_aktiv_6		char(1)	
feld_aktiv_7		char(1)	
feld_aktiv_8		char(1)	
feld_aktiv_9		char(1)	
feld_bez_1		char(20)	Designation
feld_bez_10		char(20)	Designation
feld_bez_11		char(20)	Designation
feld_bez_12		char(20)	Designation
feld_bez_13		char(20)	Designation

feld_bez_14		char(20)	Designation
feld_bez_15		char(20)	Designation
feld_bez_16		char(20)	Designation
feld_bez_17		char(20)	Designation
feld_bez_18		char(20)	Designation
feld_bez_19		char(20)	Designation
feld_bez_2	Designation	char(20)	Designation (PDM field ID: Designation)
feld_bez_20		char(20)	Designation
feld_bez_21		char(20)	Designation
feld_bez_22		char(20)	Designation
feld_bez_23		char(20)	Designation
feld_bez_24		char(20)	Designation
feld_bez_25		char(20)	Designation
feld_bez_26		char(20)	Designation
feld_bez_27		char(20)	Designation
feld_bez_28		char(20)	Designation
feld_bez_29		char(20)	Designation
feld_bez_3		char(20)	Designation
feld_bez_30		char(20)	Designation
feld_bez_4		char(20)	Designation
feld_bez_5		char(20)	Designation
feld_bez_6		char(20)	Designation
feld_bez_7		char(20)	Designation
feld_bez_8		char(20)	Designation
feld_bez_9		char(20)	Designation
feld_feldname_1		char(18)	column name incl. database.
feld_feldname_10		char(18)	column name incl. database.
feld_feldname_11		char(18)	column name incl. database.
feld_feldname_12		char(18)	column name incl. database.
feld_feldname_13		char(18)	column name incl. database.
feld_feldname_14		char(18)	column name incl. database.
feld_feldname_15		char(18)	column name incl. database.
feld_feldname_16		char(18)	column name incl. database.
feld_feldname_17		char(18)	column name incl. database.
feld_feldname_18		char(18)	column name incl. database.
feld_feldname_19		char(18)	column name incl. database.
feld_feldname_2		char(18)	column name incl. database.
feld_feldname_20		char(18)	column name incl. database.
feld_feldname_21		char(18)	column name incl. database.
feld_feldname_22		char(18)	column name incl. database.
feld_feldname_23		char(18)	column name incl. database.
feld_feldname_24		char(18)	column name incl. database.
feld_feldname_25		char(18)	column name incl. database.
feld_feldname_26		char(18)	column name incl. database.
feld_feldname_27		char(18)	column name incl. database.

feld_feldname_28		char(18)	column name incl. database.
feld_feldname_29		char(18)	column name incl. database.
feld_feldname_3		char(18)	column name incl. database.
feld_feldname_30		char(18)	column name incl. database.
feld_feldname_4		char(18)	column name incl. database.
feld_feldname_5		char(18)	column name incl. database.
feld_feldname_6		char(18)	column name incl. database.
feld_feldname_7		char(18)	column name incl. database.
feld_feldname_8		char(18)	column name incl. database.
feld_feldname_9		char(18)	column name incl. database.
feld_len_1		smallint	Field length
feld_len_10		smallint	Field length
feld_len_11		smallint	FField length
feld_len_12		smallint	Field length
feld_len_13		smallint	Field length
feld_len_14		smallint	Field length
feld_len_15		smallint	Field length
feld_len_16		smallint	Field length
feld_len_17		smallint	Field length
feld_len_18		smallint	Field length
feld_len_19		smallint	Field length
feld_len_2		smallint	Field length
feld_len_20		smallint	Field length
feld_len_21		smallint	Field length
feld_len_22		smallint	Field length
feld_len_23		smallint	Field length
feld_len_24		smallint	Field length
feld_len_25		smallint	Field length
feld_len_26		smallint	Field length
feld_len_27		smallint	Field length
feld_len_28		smallint	Field length
feld_len_29		smallint	Field length
feld_len_3		smallint	Field length
feld_len_30		smallint	Field length
feld_len_4		smallint	Field length
feld_len_5		smallint	Field length
feld_len_6		smallint	Field length
feld_len_7		smallint	Field length
feld_len_8		smallint	Field length
feld_len_9		smallint	Field length
feld_typ_1		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_10		char(1)	C' = text field N' = Numerical field D' = date

feld_typ_11		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_12		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_13		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_14		char(1)	'C' = Textfeld 'N' = Numerisches Feld 'D' = Datum
feld_typ_15		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_16		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_17		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_18		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_19		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_2		char(1)	'C' = text field 'N' = Numerical field 'D' = date
feld_typ_20		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_21		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_22		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_23		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_24		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_25		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_26		char(1)	'C' = Textfeld 'N' = Numerisches Feld 'D' = Datum
feld_typ_27		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_28		char(1)	C' = text field N' = Numerical field D' = date

feld_typ_29		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_3		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_30		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_4		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_5		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_6		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_7		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_8		char(1)	C' = text field N' = Numerical field D' = date
feld_typ_9		char(1)	C' = text field N' = Numerical field D' = date
feld_vorgabe_1		char(20)	Default value
feld_vorgabe_10		char(20)	Default value
feld_vorgabe_11		char(20)	Default value
feld_vorgabe_12		char(20)	Default value
feld_vorgabe_13		char(20)	Default value
feld_vorgabe_14		char(20)	Default value
feld_vorgabe_15		char(20)	Default value
feld_vorgabe_16		char(20)	Default value
feld_vorgabe_17		char(20)	Default value
feld_vorgabe_18		char(20)	Default value
feld_vorgabe_19		char(20)	Default value
feld_vorgabe_2		char(20)	Default value
feld_vorgabe_20		char(20)	Default value
feld_vorgabe_21		char(20)	Default value
feld_vorgabe_22		char(20)	Default value
feld_vorgabe_23		char(20)	Default value
feld_vorgabe_24		char(20)	Default value
feld_vorgabe_25		char(20)	Default value
feld_vorgabe_26		char(20)	Default value
feld_vorgabe_27		char(20)	Default value
feld_vorgabe_28		char(20)	Default value
feld_vorgabe_29		char(20)	Default value
feld_vorgabe_3		char(20)	Default value
feld_vorgabe_30		char(20)	Default value
feld_vorgabe_4		char(20)	Default value

feld_vorgabe_5		char(20)	Default value
feld_vorgabe_6		char(20)	Default value
feld_vorgabe_7		char(20)	Default value
feld_vorgabe_8		char(20)	Default value
feld_vorgabe_9		char(20)	Default value
kennung		integer	1: Additional fields within the HR master 100: Additional fields within the badge of the access control system
verantw_bereich_1		char(15)	
verantw_bereich_10		char(15)	
verantw_bereich_11		char(15)	
verantw_bereich_12		char(15)	
verantw_bereich_13		char(15)	
verantw_bereich_14		char(15)	
verantw_bereich_15		char(15)	
verantw_bereich_16		char(15)	
verantw_bereich_17		char(15)	
verantw_bereich_18		char(15)	
verantw_bereich_19		char(15)	
verantw_bereich_2		char(15)	
verantw_bereich_20		char(15)	
verantw_bereich_21		char(15)	
verantw_bereich_22		char(15)	
verantw_bereich_23		char(15)	
verantw_bereich_24		char(15)	
verantw_bereich_25		char(15)	
verantw_bereich_26		char(15)	
verantw_bereich_27		char(15)	
verantw_bereich_28		char(15)	
verantw_bereich_29		char(15)	
verantw_bereich_3		char(15)	
verantw_bereich_30		char(15)	
verantw_bereich_4		char(15)	
verantw_bereich_5		char(15)	
verantw_bereich_6		char(15)	
verantw_bereich_7		char(15)	
verantw_bereich_8		char(15)	
verantw_bereich_9		char(15)	

12.42. pze_tnr_info_konfig

Table name: pze_tnr_info_konfig		Product: PZE	
Designation: Configuration terminal information		Description: By using the "configuration of terminal information" function employees and groups of employees can define which accounts are displayed with which designation on the Time & Attendance terminal. # Key verweis (unique) firm, bezug, wert, priorität	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created tim	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bemerkung	Comment	char(100)	
bezeichnung01	Info item designation	char(40)	
bezeichnung02	Info item designation	char(40)	
bezeichnung03	Info item designation	char(40)	
bezeichnung04	Info item designation	char(40)	
bezeichnung05	Info item designation	char(40)	
bezeichnung06	Info item designation	char(40)	
bezeichnung07	Info item designation	char(40)	
bezeichnung08	Info item designation	char(40)	
bezeichnung09	Info item designation	char(40)	
bezeichnung10	Info item designation	char(40)	
bezeichnung11	Info item designation	char(40)	
bezeichnung12	Info item designation	char(40)	
bezug	Personnel selection key	char(20)	
bezug01	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug02	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug03	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug04	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug05	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug06	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug07	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug08	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug09	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug10	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug11	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
bezug12	Info item selection key	char(10)	Currently only 'KTO' is supported for account number in value
firma	Company	char(4)	
gueltig_bis	Valid until	date	

gueltig_von	Valid from	date	
personalnummer	Personnel number	integer	
prioritaet	Priority	smallint	
verweis	Reference	serial	Internal unique number of the record
wert	Personnel selection value	char(20)	
wert01	Info item selection value	char(10)	
wert02	Info item selection value	char(10)	
wert03	Info item selection value	char(10)	
wert04	Info item selection value	char(10)	
wert05	Info item selection value	char(10)	
wert06	Info item selection value	char(10)	
wert07	Info item selection value	char(10)	
wert08	Info item selection value	char(10)	
wert09	Info item selection value	char(10)	
wert10	Info item selection value	char(10)	
wert11	Info item selection value	char(10)	
wert12	Info item selection value	char(10)	

12.43. pze_ubez_pause

Table name: pze_ubez_pause		Product: PZE	
Designation: Unpaid breaks		Description: Allocation of breaks subject to the rendered working time.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
az_unterbrechung	Consider interruptions of work outside of break frame	char(1)	
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich		char(8)	Designation of the area. (PDM field ID: PAUUBEZ.BER)
datum_bis		date	Validity period for the break depending on working time (not yet processed).
datum_von		date	Validity period for the break depending on working time (not yet processed). (PDM field ID: PAUUBEZ.DATB)
firma	Company	char(4)	Designation of the company. (PDM field ID: PAUUBEZ.FIR)
istzeit	Working time	integer	Time in seconds till that the break is allocated. (PDM field ID: PAUUBEZ.IZ)
nur_komplett	Allocate break completely when working time is exceeded	char(1)	J=The break is either posted completely or not at all.. N=The break is also posted partially. (PDM field ID: PAUUBEZ.OPT:KOMPLETT)
pause	Break	integer	Break time in seconds (PDM field ID: PAUUBEZ.PAU)
typkz		char(1)	This field always contains a 'G'.
typnr		smallint	Number of the working time day type for which the break should apply (not yet processed). (PDM field ID: PAUUBEZ.GLZTMOD)
verweis	Reference	serial	Unique key to access the data record.
wenn_keine_pause	Allocate only if no break is planned	char(1)	J: Break is only allocated if no other break is configured in the working time model. N: Break is even allocated if other breaks are defined in the working time model. (PDM field ID: PAUUBEZ.OPT:PAU)

12.44. pze_url_anspruch

Table name: pze_url_anspruch		Product: PZE	
Designation: Leave entitlement			
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezug	Personnel selection key	char(20)	
bezug2	Reference	char(1)	A: Age D: Staff membership
firma	Company	char(4)	
gueltig_bis	Valid until	date	
gueltig_von	Valid from	date	
konto	for future use	smallint	
personalnummer	Personnel number	integer	
prioritaet	Priority	smallint	
sonderurl_anspruch	Special leave	integer	
url_anspruch	Annual leave	integer	
verr_datum	for future use	date	
verweis	Reference	serial	
wert	Personnel selection value	char(20)	
wert2	Value	integer	
zusatzurl_anspruch	Additional leave	integer	

12.45. pze_ztnw_liste

Table name: pze_ztnw_liste		Product: PZE	
Designation: Configurable time sheet - lists		Description: The available time sheets are filed in this table. # Special remarks In earlier versions the layout of time sheets has been defined here. In current versions the layout of the lists is not within the database but is configured with a report designer in the user interface. Thus many columns are obsolete. # Key liste_nr # Connections to other tables liste_nr = pze_ztnw_spalte.liste_nr	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
archivierungsmodus	Obsolete	char(1)	Start time sheet in archiving mode (J/N)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich	Obsolete	char(8)	Default of input parameters when starting the list (no yet used).
bezeichnung	Designation	char(40)	Designation of the time sheet (PDM field ID: ZNWLCFG.BEZ)
firma	Obsolete	char(4)	Default of input parameters when starting the list (no yet used).
gr_lohnart	Wage type group	char(4)	Wage type group for the display of montly wage types at the end of the time sheet.
im_dauer	Obsolete	char(1)	Specification for the display of terms in industrial minutes (J/N)
im_zeit	Obsolete	char(1)	Vorgabe für die Darstellung von Uhrzeiten in Industrieminuten (J/N)
konfig	Period	char(10)	Internal configuration flag. - First character (konfig[1]): "J": Daily time sheet (daily overview) Otherwise: monthly time sheet - konfig[2,5]: wage type group for monthly wage types. (PDM field ID: ZNWLCFG.OPT:TGL, ZNWLCFG.LARTGRP)
kontostand_anfang	Obsolete	char(1)	Not used (account balances at the beginning/end of the month are configured via lines)
kontostand_ende	Obsolete	char(1)	Not used (account balances at the beginning/end of the month are configured via lines)
kontostand_votr	Obsolete	char(1)	Not used (account balances at the beginning/end of the month are configured via lines)
kostenstelle	Obsolete	char(10)	Default of input parameters when starting the list (no yet used).
kstwechsel_ausbl	Wage type group	char(1)	
liste_nr	Time sheet	smallint	Unique number of the time sheet (PDM field ID: ZNWLCFG.ZNWL)
person_bis	Obsolete	integer	Default of input parameters when starting the list (no yet used).
person_von	Obsolete	integer	Default of input parameters when starting the list (no yet used).
querformat	Obsolete	char(1)	Printing in landscape format (J/N) (PDM field ID: ZNWLCFG.OPT:QUER)
seitenlaenge	Obsolete	smallint	Setting of the lines per page

summenzeile	Obsolete	char(1)	Display line totals at the end of clockings (J/N) (PDM field ID: ZNWLCFG.OPT:SUM)
tage_ohne_stemp	Obsolete	char(1)	Display days without clockings (J/N) (not yet processed)
verantw_bereich	Responsibility area	char(15)	
verarb_intern	Obsolete	char(1)	Internal processing flag "Q": Time sheet is new time sheet as data source. Otherwise: Time sheet is old time sheet and may not be used by BAPIs. (PDM field ID: (internal))
wochensumme	Obsolete	char(1)	Display subtotals on the basis of weeks (J/N) (not yet processed) (PDM field ID: ZNWLCFG.OPT:WSUM)

12.46. pze_ztnw_spalte

Table name: pze_ztnw_spalte		Product: PZE	
Designation: Configurable time sheet - columns		Description: Definition of up to 20 customer specific columns in time sheet. # Special remarks In earlier versions the complete layout of time sheet columns has been defined here. In current versions the layout of the lists is not within the database but is configured with a report designer in the user interface. Thus many columns are obsolete. # Key liste_nr, spalte_nr # Connections to other tables pze_ztnw_liste.liste_nr = pze_ztnw_spalte.liste_nr	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
breite	Obsolete	smallint	(PDM field ID: ZNWLCOL.X)
druckformat	Obsolete	char(1)	
im_param	Obsolete	char(1)	(PDM field ID: ZNWLCOL.IM)
kennung	Obsolete	char(40)	
liste_nr	List ID, fixed 10000	smallint	(PDM field ID: ZNWLCOL.ZNWL)
param_char	Parameter	char(20)	Wage type or wage type group (PDM field ID: ZNWLCOL.STR:1)
param_long1	Obsolete	integer	(PDM field ID: ZNWLCOL.NUM:1)
param_long2	Obsolete	integer	(PDM field ID: ZNWLCOL.NUM:2)
spalte_nr	Column number	smallint	(PDM field ID: ZNWLCOL.COL)
typ	Column type	char(4)	LA: Wage type LAGR: Wage type group (PDM field ID: ZNWLCOL.ART)
ueberschrift1	Obsolete	char(50)	
ueberschrift2	Obsolete	char(50)	

12.47. pzebuchung

Table name: pzebuchung		Product: PZE	
Designation: Daily wage type postings		Description: Wage types accumulated during the "labor time calculation" (part posting of wage types) including the time interval during which an employee worked for this wage type. Note: To ensure data consistency, the duration of the data record must always correspond to the difference between the end time and the start time. buch_dauer = buch_ende - buch_anfang # Key personalnummer, aw_datum (not unique) # Connections to other tables 1) personen.personalnummer = personalnummer and aw_datum between personen.gueltig_von and personen.gueltig_bis 2) lohnart = lohnarten.lohnart 3) Outer join: verweis_stempel = stempelsaetze.verweis	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausf_kostenstelle	For future use	char(10)	
aw_datum	Settlement date	date	Assigned evaluation day (PDM field ID: PZEBUCH.ABREDAT)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
buch_anfang	Start time	integer	Seconds as of midnight on the evaluation day. May be negative for time stamps of the day before or greater 24:00 for time stamps of the next day. Note: To ensure data consistency, the duration of the data record must always correspond to the difference between the end time and the start time. buch_dauer = buch_ende - buch_anfang (PDM field ID: PZEBUCH.ZEIB)
buch_dauer	Duration	integer	Note: To ensure data consistency, the duration of the data record must always correspond to the difference between the end time and the start time. buch_dauer = buch_ende - buch_anfang (PDM field ID: PZEBUCH.DAUER)
buch_ende	End time	integer	Seconds as of midnight on the evaluation day. May be negative for time stamps of the day before or greater 24:00 for time stamps of the next day. Note: To ensure data consistency, the duration of the data record must always correspond to the difference between the end time and the start time. buch_dauer = buch_ende - buch_anfang (PDM field ID: PZEBUCH.ZEIE)
certify_flag	Authorization required	char(1)	Authorization required (J=Yes, N=No). (PDM field ID: PZEBUCH.CERTIFY)
erf_leistgrp	For future use	char(8)	

firma	Company	char(4)	Person's company (not yet processed) (PDM field ID: PZEBUCH.FIR)
fn_kz	Internal processing indicator (posting origin)	char(1)	F = posting on fixed times in the payment day type N = posting on rework times/target working times K = posting as violation of the core time
gebuchtkz	Internal processing indicator (posting mark)	char(1)	A = compensation by overtime type L = standard assignment; it is a wage type posting. S = posting used for filling up the target time Z = Obsolete: Pposting generated via the module "post wage types additionally". empty = the posting was created manually.
grundlohnkz	Type	char(1)	Comes from lohnarten.grundlohn: Basic wage = "G"; bonus wage = "Z"; break = "P" (PDM field ID: PZEBUCH.OPT:LOHN)
kost_firma	Cost center of the company	char(4)	Company of the cost center (PDM field ID: PZEBUCH.FIR:KST)
kostenstelle	Cost center	char(10)	 (PDM field ID: PZEBUCH.KST)
leistgrp	For future use	char(8)	
lohnart	Wage type	char(4)	 (PDM field ID: PZEBUCH.LART)
personalnummer	Personnel number	integer	Person for that this data record applies. (PDM field ID: PZEBUCH.PNR)
prozent	Percentage	smallint	Percentage for the wage type. This field corresponds to the field prozent in the table lohnarten_zuord. (PDM field ID: PZEBUCH.PROZ)
schichtart	For future use	char(1)	
sign_flag	Authorized	char(1)	Flag whether this record was authorized: "J": The record has been approved. "A": The record has been rejected. "N": The record has so far neither been approved nor rejected. (PDM field ID: PZEBUCH.SIGN)
stempelart	Origin	char(1)	'K' = Attendance time 'F' = Absence time 'M' = Manual posting (PDM field ID: PZEBUCH.ART:STMP)
ueberstkz	Overtime indicator	char(1)	Targeted work = 'S'; overtime = 'M' (PDM field ID: PZEBUCH.OPT:MEHRARB)
user_c_09	Customer specific column	char(20)	For future use
user_c_10	Customer specific column	char(40)	For future use
user_d_01	Customer specific column	date	For future use
user_d_02	Customer specific column	date	For future use
user_f_07	Customer specific column	decimal(18,6)	For future use
user_f_08	Customer specific column	decimal(18,6)	For future use
user_n_03	Customer specific column	integer	For future use
user_n_04	Customer specific column	integer	For future use
user_n_05	Customer specific column	integer	For future use
user_n_06	Customer specific column	integer	For future use
verweis	Reference	serial	Unique record number (PDM field ID: PZEBUCH.VERWEIS)
verweis_stempel	Reference to clocking	integer	Reference to the corresponding clocking record. (PDM field ID: PZEBUCH.VERWEIS:STMP)
vor_sollanfang	Obsolete	char(1)	Obsolete: Time before the target start
zusatzkz	Internal processing indicator (overtime compensation flag)	char(1)	P = wage type from the overtime compensation. empty = normal posting

12.48. pzt_kenn

Table name: pzt_kenn		Product: PZE	
Designation: PZE shop floor terminal		Description: Properties for the PZE terminal. The terminal's mode of operation is defined here.	
Column name	Column designation	Type	Description
abteilung	Betriebsart	char(3)	Internal indication which program is to be loaded by the terminal. (operation mode) default = "AST" (PDM field ID: TNR.PZEBART)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
berecht_laden_1		integer	
berecht_laden_2		integer	
berecht_laden_3		integer	
berecht_laden_4		integer	
berecht_laden_5		integer	
berecht_laden_6		integer	
bezeichnung	Terminal-Bezeichnung	char(20)	Designation of the terminal. (PDM field ID: TNR.BEZO)
dienstg_pause	(reserviert)	char(1)	For future use
firmen_nr	HYD:Firmennummer / Systemnummer	char(5)	Not yet used. At the moment setup.firmen_nr is only read out. When printing personal badges the company number precedes the badge number. The company number is checked when reading in the badge number if this one is defined in the system. (PDM field ID: TNR.SYSNR)
info1anfang	Zeitraum für Anzeige der Informationen	integer	Time for displaying information on the terminal. (PDM field ID: TNR.INFOZEIB:1)
info1ende	Zeitraum für Anzeige der Informationen	integer	Time for displaying information on the terminal. (PDM field ID: TNR.INFOZEIE:1)
info2anfang	Zeitraum für Anzeige der Informationen	integer	Time for displaying information on the terminal. (PDM field ID: TNR.INFOZEIB:2)
info2ende	Zeitraum für Anzeige der Informationen	integer	Time for displaying information on the terminal. (PDM field ID: TNR.INFOZEIE:2)
info3anfang	Zeitraum für Anzeige der Informationen	integer	Time for displaying information on the terminal. (PDM field ID: TNR.INFOZEIB:3)
info3ende	Zeitraum für Anzeige der Informationen	integer	Time for displaying information on the terminal. (PDM field ID: TNR.INFOZEIE:3)
info4anfang	Zeitraum für Anzeige der Informationen	integer	Time for displaying information on the terminal. (PDM field ID: TNR.INFOZEIB:4)
info4ende	Zeitraum für Anzeige der Informationen	integer	Time for displaying information on the terminal. (PDM field ID: TNR.INFOZEIE:4)
info5anfang	Zeitraum für Anzeige der Informationen	integer	Period for displaying information on the terminal. Up to five periods are possible. (PDM field ID: TNR.INFOZEIB:5)
info5ende	Zeitraum für Anzeige der Informationen	integer	Period for displaying information on the terminal. End of the first period when the info button is active on the terminal. (PDM field ID: TNR.INFOZEIE:5)

info_kfg		char(3)	[1,1] "S" for displaying the last clocking in connection with the next field ->ID: TNR.PZEINFO:CFG [2,2] "J" for displaying the evaluation status on the terminal. ->ID: TNR.OPT:ABREDAT [3,3] "I" for displaying account balances in industrial minutes format. default = "" (PDM field ID: (Composed of several acronyms))
info_nr	Zusatzfunktion	smallint	1 = clocking information. Display of the last clocking records. default = 1 (PDM field ID: TNR.PZEINFO:NR)
konfig_1	Konfiguration 1	char(3)	[1,1] Configuration of the entry of absence reasons: - empty = no absence reason list - 1=Variant 1 (CT33x / CPM only) - 2=Variant 2 (CT33x / CPM only) - 3=Absence reason list (not CT33x / CPM) -> ID: TNR.FGRCFG [2,2] - empty = off - G = on: activate entry of absence reason if beyond planned time. ->ID: TNR.OPT:FGRAUTO (PDM field ID: (Composed of several acronyms))
konfig_2	Konfiguration 2	char(3)	"EPR" (alternative badge, plausibility checks, configuration of info display on the CPM terminal) [1,1] E: alternative badge processing possible; ->ID: TNR.PLAUS:PZEONL [2,2] Plausibility check P: for clocking-in on the same terminal S: for status sequence empty: none ->ID: TNR.PLAUS:PZESTA [3,3] Display of information: (CT33x only) R: remaining leave only N: anything except for remaining leave empty: anything ->ID: TNR.PZEINFO:LAY default = " " default = " " (PDM field ID: (Composed of several acronyms))
kostenstelle	Cost center	char(10)	
kurzbez	Standort/Terminalkurzbezeichnung	char(20)	Location of the terminal. (PDM field ID: TNR.BEZX)
leistgrp		char(8)	
meldezeit	(reserviert)	smallint	For future use
param_1	Relaiszeit	smallint	- Relay time door opener default = 2 (PDM field ID: TNR.RELZUG:DAUER)
param_2	Rücksprungzeit in Vorgabestatus	smallint	General return time for display output (return time to access) default = 5 (PDM field ID: TNR.PZESTA:DAUER)
param_3	Info-Anzeigedauer	smallint	Display duration of the information default = 8 (PDM field ID: TNR.PZEINFO:DAUER)
status_1	Fehlgrund 1	char(4)	Absence reason 1 to 4 (PDM field ID: TNR.FGR:1)

status_2	Fehlgrund 2	char(4)	Absence reason 1 to 4 (PDM field ID: TNR.FGR:2)
status_3	Fehlgrund 3	char(4)	Absence reason 1 to 4 (PDM field ID: TNR.FGR:3)
status_4	Fehlgrund 4	char(4)	Absence reason 1 to 4 (PDM field ID: TNR.FGR:4)
status_kfg	(reserviert)	smallint	For future use
text_nachricht	Message key	char(20)	
text_taste1	Text Taste 1 (KOMMT)	char(20)	Display text when clicking the button 1 (top left); processing mode as clocking-in does not depend on this. Default = "clock-in" (PDM field ID: TNR.TTXT:KOM)
text_taste2	Text Taste 2 (GEHT)	char(20)	Display text when clicking the button 2 (top right); processing mode as clocking-out does not depend on this. Default = "clock-out" (PDM field ID: TNR.TTXT:GEH)
text_taste3	Text Taste 3 (PAUSE/GEHT)	char(20)	Display text when clicking the button 3 (center left), processing mode as break (clocking-out) does not depend on this. default = "break" (PDM field ID: TNR.TTXT:PAU)
text_taste4	Text Taste 4 (INFO)	char(20)	Display text when clicking the button 4 (center right); processing mode as information does not depend on this. default = "Info" (PDM field ID: TNR.TTXT:INFO)
text_taste5	Fehlgrundtext 1	char(20)	Display text when clicking the button 5 (down left); processing mode does not depend on this. (PDM field ID: TNR.TTXT:FGR1)
text_taste6	Fehlgrundtext 2	char(20)	Display text when clicking the button 6 (2nd button from down left); processing mode does not depend on this. (PDM field ID: TNR.TTXT:FGR2)
text_taste7	Fehlgrundtext 3	char(20)	Display text when clicking the button 7; processing mode does not depend on this. (PDM field ID: TNR.TTXT:FGR3)
text_taste8	Fehlgrundtext 4	char(20)	Display text when clicking the button 8 (down right); processing mode does not depend on this. (PDM field ID: TNR.TTXT:FGR4)
text_vorgabestatus	Text for default status	char(20)	
usernr	Terminalnummer	smallint	User number set on the terminal. (PDM field ID: TNR.TNR)
verarbzk	Dekodertyp (?)	smallint	(still being used? ELIN software decoder) "1": The terminal decodes barcodes with a software decoder. "10": The device is equipped with a hardware decoder for barcodes.
vorgabe_status	(reserviert)	char(1)	Empty: According to operation mode K: Clocking-in G: Clocking-out P: Break I: Info A: Auto status Z: Access default = "" default = "" (PDM field ID: TNR.PZESTA:VORG)
zusatz_text		char(20)	Is preassigned to "" when creating. [1,1] For the CT380 and CT360 the additional text has the following meaning: "F": entered texts are interpreted as French "E": entered texts are interpreted as English Otherwise: Entered texts are interpreted as German
zyklload	Zyklisch Ladezeit PZE-Konfiguration	integer	Indication in seconds how often the terminal reloads its configuration. default = 3600 (PDM field ID: TNR.ZYKLLOAD:PZE)

12.49. schichtrythmus

Table name: schichtrythmus		Product: PZE	
Designation: Shift rhythm on annual basis		Description: Determination of the shift sequence for shift workers on annual basis. A shift type is assigned to each day of the year within the shift rhythm year model.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
art	Type	char(1)	Determination whether it is an 'J' annual model, 'W' week model or a 'Z' period model (currently not yet processed).
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bez_ausf	Designation	char(40)	Designation (PDM field ID: SCHZARTJMOD.BEZL)
bez_kurz	Short designation	char(6)	Designation (PDM field ID: SCHZARTJMOD.BEZX)
gueltig_bis		date	Validity period of the model (currently not yet processed).
gueltig_von		date	Validity period of the model (currently not yet processed).
jahr		smallint	Year that the table entry applies for. (PDM field ID: SCHZARTJMOD.JAHR)
modellnummer	Model	smallint	Unique number of the entry within the indicated year. (PDM field ID: SCHZARTJMOD.SCHZARTJMOD)
referenz_datum	Reference date	date	Reference date for period models. The defined period starts on the reference date and is repeated as often as required.
schichtart	Model	char(1999)	Character string with 366 characters. Each day is considered with a character. The character refers to the field schicht_art in the gltzeittagestyp table. (PDM field ID: SCHZARTJMOD.MODELL)
verantw_bereich		char(15)	Responsibility area which the shift rhythm year model is assigned to.
verweis		serial	

12.50. st_attribut

Table name: st_attribut		Product: PZE	
Designation: Absence reason		Description: Configuration of absence reasons for advance and subsequent postings on the terminal.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bezeichnung	Designation	char(40)	(PDM field ID: FGR.BEZL)
certify_flag	Authorization required	char(1)	Flag whether this posting is subject to authorization. (PDM field ID: FGR.CERTIFY)
ereignis	Absence reason	char(4)	Identification of the absence reason. (PDM field ID: FGR.FGR)
firma	Company	char(4)	Designation of the company (PDM field ID: FGR.FIR)
gueltig_bis	For future use	date	Period for which the absence reason applies. The two date fields can also be empty. (These fields are currently not yet processed). (PDM field ID: FGR.DATE)
gueltig_von	For future use	date	Period for which the absence reason applies. The two date fields can also be empty. (These fields are currently not yet processed). (PDM field ID: FGR.DATB)
konfig	Process indicators	char(10)	The first letter is used for administration if it is an SAP subsystem. The second or third letter defines when a subsequent postings starts or an advance posting ends: "R": The absence reason starts at the earliest at the beginning of skeleton time or ends at the end of skeleton time at the latest. "N" the absence reason starts at the beginning of normal time at the earliest or finishes at the end of normal time at the latest. "K" the absence reason starts at the beginning of the core time at the earliest or finishes at the end of the core time at the latest. Acronym for start: FGR.EINBL Acronym for end: FGR.AUSBL In the fourth letter it is defined whether the absence reason is to be processed like an absence planning. Thus, half days of leave can be entered on the terminal. ID: FGR.VERB:FZ (PDM field ID: FGR.EINBL, FGR.AUSBL, FGR.VERB:FZ)
lost	Payment day type	smallint	(PDM field ID: FGR.ENTLTMOD)
sap_logical_system	SAP subsystem indicator	char(10)	Assignment of the absence reason to a logical system for SAP subsystems.
sprache	SAP subsystem indicator	char(3)	Language key for absence reasons from SAP.
st_bedeutung	Meaning	char(1)	Meaning of the generated absence record F = Absence record K = Presence record D = Short business trip (PDM field ID: FGR.ART)
verantw_bereich	Responsibility area	char(15)	
verarbeitung	For future use	char(1)	Not used at the moment

weiterbuch	Post on	char(1)	"J": Absence reason is also used for the following absence days. "G": Absence reason is only used for following absence days. Otherwise: Absence reason is only used for the first day. (PDM field ID: FGR.WEITERVERB)
------------	---------	---------	---

12.51. stempelsaetze

Table name: stempelsaetze		Product: PZE	
Designation: Clocking records		Description: Entry of clocking times that are reported by the terminal. In each case a clocking-in time and a clocking-out time is saved within a data record as a pair of clockings. # Special remarks Single clockings are combined into pairs. Data of clock in is stored in columns *_1, data of clock out is stored in columns *_2. As long as single clocking events cannot be combined into pairs columns *_1 and *_2 contain the same values (time of clock in = time of clock out). Whether the pair is complete or not is indicated by column bedeutung. # Keys: personalnummer, stempeldatum_1 personalnummer, aw_tag verweis (unique) # Connections to other tables personen.personalnummer = personalnummer and stempeldatum_2 between personen.gueltig_von and personen.gueltig_bis	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
antrag_ts	Time stamp of application	datetime	
arbeitstag_anfang	Date of clock in rounded	date	Clocking-in rounded by the daily evaluation. The date is stated. (PDM field ID: STMP.ABREDATB)
arbeitstag_ende	Date of clocking-out rounded	date	Clocking-out rounded by daily evaluation. The date is stated. (PDM field ID: STMP.ABREDATE)
arbeitszeit_anfang	Time of clock in rounded	integer	Cocking-in rounded by the daily evaluation. Seconds since midnight are stated. (PDM field ID: STMP.ABREZEIB)
arbeitszeit_ende	Time of clocking-out rounded	integer	Clocking-out rounded by daily evaluation. Seconds since midnight are stated. (PDM field ID: STMP.ABREZEIE)
auftrag_nr	Not used at the moment.	char(40)	Not used at the moment.
ausf_kostenstelle	Not used at the moment.	char(10)	
ausgewertet	For future use	char(1)	Reserved.
aw_tag	Settlement date	date	Work day which the clocked time belongs to. The work day is defined by the daily evaluation. (PDM field ID: STMP.ABREDAT)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bedeutung	Type of data record	char(1)	Type of pair of clockings: K: Attendance (Clock In + Clock Out) k: Only Clock-in g: Only Clock-out F: Absence D: Business trip d: Start of Business trip (PDM field ID: STMP.ART)

bemerkung	Commentary	char(40)	Comment to the clocking. (PDM field ID: STMP.BEM)
certify_flag	Authorization required	char(1)	Flag whether this clocking is subject to authorization. (J/N or empty). (PDM field ID: (STMP.CERTIFY))
durchschn_art	Not used at the moment.	char(1)	Not used at the moment.
erf_kostenstelle	Recorded cost center	char(10)	
erf_leistgrp	For future use	char(8)	
fehlzeit_ungeplant	Unplanned absence indicator	char(1)	Flag whether it is an unplanned absence (J/N)
firma	Company	char(4)	Company which this person belongs to (filled optionally). (PDM field ID: STMP.FIR)
gleitzeittyp	Working time day type	smallint	Reference to the working time day type which the daily evaluation uses; typnummer field in gltzeittagestyp table. (PDM field ID: STMP.GLZTMOD)
kommentar	Abbreviation	char(3)	In case of absences the commentary from the absence planning is transferred to this field. (PDM field ID: STMP.BEZK)
kost_firma	Company of the cost center	char(4)	 (PDM field ID: STMP.FIR:KST)
kostenstelle	Cost center	char(10)	Cost center on which the person is working. This column is filled by the labor time calculation (PDM field ID: STMP.KST)
kz_ch1	Internal processing indicator	char(10)	H: Absence is half a leave day T: Absence results of a partly-day absence planning
kz_ch2	Customer specific use	char(10)	Executing cost center
kz_long1	Free break	integer	Contains the free break that was allocated at this clocking.
kz_long2	Not used at the moment.	integer	Not used at the moment
leistgrp	For future use	char(8)	
lle_kz	Not used at the moment.	char(1)	Not used at the moment
lohnart	Obsolete!	char(4)	Obsolete: Wage type that was posted onto during the advance or subsequent posting (not processed anymore).
lohnstatustyp	Payment day type	smallint	Reference to the payment day type that the labor time calculation uses; typnummer field in lohnarten_zuord table. In case of absences the payment day type defines the reason for the absence. (PDM field ID: STMP.ENTLTMOD)
nachbuch	Absence reason (subsequent)	char(4)	Absence reason of the advance or subsequent posting which this posting results from. This column is only filled when subsystem to SAP-HR is active in basic settings.
personalnummer	Personnel number	integer	Person who did the clocking. (PDM field ID: STMP.PNR)
rueckgemeldet_1	Upload flag for clocking-in	char(1)	J = clocking has been uploaded and may not be edited. X = clocking is blocked (not yet processed at the moment, intended only, e.g. for subsequent posting). (PDM field ID: STMP.RM:KOM)
rueckgemeldet_2	Upload flag for clocking-out	char(1)	J = clocking has been uploaded and may not be edited. X = clocking is blocked (not yet processed at the moment, intended only, e.g. for subsequent posting). (PDM field ID: STMP.RM:GEH)
satzquelle	Status	char(1)	Indication of the origin of the record. O = Original and active clocking A = Generated automatically E = Edited C = Applied correction L = Deleted. Deleted original clockings remain within the database with the record source 'L'. Before PZW 8.1: "Paid breaks" are identified with bedeutung='K' and have the status 'A'. (PDM field ID: STMP.ERFART)
schichtart	Shift type	char(1)	Reference to the shift type that the daily evaluation uses, e.g. early, late or night shift; schichtart field in gltzeittagestyp table. (PDM field ID: STMP.SCHZART)
schichtzeittyp	Obsolete!	smallint	Obsolete
sign_flag	Athorized	char(1)	Flag whether this record was authorized: "J": The clocking has been approved. "A": The clocking has been rejected. "N": The clocking has so far neither been approved nor rejected. (PDM field ID: STMP.SIGN)

sommerwinterzeit_1	DST of clock in	char(1)	Indication whether the clocking-in was made during daylight saving time (S) or winter time (W). (PDM field ID: STMP.SOWIB)
sommerwinterzeit_2	DST clock out	char(1)	Indication whether clocking-out was made during daylight saving time (S) or winter time (W). (PDM field ID: STMP.SOWIE)
speicherdatum_1	Clock in saving date	date	
speicherdatum_2	Clock out saving date	date	
speicherzeit_1	Clock in saving time	integer	
speicherzeit_2	Clock in saving time	integer	
stempeldatum_1	Date of clock in	date	Date of clocking-in. (PDM field ID: STMP.DATB)
stempeldatum_2	Date of clocking-out	date	Date of clocking-out. Cannot be set via Bapi; is computed. (PDM field ID: #STMP.DATE#)
stempeldauer	Duration	integer	Duration of clocking in seconds (after daily evaluation). (PDM field ID: STMP.DAUER)
stempelstatus_1	Original status of clocking-in	char(1)	K = Clock in K = Clock out P = Break F = Advance or subsequent clocking A = Automatic status
stempelstatus_2	Original status of clocking-out	char(1)	K = Clock in K = Clock out P = Break F = Advance or subsequent clocking A = Automatic status
stempelzeit_sec_1	Time of the clocking-in (seconds)	smallint	The time is (hours*3600)+seconds (PDM field ID: STMP.ZEIB)
stempelzeit_sec_2	Time of the clocking-out (seconds)	smallint	The time is (hours*3600)+seconds (PDM field ID: STMP.ZEIE)
stempelzeit_std_1	Time of the clocking-in (hours)	smallint	The time is (hours*3600)+seconds
stempelzeit_std_2	Time of the clocking-out (hours)	smallint	The time is (hours*3600)+seconds
terminal_1	Terminal number of clock in	smallint	Terminal number of the first clocking.
terminal_2	Terminal number of clock out	smallint	Terminal number of the second clocking.
unbezahlte_pause	Unpaid break	integer	Duration of unpaid break.
user_c_09	Customer specific column	char(20)	For future use
user_c_10	Customer specific column	char(40)	For future use
user_d_01	Customer specific column	date	For future use
user_d_02	Customer specific column	date	For future use
user_f_07	Customer specific column	decimal(18,6)	For future use
user_f_08	Customer specific column	decimal(18,6)	For future use
user_n_03	Customer specific column	integer	For future use
user_n_04	Customer specific column	integer	For future use
user_n_05	Customer specific column	integer	For future use
user_n_06	Customer specific column	integer	For future use
verarb_art	Not used at the moment.	char(1)	Not used at the moment.
verweis	Reference	serial	Unique number of the record. (PDM field ID: STMP.VERWEIS)
verweis_merk	Reference to the original clocking.	integer	
vorbuch	Absence reason (in advance)	char(4)	Absence reason of the advance or subsequent posting which this clocking resulted from. This column is only filled when subsystem to SAP-HR is active in basic settings.

12.52. tagesauswertung

Table name: tagesauswertung		Product: PZE	
Designation: Personal daily results time&attendance		Description: Result of the labor time calculation includes details on planned and actual working times or absences. The labor time calculation creates a data record for each employee and for every day. If the labor time calculation is repeated this record is checked and the results of the first calculation of the day are overwritten. # Key personalnummer, auswertungs_datum (unique) verweis (unique) # Connections to other tables personen.personalnummer = personalnummer and auswertungs_datum between personen.gueltig_von and personen.gueltig_bis	
Column name	Column designation	Type	Description
abr_datum_anf	Period for overtime calculation	date	
abr_datum_ende	Period for overtime calculation	date	
arbeitstag_anfang	Attendance time beginn (date)	date	Date when the attendance started
arbeitstag_ende	Attendance time end (date)	date	Date when the attendance ended
arbeitszeit_anfang	Attendance time beginn (time)	integer	Start of attendance
arbeitszeit_ende	Attendance time end (time)	integer	End of attendance
arbeitszeittyp	Working time day type	smallint	Number of working time day type used to evaluate this day
ausgewertet	Last calculation date	date	Date on which the day was evaluated at last. See also column ausgewertet_zeit.
ausgewertet_bearb	Last calculation user	char(10)	If Labor time calculation has been started manually on a client: User who startet calcualtion.
ausgewertet_zeit	Last calculation time	integer	Time on which the day was evaluated at last. See also column ausgewertet.
ausser_rahmen	Working time outside of skeleton time.	integer	
auswertungs_datum	Settlement date	date	(PDM field ID: TGERG.ABREDAT)
aw_datum_anf	Period for overtime calculation	date	
aw_datum_ende	Period for overtime calculation	date	
bereitschaft_az	Real working time while "On-call duty"	integer	
bez_pause	Reference to paid break clocking	integer	Reference to a possibly generated clocking for "paid break".
fehl_lohnstatus	Payment day type of absence	smallint	If the employee is absent on the calculated day the corresponding payment day type is indicated in this field. The entry refers to the typnummer field in the lohnarten_zuord table.
fehl_lohnstatus2	Payment day type of second absence	smallint	If the employee has a second absence time on the evaluated day the corresponding payment day type is indicated in this field. The entry refers to the typnummer field in the lohnarten_zuord table.
fehlzeit	Absence time	integer	(PDM field ID: TGERG.FZ)
fehlzeit1	Duration of first absence time	integer	
fehlzeit2	Duration of second absence time	integer	
firma	Company	char(4)	Company which the person belongs to. (PDM field ID: TGERG.FIR)
flexktoaend	Change of account	integer	Daily change for the flexible time account (account number: 3) The actual change is to be calculated by flexktoaend + ktoaend_3 due to backward kompatibility.
flexktodiv	Obsolete	integer	Currently not used
folgetg_lohnstatus	Payment day type of next day	smallint	
fz_weiterbuchen	Post on absence payment day type	integer	Reserved for customer specific processing: Contains the payment day type of an absence if this payment day type is configured in such a way that it should still be posted for the following days.

geplante_az	Target time	integer	(PDM field ID: TGERG.SZ)
ges_pause	Total break duration	integer	
gleitzeit_aend	Change of account	integer	Daily change for the flextime account (account number: 1) The actual change is to be calculated by gleitzeit_aend + ktoaend_1 due to backward compatibility.
glztktodiv	Attendance time vs. BDE	integer	Actually rendered attendance time for PZW/BDE comparison. For some customer enhancements this column may differ from column reale_az, but normally it has the same value.
kernzeit_kto_div	Core time violation	integer	If this field contains a value of -1 this is an indicator that this day has been evaluated by a labor time calculation with a version lower than 7.2 and therefore does not contain a real core time violation.
ktoaend_1	Change of account	integer	Daily change for the account 1
ktoaend_10	Change of account	integer	Reserved for future use: Daily change for the account 10
ktoaend_11	Change of account	integer	Reserved for future use: Daily change for the account 11
ktoaend_12	Change of account	integer	Reserved for future use: Daily change for the account 12
ktoaend_13	Change of account	integer	Reserved for future use: Daily change for the account 13
ktoaend_14	Change of account	integer	Reserved for future use: Daily change for the account 14
ktoaend_15	Change of account	integer	Reserved for future use: Daily change for the account 15
ktoaend_16	Change of account	integer	Reserved for future use: Daily change for the account 16
ktoaend_17	Change of account	integer	Reserved for future use: Daily change for the account 17
ktoaend_18	Change of account	integer	Reserved for future use: Daily change for the account 18
ktoaend_19	Change of account	integer	Reserved for future use: Daily change for the account 19
ktoaend_2	Change of account	integer	Daily change for the account 2
ktoaend_20	Change of account	integer	Reserved for future use: Daily change for the account 20
ktoaend_3	Change of account	integer	Daily change for the account 3
ktoaend_4	Change of account	integer	Daily change for the account 4
ktoaend_5	Change of account	integer	Daily change for the account 5
ktoaend_6	Change of account	integer	Daily change for the account 6
ktoaend_7	Change of account	integer	Daily change for the account 7
ktoaend_8	Change of account	integer	Daily change for the account 8
ktoaend_9	Change of account	integer	Reserved for future use: Daily change for the account 9
neue_tgaw	Recalculation done	char(1)	Flag whether the day has been reevaluated. Used to start the cyclic posting of wage type booking (J/N).
normalzeit	Normal working time of the day	integer	
nur_fehl	Absence indicator	char(1)	Single character indicating whether the employee was completely absent on this day (J/N).
personalnummer	Personnel number	integer	Person who has been evaluated. (PDM field ID: TGERG.PNR)
plan_lohnstatus	Planned payment day type	smallint	Originally planned payment day type. This day type may differ from the really used payment day types in the clockings due to special rules like "On-call duty".
reale_az	Attendance time	integer	(PDM field ID: TGERG.IZ)
rest_pause	Duration of paid breaks	integer	
rueckgesetzt	For future use	date	Currently not used
rueckgesetzt_bearb	For future use	char(10)	Currently not used
rueckgesetzt_zeit	For future use	integer	Currently not used
rufbereitschaft	Duration of "On-call duty"	integer	
ruhezeit	Rest period	integer	
ruhezeit_bis	Rest period until	datetime	
ruhezeitverletzung	Violation of rest period	integer	
schicht_art	Shift type	char(1)	(PDM field ID: TGERG.SCHZART)

tgaw_erforderlich	Recalculation required	char(1)	Flag whether it is required to reevaluate the day (J/N).
ueberstdaend	Change of account	integer	Daily change for the overtime account (account number: 2) The actual change is to be calculated by ueberstdaend+ ktoaend_2 due to backward compatibility.
unbezzeit	This day's unpaid working time.	integer	
unterbrechung	Working time interruptions duration	integer	Duration of the interruptions of working time outside the break frame
url_anspruch	Leave entitlement	integer	Annual leave entitlement (not included in ktoaend_4)
urlaubaeend	Change of account	integer	Daily change for the leave account (account number: 4) The actual change is to be calculated by urlaubaeend + ktoaend_4 + url_anspruch due to backward compatibility.
user_c_09	Customer specific column	char(20)	For future use
user_c_10	Customer specific column	char(40)	For future use
user_d_01	Customer specific column	date	For future use
user_d_02	Customer specific column	date	For future use
user_f_07	Customer specific column	decimal(18,6)	For future use
user_f_08	Customer specific column	decimal(18,6)	For future use
user_n_03	Customer specific column	integer	For future use
user_n_04	Customer specific column	integer	For future use
user_n_05	Customer specific column	integer	For future use
user_n_06	Customer specific column	integer	For future use
verweis	Reference	serial	All entries in this table are numbered consecutively. (PDM field ID: TGERG.VERWEIS)
vortg_lohnstatus	Payment day type of previous day	smallint	
weiterbuchen	Post on absence reason	char(4)	Contains the absence reason if an absence reason for advance and subsequent postings is configured in such a way that it should still be posted for the following days.

12.53. woaw_per_par

Table name: woaw_per_par		Product: PZE	
Designation: Parameters for the posting of wage types			
Column name	Column designation	Type	Description
abrech_beginn		char(2)	For future use
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausw_tgl	Type	char(1)	Type of overtime periods: - 'Z': period (e.g. daily or weekly) - 'M': monthly periods (calendar months). (PDM field ID: MEHRARBPER.ART)
aw_beginn		char(2)	Start of the overtime period (for periods): - "Mo"... "So": Period starts on the first Monday of the year. - 1...31: The period starts on January 1st (PDM field ID: MEHRARBPER.PERB)
aw_ende		char(2)	Duration of the overtime period (for periods) (PDM field ID: MEHRARBPER.DAUER)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bereich		char(8)	Designation of the area for which the definition of parameters should apply. (PDM field ID: MEHRARBPER.BER)
bezug	Personnel selection key	char(20)	
firmen_nummer		char(4)	Designation of the company for which the definition of parameters should apply. (PDM field ID: MEHRARBPER.FIR)
gueltig_bis	Valid until	date	
gueltig_von	Valid from	date	
jahr		smallint	Year for which the definition of parameters should apply. (PDM field ID: MEHRARBPER.JAHR)
kostenstelle		char(10)	Designation of the cost center for which the definition of parameters should apply. (PDM field ID: MEHRARBPER.KST)
personalnummer	Personnel number	integer	The person's personnel number for which the definition of parameters should apply. (PDM field ID: MEHRARBPER.PNR)
verweis	Reference	serial	Unique key to access the data record.
wechsel_monat	Partial periods at the end of settlement periods	char(1)	Indication of partial periods that are to be formed at month-end (for periods only). (PDM field ID: MEHRARBPER.WPERMONAT)
wert	Personnel selection value	char(20)	

12.54. woaw_periode

Table name: woaw_periode		Product: PZE	
Designation: Evaluation periods for wage type posting		Description: The wage type posting together with the daily evaluation are carried out by the system. The evaluation periods for overtime compensation can be different for companies, areas, cost centers and persons.	
Column name	Column designation	Type	Description
abrech_begin		date	Start of allocation can lie ahead of the start o f evaluation (e.g. at the end of the month).
abrech_ende		date	End of payroll period.
aw_begin		date	Start of evaluation of the period.
aw_ende		date	End of evaluation of the period
bereich		char(8)	Area (field within the HR master) for which the period applies.
firma		char(4)	Company (field within the HR master), for which the period applies.
jahr		smallint	Year in which the configuration applies.
kostenstelle		char(10)	Cost center (field within the HR master) for which the period applies
periode		smallint	Number of the period
personalnummer	Personnel number	integer	Person (field within the HR master) for which the period applies.
verweis		serial	
zusatz_kz		char(1)	For future use

12.55. zeit_kto

Table name: zeit_kto		Product: PZE	
Designation: Posting of time accounts		Description: Posting accounts via wage types.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
anw_add_sub	Compensation	char(1)	Deduct time (= '-') or add time (= '+'), which is posted to the wage type on the basis of absence time, from the flex time account. (PDM field ID: KTOVERB.VZ)
anw_hinzu	Attendance time	char(1)	Indication whether time that is posted to the wage type based on absence time is used at all for the allocation of flextime accounts ('J' or 'N'). (PDM field ID: KTOVERB.OPT:ANW)
bearb	Modified by	char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
fehl_add_sub		char(1)	Deduct time (= '-') or add time (= '+'), which is posted to the wage type on the basis of absence time, from the flex time account. At the moment, adding and subtracting are controlled irrespective of attendance or absence. There is only one field: KTOVERB.VORZ
fehl_hinzu	Absence	char(1)	Indication whether time that is posted to the wage type based on absence time is used at all for the allocation of flextime accounts ('J' or 'N'). (PDM field ID: KTOVERB.OPT:FZ)
firma	Company	char(4)	Company (field within HR master) for which the entry applies. (PDM field ID: KTOVERB.FIR)
grenze_max	Limit value	integer	Limit value for posting to this account (this processing is not active in the standard). (PDM field ID: KTOVERB.G:MAX)
kontoart		smallint	Indication for which account this configuration applies (see account number in the pze_konten table). (PDM field ID: KTOVERB.KTO)
lohnart		char(4)	Posted wage type from wage type posting. (PDM field ID: KTOVERB.LART)
lohnart_max		char(4)	When reaching the limit value in the "grenze_max" field the remaining time is reposted to this wage type. (This processing is not active within the standard). (PDM field ID: KTOVERB.LART:MAX)
reihenfolge	Order	smallint	This field controls the behavior when reposting a the end of the mont due to account limits. It is defined whether the transfer posting to another account is performed immediately and thus affects when limiting this account or whether the transfer posting is only performed after editing the account limits of all accounts. 0: Transfer posting is performed immediately. Otherwise: Transfer posting is only performed at the end of the program. (PDM field ID: KTOVERB.FOLG)

12.56. zeitspanne_aw

Table name: zeitspanne_aw		Product: PZE	
Designation: Result of period of overtime calculation		Description: Result of period of overtime calculation, contains details on the period of the evaluation, target working time within the stated period, account changes, etc. # Key personalnummer, aw_datum_anf, firma (unique) satznummer (unique) # Connections to other tables personen.personalnummer = personalnummer and aw_datum_ende between personen.gueltig_von and personen.gueltig_bis	
Column name	Column designation	Type	Description
abr_datum_anf	Start of complete overtime calculation period	date	No partial period at the end of settlement period
abr_datum_ende	End of complete overtime calculation period	date	No partial period at the end of settlement period
ae_anzahl	Number of absence days	smallint	
aw_datum_anf	Start date of the overtime calculation period	date	(Partial period at the end of settlement period)
aw_datum_ende	End date of the overtime calculation period	date	(Partial period at the end of settlement period)
az_anw	Attendance time	integer	Attendance time within the evaluation period.
az_fehl	Absence time	integer	Absence time within the evaluation period
az_soll	Target working time within the period.	integer	
az_unbez	For future use	integer	Unpaid time within the evaluation period (not yet processed).
firma	Company	char(4)	The evaluated person's company
flexktoaend	Change of the flexible time account within the period (account 3)	integer	Daily change for the flexible time account (account number: 3) The actual change is to be calculated by flexktoaend + ktoaend_3 due to backward compatibility.
gleitzeitend	Change of the flextime account within the period (account 1)	integer	Daily change for the flextime account (account number: 1) The actual change is to be calculated by gleitzeitend + ktoaend_1 due to backward compatibility.
jahr	Year	smallint	
kg_anzahl	Number of attendance days	smallint	
ktoaend_1	Change of account within overtime calculation period	integer	
ktoaend_10	Change of account within overtime calculation period	integer	For future use
ktoaend_11	Change of account within overtime calculation period	integer	For future use
ktoaend_12	Change of account within overtime calculation period	integer	For future use
ktoaend_13	Change of account within overtime calculation period	integer	For future use
ktoaend_14	Change of account within overtime calculation period	integer	For future use
ktoaend_15	Change of account within overtime calculation period	integer	For future use
ktoaend_16	Change of account within overtime calculation period	integer	For future use
ktoaend_17	Change of account within overtime calculation period	integer	For future use

ktoaend_18	Change of account within overtime calculation period	integer	For future use
ktoaend_19	Change of account within overtime calculation period	integer	For future use
ktoaend_2	Change of account within overtime calculation period	integer	
ktoaend_20	Change of account within overtime calculation period	integer	For future use
ktoaend_3	Change of account within overtime calculation period	integer	
ktoaend_4	Change of account within overtime calculation period	integer	
ktoaend_5	Change of account within overtime calculation period	integer	
ktoaend_6	Change of account within overtime calculation period	integer	
ktoaend_7	Change of account within overtime calculation period	integer	
ktoaend_8	Change of account within overtime calculation period	integer	
ktoaend_9	Change of account within overtime calculation period	integer	For future use
neue_woaw	Internal processing indicator (account booking of postings)	char(1)	J = Posting of wage types has been made anew. Booking of accounts is pending. N = Account booking of postings is performed completely. Customer specific processing: (K = Account booking of postings is performed completely. There are account changes. In case of account balance dependant payment this period has to be recalculated if a previous period is recalculated.) and there has been a transfer posting due to a limit value.) (V = Account booking of postings is performed completely. There are account changes on an account and the limit of an account balance dependant payment has been exceeded.) J = Lohnartenbuchungen wurden neu erzeugt. Die Verbuchung der Lohnarten auf Konten steht noch aus. N = Die Verbuchung der Lohnarten auf Konten wurde durchgeführt (K = kundenspezifisch: An diesem Tag liegt eine Kontoänderung vor. Bei kontostandsabhängiger Entlohnung muss dieser Tag neu bewertet werden, wenn ein vorheriger Tag neu berechnet wurde) (V = kundenspezifisch: An diesem Tag wurde der Grenzwert einer kontostandsabhängigen Entlohnung erreicht)
periode	Number of the overtime period	smallint	
personalnummer	Personnel number	integer	A result record is created for each person.
satzennummer	Reference	serial	Unique key. Reference to lohnarten_aw table.
sonderurl_aend	Undertime within the period	integer	
ueberstdaend	Change of the overtime account within the period (account 2)	integer	Daily change for the overtime account (account number: 2) The actual change is to be calculated by ueberstdaend+ ktoaend_2 due to backward compatibility.
url_vorjahr_aend	Obsolete	integer	Additional field to be evaluated.
urlaubaend	Leave taken within the period (change of account 4)	integer	Daily change for the leave account (account number: 4) The actual change is to be calculated by urlaubaend + ktoaend_4 due to backward compatibility.
user_c_09	Customer specific column	char(20)	For future use
user_c_10	Customer specific column	char(40)	For future use
user_d_01	Customer specific column	date	For future use
user_d_02	Customer specific column	date	For future use
user_f_07	Customer specific column	decimal(18,6)	For future use
user_f_08	Customer specific column	decimal(18,6)	For future use
user_n_03	Customer specific column	integer	For future use
user_n_04	Customer specific column	integer	For future use

user_n_05	Customer specific column	integer	For future use
user_n_06	Customer specific column	integer	For future use
wo_lostzeit	Time posted as overtime within the period evaluated.	integer	
woaw_erforderlich	Internal processing indicator	char(1)	J =Posting of wage types is required. (along the lines of neue_tgaw in the tagesauswertung table). N = Posting of wage types has been carried out.

12.57. zugberechtigung

Table name: zugberechtigung		Product: PZE	
Designation: Clocking authorization		Description: This table defines on which shop floor terminals an employee may clock and on which ones the access is denied. In the zugberechtigung table several entries can be made for each person from the personen table. When it comes to assigning access authorizations single terminals or terminal groups can be entered.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb		char(10)	Last editor
bearb_date	Modified date	date	
bearb_time	Time	integer	Last editing time
bezug	Personnel selection key	char(20)	
firma	Company	char(4)	Company of the person concerned (PDM field ID: ZBERECHT.FIR)
geloescht		char(1)	Access authorizations that were deleted are marked with an 'J' in this field.
gueltig_bis	Valid until	date	Validity period (PDM field ID: ZBERECHT.DATE)
gueltig_von	Valid from	date	Validity period (PDM field ID: ZBERECHT.DATB)
personalnummer	Personnel number	integer	Person that should get an access authorization. (PDM field ID: ZBERECHT.PNR)
verweis	Reference	serial	Unique data record number. (PDM field ID: ZBERECHT.VERWEIS)
wert	Personnel selection value	char(20)	
zugang_art	Assignment	char(1)	This field defines whether it is a terminal ("T"), a terminal group ("G") or an access profile ("Z"). (PDM field ID: ZBERECHT.ART)
zugang_nr	Number	smallint	Number of the terminal , the terminal group or the access profile. (PDM field ID: ZBERECHT.NR)

12.58. zuggruppe

Table name: zuggruppe		Product: PZE	
Designation: Terminal groups		Description: Terminals can be assigned to terminal groups in this table. Authorizations can be assigned via terminal gorups on PZE terminals.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb		char(10)	Last editor
bearb_date	Modified date	date	
bearb_time		integer	Last editing time
bezeichnung	Designation	char(40)	Designation of the terminal group. (PDM field ID: TGRP.BEZ)
datum_bis		date	Validity period for the assignment of the terminal to the group. (PDM field ID: TGRP.DATE)
datum_von		date	Validity period for the assignment of the terminal to the group. (PDM field ID: TGRP.DATB)
terminal_gruppe	Terminal group	smallint	Number of the terminal group. (PDM field ID: TGRP.TGRP)
terminal_nr		smallint	Terminal that is assigned to the group. (PDM field ID: TGRP.TNR)
verantw_bereich		char(15)	Responsibility area that the terminal group is assigned to.

13. WRM

13.1. event_res

Table name: event_res		Product: WRM	
Archive table: a_event_res		Reload table: r_event_res	
Designation: Events for resources and maintenance			
Column name	Column designation	Type	Description
artikel	Resource number	char(40)	Here all dialogs save the RES (PDM field ID: RES)
attribut_1		char(20)	RES_STATUS/RES_UMB: Receiving storage location (ZLO)
attribut_2	Resource type	char(20)	Here all dialogs save the RESTYP (PDM field ID: RESTYP)
attribut_3	Resource version	char(30)	Here all dialogs save the resource version (PDM field ID: RESVER)
attribut_4		char(20)	RES_STATUS: Start date of the status (DATB) RES_UPLOAD: MOD indicator of the dialog: N=New, U=Update RES_WART: Maintenance type (WARTART) RES_MASS : Indicator lamp (MELD) RES_AN : Referencing resource type RES_EIN/RES_AUS: Referencing resource type of parent ressource RES_STE/RES_STB: Status type
attribut_5		char(20)	RES_STATUS: End date of the status (DATE) RES_DOWNL, RES_UPLOAD, RES_DNCVER: DNC processing flag (OPT_DNCVERARB) RES_WART: Target day RES_MASS : Party in charge (VERANTW) RES_AN : Referencing resource number RES_STE/RES_STB: Statustext ID
attribut_6		char(10)	RES_STATUS: Start time of the status (ZEIB) RES_MASS: Date of the solution (DATLOES) RES_IH: IH number RES_STB/RES_STE: reasoncode RES_DNCVER: so far valid version
attribut_7		char(10)	RES_STATUS: End time of the status (ZEIE) RES_UPLOAD, RES_DNCVER: Identity of resource family (RESFAMID) RES_MASS: Priority (PRIO)
attribut_8		char(20)	RES_UPLOAD, RES_DNCVER: ID of resource family (RESFAM) RES_MASS : Finished by (ERLD) M_IH_BEM (WRM-IH): Action ADD, DEL, UPD
attribut_9		char(30)	RES_UPLOAD: Name of DNC file (SPEICHORT:DATA) RES_DNCVER: Name of new DNC file (SPEICHORT:DATA+" "+<new version>)
auftrag_nr		char(40)	RES_AN, RES_AB: order number
automatisch		char(1)	J : Automatic event, e.g. at the change of shifts
bearb	User	char(10)	RES_WART: Person of last maintenance (LWART:USR) (PDM field ID: BEARB)
bearb_date		date	RES_WART: Date of last maintenance (LWART:DAT)
bearb_time		integer	RES_WART: Time of last maintenance (LWART:ZEI)
bpos		char(10)	Operator position at Event P_AN
buch_dat		date	Posting time
buch_zeit		integer	Posting time
buendelnr		char(40)	RES_EIN/RES_AUS: Referencing parent ressource

bzw		char(10)	Booking obligation J/N
chargen_nr		char(20)	Assigned according to the event
datum	Date	date	{mm/dd/yyyy} date of the dialog (PDM field ID: DAT)
dialog		char(10)	RES_STATUS: "RES_STATUS" or "RES_FREI" or "RES_ABSTA" RES_DOWNL: "RES_DOWNL" RES_UPLOAD: "RES_UPLOAD" RES_WART: "RES_WART" RES_MASS: "RES_MASS" RES_AN: "RES_AN" RES_AB: "RES_AB"
dlg_data_verweis		integer	Reference to additional data record event_dlg_data
dlg_id		char(10)	Dialog reference
dllosnr		char(20)	Throughput batch number
editierbar		char(1)	J = Event may be maintained N= Event may not be maintained, e.g. master of an COP or blocked by changing the log record
ein_h_1		char(3)	not yet assigned
ein_h_10		char(3)	not yet assigned
ein_h_11		char(3)	not yet assigned
ein_h_12		char(3)	not yet assigned
ein_h_13		char(3)	not yet assigned
ein_h_14		char(3)	not yet assigned
ein_h_15		char(3)	not yet assigned
ein_h_16		char(3)	not yet assigned
ein_h_17		char(3)	not yet assigned
ein_h_18		char(3)	not yet assigned
ein_h_19		char(3)	not yet assigned
ein_h_2		char(3)	not yet assigned
ein_h_20		char(3)	not yet assigned
ein_h_3		char(3)	not yet assigned
ein_h_4		char(3)	not yet assigned
ein_h_5		char(3)	not yet assigned
ein_h_6		char(3)	not yet assigned
ein_h_7		char(3)	not yet assigned
ein_h_8		char(3)	not yet assigned
ein_h_9		char(3)	not yet assigned
ereignis		char(10)	RES_STATUS: "RES_STATUS" RES_DOWNL: "RES_DOWNL" RES_UPLOAD: "RES_UPLOAD" RES_WART: "RES_WART" RES_MASS: "RES_MASS" RES_AN: "RES_AN" RES_AB: "RES_AB" RES_DNCVER: "RES_DNCVER"
erfass_1		char(1)	RES_MAS : Finished (ERL)
erfass_10		char(1)	free
erfass_11		char(1)	free
erfass_12		char(1)	free
erfass_13		char(1)	Free
erfass_14		char(1)	free
erfass_15		char(1)	free

erfass_16		char(1)	free
erfass_17		char(1)	free
erfass_18		char(1)	free
erfass_19		char(1)	free
erfass_2		char(1)	free
erfass_20		char(1)	free
erfass_3		char(1)	free
erfass_4		char(1)	free
erfass_5		char(1)	free
erfass_6		char(1)	free
erfass_7		char(1)	free
erfass_8		char(1)	free
erfass_9		char(1)	free
erfass_dat		date	Time of entry
erfass_zeit		integer	Time of entry
erw_status_01		char(1)	
erw_status_02		char(1)	
erw_status_03		char(1)	
erw_status_04		char(1)	
erw_status_05		char(1)	for internal use
erw_status_06		char(1)	for internal use
firma_1		char(8)	Company/plant number 1
firma_2		char(8)	Company/plant number 2
grund_1		char(10)	RES_UPLOAD: User field data for field 1
grund_10		char(10)	not yet assigned
grund_11		char(10)	not yet assigned
grund_12		char(10)	not yet assigned
grund_13		char(10)	not yet assigned
grund_14		char(10)	not yet assigned
grund_15		char(10)	not yet assigned
grund_16		char(10)	not yet assigned
grund_17		char(10)	not yet assigned
grund_18		char(10)	not yet assigned
grund_19		char(10)	not yet assigned
grund_2		char(10)	RES_UPLOAD: User field data for field 2
grund_20		char(10)	not yet assigned
grund_3		char(10)	RES_UPLOAD: User field data for field 3
grund_4		char(10)	RES_UPLOAD: User field data for field 4
grund_5		char(10)	not yet assigned
grund_6		char(10)	not yet assigned
grund_7		char(10)	not yet assigned
grund_8		char(10)	not yet assigned
grund_9		char(10)	not yet assigned

herkunft		char(1)	"Blank" : original data record from the collection E: Manually generated data record L: Manually generated data record; for cancellation only O: Original data record, if maintained X: Event is blocked; no posting as plausibility error occurred
info_01		integer	Up to 7.1: here all dialogs save the reference to event_dlg_data (commentary) As of 7.2: Separate field dlg_data_verweis
info_02		integer	Here all dialogs save the RESVERWEIS / RESID (PDM field ID: RESVERWEIS)
info_03		integer	RES_STATUS: 0= Convert status immediately; 1= Convert status in future RES_WART: Maintenance reference (WARTVERWEIS) to table res_wartungen RES_MASS: Number of measure (MASSNR) RES_AN_MNR: RessourceID of the initial Ressource of the dialogue RES_AB_MNR: RessourceID of the initial Ressource of the dialogue
ist_lst_01		decimal(18,6)	Recorded activity 1 to 20
ist_lst_02		decimal(18,6)	Recorded activity 1 to 20
ist_lst_03		decimal(18,6)	Recorded activity 1 to 20
ist_lst_04		decimal(18,6)	Recorded activity 1 to 20
ist_lst_05		decimal(18,6)	Recorded activity 1 to 20
ist_lst_06		decimal(18,6)	Recorded activity 1 to 20
ist_lst_07		decimal(18,6)	Recorded activity 1 to 20
ist_lst_08		decimal(18,6)	Recorded activity 1 to 20
ist_lst_09		decimal(18,6)	Recorded activity 1 to 20
ist_lst_10		decimal(18,6)	Recorded activity 1 to 20
ist_lst_11		decimal(18,6)	Recorded activity 1 to 20
ist_lst_12		decimal(18,6)	Recorded activity 1 to 20
ist_lst_13		decimal(18,6)	Recorded activity 1 to 20
ist_lst_14		decimal(18,6)	Recorded activity 1 to 20
ist_lst_15		decimal(18,6)	Recorded activity 1 to 20
ist_lst_16		decimal(18,6)	Recorded activity 1 to 20
ist_lst_17		decimal(18,6)	Recorded activity 1 to 20
ist_lst_18		decimal(18,6)	Recorded activity 1 to 20
ist_lst_19		decimal(18,6)	Recorded activity 1 to 20
ist_lst_20		decimal(18,6)	Recorded activity 1 to 20
ist_lst_einh_01		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_02		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_03		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_04		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_05		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_06		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_07		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_08		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_09		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_10		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_11		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_12		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_13		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_14		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_15		char(3)	Unit of recorded activity 1 to 20

ist_lst_einh_16		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_17		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_18		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_19		char(3)	Unit of recorded activity 1 to 20
ist_lst_einh_20		char(3)	Unit of recorded activity 1 to 20
ist_lst_typ_01		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_02		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_03		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_04		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_05		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_06		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_07		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_08		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_09		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_10		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_11		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_12		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_13		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_14		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_15		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_16		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_17		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_18		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_19		char(10)	Type of recorded activity 1 to 20
ist_lst_typ_20		char(10)	Type of recorded activity 1 to 20
karenz		char(1)	P = Waiting period of personnel M = Waiting period of machines
klasse		char(1)	Here all dialogs save "O"
lohnart		char(4)	LLE wage type
lpkz		char(10)	Wage premium indicator
masch_nr		char(20)	RES_DOWNL, RES_UPLOAD, RES_AN, RES_AB: machine number (MNR)
menge_1		decimal(18,6)	RES_WART: Target cycle RES_STE/RES_STB: Status
menge_10		decimal(18,6)	RES_WART: Threshold 3: value range 0 to 100 %
menge_11	EMG: value of consumption ctr. (yield)	decimal(18,6)	
menge_12	EMG: value of consumption ctr. (scrap)	decimal(18,6)	
menge_13	EMG: value of consumption ctr. (rework)	decimal(18,6)	
menge_14	EMG: absol. val. of consu. ctr. (yield)	decimal(18,6)	
menge_15	EMG: absol. val. of consu. ctr. (scrap)	decimal(18,6)	
menge_16	EMG: absol. val. of consu. ctr. (rework)	decimal(18,6)	
menge_17		decimal(18,6)	free
menge_18		decimal(18,6)	free
menge_19		decimal(18,6)	free
menge_2		decimal(18,6)	RES_WART: Actual cycle
menge_20		decimal(18,6)	free
menge_3		decimal(18,6)	RES_WART: Target operating hours

menge_4		decimal(18,6)	RES_WART: Actual operating hours
menge_5		decimal(18,6)	RES_WART: Target number
menge_6		decimal(18,6)	RES_WART: Actual number
menge_7		decimal(18,6)	RES_WART: Year model
menge_8		decimal(18,6)	RES_WART: Threshold 1: value range 0 to 100 %
menge_9		decimal(18,6)	RES_WART: Threshold 2: value range 0 to 100 %
offline_kz		char(1)	J : recorded by the terminal offline
org_verweis		integer	Reference to a correction data record
p_divisor		decimal(18,6)	Recorded divisor
p_teiligkeit		decimal(18,6)	Recorded partitioning
person_nr	Personnel number	char(10)	Personnel number from PNR or KNR (PDM field ID: PNR)
pggruppe		char(20)	Assigned according to the event
pmk		char(1)	Memorize person J/N
prgrp		char(10)	STD-LLE : Wage/premium group LPGRP
prioritaet		smallint	Here all dialogs save the priority
pze_erzeugt		char(1)	"K" =BDE event was generated by PZE clock-in "G" =BDE event was generated by PZE clock-out
rest_lst_01		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_02		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_03		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_04		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_05		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_06		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_07		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_08		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_09		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_10		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_11		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_12		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_13		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_14		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_15		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_16		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_17		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_18		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_19		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_20		decimal(18,6)	Remainder of recorded activity 1 to 20
rest_lst_einh_01		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_02		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_03		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_04		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_05		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_06		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_07		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_08		char(3)	Remainder of the unit of recorded activity 1 to 20

rest_lst_einh_09		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_10		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_11		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_12		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_13		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_14		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_15		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_16		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_17		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_18		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_19		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_einh_20		char(3)	Remainder of the unit of recorded activity 1 to 20
rest_lst_typ_01		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_02		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_03		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_04		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_05		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_06		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_07		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_08		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_09		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_10		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_11		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_12		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_13		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_14		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_15		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_16		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_17		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_18		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_19		char(10)	Remainder of the type of recorded activity 1 to 20
rest_lst_typ_20		char(10)	Remainder of the type of recorded activity 1 to 20
sig_knr1		char(10)	
sig_knr2		char(10)	
sig_name1		char(40)	
sig_name2		char(40)	
sig_pnr1		char(10)	
sig_pnr2		char(10)	
sig_type1		char(20)	
sig_type2		char(20)	
soll_te		decimal(18,6)	Premium target-TE
soll_teb		decimal(18,6)	Premium target-TEB
soll_tr		decimal(18,6)	Premium target-TR
stationsnr		integer	free
status_1		integer	RES_STATUS (RES_FREI/RES_ABSTA): Resource status
status_2		integer	RES_WART: Old state. Value range 0 - 3

status_3		integer	RES_WART: New state (ZUSTAND). Value range 0 - 3
szenario_nr		integer	for future use relevant to event maintenance
terminal_nr		smallint	User who generated the data record
typ_1		char(10)	RES_UPLOAD: User field index for field 1 RES_STE/RES_STB: fix "STATUS"
typ_10		char(10)	Not yet assigned
typ_11		char(10)	Not yet assigned
typ_12		char(10)	Not yet assigned
typ_13		char(10)	Not yet assigned
typ_14		char(10)	Not yet assigned
typ_15		char(10)	Not yet assigned
typ_16		char(10)	Not yet assigned
typ_17		char(10)	Not yet assigned
typ_18		char(10)	Not yet assigned
typ_19		char(10)	Not yet assigned
typ_2		char(10)	RES_UPLOAD: User field index for field 2
typ_20		char(10)	Not yet assigned
typ_3		char(10)	RES_UPLOAD: User field index for field 3
typ_4		char(10)	RES_UPLOAD: User field index for field 4
typ_5		char(10)	Z1
typ_6		char(10)	Z2
typ_7		char(10)	Z3
typ_8		char(10)	Not yet assigned
typ_9		char(10)	Not yet assigned
umref		decimal(18,6)	Conversion factor for retrograde posting
utc_ts		datetime	
verarb_1		char(1)	RES_WART: Mode of the processing (MOD) Z = Set the condition A = Activate/deactivate R = Reset RES_MASS: Mode of the processing (MOD) S= Event over parts list
verarb_2		char(1)	RES_WART: Old active ID: J/N
verarb_3		char(1)	RES_WART: New active ID: J/N
verarb_4		char(1)	HYD-AEV: A = Flag for automatically generated dialogs; e.g. from PZE/ADE comparison
verarb_mde		char(1)	MDE processing (follow-up of MDE log messages)
verbuch_kz		char(2)	Update indicator, e.g. "ST" = COP on the terminal, "SK"= COP on the console "SB" = Beginning of shift, "SE" = End of shift "B" = Block message "W" = Winter time (PZE) "S" = Daylight saving time (PZE)
verweis		serial	Unique reference of the data record
verweis_b1		integer	Reference to a correction data record
verweis_b2		integer	Reference to an operation-related result record or clocking record
zeit	Time	integer	{seconds} current time (PDM field ID: ZEI)

13.2. res_attribute

Table name: res_attribute		Product: WRM	
Designation: resource attributes			
Column name	Column designation	Type	Description
attrib	Attribute value	char(80)	Attribute value (PDM field ID: RESATTR.ATTR)
feldid	Refers to hyd_userfieldelem.feldid	integer	Refers to hyd_userfieldelem.feldid (PDM field ID: RESATTR.IDX)
res_id	Resource ID	integer	Resource ID (PDM field ID: RESATTR.RESVERWEIS)

13.3. res_bedarfszuord

Table name: res_bedarfszuord		Product: WRM	
Designation: Required Resources			
Column name	Column designation	Type	Description
bearb		char(10)	Editor (PDM field ID: BEARB)
bearb_date		date	Editing date (PDM field ID: BEARBDAT)
bearb_time		integer	Editing time (PDM field ID: BEARBZEI)
bemerkung		char(100)	Free comment field (PDM field ID: RESBEDRES.BEM)
param_str_01		char(10)	- for future use -
param_str_02		char(20)	- for future use -
param_str_03		char(30)	- for future use -
pdouble_01		decimal(18,8)	- for future use -
plong_01		integer	- for future use -
plong_02		integer	- for future use -
pshort_01		smallint	- for future use -
res_nr_m		char(40)	Resource number of superordinate resource = required resource (PDM field ID: RESBEDRES.RES:M)
res_nr_t		char(40)	Resource number of subordinate resource (PDM field ID: RESBEDRES.RES:T)
res_typ_m		char(4)	Resource type of superordinate resource = required resource (PDM field ID: RESBEDRES.RESTYP:M)
res_typ_t		char(4)	Resource type of subordinate resource (PDM field ID: RESBEDRES.RESTYP:T)

13.4. res_belege

Table name: res_belege		Product: WRM	
Archive table: a_res_belege		Reload table: r_res_belege	
Designation: Resource documents			
Column name	Column designation	Type	Description
abmeld_dat	Logoff date	date	Logoff date (PDM field ID: DATE)
abmeld_zeit	Logoff time	integer	Logoff time (PDM field ID: ZEIE)
anmeld_dat	Logon date	date	Logon date (PDM field ID: DATB)
anmeld_zeit	Logon time	integer	Logon time (PDM field ID: ZEIB)
artikel		char(40)	Article number from backlog of orders
auftrag_nr	Operation number	char(40)	operation number (PDM field ID: ANR)
aus_bas		decimal(18,6)	
aus_pri		decimal(18,6)	
aus_sek		decimal(18,6)	
aus_ter		decimal(18,6)	
bearb	Last editor	char(10)	Last editor
bearb_date	Last editing day	date	Last editing day
bearb_time	Last editing day	integer	Last editing day
begin_ts	Start first record	datetime	Timestamp for anmeld_dat, anmeld_zeit
bmk_01	SUT	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK01)
bmk_02	DCI	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK02)
bmk_03	LCI	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK03)
bmk_04	SCI	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK04)
bmk_05	IMN	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK05)
bmk_06	IMS	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK06)
bmk_07	SET	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK07)
bmk_08	STA	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK08)
bmk_09	U8	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK09)
bmk_10	U9	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK10)
bmk_11	MUT	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK11)
bmk_12	BKS	integer	Resource performance account 1 to 12 (PDM field ID: EGR:BMK12)

dauer	Total duration	integer	(PDM field ID: EGR:DAUER)
end_ts		datetime	Timestamp for abmeld_dat, abmeld_zeit
erw_status_01		char(1)	Field is taken over from ade_protokoll when resources are logged off
erw_status_02		char(1)	Field is taken over from ade_protokoll when the resource is logged off
gut_bas		decimal(18,6)	
gut_pri		decimal(18,6)	
gut_sek		decimal(18,6)	
gut_ter		decimal(18,6)	
kostenstelle	cost center	char(10)	cost center (PDM field ID: KST)
masch_nr	machine number	char(20)	machine number (PDM field ID: MNR)
massnahme	Measures	integer	for future use
meinheit_bas		char(3)	
meinheit_pri		char(3)	
meinheit_sek		char(3)	
meinheit_ter		char(3)	
nacharb_bas		decimal(18,6)	
nacharb_pri		decimal(18,6)	
nacharb_sek		decimal(18,6)	
nacharb_ter		decimal(18,6)	
p_ausschuss	Scrap	decimal(18,6)	Scrap (PDM field ID: EGR:AUS)
p_einh_01		char(3)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGE:1)
p_einh_02		char(3)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGE:2)
p_einh_03		char(3)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGE:3)
p_einh_04		char(3)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGE:4)
p_einh_05		char(3)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGE:5)
p_einh_06		char(3)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGE:6)
p_einheit		char(3)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGE:GUT)
p_huebe	Strokes	decimal(18,6)	Strokes (PDM field ID: EGR:HUB)
p_laenge	Rework	decimal(18,6)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGR:LEN)
p_lst_01		decimal(18,6)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGR:1)
p_lst_02		decimal(18,6)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGR:2)
p_lst_03		decimal(18,6)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGR:3)
p_lst_04		decimal(18,6)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGR:4)
p_lst_05		decimal(18,6)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGR:5)

p_lst_06		decimal(18,6)	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: EGR:6)
p_stueck	Yield	decimal(18,6)	Info dated July 5th, 2004: In WRM the yield quantity is indicated here, not the actual quantity (PDM field ID: EGR:GUT)
p_teiligkeit	Distribution	integer	Field is taken over from ade_protokoll when resources are logged off (PDM field ID: TLG)
param_str_01	EMG: origin	char(10)	internal use
param_str_02		char(20)	- for future use -
param_str_03		char(30)	- for future use -
pdouble_01	EMG: absolut value of consumption ctr.	decimal(18,8)	internal use
person_nr	personnel number	char(10)	personnel number (PDM field ID: PNR)
plong_01		integer	Reference to event_dlg_data
plong_02		integer	- for future use -
problem_bas		decimal(18,6)	
problem_pri		decimal(18,6)	
problem_sek		decimal(18,6)	
problem_ter		decimal(18,6)	
pshort_01	EMG: Computation Loop Counter	smallint	
rck_01		char(1)	Field is taken over from ade_protokoll when resources are logged off
rck_02		char(1)	Field is taken over from ade_protokoll when resources are logged off
res_id	reference to resource	integer	reference to resource (PDM field ID: RESVERWEIS)
res_nr	resource number	char(40)	resource number (PDM field ID: RES)
res_typ	resource type	char(4)	resource type (PDM field ID: RESTYP)
res_version	resource version	char(20)	resource version (PDM field ID: RESVER)
satz_art	Record type	char(1)	A: Log resource on. Document does not contain times and quantities E: Log resource off. Document contains the times and quantities accrued since the logon (PDM field ID: SART)
schicht_dat	Shift date	date	Shift date (PDM field ID: SKDAT)
schichtanf	Beginning of shift	integer	Beginning of shift (PDM field ID: SKZEIB)
schichtend	End of shift	integer	End of shift (PDM field ID: SKZEIE)
schichtnr	Shift number	integer	Shift number (PDM field ID: SKNR)
status_1		integer	Field is taken over from ade_protokoll when resources are logged off
status_2		integer	internal use
terminalnr	---	smallint	--- (PDM field ID: TNR)
verweis	identity	serial	identity (PDM field ID: VERWEIS)

13.5. res_bestand

Table name: res_bestand		Product: WRM	
Designation: Resource configuration			
Column name	Column designation	Type	Description
abruest_zeit	teardown time (for HLS)	integer	(PDM field ID: RES.ABRZ)
anonym	flag whether anonymous resource	char(1)	J/N: Flag whether this resource is of the type "anonymous resource" Resources of the type PER, PRU are always anonymous B: Required resource (PDM field ID: RES.ANONYM)
anschaff_dat	date of acquisition of the resource	date	(PDM field ID: RES.ANSCHAFFDAT)
anschaff_kost	acquisition costs for the resource	decimal(18,6)	(PDM field ID: RES.ANSCHAFFKOST)
anzahl	Number of resources (anonymous resource)	integer	(PDM field ID: RES.ANZ)
artikel	material	char(50)	(PDM field ID: RES.KBN:ATK)
auf Nuest_zeit	start time (for HLS)	integer	(PDM field ID: RES.ANFZ)
auswertung	Display in evaluations	char(1)	(PDM field ID: RES.OPT:AUSWSIB)
bearb	Last editor	char(10)	
bearb_date	Last editing day	date	
bearb_zeit	Last editing time	integer	
bebuchbar	update indicator	char(1)	N = Is not to be posted J = Is to be posted Only if number = 1 (PDM field ID: RES.OPT:VERB)
belegung	Check of resource within HLS	char(1)	Check of resource within HLS N = No G = Total time (R+H) R = Setup time H = Planned time (planned MUT) (PDM field ID: RES.OPT:BEL)
bestell_nr	Purch. order no.	char(40)	
bez_fremd	External designation	char(40)	
bezeichnung	Designation	char(40)	(PDM field ID: RES.BEZ)
chargen_nr		char(20)	
datei_vorhanden	Internal: file is actually available	char(1)	J = Check program of resources has found file on the server
dateiname	Name of corresponding file	char(128)	Indication without path and suffix (PDM field ID: RES.SPEICHORT:DATA)
definitionsdatei	Definition file of DATEI	char(128)	For NC programs it serves to define the logical content in DATEINAME (PDM field ID: RES.SPEICHORT:AUSW)
eigentuemer	Owner	char(60)	(PDM field ID: RES.EIGENT)
einheit	Unit	char(50)	
emg_absolutwert_grenze	Absolute value limit	decimal(18,6)	

firma	company number	char(10)	Internal use. Currently always 0001 (PDM field ID: RES.FIR)
garant_bis	Guaranteed date	date	
genauigkeitskl	Accuracy class	char(50)	
gravur_nr	engraving number	char(40)	(PDM field ID: RES.GRAVNR)
hersteller	manufacturer	char(60)	(PDM field ID: RES.HERST)
inbetrieb_dat	Start-up date	date	
inventar_nr	inventory number	char(40)	(PDM field ID: RES.INVNR)
kbn_nr	Consecutive number	integer	(PDM field ID: RES.KBN:NR)
kommentar_1	Commentary 1	char(60)	(PDM field ID: RES.BEM:1)
kommentar_2	Commentary 2	char(60)	(PDM field ID: RES.BEM:2)
kommentar_3	Commentary 3	char(60)	(PDM field ID: RES.BEM:3)
kommentar_4	Commentary 4	char(60)	(PDM field ID: RES.BEM:4)
kommentar_5	Commentary 5	char(60)	(PDM field ID: RES.BEM:5)
kommentar_6	Commentary 6	char(60)	(PDM field ID: RES.BEM:6)
korrekturfaktor	Correction factor	float	
kostenstelle	cost center of storage location	char(10)	(PDM field ID: RES.KST)
lagerort	place of origin of the resource	char(12)	Location of resource, if not in use (PDM field ID: RES.MATPUF:S)
lbez_id	Closed loop	char(15)	(PDM field ID: RES.KBN:LBEZID)
leistgrad	Rate of resource utilization in % with 2	decimal(18,6)	e.g. 100,00 % (PDM field ID: RES.LEISTGRAD)
lfd_nr	Reserved	smallint	For internal use only/value from RPA01 is entered there
lief_dat	Delivery date	date	
lieferant_nr	Supplier No.	char(50)	
mehrfach	can be logged on	char(1)	can be logged on (several times/simultan) (PDM field ID: RES.OPT:MULTIMNR)
meistermass	Master value	float	
meistertolz_bis	Master tolerance to	float	
meistertolz_von	Master tolerance from	float	
messbereich_bis	Measurement range to	float	
messbereich_von	Measurement range from	float	
meta_res	Meta resource	char(1)	J= Meta resource, i.e. has resource list (PDM field ID: RES.OPT:METARES)
mit_anmelden	resource is logged on/off with the OP	char(1)	J = Log resource on with order in case of A_AN or log it off in case of A_AB N = Do not log on/log off resource with order (for DNC always N) E = explicit log on / Changing allowed (as of version WRM 7.2) (PDM field ID: RES.OPT:AUTOANMELD)
opt_konfig	Configuration settings	char(10)	Ten different configuration settings (PDM field ID: RES.CFG:1..10)

org_dateiname	Original file name from ext. system	char(128)	Indication without path and suffix (PDM field ID: RES.SPEICHORT:ORG)
param_str_01	Reserved	char(10)	for future use
param_str_02	Partitioning due to cavities	char(20)	[1]:Cavity management: RES.TLGNEST (WRM-NEST)
param_str_03	Reserved	char(30)	for future use
pdouble_01	Reserved	decimal(18,6)	for future use
plan_takte	Planned cycles within total life time	decimal(18,6)	(PDM field ID: RES.SGR:HUB)
plong_01	Reserved	integer	for future use
plong_02	Reserved	integer	for future use
pps	resource loaded via PPS	char(1)	(PDM field ID: RES.OPT:PPS)
pshort_01	Reserved	smallint	for future use
res_familie	Resource family	integer	(PDM field ID: RES.RESFAMID)
res_familie_dnc	DNC family	integer	Only relevant for resources of the type "MNR" (machine). Only DNC resources of this resource family are allowed.
res_id	DB reference	serial	Internal ID (PDM field ID: RES.VERWEIS)
res_id_v1	Comparison resource id 1	integer	
res_id_v2	Comparison resource id 2	integer	
res_nr	Resource number	char(40)	RESTYP and RES together result in a unique key (PDM field ID: RES.RES)
res_nr_v1	Comparison resource number 1	char(40)	
res_nr_v2	Comparison resource number 2	char(40)	
res_typ	Resource type	char(4)	RESTYP and RES together result in a unique key (PDM field ID: RES.RESTYP)
res_typ_v1	Comparison resource type 1	char(4)	
res_typ_v2	Comparison resource type 1	char(4)	
res_version	resource version	char(20)	Preassignment 1, for NC resources the version is filed here (PDM field ID: RES.RESVER)
setze_sammelsperre	Collective block	char(1)	Increase/reduce collective block of superior resource in case of block/release (PDM field ID: RES.OPT:SSPERR)
soll_erf_einh	unit of entry of resource quantity	char(3)	unit of entry of resource quantity (PDM field ID: RES.EINH)
soll_lauf_zeit	Calculatory run time	integer	Calculatory run time (PDM field ID: RES.SGR:KLKLZ)
soll_lst_01	target activity 1 to 6	decimal(18,6)	target activity 1 to 6 (PDM field ID: RES.SGR:1)
soll_lst_02	target activity 1 to 6	decimal(18,6)	target activity 1 to 6 (PDM field ID: RES.SGR:2)
soll_lst_03	target activity 1 to 6	decimal(18,6)	target activity 1 to 6 (PDM field ID: RES.SGR:3)
soll_lst_04	target activity 1 to 6	decimal(18,6)	target activity 1 to 6 (PDM field ID: RES.SGR:4)
soll_lst_05	target activity 1 to 6	decimal(18,6)	target activity 1 to 6 (PDM field ID: RES.SGR:5)
soll_lst_06	target activity 1 to 6	decimal(18,6)	target activity 1 to 6 (PDM field ID: RES.SGR:6)
soll_teiligkeit	target partitioning	integer	target partitioning (PDM field ID: RES.TLG:S)

sollzyklus	target cycle	integer	--- (PDM field ID: RES.SZY)
teiligkeit	actual partitioning	integer	In case of initial data creation identical with target partitioning (PDM field ID: RES.TLG:I)
typen_bez		char(40)	
typgleich	equal type	char(1)	Must be same type: N = No, not obligatory U = Directly assigned ones only A = All resources (even subordinate levels) (PDM field ID: RES.OPT:TYPGL)
user_c_29	userfield	char(1)	(PDM field ID: RES.FU:29)
user_c_30	userfield	char(1)	(PDM field ID: RES.FU:30)
user_c_31	userfield	char(1)	(PDM field ID: RES.FU:31)
user_c_32	userfield	char(1)	(PDM field ID: RES.FU:32)
user_c_33	userfield	char(1)	(PDM field ID: RES.FU:33)
user_c_34	userfield	char(1)	(PDM field ID: RES.FU:34)
user_c_35	userfield	char(1)	(PDM field ID: RES.FU:35)
user_c_36	userfield	char(1)	(PDM field ID: RES.FU:36)
user_c_37	userfield	char(1)	(PDM field ID: RES.FU:37)
user_c_38	userfield	char(1)	(PDM field ID: RES.FU:38)
user_c_39	userfield	char(1)	(PDM field ID: RES.FU:39)
user_c_40	userfield	char(1)	(PDM field ID: RES.FU:40)
user_c_41	userfield	char(1)	(PDM field ID: RES.FU:41)
user_c_42	userfield	char(1)	(PDM field ID: RES.FU:42)
user_c_43	userfield	char(1)	(PDM field ID: RES.FU:43)
user_c_44	userfield	char(1)	(PDM field ID: RES.FU:44)
user_c_45	userfield	char(10)	(PDM field ID: RES.FU:45)
user_c_46	userfield	char(10)	(PDM field ID: RES.FU:46)
user_c_47	userfield	char(10)	(PDM field ID: RES.FU:47)
user_c_48	userfield	char(10)	(PDM field ID: RES.FU:48)
user_c_49	userfield	char(10)	(PDM field ID: RES.FU:49)
user_c_50	userfield	char(10)	(PDM field ID: RES.FU:50)

user_c_51	userfield	char(20)	(PDM field ID: RES.FU:51)
user_c_52	userfield	char(20)	(PDM field ID: RES.FU:52)
user_c_53	userfield	char(20)	(PDM field ID: RES.FU:53)
user_c_54	userfield	char(20)	(PDM field ID: RES.FU:54)
user_c_55	userfield	char(20)	(PDM field ID: RES.FU:55)
user_c_56	userfield	char(20)	(PDM field ID: RES.FU:56)
user_c_57	userfield	char(20)	(PDM field ID: RES.FU:57)
user_c_58	userfield	char(20)	(PDM field ID: RES.FU:58)
user_c_59	userfield	char(20)	(PDM field ID: RES.FU:59)
user_c_60	userfield	char(20)	(PDM field ID: RES.FU:60)
user_c_61	userfield	char(20)	(PDM field ID: RES.FU:61)
user_c_62	userfield	char(20)	(PDM field ID: RES.FU:62)
user_c_63	userfield	char(20)	(PDM field ID: RES.FU:63)
user_c_64	userfield	char(20)	(PDM field ID: RES.FU:64)
user_c_65	userfield	char(40)	(PDM field ID: RES.FU:65)
user_c_66	userfield	char(40)	(PDM field ID: RES.FU:66)
user_code	User field key	char(8)	User field key Reference to configuration of the user field key or its user fields in the HYD_USERFIELDCFG table (PDM field ID: RES.USRFLD)
user_d_01	userfield	date	(PDM field ID: RES.FU:1)
user_d_02	userfield	date	(PDM field ID: RES.FU:2)
user_d_03	userfield	date	(PDM field ID: RES.FU:3)
user_d_04	userfield	date	(PDM field ID: RES.FU:4)
user_d_05	userfield	date	(PDM field ID: RES.FU:5)
user_d_06	userfield	date	(PDM field ID: RES.FU:6)
user_f_23	userfield	decimal(18,6)	(PDM field ID: RES.FU:23)
user_f_24	userfield	decimal(18,6)	(PDM field ID: RES.FU:24)
user_f_25	userfield	decimal(18,6)	(PDM field ID: RES.FU:25)
user_f_26	userfield	decimal(18,6)	(PDM field ID: RES.FU:26)

user_f_27	userfield	decimal(18,6)	(PDM field ID: RES.FU:27)
user_f_28	userfield	decimal(18,6)	(PDM field ID: RES.FU:28)
user_n_07	userfield	integer	(PDM field ID: RES.FU:7)
user_n_08	userfield	integer	(PDM field ID: RES.FU:8)
user_n_09	userfield	integer	(PDM field ID: RES.FU:9)
user_n_10	userfield	integer	(PDM field ID: RES.FU:10)
user_n_11	userfield	integer	(PDM field ID: RES.FU:11)
user_n_12	userfield	integer	(PDM field ID: RES.FU:12)
user_n_13	userfield	integer	(PDM field ID: RES.FU:13)
user_n_14	userfield	integer	(PDM field ID: RES.FU:14)
user_n_15	userfield	integer	(PDM field ID: RES.FU:15)
user_n_16	userfield	integer	(PDM field ID: RES.FU:16)
user_n_17	userfield	integer	(PDM field ID: RES.FU:17)
user_n_18	userfield	integer	(PDM field ID: RES.FU:18)
user_n_19	userfield	integer	(PDM field ID: RES.FU:19)
user_n_20	userfield	integer	(PDM field ID: RES.FU:20)
user_n_21	userfield	integer	(PDM field ID: RES.FU:21)
user_n_22	userfield	integer	(PDM field ID: RES.FU:22)
usrfld_key	Userfeldkey	char(20)	Redundant, as this one is determined via the resource type or the resource family Please note: The field does not have separate acronym, i.e. RES.USRFLD is not responsible for this. The field content is automatically filled when the resource is created due to its resource type or resource family.
verantw_bereich	Responsibility area	char(15)	Responsibility area to which the resource applies, analogous to PZE (PDM field ID: RES.VAB)
verantw_nr	Party in charge	char(50)	
verantw_typ	P.i.charge type	char(50)	
verwendung	Usage	char(50)	
waehrung	ISO currency code	char(3)	ISO currency code (PDM field ID: RES.WAEHRUNG)
zeich_nr	drawing issue number	char(40)	drawing issue number (PDM field ID: RES.ZEICHNR)

13.6. res_familien

Table name: res_familien		Product: WRM	
Designation: Resource families			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bez_lang	Long designation	char(60)	Long designation (PDM field ID: RESFAM.BEZL)
bezeichnung	External designation of the family	char(20)	External designation of the family (PDM field ID: RESFAM.RESFAM)
default_resname	WRM/DNC: Default resource name	char(50)	WRM/DNC: Default resource name (PDM field ID: RESFAM.VORG:RES)
kopie_param	Performance when copying a resource	char(1)	V = When copying a resource also copy its file as link without duplicating the file itself K = When copying a resource also copy its file and save it under a new name (PDM field ID: RESFAM.OPT:KOPIE)
mit_einstelldaten	Parameters for viewer	char(1)	Parameters indicating which data are available for the viewer: J = DNC program AND setting data in tabular form N = Read DNC files only (PDM field ID: RESFAM.OPT:EINST)
namenskonvention	WRM/DNC: Autom. naming	integer	In future: function to generate file names automatically (PDM field ID: RESFAM.FKT:SPEICHORT)
opt_konfig	Configuration parameters	char(10)	Configuration parameters (PDM field ID: RESFAM.CFG:1..10)
param_str_01		char(10)	- for future use -
param_str_02		char(20)	- for future use -
param_str_03		char(30)	- for future use -
pdouble_01		decimal(18,8)	- for future use -
plong_01		integer	- for future use -
plong_02		integer	- for future use -
pshort_01		smallint	- for future use -
res_familie	Identity of resource family	serial	Identity of resource family (PDM field ID: RESFAM.RESFAMID)
res_typ	Resource type of the family	char(4)	Resource type of the family (PDM field ID: RESFAM.RESTYP)
speicherart	Memory type of the family	char(1)	RSM/DNC: File or directory or package or package element (at first not used) (PDM field ID: RESFAM.SPEICHART)
usrfld_key	Assigned user field ID	char(20)	External key for the hyd_userfieldcfg table (PDM field ID: RESFAM.USRFLD)
verantw_bereich	Responsibility area	char(15)	Responsibility area (PDM field ID: RESFAM.VAB)
versionsverfahren		char(10)	Without function (PDM field ID: RESFAM.OPT:RESVER)
viewer	Viewer to display resource file	char(10)	Viewer to display resource file (PDM field ID: RESFAM.VIEWER:DATA)
viewer_param	Parameter fields for viewer	char(10)	Parameter fields for viewer (PDM field ID: RESFAM.VIEWER:EINST)

13.7. res_masch_dncfam

Table name: res_masch_dncfam		Product: WRM	
Designation: assignment of machine to resource family			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
masch_nr	Machine number	char(20)	Machine number (PDM field ID: MNRDNCFAM.MNR)
mgruppe	Machine group	char(20)	Machine group (PDM field ID: MNRDNCFAM.MGRP)
res_familie	Ident of resource family	integer	Ident of resource family (PDM field ID: MNRDNCFAM.RESFAMID)
vorgabe	default indicator	char(1)	J = Default resource family for the machine N = Otherwise (PDM field ID: MNRDNCFAM.OPT:VORG)

13.8. res_massnahmen

Table name: res_massnahmen		Product: WRM	
Designation: resource activities			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bez_lang	long name	char(60)	long name (PDM field ID: RESMASS.BEZL)
bezeichnung	short name	char(20)	short name (PDM field ID: RESMASS.BEZK)
guelt_dat_bis		date	Not used (PDM field ID: RESMASS.DATE)
guelt_dat_von		date	Not used (PDM field ID: RESMASS.DATB)
guelt_zei_bis		integer	Not used (PDM field ID: RESMASS.ZEIE)
guelt_zei_von		integer	Not used (PDM field ID: RESMASS.ZEIB)
klassifikation		char(15)	Classification which can be evaluated
kommentar	Comment	char(500)	Comment (PDM field ID: RESMASS.BEM)
massnahme	ID of the measure	integer	ID; differentiation of the single data records; entered by the user. (PDM field ID: RESMASS.MASSNR)
param_str_01		char(10)	- for future use -
param_str_02		char(20)	- for future use -
param_str_03		char(30)	- for future use -
pdouble_01		decimal(18,8)	- for future use -
plong_01		integer	- for future use -
plong_02		integer	- for future use -
pshort_01		smallint	- for future use -
res_familie	reference to resource family	integer	Resource family = attribute group; foreign key of res_familie table (PDM field ID: RESMASS.RESFAMID)
res_typ	Resource type	char(4)	Resource type > currently not evaluated (PDM field ID: RESMASS.RESTYP)
typ	Type of the measure	char(1)	Currently M only = measure (PDM field ID: RESMASS.TYP)
verantw_bereich	responsibility area	char(15)	responsibility area (PDM field ID: RESMASS.VAB)

13.9. res_ress_belegung

Table name: res_ress_belegung		Product: WRM	
Designation: Ressourcenbelegung		Description: Die Tabelle verwaltet die Zuordnung Auftrag zu Werkzeug und die Sperrdaten eines Werkzeugs	
Column name	Column designation	Type	Description
anzahl		integer	Benötigte Anzahl der Ressource Format N8.2 Also 1.50 = 150
bearb		char(10)	
bearb_datum		date	
bearb_zeit		integer	
bel_bis_dat		date	Wird bei Belegungsart A nicht benötigt Bei Wartung oder Sperre für Werkzeugbelegung (HLS)
bel_bis_zeit		integer	Wird bei Belegungsart A nicht benötigt. Bei Wartung oder Sperre für Werkzeugbelegung (HLS)
bel_von_dat		date	Wird bei Belegungsart A nicht benötigt Bei Wartung oder Sperre für Werkzeugbelegung (HLS)
bel_von_zeit		integer	Wird bei Belegungsart A nicht benötigt. Bei Wartung oder Sperre für Werkzeugbelegung (HLS)
belegungsart	Art der Belegung	char(4)	Art der Belegung (Anzeige im HLS) A = Auftrag S = Sperre W = Wartung
field1		char(20)	
field2		char(20)	
field3		char(20)	
field4		char(20)	
field5		char(20)	
firma	Firma der Ressource	char(10)	
key	Eindeutiger Schlüssel	char(40)	KEY = Auftrag, wenn nicht Wartung oder Sperre (verwendet Werkzeugbelegung im HLS)
param1		integer	
param2		integer	
param3		integer	
param4		integer	
param5		integer	
res_version	Version	char(20)	
ress_typ	Typ der Ressource	char(4)	Typ der Ressource aus Tabelle res_ress_typen.typ WZ o. WNR, ... = Werkzeug
ressource	Ressourcen ID	char(40)	Ressource (Werkzeug,...) (verwendet Werkzeugbelegung im HLS)

13.10. res_ress_typen

Table name: res_ress_typen		Product: WRM	
Designation: Ressourcentypen			
Column name	Column designation	Type	Description
bearb		char(10)	letzter Bearbeiter
bearb_datum		date	
bearb_zeit		integer	
bezeichnung		char(40)	Bezeichnung der Ressource
field1		char(20)	
field2		char(20)	
field3		char(20)	
field4		char(20)	
field5		char(20)	
param1		integer	
param2		integer	
param3		integer	
param4		integer	
param5		integer	
position		integer	
typ		char(4)	Type der Ressource M = Maschine WZ = Werkzeug

13.11. res_status

Table name: res_status		Product: WRM	
Designation: Resource status			
Column name	Column designation	Type	Description
aktiv	Resource active	char(1)	J = resource is logged on to a machine N = resource is not logged on to a machine anymore (PDM field ID: RES.AKTIV)
aktueller_lagerort	Current storage location	char(12)	Current storage location if not in storage of origin (res_bestand.lagerort) (PDM field ID: RES.MATPUF:l)
auftrag_nr	Last order which resource is logged onto	char(40)	Last order which resource is logged onto (PDM field ID: RES.ANR)
aus_bas	Scrap	decimal(18,6)	Scrap in base quantity unit (PDM field ID: EGR:AUSB)
aus_pri	Scrap	decimal(18,6)	Scrap in primary quantity unit (PDM field ID: EGR:AUSP)
aus_sek	Scrap	decimal(18,6)	Scrap in secondary quantity unit (PDM field ID: EGR:AUSS)
aus_ter	Scrap	decimal(18,6)	Scrap in tertiary quantity unit (PDM field ID: EGR:AUST)
beginn_dat	Date for start of status	date	Date for start of status
beginn_zei	Time at start of status	integer	Time at start of status
bmk_01	SUT	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK01)
bmk_02	DCI	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK02)
bmk_03	LCI	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK03)
bmk_04	SCI	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK04)
bmk_05	IMN	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK05)
bmk_06	IMS	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK06)
bmk_07	SET	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK07)
bmk_08	STA	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK08)
bmk_09	U8	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK09)
bmk_10	U9	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK10)
bmk_11	MUT	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK11)
bmk_12	BKS	integer	Resource performance account 1 to 12 (PDM field ID: RES.EGR:BMK12)
farbe	Color of status	smallint	Color of status (PDM field ID: RES.COLOR)
gut_bas	Yield	decimal(18,6)	Yield in base quantity unit (PDM field ID: EGR:GUTB)

gut_pri	Yield	decimal(18,6)	Yield in primary quantity unit (PDM field ID: EGR:GUTP)
gut_sek	Yield	decimal(18,6)	Yield in secondary quantity unit (PDM field ID: EGR:GUTS)
gut_ter	Yield	decimal(18,6)	Yield in tertiary quantity unit (PDM field ID: EGR:GUTT)
hub_gesamt	Total strokes	decimal(18,6)	Total strokes (PDM field ID: HUB)
hub_gut	Strokes yield	decimal(18,6)	Strokes, yield (PDM field ID: HUBG)
ist_ausschuss	Total scrap of the resource	decimal(18,6)	Total scrap of the resource (PDM field ID: RES.EGR:AUS)
ist_dauer	Total time of the resource	integer	Total time of the resource (PDM field ID: RES.EGR:DAUER)
ist_hub	Total stroke counter of the resource	decimal(18,6)	Total stroke counter of the resource (PDM field ID: RES.EGR:HUB)
ist_len	Counter of lengths of the resource	decimal(18,6)	Counter of lengths of the resource (PDM field ID: RES.EGR:LEN)
ist_lst_01		decimal(18,6)	Actual activity 1 to 6 (PDM field ID: RES.EGR:1)
ist_lst_02		decimal(18,6)	Actual activity 1 to 6 (PDM field ID: RES.EGR:2)
ist_lst_03		decimal(18,6)	Actual activity 1 to 6 (PDM field ID: RES.EGR:3)
ist_lst_04		decimal(18,6)	Actual activity 1 to 6 (PDM field ID: RES.EGR:4)
ist_lst_05		decimal(18,6)	Actual activity 1 to 6 (PDM field ID: RES.EGR:5)
ist_lst_06		decimal(18,6)	Actual activity 1 to 6 (PDM field ID: RES.EGR:6)
ist_stck	Total number of resource	decimal(18,6)	contains the yield quantity (not the actual quantity) (PDM field ID: RES.EGR:GUT)
kbn_egr	Actual kanban quantity	decimal(18,6)	 (PDM field ID: RES.KBN:EGR)
masch_nr	Machine number	char(20)	Last machine which resource is logged onto (PDM field ID: RES.MNR)
massnahme	Current measure	integer	Is set via HYDDI RES_MASS
meinheit_bas		char(3)	Base quantity unit (PDM field ID: SGE:B)
meinheit_pri		char(3)	Primary quantity unit (PDM field ID: SGE:P)
meinheit_sek		char(3)	Secondary quantity unit (PDM field ID: SGE:S)
meinheit_ter		char(3)	Tertiary quantity unit (PDM field ID: SGE:T)
nacharb_bas		decimal(18,6)	Rework quantity in base quantity unit (PDM field ID: EGR:NCHB)
nacharb_pri		decimal(18,6)	Rework quantity in secondary quantity unit (PDM field ID: EGR:NCHP)
nacharb_sek		decimal(18,6)	Rework quantity in secondary quantity unit (as of version HYDRA-WRM 7.2) (PDM field ID: EGR:NCHS)
nacharb_ter		decimal(18,6)	Rework quantity in tertiary quantity unit (PDM field ID: EGR:NCHT)
neuer_status	New status	integer	If the times (status_dat_von + status_dat_zei) are reached the resource is converted to this status (done by server program resource check)

opt_version	Flag, whether it is optimized version	char(1)	Flag, whether it is optimized version (PDM field ID: RES.OPT:OPTVER)
param_str_01		char(10)	- for future use -
param_str_02		char(20)	- for future use -
param_str_03		char(30)	- for future use -
pdouble_01		decimal(18,6)	- for future use -
plong_01		integer	- for future use -
plong_02		integer	- for future use -
problem_bas		decimal(18,6)	Problem quantity in base quantity unit (PDM field ID: EGR:PRBB)
problem_pri	Open quantity	decimal(18,6)	Problem quantity in primary quantity unit (PDM field ID: EGR:PRBP)
problem_sek		decimal(18,6)	Problem quantity in secondary quantity unit (as of HYDRA-WRM 7.2 version) (PDM field ID: EGR:PRBS)
problem_ter		decimal(18,6)	Problem quantity in tertiary quantity unit (PDM field ID: EGR:PRBT)
prot_dat		date	
prot_zeit		integer	
pshort_01		smallint	- for future use -
res_id	RES_ID from res_bestand	integer	Resource identity (PDM field ID: RES.VERWEIS)
res_nr	Resource number	char(40)	Resource number (PDM field ID: RES.RES)
res_typ	Resource type	char(4)	Resource type (PDM field ID: RES.RESTYP)
res_version	Please see RES_BESTAND	char(20)	Preassignment with 1, the version is filed here in case of NC resources (PDM field ID: RES.RESVER)
reset_dat		date	
reset_zeit		integer	
sammelsperre	Collective block counter	smallint	= 0 : no sub resource is blocked any longer > 0 : at least one sub resource is blocked Sub resource means: below bill of materials res_stueckliste (PDM field ID: RES.ANZ:SSPERR)
sammelstatus	(Currently without function)	integer	Planned: Current status on the basis of sub resources (PDM field ID: RES.SSTA)
status	Current status	integer	Current status Refers to table RESSOURCENSTATI (PDM field ID: RES.RESSTA)
status_dat_bis	Time for release status	date	If this time is reached the resource is converted to the release status (via server program resource check)
status_dat_von	Time for new status	date	If the times (status_dat_von + status_dat_zeit) are reached then the resource is converted to the "new" status (done by server program resource check)
status_zeit_bis	Time for release status	integer	If this time is reached the resource is converted to the release status (via server program resource check)
status_zeit_von	Time for new status	integer	If the times (status_dat_von + status_dat_zeit) are reached then the resource is converted to the "new" status (done by server program resource check)

13.12. res_status_assign

Table name: res_status_assign		Product: WRM	
Designation: Resource status assignments (BEVERAGE)			
Column name	Column designation	Type	Description
bearb		char(10)	(PDM field ID: BEARB)
bearb_date		date	(PDM field ID: BEARBDAT)
bearb_time		integer	(PDM field ID: BEARBZEIT)
berechtigung		char(10)	
ext_referenz	Id for optional mapping	char(20)	External ID For optional mapping: Status "from" machine 846457 ' to status 1 (PDM field ID: RESSTAASSIGN.EXTID)
gueltig_bis	Valid to	datetime	At first assigned to NULL (PDM field ID: RESSTAASSIGN.DATE)
gueltig_von	Valid from	datetime	At first assigned to NULL (PDM field ID: RESSTAASSIGN.DATB)
klasse	External classification	char(20)	External classification Optionally for evaluations (PDM field ID: RESSTAASSIGN.KLASSE)
res_familie	Family	integer	(PDM field ID: RESSTAASSIGN.RESFAMID)
res_nr	Resource	char(40)	(PDM field ID: RESSTAASSIGN.RES)
res_typ	Resource type key	char(4)	(PDM field ID: RESSTAASSIGN.RESTYP)
status	Status	decimal(10)	(PDM field ID: RESSTAASSIGN.STATUS)
status_typ	Status type	char(20)	Status type Reference to entry in res_status_type (PDM field ID: RESSTAASSIGN.STATYP)
status_uebord	Superior status	decimal(10)	Superior status For optional, hierarchical status configuration (PDM field ID: RESSTAASSIGN.STATUS:UEB)
text_id	Status text number	char(20)	Reference to status text number/ID (PDM field ID: RESSTAASSIGN.TEXTID)
user_c_07		char(1)	(PDM field ID: RESSTATXT.FU:7)
user_c_08		char(1)	(PDM field ID: RESSTATXT.FU:8)
user_c_09		char(1)	(PDM field ID: RESSTATXT.FU:9)
user_c_10		char(1)	(PDM field ID: RESSTATXT.FU:10)
user_c_11		char(1)	(PDM field ID: RESSTATXT.FU:11)
user_c_12		char(10)	(PDM field ID: RESSTATXT.FU:12)

user_c_13		char(10)	(PDM field ID: RESSTATXT.FU:13)
user_c_14		char(20)	(PDM field ID: RESSTATXT.FU:14)
user_c_15		char(20)	(PDM field ID: RESSTATXT.FU:15)
user_c_16		char(40)	(PDM field ID: RESSTATXT.FU:16)
user_code		char(8)	(PDM field ID: RESSTAASSIGN.USRFLD)
user_f_05		decimal(18,6)	(PDM field ID: RESSTATXT.FU:5)
user_f_06		decimal(18,6)	(PDM field ID: RESSTATXT.FU:6)
user_n_01		integer	(PDM field ID: RESSTATXT.FU:1)
user_n_02		integer	(PDM field ID: RESSTATXT.FU:2)
user_n_03		integer	(PDM field ID: RESSTATXT.FU:3)
user_n_04		integer	(PDM field ID: RESSTATXT.FU:4)
verantw_bereich		char(15)	(PDM field ID: RESSTAASSIGN.VAB)
verbuchung		char(10)	[1,1] Reserved Affects posting of quantity counters - empty ' posting according to counter configuration (by default) - A ' Quantity counter posted as scrap - X ' Quantity counter is not posted with this status This option does not affect consumption meters (PDM field ID: RESSTAASSIGN.OPT:VERBMENGE)
verweis	Reference	serial	Unique reference (is referenced from the res_status_recording table, for example) (PDM field ID: RESSTAASSIGN.VERWEIS)

13.13. res_status_booking

Table name: res_status_booking		Product: WRM	
Archive table: a_res_status_booking		Reload table: r_res_status_booking	
Designation: Resource status booking (BEVERAGE)			
Column name	Column designation	Type	Description
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
begin_ts	Beginning of status	datetime	
bmk_01		integer	
bmk_02		integer	
bmk_03		integer	
bmk_04		integer	
bmk_05		integer	
bmk_06		integer	
bmk_07		integer	
bmk_08		integer	
bmk_09		integer	
bmk_10		integer	
bmk_11		integer	
bmk_12		integer	
dauer	Duration	integer	
dlg_data_verweis		integer	
end_ts	End of status	datetime	
erfass_ts		datetime	
herkunft		char(3)	empty = recorded, valid data record "O" ' Original record "E" ' Manually generated data record (edited) "S" ' Cancellation
hyuser		integer	
rck		char(1)	
rck01		char(1)	
rck01_date		datetime	
rck02		char(1)	
rck02_date		datetime	
rck_date		datetime	
reasoncode		char(10)	Optional code (recording with status starting (RES_STB) Default: empty
res_familie		integer	
res_id		integer	
res_nr		char(40)	
res_typ		char(4)	
satz_art		char(1)	"P" ' Log record

schichtanf		integer	
schichtart		char(1)	
schichtdat		date	
schichtend		integer	
schichtmodell		smallint	
schichtnr		smallint	
schichtpause		smallint	
status	Status	decimal(10)	
status_typ	Status type	char(20)	Reference to entry in res_status_type
text_id		char(20)	Reference to status text number/ID
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	

user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	
user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
verweis		serial	

13.14. res_status_recording

Table name: res_status_recording		Product: WRM	
Designation: Resource status recording (BEVERAGE)			
Column name	Column designation	Type	Description
anmeld_dat		date	
anmeld_zeit		integer	
bearb		char(10)	
bearb_date		date	
bearb_time		integer	
bmk_01		integer	
bmk_02		integer	
bmk_03		integer	
bmk_04		integer	
bmk_05		integer	
bmk_06		integer	
bmk_07		integer	
bmk_08		integer	
bmk_09		integer	
bmk_10		integer	
bmk_11		integer	
bmk_12		integer	
dauer		integer	Duration = total of RPA 1...11
dauer_seit_stb		integer	Duration since status begining
erfass_dat		date	
erfass_zeit		integer	
hyuser		integer	
prod_kenn		char(2)	"L" - status is active is automatically set when status begin is set (RES_STB) "F" - autom. interrupted is automatically set when a shift pause is started (A_AUN)
prot_dat		date	Last update time (of duration accounts)
prot_zeit		integer	Last update time (of duration accounts)
reasoncode		char(10)	Optional code (recording with status starting (RES_STB) Default: empty
res_familie	Family	integer	
res_id		integer	
res_nr	Resource	char(40)	
res_sta_verweis		integer	Reference to the basic entry in the res_status_assign table
res_typ	Resource type key	char(4)	
schichtanf		integer	
schichtart		char(1)	
schichtdat		date	
schichtend		integer	

schichtmodell		smallint	
schichtnr		smallint	
schichtpause		smallint	
status		decimal(10)	
status_type	Status type	char(20)	Reference to the entry in the res_status_type table
text_id		char(20)	Reference to status text number/ID
user_c_29		char(1)	
user_c_30		char(1)	
user_c_31		char(1)	
user_c_32		char(1)	
user_c_33		char(1)	
user_c_34		char(1)	
user_c_35		char(1)	
user_c_36		char(1)	
user_c_37		char(1)	
user_c_38		char(1)	
user_c_39		char(1)	
user_c_40		char(1)	
user_c_41		char(1)	
user_c_42		char(1)	
user_c_43		char(1)	
user_c_44		char(1)	
user_c_45		char(10)	
user_c_46		char(10)	
user_c_47		char(10)	
user_c_48		char(10)	
user_c_49		char(10)	
user_c_50		char(10)	
user_c_51		char(20)	
user_c_52		char(20)	
user_c_53		char(20)	
user_c_54		char(20)	
user_c_55		char(20)	
user_c_56		char(20)	
user_c_57		char(20)	
user_c_58		char(20)	
user_c_59		char(20)	
user_c_60		char(20)	
user_c_61		char(20)	
user_c_62		char(20)	
user_c_63		char(20)	
user_c_64		char(20)	
user_c_65		char(40)	
user_c_66		char(40)	
user_code		char(8)	
user_d_01		date	

user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	

13.15. res_status_text

Table name: res_status_text		Product: WRM	
Designation: Resource status text (BEVERAGE)			
Column name	Column designation	Type	Description
bearb	Modified by	char(10)	(PDM field ID: BEARB)
bearb_date		date	(PDM field ID: BEARBDAT)
bearb_time		integer	(PDM field ID: BEARBZEIT)
res_familie	Family	integer	(PDM field ID: RESSTATXT.RESFAMID)
res_typ	Resource type key	char(4)	(PDM field ID: RESSTATXT.RESTYP)
rgbcolor	Color	integer	(PDM field ID: RESSTATXT.RGBCOLOR)
status_typ	Status type	char(20)	Status type Reference to entry in res_status_type (PDM field ID: RESSTATXT.STATYP)
text		char(80)	(PDM field ID: RESSTATXT.TEXT)
text_id	Status text number	char(20)	Status text number/ID May be a number (if necessary, even with leading zeros) or a combination of machine + ID (e.g. MASCH100-1, MASCH200-8534346). (PDM field ID: RESSTATXT.TEXTID)
user_c_07		char(1)	(PDM field ID: RESSTATXT.FU:7)
user_c_08		char(1)	(PDM field ID: RESSTATXT.FU:8)
user_c_09		char(1)	(PDM field ID: RESSTATXT.FU:9)
user_c_10		char(1)	(PDM field ID: RESSTATXT.FU:10)
user_c_11		char(1)	(PDM field ID: RESSTATXT.FU:11)
user_c_12		char(10)	(PDM field ID: RESSTATXT.FU:12)
user_c_13		char(10)	(PDM field ID: RESSTATXT.FU:13)
user_c_14		char(20)	(PDM field ID: RESSTATXT.FU:14)
user_c_15		char(20)	(PDM field ID: RESSTATXT.FU:15)
user_c_16		char(40)	(PDM field ID: RESSTATXT.FU:16)
user_code		char(8)	(PDM field ID: RESSTATXT.USRFLD)
user_f_05		decimal(18,6)	(PDM field ID: RESSTATXT.FU:5)

user_f_06		decimal(18,6)	(PDM field ID: RESSTATXT.FU:6)
user_n_01		integer	(PDM field ID: RESSTATXT.FU:1)
user_n_02		integer	(PDM field ID: RESSTATXT.FU:2)
user_n_03		integer	(PDM field ID: RESSTATXT.FU:3)
user_n_04		integer	(PDM field ID: RESSTATXT.FU:4)
verantw_bereich	Responsibility area	char(15)	(PDM field ID: RESSTATXT.VAB)

13.16. res_status_type

Table name: res_status_type		Product: WRM	
Designation: Resource status types (BEVERAGE)			
Column name	Column designation	Type	Description
bearb	Modified by	char(10)	(PDM field ID: BEARB)
bearb_date		date	(PDM field ID: BEARBDAT)
bearb_time		integer	(PDM field ID: BEARBZEIT)
beleggenerierung		char(10)	1,1]=Generation of documents J - the status generates posting events and documents N - the status only generates posting events but no documents By default "N" (PDM field ID: RESSTATYP.OPT:BELEGE)
bezeichnung		char(80)	(PDM field ID: RESSTATYP.BEZ)
res_familie	Family	integer	(PDM field ID: RESSTATYP.RESFAMID)
res_typ	Target resource family	char(4)	(PDM field ID: RESSTATYP.RESTYP)
schichtwechsel		char(10)	1,1]=Implicit status change when the shift changes J - The change of shifts resets the status, i.e. a document is generated, if necessary N - The change of shifts does not influence the status By default "N" (PDM field ID: RESSTATYP.OPT.SCHICHTWECHSEL)
script	Script	char(80)	The user exit may be defined here. It is executed if a status change takes place for an object (of the resource type/resource family): UX only returns the status, it does not perform the actual status change (PDM field ID: RESSTATYP.SCRIPT)
status_typ	Status type	char(20)	Status type Could be: MST machine status RESSTA Resource status UEBSTA Monitoring status STA1 Malfunctions or "100" Operation mode "200" Program etc. Processing does not depend on the status type (abbreviation). Each processing depends on the configuration. (PDM field ID: RESSTATYP.STATYP)
statusaktualisierung		char(10)	1,1]=Status update J - the current status is separately defined online N - the status only generates posting events but no "current status" By default "J" (PDM field ID: RESSTATYP.OPT:STATUS)

statuswechsel	Status change	char(1)	Status change J - setting a status replaces the previously available status = serial status N - a status is explicitly logged on or off. These statuses may be available at the same time or not at all = parallel status At first only "J" = "Serial statuses" are supported By default "J" (PDM field ID: RESSTATYP.OPT:WECHSEL)
user_c_07		char(1)	(PDM field ID: RESSTATYP.FU:7)
user_c_08		char(1)	(PDM field ID: RESSTATYP.FU:8)
user_c_09		char(1)	(PDM field ID: RESSTATYP.FU:9)
user_c_10		char(1)	(PDM field ID: RESSTATYP.FU:10)
user_c_11		char(1)	(PDM field ID: RESSTATYP.FU:11)
user_c_12		char(10)	(PDM field ID: RESSTATYP.FU:12)
user_c_13		char(10)	(PDM field ID: RESSTATYP.FU:13)
user_c_14		char(20)	(PDM field ID: RESSTATYP.FU:14)
user_c_15		char(20)	(PDM field ID: RESSTATYP.FU:15)
user_c_16		char(40)	(PDM field ID: RESSTATYP.FU:16)
user_code		char(8)	User field key (PDM field ID: RESSTATYP.USRFLD)
user_f_05		decimal(18,6)	(PDM field ID: RESSTATYP.FU:5)
user_f_06		decimal(18,6)	(PDM field ID: RESSTATYP.FU:6)
user_n_01		integer	(PDM field ID: RESSTATYP.FU:1)
user_n_02		integer	(PDM field ID: RESSTATYP.FU:2)
user_n_03		integer	(PDM field ID: RESSTATYP.FU:3)
user_n_04		integer	(PDM field ID: RESSTATYP.FU:4)
verantw_bereich		char(15)	Responsibility area (may also be empty) (PDM field ID: RESSTATYP.VAB)

13.17. res_status_zuord

Table name: res_status_zuord		Product: WRM	
Designation: Resource status assignments			
Column name	Column designation	Type	Description
anzeige_terminal	Display of resource on the terminal	char(1)	(J/N) (PDM field ID: RESSTA.OPT:SIBTNR)
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
berecht_stufe	Authorization level	smallint	authorization level of status (PDM field ID: RESSTA.STUFE)
farbe	Color of the status	smallint	Color of status (PDM field ID: RESSTA.COLOR)
geloescht	Deleted	char(1)	
guelt_dat_bis		date	- for future use -
guelt_dat_von		date	- for future use -
guelt_zei_bis		integer	- for future use -
guelt_zei_von		integer	- for future use -
lagerort	Storage location when setting the status	char(12)	Storage location when setting the status (PDM field ID: RESSTA.MATPUF)
param_str_01		char(10)	- for future use -
param_str_02		char(20)	- for future use -
param_str_03		char(30)	- for future use -
pdouble_01		decimal(18,8)	- for future use -
plong_01		integer	- for future use -
plong_02		integer	- for future use -
prioritaet	Priority	smallint	For future use (PDM field ID: RESSTA.PRIO)
prod	Update indicator	char(1)	Indicator for posting: These characters may only occur once per type (or family) (uniqueness) F =Release status (status when releasing a resource) B = Logoff status (status for logging a resource off) O = Upload status, after uploading a optimized program U = Upload status, after uploading a programm S = Automatic lock status L = resource is deleted (DNC 7.2) I = Initial status (when inserting a new resource) (DNC 7.2) (PDM field ID: RESSTA.OPT:PKENN)
pshort_01		smallint	- for future use -
res_familie	Identity of resource family	integer	Optional indication. If empty, RESTYP applies. If filled, this value also applies (PDM field ID: RESSTA.RESFAMID)
res_typ	Resource type	char(4)	resource type (PDM field ID: RESSTA.RESTYP)
status	Status	integer	Status (PDM field ID: RESSTA.RESSTA)
statustext	Status designation	char(20)	status designation (PDM field ID: RESSTA.BEZ)

verarb_erfass	Collection/processing	char(1)	S = Resource is blocked for collection/processing F = Resource is released for collection/processing (PDM field ID: RESSTA.OPT:ERF)
verarb_planung	HLS assignment	char(1)	Assignment in HLS: K = No assignment within HLS W = Assigned, i.e. shop floor scheduling checks it (PDM field ID: RESSTA.OPT:PLAN)

13.18. res_stueckliste

Table name: res_stueckliste		Product: WRM	
Designation: resource list			
Column name	Column designation	Type	Description
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
guelt_dat_bis	valid to	date	Not used (PDM field ID: RESLIST.DATE)
guelt_dat_von	valid from	date	Not used (PDM field ID: RESLIST.DATB)
menge	default 1 in case of anonymous resources	decimal(18,6)	--- (PDM field ID: RESLIST.MENGE)
param_str_01		char(10)	- for future use -
param_str_02		char(20)	- for future use -
param_str_03		char(30)	- for future use -
pdouble_01		decimal(18,8)	- for future use -
plong_01		integer	- for future use -
plong_02		integer	- for future use -
position	Display position	integer	Display position (PDM field ID: RESLIST.POS)
pshort_01		smallint	- for future use -
res_id_m	Superior resource	integer	Superior resource (PDM field ID: RESLIST.RESVERWEIS:M)
res_id_t	subordinate resource	integer	subordinate resource (PDM field ID: RESLIST.RESVERWEIS:T)
res_typ_m	Superior resource type	char(4)	Superior resource type (PDM field ID: RESLIST.RESTYP:M)
res_typ_t	Subordinate resource type	char(4)	Subordinate resource type (PDM field ID: RESLIST.RESTYP:T)

13.19. res_typen

Table name: res_typen		Product: WRM	
Designation: resource type			
Column name	Column designation	Type	Description
auswertung	display in evaluations	char(10)	J = Yes (default) N = No (e.g. for people) S = Use value defined for the resource (PDM field ID: RESTYP.OPT:AZSWSIB)
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
bebuchbar	posting of resource	char(1)	J = is to be posted N= no posting (PDM field ID: RESTYP.OPT:VERB)
belegung	assignment within HLS	char(1)	Specification of assignment within HLS: N = No G = Total time (R+H) R = Setup time H = Planned time S = Use values defined for resource Level 1: N or G only (PDM field ID: RESTYP.PLAUS:BEL)
bez_lang	Long name	char(60)	Long name (PDM field ID: RESTYP.BEZL)
bezeichnung	Name of RESTYP that is visible to custom	char(10)	Name of RESTYP that is visible to customers (PDM field ID: RESTYP.RESTYPEXT)
bm_k_01_flg	posting in case of hours of operation	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK1)
bm_k_02_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK2)
bm_k_03_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK3)
bm_k_04_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK4)
bm_k_05_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK5)
bm_k_06_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK6)
bm_k_07_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK7)
bm_k_08_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK8)
bm_k_09_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK9)

bmk_10_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK10)
bmk_11_flg	please see RESTYP.VERB:BMK1	smallint	0 : Do not count RPA in case of operating hours 1 : Count RPA in case of operating hours (PDM field ID: RESTYP.VERB:BMK11)
datei_basiert	resource based on files	char(1)	J = A file has to be assigned to the resource N = No file is assigned to the resource Required for DNC or DOC (PDM field ID: RESTYP.OPT:DATEI)
dnc_verarbeitung	Indicator for DNC processing	char(1)	K = No DNC processing L = Local DNC programs E = external programming tool O = Optimize method R = Replace method (DNC 7.2) V = based on version (only with active DNC-VER) (PDM field ID: RESTYP.OPT:DNC)
editierbar	internal flag if Ress.typ can be edited	char(1)	Internal flag, whether Ress.typ can be edited. (J/N) > to protect MPDV specification Ress.typen (PDM field ID: (RESTYP.EDIT))
ext_gueltig	file extension	char(5)	File extension (suffix) of the file. Indication incl. prefixed dot, e.g. ".DNC" (PDM field ID: RESTYP.EXT:GUELT)
ext_optimiert	file extension of optimized files	char(5)	File extension (suffix) of the optimized file. Indication incl. prefixed dot, e.g. ".OPT" (PDM field ID: RESTYP.EXT:OPTIM)
ext_usr1	file extension of program description 1	char(5)	DNC 7.2 (PDM field ID: RESTYP.EXT:USR1)
ext_usr2	file extension of program description 2	char(5)	DNC 7.2 (PDM field ID: RESTYP.EXT:USR2)
ext_usr3	file extension of program description 3	char(5)	DNC 7.2 (PDM field ID: RESTYP.EXT:USR3)
mit_anmelden	Log resource on/off with order	char(1)	J = Log resource on with order in case of A_AN or log it off in case of A_AB N = Do not log on/log off resource with order (for DNC always N) E = explizite log on / Changing allowed (as of version WRM 7.2) (PDM field ID: RESTYP.OPT:AUTOANMELD)
opt_konfig	configuration settings	char(10)	opt_konfig[1,1] : Status assignment allowed (J/N). Not allowed for MNR, PER, PRU, otherwise J (PDM field ID: RESTYP.CFG:1..10)
param_str_01		char(10)	- for internal use - [1,1] J/N: "display in resource list" ID RESTYP:OPT:RESTNRVIS
param_str_02		char(20)	- for future use -
param_str_03		char(30)	- for future use -
path	Verweis auf Tabelle hy_path	char(8)	The path to the file is defined in hy_path (FTP, FILE, ...) (PDM field ID: RESTYP.PATH)
pdouble_01		decimal(18,8)	- for future use -
plong_01	Angabe Intervalllänge für Verrechnungsbe	integer	(as of version MW 3.0) (PDM field ID: RESTYP.BELEGGR)
plong_02		integer	- for future use -
position		integer	Internal flag, (PDM field ID: (RESTYP.POS))
pshort_01		smallint	- for future use -
res_auto_anlegen	create resource automatically	char(1)	J/N Resources with this ID are created automatically provided that a new resource arrives via the bill of material of the PPS interfacing. (PDM field ID: RESTYP.AUTOANLAG)
res_typ	resource type	char(4)	resource type (PDM field ID: RESTYP.RESTYP)

steuerung	control	char(1)	V = consumptive resource R = non-consumptive resource (tool) In first level "R" only (PDM field ID: RESTYP.OPT:VBR)
usrfld_key	assigned user field ID	char(20)	Foreign key for hyd_userfieldcfg table (PDM field ID: RESTYP.USRFLD)

13.20. res_wartungen

Table name: res_wartungen		Product: WRM	
Designation: Resource maintenances			
Column name	Column designation	Type	Description
aktiv	Maintenance active	char(1)	J = Execute maintenance (green) N = Do not execute maintenance (gray) (PDM field ID: RESWART.AKTIV)
aktiv_typ	Activity type	char(1)	
anz_param1		char(40)	- for future use - (PDM field ID: RESWART.ANZPARAM:1)
anz_param2		char(40)	- for future use - (PDM field ID: RESWART.ANZPARAM:2)
anz_param3		integer	- for future use - (PDM field ID: RESWART.ANZPARAM:3)
arbplan_nr	Work plan	char(40)	no function (PDM field ID: RESWART.APUNR)
auftrag_nr	Order number	char(40)	Order number (PDM field ID: RESWART.ANR)
bearb		char(10)	Last editor
bearb_date		date	Last editing day
bearb_time		integer	Last editing time
beschreibung	Designation of maintenance	char(60)	Designation of maintenance (PDM field ID: RESWART.BEZ)
bezug	Reference of values	char(1)	If the type = T or B: Target values refer to: G = Total A = Related to order/OP When logging OP off (A_AN, A_AB) maintenance activity is automatically reset. (PDM field ID: RESWART.OPT:BZG)
guelt_dat_bis	For maintenance monitoring	date	For maintenance monitoring (PDM field ID: RESWART.DATE)
guelt_dat_von	For maintenance monitoring	date	For maintenance monitoring (PDM field ID: RESWART.DATB)
i_anzahl	Actual number	integer	Number of quantities recorded so far (PDM field ID: RESWART.ANZ:I)
i_betriebsstunden	Actual hours of operation	integer	Analogous to I_TAKTE (PDM field ID: RESWART.BSTD:I)
i_takte	Actual cycle	decimal(18,6)	Actual cycles. Not posted online! Is assigned by scheduler or manually in the client. Use: Display of cycles and calculation of limit display on the client and terminal. (PDM field ID: RESWART.TAKT:I)
info1		char(80)	Information value 1 to 7 (PDM field ID: RESWART.INFO:1)
info2		char(80)	Information value 1 to 7 (PDM field ID: RESWART.INFO:2)
info3		char(80)	Information value 1 to 7 (PDM field ID: RESWART.INFO:3)
info4		char(80)	Information value 1 to 7 (PDM field ID: RESWART.INFO:4)
info5		char(80)	Information value 1 to 7 (PDM field ID: RESWART.INFO:5)

info6		char(80)	Information value 1 to 7 (PDM field ID: RESWART.INFO:6)
info7		char(80)	Information value 1 to 7 (PDM field ID: RESWART.INFO:7)
jahresmodell	Year model	integer	If the type = K then reference to a year model, in which the days, on which the maintenance activity is relevant, are highlighted (PDM field ID: RESWART.BDEJMOD)
klasse	Classification of maintenance	char(10)	To classify maintenance activity (e.g. cleaning, ...); precise use still open (PDM field ID: RESWART.WARTKL)
kostentraeger	Cost object	char(40)	
letzte_wart_date	Date of last maintenance	date	Date of last maintenance (PDM field ID: RESWART.LWART:DAT)
letzte_wart_time	Time of last maintenance	integer	Time of last maintenance (PDM field ID: RESWART.LWART:ZEI)
letzte_wart_usr	Person of last maintenance	char(10)	Person of last maintenance (PDM field ID: RESWART.LWART:USR)
n_anzahl	Number till next maintenance	integer	Numbers after which the next maintenance activity is to be carried out (PDM field ID: RESWART.ANZ:N)
n_betriebsstunden	Hours of operation of next maintenance	integer	If the type = B then the operating hours (in seconds), after which the next maintenance activity is to be carried out, are indicated here (PDM field ID: RESWART.BSTD:N)
n_solltakte	Cycles of next maintenance	decimal(18,6)	If the type = T then the target cycles (absolute), after which the next maintenance activity is supposed to be carried out, are indicated here (calculated when carrying out the maintenance, absolute threshold) (PDM field ID: RESWART.TAKT:N)
n_tage	Date of next maintenance	date	If the type = Z, date on which the next maintenance activity is to be carried out (PDM field ID: RESWART.TG:N)
param_str_01	Special parameter String 1	char(10)	Stores a customer specific string (PDM field ID: RESWART.PARAM:STR1)
param_str_02		char(20)	[1,1] E: Option "single maintenance" (as of version WRM 7.2) RESWART.OPT:ONCE [2,2] = 0..9 = Authorization level for resetting maintenance ID: PNR.WARTSTUFE
param_str_03		char(30)	- for future use -
pdouble_01		decimal(18,8)	- for future use -
plan_auftrag	Planned order	char(40)	
plong_01	Inspection requirement number	integer	
plong_02		integer	Speicher die Ressourcenid einer verlinkten Ressource. (PDM field ID: RESWART.PARAM:LONG2)
prioritaet	Priority	smallint	Serves for sorting in lists. Priority determines from maintenance type: A = 10 T = 20 B = 30 Z = 40 K = 50
projekt_nr	Project no.	char(25)	
pshort_01		smallint	- for future use -
res_id	Reference to resource	integer	Reference to resource (PDM field ID: RESWART.RESVERWEIS)
s_anzahl	Target number	integer	Numbers after which a maintenance activity is to be carried out (PDM field ID: RESWART.ANZ:S)
s_betriebsstunden	Target hours of operation	integer	If the type = B then the operating hours (in seconds), after which a maintenance activity is to be carried out, are indicated here (PDM field ID: RESWART.BSTD:S)
s_solltakte	Target cycles	decimal(18,6)	If the type = T then the number of target cycles, after which a maintenance activity is to be carried out, is indicated here (input, delta value) (PDM field ID: RESWART.TAKT:S)

s_tage	Target days	integer	If the type = Z then the number of days, after which a maintenance activity is to be carried out, is indicated here. (PDM field ID: RESWART.TG:S)
schwelle1	Threshold value for level 1	integer	Threshold value for level 1 (PDM field ID: RESWART.WARTG:1)
schwelle2	Threshold value for level 2	integer	Threshold value for level 2 (PDM field ID: RESWART.WARTG:2)
schwelle3	Threshold value for level 3	integer	Threshold value for level 3 (PDM field ID: RESWART.WARTG:3)
wart_id	Consecutive number of maintenance activi	serial	Consecutive number of maintenance activity (PDM field ID: RESWART.VERWEIS)
wartungsart	Maintenance type	char(2)	A = number (only with alarm management) T = based on cycles B = operating hours Z = based on time(days) K = vi calendar (level 2) -> K and A are not supported in level 1 "Next maintenance": Determine the "color" of each maintenance (depending on threshold values - compare section 2.6.2 below the table); red means highest priority; light green means lowest priority.; within a color the priority depends on the maintenance type: A (highest priority) -> T -> B -> Z -> K (lowest priority); thus the "next maintenance" can be determined (PDM field ID: RESWART.ART)
zustand	Maintenance condition	integer	Current maintenance condition 0 : green 1 : blue 2 : yellow 3 : red This field is set by the cyclical process when reaching the respective threshold value (RES_WART) and it is reset due to the dialog RES_WART_RUECK (PDM field ID: RESWART.WARTSTA)

13.21. v_res_status_booking

Table name: v_res_status_booking		Product: WRM	
Designation: Resource status booking (BEVERAGE)			
Column name	Column designation	Type	Description
bearb		char	
bearb_date		date	
bearb_time		integer	
begin_ts		char	
bmk_01		integer	
bmk_02		integer	
bmk_03		integer	
bmk_04		integer	
bmk_05		integer	
bmk_06		integer	
bmk_07		integer	
bmk_08		integer	
bmk_09		integer	
bmk_10		integer	
bmk_11		integer	
bmk_12		integer	
dauer		integer	
dlg_data_verweis		integer	
end_ts		char	
erfass_ts		char	
herkunft		char	
hyuser		integer	
rck		char	
rck01		char	
rck01_date		char	
rck02		char	
rck02_date		char	
rck_date		char	
reasoncode		char	
res_familie		integer	
res_id		integer	
res_nr		char	
res_typ		char	
satz_art		char	
schichtanf		integer	
schichtart		char	
schichtdat		date	
schichtend		integer	

schichtmodell		smallint	
schichtnr		smallint	
schichtpause		smallint	
status		serial	
status_typ		char	
text_id		char	
user_c_29		char	
user_c_30		char	
user_c_31		char	
user_c_32		char	
user_c_33		char	
user_c_34		char	
user_c_35		char	
user_c_36		char	
user_c_37		char	
user_c_38		char	
user_c_39		char	
user_c_40		char	
user_c_41		char	
user_c_42		char	
user_c_43		char	
user_c_44		char	
user_c_45		char	
user_c_46		char	
user_c_47		char	
user_c_48		char	
user_c_49		char	
user_c_50		char	
user_c_51		char	
user_c_52		char	
user_c_53		char	
user_c_54		char	
user_c_55		char	
user_c_56		char	
user_c_57		char	
user_c_58		char	
user_c_59		char	
user_c_60		char	
user_c_61		char	
user_c_62		char	
user_c_63		char	
user_c_64		char	
user_c_65		char	
user_c_66		char	
user_code		char	
user_d_01		date	

user_d_02		date	
user_d_03		date	
user_d_04		date	
user_d_05		date	
user_d_06		date	
user_f_23		decimal(18,6)	
user_f_24		decimal(18,6)	
user_f_25		decimal(18,6)	
user_f_26		decimal(18,6)	
user_f_27		decimal(18,6)	
user_f_28		decimal(18,6)	
user_n_07		integer	
user_n_08		integer	
user_n_09		integer	
user_n_10		integer	
user_n_11		integer	
user_n_12		integer	
user_n_13		integer	
user_n_14		integer	
user_n_15		integer	
user_n_16		integer	
user_n_17		integer	
user_n_18		integer	
user_n_19		integer	
user_n_20		integer	
user_n_21		integer	
user_n_22		integer	
verweis		serial	

14. ZKS

14.1. zks_ausweis

Table name: zks_ausweis		Product: ZKS	
Designation: Badges		Description: Definition of badges that are available in the system. A record is automatically created in this table when creating a person in the PZE module.	
Column name	Column designation	Type	Description
aktiv	Active/inactive	char(1)	The badge is activated (entry "J") or deactivated (entry "N") in this field. Within the access control system only the active badges are accepted. Inactive badges are used to identify a previous owner. A badge can be contained multiple times in this table but it can only be active once. (PDM field ID: KNR.AKTIV)
alarm_ausloesen		char(1)	Defines whether an alarm is to be triggered when this badge is used (not yet in use). (PDM field ID: (reserved for future use))
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ansprechpartner	Contact person	integer	The contact person's personnel number when it comes to a visitor's badge.
art	Badge type	char(1)	Badge type "N" "Normal" badge for employees "E" Substitute badge "B" Visitor's badge "V" The badge is available but not assigned (free). (PDM field ID: KNR.ART)
ausgabe_zeit		integer	Date and time of issuing the badge
ausweis_ausgabe	Date of issue of badge	date	Date of issuing the badge. (PDM field ID: KNR.AUSGDAT)
ausweis_gruppe		smallint	This field is used to highlight badges, which were not processed, in the SAP interface.
ausweis_layout_1	Badge layout	integer	
ausweis_layout_2	Badge layout printed	integer	
ausweis_nr	Badge	char(10)	Badge number. The badge number length is defined in the basic settings (Table: setup, column: kart_nr_len). (PDM field ID: KNR.KNR)
ausweis_rueckgabe	Date of returning the badge.	date	Date of returning the badge. (PDM field ID: KNR.RCKGDAT)
ausweisdruck_datum	Badge printing	date	
ausweisdruck_zeit	Badge printing	integer	
bearb		char(10)	Last editor and corresponding editing date or time. It is assigned by BEARB.
bearb_datum		date	Last editor and corresponding editing date or time. It is assigned by DAT.
bearb_zeit		integer	Last editor and corresponding editing date or time. It is allocated by ZEI.
bildaufnahme_datum	Picture recording	date	
bildaufnahme_zeit	Picture recording	integer	
einziehen		char(1)	This field determines whether the badge is to be collected by the badge reader at the exit (entry "J") or not (other). (PDM field ID: KNR.OPT:EINZ)
firma	Company	char(4)	Company of the personnel number (PDM field ID: KNR.FIR)
grafikdatei	File name	char(20)	File name of the graphics file when an employee's picture is displayed. (PDM field ID: KNR.BILD)
gueltig_bis	End validity period	date	Validity period for the badge. If the field gueltig_bis is empty the validity period is not restricted. (PDM field ID: KNR.DATE)

gueltig_von	Start validity period	date	Validity period for the badge. If the field gueltig_bis is empty the validity period is not restricted. (PDM field ID: KNR.DATB)
infodatum_1		date	Freely configurable info value (PDM field ID: KNR.INFODATUM:1)
infodatum_2		date	Freely configurable info value (PDM field ID: KNR.INFODATUM:2)
infodatum_3		date	Freely configurable info value (PDM field ID: KNR.INFODATUM:3)
infodatum_4		date	Freely configurable info value (PDM field ID: KNR.INFODATUM:4)
infodatum_5		date	Freely configurable info value (PDM field ID: KNR.INFODATUM:5)
infotext_1		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:1)
infotext_10		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:10)
infotext_11		char(20)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:11)
infotext_12		char(20)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:12)
infotext_13		char(20)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:13)
infotext_14		char(20)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:14)
infotext_15		char(20)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:15)
infotext_16		char(10)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:16)
infotext_17		char(10)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:17)
infotext_18		char(10)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:18)
infotext_19		char(10)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:19)
infotext_2		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:2)
infotext_20		char(10)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:20)
infotext_3		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:3)
infotext_4		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:4)
infotext_5		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:5)
infotext_6		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:6)
infotext_7		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:7)
infotext_8		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:8)
infotext_9		char(40)	Freely configurable info value (PDM field ID: KNR.INFOTEXT:9)
infowert_1		integer	Freely configurable info value (PDM field ID: KNR.INFOWERT:1)

infowert_2		integer	Freely configurable info value (PDM field ID: KNR.INFOWERT:2)
infowert_3		integer	Freely configurable info value (PDM field ID: KNR.INFOWERT:3)
infowert_4		integer	Freely configurable info value (PDM field ID: KNR.INFOWERT:4)
infowert_5		integer	Freely configurable info value (PDM field ID: KNR.INFOWERT:5)
kfz_kennzeichen	Number plate	char(50)	License plate number for a visitor's badge
kfz_kennzeichen_2		char(20)	for future use
kfz_kennzeichen_3		char(20)	for future use
kommentar_1	Commentary	char(40)	Information on the issue of plant ID cards can be filed in these 2 fields. This is particularly useful for a visitor's badge in order to save e.g. the company and the intended purpose of the visit. (PDM field ID: KNR.BEM:1)
kommentar_2	Commentary	char(40)	Information on the issue of plant ID cards can be filed in these 2 fields. This is particularly useful for a visitor's badge in order to save e.g. the company and the intended purpose of the visit. (PDM field ID: KNR.BEM:2)
name		char(83)	
person_name		char(40)	The assigned person's name. This field is automatically filled with the name from the HR master data sheet in case of existing people. (PDM field ID: KNR.PNAME)
person_nr		integer	The person's personnel number whom the badge is assigned to. The personnel number 0 is entered in a visitor's badge. (PDM field ID: KNR.PNR)
person_vorname		char(20)	The assigned person's first name. This field is automatically filled with the first name from the HR master data sheet in case of existing people. (PDM field ID: KNR.PVORNAME)
person_vorname_2		char(20)	
pincode	Pin code	char(20)	Pin code of the badge. (PDM field ID: KNR.PIN)
rueckgabe_zeit	Badge return	integer	Date and time of returning the badge
satznum_zks		integer	Reference to accessing the last access (verweis field in the table zks_ereignis).
validierung	Validation period	char(1)	
verantw_bereich		char(15)	Responsibility area which this badge is assigned to.
verweis	Reference	serial	Unique record number to access the data record (PDM field ID: KNR.VERWEIS)
zeit_bis	End validity period	integer	
zeit_von	Start validity period	integer	

14.2. zks_ausweis_gruppe

Table name: zks_ausweis_gruppe		Product: ZKS	
Designation: Access profiles		Description: Access profiles are filed in this table. Authorizations are defined per access profile so that the respective access profiles only have to be assigned to new persons (or badges). An access profile contains access authorizations (table zks_konf_azz). Access profiles and their authorizations are connected by zks_ausweis_gruppe.ausweis_gruppe = zks_konf_azz.ausweis_gruppe	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausweis_gruppe	Badge group	smallint	Unique number of badge group (PDM field ID: ZPROF.ZPROF)
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
firma	Location	char(8)	This field is used to assign holidays to the badge group. Holidays only apply for the badge group if this company corresponds to the company in the table of holidays. The company in this table does not refer to the company in the HR master data sheet and can be filled with the federal state. (PDM field ID: ZPROF.STO)
gruppe_bez	Badge group long designation	char(40)	Long name of badge group (PDM field ID: ZPROF.BEZL)
gruppe_kurzbez	Badge group short designation	char(6)	Short name of badge group (PDM field ID: ZPROF.BEZX)
verantw_bereich		char(15)	Responsibility area to which the access profile is assigned. This responsibility area is checked when assigning the access profile to badges (e.g. persons).

14.3. zks_ausweis_zuord

Table name: zks_ausweis_zuord		Product: ZKS	
Designation: Access pofile assignement		Description: Access profiles are assigned to the badges by entries in this table. Several access profiles can be assigned to one badge.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausweis_gruppe		smallint	Badge group assigned to badge (PDM field ID: KNRZPROF.ZPROF)
ausweis_nr		char(10)	Badge number (PDM field ID: KNRZPROF.KNR)
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
geloescht		char(1)	In the database deleted profile assignments remain available with the entry "J" in this field.
gueltig_bis	Valid until	date	Validity period of profile assignment (PDM field ID: KNRZPROF.DATE)
gueltig_von	Valid from	date	Validity period of profile assignment (PDM field ID: KNRZPROF.DATB)
sap_bearb		char(10)	
sap_bearb_date		date	
sap_bearb_time		integer	
verweis	Reference	serial	Unique key for accessing the data record (PDM field ID: KNRZPROF.VERWEIS)
verweis_merk		integer	Used for Authorization history
verweis_neu		integer	Used for Authorization history
verweis_original		integer	Used for Authorization history

14.4. zks_ereignis

Table name: zks_ereignis		Product: ZKS	
Designation: Event log		Description: Logging of accesses, access attempts and alarms.	
Column name	Column designation	Type	Description
ausweis_nr		char(40)	The badge number is recorded in case of accesses and access attempts
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bis_datum		date	Time until that the event was active. Start time and end time are the same for accesses and access attempts.
bis_zeit	Time	integer	Time until that the event was active. Start time and end time are the same for accesses and access attempts.
dauer	Duration	integer	Duration of the event
firma	Company	char(4)	Company of the person.
gewicht	Weight	integer	Only used for customer specific functionality
kfz_kennzeichen	Car number plate	char(20)	
person_nr		integer	Personnel number which the badge is assigned to (if available)
pincode		char(20)	for future use
rueckgemeldet		char(1)	Flag whether the data record has been uploaded to a guiding system (e.g. SAP).
satzart	Status	char(1)	The record type determines which event was logged: "A" disturbance "U" open without permission "L" opened too long "F" activated "Z" closed "O" open "S" sabotage "V" access attempt "E" access
terminal_nr		smallint	
ursache	Reason for access attempt	smallint	Reason for rejecting the access: 2001=unauthorized badge 2002=no badges loaded 2003=beyond time zone 2004=beyond opening hours 2005=wrong pin code 2006=wrong company number 2007=pocket check 2008=alarm system activated 2010=duplicate posting within lock time 2012=ring buffer for double booking is crowded 2020=other entry of security gage open 2030=already present in room zone 2031=not present in room zone 3000=wrong badge number length (PDM field ID: ZVG)
verweis	Reference	serial	Unique key to access the data record.
von_datum		date	Time when the event occurred
von_zeit	Time	integer	Time when the event occurred
zugang_nr		smallint	Number of the entry where the event was logged.

14.5. zks_feiertag

Table name: zks_feiertag		Product: ZKS	
Designation: Public holidays (Access control)		Description: The single holidays (for access control) are defined in this table.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
art	Type	char(1)	Holiday type (1-3). When assigning authorizations the settings for these 3 holiday types can be defined separately. (PDM field ID: ZKSFEITG.ART)
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
datum	Date	date	Date of holiday (PDM field ID: ZKSFEITG.DAT)
feiertag_bez	Designation	char(20)	Designation of holiday (PDM field ID: ZKSFEITG.BEZ)
firma	Location	char(8)	By means of this field public holidays can, for example, be restricted to certain federal states. If this field is empty, the public holiday applies to all access groups and badge groups, otherwise, the public holiday is only active if the company in this table corresponds to the company indicated in the access group or badge group. In this table the company does not refer to the company within the HR master data sheet and can be filled with the federal state. (PDM field ID: ZKSFEITG.STO)
verantw_bereich		char(15)	Responsibility area to which the holiday is assigned
verweis	Unique key	serial	Unique record number for accessing the data record (PDM field ID: ZKSFEITG.VERWEIS)

14.6. zks_freischaltung

Table name: zks_freischaltung		Product: ZKS	
Designation: Alarm suppression			
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb	Last editor	char(10)	Last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bis_datum	End date	date	End date (PDM field ID: ZNRFREI.DATE)
bis_zeit	End time	integer	End time (PDM field ID: ZNRFREI.ZEIE)
frei_bez	Designation	char(20)	Designation (PDM field ID: ZNRFREI.BEZL)
frei_kurzbez	Abbreviation	char(6)	Abbreviation (PDM field ID: ZNRFREI.BEZK)
verweis	Unique data record number	serial	Unique data record number
von_datum	Start date	date	Start date (PDM field ID: ZNRFREI.DATB)
von_zeit	Start time	integer	Start time (PDM field ID: ZNRFREI.ZEIB)
zugang_nr	Access point	smallint	Access point (PDM field ID: ZNRFREI.ZNR)

14.7. zks_kalender

Table name: zks_kalender		Product: ZKS	
Designation: Consecutive calendar dates (for access control)		Description: Internal table. The table ist filled by scheduler job with consecutive calendar dates. The table is used for several join operations where it is necessary to have a result row for each day.	
Column name	Column designation	Type	Description
datum	Censecutive date values	date	

14.8. zks_konf_azz

Table name: zks_konf_azz		Product: ZKS	
Designation: Access authorizations		Description: Access authorizations of access profiles. An access profile (table zks_ausweis_gruppe) contains access authorizations. Access profiles and their authorizations are connected by zks_ausweis_gruppe.ausweis_gruppe = zks_konf_azz.ausweis_gruppe	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausweis_gruppe	Access profile	smallint	Access profile (PDM field ID: ZPROFZGRP.ZPROF)
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
buerofreigabe	Office unlocked	char(1)	
cardlink		char(1)	
cardlink_tage		smallint	
datum_bis	Validity end date	date	Validity end date (PDM field ID: ZPROFZGRP.DATE)
datum_von	Validity start date	date	Validity start date (PDM field ID: ZPROFZGRP.DATB)
fuell_datum		date	---
geloescht		char(1)	Data record has been deleted (Y/N)
kon_tag	Weekdays	char(10)	not used anymore (PDM field ID: ZPROFZGRP.WTG)
taschenkontrolle	Bag check	char(1)	
verweis	Unique data record number	serial	Unique data record number
zeitzone_nr	Time zone	smallint	Time zone (PDM field ID: ZPROFZGRP.ZZ)
zugang_gruppe	Access group	smallint	Access group (PDM field ID: ZPROFZGRP.ZGRP)

14.9. zks_konf_zzz

Table name: zks_konf_zzz		Product: ZKS	
Designation: Opening hours		Description: Configuration of opening hours for accesss points.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
datum_bis	Validity start date	date	Validity start date (PDM field ID: ZGRPZZ.DATE)
datum_von	Validity end date	date	Validity end date (PDM field ID: ZGRPZZ.DATB)
fuell_datum	--	date	Obsolete. Initialized with "datum_von".
geloescht		char(1)	Data record has been deleted (Y/N)
kon_tag		char(10)	For future use (PDM field ID: ZGRPZZ.WTG)
verweis	Unique data record reference	serial	Unique data record reference
zeitzone_nr		smallint	Time Zone (PDM field ID: ZGRPZZ.ZZ)
zugang_gruppe	Access group	smallint	Access group (PDM field ID: ZGRPZZ.ZGRP)

14.10. zks_raumzonen

Table name: zks_raumzonen		Product: ZKS	
Designation: Room zones			
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb		char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
kanal_max_belegung	Channel for max. occupancy	smallint	
max_belegung	Maximum occupancy	integer	
plaus_austritt	Plausibility check when exiting	char(1)	
plaus_eintritt	Plausibility check when entering	char(1)	
protokollierung	Log attendance in room zone	char(1)	
raumzone_bez	Designation	char(40)	
raumzone_kurzbez	Short designation	char(6)	
raumzone_nr	Room zone	smallint	
verantw_bereich	Responsibilty area	char(15)	

14.11. zks_raumzonen_prot

Table name: zks_raumzonen_prot		Product: ZKS	
Designation: Room zone logging			
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
ausweis_nr		char(10)	
bearb		char(10)	
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bis_datum	Date of exit	date	
bis_zeit	Time of exit	integer	
firma	Company	char(4)	
geloescht	Deleted	char(1)	
person_nr	Person id	integer	
raumzone_nr	ID of room zone	smallint	
satzart	Status	char(1)	
verweis	Reference	serial	
von_datum	Date of entry	date	
von_zeit	Time of entry	integer	
zugang_austritt	Access point of entry	smallint	
zugang_eintritt	Access point of exit	smallint	

14.12. zks_status

Table name: zks_status		Product: ZKS	
Designation: Access point status			
Column name	Column designation	Type	Description
abgleich_datum	Date	date	
abgleich_zeit	Time	integer	
aenderung_datum		date	
aenderung_zeit	Time	integer	
alarm_aktiv		char(1)	Determination whether an alarm is currently available (J/N)
alarme	Alarms	integer	Number of alarms since beginning of the day
anz_abgleich_pers	Quantity	integer	
anz_berecht_pers	Number of authorized staff	smallint	Number of authorized people
anz_letztabgl_pers		integer	
ausweis_nr		char(10)	for future use
berecht_datum		date	Date when the authorizations were read the last time
berecht_zeit	Time	integer	Time when the authorizations were read the last time
berechtigung_lesen		char(1)	for future use
bis_datum	Date to	date	Date when the status was reported the last time
bis_zeit	Time to	integer	Time when the status was reported the last time
dauer	Duration	integer	Duration
l_alarm_verweis		integer	for future use
l_alarm_von_datum		date	for future use
l_alarm_von_zeit		integer	for future use
letztabgl_datum		date	
letztabgl_zeit		integer	
letzter_alarm		char(1)	for future use
programmname	Version	char(20)	
programmversion		char(20)	
protokoll_datum		date	
protokoll_komplett		char(1)	
protokoll_zeit	Time	integer	
satzart		char(1)	Status of the access: Z=closed O=open U=open without permission L=opened too long F=free A=disturbance S=sabotage K=no message X=offline module
satznum_zks		integer	Data record number of the last access at this entry
status_batterie		char(1)	
status_leser		char(1)	
stoerungen	Disturbances	integer	Number of disturbances since beginning of the day

verbindung_vorh		char(1)	for future use
von_datum	Start date	date	Start date
von_zeit	Start time	integer	Start time
zugang_nr		smallint	Access
zutritt_erlaubt	Allowed accesses	integer	Number of admissible accesses since beginning of the day.
zutritt_unerlaubt	Unauthorized accesses	integer	Number of accesses without permission since beginning of the day
zutritt_versuch	Access attempts	integer	Number of access attempts since beginning of the day.

14.13. zks_zeitzonen

Table name: zks_zeitzonen		Product: ZKS	
Designation: Access time models		Description: A access time odel may contain several acesss periods (table zks_zz_bereich). Key: zeitzone_nr Access time modles and their corresponding access periods are connected by zks_zeitzonen.verweis = zks_zz_bereich.verw_zeitzonen.	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
gueltig_bis		date	Validity period of the time zone. The validity start date is only defined in the field. The end date is automatically determined and entered.
gueltig_von	Valid from	date	Date as of which this time zone becomes valid. Then all previous time zones with the same number will not be valid anymore. (PDM field ID: ZZ.DATB)
verantw_bereich	---	char(15)	Responsibility area to which the time zone is assigned.
verweis	Unique record number to access the data	serial	Unique record number to access the data record.
zeitzone_bez	Long designation of time zone	char(40)	Long designation of time zone (PDM field ID: ZZ.BEZL)
zeitzone_kurzbez	Short designation of time zone	char(6)	Short designation of time zone (PDM field ID: ZZ.BEZK)
zeitzone_nr	Unique number of time zone	smallint	Unique number of time zone (PDM field ID: ZZ.ZZ)

14.14. zks_zugang

Table name: zks_zugang		Product: ZKS	
Designation: Access points		Description: Basic configuration for each access point.	
Column name	Column designation	Type	Description
aktiv	Active	char(1)	In this field "N" determines that the access is locked. No access authorizations are valid. This field contains "J" if the accesses are activated (PDM field ID: ZNR.AKTIV)
alarm_ausloesen	Trigger alarm	char(1)	Flag whether an alarm should be triggered (entry "J") in case of an active alarm system. No alarm will be triggered if this field is not activated (entry "N"). (PDM field ID: ZNR.ALARM:AKTIV)
alarm_offen	Delay time alarm	smallint	Delay time in seconds for triggering the alarm. (PDM field ID: ZNR.ALARM:TIMER)
alarm_zut_versuch		char(1)	Determines if an alarm is to be triggered due to an access attempt (not yet in use). (PDM field ID: (reserved for future use))
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
anzahl_saetze		integer	For future use (PDM field ID: ZNR.CFGANZ)
anzahl_tage		smallint	Here it is defined for how many days in advance the access configurations are to be loaded onto the terminal. (PDM field ID: ZNR.CFGANZTG)
aufzug_etage	Floor	smallint	Control of elevators: determination of the floor
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
dauer_biometrie	Validity period	smallint	
dauer_oeffner	Relay time: opener	smallint	Time of opener signal in seconds. (PDM field ID: ZNR.ZAUF:DAUER)
dauer_oeffner_2	Relay time: opener 2	smallint	
dauer_offen	Maximum duration allowed for "open" status	smallint	Max. duration of "open access" (PDM field ID: ZNR.MAXZAUF)
dauer_schliesser	Relay time: closer	smallint	Time of closer signal in seconds. (PDM field ID: ZNR.ZZU:DAUER)
dauer_taschenktrl	Relay time: signal (bag check)	smallint	Time in seconds of the signal that is used to activate the rotating flashing beacon.
dauer_versuch		smallint	For future use (PDM field ID: ZNR.ZV:DAUER)
kanal_alarm	Alarm relay	smallint	For future use (PDM field ID: ZNR.ALARM:DIGOUT)
kanal_biometrie	Biometry channel	smallint	
kanal_in_1	Channel open. pushbutton	smallint	Terminal's channel number to which a pushbutton for opening the access is connected (PDM field ID: ZNR.DIGIN:1)
kanal_in_2	Channel alarm system	smallint	Terminal's channel number to which an alarm system is connected. The entry cannot be opened if the alarm system is activated. (PDM field ID: ZNR.DIGIN:2)
kanal_in_3		smallint	For future use (PDM field ID: ZNR.DIGIN:3)
kanal_in_4		smallint	For future use (PDM field ID: ZNR.DIGIN:4)

kanal_leser	Reader	smallint	Reader number on the terminal; together with the terminal number it is a unique assignment of this access configuration to a real access. (PDM field ID: ZNR.LESER)
kanal_oeffner	Channel opener	smallint	The terminal's channel number to which an opener is connected or 0 if not available. (PDM field ID: ZNR.ZAUF:DIGOUT)
kanal_oeffner_2	Channel opener 2	smallint	
kanal_out_1		smallint	For future use (PDM field ID: ZNR.DIGOUT:1)
kanal_out_2		smallint	For future use (PDM field ID: ZNR.DIGOUT:2)
kanal_out_3		smallint	For future use (PDM field ID: ZNR.DIGOUT:3)
kanal_out_4		smallint	For future use (PDM field ID: ZNR.DIGOUT:4)
kanal_sabotage	Channel sabotage	smallint	Terminal's channel number to which a sabotage signal is connected, or 0 if not available. By means of this channel it is possible to report when the terminal or the badge reader (according to version) is opened without permission. (PDM field ID: ZNR.SAB:DIGIN)
kanal_schliesser	Channel shutter	smallint	The terminal's channel number to which a closer is connected or 0 if not available. (PDM field ID: ZNR.ZZU:DIGOUT)
kanal_taschenktrl	Channel signal (bag check)	smallint	Number of the terminal channel where a signal is output, when a bag check is to be made. A rotating flashing beacon may be connected, for example, to this channel
kanal_versuch		smallint	For future use (PDM field ID: ZNR.ZV:DIGOUT)
kanal_zugangstatus	Channel status	smallint	Terminal's channel number on which the monitoring signal "access closed" is pending or 0 if not available. (PDM field ID: ZNR.ZST:DIGIN)
konfiguration		char(20)	[1]: Acoustic alarm on the reader (J/N) (PDM field ID: ZNR.OPT:ALARMTON)
meldung_ausloesen	Report access point status	char(1)	"N": No log messages are written. "0": Alarm messages are only written. "1": In addition to alarms, access attempts are logged. "2": All accesses are logged in addition to alarms and access attempts. From HYDRA 7.1 the following two entries are only possible, as the logging of accesses and access attempts is set via the time zones: "J": Alarm messages are written. "N": Alarm messages are not written. Since October 2005 there have been two additional options: "G": Transfer open and closed immediately. "S": Transfer all statuses immediately. (PDM field ID: ZNR.OPT:PRO)
meldung_offen		smallint	For future use (PDM field ID: ZNR.OPT:OFFEN)
offline_komponente	Offline component	char(1)	Offline components are access readers without permanent connection to the HYDRA server.
offset_oeffner_2	Delay time: opener 2	decimal(18,6)	
pze_ausloesen	Trigger clocking	char(1)	Determines whether an access includes a PZE clocking (entry "J") or not (entry "N"). In case of an entry (ART=E) a clocking-in is generated in addition to the access log and in case of an exit (ART=A) a clocking-out is generated additionally. (PDM field ID: ZNR.OPT:PZEAUTO)
raum_nr		smallint	This field is currently not used (PDM field ID: ZNR.RAUM)
raumzonen_austritt	Exit from room zone	smallint	Room zone that can be left by the access.
raumzonen_eintritt	Entrance to room zone	smallint	Room zone which the access leads to
signal_oeffner		char(1)	
terminal_nr		smallint	Assignment of the access to a shop floor terminal. (PDM field ID: ZNR.TNR)
validierung		char(1)	
verantw_bereich		char(15)	Responsibility area which the access is assigned to.

wiederhol_sperre	Block badge after successful access	integer	Minimum time for opening the entry with the same badge. (PDM field ID: ZNR.WDHSPERR)
zugang_art	Access type	char(1)	Determines whether this access is an entrance ("E"), an exit ("A"), a passage ("D") or an access for which the badge number is not checked ("O"). Current status: If ART=O the badge number will not be checked but a plant ID card is required to open it. Planned: If ART=o only the company code of the ID card will be checked (PDM field ID: ZNR.ART)
zugang_bez	Designation	char(40)	Long designation of the access (PDM field ID: ZNR.BEZL)
zugang_gruppe		smallint	Assignment of the access to an access group. (PDM field ID: ZNR.ZGRP)
zugang_kurzbez	Short designation	char(6)	Short designation of the access (PDM field ID: ZNR.BEZK)
zugang_nr	Access point	smallint	Unique number of the access. (PDM field ID: ZNR.ZNR)
zugang_schleuse	Security gate with access point	smallint	Control of security gate: definition of the corresponding access of the security gate.
zykl_konfig	Reload access configuration	integer	Time for cyclical reading of the access configuration by the server. (PDM field ID: ZNR.ZYKL:CFG)
zykl_neulesen	Reload authorizations	integer	Time for cyclical reading of authorizations by the server. Authorizations are only read if no access is performed on the terminal within the time set here. (PDM field ID: ZNR.ZYKL:BERLESEN)
zykl_status	Report access point status	integer	Time for cyclical transfer of the access status to the server. (PDM field ID: ZNR.ZYKL:STA)

14.15. zks_zugang_gruppe

Table name: zks_zugang_gruppe		Product: ZKS	
Designation: Access group		Description: Access groups are defined in this table. An access point group summarizes accesses points that have the same authorizations. An example for this are several access pointss in the same building/room or several turnstiles at one entry.	
		Key: zugang_gruppe (unique)	
Column name	Column designation	Type	Description
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb		char(10)	last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
firma	Standort	char(8)	This field is used to assign public holidays to access groups. Public holidays only apply to the access group if this company corresponds to the company indicated in the table of public holidays. In this table the company does not refer to the company within the HR master data sheet and can be filled with the federal state. (PDM field ID: ZGRP.STO)
gruppe_bez	Designation	char(40)	Long designation of access group. (PDM field ID: ZGRP.BEZL)
gruppe_kurzbez	Short designation	char(6)	Short designation of access group. (PDM field ID: ZGRP.BEZK)
verantw_bereich		char(15)	Responsibility area which the access group is assigned to. This responsibility area is checked when authorizations are allocated for the access group.
zugang_gruppe	Access group	smallint	Number of Access group (PDM field ID: ZGRP.ZGRP)

14.16. zks_zz_bereich

Table name: zks_zz_bereich		Product: ZKS	
Designation: Access periods		Description: This table contains the single access periods of the access time modes (table zks_zeitzone). Access time modes and their corresponding access periods are connected by zks_zeitzone.verweis = zks_zz_bereich.verw_zeitzone.	
Column name	Column designation	Type	Description
abfrage_ausweis	Badge required	char(1)	This field determines if the badge is to be checked within the time interval (J/N). (PDM field ID: ZZB.PLAUS:KNR)
abfrage_pincode	Pincode required	char(1)	This field defines whether the pin code is to be checked or not within this time interval (J/N). If neither the badge nor the pin code is checked the access is permanently open. (PDM field ID: ZZB.PLAUS:PIN)
anlage	Created by	char(10)	For future use
anlage_date	Created date	date	For future use
anlage_time	Created time	integer	For future use
bearb		char(10)	Last editor
bearb_date	Modified date	date	
bearb_time	Modified time	integer	
bis_zeit	To	integer	End time in seconds since the beginning of the day (PDM field ID: ZZB.ZEIE)
buerofreigabe	Office unlocked	char(1)	
kfz_erkennung		char(1)	
kon_tag		char(10)	Definition of weekdays and public holidays when this time domain applies: 1st character = Sunday ... 7th character = Saturday 8th character = Public holiday 9th character = Important public holiday 10th character = Other days off
protokollierung	Logging	char(1)	N: No logging V: Log access attempts only Z: Log accesses and access attempts (PDM field ID: ZZB.PLAUS:PRO)
reserve		char(10)	For future use
verw_zeitzone	Reference to time zones	integer	Assignment to the unique record number within the table zks_zeitzone. (PDM field ID: ZZB.VERWEIS:ZZ)
verweis	Reference	serial	Unique record number to access the data record
von_zeit	Time	integer	Start time in seconds since the beginning of the day (PDM field ID: ZZB.ZEIB)

15. OBSOLETE

15.1. ade_aas_lz

Table name: ade_aas_lz	Product: BDE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.2. ade_agst_lz

Table name: ade_agst_lz	Product: BDE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.3. ade_prot_zusatz

Table name: ade_prot_zusatz	Product: BDE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.4. anmeld_tab

Table name: anmeld_tab	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.5. bearb_masch

Table name: bearb_masch	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.6. buffer_tab

Table name: buffer_tab	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.7. caq_dokuliste

Table name: caq_dokuliste	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.8. caq_gis

Table name: caq_gis	Product: CAQ_OBSOLETE
Archive table: a_caq_gis	Reload table: r_caq_gis
Designation: OBSOLETE	Description: This table is obsolete.

15.9. caq_mengabh_prf

Table name: caq_mengabh_prf	Product: CAQ_OBSOLETE
Archive table: a_caq_mengabh_prf	Reload table: r_caq_mengabh_prf
Designation: OBSOLETE	Description: This table is obsolete.

15.10. caq_nest

Table name: caq_nest	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.11. caq_pma_bestand

Table name: caq_pma_bestand	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.12. caq_pma_lager

Table name: caq_pma_lager	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.13. caq_pma_sollkonto

Table name: caq_pma_sollkonto	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.14. caq_pma_vorgang

Table name: caq_pma_vorgang	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.15. caq_pmv_arbeitspl

Table name: caq_pmv_arbeitspl	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.16. caq_pmv_einsatz

Table name: caq_pmv_einsatz	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.17. caq_pmv_pruefm

Table name: caq_pmv_pruefm	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.18. caq_pmv_pruefung

Table name: caq_pmv_pruefung	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.19. caq_pplzert

Table name: caq_pplzert	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.20. caq_pplzmer

Table name: caq_pplzmer	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.21. caq_prueffreq

Table name: caq_prueffreq	Product: CAQ_OBSOLETE
Archive table: a_caq_prueffreq	Reload table: r_caq_prueffreq
Designation: OBSOLETE	Description: This table is obsolete.

15.22. caq_pzustand

Table name: caq_pzustand	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.23. caq_sammelanf

Table name: caq_sammelanf	Product: CAQ_OBSOLETE
Archive table: a_caq_sammelanf	Reload table: r_caq_sammelanf
Designation: OBSOLETE	Description: This table is obsolete.

15.24. caq_usr_zuord

Table name: caq_usr_zuord	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.25. caq_werkzzuord

Table name: caq_werkzzuord	Product: CAQ_OBSOLETE
Archive table: a_caq_werkzzuord	Reload table: r_caq_werkzzuord
Designation: OBSOLETE	Description: This table is obsolete.

15.26. caq_wf_conn_point

Table name: caq_wf_conn_point	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.27. caq_wf_connect

Table name: caq_wf_connect	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.28. caq_wf_element

Table name: caq_wf_element	Product: CAQ_OBSOLETE
----------------------------	-----------------------

Designation: OBSOLETE	Description: This table is obsolete.
------------------------------	---

15.29. caq_wf_formel

Table name: caq_wf_formel	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.30. caq_workflow

Table name: caq_workflow	Product: CAQ_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.31. cons_masch

Table name: cons_masch	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.32. ereig_komp

Table name: ereig_komp	Product: MDE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.33. event_pdv

Table name: event_pdv	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.34. hy_forms

Table name: hy_forms	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.35. hy_ih_meldcode

Table name: hy_ih_meldcode	Product: IH_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.36. hy_ih_meldung

Table name: hy_ih_meldung	Product: IH_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.37. hy_ih_person

Table name: hy_ih_person	Product: IH_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.38. hy_usr_prop

Table name: hy_usr_prop	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.39. hy_usr_table

Table name: hy_usr_table	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.40. hyd_product

Table name: hyd_product	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.41. hydra_user

Table name: hydra_user	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.42. hysap_pm_object

Table name: hysap_pm_object	Product: IH_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.43. kfg_dialog_event

Table name: kfg_dialog_event	Product: BDE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.44. kfg_erfassung

Table name: kfg_erfassung	Product: BDE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.45. konsolen_status

Table name: konsolen_status	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.46. kstst_tab

Table name: kstst_tab	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.47. lager_hz

Table name: lager_hz	Product: MPL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.48. pdv_eingriff

Table name: pdv_eingriff	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.49. pdv_merkmal

Table name: pdv_merkmal	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.50. pdv_messinfo

Table name: pdv_messinfo	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.51. pdv_messinfo_ausw

Table name: pdv_messinfo_ausw	Product: PDV_OBSELETE
Designation: OBSELETE	Description: This table is obsolete.

15.52. pdv_messkanal

Table name: pdv_messkanal	Product: PDV_OBSELETE
Designation: OBSELETE	Description: This table is obsolete.

15.53. pdv_messreihe

Table name: pdv_messreihe	Product: PDV_OBSELETE
Archive table: a_pdv_messreihe	
Designation: OBSELETE	Description: This table is obsolete.

15.54. pdv_messreihe_ausw

Table name: pdv_messreihe_ausw	Product: PDV_OBSELETE
Designation: OBSELETE	Description: This table is obsolete.

15.55. pdv_messreihe_imp

Table name: pdv_messreihe_imp	Product: PDV_OBSELETE
Designation: OBSELETE	Description: This table is obsolete.

15.56. pdv_messreihe_qse

Table name: pdv_messreihe_qse	Product: PDV_OBSELETE
--------------------------------------	------------------------------

Designation: OBSOLETE	Description: This table is obsolete.
------------------------------	---

15.57. pdv_messwert

Table name: pdv_messwert	Product: PDV_OBSOLETE
Archive table: a_pdv_messwert	
Designation: OBSOLETE	Description: This table is obsolete.

15.58. pdv_messwert_ausw

Table name: pdv_messwert_ausw	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.59. pdv_messwert_imp

Table name: pdv_messwert_imp	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.60. pdv_messwert_komp

Table name: pdv_messwert_komp	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.61. pdv_messwert_qse

Table name: pdv_messwert_qse	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.62. pdv_messzusatz

Table name: pdv_messzusatz	Product: PDV_OBSOLETE
Archive table: a_pdv_messzusatz	
Designation: OBSOLETE	Description: This table is obsolete.

15.63. pdv_protokoll

Table name: pdv_protokoll	Product: PDV_OBSOLETE
Archive table: a_pdv_protokoll	
Designation: OBSOLETE	Description: This table is obsolete.

15.64. pdv_pruefmerkmal

Table name: pdv_pruefmerkmal	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.65. pdv_pruefplan

Table name: pdv_pruefplan	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.66. pdv_pruefplan_idx

Table name: pdv_pruefplan_idx	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.67. pdv_status

Table name: pdv_status	Product: PDV_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.68. personalstamm

Table name: personalstamm	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.69. produkt_merkmal

Table name: produkt_merkmal	Product: KERNEL_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.70. res_ress_artikel

Table name: res_ress_artikel	Product: WRM_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.71. system_a_index

Table name: system_a_index	Product: MDE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.72. system_j_kap_mod

Table name: system_j_kap_mod	Product: HLS_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.73. system_p_index

Table name: system_p_index	Product: MDE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.74. system_t_kap_mod

Table name: system_t_kap_mod	Product: HLS_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.

15.75. zeitumstellung

Table name: zeitumstellung	Product: PZE_OBSOLETE
Designation: OBSOLETE	Description: This table is obsolete.