

1 Configurations specific to ETD

Summary

Using the HYDRA data management it can be specified how long data is to be kept for the label reprint.

Archiving

Data for reprinting labels is archived after defined periods. The central archiving script `hyarc.scr` triggers the archiving process. This program is planned to be run on a daily basis within the [Scheduler](#) by default.

Subject to the given characteristics, archiving is performed either by the archiving program `hyarc.scr` (by deleting data directly from the database) or by the [HYDRA Data Management](#).

How can I find out which archiving type is in use?

Check (you or your system administrator) whether or not the script `hyarc.scr` within the HYDRA directory on the HYDRA server includes the below entry:

```
# HYD-ETD label reprint deletion script

if [ `hyliz.exe -r HYD-ETD` -gt 0 -o `hyliz.exe -r HYD-ETDRT` -gt 0 ]
then

    echo "HYD-ETD:" >> $ERRPATH/hyarc.pro

    hysql.exe -u -s 14 db_sql/hy_ettd.sql > $ERRPATH/hy_ettd.pro

    cat $ERRPATH/hy_ettd.pro >> $ERRPATH/hyarc.pro

fi
```

If this is the case, archiving is still performed by the separate archiving program.

If the entry does not exist or is commented out by inputting "#" in front of each line or calling `hysql` has been replaced by `hymwarc`, archiving is performed using the [HYDRA Data Management](#).

Archiving using data management - configuration

In this case, configuration is made using the [HYDRA Data Management](#).

Product	Object	Object designation	Transfer	Default interval
ETD	PRN_LOG	Label reprint	Online data → data is deleted (no transfer to the medium-term dataset)	15 days