

1 Escalations for System Administrators

1.1 HYDRA 8 MES Weaver 3.0/3.1

HYDRA 8 MES Weaver 3.0/3.1 provides the following escalations:

Event	Description	Identifiers	Description	Notes
TNR.OFFLINE	Terminal is offline	TNR.TNR	Terminal number	The event is triggered if the time since the terminal's last status message (signal) exceeds the target cycle for status messages.
		TNR.BEZZL	Terminal name	
		TNR.BEZZK	Terminal location	
		TNR.ZYKL:I	Time in seconds that has passed since the last status message (signal).	
		TNR.ZYKL:S	Target cycle for messages (signals) in seconds	
DB.INCREMENT_TOO_LARGE	Fill level of table spaces too large	DB.INC:GR	Increase in percent	The event is triggered if the fill level of single files / table spaces has increased by <DB.INC:GR> within the last few days.
		DB.INC:TG	Period considered	
FILESYS.FILL_LEVEL_EXCEEDED	Fill level of the drive exceeded	FILESYS.FILESYS	File system	
		FILESYS.SUM	File system size	
		FILESYS.SUM:EINH	Unit of file size	
		FILESYS.FREE	Free disk space	
		FILESYS.FREE:EINH	Unit of free disk space	
		FILESYS.FREE:PROZ	Free disk space in percent	
		FILESYS.USED	Used disk space	
		FILESYS.USED:EINH	Unit of used disk space	
		FILESYS.USED:PROZ	Used disk space in percent	
DB.FILL_LEVEL_EXCEEDED	Fill level of database file groups/table spaces exceeded	FILESYS.USEDGR:PROZ	Limit in percent	
		DB.DBSPACE	File group / table space	
		DB.DBSPNUM	Number (Informix)	
		DB.NCHUNKS	Number of chunks (Informix)	
		DB.SUM	Size	
		DB.SUM:EINH	Size unit	
		DB.FREE	Free disk space	
		DB.FREE:EINH	Unit of free disk space	
		DB.FREE:PROZ	Free disk space in percent	
		DB.USED	Used disk space	

Event	Description	Identifiers	Description	Notes
		DB.USED:EINH	Unit of used disk space	
		DB.USED:PROZ	Used disk space in percent	
		DB.USEDGR:PROZ	Limit in percent	

1.2 HYDRA 8 MES Weaver 4.0_{pe}

HYDRA 8 MES Weaver 4.0_{pe} provides the escalations described in section 1.1 HYDRA 8 MES Weaver 3.0/3.1 and the following escalations:

Event	Description	Identifiers	Description	Notes
LOGIN.FAILED	Failed login	LOGIN.USER	User name of login	The event is triggered every time a login fails.
		LOGIN.DATE	Login date	
		LOGIN.TIME	Login time in seconds since midnight.	
		LOGIN.R_IP	Client IP (remote IP)	
		LOGIN.R_HOST	Client host name or IP (remote host name if available)	
		LOGIN.DEV_ID	Device ID of the client (identical to the IP for REST clients, identical to the computer name for SOAP clients)	
		LOGIN.AUTH_TYPE	Type of login attempt: USER_PASSWORD or PIN_LOGIN or SSO (Simple Single Sign On) or ADI (Active Directory Integration)	
		LOGIN.RETURNVALUE	Type of failed login: USER_LOCKED or USER_NOT_FOUND or PASSWORD_WRONG	