

1 INI File *hytnrcfg.ini*

Usage

The terminal configuration file *hytnrcfg.ini* is a centrally administered file with which the system behavior at the HYDRA AIP shop floor clients (*ctaip.exe*) can be influenced.

Integration

A large variety of applications use this file in order to check settings stored there and adapt the system behavior accordingly.

Filing on the HYDRA Server

The file is stored centrally on the HYDRA server.

Assignment type	Path
Standard	HYDRADIR/ctnet/win/aip/hytnrcfg.ini
Globally customer-specific	HYDRADIR/<system directory>/custom/aip/
Terminal group-specific	HYDRADIR/<system directory>/custom/aip/ tgrp_<terminal group number> Example: HYDRADIR/1/custom/aip/ tgrp_901 /hytnrcfg.ini
Terminal-specific	HYDRADIR/<system directory>/custom/aip/ tnr_<terminal number> Example: HYDRADIR/1/custom/aip/ tnr_202 /hytnrcfg.ini



The file must be created and/or stored in lower case letters. (UNIX is case sensitive).

Assignment Types

The file can be maintained and assigned on different levels:

Standard

The file is delivered in the terminal directory of MPDV. The entries contained there are provided for the standard system.

Globally customer-specific

The file assigned to this level is available to all terminals.

Customer-specific - terminal group-specific

The terminal group-specific file is only relevant to the terminals assigned to the terminal group indicated in the directory name.

Customer-specific - terminal-specific

Terminal-specific assignment enables assignment to each individual terminal.

Processing Mode Depending on Assignment Type

Upon terminal start, the standard file is loaded from the server directory `"/ctnet/win/aip/"`.

In all cases, the system attempts to merge the standard file supplied by MPDV with a customer-specific file, if present.

The customer-specific configuration files (if present) are loaded in the specified order from the following directories by the server.

- 1) Globally customer-specific
- 2) Customer-specific - terminal group-specific
- 3) Customer-specific - terminal-specific

The file loaded last is subsequently merged with the standard file and transferred to the application directory. This results in the following customizing file priority

1. Customer-specific - terminal-specific
2. Customer-specific - terminal group-specific
3. Globally customer-specific



There is no multiple merging of GLOBAL + TGRP + TNR, but only a single merging of the file loaded last and the standard file.



The merging of INI files of HYDRA standard and customizing is performed by section. For this reason, it is sufficient if only the section to be modified is entered in the customer-specific INI file.