

1 Transport Matrix

Summary

Menu	Master Data → Production Control → Transport Matrix
Transaction code	ttx
Function authorization	mdttx

A transport matrix can be defined to determine the transport time between two operations.

Usage

When a new operation is created or when an explicit workplace or group change is made manually using the operation update function, the transport time is determined using this matrix and the results are transferred into the operation. Any change to the transport matrix or any rescheduling in the graphic planning board later will have no effect on already existing operations.



This function is only meaningful and therefore relevant if order scheduling is run in HYDRA.

In order to reduce the amount of data when determining the transport time from one workplace to another, the workplaces should be assigned to so-called location groups first. To do this, create a group in the configuration application [Groups](#) with the identifier "Location group" and use the configuration application [Group assignment](#) to assign the location group to a workplace.

Field descriptions

From location group

Location group of the original workplace

To location group

Location group of the target workplace

Transport time - normal

Normal transport time in hours.

Transport time - minimum

Minimum transport time in hours, down to which, based on the steps of the reduction strategy, reductions can be made.

Calendar

With regard to the calendar that scheduling is based on, the following options are available:

- G = Gregorian calendar

Transport times are scheduled using the Gregorian calendar.

- S = Shift calendar

When this option is set, the shift calendar or the original workplace is used for scheduling.

- T = Shift model from transport matrix

The shift model entered in the field Shift model is used for scheduling.

Shift model

Shift model that should be used when the option "T" is set in the calendar field.

Please note: The number of different shift models that are defined here should be kept to a minimum, because an increased number of different shift models may adversely impact performance in HYDRA shop floor scheduling.

Comment

Comment about this entry