

1 Example: Download of CO Internal Order

IDoc ZHYDRA_CO_ORDER

IDoc ZHYDRA_CO_ORDER is used to transfer CO internal orders. It has a simple structure since the user data themselves are transferred to HYDRA in a dynamic dialog string.

Message type:	ZHYDRA_CO_ORDER
IDoc type:	ZHYDRA_CO_ORDER
Segments:	Z2BAPI000

Dialog data string

In HYDRA, one order header is created per CO internal order. Several operations may be allocated to this order header. Order header and operations can be transmitted in the same IDoc if the order header is transferred as first segment.

A dialog data string is composed of the control command and the user data. The control command is always transferred with the "DLG=" acronym followed by the command itself.

NOTE:

For all alphanumeric fields, HYDRA does not support specific special indicators. Such as: "%", "\", "/", "]" since they cannot be entered into the collection terminals and will not be supported there.

The signs ";", " ", and " ' " must not be used since they are often interpreted as comment or separation signs and will thus lead to unwanted effects.

Order header

The following commands can be used to transfer CO internal orders to the order header:

- ANR.INSERT → Creation of an order header
- ANR.UPDATE → Modification of an order header (delta download)
- ANR.DELETE → Deletion of an order header (deletion download)

The command "AUNR.MODIFY" is a special one: It checks whether the transferred order number exists already in the order header. If this is the case, the existing data record will be modified (update), otherwise it will be inserted.

- ANR.MODIFY → Creation/ modification of an order header (delta download)

The different commands ensure that the download variants such as delta or deletion download of the PP-PDC interface can be realized.

After the control command, the user data will be transferred. They are presented by the identification (Acronym column) and separated from each other by "|".

What	Acronym	SAP / Value
Order number	AUNR.SAPAUNR	SAP order number
Order type	AUNR.AART	"1" or "4"
PPS Indicator	PPS	"J"
Indicator order header	ANR.ATYP	"AU"

In this example the dialog data string for a delta download will be structured as follows:

DLG=AUNR.MODIFY|AUNR.SAPAUNR=<SAP-Auftragsnummer>|AUNR.AART=1|PPS=J

Order sequencing

The following commands can be used to transfer CO internal orders to the HYDRA operation structure:

- ANR.INSERT → Creation of an operation
- ANR.UPDATE → Modification of an operation (delta download)
- ANR.DELETE → Deletion of an operation (deletion download)

The command "ANR.MODIFY" is a special one: It checks whether an operation exists already for the transferred order and an operation number. If this is the case, the existing data record will be modified (update), otherwise it will be inserted.

- ANR.MODIFY → Creation/ modification of an operation (delta download)

The different commands ensure that the download variants such as delta or deletion download of the PP-PDC interface can be realized.

After the control command, the user data will be transferred. They are presented by the identification (Acronym column) and separated from each other by "|".

What	Acronym	SAP	Mandatory field
Order number	ANR.SAPAUNR	SAP order number	X
Sequence	ANR.SAPAFOLG	SAP sequence	X
Operation	ANR.SAPVGNR	SAP operation number If not available in this form, it is also possible to transfer "0010".	X
Sub-operation	ANR.SAPUVGNR	SAP sub-operation (if necessary)	X
Plant	ANR.WERK:S	SAP plant	
Workplace	ANR.MNR	SAP work center	X
OP designation	ANR.AGBEZ	e.g. order short text	
Order type	ANR.AART	"1"	X
PPS Indicator	PPS	"J"	X
OP indicator	ANR.ATYP	"OP"	X
Start date	ANR.DATB	ATTENTION: The date must be transmitted in American format: MM/DD/YYYY	
Start time	ANR.ZEIB	Time in seconds	
End date	ANR.DATE	ATTENTION: The date must be transmitted in American format: MM/DD/YYYY	
End time	ANR.ZEIE	Time in seconds	
The indicator can be logged on several times	ANR.OPT:MULTIMNR	"J"	

In this example the dialog data string for a delta download will be structured as follows:

```
DLG=ANR.MODIFY|ANR.SAPAUNR=<SAP order number>|ANR.SAPVGNR=<SAP transaction number>|ANR.WERKS=<SAP plant>|ANR.MNR=<Workplace>|ANR.AGBEZ=<OP name>|ANR.AART=1|PPS=J|...
```