

Manual

HYDRA Interfacing Module to SAP R/3 PS (CC4) SAP-PSCC4 8.2

Version 1.0.23049

Last changed on: 02.09.2020

Copyright

©Copyright 2012 All rights reserved.

SAP® and R/3® are registered trademarks of SAP AG.

WINDOWS® is a registered trademark of Microsoft Corporation.

MPDV® and HYDRA® are registered trademarks of MPDV Mikrolab GmbH.

ORACLE® is a registered trademark of ORACLE Corporation, California, USA.

Copying and distribution of this documentation or any part thereof, for any purpose or in any form, is prohibited without prior written permission from MPDV Mikrolab GmbH.

The information contained in this documentation is subject to change without prior notice.

Contents

1	HYDRA Interfacing Module to SAP PS (CC4)	4
2	Behavior Depending on the Transfer Types	5
3	Operations Data Download SAP --> HYDRA.....	7
4	Confirmations Upload HYDRA --> SAP	10
5	MYERPRCK - Program Parameters	12
6	Application-Relevant Settings in HYDRA.....	24
7	Protecting fields of planned operations	27

1 HYDRA Interfacing Module to SAP PS (CC4)

Overview

Purpose

You use the SAP-PSCC4 interface to download project orders from SAP PS (networks and their operations) for a specified operation. In the MES, you can record postings for these operations and upload the resulting times to SAP PS. You use the CA-PDC / CC4 interface to connect to SAP PS.

Implementation notes

You use the function package Interfacing Module to SAP R/3 PS (CC4), if you process projects in SAP PS using networks and if you want to record data for these networks in the MES and then upload this data.

Integration

If you use the component SAP-PSCC4, the orders/operations transferred with this component are used for a great number of further postings in HYDRA.

Features

- Transfer of order data
 - Download of the released operations from PS and integration as HYDRA project orders (networks)/project operations (initial and delta download and delete function)
- Recording of times
 - Recording of start/interruption/end of processing and posting of the times according to the HYDRA configuration and validation checks
- Upload of operation postings
 - Upload to SAP PS of the actual times (performances) recorded for a specific SAP time ticket

<<XcludeSubDocument=\\archive\\mast_ind\\Produktdokumentationen\\en\\Functions\\MBL\\MBL_SAP_Implementation_CC4_Overview.docx>>

2 Behavior Depending on the Transfer Types

Initial download behavior

An initial download of the order and operation data will only take place when the complete system is commissioned and a first database is to be created in HYDRA. In addition, also other scenarios are possible by which the entire operations base will be replaced.

During an initial download all operations from SAP will be transferred that have at least the status "released" or that are not technically completed yet. This means that also (end) confirmed operations will be transferred but not imported in HYDRA.

When the initial download is received, the current operations data base in HYDRA will be deleted and be replaced by the new operations data. The current data will immediately be available.

An initial download will not only delete the order base existing in HYDRA but also all current times and quantities entered for orders and/or transactions.



In addition, all operations that are being executed will not be deleted. This means that they must be interrupted and/or terminated manually in HYDRA.

Conclusion: Any initial download during the operation of HYDRA must be used with greatest care and it would be useful to contact the MPDV Support beforehand.

For security reasons, the initial download function needs to be enabled explicitly as of the below-mentioned program version. Activation is performed by an INI configuration.

.lib\b_anr.dll

V8.1.1.326

Delta download behavior

A delta download creates new operations in HYDRA that will then be added to the database. Another function of the delta download is the modification of already transferred operations. Modifications of operations with the status "Running", "Finished" or "Deleted" are not allowed by the HYDRA default settings.



CUSTOMIZING information: Modifications of the operations depend on whether the flag "alterable order data" is set for the corresponding status in the status configuration.

If an operation cannot be modified to ensure the consistency in HYDRA (in general for running operations), this will be logged in HYDRA and be saved for error tracking purposes.

The basis for the delta download in SAP is the database table ORDCOM.

Deletion download behavior

A deletion download deletes those operations that are no longer necessary in the production process from the HYDRA database.

As with the modifications, the deletion result depends on the operation's status. Operations identified as "Running", "Interrupted", "Finished" or "Deleted", will not be deleted.

Moreover, the confirmation number (CONF_NO) will be checked to identify the orders via order, sequence and transaction. This prevents any accidental deletion of orders that are seemingly the same but which have different confirmation numbers.

Behavior when re-importing master data in SAP

When master data for an existing and released order that has already been transferred to HYDRA are re-imported in SAP this impacts also the interface to HYDRA.

When master data are re-imported, SAP will assign new confirmation numbers for the individual operations even though the order and operation numbers won't change. These are then transferred together with the next delta download to HYDRA. The confirmation/upload number will then be updated in HYDRA.



The update will also be made when the current status is "Running". In this case, however, ONLY the confirmation/upload no. will be changed and all other data (order quantity, scheduling, etc.) will not be updated.

Behavior during the technical completion in SAP

If an order is technically completed in SAP this will lead to a deletion download at the interface. This means that the order data in HYDRA will be deleted.

3 Operations Data Download SAP --> HYDRA

Operation data

The following structure is part of the PP-PDC / CC4 interface and is used to transfer maintenance orders to subsystems.

Message type: OPERA4

IDoc type: OPERA4

Segments: OPERA4

Message function:

APP	→	Delta download
DEL	→	Deletion download
UPD	→	Base data download

Field Name	T	L	Description	Rel. KK4	HYDRA Reference
RUECK*	NUMC	10	Operation confirmation number	x	Is stored for the confirmation, not used elsewhere
AUFNR	CHAR	12	Order number	x	According to Configuration (*1)
APLFL	CHAR	6	Operation sequence	x	According to Configuration (*1)
VORNr	CHAR	4	Operation number	x	According to Configuration (*1)
UVORN	CHAR	4	Sub procedure	x	According to Configuration (*1)
SPLIT*	NUMC	3	Split number	x	Not used
KAPAR*	CHAR	3	Capacity type	x	Not used
BDEGR*	CHAR	3	Subsystem connection grouping	x	Not used
MGVRG	DEC	10.3	Default quantity	-	
ASVRG	DEC	10.3	Scrap quantity	-	
MEINH	CHAR	3	Operation quantity unit	-	
UMREN	DEC	5.0	Conversion denominator	-	
UMREZ	DEC	5.0	Conversion Numerator	-	
KMEIN	CHAR	3	Header quantity unit	-	
UNTMG	DEC	10.3	Underdelivery quantity	-	
UEBMG	DEC	10.3	Overdelivery quantity	-	
ACTI1	DEC	10.3	Planned activity 1	-	
UNIT1	CHAR	3	Planned activity 1 unit	-	
ACTI2	DEC	10.3	Planned activity 2	-	
UNIT2	CHAR	3	Planned activity 2 unit	-	
ACTI3	DEC	10.3	Planned activity 3	-	

Field Name	T	L	Description	Rel. KK4	HYDRA Reference
UNIT3	CHAR	3	Planned activity 3 unit	-	
ACTI4	DEC	10.3	Planned activity 4	-	
UNIT4	CHAR	3	Planned activity 4 unit	-	
ACTI5	DEC	10.3	Planned activity 5	-	
UNIT5	CHAR	3	Planned activity 5 unit	-	
ACTI6	DEC	10.3	Planned activity 6	-	
UNIT6	CHAR	3	Planned activity 6 unit	-	
LMNGA	DEC	10.3	Planned yield	-	
XMNGA	DEC	10.3	Planned scrap quantities	-	
ISTAT	CHAR	5	Operation progress	x	OPs with completion status ("E") are not transferred
ISM01	DEC	10.3	Actual activity 1	-	
ISM02	DEC	10.3	Actual activity 2	-	
ISM03	DEC	10.3	Actual activity 3	-	
ISM04	DEC	10.3	Actual activity 4	-	
ISM05	DEC	10.3	Actual activity 5	-	
ISM06	DEC	10.3	Actual activity 6	-	
LEK01	CHAR	1	Completion indicator activity 1	-	
LEK02	CHAR	1	Completion indicator activity 2	-	
LEK03	CHAR	1	Completion indicator activity 3	-	
LEK04	CHAR	1	Completion indicator activity 4.	-	
LEK05	CHAR	1	Completion indicator activity 5	-	
LEK06	CHAR	1	Completion indicator activity 6	-	
ARBPL	CHAR	8	Workplace	x	OP machine (see note)
WERKS	CHAR	4	Workplace plant	x	Plant
ARBPI	CHAR	8	Actual workplace	x	Not used
WERKI	CHAR	4	Actual workplace plant	x	Not used
ISMNW	DEC	10.3	Actual work (cannot be negative)	x	Not used
ISMNE	CHAR	3	Actual work unit	x	Not used
ARBEI	DEC	6.1	Planned work	x	Target duration
ARBEH	CHAR	3	Planned work unit	x	"STD" / "H" / "HUR" "MIN" "S" / "SEC"
OFMNW	DEC	6.1	Remaining work (cannot be negative)	x	Not used
OFMNE	CHAR	3	Remaining work unit	x	Not used
LEKNW	CHAR	1	Indicator: no remaining work	x	Not used
FSAVD	DATS	8	Earliest start date	x	PPS start date
FSAVZ	TIMS	6	Earliest start time	x	PPS Start time
SSEDD	DATS	8	Latest end date	x	PPS end date
SSEDZ	TIMS	6	Latest end time	x	PPS end time

*) The actual work (field ISMNW) may not exceed 590 hours.

(*1) See below for more information on generating the HYDRA order number.

Upload Requirement

The upload requirement controls the confirmation upload to SAP. All available confirmations will be transferred to SAP in response to such upload requirement sent from SAP to HYDRA.

Message type:	REQUI4
IDoc type:	REQUI4
Segments:	REQUI4
Message function:	REQ → Upload Requirement

4 Confirmations Upload HYDRA --> SAP

HYDRA Supported Record Types and Activities

HYDRA BDE reports the following time ticket related record types back to SAP R/3 PP:

Record Type	SAP Meaning	HYDRA triggering action
T20	Partial Time Ticket Completion	Automatic or manual order interruption at the BDE terminal or BDE console.
T40	Time Ticket Completion	Order completion message at the BDE terminal or BDE console.

Please note

When HYDRA MPL is active, each generated output batch (output batch change message) will generate OP interruption or logoff time tickets plus an L20 partial completion message.

Report Structure E2CONF7

HYDRA ADE reports time ticket related information back to SAP. Its base data consists of the order-related postings (U / E records) and the duration data in these records. The badge number is added before transmission to SAP.

Message type: CONF42
IDoc type: CONF42
Segments: E2CONF7

Field Name	Type	Length	Text	HYDRA Reference		
SATZA	CHAR	3	Report record type	T20 or T40		
TERID	CHAR	4	Terminal ID	Not used		
LDATE	DATS	8	Logical date / Actual reporting date	Logoff date		
LTIME	TIMS	6	Logical time / Actual reporting time	Logoff time		
ERDAT	DATS	8	Report entry date	Reporting date		
ERTIM	TIMS	6	Report entry time	Reporting time		

Field Name	Type	Length	Text	HYDRA Reference		
BUDAT	DATS	8	Report booking time	Set based on the booking record shift date		
ARBPL	CHAR	8	Workplace	HYDRA workplace		
WERKS	CHAR	4	Plant	Plant		
ZAUSW	NUMC	8	Badge number	Time badge number		
AUFNR	CHAR	12	Order number	Follows default		
VORN	CHAR	4	Operation number	Follows default		
UVORN	CHAR	4	Sub-operation number	Follows default		
SPLIT	NUMC	3	Split number	Not used		
KAPAR	CHAR	3	Capacity type	Not used		
ABWEI	CHAR	4	Deviation basis	Not used		
ABARB	NUMC	3	Completion level			
PEDD	DATS	8	Predicted end date	Not used		
PEDZ	TIMS	6	Predicted end time	Not used		
LEKNW	CHAR	1	Indicator: no remaining work	Not used		
LTXA1	CHAR	40	Report text	Not used		
ISMNW *	DEC	6.1	Actual work	P_DAUER		
ISMNE	CHAR	3	Actual work unit	"H" / "STD" / "HUR" "MIN" "S" / "SEC" Default "STD"		
LEARR	CHAR	6	Activity type	Not used		
IDAUR *	DEC	4.1	Actual duration	Actual duration BMK11		
IDAUE	CHAR	3	Actual duration unit	"H" / "STD" / "HUR" "MIN" "S" / "SEC" Default "STD"		
ODAU *	DEC	4.1	Remaining duration	Not used		
ODAUE	CHAR	3	Remaining duration unit	Not used		
OFMNW *	DEC	6.1	Remaining work	Not used		
OFMNE	CHAR	3	Remaining work unit	Not used		
ISDD	DATS	8	Execution start date	Logon date		
ISDZ	TIMS	6	Execution start time	Logon time		
IEDD	DATS	8	Execution end date	Logoff date		
IEDZ	TIMS	6	Execution end time	Logoff time		

5 MYERPRCK - Program Parameters

--	--	--

Purpose

Use the upload program myerprck.exe/out to create confirmations/uploads to higher-level systems. In addition to the settings you make directly in the applications, you can also use program parameters to control confirmations/uploads.

Integration

The confirmation/upload is integrated with numerous components, for example:

- Shop floor data collection
- Tracking and tracing as well as material and production logistics
- Detailed scheduling

Available program parameters:

Parameters	Meaning/use	Relevant interfaces	Productive release
Program parameters to control processing:			
/MESTYP=XXXX	The parameter MESTYP defines the structure to be generated.	All	Yes
/GRP=XXXX	The grouping type specifies the criterion by which uploads should be grouped. Possible values: PLANT --> Groups by plant	Requires customizations	Requires customizations
/V=sssss	Since SAP R/3 PP does not support correction postings, HYDRA allows to retain confirmations/uploads for correction purposes in HYDRA for a specific period of time. Use the parameter /V=sssss (sssss =	EIS-ERP EIS-XPPS SAP-PPDC SAP-PPREM	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	delay time in seconds) to activate the above described delay when the upload program is called. Examples: <pre>myerprck.exe/out /V=3600</pre> The system only uploads postings that are older than one hour.	SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	
/BIS=DDMMYYHHMM /BIS=HHMM /TILLDATE=MM/DD/YYYY /TILLTIME=sec after midnight	Use the parameter /BIS=DDMMYYHHMM (date + time) when calling the upload program to enter the delay as a point in time. You can enter this point in time with date and time or you can just enter the time in the format "HHMM". In the latter case, the time refers to the current day. <pre>Myerprck.exe /BIS=2505110600</pre> This parameter uploads postings that were recorded until 06:00 a.m. on 25 May 2011. <pre>Myerprck.exe /BIS=0600</pre> This parameter uploads postings that were recorded until 06:00 a.m. of the current day.	EIS-ERP EIS-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/TZ=+/-sssss	Use the parameter /TZ=+/-sssss to adapt uploads to different time zones. The parameter adjusts the time specifications entered in the fields EXEC__START_TIME, EXEC_FIN_TIME and LOGTIME of the upload structure of the SAP-PPDC interface according to its specifications.	SAP-PPDC	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
/KST=XXX	Use this parameter to restrict the data to be uploaded. In this case, the system only uploads data of a specified cost center. Use the parameter /KST=XXX (XXX = cost center, a max. of 8 characters) when calling the upload program myerprck.exe/out to enable the above-described restriction. Then the system only uploads data records that were posted to machines of the specified cost center. The system checks the cost center of the machine/workplace that is entered as the posting workplace/machine in the posting record. The system only checks the cost center of the workplace/machine. You can specify the parameter several times per call. <u>Example:</u> <pre>Myerprck.exe /KST=BDE100 /KST=BDE200</pre> The system only uploads records that were posted onto machines of the cost center BDE100/BDE200.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/CLEAR_RES	Use the parameter "/CLEAR_RES" to assign an "X" to the field CLEAR_RES of the upload structure when it comes to a final confirmation/upload (record type L40). Consequently, SAP will clear open reservations for the respective order.	SAP-PPDC	Yes
/NEG_MENGE	By default, quantities (L20/L40) cannot	SAP-PPDC	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	be uploaded to SAP PP using partial confirmations/uploads via the SAP-PPDC interface if data is collected at the same time via the total quantity counter of MDE machines, since SAP is not able to process negative quantities. This type of collection can result in negative quantity postings for yield when OPs are finished. This restriction does no longer apply, if it is possible to process such negative postings (e.g. by using the SAP standard BAPI or customizations). In this case, you can use the program parameter /NEG_MENGE to enable the upload of these quantities.		
/LA_MNR	The SAP_PMCC3 interface requires the activity type to be uploaded to SAP PM. The activity type can be identified via the machine/workplace where the posting was performed. Use this program parameter to enable identification of the activity type. Then the system uses the machine to identify the activity type from the activity types kept in HYDRA.	SAP-PMCC3	Yes
/IDENT_PRAEFIX=	In the upload structure of the SAP-PPDC interface, the field EX_IDENT uniquely identifies uploads from subsystems. HYDRA populates the field. You can add a prefix to the EX_IDENT field to differentiate between uploads	SAP-PPDC SAP-PPDCC	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	from various HYDRA subsystems connected to one SAP instance. <u>Example:</u> <pre>Myerprck.exe /IDENT_PRAEFIX=ABC</pre> The prefix may only include hexadecimal characters: A –H und 0 – 9.		
/ABZEICH=XX	While customizing the order type, you can specify that only signed data records are uploaded. Use the parameter /ABZEICH=XX to specify a period of time in days after that you can upload even unsigned data records.	EIS-ERP EIS-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/TRANSFER=	Use the parameter "/TRANSFER=" to only upload records whose specifications were transferred from a specific system. The transfer indicator is set during HYDRA inbound processing and may vary from interface to interface.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
/NOTTRANSFER=XXX	Use the parameter "/NOTTRANSFER=" to only upload records whose specifications were NOT transferred from a specific system. The transfer indicator is set during HYDRA inbound processing and may vary from interface to interface.	EIS-ERP ESI-XPPS SAP-PPPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/SEK	The EIS-ERP interface uploads the times of resource performance accounts in hours. In particular with very short lead times this may effect that logon times are cut off by a conversion into hours. Use this program parameter to upload times in seconds.	EIS-ERP ESI-XPPS	Yes
/RMTYP=	When customizing the order type, you can assign an upload type to the order type. Use this program parameter to only upload data records of this upload type. You can specify the parameter several times per call.	EIS-ERP ESI-XPPS SAP-PPPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
/KAT=	When customizing the order type, you can connect the order type with a category. Use the program parameter /KAT= to only upload data records of this category. You can specify the parameter several times per call.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/SART=	The system only uploads ADE log postings of the specified record type. Therefore, you can use different program parameters per call and record type for uploading. Requirement: You have to activate the corresponding uploads when customizing the order type. You can specify the parameter several times per call. <u>Example:</u> <pre>Myerprck.exe /SART=A /SART=E</pre> ⇒ The system only uploads A and E records.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/NOLOCK	When starting the upload program, the system checks if there are any lock entries for the database table ADE_PROTOKOLL. If this is the case,	All	Requires customizations

Parameters	Meaning/use	Relevant interfaces	Productive release
	the upload is not carried out. You can use this program parameter to prevent this check. Set this parameter, in particular, if the upload is not based on the table ade_protokoll.		
/EINH_CC34	The interfaces SAP-PMCC3 and SAP-PSCC4 transfer the uploaded activity quantity in seconds (SEC) to SAP. Use the parameter "/EINH_CC34" to upload the data in other units. The following units are supported: Hours: H, HUR, STD Minutes: MIN Seconds: SEC <u>Example:</u> <pre>Myerprck.exe /EINH_CC34=HUR</pre> The system uploads the recorded times in the unit "HUR" (hours).	SAP-PMCC3 SAP-PSCC4	Yes
/SDAT_STORNO	The SAP-PPPDCC interface transfers the change date along with the correction records. Use this program parameter to upload the initially collected shift date instead.	SAP-PPPDCC	Yes
/NORFC_STORNO	The SAP-PPPDCC interface transfers the cancellation records via sRFC. Use the program parameter to transfer the data in the IDoc format to SAP. To do	SAP-PPPDCC	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	so, inbound processing must be implemented in SAP. The system uploads the cancellation records via the standard PP-PDC segment (with record type K20/K40) as if the PP-PDCC license was not available.		
/PI	If you use the SAP Process Integration (previously: Exchange Infrastructure) to communicate with SAP, the version of the transferred segment is checked more strictly. Use the program parameter to transfer segment names with the version number (i.e. the trailing zeros of the segment name).	SAP-PPDC SAP-PMCC3 SAP-PSCC4	Yes
/INDEX_TMP_TABLE	Use this parameter to accelerate uploads if ORACLE is used as database system and large amounts of data are affected. To do so, use an index for a temporary table where all data to be uploaded is transferred in a first step.	All	Requires customizations
/UE_PARAMS=	Program parameter for the stand-alone user exit processing (DD format).	Various	Yes
/NOSTORNO	Use this program parameter to prevent cancellation records from being uploaded. Therefore, you can use different program parameters per call and record type for uploading. Requirement: You have to activate the	All	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	corresponding uploads when customizing the order type.		
/RECALC_NEG_YIELD	Use this parameter to offset negative yield with already posted positive uploads.	SAP-PPPDCC	Requires customizations
Program parameters to use the SIGUSR communication:			
/LOGGING	Use this program parameter to activate communication from the database table HYD_LOGGING. To do so, a customization might be required.	INDIVIDUAL CASE	Yes
/WAIT_SIGUSR1=XX	The program parameter specifies the time in seconds that has to pass before the upload is performed via the SIGUSR communication even without trigger.	INDIVIDUAL CASE	Yes
/PEEK_SIGUSR1=XX	Use this parameter to delay execution of an action triggered by the SIGUSR communication. The delay time is entered in seconds for this parameter. The program interprets this time as follows: If within the next second after the initial trigger there is another trigger, then wait for not more than <specified value> seconds. If in a specific case, triggers would indeed arrive every second then the	INDIVIDUAL CASE	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	WAIT_SIGUSR time (e.g. 120 seconds) would apply; i.e. the system would in fact perform the upload after 2 minutes.		
/SEND_SIGUSR1=	This program parameter defines which other process/ program must be triggered after processing by the SIGUSR communication. Specify the process/program WITHOUT file extension.	INDIVIDUAL CASE	Yes
/COUNT_SIGUSR1=XX	Uploading in signal mode can hardly be subjected to tracing. This is due to the fact that the program in those cases is started once via the scheduler but won't shut off. Any redirection of the program call with -d to a log file will then necessarily lead to very large log files, which will negatively affect the performance. Use the new program parameter /COUNT_SIGUSR1=XX to specify after how many calls the program will automatically shut down. A call in these instances is both, a call via SIGUSR communication and the cyclical program execution which is controlled via the parameter /WAIT_SIGUSR1. Then the scheduler restarts the program. But this will lead to a time period "t" during which SIGUSR calls will not be processed. It is, however, assumed that this will not lead to data losses since the data to be uploaded are already saved to	INDIVIDUAL CASE	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	the DB. Benefits: If the program is started via a script (*.scr) from the scheduler, you can store there the routine to generate a date/ time stamp file name for the log file to be created. This allows to restrict the log file size.		
Program parameters for debugging/ tracing/ testing/ logging purposes:			
/ONLYERR	This program parameter specifies that system log entries are only created if an error occurred during uploading. This reduces the entries in the system log.	All	Yes
/SIM	The system does not upload/confirm data during simulations (the uploaded/confirmed indicator is set to "True").	All	No
/SIMULATION	The system does not upload/confirm data to SAP during simulation (confirmed/uploaded indicator will not be changed).	All	No

6 Application-Relevant Settings in HYDRA

Maintenance of the HYDRA distribution model – inbound processing

Edit entries for HYDRA inbound processing in the [HYDRA distribution model](#):

Parameter name	Value
For processing of network plans	
Message type	OPERA4
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANTE=< MLE variant to be used >
Description	PS-CC4 – Download of network plans
Log. target system	Created logical system
Storage duration	10
For processing of upload request	
Message type	REQUI4
Priority	High
Command	hysapupl.scr
Command parameter	/UPLSEGNAM=E2CONF7
Description	PS-CC4 – Upload request
Log. target system	Created logical system
Storage duration	10

Maintenance of the HYDRA distribution model – outbound processing

Edit entries for the HYDRA outbound processing in the [HYDRA distribution model](#):

Parameter name	Value
For uploading time tickets	
Message type	CONF42
Description	PS-CC4 – Upload of time tickets
IDoc type	CONF42
Storage duration	10
Log. target system	Created logical system
Segment name 1	E2CONF7

Activation of initial download

As of program version

.lib\b_anr.dll V8.1.1.326

the initial download has to be enabled explicitly for security reasons.

Create the following entry in [HYDRA INI configuration](#) if you would like to activate the initial download for the system:

Parameter name	Value
INI name	SAP
Section	INITIAL_DOWNLOAD_ACTIVATION
Key	ACTIV_TILL
Value	<Date value in the format MM/DD/YYYY>
Active	Yes
Comment	Activation of initial download

<<XcludeSubDocument=\\archive\mast_ind\Produktdokumentationen\en\Procedures\SAP_PSCC4_Customizing_SAP\SAP_PSCC4_Customizing_SAP.docx>>

7 Protecting fields of planned operations

Purpose

Use the configuration described in this document to prevent specific data fields of a (planned) operation from being overwritten when the operation is transferred once more via the ERP interface.



This function only affects ANR.MODIFY and/or ANR.UPDATE and operations.

Operations are only updated if the status of the order/operation generally allows it. The configuration described below does not apply if the status (see [order status assignment](#)) cannot be changed in general.

Requirements

You require the relevant function authorization to access [INI configuration](#) and [INI data configuration](#).

Procedure from service pack 12 onwards (b_anr.dll version 8.1.1.354)

Create a new entry in the [INI configuration](#):

Field name	Value
Name	BAPINOUPDATE
Description	Enter a description.

For this entry, create an entry including the following values in [INI data configuration](#):

Field name	Value
Section	ANR
Key	List the fields (HYDRA BAPI acronyms) that are not overwritten.
Value	The value includes a condition. Enter the condition, for example, as follows: ANR.ATYP=AG
Active	Yes

Use "@" to separate the single fields or conditions in the fields "key" or "value". The fields and conditions are processed one after the other.

You can define the values for "key" and "value" separately. The entries are processed one after the other. The conditions entered in the "value" field correspond to an AND operation.



As of service pack 12 only use the "@" character as separator if you create new entries or change existing ones. You do not have to change existing configurations (prior to service pack 12). In this case, the "|" character is still supported.



You can enter multiple entries for the function BAPINOUPDATE in the [INI data configuration](#), as you define the values for "key" and "value" separately.

Procedure up to service pack 11

Create a new entry in the [INI configuration](#):

Field name	Value
Name	BAPINOUPDATE
Description	Enter a description.

For this entry, create an entry including the following values in [INI data configuration](#):

Field name	Value
Section	ANR
Key	List the fields (HYDRA BAPI acronyms) that are not overwritten.
Value	Enter the condition that has to be met to make sure fields will not be overwritten. Enter BAPI acronyms including value.
Active	Yes

Use "|" to separate the single fields or conditions in the fields "key" or "value". The fields and conditions are processed one after the other.



Up to service pack 11 only use the "|" character as separator.

You can define the values for "key" and "value" separately. The entries are processed one after the other. The conditions entered in the "value" field correspond to an AND operation.



You can enter multiple entries for the function BAPINOUPDATE in the [INI data configuration](#), as you define the values for "key" and "value" separately.

If you cannot enter the pipe character ("|") using the GUI, you can still enter the values via the database:

- To do so, create a new entry as described above via the [INI configuration](#). Now use the following SQL statement to determine the internal DB counter for the header entry in the INI configuration:

```
select * from hyd_ini
```

- Determine the value of the "VERWEIS" column for the new entry.
- Create the required entries. Use the following SQL statement to assign the database table fields and application fields as described below:

```
insert into hyd_ini_data (ini_verweis, section, ident, value, bemerkung, aktiv)
values (<reference from previous SQL>, 'ANR', '<fields to be protected>', '<values>',
'<comment>', 'J')
```

Use the "|" (pipe) character to separate the acronyms of the fields you want to protect and the acronyms of the values.



Use a pipe character "|" to complete the list of the fields you want to protect and the list of values.

Database field	Values/content
INI_VERWEIS	The value of the VERWEIS column identified from the HYD_INI table via SQL.
SECTION	Section
IDENT	Key
VALUE	Value
BEMERKUNG (comment)	Comment
AKTIV	Active

List of frequently used acronyms

The following table lists the most frequently used acronyms and their meaning. Please contact MPDV Support if the list does not include the acronym you require.

Acronym	Meaning
ANR.MGRP	Machine group
ANR.MNR	Workplace/ machine
ANR.OPT:PLAN	Planning indicator: M Planned for workplace/machine G Planned for machine group
ANR.DATB	Start date planned (via HLS)
ANR.ZEIB	Start time planned (via HLS)
ANR.DATE	End date planned (via HLS)
ANR.ZEIE	End time planned (via HLS)

Example: protect the planned workplace

If the operation is planned on a workstation, you have to prevent the ERP interface from cancelling this planning. To do so, enter the below-mentioned data:

Field name	Value
Section	ANR
Key	ANR.MGRP@ANR.MNR@ANR.OPT:PLAN@
Value	ANR.ATYP=AG@ANR.OPT:PLAN=M@
Active	Yes

SLQ statement:

```
insert into hyd_ini_data (ini_verweis, section, ident, value, bemerkung,
aktiv) values (<reference from previous SQL>, 'ANR',
'ANR.MGRP@ANR.MNR@ANR.OPT:PLAN@', 'ANR.ATYP=AG@ANR.OPT:PLAN=M@', '<comment>',
'J')
```

Example: protect the start/end dates of a planned OP

If the operation is planned on a workstation and, as a result, its start time is specified, you have to prevent the ERP interface from cancelling this planning. To do so, enter the below-mentioned data:

Field name	Value
Section	ANR
Key	ANR.DATB@ANR.ZEIB@ANR.DATE@ANR.ZEIE@
Value	ANR.ATYP=AG@ANR.OPT:PLAN=M@
Active	Yes

SLQ statement:

```
insert into hyd_ini_data (ini_verweis, section, ident, value, bemerkung,
aktiv) values (<reference from previous SQL>, 'ANR',
'ANR.DATB@ANR.ZEIB@ANR.DATE@ANR.ZEIE@', 'ANR.ATYP=AG@ANR.OPT:PLAN=M@',
'<comment>', 'J')
```