

1 Available Escalations

1.1 Operation started (ANR.START)

The event is triggered when an operation has been logged on.

The escalation is carried out even if the operation is logged on due to a shift change. The escalation is only carried out in online mode.

Event	Identifiers	Description
ANR.START	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Suboperation number
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	ANR.PNR	Personnel number of the reporting person
	ANR.KNR	The reporting person's badge number
	ANR.AST	OP status
	ANR.PKENN	Production identifier
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by

1.2 Manual posting of part quantity (ANR.PARTIAL_CONFIRMATION)

The event is triggered if a manual posting of a part quantity has been made for an order. The escalation is only carried out in online mode.

Event	Identifiers	Description
ANR.PARTIAL_CONFIRMATION	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Suboperation number
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	ANR.PNR	Personnel number of the reporting person
	ANR.KNR	The reporting person's badge number
	ANR.AST	OP status
	ANR.PKENN	Production identifier
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by
	BEM	Comment
	Quantities from logon dialog:	
	ANR.EGR:GUT	Yield
	ANR.EGR:AUS	Scrap
	ANR.EGR:NCH	Rework quantity
	ANR.EGR:PRB	Problem quantity
	ANR.EGE:GUT	Quantity unit
	ANR.EGG:GUT	Reason for yield
	ANR.EGG:AUS	Scrap reason
	ANR.EGG:NCH	Rework reason
	ANR.EGG:PRB	Problem reason
	ANR.EGT:GUT	Reason for yield text no.
	ANR.EGT:AUS	Scrap reason text no.
	ANR.EGT:NCH	Rework reason text no.
	ANR.EGT:PRB	Problem reason text no.
	Order data:	
	AUNR.DATSE	Basic end dates of order (date)
	AUNR.DATTERME	Scheduled end of order (date)

Event	Identifiers	Description
	AUNR.DISP	MRP controller
	AUNR.AUGRP	Order group
	Operation data, stock data	
	ANR.SGR.GUTP	Primary target quantity of OP
	ANR.DATE	Planned end of OP (date)
	ANR.DATSE	Latest end of OP (date)
	ANR.DATTERME	Scheduled end of OP (date)
	ANR.VAB	Responsibility area
	ANR.BEARBZ	Target duration of OP
	ANR.RUEZ	Target setup time of OP
	Status information of operation data:	
	ANR.EGR:GUTP	Yield (primary)
	ANR.EGR.AUSP	Scrap quantity (primary)
	ANR.EGR.NCHP	Rework quantity (primary)
	ANR.EGR.PRBP	Problem quantity (primary)
	ANR.EGR:BMK01	Actual duration RPA 1
	ANR.EGR:BMK02	Actual duration RPA 2
	ANR.EGR:BMK03	Actual duration RPA 3
	ANR.EGR:BMK04	Actual duration RPA 4
	ANR.EGR:BMK05	Actual duration RPA 5
	ANR.EGR:BMK06	Actual duration RPA 6
	ANR.EGR:BMK07	Actual duration RPA 7
	ANR.EGR:BMK08	Actual duration RPA 8
	ANR.EGR:BMK09	Actual duration RPA 9
	ANR.EGR:BMK10	Actual duration RPA 10
	ANR.EGR:BMK11	Actual duration RPA 11
	ANR.EGR:BMK12	Actual duration RPA 12
	Workplace master data:	
	MNR.BEZX	Short name
	MNR.BEZZ	Designation
	MNR.MGRP	Group
	MNR.KST	Cost center
	MNR.FIR	Company
	MNR.VAB	Responsibility area
	Personal master data:	
	PNR.PNR	Person
	PNR.PVORNAME	First name

Event	Identifiers	Description
	PNR.PNAME	Last name
	Reporting data EBDF:	
	MSGPRIO	Priority 1 = highest 2 = high 3 = normal 4 = low 5 = lowest MSGPRIO from dialog data
	MSGCLASS	Information class/importance I = information W = warning E = error MSGCLASS from dialog data
	MSGRCV	Recipient/addressee, e.g. group of plant managers MSGRCV from dialog data

1.3 Operation interrupted (ANR.INTERRUPT)

The event is triggered when an operation has been interrupted.

The escalation is also performed if the operation is interrupted due to a shift change. The escalation is only carried out in online mode.

Event	Identifiers	Description
ANR.INTERRUPT	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Suboperation number
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group

Event	Identifiers	Description
	ANR.PNR	Personnel number of the reporting person
	ANR.KNR	The reporting person's badge number
	ANR.AST	OP status
	ANR.PKENN	Production identifier
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by
	BEM	Comment
	Quantities from logon dialog:	
	ANR.EGR:GUT	Yield
	ANR.EGR:AUS	Scrap
	ANR.EGR:NCH	Rework quantity
	ANR.EGR:PRB	Problem quantity
	ANR.EGE:GUT	Quantity unit
	ANR.EGG:GUT	Yield reason (deviation reason)
	ANR.EGG:AUS	Scrap reason
	ANR.EGG:NCH	Rework reason
	ANR.EGG:PRB	Problem reason
	ANR.EGT:GUT	Reason for yield text no.
	ANR.EGT:AUS	Scrap reason text no.
	ANR.EGT:NCH	Rework reason text no.
	ANR.EGT:PRB	Problem reason text no.
	Order data:	
	AUNR.DATSE	Basic end dates of order (date)
	AUNR.DATTERME	Scheduled end of order (date)
	AUNR.DISP	MRP controller
	AUNR.AUGRP	Order group
	Operation data, stock data	
	ANR.SGR.GUTP	Primary target quantity of OP
	ANR.DATE	Planned end of OP (date)
	ANR.DATSE	Latest end of OP (date)
	ANR.DATTERME	Scheduled end of OP (date)
	ANR.VAB	Responsibility area
	ANR.BEARBZ	Target duration of OP
	ANR.RUEZ	Target setup time of OP
	Status information of operation data:	

Event	Identifiers	Description
	ANR.EGR:GUTP	Yield (primary)
	ANR.EGR:AUSP	Scrap quantity (primary)
	ANR.EGR:NCHP	Rework quantity (primary)
	ANR.EGR:PRBP	Problem quantity (primary)
	ANR.EGR:BMK01	Actual duration RPA 1
	ANR.EGR:BMK02	Actual duration RPA 2
	ANR.EGR:BMK03	Actual duration RPA 3
	ANR.EGR:BMK04	Actual duration RPA 4
	ANR.EGR:BMK05	Actual duration RPA 5
	ANR.EGR:BMK06	Actual duration RPA 6
	ANR.EGR:BMK07	Actual duration RPA 7
	ANR.EGR:BMK08	Actual duration RPA 8
	ANR.EGR:BMK09	Actual duration RPA 9
	ANR.EGR:BMK10	Actual duration RPA 10
	ANR.EGR:BMK11	Actual duration RPA 11
	ANR.EGR:BMK12	Actual duration RPA 12
	Workplace master data:	
	MNR.BEZX	Short name
	MNR.BEZX	Designation
	MNR.MGRP	Group
	MNR.KST	Cost center
	MNR.FIR	Company
	MNR.VAB	Responsibility area
	Personal master data:	
	PNR.PNR	Person
	PNR.PVORNAME	First name
	PNR.PNAME	Last name
	Reporting data EBDF:	
	MSGPRIO	Priority 1 = highest 2 = high 3 = normal 4 = low 5 = lowest MSGPRIO from dialog data

Event	Identifiers	Description
	MSGCLASS	Information class/importance I = information W = warning E = error MSGCLASS from dialog data
	MSGRCV	Recipient/addressee, e.g. group of plant managers MSGRCV from dialog data

1.4 Operation finished (ANR.END)

The event is triggered as soon as an operation has been finished. The escalation is only carried out in online mode.

Event	Identifiers	Description
ANR.INTERRUPT	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Suboperation number
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	ANR.AST	OP status
	ANR.PNR	Personnel number of the reporting person
	ANR.KNR	The reporting person's badge number
	ANR.PKENN	Production identifier
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by
	BEM	Comment
	Quantities from logon dialog:	

Event	Identifiers	Description
	ANR.EGR:GUT	Yield
	ANR.EGR:AUS	Scrap
	ANR.EGR:NCH	Rework quantity
	ANR.EGR:PRB	Problem quantity
	ANR.EGE:GUT	Quantity unit
	ANR.EGG:GUT	Yield reason (deviation reason)
	ANR.EGG:AUS	Scrap reason
	ANR.EGG:NCH	Rework reason
	ANR.EGG:PRB	Problem reason
	ANR.EGT:GUT	Reason for yield text no.
	ANR.EGT:AUS	Scrap reason text no.
	ANR.EGT:NCH	Rework reason text no.
	ANR.EGT:PRB	Problem reason text no.
	Order data:	
	AUNR.DATSE	Basic end dates of order (date)
	AUNR.DATTERME	Scheduled end of order (date)
	AUNR.DISP	MRP controller
	AUNR.AUGRP	Order group
	Operation data, stock data	
	ANR.SGR.GUTP	Primary target quantity of OP
	ANR.DATE	Planned end of OP (date)
	ANR.DATSE	Latest end of OP (date)
	ANR.DATTERME	Scheduled end of OP (date)
	ANR.VAB	Responsibility area
	ANR.BEARBZ	Target duration of OP
	ANR.RUEZ	Target setup time of OP
	Status information of operation data:	
	ANR.EGR:GUTP	Yield (primary)
	ANR.EGR:AUSP	Scrap quantity (primary)
	ANR.EGR:NCHP	Rework quantity (primary)
	ANR.EGR:PRBP	Problem quantity (primary)
	ANR.EGR:BMK01	Actual duration RPA 1
	ANR.EGR:BMK02	Actual duration RPA 2
	ANR.EGR:BMK03	Actual duration RPA 3
	ANR.EGR:BMK04	Actual duration RPA 4
	ANR.EGR:BMK05	Actual duration RPA 5
	ANR.EGR:BMK06	Actual duration RPA 6

Event	Identifiers	Description
	ANR.EGR:BMK07	Actual duration RPA 7
	ANR.EGR:BMK08	Actual duration RPA 8
	ANR.EGR:BMK09	Actual duration RPA 9
	ANR.EGR:BMK10	Actual duration RPA 10
	ANR.EGR:BMK11	Actual duration RPA 11
	ANR.EGR:BMK12	Actual duration RPA 12
	Workplace master data:	
	MNR.BEZK	Short name
	MNR.BEZL	Designation
	MNR.MGRP	Group
	MNR.KST	Cost center
	MNR.FIR	Company
	MNR.VAB	Responsibility area
	Personal master data:	
	PNR.PNR	Person
	PNR.PVORNAME	First name
	PNR.PNAME	Last name
	Reporting data EBDF:	
	MSGPRIO	Priority 1 = highest 2 = high 3 = normal 4 = low 5 = lowest MSGPRIO from dialog data
	MSGCLASS	Information class/importance I = information W = warning E = error MSGCLASS from dialog data
	MSGRCV	Recipient/addressee, e.g. group of plant managers MSGRCV from dialog data

1.5 Operation scheduled (ANR.MANUAL_SCHEDULED)

The event is triggered when an operation is moved from the pool for the group to the pool for the machine/workplace in the MOC application *Order sequencing*.

Event	Identifiers	Description
ANR.MANUAL_SCHEDULED	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub-operation No.
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by

1.6 Operation deallocated (ANR. MANUAL_DEALLOCATE)

The event is triggered when an operation is moved from the pool for the machine/workplace to the pool for the group in the MOC application *Order sequencing*. The “planned” field is set to the entry “G”.

Event	Identifiers	Description
ANR.MANUAL_DEALLOCATE	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub-operation No.
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by

1.7 Operation status changed (ANR.STATUS_CHANGE)

The event is triggered, provided that the status of the operation has been changed.

Event	Identifiers	Description
ANR.STATUS_CHANGE	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub-operation No.
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	ANR.AST	OP status
	ANR.PKENN	Production identifier
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by

1.8 Operation has been reactivated (ANR.REACTIVATE)

The event is triggered, provided that an operation has been reactivated.

Event	Identifiers	Description
ANR.REACTIVATE	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub-operation No.
	ANR.AKT	Article
	ANR.AGBEZ	OP name

Event	Identifiers	Description
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	ANR.AST	OP status
	ANR.PKENN	Production identifier
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by

1.9 LOCK/UNLOCK of an OP (ANR.LOCK/UNLOCK)

A “lock” is executed when data is being edited to ensure that several users do not modify the data record simultaneously. The “lock” is removed (“unlocked”) once the modification has been completed.

Event	Identifiers	Description
ANR.LOCK ANR.UNLOCK	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub-operation No.
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	ANR.AST	OP status
	ANR.PKENN	Production identifier
	DAT	Date of escalation
	ZEI	Time of escalation
	BEARB	Modified by

1.10 Primary target quantity reached (ANR.TARGET_QUANTITY_REACHED)

This escalation is triggered if an operation is automatically interrupted/logged off as its target quantity has been reached.

Please note:

A configuration of the processing code specifies whether or not an operation is automatically interrupted/finished, when the target quantity is reached. This escalation is never triggered, in case this configuration is not active!

Event	Identifiers	Description
ANR.TARGET_QUANTITY_REACHED	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub operation no.
	ANR.AKT	Article
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	ANR.AST	OP status
	ANR.SGR:GUTP	Target quantity
	ANR:EGR:GUTP	Actual quantity
	DAT	Date of escalation
	ZEI	Time of escalation

1.11 Comment entered (ANR.REGISTER_REMARK)

The comments recorded by the "BDE comment" function at the Windows terminal may trigger an escalation.

Event	Identifiers	Description
ANR.REGISTER_REMARK	ANR.ANR	Order + operation
	ANR.AUNR	Order

Event	Identifiers	Description
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub operation no.
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.PNR	Person
	ANR.KNR	Badge number
	BEM	Comment
	ANR.DAT	Date of escalation
	ANR.ZEI	Time of escalation
	ANR.ATK	Article of the operation
	Personal master data	
	PNR.PVORNAME	The person's first name
	PNR:PNAME	The person's surname
	PNR.FIR	Company
	PNR.KST	Cost center
	PNR.BER	Area
	PNR.ABT	Department
	PNR.KREIS	Employee subgroup
	PNR.TAETIGKEIT	Activity
	PNR.VAB	Responsibility area
	Workplace master data	
	MNR.FIR	Company
	MNR.KST	Cost center
	MNR.MGRP	Group
	MNR.BEZK	Workplace designation
	MNR.BEZL	Comment
	MNR.VAB	Responsibility area

1.12 Non-authorized posting (ANR.UNCERTIFIED_BOOKINGS)

The event is triggered when a posting record is generated that must be approved/authorized. Only order postings and personnel postings (U/E or B record) are integrated here.

An order posting must be authorized if the option *Order postings need to be signed* is enabled in tab *Options* for the relevant order type.

A personnel posting must be authorized if the option *Personnel postings need to be signed* is enabled in tab *Options* for the relevant order type.

Event	Identifiers	Description
ANR.UNCERTIFIED_BOOKINGS	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub-operation No.
	ANR.ATK	Article
	ANR.ATKBEZ	Article name
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.MNR	Workplace
	ANR.MGRP	Group
	ADEPRO.SART	Record type of the log record (B, U, E)
	DAT	Date of escalation
	ZEI	Time of escalation
	AUNR.DISP	MRP controller
	AUNR.AUGRP	Order group
	AGNR.DATE	Logoff date
	AGNR.ZEIE	Logoff time
	Personal master data:	
	PNR.PNR	Person
	PNR.PVORNAME	First name
	PNR.PNAME	Last name
	PNR.FIR	Company
	PNR.KST	Cost center
	PNR.BER	Area
	PNR.ABT	Department
	PNR.KREIS	Employee subgroup
	PNR.TAETIGKEIT	Activity
	PNR.VAB	Responsibility area

1.13 Quantity posting (ANR.QUANTITY_POSTING)

The ANR.QUANTITY_POSTING escalation is triggered if a quantity is posted with one of the following postings:

- Automatic quantity postings
- Manual quantity postings
- Postings of part quantities (partial confirmations)
- Operation logoffs
- Interruptions.

The escalation is only carried out in online mode.



At the time when this escalation is triggered, no log record is generated. If quantities are posted according to a specific configuration, then these quantities are not used here.

Here, the action is only **order-related**:

Event	Identifiers	Description
ANR.QUANTITY_POSTING	ANR.ANR	Order + operation
	ANR.AUNR	Order
	ANR.AGNR	Operation
	ANR.AFOLG	Sequence
	ANR.UAGNR	Sub operation no.
	ANR.ATK	Article
	ANR.ATKBEZ	Article designation
	ANR.AGBEZ	OP name
	ANR.AART	Order type
	ANR.SPLNR	Split number
	ANR.AST	OP status
	ANR.PKENN	Control/production identifier
	ANR.SGR:GUTP	Target quantity, primary quantity unit
	ANR.SGR:AUSP	Target scrap, primary quantity unit
	ANR.SGE:P	Primary quantity unit
	EGR:GUT	Yield to be posted, primary quantity unit
	EGR:AUS	Scrap to be posted, primary quantity unit
	EGR:NCH	Rework to be posted, primary quantity unit

Event	Identifiers	Description
	EGR:PRB	Problem quantity to be posted, primary quantity unit
	EGG:GUT	Yield reason
	EGG:AUS	Scrap reason
	EGG:NCH	Rework reason
	EGG:PRB	Problem reason
	ANR.EGR:GUT	Current (previous) yield primary quantity unit *)
	ANR.EGR:AUS	Current (previous) scrap primary quantity unit *)
	ANR.EGR:NCH	Current (previous) rework primary quantity unit *)
	ANR.EGR:PRB	Current (previous) problem quantity primary quantity unit *)
	MNR	Workplace where data collection takes place
	MNR.MGRP	Workplace group according to the configuration
	MNR.KST	Cost center of the workplace according to configuration
	MNR.FIR	Company of the workplace according to configuration
	MNR.VAB	Responsibility area of the workplace according to configuration
	MNR.FU:7	Machine user field 7
	MNR.FU:8	Machine user field 8
	MNR.FU:9	Machine user field 9
	MNR.FU:10	Machine user field 10
	MNR.FU:11	Machine user field 11
	MNR.FU:12	Machine user field 12
	MNR.FU:13	Machine user field 13
	MNR.FU:14	Machine user field 14
	MNR.FU:15	Machine user field 15
	MNR.FU:16	Machine user field 16
	MNR.FU:17	Machine user field 17
	MNR.FU:18	Machine user field 18
	MNR.FU:19	Machine user field 19
	MNR.FU:20	Machine user field 20
	MNR.FU:21	Machine user field 21
	MNR.FU:22	Machine user field 22

1.14 Order header finished

(ANR.OPEN_OP_WHEN_LAST_OP_ENDED)

This escalation monitors finished orders if the included operations are not all finished. This escalation is triggered if the last operation of an order is finished but the order cannot be set to the "finished" status as there are still open OPs. The number of operations, which have not yet been finished, is indicated in the escalation message.

Event	Identifiers	Description
ANR.OPEN_OP_WHEN_LAST_OP_ENDED	AUNR.AUNR	Order
	AUNR.AKT	Article
	AUNR.ATKBEZ	Article designation
	AUNR.AART	Order type
	AUNR.AST	Order status
	AUNR.SGR:GUTB	Target quantity (basis)
	AUNR.SGE:B	Target quantity unit (basis)
	AUNR.SGR:AUSB	Target scrap (basis)
	AUNR.EGE:B	Actual quantity unit (basis)
	AUNR:EGR:GUTB	Actual yield (basis)
	AUNR:EGR:AUSB	Actual scrap (basis)
	AUNR:EGR:NCHB	Actual rework quantity (basis)
	AUNR:EGR:PRBB	Actual problem quantity (basis)
	AUNR.DISP	MRP controller
	AUNR.AUGRP	Order group
	AUNR.DATSE	Basic end dates of order
	AUNR.ZEISE	Basic end dates of order
	AUNR.DATTERME	Scheduled end of order
	AUNR.ZEITERME	Scheduled end of order
	AUNR.OPENOP	Number of OPs that have not yet been finished when the order is finished, i.e. assigned to prod_kenn <> {Y,D,E}

Note for actual quantities:

Collected actual quantities are entered in the base quantity unit of the last OP where quantities were posted. Requirement: the conversion factors must be stored.