

Data Management

Overview

Menu	System administration → Archiving → Data management
Transaction code	arccfg
Function authorization	arccfg.*

Purpose

Use this application to view or change the centrally managed [Archiving](#) settings for recorded data.

Integration

Use this application to configure the settings for archiving / data management for all components/functions.

Field descriptions

Product

Enter the HYDRA product group for which you want to define a rule in the *Product* field.

Object

Use the *Object* to define the data you want to retain.

Retention period

Use the fields for the *Retention period* to define how long data should be available until data is archived.

Unit

Specify the retention period in days, months or years.

Last retention date

This field is computed and specifies the last day when data is still available in this object.

Action

You can choose from three options to specify the processing for an object:

D = delete	Object is deleted
M = move (archive)	Object is transferred to the next area
X = export	Object is unloaded (XUNLOAD format) and then deleted

Target object

Currently, the target object automatically results from the detail configuration.

Condition

The characters in this field are added as an additional condition to the database command that controls the action. This condition is linked to the other conditions of the original command using AND and is set in parentheses.

Last run (date/time)

Indicates the point in time when this rule was applied last.

License

Indicates which license is required for archiving. You can enter several licenses (separated by a space). If none of these licenses is licensed in the system, the data is either deleted (action D) or unloaded into files (action M or X), depending on the relevant action.

Path

Optional path to generate the file export (unload). The archiver currently only supports local HYDRA server drives. If you do not enter a path, file exports are filed as follows:

<HYDRADIR>/<SYSTEM>/custom/archive/<YYYY-MM-DD>/<PRODUCT>/

HYDRADIR ... HYDRA directory

SYSTEM ... System number

YYYY-MM-DD ... Archiving date (YYYY ... Year, MM ... Month, DD ... Day)

PRODUCT ... Product group from archiving configuration

Administration table

Name of the administration table where archiving logs are stored.

Administration duration (retention period of administration table)

Use the fields for the *retention period* to specify how long the logs should be available in the administration table before being deleted.

Unit

Specify the retention period in days, months or years.

Archiving step

Specifies if this archiving process uses archiving function I or II. Archiving function I: The function moves data from the online data set to archive tables or deletes the data: setting M (medium-term archive). Archiving function II: The function moves data from the archive table to the file export or deletes the data: setting L (long-term archive).

Configuration

Indicates whether or not the configuration is active. Possible values: Y/N

Archiving type

Identifier for time or object-related archiving. Supported modes: O = Object-related archiving (i.e. data is archived for each object individually). Z = Time-related archiving (i.e. data is archived without any object reference).

Note: Time and object-related archiving differ from each other significantly in the archiving performance (runtime). Object-related archiving of mass data is not recommended.

Priority

Integral value greater than 0. Indicates the processing sequence if several objects are defined for a product group. Processing starts with the lowest value.

Master table

Table including the data to be archived. The extensions entered in the *Condition* field refer to this table.

Date column

Date column in the master table. The system uses this date column to evaluate the retention period for the data to be archived.

Key 1

Unique key column in the master table; this key identifies the data to be archived. You can define up to 5 key columns for object-related archiving. Time-related archiving only supports one primary key in *Key 1*.

Keys 2 – 5

Additional optional key columns for object-related archiving.

Comment

Use the comment line to describe the archiving configuration.



If you copy the archiving configuration, the system currently only copies the data management configuration, but no defined data records from the object details. Currently, you must use the respective dialog to copy the data records of the object details to the new configuration.

Module	Version(s)	Description of archiving
BDE	8.1	See here
CAQ	8.1	See here
LLE	8.1	See here
MDE	8.1	See here
MPL	8.1	See here

PEP	8.1/8.2	See here
PZE/PZW	8.1/8.2	See here
ZKS	8.1/8.2	See here