

1 Function profiles

Overview

Menu	System administration → User administration → Function profiles
Transaction code	fautp
Function authorization	fautp

Use

Function profiles are used to easily assign authorizations in the user administration. A function profile consists of 1 – n function authorizations.

If you assign a function profile to a user, the user automatically obtains all authorizations included in the profile.

If you change the profile subsequently, the changes are directly enabled when the user logs on the next time.

Selection criteria

The application provides the following selection criteria:

Function profile

Select one or several function profiles, e.g. enter wildcards

Function

If you select the functions, all function profiles are displayed that include the individual function(s).

Field descriptions

Function profile

Function profile key

Function

Assigned function authorization

Name

Name of the function authorization

Action

To edit data, the following actions are available in the selection list:

- create
- copy
- edit
- delete
- view (= view only)

You can enter further actions. The actions are documented with the application that processes the specific actions.

If you assign a function without restriction to the possible data maintenance actions (the "Action" field remains empty), authorization is assigned for the Create/Copy/Change/Delete/Display actions.



If you want to assign several actions of a function authorization to a user, you must define the required authorizations with the respective actions for this user.

The actual function authorization is made up of the *function* and the *action* in the form "<function>.<action>".



The independent field *Action* is only available when you create data records. You can easily select the respective actions then. In the other detail applications, the *Action* is included in the field *Function*.

Example:

If you want to assign the authorizations *Create user* and *Edit user* to a user, but not *Delete*, the required authorizations are user.create and user.edit.

Authorization

The usual function authorizations do not process this field. You should set the value of this field to the default value 0.

In special use cases, you can enter an authorization level or another key number for the function authorization. The authorization level is rarely used and is then documented by the user where this exception is required.



When data records are edited, you can only change the field *Authorization*, as the *Function profile* and *Function* are key fields of the data record. This means: You must delete the data record and insert a new one to change the field *Function profile* and/or *Function*.

Function locks

To improve the protection of personal data, Service Pack 13 has introduced the option of locking individual functions for specific users:

- Print
- Export, STRG+C



The function locks are available for the application "Persons". You can add functions if a customization of the standard is required.



The field "Action" remains empty if you create function locks.

Available function locks

You can deactivate the print function in the HR master data application by assigning "pers_disprt" to a user or profile (buttons "Print preview" and "Print all" are hidden and the associated keyboard shortcuts are deactivated).

You can deactivate an export in the HR master data by assigning "pers_disexp" (Excel export buttons in the context menu and the export buttons in the print preview are hidden. Furthermore, the key combination CTRL+C is ineffective for selected table cells).