

1 Target Value Analysis (in table form)

Summary

Menu	Quality management → Process analysis → Target value analysis
Transaction code	ptva
Function authorization	ptva

The tabular analysis of default values is used to perform process analyses in quality management.

Usage

The tabular view offers the user an overview of the target value changes resulting from manual or automated activities. This designates the limit values and the target value of the characteristics defined in the collection rule.

Requirements

For modifications of the target values from the machine, the machine and the machine interface must transfer these values; and the corresponding assignments to the target values must be made in the logical channels.

Selection parameters

The following selection criteria are available in the application:

Machine

The pool application machine can be used to select the desired machine.

Process parameter

Possibility to enter a process parameter.

Event timestamp (from - until)

By restricting the event timestamp precise time intervals can be selected. In addition, the start and end time of an event may be selected by defining a relative date.

Default type

It is also possible to use a drop-down list to select a default type. These default types may be selected:

- Upper process action limit
- Upper tolerance limit
- Target value
- Lower tolerance limit
- Lower process action limit

Consider long-term data

Enabling this check box allows for long-term data to be considered.

Detail application: target value analysis (in tabular form)

This tabular report shows the changed default values recorded and saved in the database including the following information:

Event timestamp

Point in time when the modified default value was recorded

Machine

Machine at which the default value change was recorded/performed

Process parameter

Technical name of the process parameter for which default values have been changed

Default type

Default type that has been changed

Value

Value of the recorded default value change