

1 Configuration when using SAP PI / SAP PO

Changing the program call for sap45rck.exe/out

When using PI/PO, you have to change the program call for the upload program *myerprck.exe/out* in the [HYDRA Scheduler](#):

Situation	Value
Default program call (Windows) as delivered	sh.exe ./sap45rck.scr -K
Call including PI/PO (Windows)	sh.exe ./sap45rck.scr -K -B
Default program call (Linux) as delivered	./sap45rck.scr -K > /dev/null 2> /dev/null
Call including PI/PO (Linux)	./sap45rck.scr -K -B > /dev/null 2> /dev/null

Changing the segment name in the distribution model

Create the entry in the [HYDRA distribution model](#) in order to transfer clocking records as outbound configuration based on the following values:

Parameter name	Value
Message type	HRCC1UPTEVEN
Description	HR-PDC – Upload clocking records
IDoc type	HRCC1UPTEVEN01
Retention period	10
Log. target system	Created logical system
Segment name 1	E2BPCC1UPTEVEN 000

Create the entry in the HYDRA distribution model in order to request the upload as inbound message type based on the following values:

Parameter name	Value
Message type	HRCC1REQUPT EVEN
Priority	High
Command	hysapupl.scr
Command parameter	/UPLSEGNAM=E2BPCC1UPTEVEN 000
Description	HR-PDC – Request upload
Log. target system	Created logical system
Retention period	10