

1 Application-relevant customizing in SAP

Defining QM subsystem

In QM-IDI interface operations are only transferred if a subsystem is assigned to them. The assignment is done at the work centre in SAP. Each work centre can be assigned to one subsystem only, whereas a subsystem can be assigned to multiple work centers.

QM subsystems can be created in SAP using by IMG Quality Management → QM in Logistics → QM in Procurement → Define QM Systems.

Defining origin of results data

In SAP QM it is possible to indicate the origin at the inspection result. For that, several origins can be defined in the IMG. To enable HYDRA to support this field/information it is necessary to maintain the value created in SAP in HYDRA as well.

Origin of results data can be created in SAP using IMG Quality Management → Quality Inspection → Results Recording → Define Origins of Results Data

Defining detail level for error messages

When defining QM subsystems, the trace level can be defined. In the IDI interface, all error messages as well as changes to the worklist are written to an application log.

The exceptions, messages of the QIERRTAB error log, and the beginning and end of a function are recorded. In Customizing, you can define the level of detail for the application log. Use the RQEIFML1 report to display the application log. Use the RQEIFML2 report to delete the log.

Defining selected set / plant for usage decision

At the level of the inspection type it can be defined in SAP if a selected set shall be used and if only plant specific catalogs can be used for the final usage decision.

The download of catalogs for the usage decision together with the inspection lot depends depends on the selection options for the selected set and the plant.

In HYDRA these settings will be used to pre-select the available catalogs.