

Manual

HYDRA Interfacing Module for SAP MM SAP-MMMOB 8.2

Version 1.0.23049

Last changed on: 02.09.2020

Copyright

©Copyright 2012 All rights reserved.

SAP® and R/3® are registered trademarks of SAP AG.

WINDOWS® is a registered trademark of Microsoft Corporation.

MPDV® and HYDRA® are registered trademarks of MPDV Mikrolab GmbH.

ORACLE® is a registered trademark of ORACLE Corporation, California, USA.

Copying and distribution of this documentation or any part thereof, for any purpose or in any form, is prohibited without prior written permission from MPDV Mikrolab GmbH.

The information contained in this documentation is subject to change without prior notice.

Contents

1	HYDRA Interfacing Module to SAP MM.....	4
2	Mapping of MM-MOB in HYDRA.....	5
3	Upload of Goods Movements HYDRA --> SAP	6
3.1	Goods issues	6
3.2	Goods receipts	9
4	Application-Relevant Settings in HYDRA.....	13
5	Application-Relevant Settings in SAP	15
6	MYERPRCK - Program Parameters	17

1 HYDRA Interfacing Module to SAP MM

Summary

Fields of application

The function package provides a communication container (IDoc) by which consumptions and goods receipt recorded in the MES can be transferred to SAP ECC. Data are transferred in the SAP standard format.

Implementation notes

You use the function package if you wish:

- to record MES consumptions (with and without relation to batches) and upload them to SAP
- to upload material generated in MES as goods receipt in SAP
- to perform the upload in the SAP standard format and not according to the customer's requirements

Integration

The function package is also integrated in the following function packages:

- MPL-MBV – material and inventory management
- TRT-CLV – batch data management
- TRT-CLA – batch data processing

Features

- Interfacing module to connect HYDRA to SAP MM using the MM-MOB interface. Upload of goods movements using the SAP standard IDoc WMMBID02 (segments E2MBXYH, E2MBXYI):
- Transfer of goods receipts from the production (SAP movement type 101)
- Transfer of goods issues from the production (SAP movement type 261)
- Prerequisite: HYDRA modules (e.g. MPL) generating goods movements are used and technical details are coordinated (chargeable customization service).



Prerequisites: HYDRA modules (e.g. MPL, TRT) generating goods movements are in use.

2 Mapping of MM-MOB in HYDRA

Summary

The function package SAP-MMMOB is based on [goods movements](#) generated by other function packages (e.g. MPL, TRT). Goods receipts as well as goods issues are considered in this context.

The interface itself does not perform any further checks. Data consistency has to be ensured by the generating applications.

Prerequisite

The MES material type has to be configured as subject to uploads for the interface to make sure that goods movements can be provided.

3 Upload of Goods Movements HYDRA --> SAP

3.1 Goods issues

Material withdrawals (consumption) recorded in HYDRA are transferred to SAP.

HYDRA provides the SAP system with the data in cyclic intervals. The SAP standard IDoc WMMBID02 of the message type WMMBXY is used for this purpose.

Message type:	WMMBXY	
IDOC type	WMMBID02	
Segments:	E2MBXYH (header record)	single
	└ E2MBXYI (detail record)	single

Transaction types

Transaction type	Description/usage
261	Goods issue for production order (consumption)
262	Cancellation of goods issue for production order (consumption)

Data structure (E2MBXYH)

Field	T	L	D	Designation	Usage in HYDRA
BLDAT	DATE	8		Document date in document	Date when consumption was entered
BUDAT	DATE	8		Posting date in document	Date of material movement
XBLNR	CHAR	16		Reference document number	Reference of material movement
BKTXT	CHAR	25		Document header text	Not used
FRBNR	CHAR	16		Number of the bill of lading at time of goods receipt	Not used
XABLN	CHAR	10		Goods receipt/issue slip number	Not used
TCODE	CHAR	4		Session: Current transaction code	Fixed "MB1A"
USNAM	CHAR	12		User name (release 4.0)	Not used
VBUND	CHAR	6		Society number (release 4.0)	Not used

Data structure (E2MBXYI)

Field	T	L	D	Designation	Usage in HYDRA
BEAKZ	CHAR	1		Indicator: line already edited	Not used
XSTOB	CHAR	1		Flag: Reverse posting	Not used
MATNR	CHAR	18		Material number	Material number of the component to be withdrawn
WERKS	CHAR	4		Plant	Factory of the production order
LGORT	CHAR	4		Storage location	Storage location from user field 46 of the component list
CHARG	CHAR	10		Batch number	Recorded batch number
BWART	CHAR	3		Movement type (inventory management)	"261" for goods issues "262" cancellation for goods issue
INSMK	CHAR	1		Stock type	Not used
SOBKZ	CHAR	1		Special stock indicator	Not used
KZVBR	CHAR	1		Indicator: consumption posting	Not used
LIFNR	CHAR	10		Vendor account number	Not used
KUNNR	CHAR	10		Customer number	Not used
KDAUF	CHAR	10		Sales order number	Not used
KDPOS	CHAR	6		Item number in customer order	Not used
KDEIN	CHAR	4		Scheduling of customer order	Not used
SHKZG	CHAR	1		Debit and credit indicator	Not used
WAERS	CHAR	5		Currency key	Not used
DMBTR	CHAR	15		Amount in local currency	Not used
BWTAR	CHAR	10		Valuation type	Not used
ERFMG	QUAN	13	3	Quantity in unit of entry	Quantity recorded as consumption
ERFME	CHAR	3		Unit of entry	Quantity unit for consumption quantity
BPMNG	QUAN	13	3	Quantity in order price quantity unit	Not used
BPRME	CHAR	3		Order price quantity unit	Not used
EBELN	CHAR	10		Purchasing document number	Not used
EBELP	CHAR	5		Item number of purchasing document	Not used
ELIKZ	CHAR	1		"Delivery completed" indicator	Not used
SGTXT	CHAR	50		Item text	Not used
WEMPF	CHAR	12		Recipient of the goods	Not used
ABLAD	CHAR	25		Place of unloading	Not used
KOSTL	CHAR	10		Cost center	Not used
AUFNR	CHAR	12		Order number	SAP order number for which material has been withdrawn
ANLN1	CHAR	12		Asset main number	Not used
ANLN2	CHAR	4		Asset sub-number	Not used
RSNUM	CHAR	10		Reservation number	Number of the reservation from user field 45 of the component

Field	T	L	D	Designation	Usage in HYDRA
RSPOS	CHAR	4		Item number of the reservation	Item number of the reservation from user field 47 of the component
KZEAR	CHAR	1		Indicator: final issue	Not used
UMMAT	CHAR	18		Receiving/issuing material	Not used
UMWRK	CHAR	4		Receiving/issuing plant	Not used
UMLGO	CHAR	4		Receiving/issuing storage location	Not used
UMCHA	CHAR	10		Receiving/issuing batch	Not used
KZBEW	CHAR	1		Movement indicator	Not used
WEUNB	CHAR	1		Indicator: goods receipt	Not used
LGNUM	CHAR	3		Warehouse number	Not used
LGTYP	CHAR	3		Storage type	Not used
LGPLA	CHAR	10		Storage bin	Not used
GRUND	CHAR	4		Indicator: transaction reason	Not used
EVERS	CHAR	2		Shipping instructions	Not used
EVERE	CHAR	2		Complying with shipping instructions	Not used
IMKEY	CHAR	8		Internal key for real estate property	Not used
KSTRG	CHAR	12		Cost object	Not used
PAOBJNR	CHAR	10		Number for business segment	Not used
PRCTR	CHAR	10		Profit center	Not used
PS_PSP_PNR	CHAR	8		Planning element of project structure	Not used
NPLNR	CHAR	12		Network number for account assignment	Not used
AUFPL	CHAR	10		Planning number for transactions in the order	Not used
APLZL	CHAR	8		Continuous counter	Not used
AUFPS	CHAR	4		Number of order item	Not used
VPTNR	CHAR	10		Partner account number	Not used
FIPOS	CHAR	14		Commitment item	Not used
GSBER	CHAR	4		Business area	Not used
BSTMG	QUAN	13	3	Goods receipt quantity in order unit	Not used
BSTME	CHAR	3		Order unit	Not used
EXBWR	QUAN	13	3	Posting amount in local currency entered externally	Not used
KONTO	CHAR	10		G/L account number	Not used
RSHKZ	CHAR	1		Debit and credit indicator	Fixed "H"
BDMNG	QUAN	13	3	Requirement quantity	Not used
ENMNG	QUAN	13	3	Issued quantity	Not used
QPLOS	CHAR	12		Inspection batch number	Not used
UMZST	CHAR	1		Status of receiving batch	Not used
UMZUS	CHAR	1		Status key of transfer batch	Not used
UMBAR	CHAR	10		Valuation type of transfer batch	Not used
UMSOK	CHAR	1		Special stock indicator	Not used
LFBJA	CHAR	4		Fiscal year of a reference document	Not used
LFBNR	CHAR	10		Document number of a reference document	Not used
LFPOS	CHAR	4		Item in a reference document	Not used
SJAHR	CHAR	4		Material document year	Not used

Field	T	L	D	Designation	Usage in HYDRA
SMBLN	CHAR	10		Number of a material document	Not used
SMBLP	CHAR	4		Item in the material document	Not used
EXVKW	CHAR	15		Sales value specified externally in local currency	Not used
QM_ZUSTD	CHAR	1		Batch status with status changed in QM (internal)	Not used
POSNR	CHAR	6		Delivery item for third-party system	Not used
VBELN	CHAR	10		Delivery	Not used
QM_UMZST	CHAR	1		Status of received batch when status changed in QM (intern.)	Not used
BWLVS	CHAR	3		Movement type for warehouse management system	Not used
UMREZ	CHAR	5		Numerator for converting to base unit of measure	Not used
UMREN	CHAR	5		Denominator for conversion to base unit of measure	Not used
VFDAT	CHAR	8		Expiration date or best-before date	Not used

3.2 Goods receipts

Goods receipts recorded in HYDRA (for produced material) are transferred to SAP.

HYDRA provides the SAP system with the data in cyclic intervals. The SAP standard IDoc WMMBID02 of the message type WMMBXY is used for this purpose.

Message type:	WMMBXY	
IDOC type	WMMBID02	
Segments:	E2MBXYH (header record)	single
	└ E2MBXYI (detail record)	single

Transaction types

Transaction type	Description/usage
101	Goods receipt for production order
102	Goods receipt cancellation for production order

Data structure (E2MBXYH)

Field	T	L	D	Designation	Usage in HYDRA
BLDAT	DATE	8		Document date in document	Date of the entry

Field	T	L	D	Designation	Usage in HYDRA
BUDAT	DATE	8		Posting date in document	Date of material movement
XBLNR	CHAR	16		Reference document number	Reference of material movement
BKTX	CHAR	25		Document header text	Not used
FRBNR	CHAR	16		Number of the bill of lading at time of goods receipt	Not used
XABLN	CHAR	10		Goods receipt/issue slip number	Not used
TCODE	CHAR	4		Session: Current transaction code	Fixed "MB31"
USNAM	CHAR	12		User name (release 4.0)	Not used
VBUND	CHAR	6		Society number (release 4.0)	Not used

Data structure (E2MBXYI)

Field	T	L	D	Designation	Usage in HYDRA
BEAKZ	CHAR	1		Indicator: line already edited	Not used
XSTOB	CHAR	1		Flag: Reverse posting	Not used
MATNR	CHAR	18		Material number	Material number of the produced material
WERKS	CHAR	4		Plant	Factory of the production order producing the material
LGORT	CHAR	4		Storage location	Storage location from user field 45 of the order header
CHARG	CHAR	10		Batch number	Recorded batch number
BWART	CHAR	3		Movement type (inventory management)	"101" for goods receipts "102" goods receipt cancellation
INSMK	CHAR	1		Stock type	Not used
SOBKZ	CHAR	1		Special stock indicator	Not used
KZVBR	CHAR	1		Indicator: consumption posting	Not used
LIFNR	CHAR	10		Vendor account number	Not used
KUNNR	CHAR	10		Customer number	Not used
KDAUF	CHAR	10		Sales order number	Not used
KDPOS	CHAR	6		Item number in customer order	Not used
KDEIN	CHAR	4		Scheduling of customer order	Not used
SHKZG	CHAR	1		Debit and credit indicator	Not used
WAERS	CHAR	5		Currency key	Not used
DMBTR	CHAR	15		Amount in local currency	Not used
BWTAR	CHAR	10		Valuation type	Not used
ERFMG	QUAN	13	3	Quantity in unit of entry	Recorded quantity
ERFME	CHAR	3		Unit of entry	Quantity unit

Field	T	L	D	Designation	Usage in HYDRA
BPMNG	QUAN	13	3	Quantity in order price quantity unit	Not used
BPRME	CHAR	3		Order price quantity unit	Not used
EBELN	CHAR	10		Purchasing document number	Not used
EBELP	CHAR	5		Item number of purchasing document	Not used
ELIKZ	CHAR	1		"Delivery completed" indicator	Not used
SGTXT	CHAR	50		Item text	Not used
WEMPF	CHAR	12		Recipient of the goods	Not used
ABLAD	CHAR	25		Place of unloading	Not used
KOSTL	CHAR	10		Cost center	Not used
AUFNR	CHAR	12		Order number	SAP order number for which material has been received / produced
ANLN1	CHAR	12		Asset main number	Not used
ANLN2	CHAR	4		Asset sub-number	Not used
RSNUM	CHAR	10		Reservation number	Not used
RSPOS	CHAR	4		Item number of the reservation	Not used
KZEAR	CHAR	1		Indicator: final issue	Not used
UMMAT	CHAR	18		Receiving/issuing material	Not used
UMWRK	CHAR	4		Receiving/issuing plant	Not used
UMLGO	CHAR	4		Receiving/issuing storage location	Not used
UMCHA	CHAR	10		Receiving/issuing batch	Not used
KZBEW	CHAR	1		Movement indicator	Fixed "F"
WEUNB	CHAR	1		Indicator: goods receipt	Not used
LGNUM	CHAR	3		Warehouse number	Not used
LGTYP	CHAR	3		Storage type	Not used
LGPLA	CHAR	10		Storage bin	Not used
GRUND	CHAR	4		Indicator: transaction reason	Not used
EVERS	CHAR	2		Shipping instructions	Not used
EVERE	CHAR	2		Complying with shipping instructions	Not used
IMKEY	CHAR	8		Internal key for real estate property	Not used
KSTRG	CHAR	12		Cost object	Not used
PAOBJNR	CHAR	10		Number for business segment	Not used
PRCTR	CHAR	10		Profit center	Not used
PS_PSP_PNR	CHAR	8		Planning element of project structure	Not used
NPLNR	CHAR	12		Network number for account assignment	Not used
AUFPL	CHAR	10		Planning number for transactions in the order	Not used
APLZL	CHAR	8		Continuous counter	Not used
AUFPS	CHAR	4		Number of order item	Not used
VPTNR	CHAR	10		Partner account number	Not used
FIPOS	CHAR	14		Commitment item	Not used
GSBER	CHAR	4		Business area	Not used
BSTMG	QUAN	13	3	Goods receipt quantity in order unit	Not used
BSTME	CHAR	3		Order unit	Not used
EXBWR	QUAN	13	3	Posting amount in local currency entered externally	Not used
KONTO	CHAR	10		G/L account number	Not used

Field	T	L	D	Designation	Usage in HYDRA
RSHKZ	CHAR	1		Debit and credit indicator	Fixed "S"
BDMNG	QUAN	13	3	Requirement quantity	Not used
ENMNG	QUAN	13	3	Issued quantity	Not used
QPLOS	CHAR	12		Inspection batch number	Not used
UMZST	CHAR	1		Status of receiving batch	Not used
UMZUS	CHAR	1		Status key of transfer batch	Not used
UMBAR	CHAR	10		Valuation type of transfer batch	Not used
UMSOK	CHAR	1		Special stock indicator	Not used
LFBJA	CHAR	4		Fiscal year of a reference document	Not used
LFBNR	CHAR	10		Document number of a reference document	Not used
LFPOS	CHAR	4		Item in a reference document	Not used
SJAHR	CHAR	4		Material document year	Not used
SMBLN	CHAR	10		Number of a material document	Not used
SMBLP	CHAR	4		Item in the material document	Not used
EXVKW	CHAR	15		Sales value specified externally in local currency	Not used
QM_ZUSTD	CHAR	1		Batch status with status changed in QM (internal)	Not used
POSNR	CHAR	6		Delivery item for third-party system	Not used
VBELN	CHAR	10		Delivery	Not used
QM_UMZST	CHAR	1		Status of received batch when status changed in QM (intern.)	Not used
BWLVS	CHAR	3		Movement type for warehouse management system	Not used
UMREZ	CHAR	5		Numerator for converting to base unit of measure	Not used
UMREN	CHAR	5		Denominator for conversion to base unit of measure	Not used
VFDAT	CHAR	8		Expiration date or best-before date	Not used

4 Application-Relevant Settings in HYDRA

Maintenance of the HYDRA distribution model - outbound processing

Use the [HYDRA distribution model](#) to maintain entries for HYDRA outbound processing:

Parameter name	Value
For the upload of time tickets	
Message type	WMMBXY
Description	MM-MOB - Upload of material movements
IDOC type	WMMBID02
Storage duration	10
Log. target system	Created logical system
Segment name 1	E2MBXYH

Maintenance of the HYDRA Scheduler

Use the [HYDRA Scheduler](#) to plan jobs for outbound processing:

Parameter name	Value
Transfer of goods movements to MLE outbound transactions	
Product key	SAP-MMMOB
License key	SAP-MMMOB
Command (Windows):	sh.exe ./myerprck.scr /MESTYP=WMMBXY
Command (Unix):	./myerprck.scr /MESTYP=WMMBXY
Comment:	SAP-MMMOB: Upload of goods movements → MLE outbound transactions
Interval	5

Parameter name	Value
Upload of confirmations from MLE outbound transactions to SAP MM	
Product key	SAP-MMMOB
License key	SAP-MMMOB
Command (Windows):	sh.exe ./.hysapupl.scr /UPLSEGNAM=E2MBXYH /SINGLE_IDOC /SUBLEVEL=2
Command (Unix):	./hysapupl.scr /UPLSEGNAM=E2MBXYH /SINGLE_IDOC /SUBLEVEL=2
Comment:	SAP-MMMOB - Upload of goods movements MLE outbound transactions → SAP MM
Interval	5



Please make sure that the upload program myerprck.exe/out has not been started for the message types ZWAU (goods issues in the HYDRA format) and ZWEI (goods receipts in the HYDRA format) using the script myerprck.scr, since it cannot be operated with SAP-MMMOB at the same time.

Maintenance of the HYDRA material type

In many cases, the HYDRA material type is relevant for the interface and needs to be activated to be able to transfer goods movements. For this reason, enable the flag “goods movements → transfer to interface” for the [HYDRA material type](#).



If the HYDRA material type is not available as application, the flag can also directly be set using the database:

```
update hz_typen set we_ext_kz = ,J' where hz_typ = '<Material type for which the flag is to be set>';
```

5 Application-Relevant Settings in SAP

Maintenance of the SAP partner agreement – inbound processing

Maintain the following settings for inbound processing in the partner agreement in SAP (WE20):

Parameter name	Value
Partner number	Created logical system
Partner type	LS
Message type	WMMBXY
Transaction code	WMMB

Maintenance of the SAP distribution model – inbound processing

Parameter name	Value
To upload time tickets	
Model view	Created model view
Sender / Client	Logical system for the sender system
Recipient/ server	Logical system of the client
Message type	WMMBXY

Relevant transactions

Transaction	Meaning	Note
MB51	Display of material documents	

Possible modifications

If the standard SAP inbound processing does not meet the requirements, it can be enhanced by numerous [modifications](#).

Modification	Meaning	Note
MWMIDO07	Error processing for the receipt of IDocs: MDE for IDocs: WMMBXY, WMINVE, WMTORD together	
MWMIDO08	Message WMMBXY (goods movement) inbound	
MWMIDO13	Message WMMBXY: follow-up actions after posting goods	

6 MYERPRCK - Program Parameters

--	--	--

Purpose

Use the upload program myerprck.exe/out to create confirmations/uploads to higher-level systems. In addition to the settings you make directly in the applications, you can also use program parameters to control confirmations/uploads.

Integration

The confirmation/upload is integrated with numerous components, for example:

- Shop floor data collection
- Tracking and tracing as well as material and production logistics
- Detailed scheduling

Available program parameters:

Parameters	Meaning/use	Relevant interfaces	Productive release
Program parameters to control processing:			
/MESTYP=XXXX	The parameter MESTYP defines the structure to be generated.	All	Yes
/GRP=XXXX	The grouping type specifies the criterion by which uploads should be grouped. Possible values: PLANT --> Groups by plant	Requires customizations	Requires customizations
/V=sssss	Since SAP R/3 PP does not support correction postings, HYDRA allows to retain confirmations/uploads for correction purposes in HYDRA for a specific period of time. Use the parameter /V=sssss (sssss =	EIS-ERP EIS-XPPS SAP-PPDC SAP-PPREM	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	delay time in seconds) to activate the above described delay when the upload program is called. Examples: <pre>myerprck.exe/out /V=3600</pre> The system only uploads postings that are older than one hour.	SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	
/BIS=DDMMYYHHMM /BIS=HHMM /TILLDATE=MM/DD/YYYY /TILLTIME=sec after midnight	Use the parameter /BIS=DDMMYYHHMM (date + time) when calling the upload program to enter the delay as a point in time. You can enter this point in time with date and time or you can just enter the time in the format "HHMM". In the latter case, the time refers to the current day. <pre>Myerprck.exe /BIS=2505110600</pre> This parameter uploads postings that were recorded until 06:00 a.m. on 25 May 2011. <pre>Myerprck.exe /BIS=0600</pre> This parameter uploads postings that were recorded until 06:00 a.m. of the current day.	EIS-ERP EIS-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/TZ=+/-sssss	Use the parameter /TZ=+/-sssss to adapt uploads to different time zones. The parameter adjusts the time specifications entered in the fields EXEC__START_TIME, EXEC_FIN_TIME and LOGTIME of the upload structure of the SAP-PPDC interface according to its specifications.	SAP-PPDC	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
/KST=XXX	Use this parameter to restrict the data to be uploaded. In this case, the system only uploads data of a specified cost center. Use the parameter /KST=XXX (XXX = cost center, a max. of 8 characters) when calling the upload program myerprck.exe/out to enable the above-described restriction. Then the system only uploads data records that were posted to machines of the specified cost center. The system checks the cost center of the machine/workplace that is entered as the posting workplace/machine in the posting record. The system only checks the cost center of the workplace/machine. You can specify the parameter several times per call. <u>Example:</u> <pre>Myerprck.exe /KST=BDE100 /KST=BDE200</pre> The system only uploads records that were posted onto machines of the cost center BDE100/BDE200.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/CLEAR_RES	Use the parameter "/CLEAR_RES" to assign an "X" to the field CLEAR_RES of the upload structure when it comes to a final confirmation/upload (record type L40). Consequently, SAP will clear open reservations for the respective order.	SAP-PPDC	Yes
/NEG_MENGE	By default, quantities (L20/L40) cannot	SAP-PPDC	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	be uploaded to SAP PP using partial confirmations/uploads via the SAP-PPPDCC interface if data is collected at the same time via the total quantity counter of MDE machines, since SAP is not able to process negative quantities. This type of collection can result in negative quantity postings for yield when OPs are finished. This restriction does no longer apply, if it is possible to process such negative postings (e.g. by using the SAP standard BAPI or customizations). In this case, you can use the program parameter /NEG_MENGE to enable the upload of these quantities.		
/LA_MNR	The SAP_PMCC3 interface requires the activity type to be uploaded to SAP PM. The activity type can be identified via the machine/workplace where the posting was performed. Use this program parameter to enable identification of the activity type. Then the system uses the machine to identify the activity type from the activity types kept in HYDRA.	SAP-PMCC3	Yes
/IDENT_PRAEFIX=	In the upload structure of the SAP-PPPDCC interface, the field EX_IDENT uniquely identifies uploads from subsystems. HYDRA populates the field. You can add a prefix to the EX_IDENT field to differentiate between uploads	SAP-PPPDCC SAP-PPPDCC	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	from various HYDRA subsystems connected to one SAP instance. <u>Example:</u> <pre>Myerprck.exe /IDENT_PRAEFIX=ABC</pre> The prefix may only include hexadecimal characters: A –H und 0 – 9.		
/ABZEICH=XX	While customizing the order type, you can specify that only signed data records are uploaded. Use the parameter /ABZEICH=XX to specify a period of time in days after that you can upload even unsigned data records.	EIS-ERP EIS-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/TRANSFER=	Use the parameter "/TRANSFER=" to only upload records whose specifications were transferred from a specific system. The transfer indicator is set during HYDRA inbound processing and may vary from interface to interface.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
/NOTTRANSFER=XXX	Use the parameter "/NOTTRANSFER=" to only upload records whose specifications were NOT transferred from a specific system. The transfer indicator is set during HYDRA inbound processing and may vary from interface to interface.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/SEK	The EIS-ERP interface uploads the times of resource performance accounts in hours. In particular with very short lead times this may effect that logon times are cut off by a conversion into hours. Use this program parameter to upload times in seconds.	EIS-ERP ESI-XPPS	Yes
/RMTYP=	When customizing the order type, you can assign an upload type to the order type. Use this program parameter to only upload data records of this upload type. You can specify the parameter several times per call.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
/KAT=	When customizing the order type, you can connect the order type with a category. Use the program parameter /KAT= to only upload data records of this category. You can specify the parameter several times per call.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/SART=	The system only uploads ADE log postings of the specified record type. Therefore, you can use different program parameters per call and record type for uploading. Requirement: You have to activate the corresponding uploads when customizing the order type. You can specify the parameter several times per call. <u>Example:</u> <pre>Myerprck.exe /SART=A /SART=E</pre> ⇒ The system only uploads A and E records.	EIS-ERP ESI-XPPS SAP-PPDC SAP-PPREM SAP-PPPI SAP-PMCC3 SAP-PSCC4 SAP-COILV	Yes
/NOLOCK	When starting the upload program, the system checks if there are any lock entries for the database table ADE_PROTOKOLL. If this is the case,	All	Requires customizations

Parameters	Meaning/use	Relevant interfaces	Productive release
	the upload is not carried out. You can use this program parameter to prevent this check. Set this parameter, in particular, if the upload is not based on the table ade_protokoll.		
/EINH_CC34	The interfaces SAP-PMCC3 and SAP-PSCC4 transfer the uploaded activity quantity in seconds (SEC) to SAP. Use the parameter "/EINH_CC34" to upload the data in other units. The following units are supported: Hours: H, HUR, STD Minutes: MIN Seconds: SEC <u>Example:</u> <pre>Myerprck.exe /EINH_CC34=HUR</pre> The system uploads the recorded times in the unit "HUR" (hours).	SAP-PMCC3 SAP-PSCC4	Yes
/SDAT_STORNO	The SAP-PPPDCC interface transfers the change date along with the correction records. Use this program parameter to upload the initially collected shift date instead.	SAP-PPPDCC	Yes
/NORFC_STORNO	The SAP-PPPDCC interface transfers the cancellation records via sRFC. Use the program parameter to transfer the data in the IDoc format to SAP. To do	SAP-PPPDCC	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	so, inbound processing must be implemented in SAP. The system uploads the cancellation records via the standard PP-PDC segment (with record type K20/K40) as if the PP-PDCC license was not available.		
/PI	If you use the SAP Process Integration (previously: Exchange Infrastructure) to communicate with SAP, the version of the transferred segment is checked more strictly. Use the program parameter to transfer segment names with the version number (i.e. the trailing zeros of the segment name).	SAP-PPDC SAP-PMCC3 SAP-PSCC4	Yes
/INDEX_TMP_TABLE	Use this parameter to accelerate uploads if ORACLE is used as database system and large amounts of data are affected. To do so, use an index for a temporary table where all data to be uploaded is transferred in a first step.	All	Requires customizations
/UE_PARAMS=	Program parameter for the stand-alone user exit processing (DD format).	Various	Yes
/NOSTORNO	Use this program parameter to prevent cancellation records from being uploaded. Therefore, you can use different program parameters per call and record type for uploading. Requirement: You have to activate the	All	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	corresponding uploads when customizing the order type.		
/RECALC_NEG_YIELD	Use this parameter to offset negative yield with already posted positive uploads.	SAP-PPPDCC	Requires customizations
Program parameters to use the SIGUSR communication:			
/LOGGING	Use this program parameter to activate communication from the database table HYD_LOGGING. To do so, a customization might be required.	INDIVIDUAL CASE	Yes
/WAIT_SIGUSR1=XX	The program parameter specifies the time in seconds that has to pass before the upload is performed via the SIGUSR communication even without trigger.	INDIVIDUAL CASE	Yes
/PEEK_SIGUSR1=XX	Use this parameter to delay execution of an action triggered by the SIGUSR communication. The delay time is entered in seconds for this parameter. The program interprets this time as follows: If within the next second after the initial trigger there is another trigger, then wait for not more than <specified value> seconds. If in a specific case, triggers would indeed arrive every second then the	INDIVIDUAL CASE	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	WAIT_SIGUSR time (e.g. 120 seconds) would apply; i.e. the system would in fact perform the upload after 2 minutes.		
/SEND_SIGUSR1=	This program parameter defines which other process/ program must be triggered after processing by the SIGUSR communication. Specify the process/program WITHOUT file extension.	INDIVIDUAL CASE	Yes
/COUNT_SIGUSR1=XX	Uploading in signal mode can hardly be subjected to tracing. This is due to the fact that the program in those cases is started once via the scheduler but won't shut off. Any redirection of the program call with -d to a log file will then necessarily lead to very large log files, which will negatively affect the performance. Use the new program parameter /COUNT_SIGUSR1=XX to specify after how many calls the program will automatically shut down. A call in these instances is both, a call via SIGUSR communication and the cyclical program execution which is controlled via the parameter /WAIT_SIGUSR1. Then the scheduler restarts the program. But this will lead to a time period "t" during which SIGUSR calls will not be processed. It is, however, assumed that this will not lead to data losses since the data to be uploaded are already saved to	INDIVIDUAL CASE	Yes

Parameters	Meaning/use	Relevant interfaces	Productive release
	the DB. Benefits: If the program is started via a script (*.scr) from the scheduler, you can store there the routine to generate a date/ time stamp file name for the log file to be created. This allows to restrict the log file size.		
Program parameters for debugging/ tracing/ testing/ logging purposes:			
/ONLYERR	This program parameter specifies that system log entries are only created if an error occurred during uploading. This reduces the entries in the system log.	All	Yes
/SIM	The system does not upload/confirm data during simulations (the uploaded/confirmed indicator is set to "True").	All	No
/SIMULATION	The system does not upload/confirm data to SAP during simulation (confirmed/uploaded indicator will not be changed).	All	No