

1 AIP Add-On Task Switching

Display on the AIP

Buttons for external applications can be integrated into all AIP key bars

- to start the external application when it is not currently running
- to run the external application in the foreground while it is currently being executed

The customer is responsible for assuring that the external application is correctly installed and functions properly.

Configuring the first button

The first button that can be used to access external software is configured for "USER1" in ctaipbut.ini. Example:

```
[MNR-ALL-Page1]
1=M_INFO,L,,InfoRed.png
2=VIEW,L,,VirtualTourSmall.png
3=P_SPERRE,L,Produktionsstatus sperren,Security Risk.png
4=M_MST,L,Status ändern,Status Flag Yellow.png
5=$DNC-BP$DNC,L,DNC,DNC.png
6=M_INFO.MSPROT,L,Statusprotokoll,Table.png
7=USER1,R,Total Cmd
```

The actual functions are configured in section [ext. software] of the configuration file ctaip.ini:

```
[ext. software]
Button=Commander
WindowName=Total Commander
ProgFileName=c:\Program Files\totalcmd\TOTALCMD.EXE
SearchParts=On
```

Configuring additional buttons

Additional buttons that can be used to access external software are configured for "USER2" through "USER9" in ctaipbut.ini. Example:

```
[MNR-ALL-Pagel]
1=M_INFO,L,,InfoRed.png
2=VIEW,L,,VirtualTourSmall.png
3=P_SPERRE,L,Produktionsstatus sperren,Security Risk.png
4=M_MST,L,Status ändern,Status Flag Yellow.png
5=$DNC-BP$DNC,L,DNC,DNC.png
6=M_INFO.MSPROT,L,Statusprotokoll,Table.png
7=USER1,R,Total Cmd
8=USER2,R,Notepad
```

The actual functions are configured in section [ext. software] of the configuration file ctaip.ini:

```
[ext. software]
Button2=Notepad
WindowName2=Notepad
ProgFileName2=c:\WINDOWS\notepad.exe
SearchParts2=On
```

Consequently, a maximum of nine buttons can be configured in ctaip.exe (USER1..USER9). The respective entries in [ext. software] receive a corresponding index for this purpose (Button2, Windowname2, ...).

Field descriptions

Button(x)

Logical name of the button

WindowName(x)

Window title for the external application running

ProgFileName(x)

Windows path and file name for the external application

SearchParts(x)

If "SearchParts=On", then AIP uses a substring search to determine the window to switch to the external application that is running:

WindowsName=Total Commander then also finds the window entitled

"Total Commander 7.5"